FCC RF Test Report

APPLICANT	**: ZTE CORPORATION**
EQUIPMENT	**: LTE Tablet**
BRAND NAME	**: ZTE**
MODEL NAME	**: K90U**
FCC ID	**: SRQ-K90U**
STANDARD	**: 47 CFR Part 2, 22(H), 24(E), 27(L), 27(H)**
CLASSIFICATION	**: PCS Licensed Transmitter (PCB)**

The product was received on Jul. 19, 2016 and completely tested on Aug. 12, 2016. We, SPORTON INTERNATIONAL (KUNSHAN) INC., would like to declare that the tested sample has been evaluated in accordance with the test procedures given in ANSI / TIA / EIA-603-D-2010 and the testing has shown the tested sample to be in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL (KUNSHAN) INC., the test report shall not be reproduced except in full.

James Huang

Prepared by: James Huang / Manager

Jones Tsai

Approved by: Jones Tsai / Manager

Testing Laboratory 2627

SPORTON INTERNATIONAL (KUNSHAN) INC.
No. 3-2, PingXiang Road, Kunshan, Jiangsu Province, P. R. China

SPORTON INTERNATIONAL (KUNSHAN) INC.
TEL : 86-0512-5790-0158
FAX : 86-0512-5790-0958
FCC ID : SRQ-K90U

Page Number   : 1 of 30
Report Issued Date : Sep. 13, 2016
Report Version   : Rev. 01
Report Template No.: BU5-FGLTE Version 1.5

TABLE OF CONTENTS

SPORTON INTERNATIONAL (KUNSHAN) INC.

TEL : 86-0512-5790-0158

FAX : 86-0512-5790-0958

FCC ID : SRQ-K90U

Page Number   : 2 of 30

Report Issued Date : Sep. 13, 2016

Report Version   : Rev. 01

Report Template No.: BU5-FGLTE Version 1.5

APPENDIX B. TEST RESULTS OF RADIATED TEST

APPENDIX C. TEST SETUP PHOTOGRAPHS

SPORTON INTERNATIONAL (KUNSHAN) INC.

TEL : 86-0512-5790-0158

FAX : 86-0512-5790-0958

FCC ID : SRQ-K90U

Page Number   : 3 of 30

Report Issued Date : Sep. 13, 2016

Report Version   : Rev. 01

Report Template No.: BU5-FGLTE Version 1.5

REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FG671906B	Rev. 01	Initial issue of report	Sep. 13, 2016

SPORTON INTERNATIONAL (KUNSHAN) INC.
TEL : 86-0512-5790-0158
FAX : 86-0512-5790-0958
FCC ID : SRQ-K90U

Page Number   : 4 of 30
Report Issued Date : Sep. 13, 2016
Report Version   : Rev. 01
Report Template No.: BU5-FGLTE Version 1.5

SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.4	§2.1046	Conducted Output Power	Reporting Only	PASS	-
	§22.913(a)(2)	Effective Radiated Power (Band 5)	ERP < 7 Watt	PASS	-
	§27.50(c)(10)	Effective Radiated Power (Band 12)	ERP < 3 Watt	PASS	-
	§24.232(c)	Equivalent Isotropic Radiated Power (Band 2)(Band 25)	EIRP < 2Watt	PASS	-
	§27.50(d)(4)	Equivalent Isotropic Radiated Power (Band 4)	EIRP < 1Watt	PASS	-
3.5	§24.232(d)	Peak-to-Average Ratio	<13 dB	PASS	-
3.6	§2.1049	Occupied Bandwidth	Reporting Only	PASS	-
3.7	§2.1051 §22.917(a) §24.238(a) §27.53(g) §27.53(h)	Conducted Band Edge Measurement (Band 2) (Band 4) (Band 5) (Band 12) (Band 25)	$< 43+10\log 10(P[\text{Watts}])$	PASS	-
3.8	§2.1051 §22.917(a) §24.238(a) §27.53(g) §27.53(h)	Conducted Spurious Emission (Band 2) (Band 4) (Band 5) (Band 12) (Band 25)	$< 43+10\log 10(P[\text{Watts}])$	PASS	-
3.9	§2.1055 §22.355	Frequency Stability Temperature & Voltage	< 2.5 ppm for Part 22H	PASS	-
	§2.1055 §24.235 §27.54		Within Authorized Band		
4.4	§2.1053 §22.917(a) §24.238(a) §27.53(g) §27.53(h)	Radiated Spurious Emission (Band 2) (Band 4) (Band 5) (Band 12) (Band 25)	$< 43+10\log_{10}(P[\text{Watts}])$	PASS	Under limit 3.50 dB at 3456.180 MHz

SPORTON INTERNATIONAL (KUNSHAN) INC.
TEL : 86-0512-5790-0158
FAX : 86-0512-5790-0958
FCC ID : SRQ-K90U

Page Number   : 5 of 30
Report Issued Date : Sep. 13, 2016
Report Version   : Rev. 01
Report Template No.: BU5-FGLTE Version 1.5

1   General Description
1.1   Applicant

ZTE CORPORATION

ZTE Plaza, Keji Road South, Hi-Tech, Industrial Park, Nanshan District, Shenzhen, Guangdong, 518057, P.R.China

1.2   Manufacturer

ZTE CORPORATION

ZTE Plaza, Keji Road South, Hi-Tech, Industrial Park, Nanshan District, Shenzhen, Guangdong, 518057, P.R.China

1.3   Product Feature of Equipment Under Test

Product Feature	
Equipment	LTE Tablet
Brand Name	ZTE
Model Name	K90U
FCC ID	SRQ-K90U
EUT supports Radios application	LTE/ WLAN2.4GHz 802.11b/g/n HT20/HT40/ WLAN5GHz 802.11a/n HT20/HT40/ WLAN5GHz 802.11ac VHT20/VHT40/VHT80/ Bluetooth v3.0+EDR/Bluetooth v4.1 LE
IMEI Code	Conducted: 990006081532235 Radiation: 99000608153033 ERP/EIRP: N/A
HW Version	u1pA
SW Version	K90UV1.0.0B06
EUT Stage	Identical Prototype

SPORTON INTERNATIONAL (KUNSHAN) INC.
TEL : 86-0512-5790-0158
FAX : 86-0512-5790-0958
FCC ID : SRQ-K90U

Page Number   : 6 of 30
Report Issued Date : Sep. 13, 2016
Report Version   : Rev. 01
Report Template No.: BU5-FGLTE Version 1.5

1.4   Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx Frequency	LTE Band 2 : 1850.7 MHz ~ 1909.3 MHz LTE Band 4 : 1710.7 MHz ~ 1754.3 MHz LTE Band 5 : 824.7 MHz ~ 848.3 MHz LTE Band 12 : 699.7 MHz ~ 715.3 MHz LTE Band 25 : 1850.7MHz ~ 1914.3 MHz
Rx Frequency	LTE Band 2 : 1930.7 MHz ~ 1989.3 MHz LTE Band 4 : 2110.7 MHz ~ 2154.3 MHz LTE Band 5 : 869.7 MHz ~ 893.3 MHz LTE Band 12 : 729.7 MHz ~ 745.3 MHz LTE Band 25 : 1930.7MHz ~ 1994.3 MHz
Bandwidth	LTE Band 2 : 1.4MHz / 3MHz / 5MHz / 10MHz / 15MHz / 20MHz LTE Band 4 : 1.4MHz / 3MHz / 5MHz / 10MHz / 15MHz / 20MHz LTE Band 5 : 1.4MHz / 3MHz / 5MHz / 10MHz LTE Band 12 : 1.4MHz / 3MHz / 5MHz / 10MHz LTE Band 25 : 1.4MHz / 3MHz / 5MHz / 10MHz / 15MHz / 20MHz
Maximum Output Power to Antenna	LTE Band 2 : 23.37 dBm LTE Band 4 : 23.68 dBm LTE Band 5 : 24.55 dBm LTE Band 12 : 24.65 dBm LTE Band 25 : 23.50 dBm
Antenna Gain	LTE Band 2 : -1.87 dBi LTE Band 4 : -3.30 dBi LTE Band 5 : -3.90 dBi LTE Band 12 : -3.70 dBi LTE Band 25 : -1.87 dBi
Type of Modulation	QPSK / 16QAM / 64QAM(Downlink only)

1.5 Modification of EUT

No modifications are made to the EUT during all test items.

1.6 Maximum ERP/EIRP Power, Frequency Tolerance, and Emission Designator

LTE Band 2	QPSK			16QAM		
BW(MHz)	Emission Designator (99%OBW)	Frequency Tolerance (ppm)	Maximum EIRP(W)	Emission Designator (99%OBW)	Frequency Tolerance (ppm)	Maximum EIRP(W)
1.4	1M10G7D	-	0.1371	1M10W7D	-	0.1084
3	2M73G7D	-	0.1406	2M72W7D	-	0.1033
5	4M49G7D	-	0.1413	4M49W7D	-	0.1045
10	9M05G7D	0.0033	0.1300	9M03W7D	-	0.1069
15	13M5G7D	-	0.1337	13M5W7D	-	0.1038
20	18M5G7D	-	0.1368	18M6W7D	-	0.0995

LTE Band 25	QPSK			16QAM		
BW(MHz)	Emission Designator (99%OBW)	Frequency Tolerance (ppm)	Maximum EIRP(W)	Emission Designator (99%OBW)	Frequency Tolerance (ppm)	Maximum EIRP(W)
1.4	1M10G7D	-	0.1455	1M10W7D	-	0.1122
3	2M70G7D	-	0.1380	2M72W7D	-	0.1057
5	4M49G7D	-	0.1358	4M49W7D	-	0.1042
10	8M97G7D	0.0023	0.1422	9M01W7D	-	0.1062
15	13M4G7D	-	0.1400	13M4W7D	-	0.1130
20	18M3G7D	-	0.1330	18M3W7D	-	0.1102

LTE Band 4	QPSK			16QAM		
BW(MHz)	Emission Designator (99%OBW)	Frequency Tolerance (ppm)	Maximum EIRP(W)	Emission Designator (99%OBW)	Frequency Tolerance (ppm)	Maximum EIRP(W)
1.4	1M10G7D	-	0.1091	1M10W7D	-	0.0841
3	2M72G7D	-	0.1050	2M72W7D	-	0.0849
5	4M49G7D	-	0.1019	4M49W7D	-	0.0843
10	9M05G7D	0.0033	0.1009	8M99W7D	-	0.0785
15	13M4G7D	-	0.1064	13M4W7D	-	0.0778
20	18M4G7D	-	0.1038	18M3W7D	-	0.0776

SPORTON INTERNATIONAL (KUNSHAN) INC.
TEL : 86-0512-5790-0158
FAX : 86-0512-5790-0958
FCC ID : SRQ-K90U

Page Number   : 8 of 30
Report Issued Date : Sep. 13, 2016
Report Version   : Rev. 01
Report Template No.: BU5-FGLTE Version 1.5

LTE Band 5	QPSK			16QAM		
BW(MHz)	Emission Designator (99%OBW)	Frequency Tolerance (ppm)	Maximum ERP(W)	Emission Designator (99%OBW)	Frequency Tolerance (ppm)	Maximum ERP(W)
1.4	1M10G7D	-	0.0701	1M10W7D	-	0.0708
3	2M73G7D	-	0.0708	2M75W7D	-	0.0647
5	4M51G7D	-	0.0698	4M49W7D	-	0.0676
10	9M05G7D	0.0047	0.0671	9M01W7D	-	0.0662
LTE Band 12	QPSK			16QAM		
BW(MHz)	Emission Designator (99%OBW)	Frequency Tolerance (ppm)	Maximum ERP(W)	Emission Designator (99%OBW)	Frequency Tolerance (ppm)	Maximum ERP(W)
1.4	1M09G7D	-	0.0735	1M09W7D	-	0.0647
3	2M73G7D	-	0.0757	2M73W7D	-	0.0556
5	4M50G7D	-	0.0759	4M49W7D	-	0.0547
10	9M05G7D	0.0065	0.0733	9M05W7D	-	0.0535

SPORTON INTERNATIONAL (KUNSHAN) INC.
TEL : 86-0512-5790-0158
FAX : 86-0512-5790-0958
FCC ID : SRQ-K90U

Page Number : 9 of 30
Report Issued Date : Sep. 13, 2016
Report Version : Rev. 01
Report Template No.: BU5-FGLTE Version 1.5

1.7   Testing Location

Test Site	SPORTON INTERNATIONAL (KUNSHAN) INC.
Test Site Location	No. 3-2, PingXiang Road, Kunshan, Jiangsu Province, P. R. China TEL: +86-0512-5790-0158 FAX: +86-0512-5790-0958
Test Site No.	**Sporton Site No.**
	TH01-KS

Test Site	SPORTON INTERNATIONAL (SHENZHEN) INC.	
Test Site Location	No. 3 Building, the third floor of south, Shahe River west, Fengzeyuan warehouse, Nanshan District, Shenzhen, Guangdong, P. R. China TEL: +86-755- 3320-2398	
Test Site No.	**Sporton Site No.**	**FCC Registration No.**
	03CH02-SZ	566869
	03CH03-SZ	565805

1.8   Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ⬧ 47 CFR Part 2, 22(H), 24(E), 27(L), 27(H)
- ⬧ ANSI / TIA / EIA-603-D-2010
- ⬧ FCC KDB 971168 D01 Power Meas. License Digital Systems v02r02

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2   Test Configuration of Equipment Under Test

2.1   Test Mode

Antenna port conducted and radiated test items listed below are performed according to KDB 971168 D01 Power Meas. License Digital Systems v02r02 with maximum output power.

Radiated measurements are performed by rotating the EUT in three different orthogonal test planes to find the maximum emission.

Test Items	Band	Bandwidth (MHz)						Modulation		RB #			Test Channel		
		1.4	3	5	10	15	20	QPSK	16QAM	1	Half	Full	L	M	H
Max. Output Power	2	ν	ν	ν	ν	ν	ν	ν	ν	ν	ν	ν	ν	ν	ν
	4	ν	ν	ν	ν	ν	ν	ν	ν	ν	ν	ν	ν	ν	ν
	5	ν	ν	ν	ν	-	-	ν	ν	ν	ν	ν	ν	ν	ν
	12	ν	ν	ν	ν	-	-	ν	ν	ν	ν	ν	ν	ν	ν
	25	ν	ν	ν	ν	ν	ν	ν	ν	ν	ν	ν	ν	ν	ν
Peak-to-Average Ratio	2						ν	ν	ν	ν		ν	ν	ν	ν
	4						ν	ν	ν	ν		ν	ν	ν	ν
	5				ν	-	-	ν	ν	ν		ν	ν	ν	ν
	12				ν	-	-	ν	ν	ν		ν	ν	ν	ν
	25						ν	ν	ν	ν		ν			ν
26dB and 99% Bandwidth	2	ν	ν	ν	ν	ν	ν	ν	ν			ν	ν	ν	ν
	4	ν	ν	ν	ν	ν	ν	ν	ν			ν	ν	ν	ν
	5	ν	ν	ν	ν	-	-	ν	ν			ν	ν	ν	ν
	12	ν	ν	ν	ν	-	-	ν	ν			ν	ν	ν	ν
	25	ν	ν	ν	ν	ν	ν	ν	ν			ν			ν
Conducted Band Edge	2	ν	ν	ν	ν	ν	ν	ν	ν	ν		ν	ν		ν
	4	ν	ν	ν	ν	ν	ν	ν	ν	ν		ν	ν		ν
	5	ν	ν	ν	ν	-	-	ν	ν	ν		ν	ν		ν
	12	ν	ν	ν	ν	-	-	ν	ν	ν		ν	ν		ν
	25	ν	ν	ν	ν	ν	ν	ν	ν	ν		ν			ν

Test Items	Band	Bandwidth (MHz)						Modulation		RB #			Test Channel		
		1.4	3	5	10	15	20	QPSK	16QAM	1	Half	Full	L	M	H
Conducted Spurious Emission	2	v	v	v	v	v	v	v	v	v	v		v	v	v
	4	v	v	v	v	v	v	v	v	v	v		v	v	v
	5	v	v	v	v	-	-	v	v	v	v		v	v	v
	12	v	v	v	v	-	-	v	v	v	v		v	v	v
	25	v	v	v	v	v	v	v	v	v					v
Frequency Stability	2				v			v				v		v	
	4				v			v				v		v	
	5				v	-	-	v				v		v	
	12				v	-	-	v				v		v	
	25				v			v				v		v	
E.R.P./ E.I.R.P.	2	v	v	v	v	v	v	v	v	v	v		v	v	v
	4	v	v	v	v	v	v	v	v	v	v		v	v	v
	5	v	v	v	v	-	-	v	v	v	v		v	v	v
	12	v	v	v	v	-	-	v	v	v	v		v	v	v
	25	v	v	v	v	v	v	v	v	v	v		v	v	v
Radiated Spurious Emission	2	v	v	v	v	v	v	v		v				v	
	4	v	v	v	v	v	v	v		v				v	
	5	v	v	v	v	-	-	v		v				v	
	12	v	v	v	v	-	-	v		v				v	
	25	v	v	v	v	v	v	v		v				v	
Note	1. The mark "v " means that this configuration is chosen for testing 2. The mark "-" means that this bandwidth is not supported. 3. The device is investigated from 30MHz to 10 times of fundamental signal for radiated spurious emission test under different RB size/offset and modulations in exploratory test. Subsequently, only the worst case emissions are reported.														

SPORTON INTERNATIONAL (KUNSHAN) INC.
TEL : 86-0512-5790-0158
FAX : 86-0512-5790-0958
FCC ID : SRQ-K90U

Page Number   : 12 of 30
Report Issued Date : Sep. 13, 2016
Report Version   : Rev. 01
Report Template No.: BU5-FGLTE Version 1.5

2.2 Connection Diagram of Test System

For LTE Band 2 / 4 / 5

For LTE Band 12 / 25

2.3   Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model No.	FCC ID	Data Cable	Power Cord
1.	System Simulator	R&S	CMU 200	N/A	N/A	Unshielded, 1.8 m
2.	DC Power Supply	GW INSTEK	GPD-2303S	N/A	N/A	Unshielded, 1.8 m
3.	Earphone	Apple	MC690ZP/A	N/A	Unshielded, 1.0 m	N/A

2.4 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

The spectrum analyzer offset is derived from RF cable loss.

Offset = RF cable loss.

Following shows an offset computation example with cable loss 5.0 dB.

Example :

Offset(dB) = RF cable loss(dB).

$\qquad\qquad$ = 5.0 (dB)

2.5 Frequency List of Low/Middle/High Channels

LTE Band 2 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
20	Channel	18700	18900	19100
	Frequency	1860	1880	1900
15	Channel	18675	18900	19125
	Frequency	1857.5	1880	1902.5
10	Channel	18650	18900	19150
	Frequency	1855	1880	1905
5	Channel	18625	18900	19175
	Frequency	1852.5	1880	1907.5
3	Channel	18615	18900	19185
	Frequency	1851.5	1880	1908.5
1.4	Channel	18607	18900	19193
	Frequency	1850.7	1880	1909.3

LTE Band 4 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
20	Channel	20050	20175	20300
	Frequency	1720	1732.5	1745
15	Channel	20025	20175	20325
	Frequency	1717.5	1732.5	1747.5
10	Channel	20000	20175	20350
	Frequency	1715	1732.5	1750
5	Channel	19975	20175	20375
	Frequency	1712.5	1732.5	1752.5
3	Channel	19965	20175	20385
	Frequency	1711.5	1732.5	1753.5
1.4	Channel	19957	20175	20393
	Frequency	1710.7	1732.5	1754.3

LTE Band 5 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
10	Channel	20450	20525	20600
	Frequency	829	836.5	844
5	Channel	20425	20525	20625
	Frequency	826.5	836.5	846.5
3	Channel	20415	20525	20635
	Frequency	825.5	836.5	847.5
1.4	Channel	20407	20525	20643
	Frequency	824.7	836.5	848.3

LTE Band 12 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
10	Channel	23060	23095	23130
	Frequency	704	707.5	711
5	Channel	23035	23095	23155
	Frequency	701.5	707.5	713.5
3	Channel	23025	23095	23165
	Frequency	700.5	707.5	714.5
1.4	Channel	23017	23095	23173
	Frequency	699.7	707.5	715.3

| LTE Band 25 Channel and Frequency List				
BW [MHz]	**Channel/Frequency(MHz)**	**Lowest**	**Middle**	**Highest**
20	Channel	26140	26340	26590
	Frequency	1860	1880	1905
15	Channel	26115	26340	26615
	Frequency	1857.5	1880	1907.5
10	Channel	26090	26340	26640
	Frequency	1855	1880	1910
5	Channel	26065	26340	26665
	Frequency	1852.5	1880	1912.5
3	Channel	26055	26340	26675
	Frequency	1851.5	1880	1913.5
1.4	Channel	26047	26340	26683
	Frequency	1850.7	1880	1914.3

3 Conducted Test Items

3.1 Measuring Instruments

See list of measuring instruments of this test report.

3.2 Test Setup

3.2.1 Conducted Output Power

3.2.2 Peak-to-Average Ratio, Occupied Bandwidth ,Conducted Band-Edge and Conducted Spurious Emission

3.2.3 Frequency Stability

3.3 Test Result of Conducted Test

Please refer to Appendix A.

3.4   Conducted Output Power and ERP/EIRP

3.4.1   Description of the Conducted Output Power Measurement and ERP/EIRP Measurement

A system simulator was used to establish communication with the EUT. Its parameters were set to force the EUT transmitting at maximum output power. The measured power in the radio frequency on the transmitter output terminals shall be reported.

The ERP of mobile transmitters must not exceed 7 Watts for LTE Band 5.

The ERP of mobile transmitters must not exceed 3 Watts for LTE Band 12.

The EIRP of mobile transmitters must not exceed 2 Watts for LTE Band 2 and Band 25.

The EIRP of mobile transmitters must not exceed 1 Watts for LTE Band 4.

According to KDB 412172 D01 Power Approach,

$EIRP = P_T + G_T - L_C$, $ERP = EIRP - 2.15$, where

P_T = transmitter output power in dBm

G_T = gain of the transmitting antenna in dBi

L_C = signal attenuation in the connecting cable between the transmitter and antenna in dB

3.4.2   Test Procedures

1. The transmitter output port was connected to the system simulator.
2. Set EUT at maximum power through the system simulator.
3. Select lowest, middle, and highest channels for each band and different modulation.
4. Measure and record the power level from the system simulator.

3.5   Peak-to-Average Ratio

3.5.1   Description of the PAR Measurement

Power Complementary Cumulative Distribution Function (CCDF) curves provide a means for characterizing the power peaks of a digitally modulated signal on a statistical basis. A CCDF curve depicts the probability of the peak signal amplitude exceeding the average power level. Most contemporary measurement instrumentation include the capability to produce CCDF curves for an input signal provided that the instrument's resolution bandwidth can be set wide enough to accommodate the entire input signal bandwidth. In measuring transmissions in this band using an average power technique, the peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.

3.5.2   Test Procedures

1. The testing follows FCC KDB 971168 v02r02 Section 5.7.1.
2. The EUT was connected to spectrum and system simulator via a power divider.
3. Set the CCDF (Complementary Cumulative Distribution Function) option in spectrum analyzer.
4. The highest RF powers were measured and recorded the maximum PAPR level associated with a probability of 0.1 %.
5. Record the deviation as Peak to Average Ratio.

3.6   99% Occupied Bandwidth and 26dB Bandwidth Measurement

3.6.1   Description of 99% Occupied Bandwidth and 26dB Bandwidth Measurement

The 99% occupied bandwidth is the width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean transmitted power.

The 26 dB emission bandwidth is defined as the frequency range between two points, one above and one below the carrier frequency, at which the spectral density of the emission is attenuated 26 dB below the maximum in-band spectral density of the modulated signal. Spectral density (power per unit bandwidth) is to be measured with a detector of resolution bandwidth equal to approximately 1.0% of the emission bandwidth.

3.6.2   Test Procedures

1. The testing follows FCC KDB 971168 v02r02 Section 4.2.
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The span range for the spectrum analyzer shall be between two and five times the anticipated OBW.
4. The nominal resolution bandwidth (RBW) shall be in the range of 1 to 5 % of the anticipated OBW, and the VBW shall be at least 3 times the RBW.
5. Set the detection mode to peak, and the trace mode to max hold.
6. Determine the reference value: Set the EUT to transmit a modulated signal. Allow the trace to stabilize. Set the spectrum analyzer marker to the highest level of the displayed trace. (this is the reference value)
7. Determine the "-26 dB down amplitude" as equal to (Reference Value – X).
8. Place two markers, one at the lowest and the other at the highest frequency of the envelope of the spectral display such that each marker is at or slightly below the "–X dB down amplitude" determined in step 6. If a marker is below this "-X dB down amplitude" value it shall be placed as close as possible to this value. The OBW is the positive frequency difference between the two markers.
9. Use the 99 % power bandwidth function of the spectrum analyzer and report the measured bandwidth.

SPORTON INTERNATIONAL (KUNSHAN) INC.   Page Number   : 21 of 30
TEL : 86-0512-5790-0158   Report Issued Date : Sep. 13, 2016
FAX : 86-0512-5790-0958   Report Version   : Rev. 01
FCC ID : SRQ-K90U   Report Template No.: BU5-FGLTE Version 1.5

3.7   Conducted Band Edge

3.7.1   Description of Conducted Band Edge Measurement

22.917(a)

For operations in the 824 – 849 MHz band, the FCC limit is $43 + 10\log_{10}(P[Watts])$ dB below the transmitter power P(Watts) in a 100kHz bandwidth. However, in the 1MHz bands immediately outside and adjacent to the licensee's frequency block, a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed.

24.238 (a)

For operations in the 1850-1910 and 1930-1990 MHz band, the FCC limit is $43 + 10\log_{10}(P[Watts])$ dB below the transmitter power P(Watts) in a 1MHz bandwidth. However, in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed.

27.53 (g)

For operations in the 698 -746 MHz band, the FCC limit is $43 + 10\log10(P[Watts])$ dB below the transmitter power P(Watts) in a 100 kHz bandwidth. However, in the 100 kilohertz bands immediately outside and adjacent to a licensee's frequency block, a resolution bandwidth of at least 30 kHz may be employed.

27.53 (h)

For operations in the 1710 – 1755 MHz band, the FCC limit is $43 + 10\log_{10}(P[Watts])$ dB below the transmitter power P(Watts) in a 1 MHz bandwidth. However, in the 1MHz bands immediately outside and adjacent to the licensee's frequency block, a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed.

3.7.2   Test Procedures

1.   The testing follows FCC KDB 971168 v02r02 Section 6.0.

2.   The EUT was connected to spectrum analyzer and system simulator via a power divider.

3.   The band edges of low and high channels for the highest RF powers were measured.

4.   Set RBW >= 1% EBW in the 1MHz band immediately outside and adjacent to the band edge.

5.   Beyond the 1 MHz band from the band edge, RBW=1MHz was used or a narrower RBW was used and the measured power was integrated over the full required measurement bandwidth of 1 MHz.

6.   Set spectrum analyzer with RMS detector.

7.   The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

8.   Checked that all the results comply with the emission limit line.

   Example:

   The limit line is derived from 43 + 10log(P)dB below the transmitter power P(Watts)

   = P(W)- [43 + 10log(P)] (dB)

   = [30 + 10log(P)] (dBm) - [43 + 10log(P)] (dB) = -13dBm.

3.8   Conducted Spurious Emission

3.8.1   Description of Conducted Spurious Emission Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least 43 + 10 log (P) dB.

It is measured by means of a calibrated spectrum analyzer and scanned from 30 MHz up to a frequency including its 10[th] harmonic.

3.8.2   Test Procedures

1. The testing follows FCC KDB 971168 v02r02 Section 6.0.
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
4. The middle channel for the highest RF power within the transmitting frequency was measured.
5. The conducted spurious emission for the whole frequency range was taken.
6. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz.
7. Set spectrum analyzer with RMS detector.
8. Taking the record of maximum spurious emission.
9. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
10. The limit line is derived from 43 + 10log(P)dB below the transmitter power P(Watts)

    = P(W)- [43 + 10log(P)] (dB)

    = [30 + 10log(P)] (dBm) - [43 + 10log(P)] (dB)

    = -13dBm.

3.9   Frequency Stability

3.9.1   Description of Frequency Stability Measurement

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within ±0.00025% (±2.5ppm) of the center frequency.

3.9.2   Test Procedures for Temperature Variation

1. The testing follows FCC KDB 971168 v02r02 Section 9.0.
2. The EUT was set up in the thermal chamber and connected with the system simulator.
3. With power OFF, the temperature was decreased to -30°C and the EUT was stabilized before testing. Power was applied and the maximum change in frequency was recorded within one minute.
4. With power OFF, the temperature was raised in 10°C step up to 50°C. The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.

3.9.3   Test Procedures for Voltage Variation

1. The testing follows FCC KDB 971168 v02r02 Section 9.0.
2. The EUT was placed in a temperature chamber at 20±5° C and connected with the system simulator.
3. The power supply voltage to the EUT was varied from 85% to 115% of the nominal value measured at the input to the EUT.
4. The variation in frequency was measured for the worst case.

4   Radiated Test Items

4.1   Measuring Instruments

See list of measuring instruments of this test report.

4.2   Test Setup

4.2.1   For radiated test from 30MHz to 1GHz

4.2.2   For radiated test above 1GHz

4.3   Test Result of Radiated Test

Please refer to Appendix B.

SPORTON INTERNATIONAL (KUNSHAN) INC.   Page Number   : 26 of 30
TEL : 86-0512-5790-0158   Report Issued Date : Sep. 13, 2016
FAX : 86-0512-5790-0958   Report Version   : Rev. 01
FCC ID : SRQ-K90U   Report Template No.: BU5-FGLTE Version 1.5

4.4   Radiated Spurious Emission

4.4.1   Description of Radiated Spurious Emission

The radiated spurious emission was measured by substitution method according to ANSI / TIA / EIA-603-D-2010. The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least 43 + 10 log (P) dB.

For LTE Band 12

For operations in the 746-758 MHz, 775-788 MHz, and 805-806 MHz bands, emissions in the band 1559-1610 MHz shall be limited to −70 dBW/MHz equivalent isotropically radiated power (EIRP) for wideband signals, and −80 dBW EIRP for discrete emissions of less than 700 Hz bandwidth.

The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

4.4.2   Test Procedures

1. The testing follows FCC KDB 971168 v02r02 Section 5.8 and ANSI / TIA-603-D-2010 Section 2.2.12.
2. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
3. The EUT was set 3 meters from the receiving antenna, which was mounted on the antenna tower.
4. The table was rotated 360 degrees to determine the position of the highest spurious emission.
5. The height of the receiving antenna is varied between one meter and four meters to search the maximum spurious emission for both horizontal and vertical polarizations.
6. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking the record of maximum spurious emission.
7. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
8. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
9. Taking the record of output power at antenna port.
10. Repeat step 7 to step 8 for another polarization.
11. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
   The limit line is derived from 43 + 10log(P)dB below the transmitter power P(Watts)
   = P(W)- [43 + 10log(P)] (dB)
   = [30 + 10log(P)] (dBm) - [43 + 10log(P)] (dB)
   = -13dBm.

SPORTON INTERNATIONAL (KUNSHAN) INC.   Page Number   : 27 of 30
TEL : 86-0512-5790-0158   Report Issued Date : Sep. 13, 2016
FAX : 86-0512-5790-0958   Report Version   : Rev. 01
FCC ID : SRQ-K90U   Report Template No.: BU5-FGLTE Version 1.5

5   List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV40	101040	10Hz~40GHz	Sep. 10, 2015	Jul. 30, 2016~ Jul. 31, 2016	Sep. 09, 2016	Conducted (TH01-KS)
Thermal Chamber	Ten Billion	TTC-B3S	TBN-960502	-40~+150°C	Oct. 24, 2015	Jul. 30, 2016~ Jul. 31, 2016	Oct. 23, 2016	Conducted (TH01-KS)
Spectrum Analyzer	R&S	FSV40	101041	10kHz~40GHz;Max 30dBm	Oct. 20, 2015	Aug. 11, 2016~ Aug. 12, 2016	Oct. 19, 2016	Radiation (03CH02-SZ)
Bilog Antenna	TeseQ	CBL6112D	35407	30MHz-2GHz	May 21, 2016	Aug. 11, 2016~ Aug. 12, 2016	May 20, 2017	Radiation (03CH02-SZ)
Double Ridge Horn Antenna	SCHWARZBECK	BBHA 9120D	9120D-1285	1GHz~18GHz	Jan. 11, 2016	Aug. 11, 2016~ Aug. 12, 2016	Jan. 10, 2017	Radiation (03CH02-SZ)
SHF-EHF Horn	com-power	AH-840	101071	18Ghz-40GHz	Aug. 17, 2015	Aug. 11, 2016~ Aug. 12, 2016	Aug. 16, 2016	Radiation (03CH02-SZ)
Amplifier	HP	8447F	3113A04622	9kHz ~1300MHz / 30 dB	Jul. 16, 2016	Aug. 11, 2016~ Aug. 12, 2016	Jul. 15, 2017	Radiation (03CH02-SZ
Amplifier	Agilent	8449B	3008A01023	1GHz~26.5GHz	Oct. 20, 2015	Aug. 11, 2016~ Aug. 12, 2016	Oct. 19, 2016	Radiation (03CH02-SZ)
AC Power Source	Chroma	61601	616010002470	N/A	NCR	Aug. 11, 2016~ Aug. 12, 2016	NCR	Radiation (03CH02-SZ)
Turn Table	Chaintek	T-200	N/A	0~360 degree	NCR	Aug. 11, 2016~ Aug. 12, 2016	NCR	Radiation (03CH02-SZ)
Antenna Mast	Chaintek	MBS-400	N/A	1 m~4 m	NCR	Aug. 11, 2016~ Aug. 12, 2016	NCR	Radiation (03CH02-SZ)

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
EMI Test Receiver&SA	KEYSIGHT	N9038A	MY54450083	20Hz~8.4GHz	May 07, 2016	Aug. 11, 2016~ Aug. 12, 2016	May 06, 2017	Radiation (03CH03-SZ)
EXA Spectrum Anaiyzer	KEYSIGHT	N9010A	MY55150246	10Hz~44GHz	May 07, 2016	Aug. 11, 2016~ Aug. 12, 2016	May 06, 2017	Radiation (03CH03-SZ)
Bilog Antenna	TeseQ	CBL6112D	35408	30MHz~2GHz	May 21, 2016	Aug. 11, 2016~ Aug. 12, 2016	May 20, 2017	Radiation (03CH03-SZ)
Double Ridge Horn Antenna	SCHWARZBECK	BBHA9120D	9120D-1355	1GHz~18GHz	May 07, 2016	Aug. 11, 2016~ Aug. 12, 2016	May 06, 2017	Radiation (03CH03-SZ)
SHF-EHF Horn	com-power	AH-840	101071	18GHz~40GHz	Aug.19, 2015	Aug. 11, 2016~ Aug. 12, 2016	Aug. 18, 2016	Radiation (03CH03-SZ)
Amplifier	Burgeon	BPA-530	102210	0.01Hz ~3000MHz	Oct. 20, 2015	Aug. 11, 2016~ Aug. 12, 2016	Oct. 19, 2016	Radiation (03CH03-SZ)
Amplifier	Agilent Technologies	83017A	MY39501302	500MHz~26.5GHz	Jan. 12, 2016	Aug. 11, 2016~ Aug. 12, 2016	Jan. 11, 2017	Radiation (03CH03-SZ)
AC Power Source	Chroma	61601	616010001985	N/A	NCR	Aug. 11, 2016~ Aug. 12, 2016	NCR	Radiation (03CH03-SZ)
Turn Table	EM	EM1000	N/A	0~360 degree	NCR	Aug. 11, 2016~ Aug. 12, 2016	NCR	Radiation (03CH03-SZ)
Antenna Mast	EM	EM1000	N/A	1 m~4 m	NCR	Aug. 11, 2016~ Aug. 12, 2016	NCR	Radiation (03CH03-SZ)

NCR: No Calibration Required

SPORTON INTERNATIONAL (KUNSHAN) INC.

TEL : 86-0512-5790-0158

FAX : 86-0512-5790-0958

FCC ID : SRQ-K90U

Page Number   : 29 of 30

Report Issued Date : Sep. 13, 2016

Report Version   : Rev. 01

Report Template No.: BU5-FGLTE Version 1.5

6   Uncertainty of Evaluation

<u>Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz) for 03CH02-SZ</u>

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	2.5dB

<u>Uncertainty of Radiated Emission Measurement (1GHz ~ 18GHz) for 03CH02-SZ</u>

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	3.3dB

<u>Uncertainty of Radiated Emission Measurement (18GHz ~ 40GHz) for 03CH02-SZ</u>

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	3.7dB

<u>Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz) for 03CH03-SZ</u>

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	3.0dB

<u>Uncertainty of Radiated Emission Measurement (1GHz ~ 18GHz) for 03CH03-SZ</u>

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	3.6dB

<u>Uncertainty of Radiated Emission Measurement (18GHz ~ 40GHz) for 03CH03-SZ</u>

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	3.8dB

Appendix A. Test Results of Conducted Test

Conducted Output Power(Average power)

BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
\multicolumn{7}{c}{LTE Band 2 Maximum Average Power [dBm]}						
20	1	0	QPSK	22.67	22.68	22.74
20	1	49		22.60	22.74	22.84
20	1	99		22.91	22.80	23.23
20	50	0		21.99	22.01	22.04
20	50	24		21.87	21.93	21.91
20	50	50		21.63	21.89	22.01
20	100	0		21.82	21.91	22.01
20	1	0	16-QAM	21.73	21.71	21.73
20	1	49		21.71	21.60	21.85
20	1	99		21.43	21.79	21.85
20	50	0		20.89	20.94	20.99
20	50	24		20.79	21.04	21.02
20	50	50		20.62	20.99	21.04
20	100	0		20.81	21.00	20.93
15	1	0	QPSK	22.82	22.95	22.96
15	1	37		23.10	23.12	23.03
15	1	74		22.66	22.93	23.13
15	36	0		21.86	22.04	21.98
15	36	20		21.81	21.91	22.02
15	36	39		21.80	21.89	22.03
15	75	0		21.77	21.93	21.95
15	1	0	16-QAM	21.72	21.86	21.90
15	1	37		21.84	21.69	22.03
15	1	74		21.56	21.66	21.93
15	36	0		20.94	21.05	21.00
15	36	20		20.89	20.93	21.05
15	36	39		20.99	20.90	21.16
15	75	0		20.95	21.04	20.97

\ multicolumn{7}{|c|}{LTE Band 2 Maximum Average Power [dBm]}						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
10	1	0	QPSK	22.65	22.86	22.80
10	1	25		22.59	22.85	23.01
10	1	49		22.90	22.68	22.91
10	25	0		21.86	21.94	21.97
10	25	12		21.83	21.89	22.07
10	25	25		21.73	21.89	22.08
10	50	0		21.86	21.95	22.01
10	1	0	16-QAM	21.71	21.92	22.16
10	1	25		21.65	21.70	22.03
10	1	49		21.73	21.81	22.11
10	25	0		20.95	21.16	21.00
10	25	12		20.97	21.00	21.11
10	25	25		20.70	20.99	21.24
10	50	0		20.86	21.16	21.05
5	1	0	QPSK	22.51	22.80	23.04
5	1	12		22.81	22.93	23.37
5	1	24		22.87	22.79	22.93
5	12	0		21.73	21.84	22.05
5	12	7		21.81	21.83	22.06
5	12	13		21.83	21.85	22.11
5	25	0		21.80	21.86	22.03
5	1	0	16-QAM	21.64	21.54	22.06
5	1	12		21.63	21.70	22.01
5	1	24		21.52	21.70	21.96
5	12	0		20.73	20.95	21.01
5	12	7		20.80	20.76	20.97
5	12	13		20.80	20.76	20.98
5	25	0		20.80	20.75	21.07

SPORTON INTERNATIONAL (KUNSHAN) INC.
TEL : 86-0512-5790-0158
FAX : 86-0512-5790-0958
FCC ID : SRQ-K90U

Page Number   : A2 of A169
Report Issued Date : Sep. 13, 2016
Report Version   : Rev. 01
Report Template No.: BU5-FGLTE Version 1.5

LTE Band 2 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
3	1	0	QPSK	22.79	22.68	23.12
3	1	8		22.94	22.90	23.35
3	1	14		22.79	22.94	22.99
3	8	0		21.81	21.80	22.14
3	8	4		21.82	21.96	22.13
3	8	7		21.85	21.88	22.18
3	15	0		21.82	21.87	22.10
3	1	0	16-QAM	21.61	21.67	22.00
3	1	8		21.54	21.45	21.94
3	1	14		21.68	21.87	22.01
3	8	0		20.93	20.98	21.19
3	8	4		21.05	20.92	21.25
3	8	7		21.17	20.92	21.15
3	15	0		21.00	21.08	21.23
1.4	1	0	QPSK	22.64	22.87	23.15
1.4	1	3		22.92	23.05	23.20
1.4	1	5		22.84	22.90	23.10
1.4	3	0		22.89	23.01	23.20
1.4	3	1		22.97	23.01	23.24
1.4	3	3		23.00	22.82	23.24
1.4	6	0		21.94	21.79	22.06
1.4	1	0	16-QAM	21.90	21.71	22.03
1.4	1	3		21.59	21.67	21.97
1.4	1	5		21.50	21.41	22.20
1.4	3	0		21.83	21.82	22.19
1.4	3	1		21.91	21.96	22.22
1.4	3	3		21.95	21.95	22.20
1.4	6	0		20.79	20.76	20.79

LTE Band 25 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
20	1	0	QPSK	22.83	22.94	22.95
20	1	49		22.85	22.99	23.11
20	1	99		22.69	22.98	22.85
20	50	0		21.98	22.00	22.22
20	50	24		21.95	21.95	22.13
20	50	50		21.83	21.96	22.19
20	100	0		21.86	22.04	22.13
20	1	0	16-QAM	21.76	21.86	22.29
20	1	49		21.79	21.82	22.19
20	1	99		21.65	21.84	21.80
20	50	0		20.90	20.97	21.44
20	50	24		20.88	21.06	21.29
20	50	50		20.84	21.11	21.35
20	100	0		20.82	21.03	21.12
15	1	0	QPSK	22.72	22.96	23.21
15	1	37		23.06	23.14	23.33
15	1	74		22.84	23.06	23.25
15	36	0		21.93	22.01	22.17
15	36	20		21.91	21.98	22.31
15	36	39		21.87	22.11	22.25
15	75	0		21.85	22.01	22.16
15	1	0	16-QAM	21.78	21.88	21.99
15	1	37		21.99	21.58	22.40
15	1	74		21.69	21.99	22.03
15	36	0		20.92	20.90	21.43
15	36	20		20.98	20.97	21.36
15	36	39		20.97	21.13	21.37
15	75	0		20.93	21.01	21.34

LTE Band 25 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
10	1	0	QPSK	22.65	22.93	23.40
10	1	25		22.62	23.02	23.30
10	1	49		22.90	23.08	23.04
10	25	0		21.87	21.95	22.19
10	25	12		21.89	21.99	22.28
10	25	25		21.89	21.99	22.28
10	50	0		21.88	21.95	22.10
10	1	0	16-QAM	21.74	21.74	22.13
10	1	25		21.75	21.70	22.10
10	1	49		21.45	22.03	21.97
10	25	0		20.88	21.02	21.48
10	25	12		20.89	21.09	21.35
10	25	25		21.05	20.99	21.04
10	50	0		20.97	20.86	21.39
5	1	0	QPSK	22.80	22.69	23.20
5	1	12		22.80	22.92	23.16
5	1	24		22.53	23.06	23.05
5	12	0		21.84	21.84	22.28
5	12	7		21.91	21.93	22.10
5	12	13		21.85	21.85	22.12
5	25	0		21.82	21.86	22.20
5	1	0	16-QAM	21.67	21.81	22.05
5	1	12		21.70	21.67	21.99
5	1	24		21.63	21.64	22.05
5	12	0		20.65	20.86	21.36
5	12	7		20.66	20.98	21.03
5	12	13		20.65	20.96	20.97
5	25	0		20.61	20.97	20.99

LTE Band 25 Maximum Average Power [dBm]					
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
3	1	0	QPSK	22.85	22.95	23.03
3	1	8		22.87	22.94	23.21
3	1	14		22.93	22.98	23.27
3	8	0		21.86	21.87	22.17
3	8	4		21.97	22.04	22.30
3	8	7		21.91	21.96	22.17
3	15	0		21.88	21.95	22.21
3	1	0	16-QAM	21.51	21.85	22.11
3	1	8		21.44	21.51	21.93
3	1	14		21.75	21.65	22.10
3	8	0		20.60	20.73	21.25
3	8	4		20.82	20.81	21.27
3	8	7		20.96	21.07	21.24
3	15	0		20.89	20.79	21.02
1.4	1	0	QPSK	22.84	22.84	23.19
1.4	1	3		22.94	23.02	23.18
1.4	1	5		22.84	22.88	23.19
1.4	3	0		22.97	23.21	23.30
1.4	3	1		22.91	23.08	23.50
1.4	3	3		22.83	22.98	23.47
1.4	6	0		21.82	21.88	22.13
1.4	1	0	16-QAM	21.71	21.70	22.07
1.4	1	3		21.70	21.67	22.37
1.4	1	5		21.56	21.76	22.16
1.4	3	0		21.86	21.90	22.00
1.4	3	1		21.86	22.05	22.03
1.4	3	3		22.05	21.96	22.01
1.4	6	0		20.75	20.83	20.86

BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
\multicolumn{7}{c}{LTE Band 4 Maximum Average Power [dBm]}
20	1	0	QPSK	23.41	23.07	23.38
20	1	49		23.43	23.46	23.41
20	1	99		23.32	23.13	23.21
20	50	0		22.37	22.39	22.38
20	50	24		22.33	22.36	22.32
20	50	50		22.28	22.28	22.31
20	100	0		22.31	22.35	22.31
20	1	0	16-QAM	22.03	22.17	22.16
20	1	49		22.00	22.20	21.88
20	1	99		22.20	21.92	21.84
20	50	0		21.29	21.21	21.32
20	50	24		21.34	21.34	21.38
20	50	50		21.34	21.33	21.37
20	100	0		21.32	21.33	21.40
15	1	0	QPSK	23.54	23.28	23.29
15	1	37		23.33	23.57	23.48
15	1	74		22.85	23.35	23.11
15	36	0		22.37	22.39	22.41
15	36	20		22.34	22.37	22.31
15	36	39		22.29	22.39	22.33
15	75	0		22.33	22.35	22.31
15	1	0	16-QAM	21.89	22.12	21.89
15	1	37		22.07	22.21	21.99
15	1	74		21.96	21.99	21.86
15	36	0		21.31	21.36	21.50
15	36	20		21.37	21.50	21.48
15	36	39		21.45	21.46	21.30
15	75	0		21.37	21.50	21.36

SPORTON INTERNATIONAL (KUNSHAN) INC.
TEL : 86-0512-5790-0158
FAX : 86-0512-5790-0958
FCC ID : SRQ-K90U
Page Number : A7 of A169
Report Issued Date : Sep. 13, 2016
Report Version : Rev. 01
Report Template No.: BU5-FGLTE Version 1.5

LTE Band 4 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
10	1	0	QPSK	23.11	23.25	23.29
10	1	25		23.18	23.34	23.31
10	1	49		23.14	23.19	23.17
10	25	0		22.29	22.34	22.40
10	25	12		22.31	22.38	22.34
10	25	25		22.34	22.39	22.32
10	50	0		22.31	22.35	22.34
10	1	0	16-QAM	22.25	22.22	21.94
10	1	25		22.12	22.23	21.83
10	1	49		21.90	22.13	21.76
10	25	0		21.36	21.32	21.48
10	25	12		21.27	21.35	21.31
10	25	25		21.49	21.57	21.38
10	50	0		21.36	21.54	21.31
5	1	0	QPSK	23.10	23.38	23.02
5	1	12		23.28	23.33	23.26
5	1	24		23.09	23.17	22.96
5	12	0		22.30	22.36	22.29
5	12	7		22.19	22.41	22.23
5	12	13		22.28	22.43	22.25
5	25	0		22.27	22.37	22.29
5	1	0	16-QAM	22.02	22.04	21.81
5	1	12		22.01	22.56	22.32
5	1	24		22.13	22.48	22.19
5	12	0		21.17	21.34	21.26
5	12	7		21.15	21.30	21.20
5	12	13		21.10	21.47	21.21
5	25	0		21.35	21.27	21.26

LTE Band 4 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
3	1	0	QPSK	23.35	23.11	23.38
3	1	8		23.27	23.37	23.21
3	1	14		23.24	23.51	23.51
3	8	0		22.34	22.45	22.28
3	8	4		22.29	22.42	22.25
3	8	7		22.24	22.46	22.28
3	15	0		22.21	22.35	22.28
3	1	0	16-QAM	21.99	22.16	22.59
3	1	8		22.02	21.87	21.81
3	1	14		21.94	22.32	21.98
3	8	0		21.34	21.28	21.30
3	8	4		21.30	21.55	21.27
3	8	7		21.24	21.48	21.30
3	15	0		21.03	21.24	21.15
1.4	1	0	QPSK	23.19	23.37	23.33
1.4	1	3		23.50	23.37	23.49
1.4	1	5		23.34	23.20	23.31
1.4	3	0		23.40	23.54	23.40
1.4	3	1		23.33	23.68	23.45
1.4	3	3		23.32	23.51	23.45
1.4	6	0		22.31	22.36	22.19
1.4	1	0	16-QAM	21.82	22.31	22.07
1.4	1	3		21.85	22.23	22.02
1.4	1	5		22.08	22.52	22.09
1.4	3	0		22.03	22.30	22.42
1.4	3	1		22.18	22.40	22.55
1.4	3	3		22.36	22.47	22.54
1.4	6	0		21.10	21.33	21.45

LTE Band 5 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
10	1	0	QPSK	24.32	24.24	24.18
10	1	25		24.17	24.17	24.04
10	1	49		23.93	24.19	24.12
10	25	0		24.43	24.26	24.27
10	25	12		24.26	24.24	24.26
10	25	25		24.24	24.25	24.24
10	50	0		24.30	24.29	24.29
10	1	0	16-QAM	24.14	24.23	24.05
10	1	25		24.26	24.00	24.26
10	1	49		23.97	23.56	24.13
10	25	0		23.24	23.18	23.27
10	25	12		23.26	23.22	23.39
10	25	25		23.28	23.13	23.18
10	50	0		23.21	23.30	23.27
5	1	0	QPSK	24.04	24.00	24.14
5	1	12		24.30	24.18	24.19
5	1	24		23.93	24.33	24.03
5	12	0		24.49	24.30	24.26
5	12	7		24.38	24.29	24.18
5	12	13		24.26	24.27	24.22
5	25	0		24.31	24.22	24.31
5	1	0	16-QAM	23.85	24.35	23.82
5	1	12		23.85	23.99	23.98
5	1	24		23.94	24.08	23.86
5	12	0		23.53	23.31	23.20
5	12	7		23.08	23.35	23.14
5	12	13		23.06	23.32	23.10
5	25	0		23.12	23.27	23.37

LTE Band 5 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
3	1	0	QPSK	24.04	24.41	24.14
3	1	8		24.38	24.52	24.27
3	1	14		24.01	24.51	24.28
3	8	0		24.40	24.31	24.27
3	8	4		24.55	24.23	24.41
3	8	7		24.36	24.21	24.38
3	15	0		24.38	24.21	24.33
3	1	0	16-QAM	23.97	23.97	24.04
3	1	8		23.91	23.99	23.91
3	1	14		24.16	24.04	24.08
3	8	0		23.31	23.42	23.19
3	8	4		23.45	23.24	23.32
3	8	7		23.36	23.32	23.22
3	15	0		23.34	23.28	23.29
1.4	1	0	QPSK	24.19	24.06	24.31
1.4	1	3		24.35	24.25	24.37
1.4	1	5		24.13	24.12	24.15
1.4	3	0		24.37	24.18	24.39
1.4	3	1		24.42	24.23	24.51
1.4	3	3		24.38	24.22	24.39
1.4	6	0		24.30	24.10	24.38
1.4	1	0	16-QAM	23.94	24.00	24.26
1.4	1	3		24.09	23.99	24.23
1.4	1	5		24.01	23.77	24.22
1.4	3	0		24.28	24.35	24.51
1.4	3	1		24.33	24.40	24.55
1.4	3	3		24.34	24.45	24.54
1.4	6	0		23.00	23.13	23.24

| \multicolumn{7}{c}{LTE Band 12   Maximum Average Power [dBm]} |

BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
10	1	0	QPSK	24.04	23.99	24.00
10	1	25		24.30	24.50	24.49
10	1	49		24.18	24.24	23.79
10	25	0		23.24	23.25	23.26
10	25	12		23.28	23.31	23.28
10	25	25		23.26	23.25	23.27
10	50	0		23.32	23.41	23.25
10	1	0	16-QAM	23.11	22.82	22.85
10	1	25		23.02	23.06	22.72
10	1	49		23.13	23.05	22.93
10	25	0		22.26	22.44	22.32
10	25	12		22.34	22.34	22.20
10	25	25		22.33	22.31	22.45
10	50	0		22.48	22.21	22.42
5	1	0	QPSK	24.06	24.06	23.77
5	1	12		24.64	24.65	24.35
5	1	24		24.25	24.29	23.71
5	12	0		23.35	23.29	23.22
5	12	7		23.30	23.35	23.13
5	12	13		23.21	23.31	23.16
5	25	0		23.08	23.28	23.14
5	1	0	16-QAM	23.23	22.92	22.81
5	1	12		22.83	23.10	22.79
5	1	24		22.59	22.97	22.82
5	12	0		22.22	22.17	22.11
5	12	7		22.27	22.46	22.05
5	12	13		22.04	22.53	22.00
5	25	0		22.14	22.34	22.16

LTE Band 12 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
3	1	0	QPSK	24.25	24.14	24.09
3	1	8		24.52	24.64	24.30
3	1	14		24.18	24.22	24.02
3	8	0		23.35	23.15	23.20
3	8	4		23.45	23.32	23.24
3	8	7		23.39	23.27	23.30
3	15	0		23.41	23.30	23.19
3	1	0	16-QAM	22.74	23.02	23.11
3	1	8		22.89	23.09	23.30
3	1	14		22.73	23.06	22.92
3	8	0		22.03	22.26	22.00
3	8	4		22.34	22.43	22.28
3	8	7		22.27	22.48	22.21
3	15	0		22.34	22.29	22.16
1.4	1	0	QPSK	24.25	24.17	24.29
1.4	1	3		24.34	24.28	24.51
1.4	1	5		24.45	24.35	24.31
1.4	3	0		24.50	24.29	24.32
1.4	3	1		24.39	24.45	24.27
1.4	3	3		24.43	24.48	24.30
1.4	6	0		23.25	23.28	23.26
1.4	1	0	16-QAM	22.76	22.34	23.08
1.4	1	3		22.97	23.96	23.21
1.4	1	5		22.85	23.00	23.09
1.4	3	0		23.40	23.44	23.21
1.4	3	1		23.36	23.12	23.31
1.4	3	3		23.39	23.35	23.30
1.4	6	0		22.25	22.11	22.11

LTE Band 2 (G_T - L_C = -1.87 dB) QPSK								
Bandwidth	**1.4M**			**3M**			**5M**		
Channel	18607	18900	19193	18615	18900	19185	18625	18900	19175
	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)
Frequency (MHz)	1850.7	1880	1909.3	1851.5	1880	1908.5	1852.5	1880	1907.5
Conducted Power (dBm)	23.00	23.05	23.24	22.94	22.94	23.35	22.87	22.93	23.37
Conducted Power (Watts)	0.1995	0.2018	0.2109	0.1968	0.1968	0.2163	0.1936	0.1963	0.2173
EIRP(dBm)	21.13	21.18	21.37	21.07	21.07	21.48	21.00	21.06	21.50
EIRP(Watts)	0.1297	0.1312	0.1371	0.1279	0.1279	0.1406	0.1259	0.1276	0.1413

LTE Band 2 (G_T - L_C = -1.87 dB) QPSK								
Bandwidth	**10M**			**15M**			**20M**		
Channel	18650	18900	19150	18675	18900	19125	18650	18900	19100
	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)
Frequency (MHz)	1855	1880	1905	1857.5	1880	1902.5	1860	1880	1900
Conducted Power (dBm)	22.90	22.86	23.01	23.10	23.12	23.13	22.91	22.8	23.23
Conducted Power (Watts)	0.1950	0.1932	0.2000	0.2042	0.2051	0.2056	0.1954	0.1905	0.2104
EIRP(dBm)	21.03	20.99	21.14	21.23	21.25	21.26	21.04	20.93	21.36
EIRP(Watts)	0.1268	0.1256	0.1300	0.1327	0.1334	0.1337	0.1271	0.1239	0.1368

SPORTON INTERNATIONAL (KUNSHAN) INC.
TEL : 86-0512-5790-0158
FAX : 86-0512-5790-0958
FCC ID : SRQ-K90U

Page Number   : A14 of A169
Report Issued Date : Sep. 13, 2016
Report Version   : Rev. 01
Report Template No.: BU5-FGLTE Version 1.5

LTE Band 2 (G_T - L_C = -1.87 dB) 16QAM								
Bandwidth	**1.4M**			**3M**			**5M**		
Channel	18607	18900	19193	18615	18900	19185	18625	18900	19175
	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)
Frequency (MHz)	1850.7	1880	1909.3	1851.5	1880	1908.5	1852.5	1880	1907.5
Conducted Power (dBm)	21.95	21.96	22.22	21.68	21.87	22.01	21.64	21.7	22.06
Conducted Power (Watts)	0.1567	0.1570	0.1667	0.1472	0.1538	0.1589	0.1459	0.1479	0.1607
EIRP(dBm)	20.08	20.09	20.35	19.81	20.00	20.14	19.77	19.83	20.19
EIRP(Watts)	0.1019	0.1021	0.1084	0.0957	0.1000	0.1033	0.0948	0.0962	0.1045

LTE Band 2 (G_T - L_C = -1.87 dB) 16QAM								
Bandwidth	**10M**			**15M**			**20M**		
Channel	18650	18900	19150	18675	18900	19125	18650	18900	19100
	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)
Frequency (MHz)	1855	1880	1905	1857.5	1880	1902.5	1860	1880	1900
Conducted Power (dBm)	21.73	21.92	22.16	21.84	21.86	22.03	21.73	21.79	21.85
Conducted Power (Watts)	0.1489	0.1556	0.1644	0.1528	0.1535	0.1596	0.1489	0.1510	0.1531
EIRP(dBm)	19.86	20.05	20.29	19.97	19.99	20.16	19.86	19.92	19.98
EIRP(Watts)	0.0968	0.1012	0.1069	0.0993	0.0998	0.1038	0.0968	0.0982	0.0995

SPORTON INTERNATIONAL (KUNSHAN) INC.

TEL : 86-0512-5790-0158

FAX : 86-0512-5790-0958

FCC ID : SRQ-K90U

Page Number   : A15 of A169

Report Issued Date : Sep. 13, 2016

Report Version   : Rev. 01

Report Template No.: BU5-FGLTE Version 1.5

LTE Band 4 (G_T - L_C = -3.30 dB) QPSK								
Bandwidth	**1.4M**			**3M**			**5M**		
Channel	19957	20175	20393	19965	20175	20385	19975	20175	20375
	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)
Frequency (MHz)	1710.7	1732.5	1754.3	1711.5	1732.5	1753.5	1712.5	1732.5	1752.5
Conducted Power (dBm)	23.50	23.68	23.49	23.35	23.51	23.51	23.28	23.38	23.26
Conducted Power (Watts)	0.2239	0.2333	0.2234	0.2163	0.2244	0.2244	0.2128	0.2178	0.2118
EIRP(dBm)	20.20	20.38	20.19	20.05	20.21	20.21	19.98	20.08	19.96
EIRP(Watts)	0.1047	0.1091	0.1045	0.1012	0.1050	0.1050	0.0995	0.1019	0.0991

LTE Band 4 (G_T - L_C = -3.30 dB) QPSK								
Bandwidth	**10M**			**15M**			**20M**		
Channel	20000	20175	20350	20025	20175	20325	20050	20175	20300
	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)
Frequency (MHz)	1715	1732.5	1750	1717.5	1732.5	1747.5	1720	1732.5	1745
Conducted Power (dBm)	23.18	23.34	23.31	23.54	23.57	23.48	23.43	23.46	23.41
Conducted Power (Watts)	0.2080	0.2158	0.2143	0.2259	0.2275	0.2228	0.2203	0.2218	0.2193
EIRP(dBm)	19.88	20.04	20.01	20.24	20.27	20.18	20.13	20.16	20.11
EIRP(Watts)	0.0973	0.1009	0.1002	0.1057	0.1064	0.1042	0.1030	0.1038	0.1026

SPORTON INTERNATIONAL (KUNSHAN) INC.
TEL : 86-0512-5790-0158
FAX : 86-0512-5790-0958
FCC ID : SRQ-K90U

Page Number : A16 of A169
Report Issued Date : Sep. 13, 2016
Report Version : Rev. 01
Report Template No.: BU5-FGLTE Version 1.5

LTE Band 4 (G_T - L_C = -3.30 dB) 16QAM								
Bandwidth	**1.4M**			**3M**			**5M**		
Channel	19957	20175	20393	19965	20175	20385	19975	20175	20375
	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)
Frequency (MHz)	1710.7	1732.5	1754.3	1711.5	1732.5	1753.5	1712.5	1732.5	1752.5
Conducted Power (dBm)	22.36	22.52	22.55	22.02	22.32	22.59	22.13	22.56	22.32
Conducted Power (Watts)	0.1722	0.1786	0.1799	0.1592	0.1706	0.1816	0.1633	0.1803	0.1706
EIRP(dBm)	19.06	19.22	19.25	18.72	19.02	19.29	18.83	19.26	19.02
EIRP(Watts)	0.0805	0.0836	0.0841	0.0745	0.0798	0.0849	0.0764	0.0843	0.0798

LTE Band 4 (G_T - L_C = -3.30 dB) 16QAM								
Bandwidth	**10M**			**15M**			**20M**		
Channel	20000	20175	20350	20025	20175	20325	20050	20175	20300
	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)
Frequency (MHz)	1715	1732.5	1750	1717.5	1732.5	1747.5	1720	1732.5	1745
Conducted Power (dBm)	22.25	22.23	21.94	22.07	22.21	21.99	22.20	22.20	22.16
Conducted Power (Watts)	0.1679	0.1671	0.1563	0.1611	0.1663	0.1581	0.1660	0.1660	0.1644
EIRP(dBm)	18.95	18.93	18.64	18.77	18.91	18.69	18.90	18.90	18.86
EIRP(Watts)	0.0785	0.0782	0.0731	0.0753	0.0778	0.0740	0.0776	0.0776	0.0769

SPORTON INTERNATIONAL (KUNSHAN) INC.
TEL : 86-0512-5790-0158
FAX : 86-0512-5790-0958
FCC ID : SRQ-K90U

Page Number   : A17 of A169
Report Issued Date : Sep. 13, 2016
Report Version   : Rev. 01
Report Template No.: BU5-FGLTE Version 1.5

LTE Band 5 (G_T - L_C = -3.90 dB) QPSK								
Bandwidth	**1.4M**			**3M**			**5M**		
Channel	20407	20525	20643	20415	20525	20635	20425	20525	20625
	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)
Frequency (MHz)	824.7	836.5	848.3	825.5	836.5	847.5	826.5	836.5	846.5
Conducted Power (dBm)	24.42	24.25	24.51	24.55	24.52	24.41	24.49	24.33	24.31
Conducted Power (Watts)	0.2767	0.2661	0.2825	0.2851	0.2831	0.2761	0.2812	0.2710	0.2698
ERP(dBm)	18.37	18.20	18.46	18.50	18.47	18.36	18.44	18.28	18.26
ERP(Watts)	0.0687	0.0661	0.0701	0.0708	0.0703	0.0685	0.0698	0.0673	0.0670

LTE Band 5 (G_T - L_C = -3.90 dB) QPSK		
Bandwidth	**10M**	
Channel	20450	20525	20600
	(Low)	(Mid)	(High)
Frequency (MHz)	829	836.5	844
Conducted Power (dBm)	24.32	24.29	24.29
Conducted Power (Watts)	0.2704	0.2685	0.2685
ERP(dBm)	18.27	18.24	18.24
ERP(Watts)	0.0671	0.0667	0.0667

SPORTON INTERNATIONAL (KUNSHAN) INC.
TEL : 86-0512-5790-0158
FAX : 86-0512-5790-0958
FCC ID : SRQ-K90U

Page Number : A18 of A169
Report Issued Date : Sep. 13, 2016
Report Version : Rev. 01
Report Template No.: BU5-FGLTE Version 1.5

LTE Band 5 (G_T - L_C = -3.90 dB) 16QAM								
Bandwidth	**1.4M**			**3M**			**5M**		
Channel	20407	20525	20643	20415	20525	20635	20425	20525	20625
	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)
Frequency (MHz)	824.7	836.5	848.3	825.5	836.5	847.5	826.5	836.5	846.5
Conducted Power (dBm)	24.34	24.45	24.55	24.16	24.04	24.08	23.94	24.35	23.98
Conducted Power (Watts)	0.2716	0.2786	0.2851	0.2606	0.2535	0.2559	0.2477	0.2723	0.2500
ERP(dBm)	18.29	18.40	18.50	18.11	17.99	18.03	17.89	18.30	17.93
ERP(Watts)	0.0675	0.0692	0.0708	0.0647	0.0630	0.0635	0.0615	0.0676	0.0621

LTE Band 5 (G_T - L_C = -3.90 dB) 16QAM			
Bandwidth	**10M**		
Channel	20450	20525	20600
	(Low)	(Mid)	(High)
Frequency (MHz)	829	836.5	844
Conducted Power (dBm)	24.26	24.23	24.26
Conducted Power (Watts)	0.2667	0.2649	0.2667
ERP(dBm)	18.21	18.18	18.21
ERP(Watts)	0.0662	0.0658	0.0662

SPORTON INTERNATIONAL (KUNSHAN) INC.
TEL : 86-0512-5790-0158
FAX : 86-0512-5790-0958
FCC ID : SRQ-K90U

Page Number : A19 of A169
Report Issued Date : Sep. 13, 2016
Report Version : Rev. 01
Report Template No.: BU5-FGLTE Version 1.5

LTE Band 12 (G_T - L_C = -3.70 dB) QPSK								
Bandwidth	1.4M			3M			5M		
Channel	23017	23095	23173	23025	23095	23165	23035	23095	23155
	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)
Frequency (MHz)	699.7	707.5	715.3	700.5	707.5	714.5	701.5	707.5	713.5
Conducted Power (dBm)	24.50	24.48	24.51	24.52	24.64	24.3	24.64	24.65	24.35
Conducted Power (Watts)	0.2818	0.2805	0.2825	0.2831	0.2911	0.2692	0.2911	0.2917	0.2723
ERP(dBm)	18.65	18.63	18.66	18.67	18.79	18.45	18.79	18.80	18.50
ERP(Watts)	0.0733	0.0729	0.0735	0.0736	0.0757	0.0700	0.0757	0.0759	0.0708

LTE Band 12 (G_T - L_C = -3.70 dB) QPSK			
Bandwidth	10M		
Channel	23060	23095	23130
	(Low)	(Mid)	(High)
Frequency (MHz)	704	707.5	711
Conducted Power (dBm)	24.18	24.5	24.49
Conducted Power (Watts)	0.2618	0.2818	0.2812
ERP(dBm)	18.33	18.65	18.64
ERP(Watts)	0.0681	0.0733	0.0731

LTE Band 12 (G_T - L_C = -3.70 dB) 16QAM									
Bandwidth	**1.4M**			**3M**			**5M**		
Channel	**23017**	**23095**	**23173**	**23025**	**23095**	**23165**	**23035**	**23095**	**23155**
	(Low)	**(Mid)**	**(High)**	**(Low)**	**(Mid)**	**(High)**	**(Low)**	**(Mid)**	**(High)**
Frequency (MHz)	**699.7**	**707.5**	**715.3**	**700.5**	**707.5**	**714.5**	**701.5**	**707.5**	**713.5**
Conducted Power (dBm)	23.40	23.96	23.31	22.89	23.09	23.3	23.23	23.1	22.82
Conducted Power (Watts)	0.2188	0.2489	0.2143	0.1945	0.2037	0.2138	0.2104	0.2042	0.1914
ERP(dBm)	17.55	18.11	17.46	17.04	17.24	17.45	17.38	17.25	16.97
ERP(Watts)	0.0569	0.0647	0.0557	0.0506	0.0530	0.0556	0.0547	0.0531	0.0498

LTE Band 12 (G_T - L_C = -3.70 dB) 16QAM			
Bandwidth	**10M**		
Channel	**23060**	**23095**	**23130**
	(Low)	**(Mid)**	**(High)**
Frequency (MHz)	**704**	**707.5**	**711**
Conducted Power (dBm)	23.13	23.06	22.93
Conducted Power (Watts)	0.2056	0.2023	0.1963
ERP(dBm)	17.28	17.21	17.08
ERP(Watts)	0.0535	0.0526	0.0511

LTE Band 25 (G_T - L_C = -1.87 dB) QPSK								
Bandwidth	**1.4M**			**3M**			**5M**		
Channel	26407	26340	26683	26055	26340	26675	26065	26340	26665
	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)
Frequency (MHz)	1850.7	1880	1914.3	1851.5	1880	1913.5	1852.5	1880	1912.5
Conducted Power (dBm)	22.97	23.21	23.5	22.93	22.98	23.27	22.80	23.06	23.2
Conducted Power (Watts)	0.1982	0.2094	0.2239	0.1963	0.1986	0.2123	0.1905	0.2023	0.2089
EIRP(dBm)	21.10	21.34	21.63	21.06	21.11	21.40	20.93	21.19	21.33
EIRP(Watts)	0.1288	0.1361	0.1455	0.1276	0.1291	0.1380	0.1239	0.1315	0.1358

LTE Band 25 (G_T - L_C = -1.87 dB) QPSK								
Bandwidth	**10M**			**15M**			**20M**		
Channel	26090	26340	26640	26115	26340	26615	26140	26340	26590
	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)
Frequency (MHz)	1855	1880	1910	1857.5	1880	1907.5	1860	1880	1905
Conducted Power (dBm)	22.90	23.08	23.4	23.06	23.14	23.33	22.85	22.99	23.11
Conducted Power (Watts)	0.1950	0.2032	0.2188	0.2023	0.2061	0.2153	0.1928	0.1991	0.2046
EIRP(dBm)	21.03	21.21	21.53	21.19	21.27	21.46	20.98	21.12	21.24
EIRP(Watts)	0.1268	0.1321	0.1422	0.1315	0.1340	0.1400	0.1253	0.1294	0.1330

LTE Band 25 (G_T - L_C = -1.87 dB) 16QAM								
Bandwidth	**1.4M**			**3M**			**5M**		
Channel	26407	26340	26683	26055	26340	26675	26065	26340	26665
	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)
Frequency (MHz)	1850.7	1880	1914.3	1851.5	1880	1913.5	1852.5	1880	1912.5
Conducted Power (dBm)	22.05	22.05	22.37	21.75	21.85	22.11	21.70	21.81	22.05
Conducted Power (Watts)	0.1603	0.1603	0.1726	0.1496	0.1531	0.1626	0.1479	0.1517	0.1603
EIRP(dBm)	20.18	20.18	20.50	19.88	19.98	20.24	19.83	19.94	20.18
EIRP(Watts)	0.1042	0.1042	0.1122	0.0973	0.0995	0.1057	0.0962	0.0986	0.1042

LTE Band 25 (G_T - L_C = -1.87 dB) 16QAM								
Bandwidth	**10M**			**15M**			**20M**		
Channel	26090	26340	26640	26115	26340	26615	26140	26340	26590
	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)
Frequency (MHz)	1855	1880	1910	1857.5	1880	1907.5	1860	1880	1905
Conducted Power (dBm)	21.75	21.74	22.13	21.99	21.99	22.4	21.79	21.86	22.29
Conducted Power (Watts)	0.1496	0.1493	0.1633	0.1581	0.1581	0.1738	0.1510	0.1535	0.1694
EIRP(dBm)	19.88	19.87	20.26	20.12	20.12	20.53	19.92	19.99	20.42
EIRP(Watts)	0.0973	0.0971	0.1062	0.1028	0.1028	0.1130	0.0982	0.0998	0.1102

Peak-to-Average Ratio

Mode	LTE Band 2 / 20MHz				
Mod.	QPSK		16QAM		Limit: 13dB
RB Size	1RB	Full RB	1RB	Full RB	Result
Lowest CH	3.86	4.55	4.64	5.74	**PASS**
Middle CH	3.51	4.38	4.43	5.45	
Highest CH	4.23	4.12	4.72	5.1	

Mode	LTE Band 4 / 20MHz				
Mod.	QPSK		16QAM		Limit: 13dB
RB Size	1RB	Full RB	1RB	Full RB	Result
Lowest CH	4.2	4.49	5.36	5.62	**PASS**
Middle CH	3.45	4.35	4.67	5.51	
Highest CH	3.86	4.67	4.93	5.68	

Mode	LTE Band 5 / 10MHz				
Mod.	QPSK		16QAM		Limit: 13dB
RB Size	1RB	Full RB	1RB	Full RB	Result
Lowest CH	4.41	4.64	5.04	5.59	**PASS**
Middle CH	4.12	4.32	5.1	5.25	
Highest CH	4.46	4.61	5.07	5.59	

Mode	LTE Band 12 / 10MHz				
Mod.	QPSK		16QAM		Limit: 13dB
RB Size	1RB	Full RB	1RB	Full RB	Result
Lowest CH	4.12	4.78	5.3	5.74	**PASS**
Middle CH	4.26	4.43	5.33	5.59	
Highest CH	4.2	4.55	5.16	5.65	

Mode	LTE Band 25 / 20MHz				
Mod.	QPSK		16QAM		Limit: 13dB
RB Size	1RB	Full RB	1RB	Full RB	Result
Lowest CH	-	-	-	-	**PASS**
Middle CH	-	-	-	-	
Highest CH	3.62	4.09	4.06	5.19	

LTE Band 2 / 20MHz / QPSK

Lowest Channel / 1RB

	Mean	Peak	Crest	10%	1%	0.1%	0.01%
Trace 1	20.73 dBm	24.66 dBm	3.93 dB	2.70 dB	3.71 dB	3.86 dB	3.94 dB

Date: 30.JUL.2016 22:59:13

Lowest Channel / Full RB

	Mean	Peak	Crest	10%	1%	0.1%	0.01%
Trace 1	21.56 dBm	26.54 dBm	4.98 dB	2.41 dB	4.03 dB	4.55 dB	4.87 dB

Date: 30.JUL.2016 22:59:29

Middle Channel / 1RB

	Mean	Peak	Crest	10%	1%	0.1%	0.01%
Trace 1	20.94 dBm	24.59 dBm	3.64 dB	2.61 dB	3.39 dB	3.51 dB	3.59 dB

Date: 30.JUL.2016 22:59:39

Middle Channel / Full RB

	Mean	Peak	Crest	10%	1%	0.1%	0.01%
Trace 1	21.47 dBm	26.31 dBm	4.84 dB	2.43 dB	3.91 dB	4.38 dB	4.67 dB

Date: 30.JUL.2016 22:59:50

Highest Channel / 1RB

	Mean	Peak	Crest	10%	1%	0.1%	0.01%
Trace 1	20.95 dBm	25.54 dBm	4.59 dB	2.64 dB	3.71 dB	4.23 dB	4.49 dB

Date: 30.JUL.2016 23:00:04

Highest Channel / Full RB

	Mean	Peak	Crest	10%	1%	0.1%	0.01%
Trace 1	21.60 dBm	26.22 dBm	4.54 dB	2.41 dB	3.71 dB	4.12 dB	4.38 dB

Date: 30.JUL.2016 23:00:14

SPORTON INTERNATIONAL (KUNSHAN) INC.
TEL : 86-0512-5790-0158
FAX : 86-0512-5790-0958
FCC ID : SRQ-K90U

Page Number : A25 of A169
Report Issued Date : Sep. 13, 2016
Report Version : Rev. 01
Report Template No.: BU5-FGLTE Version 1.5

LTE Band 2 / 20MHz / 16QAM	
Lowest Channel / 1RB	**Lowest Channel / Full RB**

Spectrum
Ref Level 25.00 dBm Offset 5.00 dB
Att 30 dB AQT 2 ms RBW 20 MHz
1Sa View
CF 1.86 GHz   Mean Pwr + 20.00 dB
Complementary Cumulative Distribution Function   Samples: 130000

	Mean	Peak	Crest	10%	1%	0.1%	0.01%
Trace 1	19.85 dBm	24.55 dBm	4.70 dB	3.10 dB	4.49 dB	4.64 dB	4.72 dB

Date: 30.JUL.2016 22:57:29

Spectrum
Ref Level 25.00 dBm Offset 5.00 dB
Att 30 dB AQT 2 ms RBW 20 MHz
1Sa View
CF 1.86 GHz   Mean Pwr + 20.00 dB
Complementary Cumulative Distribution Function   Samples: 130000

	Mean	Peak	Crest	10%	1%	0.1%	0.01%
Trace 1	20.40 dBm	26.73 dBm	6.32 dB	3.13 dB	4.96 dB	5.74 dB	6.09 dB

Date: 30.JUL.2016 22:57:59

Middle Channel / 1RB	**Middle Channel / Full RB**

Spectrum
Ref Level 25.00 dBm Offset 5.00 dB
Att 30 dB AQT 2 ms RBW 20 MHz
1Sa View
CF 1.88 GHz   Mean Pwr + 20.00 dB
Complementary Cumulative Distribution Function   Samples: 130000

	Mean	Peak	Crest	10%	1%	0.1%	0.01%
Trace 1	19.92 dBm	24.39 dBm	4.47 dB	3.01 dB	4.23 dB	4.43 dB	4.49 dB

Date: 30.JUL.2016 22:58:09

Spectrum
Ref Level 25.00 dBm Offset 5.00 dB
Att 30 dB AQT 2 ms RBW 20 MHz
1Sa View
CF 1.88 GHz   Mean Pwr + 20.00 dB
Complementary Cumulative Distribution Function   Samples: 130000

	Mean	Peak	Crest	10%	1%	0.1%	0.01%
Trace 1	20.45 dBm	26.25 dBm	5.80 dB	3.07 dB	4.78 dB	5.45 dB	5.71 dB

Date: 30.JUL.2016 22:58:33

Highest Channel / 1RB	**Highest Channel / Full RB**

Spectrum
Ref Level 25.00 dBm Offset 5.00 dB
Att 30 dB AQT 2 ms RBW 20 MHz
1Sa View
CF 1.9 GHz   Mean Pwr + 20.00 dB
Complementary Cumulative Distribution Function   Samples: 130000

	Mean	Peak	Crest	10%	1%	0.1%	0.01%
Trace 1	19.84 dBm	24.63 dBm	4.79 dB	3.07 dB	4.55 dB	4.72 dB	4.81 dB

Date: 30.JUL.2016 22:58:47

Spectrum
Ref Level 25.00 dBm Offset 5.00 dB
Att 30 dB AQT 2 ms RBW 20 MHz
1Sa View
CF 1.9 GHz   Mean Pwr + 20.00 dB
Complementary Cumulative Distribution Function   Samples: 130000

	Mean	Peak	Crest	10%	1%	0.1%	0.01%
Trace 1	20.61 dBm	26.23 dBm	5.62 dB	3.04 dB	4.52 dB	5.10 dB	5.36 dB

Date: 30.JUL.2016 22:58:58

LTE Band 4 / 20MHz / QPSK

Lowest Channel / 1RB	Lowest Channel / Full RB

Date: 31.JUL.2016 01:52:25

Date: 31.JUL.2016 01:52:47

Middle Channel / 1RB	Middle Channel / Full RB

Date: 31.JUL.2016 01:53:27

Date: 31.JUL.2016 01:53:12

Highest Channel / 1RB	Highest Channel / Full RB

Date: 31.JUL.2016 01:53:48

Date: 31.JUL.2016 01:54:09

SPORTON INTERNATIONAL (KUNSHAN) INC.
TEL : 86-0512-5790-0158
FAX : 86-0512-5790-0958
FCC ID : SRQ-K90U

Page Number   : A27 of A169
Report Issued Date : Sep. 13, 2016
Report Version   : Rev. 01
Report Template No.: BU5-FGLTE Version 1.5

LTE Band 4 / 20MHz / 16QAM	
Lowest Channel / 1RB	**Lowest Channel / Full RB**

Date: 31.JUL.2016 01:50:33

Date: 31.JUL.2016 01:50:56

Middle Channel / 1RB	**Middle Channel / Full RB**

Date: 31.JUL.2016 01:51:10

Date: 31.JUL.2016 01:51:21

Highest Channel / 1RB	**Highest Channel / Full RB**

Date: 31.JUL.2016 01:51:37

Date: 31.JUL.2016 01:51:55

LTE Band 5 / 10MHz / QPSK

Lowest Channel / 1RB

Spectrum
Ref Level 24.50 dBm Offset 4.50 dB
Att   30 dB   AQT   2 ms RBW 10 MHz
1Sa View

0.1
0.01
1E-03
1E-04
1E-05

CF 829.0 MHz   Mean Pwr + 20.00 dB
Complementary Cumulative Distribution Function   Samples: 130000

	Mean	Peak	Crest	10%	1%	0.1%	0.01%
Trace 1	21.27 dBm	25.78 dBm	4.51 dB	2.49 dB	4.17 dB	4.41 dB	4.49 dB

Date: 31.JUL.2016 04:48:09

Lowest Channel / Full RB

Spectrum
Ref Level 24.50 dBm Offset 4.50 dB
Att   30 dB   AQT   2 ms RBW 10 MHz
1Sa View

0.1
0.01
1E-03
1E-04
1E-05

CF 829.0 MHz   Mean Pwr + 20.00 dB
Complementary Cumulative Distribution Function   Samples: 130000

	Mean	Peak	Crest	10%	1%	0.1%	0.01%
Trace 1	22.86 dBm	28.13 dBm	5.27 dB	2.43 dB	4.06 dB	4.64 dB	5.13 dB

Date: 31.JUL.2016 04:48:26

Middle Channel / 1RB

Spectrum
Ref Level 24.50 dBm Offset 4.50 dB
Att   30 dB   AQT   2 ms RBW 10 MHz
1Sa View

0.1
0.01
1E-03
1E-04
1E-05

CF 836.5 MHz   Mean Pwr + 20.00 dB
Complementary Cumulative Distribution Function   Samples: 130000

	Mean	Peak	Crest	10%	1%	0.1%	0.01%
Trace 1	21.05 dBm	25.22 dBm	4.16 dB	2.52 dB	3.97 dB	4.12 dB	4.14 dB

Date: 31.JUL.2016 04:48:53

Middle Channel / Full RB

Spectrum
Ref Level 24.50 dBm Offset 4.50 dB
Att   30 dB   AQT   2 ms RBW 10 MHz
1Sa View

0.1
0.01
1E-03
1E-04
1E-05

CF 836.5 MHz   Mean Pwr + 20.00 dB
Complementary Cumulative Distribution Function   Samples: 130000

	Mean	Peak	Crest	10%	1%	0.1%	0.01%
Trace 1	22.81 dBm	27.57 dBm	4.76 dB	2.43 dB	3.88 dB	4.32 dB	4.61 dB

Date: 31.JUL.2016 04:49:13

Highest Channel / 1RB

Spectrum
Ref Level 24.50 dBm Offset 4.50 dB
Att   30 dB   AQT   2 ms RBW 10 MHz
1Sa View

0.1
0.01
1E-03
1E-04
1E-05

CF 844.0 MHz   Mean Pwr + 20.00 dB
Complementary Cumulative Distribution Function   Samples: 130000

	Mean	Peak	Crest	10%	1%	0.1%	0.01%
Trace 1	21.36 dBm	25.92 dBm	4.55 dB	2.55 dB	4.29 dB	4.46 dB	4.55 dB

Date: 31.JUL.2016 04:49:59

Highest Channel / Full RB

Spectrum
Ref Level 24.50 dBm Offset 4.50 dB
Att   30 dB   AQT   2 ms RBW 10 MHz
1Sa View

0.1
0.01
1E-03
1E-04
1E-05

CF 844.0 MHz   Mean Pwr + 20.00 dB
Complementary Cumulative Distribution Function   Samples: 130000

	Mean	Peak	Crest	10%	1%	0.1%	0.01%
Trace 1	22.76 dBm	27.89 dBm	5.14 dB	2.41 dB	4.06 dB	4.61 dB	4.96 dB

Date: 31.JUL.2016 04:49:30

SPORTON INTERNATIONAL (KUNSHAN) INC.
TEL : 86-0512-5790-0158
FAX : 86-0512-5790-0958
FCC ID : SRQ-K90U

Page Number   : A29 of A169
Report Issued Date : Sep. 13, 2016
Report Version   : Rev. 01
Report Template No.: BU5-FGLTE Version 1.5

LTE Band 5 / 10MHz / 16QAM	
Lowest Channel / 1RB	**Lowest Channel / Full RB**

Date: 31.JUL.2016 04:38:21

Date: 31.JUL.2016 04:38:30

Middle Channel / 1RB	**Middle Channel / Full RB**

Date: 31.JUL.2016 04:38:41

Date: 31.JUL.2016 04:38:52

Highest Channel / 1RB	**Highest Channel / Full RB**

Date: 31.JUL.2016 04:39:04

Date: 31.JUL.2016 04:39:14

SPORTON INTERNATIONAL (KUNSHAN) INC.
TEL : 86-0512-5790-0158
FAX : 86-0512-5790-0958
FCC ID : SRQ-K90U

Page Number   : A30 of A169
Report Issued Date : Sep. 13, 2016
Report Version   : Rev. 01
Report Template No.: BU5-FGLTE Version 1.5

LTE Band 12 / 10MHz / QPSK	
Lowest Channel / 1RB	**Lowest Channel / Full RB**
Middle Channel / 1RB	**Middle Channel / Full RB**
Highest Channel / 1RB	**Highest Channel / Full RB**

LTE Band 12 / 10MHz / 16QAM	
Lowest Channel / 1RB	**Lowest Channel / Full RB**

Middle Channel / 1RB	**Middle Channel / Full RB**

Highest Channel / 1RB	**Highest Channel / Full RB**

26dB Bandwidth

Mode	LTE Band 2 : 26dB BW(MHz)											
BW	1.4MHz		3MHz		5MHz		10MHz		15MHz		20MHz	
Mod.	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM
Lowest CH	1.267	1.264	2.979	3.015	4.885	4.885	9.77	9.83	14.266	14.446	20.26	20.14
Middle CH	1.284	1.267	3.009	2.991	4.865	4.935	9.77	9.81	14.476	14.356	20.18	20.06
Highest CH	1.281	1.287	3.015	2.991	4.905	4.905	9.89	9.67	14.356	14.296	20.34	20.02

Mode	LTE Band 4 : 26dB BW(MHz)											
BW	1.4MHz		3MHz		5MHz		10MHz		15MHz		20MHz	
Mod.	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM
Lowest CH	1.287	1.264	2.973	2.985	4.915	4.905	10.01	9.89	14.356	14.206	20.18	20.26
Middle CH	1.236	1.264	2.955	3.033	4.965	4.925	9.77	9.85	14.476	14.236	20.02	20.14
Highest CH	1.278	1.318	3.015	2.991	4.945	4.945	9.87	9.69	14.476	14.476	20.14	20.22

Mode	LTE Band 5 : 26dB BW(MHz)											
BW	1.4MHz		3MHz		5MHz		10MHz		15MHz		20MHz	
Mod.	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM
Lowest CH	1.276	1.284	2.985	2.991	5.005	4.825	9.79	9.89	-	-	-	-
Middle CH	1.281	1.262	2.979	2.985	4.965	4.895	9.73	9.83	-	-	-	-
Highest CH	1.256	1.276	3.015	3.009	4.935	4.825	9.77	9.87	-	-	-	-

Mode	LTE Band 12 : 26dB BW(MHz)											
BW	1.4MHz		3MHz		5MHz		10MHz		15MHz		20MHz	
Mod.	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM
Lowest CH	1.281	1.284	2.985	3.015	4.945	4.915	9.87	9.75	-	-	-	-
Middle CH	1.262	1.267	3.003	3.003	4.835	4.805	9.77	9.61	-	-	-	-
Highest CH	1.256	1.29	2.991	3.045	4.895	5.005	9.87	9.81	-	-	-	-

Mode	LTE Band 25 : 26dB BW(MHz)											
BW	1.4MHz		3MHz		5MHz		10MHz		15MHz		20MHz	
Mod.	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM
Lowest CH	-	-	-	-	-	-	-	-	-	-	-	-
Middle CH	-	-	-	-	-	-	-	-	-	-	-	-
Highest CH	1.253	1.315	3.027	2.979	4.985	4.855	9.95	9.85	14.206	14.416	20.06	20.1

SPORTON INTERNATIONAL (KUNSHAN) INC.
TEL : 86-0512-5790-0158
FAX : 86-0512-5790-0958
FCC ID : SRQ-K90U

Page Number : A34 of A169
Report Issued Date : Sep. 13, 2016
Report Version : Rev. 01
Report Template No.: BU5-FGLTE Version 1.5

LTE Band 2	
Lowest Channel / 1.4MHz / QPSK	**Lowest Channel / 1.4MHz / 16QAM**
Middle Channel / 1.4MHz / QPSK	**Middle Channel / 1.4MHz / 16QAM**
Highest Channel / 1.4MHz / QPSK	**Highest Channel / 1.4MHz / 16QAM**

SPORTON INTERNATIONAL (KUNSHAN) INC.

TEL : 86-0512-5790-0158

FAX : 86-0512-5790-0958

FCC ID : SRQ-K90U

Page Number   : A35 of A169

Report Issued Date : Sep. 13, 2016

Report Version   : Rev. 01

Report Template No.: BU5-FGLTE Version 1.5

LTE Band 2

Lowest Channel / 3MHz / QPSK	Lowest Channel / 3MHz / 16QAM

Middle Channel / 3MHz / QPSK	Middle Channel /3MHz / 16QAM

Highest Channel /3MHz / QPSK	Highest Channel /3MHz / 16QAM

SPORTON INTERNATIONAL (KUNSHAN) INC.

TEL : 86-0512-5790-0158

FAX : 86-0512-5790-0958

FCC ID : SRQ-K90U

Page Number   : A36 of A169

Report Issued Date : Sep. 13, 2016

Report Version   : Rev. 01

Report Template No.: BU5-FGLTE Version 1.5

LTE Band 2	
Lowest Channel / 5MHz / QPSK	**Lowest Channel / 5MHz / 16QAM**
Date: 30.JUL.2016 21:50:56	Date: 30.JUL.2016 21:51:07
Middle Channel / 5MHz / QPSK	**Middle Channel / 5MHz / 16QAM**
Date: 30.JUL.2016 21:58:01	Date: 30.JUL.2016 21:58:12
Highest Channel / 5MHz / QPSK	**Highest Channel / 5MHz / 16QAM**
Date: 30.JUL.2016 22:00:34	Date: 30.JUL.2016 22:00:45