

---

# TEST REPORT

---

Report No.: SRTC2022-9003(F)-0020  
Product Name: LTE USB Dongle  
Model Name: MF833U1  
Applicant: ZTE Corporation  
Manufacturer: ZTE Corporation  
Specification: FCC Part15B (Certification)  
(2022 edition)  
FCC ID: SRQ-MF833U

The State Radio\_monitoring\_center Testing Center (SRTC)

15th Building, No.30 Shixing Street, Shijingshan District,

Beijing, China

Tel: 86-10-57996183 Fax: 86-10-57996388

---

## CONTENTS

1. General information .....	3
1.1 Notes of the test report .....	3
1.2 Information about the testing laboratory.....	3
1.3 Applicant's details .....	3
1.4 Manufacturer's details.....	3
1.5 Application details .....	4
1.6 Reference specification.....	4
1.7 Information of EUT.....	4
1.7.1 General information.....	4
1.7.2EUT details .....	5
1.7.3 Auxiliary equipment details.....	5
2. Test information .....	6
2.1 Summary of the test results .....	6
2.2 Test result.....	7
2.2.1Conducted Emissions-FCC Part15.107 .....	7
2.2.2RadiatedEmissions-FCC Part15.109.....	10
2.3. List of test equipments .....	14

## 1. General information

### 1.1 Notes of the test report

The test report may only be reproduced or published in full. Reproduction or publication of extracts from the report requires the prior written permission of The State Radio\_monitoring\_center Testing Center (SRTC).

The test results relate only to individual items of the samples which have been tested.

### 1.2 Information about the testing laboratory

Company: The State Radio\_monitoring\_center Testing Center (SRTC)  
Address: 15th Building, No.30 Shixing Street, Shijingshan District  
Testing location: No.80, Zhaojiachang, BeizangCun, Daxing District, Beijing, China.  
City: Beijing  
Country or Region: China  
Contacted person: Liu Jia  
Tel: +86 10 57996183  
Fax: +86 10 57996388  
Email: liujiaf@srtc.org.cn

### 1.3 Applicant's details

Company: ZTE Corporation  
Address: ZTE Plaza, #55 Keji Road South, Hi-Tech, Industrial Park, Nanshan District, Shenzhen, Guangdong, 518057  
City: Shenzhen  
Country or Region: P.R.China  
Contacted person: Ding Chaijue  
Tel: + 86-13764330709  
Email: ding.chaijue@zte.com.cn

### 1.4 Manufacturer's details

Company: ZTE Corporation  
Address: ZTE Plaza, #55 Keji Road South, Hi-Tech, Industrial Park, Nanshan District, Shenzhen, Guangdong, 518057  
City: Shenzhen  
Country or Region: P.R.China  
Contacted person: Ding Chaijue  
Tel: + 86-13764330709  
Email: ding.chaijue@zte.com.cn

## 1.5 Application details

Date of reception of test sample: 7<sup>th</sup> May 2022

Date of test: 7<sup>th</sup> May 2022 to 16<sup>th</sup> May 2022

## 1.6 Reference specification

FCC Part 15B, 2022 (Certification)

## 1.7 Information of EUT

### 1.7.1 General information

Name of EUT	LTE USB Dongle
Model Name	MF833U1
FCC ID	SRQ-MF833U
Frequency Range	GSM: GSM850 / PCS1900 WCDMA: FDD II / FDD IV / FDD V LTE: FDD 2/ FDD 4/ FDD 7/ TDD 66
Equipment Class	Class B
Power Supply	USB supply
Rated Power Supply Voltage	5V
Extreme Temperature	Lowest: -10°C Highest: +55°C
HW Version	dveB
SW Version	BD_MF833U1V1.0.0B01

### 1.7.2 EUT details

Product Name	Model Name	IMEI
LTE USB Dongle	MF833U1	860220049274486

### 1.7.3 Auxiliary equipment details

AE (Auxiliary Equipment) 1#: Laptop




Manufacturer	Lenovo
Model Number	E470c
S/N	PF10VBX6
Input Voltage	100V-240V AC

Note1: AE1# Laptop was selected by testing laboratory and was only cooperated with this test, not for sale.

## 2. Test information

### 2.1 Summary of the test results

No.	Test case	FCC reference	Verdict
1	Conducted emissions	15.107	Pass
2	Radiated emissions	15.109	Pass

Approved By: Mr. Liu Wei Director of the test department  	Checked By: Mr. Guo Yu Vice director of the test department  
Tested By: Mr. Wu Chengwang  	Issued date:  2022.07.28

## 2.2 Test result

### 2.2.1 Conducted Emissions-FCC Part15.107

Ambient condition:

Temperature	Relative humidity	Pressure
24.6°C	41.2%	100.8kPa

Test Setup with laptop:




Figure 1

Test Procedure:

The EUT is placed on a non-metallic table 0.8m above the horizontal metal reference ground plane. The EUT was connected with a laptop via the USB port and transferred the data. The laptop's LAN port is connected with another laptop via cable. And the data transferring between two laptops is maintained.

The AC main power supply of the laptop is connected to LISN and LISN is connected to the reference ground. The test set-up and the test methods are performed according to ANSI C63.4:2014.

Then start the test software EMC32. Sweep the whole frequency band through the range from 150 KHz to 30 MHz with RBW 9kHz, VBW 30kHz. The measurement should be done for both L line and N line. During pre-test, the receiver uses both peak detector and average detector. And the final test, the receiver uses both average detector and Quasi-peak detector.

The data of cable loss has been calibrated in full testing frequency range before the testing. A "reference path loss" Corr.(dB) is established and the  $L_{\text{cable}} + \text{ATT} + \text{VDF}$  is the attenuation of "reference path loss", and including the cable loss, the attenuation of the attenuator, the voltage division factor of AMN.

The measurement results are obtained as described below:

$$P_{\text{result}} = P_{\text{mea}} + \text{Corr. (dB)}$$

Sample calculation:  $(50.78 \text{ dB}\mu\text{V}) = (21.18 \text{ dB}\mu\text{V}) + (29.6 \text{ dB})$ , the corresponding frequency is 0.158529MHz.


Limit:

Frequency of Emission(MHz)	Limits(dB $\mu$ V)	
	Quasi-peak	Average
0.15~0.5	66 to 56*	56 to 46*
0.5~5	56	46
5~30	60	50

Note: \* Decreases with the logarithm of the frequency

Test result:


Noise Level of the Measuring Instrument



Pic1. Conducted emission L and N Line



EUT + 1#AE:



Pic2. Conducted emission L&N Line

Frequency (MHz)	QuasiPeak (dBμV)	Average (dBμV)	Limit (dBμV)	Margin (dB)	Line	Corr. (dB)	Pmea QuasiPeak (dBμV)	Pmea Average (dBμV)
0.158529	50.78	---	65.54	14.76	L1	29.6	21.18	---
0.162793	---	35.00	55.32	20.33	L1	29.6	---	5.4
0.520993	41.90	---	56.00	14.10	L1	29.6	12.3	---
0.525257	---	36.40	46.00	9.60	L1	29.6	---	6.8
0.755529	28.38	---	56.00	27.62	L1	29.6	-1.22	---
2.077457	31.26	---	56.00	24.74	L1	29.7	1.56	---
2.120100	---	27.21	46.00	18.79	N	29.7	---	-2.49
2.456979	---	29.43	46.00	16.57	N	29.7	---	-0.27
2.555057	33.83	---	56.00	22.17	L1	29.7	4.13	---
3.544371	29.92	---	56.00	26.08	L1	29.7	0.22	---
5.757536	---	21.06	50.00	28.94	L1	29.7	---	-8.64
19.475743	---	26.05	50.00	23.95	L1	29.8	---	-3.75

## 2.2.2 Radiated Emissions-FCC Part15.109

Ambient condition:

Temperature	Relative humidity	Pressure
24.5°C	39.7%	100.8kPa

Test Setup:




Figure 2

Test Procedure:

EUT+Laptop:

The EUT should be placed on a non-metallic table 80cm above the ground plane. The receive antennas shall be moved from 1 to 4 meters. The distance between EUT and receive antenna should be 3 meters.

The EUT was connected with a laptop via the USB cable and transferred the data. The test set-up and the test methods are performed according to ANSI C63.4:2014. Then start the test software EMC32. Sweep the whole frequency band through the range from 30MHz to 1GHz, using receive log period antenna VULB 9163.

During the test, the height of receive antenna shall be moved from 1 to 4 meters, and the antenna shall be performed under horizontal and vertical polarization. The turn table shall be rotated from 0 to 360 degrees for detecting the maximum of radiated spurious signal level. The measurements shall be repeated with orthogonal polarization of the test antenna. The EUT is laid in two modes as follow:  
1. put the EUT in horizontal direction; 2. put the EUT in vertical direction.

The data of cable loss and antenna factor have been calibrated in full testing frequency range before the testing. All test results are performed with max hold at the horizontal and vertical polarity.

RBW=120kHz, VBW=300kHz, when the test frequency: 30MHz<f<1GHz

RBW=1MHz, VBW=3MHz, when the test frequency: f>1GHz

A “reference path loss” is established and the  $A_{Rpl}$  is the attenuation of “reference path loss”, and including the gain of receive antenna, the gain of the preamplifier, the cable loss.

The measurement results are obtained as described below:

$$\text{Result} = P_{\text{mea}} + A_{Rpl}$$

Limit:

Frequency of Emission(MHz)	Limits	
	Detector	Unit (dB $\mu$ V/m)
30~88	Quasi-peak	40
88~216	Quasi-peak	43.5
216~960	Quasi-peak	46
960~1000	Quasi-peak	54
1000~5th harmonic of the highest frequency or 40GHz, whichever is lower	Average	54
	Peak	74


Test result:

Sample calculation: (8.16 dB  $\mu$  V/m) = (25.86 dB  $\mu$  V) + (-17.7 dB/m), the corresponding frequency is 51.300500MHz.

EUT + 1#AE:


Frequency (MHz)	Result ( dB $\mu$ V/m )	Limit (dB $\mu$ V/m)	ARpl ( dB/m )	Pmea ( dB $\mu$ V )	Polarity
51.300500	8.16	40.00	-17.7	25.86	V
119.987500	21.27	43.50	-21.4	42.67	V
168.002500	20.83	43.50	-21.8	42.63	V
269.998000	14.72	46.00	-16.7	31.42	V
404.773500	28.73	46.00	-12.9	41.63	V
600.000500	28.17	46.00	-8.1	36.27	V

EUT + 1#AE: refer to Pic3, Pic4, Pic5



**Pic3. Radiated emission (30MHz – 1GHz)**


Note: The test data in the graph includes two polarizations: horizontal and vertical



**Pic4. Radiated emission (1GHz –6GHz)**

Note: The test data in the graph includes two polarizations: horizontal and vertical.

Full Spectrum



Comment

### Pic5. Radiated emission (6GHz –18GHz)

Note: The test data in the graph includes two polarizations: horizontal and vertical.

### 2.3. List of test equipments

No.	Name/Model	Manufacturer	S/N	Calibration Due Date	Calibration Date
1	23.18m×16.88m×9.60mS emi-AnechoicChamber	FRANKONIA	-----	2023.11.15	2018.11.16
2	ESW EMI test receiver	R&S	101574	2022.06.19	2021.06.20
3	ESR3 EMI test receiver	R&S	102361	2023.04.11	2022.04.12
4	9.080m×5.255m×3.525m Shielding room	FRANKONIA	-----	2023.09.05	2018.09.06
5	VULB 9163 Ultra log test antenna	schwarzbeck	867	2023.05.28	2021.05.29
6	HF 907 Double-Ridged Waveguide Horn Antenna	R&S	100512	2023.05.12	2021.05.13
7	SAS-574 Horn Antenna	schwarzbeck	535	2023.06.19	2021.06.20
8	ENV216 AMN	R&S	3560.6550. 12	2022.06.19	2021.06.20
9	EMC32EMI test software	R&S	-----	-----	-----

-----The end-----