

Test Report	18070040-FCC-R1
Page	43 of 94

# EGPRS (MCS5):

Cellular Band (Part 22H) result





Test Report	18070040-FCC-R1
Page	44 of 94

PCS Band (Part24E) result





Test Report	18070040-FCC-R1
Page	45 of 94

### RMC

### UMTS-FDD Band V (Part 22H)





Test Report	18070040-FCC-R1
Page	46 of 94





Test Report	18070040-FCC-R1
Page	47 of 94





Test Report	18070040-FCC-R1
Page	48 of 94

### HSUPA:

# UMTS-FDD Band V (Part 22H)





Test Report	18070040-FCC-R1
Page	49 of 94





Test Report	18070040-FCC-R1
Page	50 of 94





Test Report	18070040-FCC-R1
Page	51 of 94

### HSDPA:

# UMTS-FDD Band V (Part 22H)





Test Report	18070040-FCC-R1
Page	52 of 94





Test Report	18070040-FCC-R1
Page	53 of 94





# 6.6 Spurious Radiated Emissions

Temperature	24 °C
Relative Humidity	54%
Atmospheric Pressure	1020mbar
Test date :	January 29, 2018
Tested By :	Aaron Liang

### Requirement(s):

Spec	Item	Requirement	Applicable		
§2.1053, §22.917 & §24.238 § 27.53(h)	a)	The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least 43 + 10 log (P) dB. The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.			
Test setup	EUT& Suppo	Ant. Tower 3m Turn Table Ground Plane Test Receiver	le		
Test Procedure	<ol> <li>The radi</li> <li>The Dur</li> <li>Vari</li> <li>was</li> <li>Rer</li> <li>con</li> <li>of th</li> <li>Sar</li> <li>EUT</li> <li>Fact</li> </ol>	<ol> <li>The transmitter was placed on a wooden turntable, and it was transmitting into a non-radiating load which was also placed on the turntable.</li> <li>The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and polarization as well as EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. The test was performed by placing the EUT on 3-orthogonal axis.</li> <li>Remove the EUT and replace it with substitution antenna. A signal generator was connected to the substitution antenna by a non-radiating cable. The absolute levels of the spurious emissions were measured by the substitution. Sample Calculation:</li> <li>EUT Field Strength = Raw Amplitude (dBµV/m) – Amplifier Gain (dB) + Antenna Factor (dB) + Cable Loss (dB) + Filter Attenuation (dB, if used)</li> </ol>			



 Test Report
 18070040-FCC-R1

 Page
 55 of 94

Remark						
Result	F	Pass	🗖 Fail			
Test Data	▼ Yes		□ <sub>N/A</sub>			
Test Plot	Yes (Se	ee below)	✓ <sub>N/A</sub>			



Test Report	18070040-FCC-R1
Page	56 of 94

# Cellular Band (Part 22H) result

Low channel					
Frequency	Antenna Polarization	Corrected Reading	Limit	Margin	
(MHz)	( <b>H</b> / <b>V</b> )	(dBm)	(dBm)	( <b>dB</b> )	
1648.4	V	-31.39	-13	-18.39	
1648.4	Н	-24.24	-13	-11.24	
764.45	V	-34.75	-13	-21.75	
383.86	Н	-36.55	-13	-23.55	

# Middle channel

Frequency (MHz)	Antenna Polarization (H/V)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
1673.2	V	-32.64	-13	-19.64
1673.2	Н	-28.48	-13	-15.48
244.04	V	-38.54	-13	-25.54
786.85	Н	-37.93	-13	-24.93

# High channel

Frequency (MHz)	Antenna Polarization (H/V)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
1697.6	V	-26.21	-13	-13.21
1697.6	Н	-31.14	-13	-18.14
305.56	V	-40.28	-13	-27.28
239.78	Н	-41.3	-13	-28.3

#### Note:

1, The testing has been conformed to 10\*848.8MHz=8,488MHz

2, All other emissions more than 30 dB below the limit

3,GSM voice, GPRS and EGPRS mode were investigated. The results above show only the worse cases

4, X-Axis, Y-Axis and Z-Axis were investigated. The results above show only the worst case.



Test Report	18070040-FCC-R1
Page	57 of 94

# PCS Band (Part24E) result

### Low channel

Frequency (MHz)	Antenna Polarization (H/V)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
3700.4	V	-37.79	-13	-24.79
3700.4	Н	-31.86	-13	-18.86
660.88	V	-38.28	-13	-25.28
226.72	Н	-43.3	-13	-30.3

### Middle channel

Frequency	Antenna Polarization	Corrected Reading	Limit	Margin
(MHZ)	$(\mathbf{H}/\mathbf{V})$	(abm)	(abm)	( <b>aB</b> )
3760	V	-32.54	-13	-19.54
3760	Н	-36.32	-13	-23.32
501.45	V	-39.86	-13	-26.86
834.14	Н	-41.54	-13	-28.54

### High channel

Frequency (MHz)	Antenna Polarization (H/V)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
3819.6	V	-31.51	-13	-18.51
3819.6	Н	-37.81	-13	-24.81
330.16	V	-38.71	-13	-25.71
425.81	Н	-38.77	-13	-25.77

#### Note:

1, The testing has been conformed to 10\*1909.8MHz=19,098MHz

2, All other emissions more than 30 dB below the limit

3, GPRS and EGPRS mode were investigated. The results above show only the worse cases

4, X-Axis, Y-Axis and Z-Axis were investigated. The results above show only the worst case.

5, The radiated spurious test above 18GHz is subcontracted to SIEMIC (Nanjing-China) Laboratories. and found 30dB below the li mit at least.



 Test Report
 18070040-FCC-R1

 Page
 58 of 94

# UMTS-FDD Band V (Part 22H)

### Low channel

Frequency (MHz)	Antenna Polarization (H/V)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
1652.8	V	-29.09	-13	-16.09
1652.8	Н	-34.13	-13	-21.13
483.4	V	-33.99	-13	-20.99
568.91	Н	-37.72	-13	-24.72

### Middle channel

Frequency (MHz)	Antenna Polarization (H/V)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
1670	V	-35.73	-13	-22.73
1670	Н	-28.96	-13	-15.96
497.37	V	-34.35	-13	-21.35
518.88	Н	-35.19	-13	-22.19

### High channel

Frequency (MHz)	Antenna Polarization (H/V)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
1693.2	V	-34.47	-13	-21.47
1693.2	Н	-35.43	-13	-22.43
246.42	V	-38.23	-13	-25.23
211.08	Н	-34.57	-13	-21.57

#### Note:

1, The testing has been conformed to 10\*846.6MHz=8,466MHz

2, All other emissions more than 30 dB below the limit

3,RMC, HSUPA and HSDPA mode were investigated. The results above show only the worse cases

4, X-Axis, Y-Axis and Z-Axis were investigated. The results above show only the worst case.



 Test Report
 18070040-FCC-R1

 Page
 59 of 94

# UMTS-FDD Band II (Part 24E)

### Low channel

Frequency (MHz)	Antenna Polarization (H/V)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
3704.8	V	-32.47	-13	-19.47
3704.8	Н	-32.89	-13	-19.89
714.88	V	-35.38	-13	-22.38
224.67	Н	-38.04	-13	-25.04

### Middle channel

Frequency	Antenna Polarization	Corrected Reading	Limit	Margin
(MHZ)	$(\mathbf{H}/\mathbf{V})$	(dBm)	(dBm)	( <b>dB</b> )
3760	V	-35.08	-13	-22.08
3760	Н	-30.79	-13	-17.79
452.91	V	-39.35	-13	-26.35
765.67	Н	-41.84	-13	-28.84

### High channel

Frequency (MHz)	Antenna Polarization (H/V)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
3815.2	V	-37.94	-13	-24.94
3815.2	Н	-39.02	-13	-26.02
678.16	V	-34.21	-13	-21.21
780.99	Н	-38.23	-13	-25.23

#### Note:

1, The testing has been conformed to 10\*1907.6MHz=19,076MHz

2, All other emissions more than 30 dB below the limit

3,RMC, HSUPA and HSDPA mode were investigated. The results above show only the worse cases

4, X-Axis, Y-Axis and Z-Axis were investigated. The results above show only the worst case

5, The radiated spurious test above 18GHz is subcontracted to SIEMIC (Nanjing-China) Laboratories. and found 30dB below the limit at least.



Test Report	18070040-FCC-R1
Page	60 of 94

#### Low channel

Frequency (MHz)	Antenna Polarization (H/V)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
3424.8	V	-25.24	-13	-12.24
3424.8	Н	-26.86	-13	-13.86
822.71	V	-34.6	-13	-21.6
563.98	Н	-40.11	-13	-27.11

### Middle channel

Frequency	Antenna Polarization	Corrected Reading	Limit	Margin
(MHz)	(H/V)	(dBm)	(dBm)	( <b>dB</b> )
3480	V	-31.9	-13	-18.9
3480	Н	-32.57	-13	-19.57
590.24	V	-33.11	-13	-20.11
369.36	Н	-34.29	-13	-21.29

### High channel

Frequency	Antenna Polarization	Corrected Reading	Limit	Margin
(MHz)	(H/V)	(dBm)	(dBm)	( <b>dB</b> )
3505.2	V	-28.92	-13	-15.92
3505.2	Н	-32.63	-13	-19.63
489.51	V	-36.3	-13	-23.3
271.16	Н	-32.88	-13	-19.88

#### Note:

1, The testing has been conformed to 10\*1752.6MHz=17,526MHz

2, All other emissions more than 30 dB below the limit

3,RMC, HSUPA and HSDPA mode were investigated. The results above show only the worse cases.

4, X-Axis, Y-Axis and Z-Axis were investigated. The results above show only the worst case.