



# RF TEST REPORT

**Applicant** ZTE Corporation  
**FCC ID** SRQ-R218Z  
**Product** Vodafone Mobile WiFi  
**Model** R218z  
**Report No.** RXA1712-0417RF01R2  
**Issue Date** February 6, 2018

TA Technology (Shanghai) Co., Ltd. tested the above equipment in accordance with the requirements in **FCC CFR47 Part 2 (2017)/ FCC CFR 47 Part 22H (2017)**. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

*Jiang peng Lan*

*Performed by: Jiangpeng Lan*

*Kai Xu*

*Approved by: Kai Xu*

---

## TA Technology (Shanghai) Co., Ltd.

No.145, Jintang Rd, Tangzhen Industry Park, Pudong Shanghai, China

TEL: +86-021-50791141/2/3

FAX: +86-021-50791141/2/3-8000



## TABLE OF CONTENT

1. Test Laboratory .....	4
1.1. Notes of the Test Report .....	4
1.2. Test facility .....	4
1.3. Testing Location .....	5
2. General Description of Equipment under Test .....	6
3. Applied Standards .....	7
4. Test Configuration .....	8
5. Test Case Results .....	9
5.1. RF Power Output .....	9
5.2. Effective Radiated Power .....	11
5.3. Occupied Bandwidth .....	14
5.4. Band Edge Compliance .....	18
5.5. Peak-to-Average Power Ratio (PAPR) .....	20
5.6. Frequency Stability .....	22
5.7. Spurious Emissions at Antenna Terminals .....	24
5.8. Radiates Spurious Emission .....	26
6. Main Test Instruments .....	31

### Summary of measurement results

No.	Test Type	Clause in FCC rules	Verdict
1	RF power output	2.1046	PASS
2	Effective Radiated Power	22.913(a)(2)	PASS
3	Occupied Bandwidth	2.1049	PASS
4	Band Edge Compliance	2.1051 / 22.917(a)	PASS
5	Peak-to-Average Power Ratio	22.913(d)/ KDB 971168 D01(5.7)	PASS
6	Frequency Stability	2.1055 / 22.355	PASS
7	Spurious Emissions at Antenna Terminals	2.1051 / 22.917(a)	PASS
8	Radiates Spurious Emission	2.1053 / 22.917 (a)	PASS
Date of Testing: December 17, 2017~ January 20, 2018			
Note: PASS: The EUT complies with the essential requirements in the standard. FAIL: The EUT does not comply with the essential requirements in the standard.			



## 1. Test Laboratory

### 1.1. Notes of the Test Report

This report shall not be reproduced in full or partial, without the written approval of **TA technology (shanghai) co., Ltd.** The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein .Measurement Uncertainties were not taken into account and are published for informational purposes only. This report is written to support regulatory compliance of the applicable standards stated above.

### 1.2. Test facility

#### **CNAS (accreditation number: L2264)**

TA Technology (Shanghai) Co., Ltd. has obtained the accreditation of China National Accreditation Service for Conformity Assessment (CNAS).

#### **FCC (Designation number: CN1179, Test Firm Registration Number: 446626)**

TA Technology (Shanghai) Co., Ltd. has been listed on the US Federal Communications Commission list of test facilities recognized to perform electromagnetic emissions measurements.

#### **IC (recognition number is 8510A)**

TA Technology (Shanghai) Co., Ltd. has been listed by industry Canada to perform electromagnetic emission measurement.

#### **VCCI (recognition number is C-4595, T-2154, R-4113, G-10766)**

TA Technology (Shanghai) Co., Ltd. has been listed by industry Japan to perform electromagnetic emission measurement.

#### **A2LA (Certificate Number: 3857.01)**

TA Technology (Shanghai) Co., Ltd. has been listed by American Association for Laboratory Accreditation to perform electromagnetic emission measurement.



### 1.3. Testing Location

Company: TA Technology (Shanghai) Co., Ltd.  
Address: No.145, Jintang Rd, Tangzhen Industry Park, Pudong  
City: Shanghai  
Post code: 201201  
Country: P. R. China  
Contact: Xu Kai  
Telephone: +86-021-50791141/2/3  
Fax: +86-021-50791141/2/3-8000  
Website: <http://www.ta-shanghai.com>  
E-mail: [xukai@ta-shanghai.com](mailto:xukai@ta-shanghai.com)

## 2. General Description of Equipment under Test

### Client Information

Applicant	ZTE Corporation
Applicant address	ZTE Plaza, Keji Road South, Hi-Tech, Industrial Park, Nanshan District, Shenzhen, Guangdong, 518057, P.R.China
Manufacturer	ZTE Corporation
Manufacturer address	ZTE Plaza, Keji Road South, Hi-Tech, Industrial Park, Nanshan District, Shenzhen, Guangdong, 518057, P.R.China

### General Information

EUT Description			
Device Type:	Portable Device		
Model	R218z		
IMEI	355063090001842		
Hardware Version	Ver.A(T1)		
Software Version	BD_R218zV1.0		
Power Supply	Battery/AC adapter		
Antenna Type	Internal Antenna		
Test Mode(s)	GSM 850: WCDMA Band V;		
Test Modulation	(GSM)GMSK,8PSK; (WCDMA)QPSK;		
GPRS Multislot Class	10		
EGPRS Multislot Class	12		
HSDPA UE Category	24		
HSUPA UE Category	6		
Maximum E.R.P.	GSM 850:	31.65dBm	
	WCDMA Band V:	22.59dBm	
Rated Power Supply Voltage	3.8V		
Extreme Voltage	Minimum: 3.5V    Maximum: 4.2V		
Extreme Temperature	Lowest: -30°C    Highest: +55°C		
Operating Frequency Range(s)	Band	Tx (MHz)	Rx (MHz)
	GSM850	824 ~ 849	869 ~ 894
	WCDMA Band V	824 ~ 849	869 ~ 894
EUT Accessory			
Battery	Manufacturer: Harbin Coslight Power Co., Ltd. Model: Li3820T43P3h715345		
Note: The information of the EUT is declared by the manufacturer.			



### **3. Applied Standards**

According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

**FCC CFR47 Part 2 (2017)**

**FCC CFR 47 Part 22H (2017)**

**ANSI/TIA-603-E (2016)**

**KDB 971168 D01 Power Meas License Digital Systems v03**

## 4. Test Configuration

Radiated measurements are performed by rotating the EUT in three different orthogonal test planes. EUT stand-up position (Z axis), lie-down position (X, Y axis). Receiver antenna polarization (horizontal and vertical), the worst emission was found in position (X axis, horizontal polarization) and the worst case was recorded.

All mode and data rates and positions were investigated. Subsequently, only the worst case emissions are reported.

The following testing in GSM/WCDMA is set based on the maximum RF Output Power.

Test modes are chosen to be reported as the worst case configuration below:

	Test items	Modes/Modulation	
		GSM 850	WCDMA Band V
Conducted Test cases	RF power output	GPRS EGPRS	RMC HSDPA/HSUPA DC-HSDPA
	Occupied Bandwidth	GPRS(1Tx slot) EGPRS(1Tx slot)	RMC
	Band Edge Compliance	GPRS(1Tx slot) EGPRS(1Tx slot)	RMC
	Peak-to-Average Power Ratio	GPRS(1Tx slot) EGPRS(1Tx slot)	RMC
	Frequency Stability	GPRS(1Tx slot) EGPRS(1Tx slot)	RMC
	Spurious Emissions at Antenna Terminals	GPRS	RMC
Radiated Test cases	Effective Radiated Power	GPRS(1Tx slot) EGPRS(1Tx slot)	RMC
	Radiates Spurious Emission	GPRS	RMC



## 5. Test Case Results

### 5.1. RF Power Output


#### Ambient condition

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

#### Methods of Measurement

During the process of the testing, The EUT is controlled by the Base Station Simulator to ensure max power transmission and proper modulation.

#### Test Setup



The loss between RF output port of the EUT and the input port of the tester has been taken into consideration.

#### Limits

No specific RF power output requirements in part 2.1046.

#### Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor  $k = 2$ ,  $U = 0.4$  dB.

**Test Results**

GSM 850		Conducted Power(dBm)		
		Channel 128	Channel 190	Channel 251
		824.2 (MHz)	836.6 (MHz)	848.8 (MHz)
GPRS (GMSK)	1TXslot	31.65	31.64	31.58
	2TXslots	29.87	29.91	29.87
EGPRS (GMSK)	1TXslot	31.48	31.53	31.47
	2TXslots	29.93	30.02	29.86
	3TXslots	27.80	27.75	27.91
	4TXslots	26.55	26.52	26.56
EGPRS (8PSK)	1TXslot	26.13	26.08	25.89
	2TXslots	24.14	24.03	23.96
	3TXslots	21.88	21.73	21.97
	4TXslots	20.67	20.68	20.70

WCDMA Band V		Conducted Power(dBm)		
		Channel 4132	Channel 4183	Channel 4233
		826.4(MHz)	836.6(MHz)	846.6(MHz)
<b>RMC</b>		22.47	22.56	22.59
<b>HSDPA</b>	Sub - Test 1	21.56	21.45	21.80
	Sub - Test 2	21.57	21.43	21.75
	Sub - Test 3	21.08	20.91	20.94
	Sub - Test 4	21.10	20.90	21.02
<b>HSUPA</b>	Sub - Test 1	21.58	21.36	21.76
	Sub - Test 2	21.07	20.94	21.11
	Sub - Test 3	21.64	21.42	21.80
	Sub - Test 4	21.60	21.41	21.82
	Sub - Test 5	21.57	21.40	21.79
<b>DC-HSDPA</b>	Sub - Test 1	21.55	21.43	21.79
	Sub - Test 2	21.55	21.40	21.70
	Sub - Test 3	21.06	20.90	20.92
	Sub - Test 4	21.06	20.87	21.00

## 5.2. Effective Radiated Power

### Ambient condition


Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

### Methods of Measurement

The testing follows FCC KDB 971168 v03 Section 5.8 and ANSI/TIA-603-E (2016).

- a) Connect the equipment as illustrated. Mount the equipment with the manufacturer specified antenna in a vertical orientation on a manufacturer specified mounting surface located on a non-conducting rotating platform of a RF anechoic chamber (preferred) or a standard radiation site.
- b) Key the transmitter, then rotate the EUT 360° azimuthally and record spectrum analyzer power level (LVL) measurements at angular increments that are sufficiently small to permit resolution of all peaks. If a standard radiation test site is used, raise and lower the test antenna to obtain a maximum reading at each angular increment. (Note: several batteries may be needed to offset the effect of battery voltage droop, which should not exceed 5% of the manufactured specified battery voltage during transmission).
- c) Replace the transmitter under test with a vertically polarized half-wave dipole (or an antenna whose gain is known relative to an ideal half-wave dipole). The center of the antenna should be at the same location as the center of the antenna under test.
- d) Connect the antenna to a signal generator with a known output power and record the path loss (in dB) as LOSS. If a standard radiation test site is used, raise and lower the test antenna to obtain a maximum reading.  $LOSS = \text{Generator Output Power (dBm)} - \text{Analyzer reading (dBm)}$
- e) Determine the effective radiated output power at each angular position from the readings in steps b) and d) using the following equation:  $ERP \text{ (dBm)} = \text{LVL (dBm)} + \text{LOSS (dB)}$
- f) The maximum ERP is the maximum value determined in the preceding step.
- g) When calculating ERP, in addition to knowing the antenna radiation and matching characteristics, it is necessary to know the loss values of all elements (e.g. transmission line attenuation, mismatches, filters, combiners) interposed between the point where transmitter output power is measured, and the point where power is applied to the antenna. ERP can then be calculated as follows:  
 $ERP \text{ (dBm)} = \text{Output Power (dBm)} - \text{Losses (dB)} + \text{Antenna Gain (dBd)}$   
where: dBd refers to gain relative to an ideal dipole.  
 $EIRP \text{ (dBm)} = ERP \text{ (dBm)} + 2.15 \text{ (dB.)}$

**Test setup**



**Limits**

Rule Part 22.913(a) specifies that "Mobile/portable stations are limited to 7 watts ERP".

Limit	$\leq 7 \text{ W}$ (38.45 dBm)
-------	--------------------------------

**Measurement Uncertainty**

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor  $k = 2$ ,  $U = 1.19 \text{ dB}$

**Test Results:**

The measurement is performed for both of horizontal and vertical antenna Polarization, and only the data of worst mode is recorded in this report.

Mode	Channel	Frequency (MHz)	Polarization	Output Power (dBm)	Losses (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Conclusion
GPRS 850	Low	824.2	Horizontal	-15.63	-45.53	1.06	30.96	38.45	Pass
	Mid	836.6	Horizontal	-15.28	-45.38	1.24	31.34	38.45	Pass
	High	848.8	Horizontal	-14.98	-45.37	1.38	31.77	38.45	Pass
EGPRS 850	Low	824.2	Horizontal	-18.58	-45.53	1.06	28.01	38.45	Pass
	Mid	836.6	Horizontal	-18.23	-45.38	1.24	28.39	38.45	Pass
	High	848.8	Horizontal	-18.06	-45.37	1.38	28.69	38.45	Pass
WCDMA Band V	Low	826.4	Horizontal	-24.69	-45.44	1.13	21.88	38.45	Pass
	Mid	836.6	Horizontal	-24.70	-45.38	1.24	21.92	38.45	Pass
	High	846.6	Horizontal	-24.80	-45.38	1.35	21.93	38.45	Pass

### 5.3. Occupied Bandwidth

#### Ambient condition

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

#### Method of Measurement


The EUT was connected to Spectrum Analyzer and Base Station Simulator via power Splitter. The occupied bandwidth is measured using spectrum analyzer.

RBW is set to 3kHz, VBW is set to 10kHz for GSM 850,

RBW is set to 51kHz, VBW is set to 160kHz for WCDMA Band V,

99% power and -26dBc occupied bandwidths are recorded. Spectrum analyzer plots are included on the following pages.

#### Test Setup



#### Limits


No specific occupied bandwidth requirements in part 2.1049.

#### Measurement Uncertainty


The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor  $k = 2$ ,  $U = 624\text{Hz}$ .

**Test Result**

Mode	Channel	Frequency (MHz)	99% Power Bandwidth (MHz)	-26dBc Bandwidth(MHz)
<b>GPRS 850 (GMSK)</b>	128	824.2	0.24486	0.3157
	190	836.6	0.24568	0.3128
	251	848.8	0.24423	0.3129
<b>EGPRS 850 (8-PSK)</b>	128	824.2	0.24475	0.3092
	190	836.6	0.24413	0.3091
	251	848.8	0.24651	0.3069
<b>WCDMA Band V (RMC)</b>	4132	826.4	4.1111	4.681
	4183	836.6	4.1249	4.691
	4233	846.6	4.1250	4.690







### 5.4. Band Edge Compliance

#### Ambient condition

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

#### Method of Measurement


The EUT was connected to Spectrum Analyzer and Base Station Simulator via power Splitter. The band edge of the lowest and highest channels were measured. The average detector is used.

RBW is set to 3kHz,VBW is set to 10kHz for GSM 850,

RBW is set to 51kHz,VBW is set to 160kHz for WCDMA Band V,

Spectrum analyzer plots are included on the following pages.

#### Test Setup



#### Limits

Rule Part 22.917(a) specifies that “The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least 43 + 10 log(P) dB.”

Limit	-13 dBm
-------	---------

#### Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor  $k = 1.96$ ,  $U=0.684$ dB.

Test Result:

GSM 850 GPRS CH-Low




GSM 850 GPRS CH-High




GSM 850 EGPRS CH-Low



GSM 850 EGPRS CH-High



WCDMA Band V CH-Low



WCDMA Band V CH-High



### 5.5. Peak-to-Average Power Ratio (PAPR)

#### Ambient condition


Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

#### Methods of Measurement

Measure the total peak power and record as  $P_{Pk}$ . And measure the total average power and record as  $P_{Avg}$ . Both the peak and average power levels must be expressed in the same logarithmic units (e.g., dBm). Determine the PAPR from:

$$PAPR (dB) = P_{Pk} (dBm) - P_{Avg} (dBm).$$

#### Test Setup



#### Limits

According to the Sec. 22.913(d), The peak-to-average ratio (PAR) of the transmission must not exceed 13 dB.

#### Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor  $k = 2$ ,  $U = 0.4$  dB.

**Test Results**

Mode	Channel	Frequency (MHz)	Peak (dBm)	Avg (dBm)	PAPR (dB)	Limit (dB)	Conclusion
<b>GPRS 850 (GMSK)</b>	128	824.2	30.89	29.87	1.02	≤13	PASS
	190	836.6	30.96	29.91	1.05	≤13	PASS
	251	848.8	30.88	29.87	1.01	≤13	PASS
<b>EGPRS 850 (8-PSK)</b>	128	824.2	21.73	20.67	1.06	≤13	PASS
	190	836.6	21.76	20.68	1.08	≤13	PASS
	251	848.8	21.82	20.70	1.12	≤13	PASS
<b>WCDMA Band V (RMC)</b>	4132	826.4	25.50	22.47	3.03	≤13	PASS
	4183	836.6	25.59	22.56	3.03	≤13	PASS
	4233	846.6	25.64	22.59	3.05	≤13	PASS

## 5.6. Frequency Stability

### Ambient condition

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

### Method of Measurement

#### 1. Frequency Stability (Temperature Variation)

The temperature inside the climate chamber is varied from -30°C to +55°C in 10°C step size,

(1) With all power removed, the temperature was decreased to 0°C and permitted to stabilize for three hours.

(2) Measure the carrier frequency with the test equipment in a “call mode”. These measurements should be made within 1 minute of powering up the mobile station, to prevent significant self warming.

(3) Repeat the above measurements at 10°C increments from -30°C to +55°C. Allow at least 1.5 hours at each temperature, un-powered, before making measurements. Frequency Stability (Voltage Variation)


The frequency stability shall be measured with variation of primary supply voltage as follows:

(1) Vary primary supply voltage from 85 to 115 percent of the nominal value for other than hand carried battery equipment.

(2) For hand carried, battery powered equipment, reduce primary supply voltage to the battery-operating end point which shall be specified by the manufacturer.

This transceiver is specified to operate with an input voltage of between 3.5 V and 4.2 V, with a nominal voltage of 3.8V.

### Test setup



**Limits**

According to the Sec. 22.355, the frequency stability of the carrier shall be accurate to within 2.5 ppm of the received frequency for mobile stations.

Limits	≤ 2.5 ppm
--------	-----------

**Measurement Uncertainty**

The assessed measurement uncertainty to ensure 99.75% confidence level for the normal distribution is with the coverage factor  $k = 3$ ,  $U = 0.01\text{ppm}$ .

**Test Result**

Mode	Test status	Test Results (ppm)		Limit (ppm)	Conclusion
		GPRS (GMSK)	EGPRS (8PSK)		
GSM 850 Middle Channel	-30°C/Normal Voltage	0.03092	0.01023	2.5	PASS
	-20°C/Normal Voltage	0.01828	0.01096	2.5	PASS
	-10°C/Normal Voltage	0.01224	0.00409	2.5	PASS
	0°C/Normal Voltage	0.01936	0.00641	2.5	PASS
	10°C/Normal Voltage	0.01554	0.00506	2.5	PASS
	20°C/Normal Voltage	0.02878	0.00304	2.5	PASS
	30°C/Normal Voltage	0.01144	0.00556	2.5	PASS
	40°C/Normal Voltage	0.01438	0.01044	2.5	PASS
	50°C/Normal Voltage	0.01104	0.00894	2.5	PASS
	55°C/Normal Voltage	0.02082	0.01237	2.5	PASS
	20°C/Minimum Voltage	0.01972	0.00544	2.5	PASS
	20°C/Maximum Voltage	0.01471	0.00300	2.5	PASS
/	/	<b>RMC</b>		/	/
WCDMA Band V Middle Channel	-30°C/Normal Voltage	-0.00050		2.5	PASS
	-20°C/Normal Voltage	0.00082		2.5	PASS
	-10°C/Normal Voltage	0.00043		2.5	PASS
	0°C/Normal Voltage	0.00149		2.5	PASS
	10°C/Normal Voltage	-0.00057		2.5	PASS
	20°C/Normal Voltage	-0.00047		2.5	PASS
	30°C/Normal Voltage	-0.00007		2.5	PASS
	40°C/Normal Voltage	-0.00026		2.5	PASS
	50°C/Normal Voltage	-0.00084		2.5	PASS
	55°C/Normal Voltage	-0.00226		2.5	PASS
	20°C/Minimum Voltage	0.00176		2.5	PASS
	20°C/Maximum Voltage	-0.00011		2.5	PASS

### 5.7. Spurious Emissions at Antenna Terminals


#### Ambient condition

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

#### Method of Measurement

The EUT was connected to Spectrum Analyzer and Base Station Simulator via power Splitter. The measurement is carried out using a spectrum analyzer. The spectrum analyzer scans from 9kHz to the 10th harmonic of the carrier. The peak detector is used. RBW are set to 100 kHz and VBW are set to 300 kHz for below 1G, RBW are set to 1MHz and VBW are set to 3MHz for above 1G, Sweep is set to ATUO.

#### Test setup



#### Limits

Rule Part 22.917(a) specifies that “The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least 43 + 10 log (P) dB.”

Limit	-13 dBm
-------	---------

#### Measurement Uncertainty

The assessed measurement uncertainty to ensure 99.75% confidence level for the normal distribution is with the coverage factor  $k = 1.96$ .

Frequency	Uncertainty
100kHz-2GHz	0.684 dB
2GHz-18GHz	1.407 dB




**Test Result**

Sweep from 9 kHz to 30MHz, and the emissions more than 20 dB below the permissible value are not reported.

If disturbances were found more than 20dB below limit line, the mark is not required for the EUT.

The signal beyond the limit is carrier.



## 5.8. Radiates Spurious Emission

### Ambient condition


Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

### Method of Measurement


1. The testing follows FCC KDB 971168 v03 Section 5.8 and ANSI/TIA-603-E (2016).
2. The EUT is placed on a turntable 0.8 meters above the ground in the chamber, 3 meter away from the antenna. The maximal emission value is acquired by adjusting the antenna height, polarisation and turntable azimuth. Normally, the height range of antenna is 1 m to 4 m, the azimuth range of turntable is 0° to 360°, and the receive antenna has two polarizations Vertical (V) and Horizontal (H).
3. A log-periodic antenna or double-ridged waveguide horn antenna shall be substituted in place of the EUT. The log-periodic antenna will be driven by a signal generator and the level will be adjusted till the same power value on the spectrum analyzer or receiver. The level of the spurious emissions can be calculated through the level of the signal generator, cable loss, the gain of the substitution antenna and the reading of the spectrum analyzer or receiver.
4. The EUT is then put into continuously transmitting mode at its maximum power level during the test. Set Test Receiver or Spectrum RBW=1MHz, VBW=3MHz for above 1GHz and RBW=100kHz, VBW=300kHz for 30MHz to 1GHz, And the maximum value of the receiver should be recorded as (Pr).
5. The EUT shall be replaced by a substitution antenna. In the chamber, an substitution antenna for the frequency band of interest is placed at the reference point of the chamber. An RF Signal source for the frequency band of interest is connected to the substitution antenna with a cable that has been constructed to not interfere with the radiation pattern of the antenna. A power (PMea) is applied to the input of the substitution antenna, and adjust the level of the signal generator output until the value of the receiver reach the previously recorded (Pr). The power of signal source (PMea) is recorded. The test should be performed by rotating the test item and adjusting the receiving antenna polarization.
6. A amplifier should be connected to the Signal Source output port. And the cable should be connect between the Amplifier and the Substitution Antenna. The cable loss (Pcl), the Substitution Antenna Gain (Ga) and the Amplifier Gain (PAg) should be recorded after test.
7. The measurement results are obtained as described below:  
Power(EIRP)=PMea- PAg - Pcl + Ga  
The measurement results are amend as described below:  
Power(EIRP)=PMea- Pcl + Ga
8. This value is EIRP since the measurement is calibrated using an antenna of known gain (2.15 dBi) and known input power. ERP can be calculated from EIRP by subtracting the gain of the dipole, ERP = EIRP-2.15dBi.

**Test setup**

**30MHz~~~ 1GHz**



**Above 1GHz**



Note: Area side:2.4mX3.6m

**Limits**

Rule Part 22.917(a) specifies that “The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least  $43 + 10 \log (P)$  dB.”

Limit	-13 dBm
-------	---------

**Measurement Uncertainty**

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor  $k = 1.96$ ,  $U = 3.55$  dB.

**Test Result**

## GSM 850 CH-Low

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	ERP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	1648.4	-52.50	2	10.15	Horizontal	-46.50	-13.00	33.50	45
3	2472.6	-55.19	2.51	11.35	Horizontal	-48.50	-13.00	35.50	90
4	3296.8	-54.30	4.2	10.85	Horizontal	-49.80	-13.00	36.80	270
5	4121.0	-50.90	5.2	11.35	Horizontal	-46.90	-13.00	33.90	180
6	4945.2	-50.50	5.5	11.95	Horizontal	-46.20	-13.00	33.20	270
7	5769.4	-50.70	5.7	13.55	Horizontal	-45.00	-13.00	32.00	135
8	6593.6	-50.00	6.3	13.75	Horizontal	-44.70	-13.00	31.70	45
9	7417.8	-48.00	6.8	13.85	Horizontal	-43.10	-13.00	30.10	180
10	8242.0	-48.00	6.9	14.25	Horizontal	-42.80	-13.00	29.80	270

Note: 1.The other Spurious RF Radiated emissions level is no more than noise floor.  
2.The worst emission was found in the antenna is Horizontal position.

## GSM 850 CH-Middle

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	ERP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	1673.2	-52.10	2	10.75	Horizontal	-45.50	-13.00	32.50	180
3	2509.8	-54.99	2.51	11.05	Horizontal	-48.60	-13.00	35.60	270
4	3346.4	-54.20	4.2	11.15	Horizontal	-49.40	-13.00	36.40	135
5	4183.0	-51.00	5.2	11.15	Horizontal	-47.20	-13.00	34.20	45
6	5019.6	-49.40	5.5	11.95	Horizontal	-45.10	-13.00	32.10	270
7	5856.2	-50.40	5.7	13.55	Horizontal	-44.70	-13.00	31.70	180
8	6692.8	-48.40	6.3	13.75	Horizontal	-43.10	-13.00	30.10	270
9	7529.4	-45.50	6.8	13.85	Horizontal	-40.60	-13.00	27.60	135
10	8366.0	-47.30	6.9	14.25	Horizontal	-42.10	-13.00	29.10	45

Note: 1.The other Spurious RF Radiated emissions level is no more than noise floor.  
2.The worst emission was found in the antenna is Horizontal position.



## GSM 850 CH-High

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	ERP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	1697.6	-51.60	2	10.15	Horizontal	-45.60	-13.00	32.60	225
3	2546.4	-53.69	2.51	11.05	Horizontal	-47.30	-13.00	34.30	135
4	3395.2	-53.90	4.2	11.15	Horizontal	-49.10	-13.00	36.10	180
5	4244.0	-50.70	5.2	11.15	Horizontal	-46.90	-13.00	33.90	270
6	5092.8	-49.90	5.5	11.95	Horizontal	-45.60	-13.00	32.60	135
7	5941.6	-49.90	5.7	13.55	Horizontal	-44.20	-13.00	31.20	45
8	6790.4	-48.20	6.3	13.75	Horizontal	-42.90	-13.00	29.90	270
9	7639.2	-46.50	6.8	13.85	Horizontal	-41.60	-13.00	28.60	180
10	8488.0	-45.70	6.9	14.25	Horizontal	-40.50	-13.00	27.50	270

Note: 1.The other Spurious RF Radiated emissions level is no more than noise floor.

2.The worst emission was found in the antenna is Horizontal position.

## WCDMA Band V CH-Low

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	ERP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	1651.1	-58.30	2	10.15	Horizontal	-52.30	-13.00	39.30	180
3	2479.2	-57.39	2.51	11.35	Horizontal	-50.70	-13.00	37.70	90
4	3305.6	-52.00	4.2	10.85	Horizontal	-47.50	-13.00	34.50	180
5	4132.0	-50.80	5.2	11.35	Horizontal	-46.80	-13.00	33.80	270
6	4958.4	-50.50	5.5	11.95	Horizontal	-46.20	-13.00	33.20	135
7	5784.8	-51.40	5.7	13.55	Horizontal	-45.70	-13.00	32.70	45
8	6611.2	-48.80	6.3	13.75	Horizontal	-43.50	-13.00	30.50	270
9	7437.6	-47.70	6.8	13.85	Horizontal	-42.80	-13.00	29.80	180
10	8264.0	-46.80	6.9	14.25	Horizontal	-41.60	-13.00	28.60	270

Note: 1.The other Spurious RF Radiated emissions level is no more than noise floor.

2.The worst emission was found in the antenna is Horizontal position.



## WCDMA Band V CH-Middle

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	ERP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	1670.8	-58.10	2	10.75	Horizontal	-51.50	-13.00	38.50	135
3	2509.8	-56.99	2.51	11.05	Horizontal	-50.60	-13.00	37.60	270
4	3346.4	-52.70	4.2	11.15	Horizontal	-47.90	-13.00	34.90	135
5	4183.0	-51.30	5.2	11.15	Horizontal	-47.50	-13.00	34.50	180
6	5019.6	-49.50	5.5	11.95	Horizontal	-45.20	-13.00	32.20	270
7	5856.2	-50.50	5.7	13.55	Horizontal	-44.80	-13.00	31.80	135
8	6692.8	-48.40	6.3	13.75	Horizontal	-43.10	-13.00	30.10	45
9	7529.4	-47.20	6.8	13.85	Horizontal	-42.30	-13.00	29.30	270
10	8366.0	-46.90	6.9	14.25	Horizontal	-41.70	-13.00	28.70	180

Note: 1.The other Spurious RF Radiated emissions level is no more than noise floor.  
2.The worst emission was found in the antenna is Horizontal position.

## WCDMA Band V CH-High

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	ERP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	1693.2	-58.50	2	10.15	Horizontal	-52.50	-13.00	39.50	225
3	2539.8	-57.19	2.51	11.05	Horizontal	-50.80	-13.00	37.80	45
4	3386.4	-52.40	4.2	11.15	Horizontal	-47.60	-13.00	34.60	270
5	4233.0	-51.60	5.2	11.15	Horizontal	-47.80	-13.00	34.80	135
6	5079.6	-48.90	5.5	11.95	Horizontal	-44.60	-13.00	31.60	90
7	5926.2	-49.80	5.7	13.55	Horizontal	-44.10	-13.00	31.10	225
8	6772.8	-48.10	6.3	13.75	Horizontal	-42.80	-13.00	29.80	90
9	7619.4	-46.50	6.8	13.85	Horizontal	-41.60	-13.00	28.60	135
10	8466.0	-46.70	6.9	14.25	Horizontal	-41.50	-13.00	28.50	225

Note: 1.The other Spurious RF Radiated emissions level is no more than noise floor.  
2.The worst emission was found in the antenna is Horizontal position.

## 6. Main Test Instruments

Name	Manufacturer	Type	Serial Number	Calibration Date	Expiration Date
Power Splitter	Hua Xiang	SHX-GF2-2-13	10120101	2017-05-14	2018-05-13
Spectrum Analyzer	Agilent	N9010A	MY47191109	2017-05-20	2018-05-19
Universal Radio Communication Tester	Agilent	E5515C	MY48367192	2017-05-20	2018-05-19
Signal Analyzer	R&S	FSV30	100815	2017-12-17	2018-12-16
EMI Test Receiver	R&S	ESCI	100948	2017-05-20	2018-05-19
Signal generator	R&S	SMB 100A	102594	2017-05-14	2018-05-13
Signal generator	R&S	SMR27	100365	2017-05-14	2018-05-13
Trilog Antenna	SCHWARZBECK	VUBL 9163	9163-201	2017-11-18	2020-11-17
Horn Antenna	R&S	HF907	100126	2014-12-06	2019-12-05
Horn Antenna	ETS-Lindgren	3160-09	00102644	2015-01-30	2018-01-29
Climatic Chamber	Re Ce	PT-30B	20101891	2015-07-18	2018-07-17
RF Cable	Agilent	SMA 15cm	0001	2017-08-04	2018-02-03
Preampfier	R&S	SCU18	102327	2017-06-18	2018-06-17
Software	R&S	EMC32	V 8.52.0	NA	NA

\*\*\*\*\*END OF REPORT \*\*\*\*\*