



# FCC Test Report

**APPLICANT** : ZTE CORPORATION  
**EQUIPMENT** : LTE/WCDMA/GSM (GPRS) Multi-Mode Digital  
Mobile Phone  
**BRAND NAME** : ZTE  
**MODEL NAME** : Z557BL  
**FCC ID** : SRQ-Z557BL  
**STANDARD** : FCC 47 CFR FCC Part 15 Subpart B  
**CLASSIFICATION** : Certification

The product was received on Jul. 19, 2017 and testing was completed on Aug. 24, 2017. We, Sporton International (Kunshan) Inc., would like to declare that the tested sample has been evaluated in accordance with the test procedures given in ANSI C63.4-2014 and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International (Kunshan) Inc., the test report shall not be reproduced except in full.



Approved by: James Huang / Manager

**Sporton International (Kunshan) Inc.**

**No.3-2 Ping-Xiang Rd, Kunshan Development Zone Kunshan City Jiangsu Province 215335  
China**



# TABLE OF CONTENTS

**REVISION HISTORY..... 3**

**SUMMARY OF TEST RESULT ..... 4**

**1. GENERAL DESCRIPTION ..... 5**

    1.1. Applicant..... 5

    1.2. Manufacturer ..... 5

    1.3. Product Feature of Equipment Under Test ..... 5

    1.4. Product Specification of Equipment Under Test ..... 6

    1.5. Modification of EUT ..... 6

    1.6. Test Location ..... 7

    1.7. Applicable Standards ..... 7

**2. TEST CONFIGURATION OF EQUIPMENT UNDER TEST ..... 8**

    2.1. Test Mode ..... 8

    2.2. Connection Diagram of Test System ..... 9

    2.3. Support Unit used in test configuration and system ..... 10

    2.4. EUT Operation Test Setup ..... 11

**3. TEST RESULT ..... 12**

    3.1. Test of AC Conducted Emission Measurement ..... 12

    3.2. Test of Radiated Emission Measurement ..... 19

**4. LIST OF MEASURING EQUIPMENT ..... 25**

**5. UNCERTAINTY OF EVALUATION ..... 26**

**APPENDIX A. SETUP PHOTOGRAPHS**



### REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FC771907	Rev. 01	Initial issue of report	Sep. 04, 2017



### SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.107	AC Conducted Emission	< 15.107 limits	PASS	Under limit 9.09 dB at 2.581/2.500 MHz
3.2	15.109	Radiated Emission	< 15.109 limits	PASS	Under limit 4.32 dB at 45.930 MHz for Quasi-Peak



# 1. General Description

## 1.1. Applicant

**ZTE CORPORATION**

ZTE Plaza, Keji Road South, Hi-Tech, Industrial Park, Nanshan District, Shenzhen, Guangdong, 518057, P.R.China

## 1.2. Manufacturer

**ZTE CORPORATION**

ZTE Plaza, Keji Road South, Hi-Tech, Industrial Park, Nanshan District, Shenzhen, Guangdong, 518057, P.R.China

## 1.3. Product Feature of Equipment Under Test

Product Feature	
<b>Equipment</b>	LTE/WCDMA/GSM (GPRS) Multi-Mode Digital Mobile Phone
<b>Brand Name</b>	ZTE
<b>Model Name</b>	Z557BL
<b>FCC ID</b>	SRQ-Z557BL
<b>EUT supports Radios application</b>	GSM/GPRS/EGPRS/WCDMA/HSPA/ HSPA+(16QAM uplink is not supported)/LTE WLAN 2.4GHz 802.11b/g/n HT20 Bluetooth v3.0 + EDR/Bluetooth v4.0 LE/ Bluetooth v4.1 LE/Bluetooth v4.2 LE
<b>IMEI Code</b>	Conduction: 865356030009708 Radiation: 865356030009708
<b>HW Version</b>	Z557BLHWV1.0
<b>SW Version</b>	Z557BLV1.0.0B01
<b>EUT Stage</b>	Identical Prototype

**Remark:** The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

### 1.4. Product Specification of Equipment Under Test

Standards-related Product Specification	
<b>Tx Frequency</b>	GSM850: 824.2 MHz ~ 848.8 MHz GSM1900: 1850.2 MHz ~ 1909.8MHz WCDMA Band V: 826.4 MHz ~ 846.6 MHz WCDMA Band IV: 1712.4 MHz ~ 1752.6 MHz WCDMA Band II: 1852.4 MHz ~ 1907.6 MHz LTE Band 2 : 1850.7 MHz ~ 1909.3 MHz LTE Band 4 : 1710.7 MHz ~ 1754.3 MHz LTE Band 5 : 824.7 MHz ~ 848.3 MHz LTE Band 12 : 699.7 MHz ~ 715.3 MHz LTE Band 66 : 1710.7 MHz ~ 1779.3 MHz 802.11b/g/n: 2412 MHz ~ 2462 MHz Bluetooth: 2402 MHz ~ 2480 MHz
<b>Rx Frequency</b>	GSM850: 869.2 MHz ~ 893.8 MHz GSM1900: 1930.2 MHz ~ 1989.8 MHz WCDMA Band V: 871.4 MHz ~ 891.6 MHz WCDMA Band IV: 2112.4 MHz ~ 2152.6 MHz WCDMA Band II: 1932.4 MHz ~ 1987.6 MHz LTE Band 2 : 1930.7 MHz ~ 1989.3 MHz LTE Band 4 : 2110.7 MHz ~ 2154.3 MHz LTE Band 5 : 869.7 MHz ~ 893.3 MHz LTE Band 12 : 729.7 MHz ~ 745.3 MHz LTE Band 66 : 2110.7 MHz~ 2179.3 MHz 802.11b/g/n: 2412 MHz ~ 2462 MHz Bluetooth: 2402 MHz ~ 2480 MHz GNSS : 1559 MHz ~ 1610 MHz
<b>Antenna Type</b>	WWAN : PIFA Antenna WLAN : PIFA Antenna Bluetooth : PIFA Antenna GNSS: PIFA Antenna
<b>Type of Modulation</b>	GSM: GMSK GPRS: GMSK EDGE(MCS 0-4): GMSK / (MCS 5-9): 8PSK WCDMA : BPSK (Uplink) HSDPA : QPSK (Uplink) HSUPA : QPSK (Uplink) HSPA+ : 16QAM (uplink is not supported) LTE: QPSK / 16QAM 802.11b : DSSS (DBPSK / DQPSK / CCK) 802.11g/n : OFDM (BPSK / QPSK / 16QAM / 64QAM) Bluetooth LE : GFSK Bluetooth (1Mbps) : GFSK Bluetooth (2Mbps) : $\pi/4$ -DQPSK Bluetooth (3Mbps) : 8-DPSK GNSS: BPSK

### 1.5. Modification of EUT

No modifications are made to the EUT during all test items.



### 1.6. Test Location

Sporton Lab is accredited to ISO 17025 by National Voluntary Laboratory Accreditation Program (NVLAP code: 600155-0) and the FCC designation No. is CN5013.

<b>Test Site</b>	Sporton International (Kunshan) Inc.		
<b>Test Site Location</b>	No.3-2 Ping-Xiang Rd, Kunshan Development Zone Kunshan City Jiangsu Province 215335 China TEL : +86-512-57900158 FAX : +86-512-57900958		
<b>Test Site No.</b>	<b>Sporton Site No.</b>		<b>FCC Test Firm Registration No.</b>
	CO01-KS	03CH02-KS	630927

**Note:** The test site complies with ANSI C63.4 2014 requirement.

### 1.7. Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC 47 CFR FCC Part 15 Subpart B
- ♦ ANSI C63.4-2014

**Remark:** All test items were verified and recorded according to the standards and without any deviation during the test.



## 2. Test Configuration of Equipment Under Test

### 2.1. Test Mode

The EUT has been associated with peripherals pursuant to ANSI C63.4-2014 and configuration operated in a manner tended to maximize its emission characteristics in a typical application.

Frequency range investigated: conduction (150 kHz to 30 MHz), radiation (30MHz to the 5th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower).


Test Items	Function Type
AC Conducted Emission	Mode 1: GSM850 Idle + Bluetooth Idle + WLAN Idle(2.4G) + USB Cable (Charging from Adapter 1) + Earphone + Camera(Rear) <Fig.1>
	Mode 2: GSM1900 Idle + Bluetooth Idle + WLAN Idle(2.4G) + USB Cable (Charging from Adapter 2) + Earphone + Camera(Front) <Fig.1>
	Mode 3: WCDMA Band V Idle + Bluetooth Idle + WLAN Idle(2.4G) + USB Cable (Charging from Adapter 3) + Earphone + MPEG4 <Fig.1>
	Mode 4: LTE Band 2 Idle + Bluetooth Idle + WLAN Idle(2.4G) + USB Cable (Data Link with Notebook) + Earphone + GNSS Rx <Fig.2>
Radiated Emissions < 1GHz	Mode 1: GSM850 Idle + Bluetooth Idle + WLAN Idle(2.4G) + USB Cable (Charging from Adapter 1) + Earphone + Camera(Rear) <Fig.1>
	Mode 2: GSM1900 Idle + Bluetooth Idle + WLAN Idle(2.4G) + USB Cable (Charging from Adapter 2) + Earphone + Camera(Front) <Fig.1>
	Mode 3: WCDMA Band V Idle + Bluetooth Idle + WLAN Idle(2.4G) + USB Cable (Charging from Adapter 3) + Earphone + MPEG4 <Fig.1>
	Mode 4: LTE Band 2 Idle + Bluetooth Idle + WLAN Idle(2.4G) + USB Cable (Data Link with Notebook) + Earphone + GNSS Rx <Fig.2>
Radiated Emissions ≥ 1GHz	Mode 1: GSM850 Idle + Bluetooth Idle + WLAN Idle(2.4G) + USB Cable (Charging from Adapter 1) + Earphone + Camera(Rear)
	Mode 2: LTE Band 2 Idle + Bluetooth Idle + WLAN Idle(2.4G) + USB Cable (Data Link with Notebook) + Earphone + GNSS Rx

**Remark:**


1. The worst case of AC is mode 2, and the USB Link mode is mode 4, the test data of these modes are reported.
2. The worst case of RE is mode 1, and the USB Link mode is mode 4, the test data of these modes are reported.
3. Data Link with Notebook means data application transferred mode between EUT and Notebook.
4. GNSS Rx = GPS Rx + Glonass Rx



## 2.2. Connection Diagram of Test System



<Fig.1>



<Fig.2>



### 2.3. Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	System Simulator	Anritsu	MT8820C	N/A	N/A	Unshielded, 1.8m
2.	GPS Station	ADIVIC	MP9000	N/A	N/A	Unshielded, 1.8m
3.	Glomass Station	RACELOGIC	RLLS03-2RP	N/A	N/A	Unshielded, 1.8m
4.	WLAN AP	LINKSYS	WRT600N	Q87-WRT600NV11	N/A	Unshielded, 1.8m
5.	WLAN AP	D-Link	DIR-855	KA2DIR855A2	N/A	Unshielded, 1.8m
6.	Bluetooth Earphone	Lenovo	LBH308	N/A	N/A	N/A
7.	Bluetooth Earphone	Lenovo	LBH301	N/A	N/A	N/A
8.	Notebook	DELL	Latitude3440	N/A	N/A	AC I/P : Unshielded, 1.8m DC O/P : Shielded, 1.8m
9.	Notebook	Lenovo	G480	N/A	N/A	AC I/P : Unshielded, 1.8m DC O/P : Shielded, 1.8m
10.	Earphone	Lenovo	LH102	N/A	Unshielded, 1.2m	N/A
11.	Earphone	Lenovo	SH100	N/A	Unshielded, 1.2m	N/A
12.	SD Card	Kingston	SDC4/4GB	N/A	N/A	N/A
13.	SD Card	SanDisk	Uitra	N/A	N/A	N/A
14.	iPod	Apple	A1199	FCC DoC	Shielded, 1.2m	N/A



## **2.4. EUT Operation Test Setup**

The EUT was in GSM or WCDMA or LTE idle mode during the testing. The EUT was synchronized to the BCCH, and is in continuous receiving mode by setting system simulator's paging reorganization.

At the same time, the EUT was attached to the Bluetooth earphone or WLAN AP, and the following programs installed in the EUT were programmed during the test.

1. Data application is transferred between Notebook and EUT via USB cable.
2. Turn on GNSS function to make the EUT receive continuous signals from GNSS station.
3. Execute "Video Player" to play MPEG4 files.
4. Turn on camera to capture images.

### 3. Test Result

#### 3.1. Test of AC Conducted Emission Measurement

##### 3.1.1 Limits of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

\*Decreases with the logarithm of the frequency.


##### 3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

##### 3.1.3 Test Procedure

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.


### 3.1.4 Test Setup





3.1.5 Test Result of AC Conducted Emission

Test Mode :	Mode 2	Temperature :	22~24°C
Test Engineer :	Amos Zhang	Relative Humidity :	42~46%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Function Type :	GSM1900 Idle + Bluetooth Idle + WLAN Idle(2.4G) + USB Cable (Charging from Adapter 2) + Earphone + Camera(Front)		




Site : CO01-KS  
 Condition : FCC CLASS-B LISN-L-161017-060103 LINE  
 Project : (FC) 771907  
 mode : Mode 2  
 : 865356030009708 #3

	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	2.044	40.00	-16.00	56.00	29.60	0.21	10.19	QP
2	2.044	33.00	-13.00	46.00	22.60	0.21	10.19	Average
3	2.225	41.01	-14.99	56.00	30.60	0.21	10.20	QP
4	2.225	33.71	-12.29	46.00	23.30	0.21	10.20	Average
5	2.435	41.71	-14.29	56.00	31.30	0.21	10.20	QP
6 *	2.435	35.01	-10.99	46.00	24.60	0.21	10.20	Average
7	2.608	42.02	-13.98	56.00	31.60	0.21	10.21	QP
8	2.608	34.62	-11.38	46.00	24.20	0.21	10.21	Average
9	2.854	41.32	-14.68	56.00	30.90	0.21	10.21	QP
10	2.854	34.02	-11.98	46.00	23.60	0.21	10.21	Average
11	3.025	40.03	-15.97	56.00	29.60	0.21	10.22	QP
12	3.025	33.03	-12.97	46.00	22.60	0.21	10.22	Average



Test Mode :	Mode 2	Temperature :	22~24°C
Test Engineer :	Amos Zhang	Relative Humidity :	42~46%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Function Type :	GSM1900 Idle + Bluetooth Idle + WLAN Idle(2.4G) + USB Cable (Charging from Adapter 2) + Earphone + Camera(Front)		




Site : CO01-KS  
 Condition : FCC CLASS-B LISN-N-161017-060103 NEUTRAL  
 Project : (FC) 771907  
 mode : Mode 2  
 : 865356030009708 #3

	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	1.396	40.19	-15.81	56.00	29.60	0.40	10.19	QP
2	1.396	30.89	-15.11	46.00	20.30	0.40	10.19	Average
3	1.552	42.89	-13.11	56.00	32.29	0.41	10.19	QP
4	1.552	32.89	-13.11	46.00	22.29	0.41	10.19	Average
5	1.619	42.79	-13.21	56.00	32.19	0.41	10.19	QP
6	1.619	32.89	-13.11	46.00	22.29	0.41	10.19	Average
7	1.781	44.20	-11.80	56.00	33.60	0.41	10.19	QP
8	1.781	34.20	-11.80	46.00	23.60	0.41	10.19	Average
9	1.939	44.20	-11.80	56.00	33.60	0.41	10.19	QP
10	1.939	34.20	-11.80	46.00	23.60	0.41	10.19	Average
11	2.077	44.20	-11.80	56.00	33.60	0.41	10.19	QP
12	2.077	35.80	-10.20	46.00	25.20	0.41	10.19	Average
13	2.309	44.80	-11.20	56.00	34.19	0.41	10.20	QP
14	2.309	36.80	-9.20	46.00	26.19	0.41	10.20	Average
15	2.500	45.41	-10.59	56.00	34.81	0.40	10.20	QP
16	2.500	36.91	-9.09	46.00	26.31	0.40	10.20	Average
17	2.581	45.21	-10.79	56.00	34.60	0.40	10.21	QP



Test Mode :	Mode 2	Temperature :	22~24°C
Test Engineer :	Amos Zhang	Relative Humidity :	42~46%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Function Type :	GSM1900 Idle + Bluetooth Idle + WLAN Idle(2.4G) + USB Cable (Charging from Adapter 2) + Earphone + Camera(Front)		




Site : CO01-KS  
 Condition : FCC CLASS-B LISN-N-161017-060103 NEUTRAL  
 Project : (FC) 771907  
 mode : Mode 2  
 : 865356030009708 #3

	Freq	Level	Over	Limit	Read	LISN	Cable	Remark
	MHz	dBuV	Limit	Line	Level	Factor	Loss	
			dB	dBuV	dBuV	dB	dB	
18 *	2.581	36.91	-9.09	46.00	26.30	0.40	10.21	Average
19	2.779	44.91	-11.09	56.00	34.30	0.40	10.21	QP
20	2.779	36.81	-9.19	46.00	26.20	0.40	10.21	Average
21	3.107	42.92	-13.08	56.00	32.30	0.40	10.22	QP
22	3.107	34.82	-11.18	46.00	24.20	0.40	10.22	Average
23	3.399	40.22	-15.78	56.00	29.60	0.39	10.23	QP
24	3.399	30.92	-15.08	46.00	20.30	0.39	10.23	Average





Test Mode :	Mode 4	Temperature :	22~24°C
Test Engineer :	Amos Zhang	Relative Humidity :	42~46%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Function Type :	LTE Band 2 Idle + Bluetooth Idle + WLAN Idle(2.4G) + USB Cable (Data Link with Notebook) + Earphone + GNSS Rx		




Site : CO01-KS  
 Condition : FCC CLASS-B LISN-L-161017-060103 LINE  
 Project : (FC) 771907  
 mode : Mode 4  
 : 865356030009708 #3

	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.151	42.24	-23.72	65.96	31.30	0.55	10.39	QP
2	0.151	31.84	-24.12	55.96	20.90	0.55	10.39	Average
3	0.161	38.07	-27.36	65.43	27.20	0.49	10.38	QP
4	0.161	21.17	-34.26	55.43	10.30	0.49	10.38	Average
5	0.171	36.39	-28.51	64.90	25.60	0.42	10.37	QP
6	0.171	21.99	-32.91	54.90	11.20	0.42	10.37	Average
7	0.182	35.31	-29.06	64.37	24.60	0.36	10.35	QP
8	0.182	21.01	-33.36	54.37	10.30	0.36	10.35	Average
9	0.192	33.94	-29.99	63.93	23.30	0.30	10.34	QP
10	0.192	21.24	-32.69	53.93	10.60	0.30	10.34	Average
11	0.454	35.66	-21.14	56.80	25.20	0.27	10.19	QP
12 *	0.454	33.36	-13.44	46.80	22.90	0.27	10.19	Average



Test Mode :	Mode 4	Temperature :	22~24°C
Test Engineer :	Amos Zhang	Relative Humidity :	42~46%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Function Type :	LTE Band 2 Idle + Bluetooth Idle + WLAN Idle(2.4G) + USB Cable (Data Link with Notebook) + Earphone + GNSS Rx		



Site : CO01-KS  
 Condition : FCC CLASS-B LISN-N-161017-060103 NEUTRAL  
 Project : (FC) 771907  
 mode : Mode 4  
 : 865356030009708 #3

	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.150	43.93	-22.07	66.00	33.20	0.34	10.39	QP
2	0.150	32.33	-23.67	56.00	21.60	0.34	10.39	Average
3	0.166	37.01	-28.15	65.16	26.30	0.34	10.37	QP
4	0.166	24.01	-31.15	55.16	13.30	0.34	10.37	Average
5	0.179	35.29	-29.26	64.55	24.60	0.33	10.36	QP
6	0.179	26.19	-28.36	54.55	15.50	0.33	10.36	Average
7	0.203	32.86	-30.63	63.49	22.20	0.33	10.33	QP
8	0.203	23.86	-29.63	53.49	13.20	0.33	10.33	Average
9	0.486	37.17	-19.06	56.23	26.60	0.38	10.19	QP
10 *	0.486	33.87	-12.36	46.23	23.30	0.38	10.19	Average
11	4.874	28.52	-27.48	56.00	17.90	0.38	10.24	QP
12	4.874	21.92	-24.08	46.00	11.30	0.38	10.24	Average



### 3.2. Test of Radiated Emission Measurement

#### 3.2.1. Limit of Radiated Emission

The emissions from an unintentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

#### 3.2.2. Measuring Instruments


The measuring equipment is listed in the section 4 of this test report.

#### 3.2.3. Test Procedures


1. The EUT was placed on a turntable with 0.8 meter above ground.
2. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
3. The table was rotated 360 degrees to determine the position of the highest radiation.
4. The antenna is a Bi-Log antenna and its height is adjusted between one to four meters above ground to find the maximum value of the field strength for both horizontal polarization and vertical polarization of the antenna.
5. For each suspected emission, the EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading.
6. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode (RBW=120kHz/VBW=300kHz for frequency below 1GHz; RBW=1MHz VBW=3MHz (Peak), RBW=1MHz/VBW=10Hz (Average) for frequency above 1GHz).
7. If the emission level of the EUT in peak mode was 3 dB lower than the limit specified, peak values of EUT will be reported. Otherwise, the emission will be repeated by using the quasi-peak method and reported.
8. Emission level (dBµV/m) = 20 log Emission level (µV/m)
9. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level

### 3.2.4. Test Setup of Radiated Emission

For radiated emissions from 30MHz to 1GHz




For radiated emissions above 1GHz





3.2.5. Test Result of Radiated Emission

Test Mode :	Mode 1	Temperature :	21~22°C
Test Engineer :	Carl Ni	Relative Humidity :	41~42%
Test Distance :	3m	Polarization :	Horizontal
Function Type :	GSM850 Idle + Bluetooth Idle + WLAN Idle(2.4G) + USB Cable (Charging from Adapter 1) + Earphone + Camera(Rear)		
Remark :	#7 is system simulator signal which can be ignored.		




Site : 03CH02-KS  
 Condition : FCC CLASS-B 3m 02 LF ANT HORIZONTAL  
 Project : (FC) 771907  
 Mode : 1  
 IMEI : 865356030009708 #3

	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark	
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1	45.39	24.13	-15.87	40.00	36.24	19.80	0.14	32.05	---	---	Peak
2	101.55	29.64	-13.86	43.50	43.42	17.90	0.24	31.92	100	0	Peak
3	135.84	24.62	-18.88	43.50	38.54	17.61	0.30	31.83	---	---	Peak
4	154.20	23.04	-20.46	43.50	37.14	17.36	0.33	31.79	---	---	Peak
5	414.10	22.76	-23.24	46.00	26.99	25.39	0.94	30.56	---	---	Peak
6	750.10	24.95	-21.05	46.00	25.42	26.69	1.36	28.52	---	---	Peak
7 *	881.00	47.24			45.93	27.35	1.58	27.62	---	---	Peak
8	1962.00	43.21	-30.79	74.00	42.13	29.94	4.47	33.33	---	---	Peak
9	2186.00	44.63	-29.37	74.00	41.30	30.75	5.80	33.22	---	---	Peak
10	2872.00	43.86	-30.14	74.00	41.04	32.00	2.85	32.03	---	---	Peak
11	3501.00	46.46	-27.54	74.00	39.12	33.44	6.02	32.12	---	---	Peak
12	3981.00	45.50	-28.50	74.00	36.91	34.96	6.03	32.40	---	---	Peak
13	4767.00	45.93	-28.07	74.00	36.64	35.39	6.00	32.10	---	---	Peak



Test Mode :	Mode 1	Temperature :	21~22°C
Test Engineer :	Carl Ni	Relative Humidity :	41~42%
Test Distance :	3m	Polarization :	Vertical
Function Type :	GSM850 Idle + Bluetooth Idle + WLAN Idle(2.4G) + USB Cable (Charging from Adapter 1) + Earphone + Camera(Rear)		
Remark :	#7 is system simulator signal which can be ignored.		




Site : 03CH02-KS  
 Condition : FCC CLASS-B 3m 02 LF ANT VERTICAL  
 Project : (FC) 771907  
 Mode : 1  
 IMEI : 865356030009708 #3

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Cable Factor	Preamp Loss	A/Pos	T/Pos	Remark	
	MHz	dBUV/m	dB	dBUV/m	dBuV	dB/m	dB	dB	cm	deg	
1 !	33.24	34.91	-5.09	40.00	42.01	24.87	0.11	32.08	---	---	Peak
2 !	44.04	35.64	-4.36	40.00	47.00	20.57	0.13	32.06	100	256	QP
3 !	45.93	35.68	-4.32	40.00	47.79	19.80	0.14	32.05	100	0	QP
4	101.55	34.64	-8.86	43.50	48.42	17.90	0.24	31.92	---	---	Peak
5	418.30	22.45	-23.55	46.00	26.75	25.30	0.94	30.54	---	---	Peak
6	827.80	25.00	-21.00	46.00	24.77	26.84	1.41	28.02	---	---	Peak
7 *	881.70	46.61			45.28	27.35	1.59	27.61	---	---	Peak
8	1514.00	41.30	-32.70	74.00	42.83	28.65	3.79	33.97	---	---	Peak
9	2112.00	43.86	-30.14	74.00	41.42	30.50	5.20	33.26	---	---	Peak
10	2920.00	43.57	-30.43	74.00	40.39	32.15	2.95	31.92	---	---	Peak
11	3246.00	45.20	-28.80	74.00	38.04	33.13	6.02	31.99	---	---	Peak
12	4122.00	45.56	-28.44	74.00	36.38	35.22	6.46	32.50	---	---	Peak
13	4770.00	44.99	-29.01	74.00	35.70	35.39	6.00	32.10	---	---	Peak



Test Mode :	Mode 4	Temperature :	21~22°C
Test Engineer :	Carl Ni	Relative Humidity :	41~42%
Test Distance :	3m	Polarization :	Horizontal
Function Type :	LTE Band 2 Idle + Bluetooth Idle + WLAN Idle(2.4G) + USB Cable (Data Link with Notebook) + Earphone + GNSS Rx		




Site : 03CH02-KS  
 Condition : FCC CLASS-B 3m 02 LF ANT HORIZONTAL  
 Project : (FC) 771907  
 Mode : 4  
 IMEI : 865356030009708 #3

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Cable Factor	Preamp Loss	A/Pos	T/Pos	Remark	
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1	80.22	25.07	-14.93	40.00	41.96	14.90	0.20	31.99	---	---	Peak
2	165.54	39.54	-3.96	43.50	53.98	16.96	0.35	31.75	100	0	Peak
3	194.43	32.71	-10.79	43.50	47.97	16.00	0.40	31.66	---	---	Peak
4	255.18	36.55	-9.45	46.00	50.47	17.00	0.49	31.41	---	---	Peak
5	400.10	30.56	-15.44	46.00	34.55	25.70	0.93	30.62	---	---	Peak
6	734.70	32.24	-13.76	46.00	32.94	26.62	1.30	28.62	---	---	Peak
7	1796.00	42.62	-31.38	74.00	42.37	29.13	4.59	33.47	---	---	Peak
8	2218.00	44.79	-29.21	74.00	41.36	30.84	5.78	33.19	---	---	Peak
9	2908.00	43.30	-30.70	74.00	40.17	32.10	2.95	31.92	---	---	Peak
10	3276.00	45.80	-28.20	74.00	38.67	33.16	6.01	32.04	---	---	Peak
11	3771.00	46.20	-27.80	74.00	37.35	34.63	6.44	32.22	---	---	Peak
12	4770.00	46.36	-27.64	74.00	37.07	35.39	6.00	32.10	---	---	Peak



Test Mode :	Mode 4	Temperature :	21~22°C
Test Engineer :	Carl Ni	Relative Humidity :	41~42%
Test Distance :	3m	Polarization :	Vertical
Function Type :	LTE Band 2 Idle + Bluetooth Idle + WLAN Idle(2.4G) + USB Cable (Data Link with Notebook) + Earphone + GNSS Rx		



Site : 03CH02-KS  
 Condition : FCC CLASS-B 3m 02 LF ANT VERTICAL  
 Project : (FC) 771907  
 Mode : 4  
 IMEI : 865356030009708 #3

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	A/Pos	T/Pos	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1	56.19	22.70	-17.30	40.00	40.49	14.10	0.16	32.05	---	---	Peak
2	97.77	25.36	-18.14	43.50	39.57	17.50	0.23	31.94	---	---	Peak
3	165.81	34.74	-8.76	43.50	49.18	16.96	0.35	31.75	100	0	Peak
4	194.43	27.38	-16.12	43.50	42.64	16.00	0.40	31.66	---	---	Peak
5	598.90	34.63	-11.37	46.00	38.64	24.60	0.90	29.51	---	---	Peak
6	734.00	34.89	-11.11	46.00	35.61	26.60	1.30	28.62	---	---	Peak
7	1484.00	41.56	-32.44	74.00	43.27	28.60	3.70	34.01	---	---	Peak
8	2188.00	44.44	-29.56	74.00	41.11	30.75	5.80	33.22	---	---	Peak
9	2654.00	43.38	-30.62	74.00	40.99	31.54	3.31	32.46	---	---	Peak
10	3201.00	45.27	-28.73	74.00	38.00	33.10	6.05	31.88	---	---	Peak
11	3822.00	45.29	-28.71	74.00	36.29	34.71	6.56	32.27	---	---	Peak
12	4188.00	45.22	-28.78	74.00	35.88	35.32	6.59	32.57	---	---	Peak





### 4. List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
EMI Receiver	R&S	ESCI7	100768	9kHz~7GHz;	Apr. 20, 2017	Aug. 24, 2017	Apr. 19, 2018	Conduction (CO01-KS)
AC LISN	MessTec	AN3016	060103	9kHz~30MHz	Oct. 13, 2016	Aug. 24, 2017	Oct. 12, 2017	Conduction (CO01-KS)
AC LISN (for auxiliary equipment)	MessTec	AN3016	060105	9kHz~30MHz	Oct. 13, 2016	Aug. 24, 2017	Oct. 12, 2017	Conduction (CO01-KS)
AC Power Source	Chroma	61602	ABP0000008 11	AC 0V~300V, 45Hz~1000Hz	Oct. 13, 2016	Aug. 24, 2017	Oct. 12, 2017	Conduction (CO01-KS)
EMI Test Receiver	R&S	ESR7	101403	9kHz~7GHz; Max 30dBm	Aug. 08, 2017	Aug. 19, 2017	Aug. 07, 2018	Radiation (03CH02-KS)
EXA Spectrum Analyzer	Keysight	N9010A	MY55150208	10Hz~44GHz, MAX 30dB	Apr. 18, 2017	Aug. 19, 2017	Apr. 17, 2018	Radiation (03CH02-KS)
Bilog Antenna	TeseQ	CBL6112D	23182	30MHz~2GHz	Jan. 22, 2017	Aug. 19, 2017	Jan. 21, 2018	Radiation (03CH02-KS)
Double Ridge Horn Antenna	ETS-Lindgren	3117	75957	1GHz~18GHz	Oct. 22, 2016	Aug. 19, 2017	Oct. 21, 2017	Radiation (03CH02-KS)
Amplifier	SONOMA	310N	187289	9kHz~1GHz	Aug. 07, 2017	Aug. 19, 2017	Aug. 06, 2018	Radiation (03CH02-KS)
Amplifier	Agilent	8449B	3008A02384	1-26.5GHz Gain 30dB	Oct. 13, 2016	Aug. 19, 2017	Oct. 12, 2017	Radiation (03CH02-KS)
AC Power Source	Chroma	61601	61601000247 3	N/A	NCR	Aug. 19, 2017	NCR	Radiation (03CH02-KS)
Turn Table	MF	MF7802	N/A	0~360 degree	NCR	Aug. 19, 2017	NCR	Radiation (03CH02-KS)
Antenna Mast	MF	MF7802	N/A	1 m~4 m	NCR	Aug. 19, 2017	NCR	Radiation (03CH02-KS)

NCR: No Calibration Required



## 5. Uncertainty of Evaluation

### Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	2.3dB
---	-------

### Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	5.2dB
---	-------

### Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	4.7dB
---	-------