

FCC Test Report

APPLICANT : ZTE CORPORATION
EQUIPMENT : WCDMA/ LTE Multi-Mode Digital Mobile Phone
BRAND NAME : ZTE
MODEL NAME : Z982
FCC ID : SRQ-Z982
STANDARD : FCC 47 CFR FCC Part 15 Subpart B
CLASSIFICATION : Certification

The product was received on Apr. 07, 2017 and testing was completed on May 20, 2017. We, Sporton International (KunShan) INC., would like to declare that the tested sample has been evaluated in accordance with the test procedures given in ANSI C63.4-2014 and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International (KunShan) INC., the test report shall not be reproduced except in full.



Prepared by: James Huang / Manager



Approved by: Jones Tsai / Manager



Sporton International (KunShan) INC.
No.3-2, Pingxiang Road, Kunshan Development Zone, Jiangsu, China



TABLE OF CONTENTS

REVISION HISTORY	3
SUMMARY OF TEST RESULT	4
1. GENERAL DESCRIPTION	5
1.1. Applicant.....	5
1.2. Manufacturer	5
1.3. Product Feature of Equipment Under Test	5
1.4. Product Specification of Equipment Under Test	6
1.5. Modification of EUT	7
1.6. Test Location	7
1.7. Applicable Standards	7
2. TEST CONFIGURATION OF EQUIPMENT UNDER TEST	8
2.1. Test Mode	8
2.2. Connection Diagram of Test System	9
2.3. Support Unit used in test configuration and system.....	11
2.4. EUT Operation Test Setup	12
3. TEST RESULT	13
3.1. Test of AC Conducted Emission Measurement	13
3.2. Test of Radiated Emission Measurement	20
4. LIST OF MEASURING EQUIPMENT	25
5. UNCERTAINTY OF EVALUATION	26
APPENDIX A. SETUP PHOTOGRAPHS	



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FC740701	Rev. 01	Initial issue of report	May 26, 2017



SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.107	AC Conducted Emission	< 15.107 limits	PASS	Under limit 3.62 dB at 0.413 MHz
3.2	15.109	Radiated Emission	< 15.109 limits	PASS	Under limit 3.14 dB at 719.670 MHz



1. General Description

1.1. Applicant

ZTE CORPORATION

ZTE Plaza, Keji Road South, Hi-Tech, Industrial Park, Nanshan District, Shenzhen, Guangdong, 518057, P. R. China

1.2. Manufacturer

ZTE CORPORATION

ZTE Plaza, Keji Road South, Hi-Tech, Industrial Park, Nanshan District, Shenzhen, Guangdong, 518057, P. R. China

1.3. Product Feature of Equipment Under Test

Product Feature	
Equipment	WCDMA/ LTE Multi-Mode Digital Mobile Phone
Brand Name	ZTE
Model Name	Z982
FCC ID	SRQ-Z982
EUT supports Radios application	GSM/GPRS/EGPRS/WCDMA/HSPA/DC-HSDPA/ HSPA+(16QAM uplink is not supported)/LTE/ WLAN 2.4GHz 802.11b/g/n HT20/HT40 Bluetooth v3.0 + EDR/Bluetooth v4.0 LE/ Bluetooth v4.1 LE/Bluetooth v4.2 LE
IMEI Code	Conduction: 864650030003963 Radiation: 864650030003963
HW Version	Z982HW1.0
SW Version	Z982V1.0.0B01
EUT Stage	Identical Prototype

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.4. Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx Frequency	GSM850: 824.2 MHz ~ 848.8 MHz GSM1900: 1850.2 MHz ~ 1909.8MHz WCDMA Band V: 826.4 MHz ~ 846.6 MHz WCDMA Band IV : 1712.4 MHz ~ 1752.6 MHz WCDMA Band II: 1852.4 MHz ~ 1907.6 MHz LTE Band 2 : 1850.7 MHz ~ 1909.3 MHz LTE Band 4 : 1710.7 MHz ~ 1754.3 MHz LTE Band 5 : 824.7 MHz ~ 848.3 MHz LTE Band 12 : 699.7 MHz ~ 715.3 MHz LTE Band 66 : 1710.7 MHz ~ 1779.3 MHz 802.11b/g/n: 2412 MHz ~ 2462 MHz Bluetooth: 2402 MHz ~ 2480 MHz
Rx Frequency	GSM850: 869.2 MHz ~ 893.8 MHz GSM1900: 1930.2 MHz ~ 1989.8 MHz WCDMA Band V: 871.4 MHz ~ 891.6 MHz WCDMA Band IV : 2112.4 MHz ~ 2152.6 MHz WCDMA Band II: 1932.4 MHz ~ 1987.6 MHz LTE Band 2 : 1930.7 MHz ~ 1989.3 MHz LTE Band 4 : 2110.7 MHz ~ 2154.3 MHz LTE Band 5 : 869.7 MHz ~ 893.3 MHz LTE Band 12 : 729.7 MHz ~ 745.3 MHz LTE Band 66 : 2110.7 MHz~ 2199.3 MHz 802.11b/g/n: 2412 MHz ~ 2462 MHz Bluetooth: 2402 MHz ~ 2480 MHz GPS : 1.57542 GHz Glonass : 1602 MHz + $n \times 0.5625\text{MHz}$ ($n=-7, -6, -5, \dots, 0, \dots, 6$) FM : 88 MHz ~ 108 MHz
Antenna Type	WWAN : PIFA Antenna WLAN : PIFA Antenna Bluetooth : PIFA Antenna GPS/Glonass : PIFA Antenna FM: External headset Antenna
Type of Modulation	GSM: GMSK GPRS: GMSK EDGE(MCS 0-4): GMSK / (MCS 5-9): 8PSK WCDMA: BPSK (Uplink) HSDPA/ DC-HSDPA: QPSK (Uplink) HSUPA: QPSK (Uplink) HSPA+: 16QAM (Uplink is not supported) DC-HSDPA: 64QAM LTE: QPSK / 16QAM 802.11b : DSSS (DBPSK / DQPSK / CCK) 802.11g/n : OFDM (BPSK / QPSK / 16QAM / 64QAM) Bluetooth LE : GFSK Bluetooth (1Mbps) : GFSK Bluetooth (2Mbps) : $\pi/4$ -DQPSK Bluetooth (3Mbps) : 8-DPSK GPS/Glonass : BPSK FM : FM

1.5. Modification of EUT

No modifications are made to the EUT during all test items.

1.6. Test Location

Test Site	Sporton International (KunShan) INC.		
Test Site Location	No.3-2, Pingxiang Road, Kunshan Development Zone, Jiangsu, China TEL: +86-0512-5790-0158 FAX: +86-0512-5790-0958		
Test Site No.	Sporton Site No.		FCC Registration No.
	CO01-KS	03CH02-KS	418269

Note: The test site complies with ANSI C63.4 2014 requirement.

1.7. Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC 47 CFR FCC Part 15 Subpart B
- ♦ ANSI C63.4-2014

Remark: All test items were verified and recorded according to the standards and without any deviation during the test.

2. Test Configuration of Equipment Under Test


2.1. Test Mode

The EUT has been associated with peripherals pursuant to ANSI C63.4-2014 and configuration operated in a manner tended to maximize its emission characteristics in a typical application.


Frequency range investigated: conduction (150 kHz to 30 MHz), radiation (30MHz to the 5th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower).

Test Items	Function Type
AC Conducted Emission	Mode 1: GSM850 Idle + Bluetooth Idle + WLAN Idle (2.4G) + USB Cable (Charging from Adapter) + Earphone + Camera(Rear)<Fig.1> Mode 2: GSM1900 Idle + Bluetooth Idle + WLAN Idle (2.4G) + USB Cable (Charging from Adapter) + Earphone + Camera(Front)<Fig.1> Mode 3: WCDMA Band V Idle + Bluetooth Idle + WLAN Idle (2.4G) + USB Cable (Charging from Adapter) + Earphone + MPEG4<Fig.1> Mode 4: LTE Band 4 Idle + Bluetooth Idle + WLAN Idle (2.4G) + USB Cable (Charging from Adapter) + Earphone + Glonass Rx<Fig.2> Mode 5: LTE Band 2 Idle + Bluetooth Idle + WLAN Idle (2.4G) + USB Cable (Data Link with Notebook) + Earphone + GPS Rx<Fig.3>
Radiated Emissions < 1GHz	Mode 1: GSM850 Idle + Bluetooth Idle + WLAN Idle (2.4G) + USB Cable (Charging from Adapter) + Earphone + Camera(Rear)<Fig.1> Mode 2: GSM1900 Idle + Bluetooth Idle + WLAN Idle (2.4G) + USB Cable (Charging from Adapter) + Earphone + Camera(Front)<Fig.1> Mode 3: WCDMA Band V Idle + Bluetooth Idle + WLAN Idle (2.4G) + USB Cable (Charging from Adapter) + Earphone + MPEG4<Fig.1> Mode 4: LTE Band 4 Idle + Bluetooth Idle + WLAN Idle (2.4G) + USB Cable (Charging from Adapter) + Earphone + Glonass Rx<Fig.2> Mode 5: LTE Band 2 Idle + Bluetooth Idle + WLAN Idle (2.4G) + USB Cable (Data Link with Notebook) + Earphone + GPS Rx<Fig.3>
Radiated Emissions ≥ 1GHz	Mode 1: LTE Band 2 Idle + Bluetooth Idle + WLAN Idle (2.4G) + USB Cable (Data Link with Notebook) + Earphone + GPS Rx<Fig.3>
Remark: 1. The worst case of AC is mode 4, and the USB Link mode of AC is mode 5; the test data of these modes are reported. 2. The worst case of RE < 1G is mode 5; only the test data of this mode is reported. 3. Data Link with Notebook means data application transferred mode between EUT and Notebook.	


2.2. Connection Diagram of Test System



<Fig.1>



<Fig.2>



<Fig.3>

2.3. Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	System Simulator	R&S	CMU 200	N/A	N/A	Unshielded, 1.8 m
2.	LTE Base Station	Anritsu	MT8820C	N/A	N/A	Unshielded, 1.8 m
3.	GPS Station	ADIVIC	MP9000	N/A	N/A	Unshielded, 1.8 m
4.	Glomass Station	RACELOGIC	RLLS03-2RP	N/A	N/A	Unshielded, 1.8 m
5.	WLAN AP	TP-Link	TL-WDR5600	N/A	N/A	Unshielded, 1.8 m
6.	WLAN AP	LINKSYS	WRT600N	Q87-WRT600NV11	N/A	Unshielded, 1.8 m
7.	Bluetooth Earphone	Lenovo	LBH308	QTLBH-106	N/A	N/A
8.	Notebook	Lenovo	G480	N/A	N/A	AC I/P: Unshielded, 1.8 m DC O/P: Shielded, 1.8 m
9.	Notebook	Dell	Latitude3440	N/A	N/A	AC I/P: Unshielded, 1.8 m DC O/P: Shielded, 1.8 m
10.	SD Card	Kingston	4GB	N/A	N/A	N/A
11.	SD Card	SanDisk	Uitra	N/A	N/A	N/A
12.	iPod	Apple	A1199	FCC DoC	Shielded, 1.2 m	N/A
13.	Earphone	Lenovo	LH102	N/A	Unshielded,1.2m	N/A
14.	Earphone	Lenovo	SH100	N/A	N/A	N/A

2.4. EUT Operation Test Setup

The EUT was in GSM or WCDMA or LTE idle mode during the testing. The EUT was synchronized to the BCCH, and is in continuous receiving mode by setting system simulator's paging reorganization.

At the same time, the EUT was attached to the Bluetooth earphone or WLAN AP, and the following programs installed in the EUT were programmed during the test.

1. Data application is transferred between Notebook and EUT via USB cable.
2. Turn on GPS/Glonass function to make the EUT receive continuous signals from GPS/Glonass station.
3. Execute "Video player" to play MPEG4 files.
4. Turn on camera to capture images.

3. Test Result

3.1. Test of AC Conducted Emission Measurement

3.1.1 Limits of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.1.3 Test Procedure

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.


3.1.4 Test Setup





3.1.5 Test Result of AC Conducted Emission

Test Mode :	Mode 4	Temperature :	22~24℃
Test Engineer :	Amos Zhang	Relative Humidity :	42~46%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Function Type :	LTE Band 4 Idle + Bluetooth Idle + WLAN Idle (2.4G) + USB Cable (Charging from Adapter) + Earphone + Glonass Rx		




Site : CO01-KS
Condition : FCC CLASS-B LISN-L-161017-060103 LINE
Project : (FC) 740701
mode : Mode 4
: 864650030003963 #9

	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.417	46.07	-11.44	57.51	35.60	0.27	10.20	QP
2 *	0.417	40.07	-7.44	47.51	29.60	0.27	10.20	Average
3	0.494	42.06	-14.04	56.10	31.60	0.27	10.19	QP
4	0.494	36.76	-9.34	46.10	26.30	0.27	10.19	Average
5	0.544	41.05	-14.95	56.00	30.60	0.26	10.19	QP
6	0.544	33.05	-12.95	46.00	22.60	0.26	10.19	Average
7	2.946	39.33	-16.67	56.00	28.90	0.21	10.22	QP
8	2.946	33.73	-12.27	46.00	23.30	0.21	10.22	Average
9	3.276	39.73	-16.27	56.00	29.30	0.21	10.22	QP
10	3.276	33.73	-12.27	46.00	23.30	0.21	10.22	Average
11	3.603	39.74	-16.26	56.00	29.30	0.21	10.23	QP
12	3.603	34.04	-11.96	46.00	23.60	0.21	10.23	Average
13	4.224	40.25	-15.75	56.00	29.80	0.21	10.24	QP
14	4.224	34.55	-11.45	46.00	24.10	0.21	10.24	Average
15	4.622	40.05	-15.95	56.00	29.60	0.21	10.24	QP
16	4.622	34.05	-11.95	46.00	23.60	0.21	10.24	Average



Test Mode :	Mode 4	Temperature :	22~24℃
Test Engineer :	Amos Zhang	Relative Humidity :	42~46%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Function Type :	LTE Band 4 Idle + Bluetooth Idle + WLAN Idle (2.4G) + USB Cable (Charging from Adapter) + Earphone + Glonass Rx		




Site : CO01-KS
 Condition : FCC CLASS-B LISN-N-161017-060103 NEUTRAL
 Project : (FC) 740701
 mode : Mode 4
 : 864650030003963 #9

	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.413	52.17	-5.42	57.59	41.60	0.37	10.20	QP
2 *	0.413	43.97	-3.62	47.59	33.40	0.37	10.20	Average
3	0.497	47.17	-8.88	56.05	36.60	0.38	10.19	QP
4	0.497	38.17	-7.88	46.05	27.60	0.38	10.19	Average
5	0.549	46.86	-9.14	56.00	36.30	0.38	10.18	QP
6	0.549	37.16	-8.84	46.00	26.60	0.38	10.18	Average
7	0.641	41.86	-14.14	56.00	31.30	0.38	10.18	QP
8	0.641	33.16	-12.84	46.00	22.60	0.38	10.18	Average
9	1.043	41.39	-14.61	56.00	30.80	0.40	10.19	QP
10	1.043	32.19	-13.81	46.00	21.60	0.40	10.19	Average
11	1.289	41.19	-14.81	56.00	30.60	0.40	10.19	QP
12	1.289	31.79	-14.21	46.00	21.20	0.40	10.19	Average
13	1.396	41.19	-14.81	56.00	30.60	0.40	10.19	QP
14	1.396	31.89	-14.11	46.00	21.30	0.40	10.19	Average
15	1.636	41.89	-14.11	56.00	31.29	0.41	10.19	QP
16	1.636	33.79	-12.21	46.00	23.19	0.41	10.19	Average
17	1.878	41.90	-14.10	56.00	31.30	0.41	10.19	QP



Test Mode :	Mode 4	Temperature :	22~24°C
Test Engineer :	Amos Zhang	Relative Humidity :	42~46%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Function Type :	LTE Band 4 Idle + Bluetooth Idle + WLAN Idle (2.4G) + USB Cable (Charging from Adapter) + Earphone + Glonass Rx		




Site : CO01-KS
 Condition : FCC CLASS-B LISN-N-161017-060103 NEUTRAL
 Project : (FC) 740701
 mode : Mode 4
 : 864650030003963 #9

	Freq	Level	Over	Limit	Read	LISN	Cable	
	MHz	dBuV	Limit	Line	Level	Factor	Loss	Remark
			dB	dBuV	dBuV	dB	dB	
18	1.878	33.80	-12.20	46.00	23.20	0.41	10.19	Average
19	2.088	42.20	-13.80	56.00	31.60	0.41	10.19	QP
20	2.088	33.80	-12.20	46.00	23.20	0.41	10.19	Average
21	2.487	42.81	-13.19	56.00	32.21	0.40	10.20	QP
22	2.487	34.21	-11.79	46.00	23.61	0.40	10.20	Average
23	2.707	42.91	-13.09	56.00	32.30	0.40	10.21	QP
24	2.707	33.81	-12.19	46.00	23.20	0.40	10.21	Average
25	3.074	43.22	-12.78	56.00	32.60	0.40	10.22	QP
26	3.074	34.52	-11.48	46.00	23.90	0.40	10.22	Average
27	3.528	43.92	-12.08	56.00	33.30	0.39	10.23	QP
28	3.528	34.92	-11.08	46.00	24.30	0.39	10.23	Average
29	4.049	44.13	-11.87	56.00	33.50	0.39	10.24	QP
30	4.049	35.23	-10.77	46.00	24.60	0.39	10.24	Average
31	4.900	44.52	-11.48	56.00	33.90	0.38	10.24	QP
32	4.900	35.92	-10.08	46.00	25.30	0.38	10.24	Average
33	6.024	45.21	-14.79	60.00	34.60	0.35	10.26	QP
34	6.024	36.21	-13.79	50.00	25.60	0.35	10.26	Average
35	6.592	44.91	-15.09	60.00	34.30	0.34	10.27	QP
36	6.592	35.91	-14.09	50.00	25.30	0.34	10.27	Average
37	7.566	44.82	-15.18	60.00	34.20	0.32	10.30	QP
38	7.566	35.82	-14.18	50.00	25.20	0.32	10.30	Average



Test Mode :	Mode 5	Temperature :	22~24℃
Test Engineer :	Amos Zhang	Relative Humidity :	42~46%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Function Type :	LTE Band 2 Idle + Bluetooth Idle + WLAN Idle (2.4G) + USB Cable (Data Link with Notebook) + Earphone + GPS Rx		




Site : CO01-KS
 Condition : FCC CLASS-B LISN-L-161017-060103 LINE
 Project : (FC) 740701
 mode : Mode 5
 : 864650030003963 #9

	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.159	38.08	-27.44	65.52	27.21	0.49	10.38	QP
2	0.159	26.48	-29.04	55.52	15.61	0.49	10.38	Average
3	0.170	36.39	-28.55	64.94	25.60	0.42	10.37	QP
4	0.170	31.09	-23.85	54.94	20.30	0.42	10.37	Average
5	0.447	36.66	-20.27	56.93	26.20	0.27	10.19	QP
6	0.447	32.06	-14.87	46.93	21.60	0.27	10.19	Average
7	0.481	35.66	-20.66	56.32	25.20	0.27	10.19	QP
8 *	0.481	33.36	-12.96	46.32	22.90	0.27	10.19	Average
9	1.790	31.61	-24.39	56.00	21.20	0.22	10.19	QP
10	1.790	24.01	-21.99	46.00	13.60	0.22	10.19	Average
11	4.746	33.65	-22.35	56.00	23.20	0.21	10.24	QP
12	4.746	27.65	-18.35	46.00	17.20	0.21	10.24	Average



Test Mode :	Mode 5	Temperature :	22~24℃
Test Engineer :	Amos Zhang	Relative Humidity :	42~46%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Function Type :	LTE Band 2 Idle + Bluetooth Idle + WLAN Idle (2.4G) + USB Cable (Data Link with Notebook) + Earphone + GPS Rx		



Site : CO01-KS
Condition : FCC CLASS-B LISN-N-161017-060103 NEUTRAL
Project : (FC) 740701
mode : Mode 5
: 864650030003963 #9

	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.157	38.32	-27.28	65.60	27.60	0.34	10.38	QP
2	0.157	27.92	-27.68	55.60	17.20	0.34	10.38	Average
3	0.169	37.01	-28.02	65.03	26.30	0.34	10.37	QP
4	0.169	27.01	-28.02	55.03	16.30	0.34	10.37	Average
5	0.474	37.47	-18.98	56.45	26.90	0.38	10.19	QP
6 *	0.474	34.17	-12.28	46.45	23.60	0.38	10.19	Average
7	1.753	32.20	-23.80	56.00	21.60	0.41	10.19	QP
8	1.753	29.20	-16.80	46.00	18.60	0.41	10.19	Average
9	2.309	32.90	-23.10	56.00	22.29	0.41	10.20	QP
10	2.309	25.90	-20.10	46.00	15.29	0.41	10.20	Average
11	4.772	32.22	-23.78	56.00	21.60	0.38	10.24	QP
12	4.772	27.82	-18.18	46.00	17.20	0.38	10.24	Average

3.2. Test of Radiated Emission Measurement

3.2.1. Limit of Radiated Emission

The emissions from an unintentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.2.2. Measuring Instruments


The measuring equipment is listed in the section 4 of this test report.

3.2.3. Test Procedures


1. The EUT was placed on a turntable with 0.8 meter above ground.
2. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
3. The table was rotated 360 degrees to determine the position of the highest radiation.
4. The antenna is a Bi-Log antenna and its height is adjusted between one to four meters above ground to find the maximum value of the field strength for both horizontal polarization and vertical polarization of the antenna.
5. For each suspected emission, the EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading.
6. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode (RBW=120kHz/VBW=300kHz for frequency below 1GHz; RBW=1MHz VBW=3MHz (Peak), RBW=1MHz/VBW=10Hz (Average) for frequency above 1GHz).
7. If the emission level of the EUT in peak mode was 3 dB lower than the limit specified, peak values of EUT will be reported. Otherwise, the emission will be repeated by using the quasi-peak method and reported.
8. Emission level (dB μ V/m) = 20 log Emission level (μ V/m)
9. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level

3.2.4. Test Setup of Radiated Emission

For radiated emissions from 30MHz to 1GHz




For radiated emissions above 1GHz





3.2.5. Test Result of Radiated Emission

Test Mode :	Mode 5	Temperature :	22~23°C
Test Engineer :	Leve Zhao	Relative Humidity :	41~42%
Test Distance :	3m	Polarization :	Horizontal
Function Type :	LTE Band 2 Idle + Bluetooth Idle + WLAN Idle (2.4G) + USB Cable (Data Link with Notebook) + Earphone + GPS Rx		




Site : 03CH02-KS
Condition : FCC CLASS-B 3m 966-04 LF ANT HORIZONTAL
Project : (FC)740701
Mode : 5
IMEI : 864650030003963 #9

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	A/Pos	T/Pos	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1	30.00	25.05	-14.95	40.00	29.35	26.30	0.50	31.10	---	---	Peak
2	88.20	28.80	-14.70	43.50	42.19	16.62	0.91	30.92	---	---	Peak
3	165.80	37.42	-6.08	43.50	50.04	16.80	1.54	30.96	100	36	Peak
4	239.52	31.52	-14.48	46.00	43.72	17.43	1.55	31.18	---	---	Peak
5	321.00	37.56	-8.44	46.00	46.99	20.28	1.79	31.50	---	---	Peak
6	468.44	37.92	-8.08	46.00	43.74	23.59	2.19	31.60	---	---	Peak
7	3368.00	40.19	-33.81	74.00	38.55	28.01	5.74	32.11	---	---	Peak
8	4864.00	43.01	-30.99	74.00	37.31	30.97	6.86	32.13	---	---	Peak
9	6680.00	48.57	-25.43	74.00	37.67	34.55	8.27	31.92	---	---	Peak
10	6984.00	48.40	-25.60	74.00	37.54	34.60	8.35	32.09	---	---	Peak
11	7760.00	48.57	-25.43	74.00	35.93	35.80	8.65	31.81	---	---	Peak
12	8544.00	50.20	-23.80	74.00	36.27	36.49	9.13	31.69	---	---	Peak



Test Mode :	Mode 5	Temperature :	22~23°C
Test Engineer :	Leve Zhao	Relative Humidity :	41~42%
Test Distance :	3m	Polarization :	Vertical
Function Type :	LTE Band 2 Idle + Bluetooth Idle + WLAN Idle (2.4G) + USB Cable (Data Link with Notebook) + Earphone + GPS Rx		



Site : 03CH02-KS
Condition : FCC CLASS-B 3m 966-04 LF ANT VERTICAL
Project : (FC)740701
Mode : 5
IMEI : 864650030003963 #9

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level Factor	Cable Loss	Preamp Factor	A/Pos	T/Pos	Remark	
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1	47.46	28.32	-11.68	40.00	42.71	16.40	0.66	31.45	---	---	Peak
2 !	165.80	37.58	-5.92	43.50	50.20	16.80	1.54	30.96	---	---	Peak
3	224.97	30.34	-15.66	46.00	43.18	16.80	1.51	31.15	---	---	Peak
4 !	469.41	40.54	-5.46	46.00	46.34	23.61	2.19	31.60	---	---	Peak
5	597.45	37.60	-8.40	46.00	41.18	25.46	2.46	31.50	---	---	Peak
6 !	719.67	42.86	-3.14	46.00	44.01	27.00	2.71	30.86	100	36	Peak
7	3320.00	40.30	-33.70	74.00	39.09	27.76	5.71	32.26	---	---	Peak
8	5064.00	44.02	-29.98	74.00	38.01	31.21	6.91	32.11	---	---	Peak
9	6192.00	45.35	-28.65	74.00	37.05	33.01	7.74	32.45	---	---	Peak
10	7008.00	48.72	-25.28	74.00	37.87	34.60	8.35	32.10	---	---	Peak
11	7768.00	49.01	-24.99	74.00	36.37	35.80	8.65	31.81	---	---	Peak
12	8704.00	49.16	-24.84	74.00	35.16	36.46	9.20	31.66	---	---	Peak



4. List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
EMI Test Receiver	R&S	ESR7	101403	9kHz~7GHz;Max 30dBm	Aug. 09, 2016	May 20, 2017	Aug. 08, 2017	Radiation (03CH02-KS)
EXA Spectrum Analyzer	Keysight	N9010A	MY55150208	10Hz-44G,MAX 30dB	Apr.18, 2017	May 20, 2017	Apr. 17, 2018	Radiation (03CH02-KS)
Bilog Antenna	TeseQ	CBL6112D	37879	30MHz-2GHz	Aug. 20, 2016	May 20, 2017	Aug. 19, 2017	Radiation (03CH02-KS)
Double Ridge Horn Antenna	ETS-Lindgren	3117	75957	1GHz~18GHz	Oct. 22, 2016	May 20, 2017	Oct. 21, 2017	Radiation (03CH02-KS)
Amplifier	SONOMA	310N	187289	9KHz-1GHz	Aug. 09, 2016	May 20, 2017	Aug. 08, 2017	Radiation (03CH02-KS)
Amplifier	Agilent	8449B	3008A02384	1-26.5GHz Gain 30dB	Oct. 13, 2016	May 20, 2017	Oct. 12, 2017	Radiation (03CH02-KS)
AC Power Source	Chroma	61601	616010002473	N/A	NCR	May 20, 2017	NCR	Radiation (03CH02-KS)
Turn Table	MF	MF7802	N/A	0~360 degree	NCR	May 20, 2017	NCR	Radiation (03CH02-KS)
Antenna Mast	MF	MF7802	N/A	1 m~4 m	NCR	May 20, 2017	NCR	Radiation (03CH02-KS)
EMI Receiver	R&S	ESC17	100768	9kHz~7GHz;	Apr. 20, 2017	May 01, 2017	Apr. 19, 2018	Conduction (CO01-KS)
AC LISN	MessTec	AN3016	060103	9kHz~30MHz	Oct. 13, 2016	May 01, 2017	Oct. 13, 2017	Conduction (CO01-KS)
AC LISN (for auxiliary equipment)	MessTec	AN3016	060105	9kHz~30MHz	Oct. 13, 2016	May 01, 2017	Oct. 13, 2017	Conduction (CO01-KS)
AC Power Source	Chroma	61602	ABP000000811	AC 0V~300V, 45Hz~1000Hz	Oct. 13, 2016	May 01, 2017	Oct. 13, 2017	Conduction (CO01-KS)

NCR: No Calibration Required

5. Uncertainty of Evaluation

Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	2.3 dB
---	--------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.2 dB
---	--------

Uncertainty of Radiated Emission Measurement (1GHz ~ 18GHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	4.7 dB
---	--------