



RF TEST REPORT

Applicant ZTE Corporation

FCC ID SRQ-ZM8300G

Product NB-IoT/eMTC Module

Brand ZTE

Model ZM8300G

Report No. RXA1709-0333RF04R1

Issue Date November 14, 2017

TA Technology (Shanghai) Co., Ltd. tested the above equipment in accordance with the requirements in **FCC CFR47 Part 2 (2017)/ FCC CFR 47 Part 22H (2017)**. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

Performed by: Jiangpeng Lan

Approved by: Kai Xu

TA Technology (Shanghai) Co., Ltd.

No.145, Jintang Rd, Tangzhen Industry Park, Pudong Shanghai, China

TEL: +86-021-50791141/2/3

FAX: +86-021-50791141/2/3-8000



TABLE OF CONTENT

1. Test Laboratory	4
1.1. Notes of the Test Report	4
1.2. Test facility	4
1.3. Testing Location.....	5
2. General Description of Equipment under Test.....	6
3. Applied Standards	7
4. Test Configuration	8
5. Test Case Results	9
5.1. RF Power Output	9
5.2. Effective Radiated Power	11
5.3. Occupied Bandwidth	14
5.4. Band Edge Compliance	17
5.5. Peak-to-Average Power Ratio (PAPR).....	24
5.6. Frequency Stability.....	26
5.7. Spurious Emissions at Antenna Terminals.....	29
5.8. Radiates Spurious Emission	34
6. Main Test Instruments.....	43
ANNEX A: EUT Appearance and Test Setup	44
A.1 EUT Appearance.....	44
A.2 Test Setup.....	46



Summary of measurement results

No.	Test Type	Clause in FCC rules	Verdict
1	RF power output	2.1046	PASS
2	Effective Radiated Power	22.913(a)(2)	PASS
3	Occupied Bandwidth	2.1049	PASS
4	Band Edge Compliance	2.1051 / 22.917(a)	PASS
5	Peak-to-Average Power Ratio	22.913(d)/ KDB 971168 D01(5.7)	PASS
6	Frequency Stability	2.1055 / 22.355	PASS
7	Spurious Emissions at Antenna Terminals	2.1051 / 22.917(a)	PASS
8	Radiates Spurious Emission	2.1053 / 22.917 (a)	PASS

Date of Testing: October 20 2017~ November 1, 2017

Note: PASS: The EUT complies with the essential requirements in the standard.
FAIL: The EUT does not comply with the essential requirements in the standard.



1. Test Laboratory

1.1. Notes of the Test Report

This report shall not be reproduced in full or partial, without the written approval of **TA technology (shanghai) co., Ltd.** The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein .Measurement Uncertainties were not taken into account and are published for informational purposes only. This report is written to support regulatory compliance of the applicable standards stated above. This report must not be used by the client to claim product certification, approval, or endorsement by any government agencies.

1.2. Test facility

CNAS (accreditation number: L2264)

TA Technology (Shanghai) Co., Ltd. has obtained the accreditation of China National Accreditation Service for Conformity Assessment (CNAS).

FCC (Designation number: CN1179, Test Firm Registration Number: 446626)

TA Technology (Shanghai) Co., Ltd. has been listed on the US Federal Communications Commission list of test facilities recognized to perform electromagnetic emissions measurements.

IC (recognition number is 8510A)

TA Technology (Shanghai) Co., Ltd. has been listed by industry Canada to perform electromagnetic emission measurement.

VCCI (recognition number is C-4595, T-2154, R-4113, G-10766)

TA Technology (Shanghai) Co., Ltd. has been listed by industry Japan to perform electromagnetic emission measurement.

A2LA (Certificate Number: 3857.01)

TA Technology (Shanghai) Co., Ltd. has been listed by American Association for Laboratory Accreditation to perform electromagnetic emission measurement.



1.3. Testing Location

Company: TA Technology (Shanghai) Co., Ltd.
Address: No.145, Jintang Rd, Tangzhen Industry Park, Pudong
City: Shanghai
Post code: 201201
Country: P. R. China
Contact: Xu Kai
Telephone: +86-021-50791141/2/3
Fax: +86-021-50791141/2/3-8000
Website: <http://www.ta-shanghai.com>
E-mail: xukai@ta-shanghai.com



3. Applied Standards

According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC CFR47 Part 2 (2017)

FCC CFR 47 Part 22H (2017)

ANSI/TIA-603-D (2010)

KDB 971168 D01 Power Meas License Digital Systems v03

5. Test Case Results

5.1. RF Power Output


Ambient condition

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

Methods of Measurement

During the process of the testing, The EUT is controlled by the Base Station Simulator to ensure max power transmission and proper modulation.

Test Setup



The loss between RF output port of the EUT and the input port of the tester has been taken into consideration.

Limits

No specific RF power output requirements in part 2.1046.

Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor k = 2, U= 0.4 dB.



5.2. Effective Radiated Power

Ambient condition

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa


Methods of Measurement

The testing follows FCC KDB 971168 v03 Section 5.8 and ANSI/TIA-603-D-2010.

- a) Connect the equipment as illustrated. Mount the equipment with the manufacturer specified antenna in a vertical orientation on a manufacturer specified mounting surface located on a non-conducting rotating platform of a RF anechoic chamber (preferred) or a standard radiation site.
- b) Key the transmitter, then rotate the EUT 360° azimuthally and record spectrum analyzer power level (LVL) measurements at angular increments that are sufficiently small to permit resolution of all peaks. If a standard radiation test site is used, raise and lower the test antenna to obtain a maximum reading at each angular increment. (Note: several batteries may be needed to offset the effect of battery voltage droop, which should not exceed 5% of the manufactured specified battery voltage during transmission).
- c) Replace the transmitter under test with a vertically polarized half-wave dipole (or an antenna whose gain is known relative to an ideal half-wave dipole). The center of the antenna should be at the same location as the center of the antenna under test.
- d) Connect the antenna to a signal generator with a known output power and record the path loss (in dB) as LOSS. If a standard radiation test site is used, raise and lower the test antenna to obtain a maximum reading.
$$\text{LOSS} = \text{Generator Output Power (dBm)} - \text{Analyzer reading (dBm)}$$
- e) Determine the effective radiated output power at each angular position from the readings in steps b) and d) using the following equation:
$$\text{ERP (dBm)} = \text{LVL (dBm)} + \text{LOSS (dB)}$$
- f) The maximum ERP is the maximum value determined in the preceding step.
- g) When calculating ERP, in addition to knowing the antenna radiation and matching characteristics, it is necessary to know the loss values of all elements (e.g.transmission line attenuation, mismatches, filters, combiners) interposed between the point where transmitter output power is measured, and the point where power is applied to the antenna. ERP can then be calculated as follows:
$$\text{ERP (dBm)} = \text{Output Power (dBm)} - \text{Losses (dB)} + \text{Antenna Gain (dBi)}$$
where:dBi refers to gain relative to an ideal dipole.

$$\text{EIRP (dBm)} = \text{ERP (dBm)} + 2.15 \text{ (dB.)}$$

Test setup



Limits

Rule Part 22.913(a) specifies that "Mobile/portable stations are limited to 7 watts ERP".

Limit	$\leq 7 \text{ W} \quad (38.45 \text{ dBm})$
-------	--

Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor $k = 2$, $U = 1.19 \text{ dB}$

5.3. Occupied Bandwidth

Ambient condition

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa


Method of Measurement

The EUT was connected to Spectrum Analyzer and Base Station Simulator via power Splitter. The occupied bandwidth is measured using spectrum analyzer.

RBW is set to 51 kHz, VBW is set to 160 kHz for LTE Band 5.

99% power and -26dBc occupied bandwidths are recorded. Spectrum analyzer plots are included on the following pages.

Test Setup



Limits

No specific occupied bandwidth requirements in part 2.1049.

Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor $k = 2$, $U = 624\text{Hz}$.



LTE Band 5 16QAM 1.4MHz CH-Middle



LTE Band 5 16QAM 3MHz CH-Middle



LTE Band 5 16QAM 5MHz CH-Middle



LTE Band 5 16QAM 10MHz CH-Middle



5.4. Band Edge Compliance


Ambient condition

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

Method of Measurement

The EUT was connected to Spectrum Analyzer and Base Station Simulator via power Splitter. The band edge of the lowest and highest channels were measured. The average detector is used. RBW is set to 51 kHz, VBW is set to 160 kHz for LTE Band 5. Spectrum analyzer plots are included on the following pages.

Test Setup




Limits

Rule Part 22.917(a) specifies that "The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB."

Limit	-13 dBm
-------	---------


Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor $k = 1.96$, $U=0.684\text{dB}$.


**Test Result:**



LTE Band 5 16QAM 10MHz CH-Low 100%RB



LTE Band 5 16QAM 10MHz CH-High 100%RB



5.5. Peak-to-Average Power Ratio (PAPR)

Ambient condition


Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

Methods of Measurement

Measure the total peak power and record as P_{Pk} . And measure the total average power and record as P_{Avg} . Both the peak and average power levels must be expressed in the same logarithmic units (e.g., dBm). Determine the PAPR from:

$$\text{PAPR (dB)} = P_{Pk} (\text{dBm}) - P_{Avg} (\text{dBm}).$$

Test Setup



Limits

According to the Sec. 22.913(d), The peak-to-average ratio (PAR) of the transmission must not exceed 13 dB.

Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor $k = 2$, $U = 0.4$ dB.

**Test Results**

Mode	Bandwidth	Modulation	Channel/ Frequency(MHz)	Peak-to-Average Power Ratio (PAPR)		
				Peak(dBm)	Avg(dBm)	PAPR(dB)
Band5	1.4MHz	QPSK	20525/836.5	32.83	23.05	9.78
		16QAM	20525/836.5	32.97	22.55	10.42
	3MHz	QPSK	20525/836.5	33.32	23.41	9.91
		16QAM	20525/836.5	32.21	21.67	10.54
	5MHz	QPSK	20525/836.5	32.90	23.03	9.87
		16QAM	20525/836.5	33.93	23.59	10.34
	10MHz	QPSK	20525/836.5	32.73	23.51	9.22
		16QAM	20525/836.5	32.65	22.98	9.67

5.6. Frequency Stability

Ambient condition

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

Method of Measurement

1. Frequency Stability (Temperature Variation)

The temperature inside the climate chamber is varied from -30°C to +50°C in 10°C step size,

(1) With all power removed, the temperature was decreased to 0°C and permitted to stabilize for three hours.

(2) Measure the carrier frequency with the test equipment in a “call mode”. These measurements should be made within 1 minute of powering up the mobile station, to prevent significant self warming.

(3) Repeat the above measurements at 10°C increments from -30°C to +50°C. Allow at least 1.5 hours at each temperature, un-powered, before making measurements. Frequency Stability (Voltage Variation)


The frequency stability shall be measured with variation of primary supply voltage as follows:

(1) Vary primary supply voltage from 85 to 115 percent of the nominal value for other than hand carried battery equipment.

(2) For hand carried, battery powered equipment, reduce primary supply voltage to the battery-operating end point which shall be specified by the manufacturer.

This transceiver is specified to operate with an input voltage of between 3.0 V and 4.2 V, with a nominal voltage of 3.6V.

Test setup





Limits

According to the Sec. 22.355, the frequency stability of the carrier shall be accurate to within 2.5 ppm of the received frequency for mobile stations.

Limits	≤ 2.5 ppm
--------	-----------

Measurement Uncertainty

The assessed measurement uncertainty to ensure 99.75% confidence level for the normal distribution is with the coverage factor $k = 3$, $U = 0.01\text{ppm}$.

Test Result

Mode	Bandwidth	Channel/ Frequency(MHz)	Test status	Frequency Stability (ppm)	
				QPSK	16QAM
Band5	1.4MHz	20525/836.5	-40°C/Normal Voltage	-0.00080	0.00166
		20525/836.5	-30°C/Normal Voltage	-0.00365	-0.00405
		20525/836.5	-20°C/Normal Voltage	-0.00143	-0.00207
		20525/836.5	-10°C/Normal Voltage	-0.00059	-0.00130
		20525/836.5	0°C/Normal Voltage	-0.00154	-0.00279
		20525/836.5	10°C/Normal Voltage	-0.00004	-0.00123
		20525/836.5	20°C/Normal Voltage	-0.00299	-0.00274
		20525/836.5	30°C/Normal Voltage	-0.00253	-0.00063
		20525/836.5	40°C/Normal Voltage	-0.00190	-0.00087
		20525/836.5	50°C/Normal Voltage	-0.00317	-0.00219
		20525/836.5	60°C/Normal Voltage	-0.00147	-0.00126
		20525/836.5	70°C/Normal Voltage	-0.00151	-0.00066
		20525/836.5	80°C/Normal Voltage	-0.00018	-0.00032
		20525/836.5	85°C/Normal Voltage	-0.00031	-0.00073
	3MHz	20525/836.5	20°C/Minimum Voltage	-0.00184	-0.00265
		20525/836.5	20°C/Maximum Voltage	-0.00104	-0.00135



	5MHz	20525/836.5	70°C/Normal Voltage	-0.00127	-0.00274
		20525/836.5	80°C/Normal Voltage	-0.00019	-0.00020
		20525/836.5	85°C/Normal Voltage	-0.00069	-0.00012
		20525/836.5	20°C/Minimum Voltage	0.00017	-0.00378
		20525/836.5	20°C/Maximum Voltage	-0.00195	-0.00241
	10MHz	20525/836.5	-40°C/Normal Voltage	-0.00250	-0.00202
		20525/836.5	-30°C/Normal Voltage	-0.00255	-0.00123
		20525/836.5	-20°C/Normal Voltage	-0.00005	-0.00479
		20525/836.5	-10°C/Normal Voltage	-0.00159	-0.00109
		20525/836.5	0°C/Normal Voltage	-0.00179	-0.00198
		20525/836.5	10°C/Normal Voltage	-0.00012	-0.00289
		20525/836.5	20°C/Normal Voltage	0.00080	-0.00549
		20525/836.5	30°C/Normal Voltage	-0.00047	-0.00355
		20525/836.5	40°C/Normal Voltage	-0.00307	-0.00295
		20525/836.5	50°C/Normal Voltage	-0.00175	-0.00597
		20525/836.5	60°C/Normal Voltage	-0.00109	-0.00006
		20525/836.5	70°C/Normal Voltage	-0.00153	-0.00060
		20525/836.5	80°C/Normal Voltage	-0.00047	-0.00067
		20525/836.5	85°C/Normal Voltage	-0.00018	-0.00311
		20525/836.5	20°C/Minimum Voltage	-0.00171	-0.00341
		20525/836.5	20°C/Maximum Voltage	0.00259	-0.00537

5.7. Spurious Emissions at Antenna Terminals


Ambient condition

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

Method of Measurement

The EUT was connected to Spectrum Analyzer and Base Station Simulator via power Splitter. The measurement is carried out using a spectrum analyzer. The spectrum analyzer scans from 9kHz to the 10th harmonic of the carrier. The peak detector is used. RBW are set to 100 kHz and VBW are set to 300 kHz for below 1G, RBW are set to 1MHz and VBW are set to 3MHz for above 1G, Sweep is set to ATUO.

Test setup



Limits

Rule Part 22.917(a) specifies that "The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB."

Limit	-13 dBm

Measurement Uncertainty

The assessed measurement uncertainty to ensure 99.75% confidence level for the normal distribution is with the coverage factor $k = 1.96$.

Frequency	Uncertainty
100kHz-2GHz	0.684 dB
2GHz-12.75GHz	1.407 dB




Test Result

Sweep from 9 kHz to 30MHz, and the emissions more than 20 dB below the permissible value are not reported.


If disturbances were found more than 20dB below limit line, the mark is not required for the EUT.

The signal beyond the limit is carrier.







LTE Band 5 3MHz CH-Low 30MHz~1.5GHz




LTE Band 5 3MHz CH-Low 1.5GHz~9GHz




LTE Band 5 3MHz CH-Middle 30MHz~1.5GHz




LTE Band 5 3MHz CH-Middle 1.5GHz~9GHz



LTE Band 5 3MHz CH-High 30MHz~1.5GHz




LTE Band 5 3MHz CH-High 1.5GHz~9GHz







LTE Band 5 5MHz CH-Low 30MHz~1.5GHz




LTE Band 5 5MHz CH-Low 1.5GHz~9GHz




LTE Band 5 5MHz CH-Middle 30MHz~1.5GHz




LTE Band 5 5MHz CH-Middle 1.5GHz~9GHz



LTE Band 5 5MHz CH-High 30MHz~1.5GHz




LTE Band 5 5MHz CH-High 1.5GHz~9GHz







LTE Band 5 10MHz CH-Low 30MHz~1.5GHz




LTE Band 5 10MHz CH-Low 1.5GHz~9GHz




LTE Band 5 10MHz CH-Middle 30MHz~1.5GHz




LTE Band 5 10MHz CH-Middle 1.5GHz~9GHz



LTE Band 5 10MHz CH-High 30MHz~1.5GHz



LTE Band 5 10MHz CH-High 1.5GHz~9GHz





5.8. Radiates Spurious Emission

Ambient condition

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

Method of Measurement

1. The testing follows FCC KDB 971168 v03 Section 5.8 and ANSI/TIA-603-D-2010.
2. The EUT is placed on a turntable 0.8 meters above the ground in the chamber, 3 meter away from the antenna. The maximal emission value is acquired by adjusting the antenna height, polarisation and turntable azimuth. Normally, the height range of antenna is 1 m to 4 m, the azimuth range of turntable is 0° to 360°, and the receive antenna has two polarizations Vertical (V) and Horizontal (H).
3. A log-periodic antenna or double-ridged waveguide horn antenna shall be substituted in place of the EUT. The log-periodic antenna will be driven by a signal generator and the level will be adjusted till the same power value on the spectrum analyzer or receiver. The level of the spurious emissions can be calculated through the level of the signal generator, cable loss, the gain of the substitution antenna and the reading of the spectrum analyzer or receiver.
4. The EUT is then put into continuously transmitting mode at its maximum power level during the test. Set Test Receiver or Spectrum RBW=1MHz, VBW=3MHz for above 1GHz and RBW=100kHz, VBW=300kHz for 30MHz to 1GHz, And the maximum value of the receiver should be recorded as (Pr).
5. The EUT shall be replaced by a substitution antenna. In the chamber, an substitution antenna for the frequency band of interest is placed at the reference point of the chamber. An RF Signal source for the frequency band of interest is connected to the substitution antenna with a cable that has been constructed to not interfere with the radiation pattern of the antenna. A power (PMea) is applied to the input of the substitution antenna, and adjust the level of the signal generator output until the value of the receiver reach the previously recorded (Pr). The power of signal source (PMea) is recorded. The test should be performed by rotating the test item and adjusting the receiving antenna polarization.
6. A amplifier should be connected to the Signal Source output port. And the cable should be connect between the Amplifier and the Substitution Antenna. The cable loss (Pcl), the Substitution Antenna Gain (Ga) and the Amplifier Gain (PAg) should be recorded after test.
7. The measurement results are obtained as described below:

$$\text{Power(EIRP)} = \text{PMea} - \text{PAg} - \text{Pcl} + \text{Ga}$$


The measurement results are amend as described below:

$$\text{Power(EIRP)} = \text{PMea} - \text{Pcl} + \text{Ga}$$


8. This value is EIRP since the measurement is calibrated using an antenna of known gain (2.15 dBi) and known input power. ERP can be calculated from EIRP by subtracting the gain of the dipole, ERP = EIRP-2.15dBi.

Test setup

30MHz~~~ 1GHz



Above 1GHz



Note: Area side:2.4mX3.6m

Limits

Rule Part 22.917(a) specifies that "The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB."

Limit	-13 dBm
-------	---------

Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor $k = 1.96$, $U = 3.55$ dB.

**Test Result****LTE Band 5 1.4MHz CH-Low**

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	ERP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	1649.4	-59.30	2.00	10.75	Horizontal	-52.70	-13.00	39.70	270.00
3	2474.1	-50.29	2.51	11.05	Horizontal	-43.90	-13.00	30.90	45.00
4	3298.8	-55.96	4.20	11.15	Horizontal	-51.16	-13.00	38.16	180.00
5	4123.5	-52.25	5.20	11.15	Horizontal	-48.45	-13.00	35.45	135.00
6	4948.2	-53.07	5.50	11.95	Horizontal	-48.77	-13.00	35.77	0.00
7	5772.9	-53.87	5.70	13.55	Horizontal	-48.17	-13.00	35.17	315.00
8	6597.6	-51.14	6.30	13.75	Horizontal	-45.84	-13.00	32.84	180.00
9	7422.3	-47.43	6.80	13.85	Horizontal	-42.53	-13.00	29.53	225.00
10	8247.0	-47.95	6.90	14.25	Horizontal	-42.75	-13.00	29.75	0.00

Note: 1.The other Spurious RF Radiated emissions level is no more than noise floor.

2.The worst emission was found in the antenna is Horizontal position.

LTE Band 5 1.4MHz CH-Middle

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	ERP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	1673.0	-58.90	2.00	10.75	Horizontal	-52.30	-13.00	39.30	225.00
3	2509.5	-48.29	2.51	11.05	Horizontal	-41.90	-13.00	28.90	270.00
4	3346.0	-57.04	4.20	11.15	Horizontal	-52.24	-13.00	39.24	180.00
5	4182.5	-53.26	5.20	11.15	Horizontal	-49.46	-13.00	36.46	135.00
6	5019.0	-51.53	5.50	11.95	Horizontal	-47.23	-13.00	34.23	0.00
7	5855.5	-52.84	5.70	13.55	Horizontal	-47.14	-13.00	34.14	315.00
8	6692.0	-49.65	6.30	13.75	Horizontal	-44.35	-13.00	31.35	180.00
9	7528.5	-47.89	6.80	13.85	Horizontal	-42.99	-13.00	29.99	225.00
10	8365.0	-48.81	6.90	14.25	Horizontal	-43.61	-13.00	30.61	0.00

Note: 1.The other Spurious RF Radiated emissions level is no more than noise floor.

2.The worst emission was found in the antenna is Horizontal position.



LTE Band 5 3MHz CH-Middle

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	ERP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	1670.3	-58.40	2.00	10.75	Horizontal	-51.80	-13.00	38.80	270.00
3	2509.5	-50.59	2.51	11.05	Horizontal	-44.20	-13.00	31.20	45.00
4	3346.0	-57.66	4.20	11.15	Horizontal	-52.86	-13.00	39.86	180.00
5	4182.5	-54.73	5.20	11.15	Horizontal	-50.93	-13.00	37.93	135.00
6	5019.0	-50.87	5.50	11.95	Horizontal	-46.57	-13.00	33.57	0.00
7	5855.5	-51.70	5.70	13.55	Horizontal	-46.00	-13.00	33.00	315.00
8	6692.0	-50.67	6.30	13.75	Horizontal	-45.37	-13.00	32.37	180.00
9	7528.5	-47.05	6.80	13.85	Horizontal	-42.15	-13.00	29.15	225.00
10	8365.0	-48.02	6.90	14.25	Horizontal	-42.82	-13.00	29.82	0.00

Note: 1.The other Spurious RF Radiated emissions level is no more than noise floor.

2.The worst emission was found in the antenna is Horizontal position.



LTE Band 5 3MHz CH-High

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	ERP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	1692.5	-59.40	2.00	10.75	Horizontal	-52.80	-13.00	39.80	180.00
3	2542.5	-50.69	2.51	11.05	Horizontal	-44.30	-13.00	31.30	45.00
4	3390.0	-57.29	4.20	11.15	Horizontal	-52.49	-13.00	39.49	180.00
5	4237.5	-54.04	5.20	11.15	Horizontal	-50.24	-13.00	37.24	135.00
6	5085.0	-52.06	5.50	11.95	Horizontal	-47.76	-13.00	34.76	0.00
7	5932.5	-52.58	5.70	13.55	Horizontal	-46.88	-13.00	33.88	315.00
8	6780.0	-51.42	6.30	13.75	Horizontal	-46.12	-13.00	33.12	180.00
9	7627.5	-47.13	6.80	13.85	Horizontal	-42.23	-13.00	29.23	225.00
10	8475.0	-48.24	6.90	14.25	Horizontal	-43.04	-13.00	30.04	0.00

Note: 1.The other Spurious RF Radiated emissions level is no more than noise floor.

2.The worst emission was found in the antenna is Horizontal position.

LTE Band 5 5MHz CH-Low

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	ERP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	1649.6	-59.10	2.00	10.75	Horizontal	-52.50	-13.00	39.50	45.00
3	2479.5	-56.69	2.51	11.05	Horizontal	-50.30	-13.00	37.30	135.00
4	3306.0	-57.04	4.20	11.15	Horizontal	-52.24	-13.00	39.24	180.00
5	4132.5	-54.76	5.20	11.15	Horizontal	-50.96	-13.00	37.96	135.00
6	4959.0	-52.36	5.50	11.95	Horizontal	-48.06	-13.00	35.06	0.00
7	5785.5	-53.62	5.70	13.55	Horizontal	-47.92	-13.00	34.92	315.00
8	6612.0	-50.32	6.30	13.75	Horizontal	-45.02	-13.00	32.02	180.00
9	7438.5	-46.06	6.80	13.85	Horizontal	-41.16	-13.00	28.16	225.00
10	8265.0	-47.53	6.90	14.25	Horizontal	-42.33	-13.00	29.33	0.00

Note: 1.The other Spurious RF Radiated emissions level is no more than noise floor.

2.The worst emission was found in the antenna is Horizontal position.



LTE Band 5 5MHz CH-Middle

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	ERP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	1673.0	-58.00	2.00	10.75	Horizontal	-51.40	-13.00	38.40	225.00
3	2509.5	-51.69	2.51	11.05	Horizontal	-45.30	-13.00	32.30	90.00
4	3346.0	-57.42	4.20	11.15	Horizontal	-52.62	-13.00	39.62	180.00
5	4182.5	-54.38	5.20	11.15	Horizontal	-50.58	-13.00	37.58	135.00
6	5019.0	-51.67	5.50	11.95	Horizontal	-47.37	-13.00	34.37	0.00
7	5855.5	-53.10	5.70	13.55	Horizontal	-47.40	-13.00	34.40	315.00
8	6692.0	-50.18	6.30	13.75	Horizontal	-44.88	-13.00	31.88	180.00
9	7528.5	-48.16	6.80	13.85	Horizontal	-43.26	-13.00	30.26	225.00
10	8365.0	-49.26	6.90	14.25	Horizontal	-44.06	-13.00	31.06	0.00

Note: 1.The other Spurious RF Radiated emissions level is no more than noise floor.

2.The worst emission was found in the antenna is Horizontal position.

LTE Band 5 5MHz CH-High

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	ERP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	1693.0	-56.90	2.00	10.75	Horizontal	-50.30	-13.00	37.30	270.00
3	2539.5	-53.79	2.51	11.05	Horizontal	-47.40	-13.00	34.40	45.00
4	3386.0	-57.87	4.20	11.15	Horizontal	-53.07	-13.00	40.07	180.00
5	4232.5	-53.64	5.20	11.15	Horizontal	-49.84	-13.00	36.84	135.00
6	5079.0	-52.86	5.50	11.95	Horizontal	-48.56	-13.00	35.56	0.00
7	5925.5	-52.36	5.70	13.55	Horizontal	-46.66	-13.00	33.66	315.00
8	6772.0	-49.96	6.30	13.75	Horizontal	-44.66	-13.00	31.66	180.00
9	7618.5	-48.13	6.80	13.85	Horizontal	-43.23	-13.00	30.23	225.00
10	8465.0	-48.58	6.90	14.25	Horizontal	-43.38	-13.00	30.38	0.00

Note: 1.The other Spurious RF Radiated emissions level is no more than noise floor.

2.The worst emission was found in the antenna is Horizontal position.



LTE Band 5 10MHz CH-High

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	ERP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	1688.0	-56.70	2.00	10.75	Horizontal	-50.10	-13.00	37.10	135.00
3	2532.0	-50.09	2.51	11.05	Horizontal	-43.70	-13.00	30.70	225.00
4	3376.0	-58.13	4.20	11.15	Horizontal	-53.33	-13.00	40.33	180.00
5	4220.0	-52.49	5.20	11.15	Horizontal	-48.69	-13.00	35.69	135.00
6	5064.0	-51.05	5.50	11.95	Horizontal	-46.75	-13.00	33.75	0.00
7	5908.0	-52.14	5.70	13.55	Horizontal	-46.44	-13.00	33.44	315.00
8	6752.0	-50.17	6.30	13.75	Horizontal	-44.87	-13.00	31.87	180.00
9	7596.0	-48.86	6.80	13.85	Horizontal	-43.96	-13.00	30.96	225.00
10	8440.0	-48.24	6.90	14.25	Horizontal	-43.04	-13.00	30.04	0.00

Note: 1.The other Spurious RF Radiated emissions level is no more than noise floor.

2.The worst emission was found in the antenna is Horizontal position.



6. Main Test Instruments

Name	Manufacturer	Type	Serial Number	Calibration Date	Expiration Time
Base Station Simulator	R&S	CMW500	113645	2017-05-14	2018-05-13
Power Splitter	Hua Xiang	SHX-GF2-2-13	10120101	2017-05-14	2018-05-13
Spectrum Analyzer	Agilent	N9010A	MY47191109	2017-05-20	2018-05-19
Universal Radio Communication Tester	Agilent	E5515C	MY48367192	2017-05-20	2018-05-19
Signal Analyzer	R&S	FSV30	100815	2016-12-16	2017-12-15
EMI Test Receiver	R&S	ESCI	100948	2017-05-20	2018-05-19
Signal generator	R&S	SMB 100A	102594	2017-05-14	2018-05-13
Signal generator	R&S	SMR27	100365	2017-05-14	2018-05-13
Trilog Antenna	SCHWARZBECK	VUBL 9163	9163-201	2014-12-06	2017-12-05
Horn Antenna	R&S	HF907	100126	2014-12-06	2017-12-05
Horn Antenna	ETS-Lindgren	3160-09	00102644	2015-01-30	2018-01-29
Climatic Chamber	Re Ce	PT-30B	20101891	2015-07-18	2018-07-17
RF Cable	Agilent	SMA 15cm	0001	2017-08-04	2018-02-03
Preamplifier	R&S	SCU18	102327	2017-06-18	2018-06-17


*****END OF REPORT*****

ANNEX A: EUT Appearance and Test Setup

A.1 EUT Appearance



Front Side



Back Side





Shield

a: EUT

Picture 1 EUT and Accessory

A.2 Test Setup



Picture 2: Radiated Spurious Emissions Test setup