



# RF TEST REPORT

**Report No.:** SET2020-02148

**Product Name:** LTE/WCDMA/GSM (GPRS) Multi-Mode Digital Mobile Phone

**FCC ID:** SRQ-ZTEA2021L

**Model No. :** ZTE A2021L

**Marketing Name:** ZTE Axon 11

**Applicant:** ZTE Corporation.

**Address:** ZTE Plaza, Keji Road South, Shenzhen, China.

**Dates of Testing:** 02/10/2020 —04/03/2020

**Issued by:** CCIC Southern Testing Co., Ltd.

**Lab Location:** Electronic Testing Building, No. 43 Shahe Road, Xili Street,  
Nanshan District, Shenzhen, Guangdong, China.

**Tel:** 86 755 26627338    **Fax:** 86 755 26627238

This test report consists of 108 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product endorsement by CCIC-SET. The test results in the report only apply to the tested sample. The test report shall be invalid without all the signatures of testing engineers, reviewer and approver. Any objections must be raised to CCIC-SET. within 20 days since the date when the report is received. It will not be taken into consideration beyond this limit.



## Test Report

**Product Name** ..... : LTE/WCDMA/GSM (GPRS) Multi-Mode Digital Mobile  
Phone

**Brand Name** ..... : ZTE

**Trade Name** ..... : ZTE

**Applicant** ..... : ZTE Corporation.

**Applicant Address** ..... : ZTE Plaza, Keji Road South, Shenzhen, China

**Manufacturer** ..... : ZTE Corporation.

**Manufacturer Address** ..... : ZTE Plaza, Keji Road South, Shenzhen, China

**Test Standards** ..... : 47 CFR Part 15 Subpart E 15.407

**Test Result** ..... : PASS

**Tested by** ..... : *Vincent*  
2020.04.03

\_\_\_\_\_  
Vincent, Test Engineer

**Reviewed by** ..... : *Chris You*  
2020.04.03

\_\_\_\_\_  
Chris You, Senior Engineer

**Approved by** ..... : *Shuangwen Zhang*  
2020.04.03

\_\_\_\_\_  
Shuangwen Zhang, Manager



## TABLE OF CONTENTS

**RF TEST REPORT ..... 1**

**1. GENERAL INFORMATION ..... 4**

1.1. EUT Description ..... 4

1.2. Test Standards and Results ..... 5

1.3. Channel List ..... 6

1.4. Test environment and mode ..... 7

1.5. Power level setup in software ..... 9

1.6. Laboratory Facilities ..... 10

**2. 47 CFR PART 15E REQUIREMENTS ..... 11**

2.1. Antenna requirement ..... 11

2.2. Output Power ..... 12

2.3. Emission Bandwidth ..... 15

2.4. Power spectral density (PSD) ..... 17

2.5. Frequency Stability ..... 19

2.6. Radiated Band Edge and Spurious Emission ..... 21

2.7. Conducted Emission ..... 56

**3. LIST OF MEASURING EQUIPMENT ..... 60**

**4. UNCERTAINTY OF EVALUATION ..... 61**

**APPENDIX A ..... 62**

Change History		
Issue	Date	Reason for change
1.0	2020.04.03	First edition

## 1. General Information

### 1.1. EUT Description

EUT Type	LTE/WCDMA/GSM(GPRS) Multi-Mode Digital Mobile Phone
EUT supports Radios application	WLAN5.0GHz 802.11a/n (HT20/40)/ac(VHT20/40/80)
Hardware Version	uqxA
Software Version	TEL_MX_ZTE_A2021LV1.0
Product Type	Indoor
Modulation Type	CCK, DQPSK, DBPSK for DSSS 256QAM, 64QAM,16QAM, QPSK, BPSK for OFDM 256QAM for OFDM in 11ac mode only
Transfer Rate	802.11a: 54/48/36/24/18/12/9/6 Mbps 802.11n : up to 135 Mbps 802.11ac: up to V9
Frequency Range	Band UNII-1: 5150 ~ 5250MHz Band UNII-3: 5725 ~ 5850MHz
Channel Bandwidth	802.11a: 20MHz, 802.11n: 20MHz/40MHz 802.11ac: 20MHz/40MHz/80MHz
Channel Number	5150 MHz ~ 5250MHz/5725 MHz ~ 5850MHz:4/5 for 802.11a, 802.11n(HT20), 802.11ac(VHT20), 2 for 802.11n (HT40), 802.11ac(VHT40), 1 for 802.11ac (VHT80)
Antenna Type	Internal
Output Power (Max.)	Band UNII-1: 13.47 dBm Band UNII-3: 12.74dBm

## 1.2. Test Standards and Results

The objective of the report is to perform testing according to 47 CFR Part 15 Subpart E for the EUT FCC Certification:

No.	Identity	Document Title
1	47 CFR Part 15 Subpart E § 15.407	Radio Frequency Devices
2	KDB Publication 789033D02 V02r01	Guidelines for Compliance Testing of Unlicensed National Information Infrastructure (U-NII) Devices Part 15, Subpart E
6	ANSI C63.10-2013	American National Standard for Testing Unlicensed Wireless Devices

Test detailed items/section required by FCC rules, and results are as below:

No.	FCC Rule	Description	Result
1	15.203	Antenna Requirement	PASS
2	15.407(a)	Maximum Conducted Output Power	PASS
3	15.407(a)	Emission Bandwidth (26 dB Bandwidth)	PASS
	15.407(e)	Emission Bandwidth (6 dB Bandwidth)	PASS
4	15.407(a)	Power spectral density (PSD)	PASS
5	15.207	AC Power Line Conducted Emission	PASS
6	15.209 15.407(b)	Radiated Band Edges and Spurious Emission	PASS
7	15.407(g)	Frequency Stability	PASS

### 1.3. Channel List

#### Operated band in 5150 MHz ~ 5250MHz

4 channels are provided for 802.11a, 802.11n-HT20, and 802.11ac-VHT20

Channel	Frequency	Channel	Frequency
36	5180 MHz	44	5220 MHz
40	5200 MHz	48	5240 MHz

2 channels are provided for 802.11n-HT40 and 802.11ac-VHT40

Channel	Frequency	Channel	Frequency
38	5190 MHz	46	5230 MHz

1 channel are provided for 802.11ac-VHT80

Channel	Frequency	Channel	Frequency
42	5210 MHz	/	/

#### Operated band in 5725 MHz ~ 5850MHz

5 channels are provided for 802.11a

Channel	Frequency	Channel	Frequency
149	5745 MHz	161	5805 MHz
153	5765 MHz	165	5825 MHz
157	5785 MHz	/	/

2 channels are provided for 802.11n-HT40 and 802.11ac-VHT40

Channel	Frequency	Channel	Frequency
151	5755 MHz	159	5795 MHz

1 channel are provided for 802.11ac-VHT80

Channel	Frequency	Channel	Frequency
155	5775 MHz	/	/

## 1.4. Test environment and mode

Operating Environment	
Temperature	24°C
Humidity	57 % RH
Atmospheric Pressure	1010 mbar
Test mode:	
Continuously transmitting mode	Keeps the EUT in 100% duty cycle transmitting with modulation in SISO, duty cycle factor is not required.

We have verified the construction and function in typical operation. All the test modes were carried out with the EUT in transmitting operation, which was shown in this test report and defined as follows:

For Frequency band 5150 ~ 5250 MHz			
Mode	Modulation scheme / bandwidth		
	5180 MHz	5220 MHz	5240 MHz
802.11a	6 Mbps	6 Mbps	6 Mbps
802.11n/ac – HT20	MCS 0	MCS 0	MCS 0
Frequency	5190 MHz		5230 MHz
802.11n/ac – HT40	MCS 0		MCS 0
Frequency	5210 MHz		
802.11ac – VHT80	MCS 0		
For Frequency band 5725 ~ 5850 MHz			
Mode	Modulation scheme / bandwidth		
	5745 MHz	5785 MHz	5825 MHz
802.11a	6 Mbps	6 Mbps	6 Mbps
802.11n/ac – HT20	MCS 0	MCS 0	MCS 0
Frequency	5755 MHz		5795 MHz
802.11n/ac – HT40	MCS 0		MCS 0
Frequency	5775 MHz		
802.11ac – VHT80	MCS 0		

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation modes or test configuration modes mentioned above was evaluated respectively.

Pretest Test Mode	Description
Mode 1	TX A Mode / CH36, CH44, CH48 (UNII-1)
Mode 2	TX N20 Mode / CH36, CH44, CH48 (UNII-1)
Mode 3	TX N40 Mode / CH38, CH46 (UNII-1)
Mode 4	TX AC20 Mode / CH36, CH44, CH48 (UNII-1)
Mode 5	TX AC40 Mode / CH38, CH46 (UNII-1)
Mode 6	TX AC80 Mode / CH42 (UNII-1)
Mode 7	TX A Mode / CH149, CH157, CH165 (UNII-3)
Mode 8	TX N20 Mode / CH149, CH157, CH165 (UNII-3)
Mode 9	TX N40 Mode / CH151, CH159 (UNII-3)
Mode 10	TX AC20 Mode / CH149, CH157, CH165 (UNII-3)
Mode 11	TX AC40 Mode / CH151, CH159 (UNII-3)
Mode 12	TX AC80 Mode / CH155 (UNII-3)
Mode 13	TX Mode

The EUT system operated these modes were found to be the worst case during the pre-scanning test as following:

For Conducted Test	
Final Test Mode	Description
Mode 13	TX Mode
For Radiated Test	
Final Test Mode	Description
Mode 1	TX A Mode / CH36, CH44, CH48 (UNII-1)
Mode 2	TX AC20 Mode / CH36, CH44, CH48 (UNII-1)
Mode 3	TX AC40 Mode / CH38, CH46 (UNII-1)
Mode 4	TX AC80 Mode / CH42 (UNII-1)
Mode 5	TX A Mode / CH149, CH157, CH165 (UNII-3)
Mode 6	TX AC20 Mode / CH149, CH157, CH165 (UNII-3)
Mode 7	TX AC40 Mode / CH151, CH159 (UNII-3)
Mode 8	TX AC80 Mode / CH155 (UNII-3)



## 1.5. Power level setup in software

Power level setup in software for 5G wifi			
UNII-1			
Frequency (MHz)	5180	5220	5240
A mode	15	15	15
Frequency (MHz)	5180	5220	5240
N20 mode	15	15	15
Frequency (MHz)	5190	5230	\
N40 mode	14	14	\
Frequency (MHz)	5180	5220	5240
AC20 mode	15	15	15
Frequency (MHz)	5190	5230	\
AC40 mode	14	14	\
Frequency (MHz)	5210	\	\
AC80 mode	14	\	\
Power level setup in software for 5G wifi			
UNII-3			
Frequency (MHz)	5745	5785	5825
A mode	15	15	15
Frequency (MHz)	5745	5785	5825
N20 mode	15	15	15
Frequency (MHz)	5755	5795	\
N40 mode	14	14	\
Frequency (MHz)	5745	5785	5825
AC20 mode	15	15	15
Frequency (MHz)	5755	5795	\
AC40 mode	14	14	\
Frequency (MHz)	5775	\	\
AC80 mode	14	\	\



## **1.6. Laboratory Facilities**

### **FCC-Registration No.: CN5031**

CCIC Southern Testing Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files. Designation Number: CN5031, valid time is until December 31, 2020.

### **ISED Registration: 11185A-1**

CCIC Southern Testing Co., Ltd. EMC Laboratory has been registered by Certification and Engineering Bureau of Industry Canada for the performance of radiated measurements with Registration No. 11185A-1 on Aug. 04, 2016, valid time is until Dec. 31, 2020.

### **NVLAP Lab Code: 201008-0**

CCIC-SET is a third party testing organization accredited by NVLAP according to ISO/IEC 17025. The accreditation certificate number is 201008-0.

## 2. 47 CFR Part 15E Requirements

### 2.1. Antenna requirement

#### 2.1.1. Applicable Standard

According to FCC 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

And according to FCC 47 CFR Section 15.407(E), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

#### 2.1.2. Antenna Information

Antenna Type	Internal
Antenna Gain	-1.79dBi

#### 2.1.3. Result: comply

The EUT has a permanently and irreplaceable attached antenna. Please refer to the EUT internal photos.

## 2.2. Output Power

### 2.2.1. Limit of Output Power

#### FCC 15.407(a)


The maximum conducted output power should not exceed:

Band	EUT Category	Limit
U-NII-1	<input type="checkbox"/> Outdoor Access Point	1 Watt (30 dBm) (Max. e.i.r.p $\leq$ 125mW(21dBm) at any elevation angle above 30 degrees as measured from the horizon)
	<input type="checkbox"/> Fixed point-to-point Access device	1 Watt (30 dBm)
	<input type="checkbox"/> Indoor Access Point	1 Watt (30 dBm)
	<input checked="" type="checkbox"/> Mobile and portable client device	250mW (24 dBm)
U-NII-2A	<input type="checkbox"/>	250mW (24 dBm) or 11dBm+10logB* Whichever is less.
U-NII-2C	<input type="checkbox"/>	250mW (24 dBm) or 11dBm+10logB* Whichever is less.
U-NII-3	<input checked="" type="checkbox"/>	1 Watt (30 dBm)
Note: B* is the 26 dB emission bandwidth in MHz.		

### 2.2.2. Measuring Instruments

The measuring equipment is listed in the section 3 of this test report.

### 2.2.3. Test Setup



### 2.2.4. Test Procedures

1. The testing follows the Measurement Procedure of FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01 Method SA-1
2. The RF output of EUT was connected to spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Set RBW=1MHz, VBW=3MHz, Sweep time=Auto, Detector=average (RMS), Compute power by integrating the spectrum across the 99%OBW.
5. Measure the conducted output power and record the results in the test report.



### **2.2.5. Test Result**

Please refer to APPENDIX A for detail

## 2.3. Emission Bandwidth

### 2.3.1. Limit of Bandwidth


There is no limit bandwidth for band U-NII-1, U-NII-2A and U-NII-2C.

The minimum of 6dB bandwidth measurement is 0.5 MHz for U-NII-3.

### 2.3.2. Measuring Instruments

The measuring equipment is listed in the section 3 of this test report.

### 2.3.3. Test Setup



### 2.3.4. Test Procedures

1. The testing follows the Measurement Procedure of FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.

2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.

3. Set to the maximum power setting and enable the EUT transmit continuously.

4. For 26dB bandwidth Measurement, the spectrum analyzer's resolution bandwidth (RBW) = approximately 1%EBW, VBW  $\geq$  3RBW, Detector = Peak, Trace mode = max hold  
Span > 26 dB bandwidth and Sweep time = auto

5. Use the spectrum analyzer N dB down function to find the 26dB bandwidth.

6. For 6 Bandwidth Measurement, the spectrum analyzer's resolution bandwidth (RBW) = 100kHz  
VBW = 300 kHz, Detector = Peak, Trace mode = max hold

7. Use the spectrum analyzer N dB down function to find the 6dB bandwidth

8. Measure and record the worst results in the test report.



### **2.3.5. Test Results Bandwidth**

Please refer to APPENDIX A for detail



## 2.4. Power spectral density (PSD)

### 2.4.1. Limit of Power Spectral Density

FCC 15.407(a)


The maximum power spectral density should not exceed:

Band	EUT Category	Limit
U-NII-1	<input type="checkbox"/> Access Point (Master device)	17 dBm/MHz
	<input type="checkbox"/> Fixed point-to-point Access device	
	<input checked="" type="checkbox"/> Mobile and portable client device	11 dBm/MHz
U-NII-2A	<input type="checkbox"/>	11 dBm/MHz
U-NII-2C	<input type="checkbox"/>	11 dBm/MHz
U-NII-3	<input checked="" type="checkbox"/>	30dBm/500kHz

### 2.4.2. Measuring Instruments

The measuring equipment is listed in the section 3 of this test report.

### 2.4.3. Test Setup



### 2.4.4. Test Procedures

1. Place the EUT on the table and set it in transmitting mode.
2. The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.
3. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to Spectrum.

#### 4. For U-NII-1, U-NII-2A, U-NII-2C Band:

Using method SA-1

Set RBW=1MHz, VBW=3MHz, where span is enough to capture the entire bandwidth, Sweep time = Auto, detector = sample, traces 100 sweeps of averaging mode.

#### For U-NII-3 Band:

Set RBW=500 kHz,  $VBW \geq 3RBW$ , where span is enough to capture the entire bandwidth, Sweep time = Auto, detector = sample, traces 100 sweeps of averaging mode.

5. Use peak search function on the instrument to find the peak of the spectrum and record its value
6. Repeat above procedures until all default test channel (low, middle, and high) was complete.



#### **2.4.5. Test Results of Power spectral density**

Please refer to APPENDIX A for detail

## 2.5. Frequency Stability


### 2.5.1. Limit

FCC 15.407(b) Frequency Stability	
Frequency Band(MHz)	Limit
5150~5250	Specified in the user's manual
5250~5350	
5470~5725	
5725~5850	

### 2.5.2. Measuring Instruments

The measuring equipment is listed in the section 3 of this test report.

### 2.5.3. Test Setup



### 2.5.4. Test Procedures

1. The EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
2. Set to the maximum power setting and enable the EUT transmit continuously.
3. The EUT is installed in an environment test chamber with external power source.
4. Set the chamber to operate at 50 centigrade and external power source to output at nominal voltage of EUT.
5. A sufficient stabilization period at each temperatures in used prior to each frequency measurement.
6. The test shall be performed under -10 to 55 centigrade and 85 to 115 percent of the nominal voltage. Change setting of chamber and external power source to complete all conditions.
7. Measure and record the worst results in the test report.



### **2.5.5. Test Results of Frequency Stability**

Please refer to APPENDIX A for detail

## 2.6. Radiated Band Edge and Spurious Emission

### 2.6.1. Limit of Radiated Band Edges and Spurious Emission

Radiated emission which fall in the restricted bands must comply with the radiated emission limits specified as below table. Other emissions shall be at least 20dB below the highest level of the desired power:

Frequency (MHz)	Field Strength ( $\mu\text{V}/\text{m}$ )	Measurement Distance (m)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 - 30.0	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. For frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.

#### Limits of unwanted emission out of the restricted bands

Applicable To	Limit	
789033 D02 General UNII Test Procedures New Rules V02r01	Field Strength at 3m	
	PK:74(dB $\mu\text{V}/\text{m}$ )	AV:54 (dB $\mu\text{V}/\text{m}$ )

Frequency Band (MHz)	Frequency (MHz)	EIRP Limit (dBm)	Equivalent Field Strength (3m) (dB $\mu\text{V}/\text{m}$ )
5150 - 5250	Outside of the 5.15~5.35 GHz	-27	68.2
5250 - 5350	Outside of the 5.15~5.35 GHz		
5470 -5725	Outside of the 5.47~5.725 GHz		

FCC 15.407			
Frequency Band (MHz)	Frequency (MHz)	EIRP Limit (dBm)	Equivalent Field Strength (3m) (dBμV/m)
5725 - 5850	<5650	-27	68.2
	5650~5700	-27~10	68.2~105.2
	5700~5720	10~15.6	105.2~110.8
	5720~5725	15.6~27	110.8~122.2
	5850~5855	27~15.6	122.2~110.8
	5855~5875	15.6~10	110.8~105.2
	5875~5925	10~-27	105.2~68.2
	>5925	-27	68.2

Note: 1. The following formula is used to convert the equipment isotropic radiated power (eirp) to field strength:


$$E = \frac{1000000 \sqrt{30P}}{3} \mu\text{V/m, where } P \text{ is the eirp (Watts).}$$

### 2.6.2. Measuring Instruments


The measuring equipment is listed in the section 3 of this test report.

### 2.6.3. Test Setup


For radiated emissions from 9 KHz to 30 MHz



For radiated emissions from 30MHz to 1GHz



### For radiated emissions above 1GHz



#### 2.6.4. Test Procedures

1. The EUT was placed on the top of a rotating table 0.8 meters (for below 1GHz) / 1.5 meters (for above 1GHz) above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
3. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
5. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
6. The test-receiver system was set to peak and average detects function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.



## Note:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Quasi-peak detection (QP) at frequency below 1 GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 3MHz for RMS Average (Duty cycle < 98%) for Average detection (AV) at frequency above 1GHz, then the measurement results was added to a correction factor ( $10 \log(1/\text{duty cycle})$ ).
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 10Hz (Duty cycle  $\geq 98\%$ ) for Average detection (AV) at frequency above 1GHz.
5. All modes of operation were investigated and the worst-case emissions are reported.

The worst mode as below:


11a CH36 TX for below 1GHz

### 2.6.5. Test Results of Radiated Band Edge and Spurious Emission

#### For 9 KHz to 30MHz


The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

#### For 30MHz to 1000 MHz



30MHz to 1GHz, Antenna Horizontal

Frequency (MHz)	QuasiPeak (dB µ V/m)	Bandwidth (kHz)	Corr. Factor (dB/m)	Antenna height (cm)	Limit (dB µ V/m)	Margin	Antenna	Verdict
30.510000	29.52	120.000	17.9	100.0	40.0	10.48	Horizontal	Pass
61.100000	25.28	120.000	8.2	100.0	40.0	14.72	Horizontal	Pass
138.860000	26.47	120.000	12.9	100.0	43.5	17.03	Horizontal	Pass
350.740000	30.81	120.000	15.8	100.0	46.0	15.19	Horizontal	Pass
420.720000	33.42	120.000	17.5	100.0	46.0	12.58	Horizontal	Pass
900.860000	39.39	120.000	24.8	100.0	46.0	6.61	Horizontal	Pass



30MHz to 1GHz, Antenna Vertical

Frequency (MHz)	QuasiPeak (dB $\mu$ V/m)	Bandwidth (kHz)	Corr. Factor (dB $\mu$ V/m)	Antenna height (cm)	Limit (dB $\mu$ V/m)	Margin	Antenna	Verdict
30.600000	29.81	120.000	17.90	100.0	40.0	10.19	Vertical	Pass
158.300000	28.46	120.000	11.20	100.0	43.5	15.04	Vertical	Pass
350.740000	32.81	120.000	15.80	100.0	46.0	13.19	Vertical	Pass
510.140000	32.84	120.000	19.30	100.0	46.0	13.16	Vertical	Pass
698.700000	35.71	120.000	22.00	100.0	46.0	10.29	Vertical	Pass
885.310000	40.31	120.000	24.80	100.0	46.0	5.69	Vertical	Pass

**For 1GHz to 40 GHz****ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M (802.11a\_5180MHz)**

No.	Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV/m)	Correction Factor (dB/m)
1	5150.00	58.64	PK	68.20	-9.56	1.80	90	51.14	7.50
2	5150.00	48.26	AV	54.00	-5.74	1.80	90	40.76	7.50
3	10360.00	54.39	PK	68.20	-13.81	1.80	90	34.59	19.80
4	10360.00	44.33	AV	54.00	-9.67	1.80	90	24.53	19.80

**ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M (802.11a\_5180MHz)**

No.	Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV/m)	Correction Factor (dB/m)
1	5150.00	57.84	PK	68.20	-10.36	1.70	300	50.34	7.50
2	5150.00	48.08	AV	54.00	-5.92	1.70	300	40.58	7.50
3	10360.00	55.97	PK	68.20	-12.23	1.70	300	36.17	19.80
4	10360.00	46.12	AV	54.00	-7.88	1.70	300	26.32	19.80

**ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M (802.11a\_5220MHz)**

No.	Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV/m)	Correction Factor (dB/m)
1	10400.00	56.85	PK	68.20	-11.35	1.80	180	36.95	19.90
2	10400.00	46.69	AV	54.00	-7.31	1.80	180	26.79	19.90

**ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M (802.11a\_5220MHz)**

No.	Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV/m)	Correction Factor (dB/m)
1	10400.00	54.87	PK	68.20	-13.33	1.70	300	34.97	19.90
2	10400.00	44.61	AV	54.00	-9.39	1.70	300	24.71	19.90

**ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M (802.11a\_5240MHz)**

No.	Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV/m)	Correction Factor (dB/m)
1	5350.00	54.12	PK	68.20	-14.08	1.80	190	46.12	8.00
2	5350.00	43.76	AV	54.00	-10.24	1.80	190	35.76	8.00
3	10480.00	54.87	PK	68.20	-13.33	1.80	190	34.97	19.90
4	10480.00	44.75	AV	54.00	-9.25	1.80	190	24.85	19.90

**ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M (802.11a\_5240MHz)**

No.	Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV/m)	Correction Factor (dB/m)
1	5350.00	53.26	PK	68.20	-14.94	1.70	300	45.26	8.00
2	5350.00	43.61	AV	54.00	-10.39	1.70	300	35.61	8.00
3	10480.00	55.09	PK	68.20	-13.11	1.70	300	35.19	19.90
4	10480.00	44.74	AV	54.00	-11.6	1.70	300	24.84	19.90

**ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M (802.11a\_5745MHz)**

No.	Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV/m)	Correction Factor (dB/m)
1	5725.00	54.48	PK	68.20	-13.72	1.50	290	44.83	9.65
2	5725.00	44.88	AV	54.00	-9.12	1.50	290	35.23	9.65
2	11490.00	55.26	PK	68.20	-12.94	1.60	290	33.56	21.70
3	11490.00	45.10	AV	54.00	-8.9	1.60	290	23.40	21.70

**ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M (802.11a\_5745MHz)**

No.	Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV/m)	Correction Factor (dB/m)
1	5725.00	55.94	PK	68.20	-12.26	1.70	120	46.29	9.65
2	5725.00	45.34	AV	54.00	-8.66	1.70	120	35.69	9.65
2	11490.00	56.32	PK	68.20	-11.88	1.70	120	34.62	21.70
3	11490.00	46.93	AV	54.00	-7.07	1.70	120	25.23	21.70

**ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M (802.11a\_5785MHz)**

No.	Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV/m)	Correction Factor (dB/m)
1	11570.00	55.47	PK	68.20	-12.73	1.80	120	33.77	21.70
2	11570.00	45.73	AV	54.00	-8.27	1.80	120	24.03	21.70

**ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M (802.11a\_5785MHz)**

No.	Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV/m)	Correction Factor (dB/m)
1	11570.00	54.29	PK	68.20	-13.91	1.80	300	32.59	21.70
2	11570.00	44.16	AV	54.00	-9.84	1.80	300	22.46	21.70



**ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M (802.11a\_5825MHz)**

No.	Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV/m)	Correction Factor (dB/m)
1	5850.00	57.48	PK	68.20	-10.72	1.70	300	47.70	9.78
2	5850.00	47.88	AV	54.00	-6.12	1.70	300	38.10	9.78
2	11650.00	56.29	PK	68.20	-11.91	1.70	300	34.39	21.90
3	11650.00	46.87	AV	54.00	-7.13	1.70	300	24.97	21.90

**ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M (802.11a\_5825MHz)**

No.	Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV/m)	Correction Factor (dB/m)
1	5850.00	55.18	PK	68.20	-13.02	1.70	330	45.40	9.78
2	5850.00	45.58	AV	54.00	-8.42	1.70	330	35.93	9.65
2	11650.00	54.97	PK	68.20	-13.23	1.70	330	33.07	21.90
3	11650.00	45.02	AV	54.00	-8.98	1.70	330	23.12	21.90

**ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M (802.11n20\_5180MHz)**

No.	Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV/m)	Correction Factor (dB/m)
1	5150.00	54.36	PK	68.20	-13.84	1.60	320	46.86	7.50
2	5150.00	44.11	AV	54.00	-9.89	1.60	320	36.61	7.50
3	10360.00	56.32	PK	68.20	-11.88	1.60	320	36.52	19.80

**ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M (802.11n20\_5180MHz)**

No.	Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV/m)	Correction Factor (dB/m)
1	5150.00	55.74	PK	68.20	-12.46	1.50	250	48.24	7.50
2	5150.00	45.50	AV	54.00	-8.50	1.50	250	38.00	7.50
3	10360.00	56.12	PK	68.20	-12.08	1.50	250	36.32	19.80

**ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M (802.11n20\_5220MHz)**

No.	Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV/m)	Correction Factor (dB/m)
1	10400.00	54.25	PK	68.20	-13.95	1.60	320	34.35	19.90

**ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M (802.11n20\_5220MHz)**

No.	Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV/m)	Correction Factor (dB/m)
1	10400.00	55.36	PK	68.20	-12.84	1.50	250	35.46	19.90

**ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M (802.11n20\_5240MHz)**

No.	Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV/m)	Correction Factor (dB/m)
1	5350.00	55.84	PK	68.20	-12.36	1.60	320	47.84	8.00
2	5350.00	45.57	AV	54.00	-8.43	1.60	320	37.57	8.00
3	10480.00	56.35	PK	68.20	-11.85	1.60	320	36.45	19.90

**ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M (802.11n20\_5240MHz)**

No.	Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV/m)	Correction Factor (dB/m)
1	5350.00	54.18	PK	68.20	-14.02	1.50	250	46.18	8.00
2	5350.00	44.20	AV	54.00	-9.8	1.50	250	36.20	8.00
3	10480.00	54.95	PK	68.20	-13.25	1.50	250	35.05	19.90

**ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M (802.11n20\_5745MHz)**

No.	Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV/m)	Correction Factor (dB/m)
1	5725.00	56.35	PK	68.20	-11.85	1.60	220	46.70	9.65
2	5725.00	46.38	AV	54.00	-7.62	1.60	220	36.73	9.65
2	11490.00	55.84	PK	68.20	-12.36	1.60	220	34.14	21.70
3	11490.00	45.76	AV	54.00	-8.24	1.60	220	24.06	21.70

**ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M (802.11n20\_5745MHz)**

No.	Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV/m)	Correction Factor (dB/m)
1	5725.00	54.18	PK	68.20	-14.02	1.80	320	44.53	9.65
2	5725.00	43.61	AV	54.00	-10.39	1.80	320	33.96	9.65
2	11490.00	55.29	PK	68.20	-12.91	1.80	320	33.59	21.70
3	11490.00	45.32	AV	54.00	-8.68	1.80	320	23.62	21.70

**ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M (802.11n20\_5785MHz)**

No.	Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV/m)	Correction Factor (dB/m)
1	11570.00	53.69	PK	68.20	-14.51	1.60	220	31.99	21.70
2	11570.00	43.72	AV	54.00	-10.28	1.60	220	22.02	21.70

**ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M (802.11n20\_5785MHz)**

No.	Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV/m)	Correction Factor (dB/m)
1	11570.00	54.18	PK	68.20	-14.02	1.80	320	32.48	21.70
2	11570.00	44.10	AV	54.00	-9.9	1.80	320	22.40	21.70

**ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M (802.11n20\_5825MHz)**

No.	Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV/m)	Correction Factor (dB/m)
1	5850.00	56.26	PK	68.20	-11.94	1.80	300	46.48	9.78
2	5850.00	46.29	AV	54.00	-7.71	1.80	300	36.51	9.78
3	11650.00	55.84	PK	68.20	-12.36	1.80	300	33.94	21.90
4	11650.00	45.95	AV	54.00	-8.05	1.80	300	24.05	21.90

**ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M (802.11n20\_5825MHz)**

No.	Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV/m)	Correction Factor (dB/m)
1	5850.00	55.97	PK	68.20	-12.23	1.70	320	46.19	9.78
2	5850.00	46	AV	54.00	-8	1.70	320	36.35	9.65
3	11650.00	56.32	PK	68.20	-11.88	1.70	320	34.42	21.90
4	11650.00	46.45	AV	54.00	-7.55	1.70	320	24.55	21.90

**ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M (802.11ac20\_5180MHz)**

No.	Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV/m)	Correction Factor (dB/m)
1	5150.00	56.84	PK	68.20	-11.36	1.80	90	49.34	7.50
2	5150.00	46.65	AV	54.00	-7.35	1.80	90	39.15	7.50
3	10360.00	53.97	PK	68.20	-14.23	1.80	90	34.17	19.80
4	10360.00	43.69	AV	54.00	-10.31	1.80	90	23.89	19.80

**ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M (802.11ac20\_5180MHz)**

No.	Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV/m)	Correction Factor (dB/m)
1	5150.00	56.95	PK	68.20	-11.25	1.70	300	49.45	7.50
2	5150.00	47.68	AV	54.00	-6.32	1.70	300	40.18	7.50
3	10360.00	54.18	PK	68.20	-14.02	1.70	300	34.38	19.80
4	10360.00	44.21	AV	54.00	-9.79	1.70	300	24.41	19.80



**ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M (802.11ac20\_5220MHz)**

No.	Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV/m)	Correction Factor (dB/m)
1	10400.00	54.23	PK	68.20	-13.97	1.80	180	34.33	19.90
2	10400.00	43.86	AV	54.00	-10.14	1.80	180	23.96	19.90

**ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M (802.11ac20\_5220MHz)**

No.	Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV/m)	Correction Factor (dB/m)
1	10400.00	55.62	PK	68.20	-12.58	1.70	300	35.72	19.90
2	10400.00	45.43	AV	54.00	-8.57	1.70	300	25.53	19.90

**ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M (802.11ac20\_5240MHz)**

No.	Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV/m)	Correction Factor (dB/m)
1	5350.00	56.95	PK	68.20	-11.25	1.80	190	48.95	8.00
2	5350.00	46.59	AV	54.00	-7.41	1.80	190	38.59	8.00
3	10480.00	55.47	PK	68.20	-12.73	1.80	190	35.57	19.90
4	10480.00	45.35	AV	54.00	-8.65	1.80	190	25.45	19.90

**ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M (802.11ac20\_5240MHz)**

No.	Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV/m)	Correction Factor (dB/m)
1	5350.00	52.97	PK	68.20	-15.23	1.70	300	44.97	8.00
2	5350.00	43.32	AV	54.00	-10.68	1.70	300	35.32	8.00
3	10480.00	54.36	PK	68.20	-13.84	1.70	300	34.46	19.90
4	10480.00	44.01	AV	54.00	-11.6	1.70	300	24.11	19.90



**ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M (802.11ac20\_5745MHz)**

No.	Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV/m)	Correction Factor (dB/m)
1	5725.00	55.94	PK	68.20	-12.26	1.70	180	46.29	9.65
2	5725.00	46.34	AV	54.00	-7.66	1.70	180	36.69	9.65
2	11490.00	55.26	PK	68.20	-12.94	1.70	180	33.56	21.70
3	11490.00	45.10	AV	54.00	-8.9	1.70	180	23.40	21.70

**ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M (802.11ac20\_5745MHz)**

No.	Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV/m)	Correction Factor (dB/m)
1	5725.00	54.18	PK	68.20	-14.02	1.70	120	44.53	9.65
2	5725.00	43.58	AV	54.00	-10.42	1.70	120	33.93	9.65
2	11490.00	55.28	PK	68.20	-12.92	1.70	120	33.58	21.70
3	11490.00	45.89	AV	54.00	-8.11	1.70	120	24.19	21.70

**ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M (802.11ac20\_5785MHz)**

No.	Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV/m)	Correction Factor (dB/m)
1	11570.00	53.62	PK	68.20	-14.58	1.80	120	31.92	21.70
2	11570.00	43.88	AV	54.00	-10.12	1.80	120	22.18	21.70

**ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M (802.11ac20\_5785MHz)**

No.	Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV/m)	Correction Factor (dB/m)
1	11570.00	54.19	PK	68.20	-14.01	1.80	300	32.49	21.70
2	11570.00	44.06	AV	54.00	-9.94	1.80	300	22.36	21.70

**ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M (802.11ac20\_5825MHz)**

No.	Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV/m)	Correction Factor (dB/m)
1	5850.00	57.84	PK	68.20	-10.36	1.70	300	48.06	9.78
2	5850.00	48.24	AV	54.00	-5.76	1.70	300	38.46	9.78
2	11650.00	55.29	PK	68.20	-12.91	1.70	300	33.39	21.90
3	11650.00	45.87	AV	54.00	-8.13	1.70	300	23.97	21.90

**ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M (802.11ac20\_5825MHz)**

No.	Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV/m)	Correction Factor (dB/m)
1	5850.00	53.64	PK	68.20	-14.56	1.70	330	43.86	9.78
2	5850.00	44.04	AV	54.00	-9.96	1.70	330	34.39	9.65
2	11650.00	52.19	PK	68.20	-16.01	1.70	330	30.29	21.90
3	11650.00	42.24	AV	54.00	-11.76	1.70	330	20.34	21.90

**ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3M (802.11n40\_5190MHz)**

No.	Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV/m)	Correction Factor (dB/m)
1	5150.00	54.18	PK	68.20	-14.02	1.70	260.00	46.68	7.50
2	5150.00	43.85	AV	54.00	-10.15	1.70	260.00	36.35	7.50
3	10380.00	55.69	PK	68.20	-12.51	1.70	260.00	35.89	19.80

**ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3M (802.11n40\_5190MHz)**

No.	Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV/m)	Correction Factor (dB/m)
1	5150.00	56.29	PK	68.20	-11.91	1.80	330.00	48.79	7.50
2	5150.00	46.55	AV	54.00	-7.45	1.80	330.00	39.05	7.50
3	10380.00	55.48	PK	68.20	-12.72	1.80	330.00	35.68	19.80

**ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M (802.11n40\_5230MHz)**

No.	Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV/m)	Correction Factor (dB/m)
1	5350.00	56.32	PK	68.20	-11.88	1.60	220.00	48.32	8.00
2	5350.00	46.04	AV	54.00	-7.96	1.60	220.00	38.04	8.00
3	10460.00	54.28	PK	68.20	-13.92	1.60	220.00	34.38	19.90

**ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M (802.11n40\_5230MHz)**

No.	Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV/m)	Correction Factor (dB/m)
1	5350.00	54.84	PK	68.20	-13.36	1.80	300.00	46.84	8.00
2	5350.00	44.61	AV	54.00	-9.39	1.80	300.00	36.61	8.00
3	10460.00	56.62	PK	68.20	-11.58	1.80	300.00	36.72	19.90

**ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M (802.11n40\_5755MHz)**

No.	Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV/m)	Correction Factor (dB/m)
1	5725.00	56.32	PK	68.20	-11.88	1.60	120.00	46.67	9.65
2	5725.00	47.34	AV	54.00	-6.66	1.60	120.00	37.69	9.65
3	11510.00	56.14	PK	68.20	-12.06	1.60	120.00	34.44	21.70
4	11510.00	45.62	AV	54.00	-8.38	1.60	120.00	23.92	21.70

**ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M (802.11n40\_5755MHz)**

No.	Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV/m)	Correction Factor (dB/m)
1	5725.00	53.87	PK	68.20	-14.33	1.80	300.00	44.22	9.65
2	5725.00	43.22	AV	54.00	-10.78	1.80	300.00	33.57	9.65
3	11510.00	56.54	PK	68.20	-11.66	1.80	300.00	34.84	21.70
4	11510.00	46.00	AV	54.00	-8	1.80	300.00	24.30	21.70



**ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M (802.11n40\_5795MHz)**

No.	Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV/m)	Correction Factor (dB/m)
1	5850.00	56.32	PK	68.20	-11.88	1.60	240.00	46.54	9.78
2	5850.00	45.58	AV	54.00	-8.42	1.60	240.00	35.80	9.78
3	11590.00	53.87	PK	68.20	-14.33	1.60	240.00	32.07	21.80
4	11590.00	43.19	AV	54.00	-10.81	1.60	240.00	21.39	21.80

**ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M (802.11n40\_5795MHz)**

No.	Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV/m)	Correction Factor (dB/m)
1	5850.00	57.12	PK	68.20	-11.08	1.80	290.00	47.34	9.78
2	5850.00	46.47	AV	54.00	-7.53	1.80	290.00	36.69	9.78
3	11590.00	55.29	PK	68.20	-12.91	1.80	290.00	33.49	21.80
4	11590.00	44.71	AV	54.00	-9.29	1.80	290.00	22.91	21.80

**ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M (802.11ac40\_5190MHz)**

No.	Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV/m)	Correction Factor (dB/m)
1	5150.00	54.25	PK	68.20	-13.95	1.80	230.00	46.75	7.50
2	5150.00	43.92	AV	54.00	-10.08	1.80	230.00	36.42	7.50
3	10380.00	55.97	PK	68.20	-12.23	1.80	120.00	36.17	19.80
4	10380.00	45.68	AV	54.00	-8.32	1.80	120.00	25.88	19.80

**ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M (802.11ac40\_5190MHz)**

No.	Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV/m)	Correction Factor (dB/m)
1	5150.00	56.29	PK	68.20	-11.91	1.70	330.00	48.79	7.50
2	5150.00	46.55	AV	54.00	-7.45	1.70	330.00	39.05	7.50
3	10380.00	55.47	PK	68.20	-12.73	1.70	330.00	35.67	19.80
4	10380.00	45.62	AV	54.00	-8.38	1.70	330.00	25.82	19.80

**ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M (802.11ac40\_5230MHz)**

No.	Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV/m)	Correction Factor (dB/m)
1	5350.00	55.84	PK	68.20	-12.36	1.70	120.00	47.84	8.00
2	5350.00	45.56	AV	54.00	-8.44	1.70	120.00	37.56	8.00
3	10460.00	56.32	PK	68.20	-11.88	1.70	120.00	36.42	19.90
4	10460.00	46.20	AV	54.00	-7.8	1.70	120.00	26.30	19.90

**ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M (802.11ac40\_5230MHz)**

No.	Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV/m)	Correction Factor (dB/m)
1	5350.00	54.19	PK	68.20	-14.01	1.70	300.00	46.19	8.00
2	5350.00	43.96	AV	54.00	-10.04	1.70	300.00	35.96	8.00
3	10460.00	56.32	PK	68.20	-11.88	1.70	300.00	36.42	19.90
4	10460.00	45.97	AV	54.00	-11.6	1.70	300.00	26.07	19.90

**ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M (802.11ac40\_5755MHz)**

No.	Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV/m)	Correction Factor (dB/m)
1	5725.00	56.32	PK	68.20	-11.88	1.80	300.00	46.67	9.65
2	5725.00	47.34	AV	54.00	-6.66	1.80	300.00	37.69	9.65
3	11510.00	55.94	PK	68.20	-12.26	1.80	300.00	34.24	21.70
4	11510.00	45.42	AV	54.00	-8.58	1.80	300.00	23.72	21.70

**ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M (802.11ac40\_5755MHz)**

No.	Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV/m)	Correction Factor (dB/m)
1	5725.00	55.84	PK	68.20	-12.36	1.60	270.00	46.19	9.65
2	5725.00	45.19	AV	54.00	-8.81	1.60	270.00	35.54	9.65
3	11510.00	56.95	PK	68.20	-11.25	1.60	270.00	35.25	21.70
4	11510.00	46.41	AV	54.00	-7.59	1.60	270.00	24.71	21.70

**ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M (802.11ac40\_5795MHz)**

No.	Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV/m)	Correction Factor (dB/m)
1	5850.00	54.18	PK	68.20	-14.02	1.80	320.00	44.40	9.78
2	5850.00	43.44	AV	54.00	-10.56	1.80	320.00	33.66	9.78
3	11590.00	56.38	PK	68.20	-11.82	1.80	320.00	34.58	21.80
4	11590.00	45.70	AV	54.00	-8.3	1.80	320.00	23.90	21.80

**ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M (802.11ac40\_5795MHz)**

No.	Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV/m)	Correction Factor (dB/m)
1	5850.00	58.23	PK	68.20	-9.97	1.90	280.00	48.45	9.78
2	5850.00	47.58	AV	54.00	-6.42	1.90	280.00	37.80	9.78
3	11590.00	56.97	PK	68.20	-11.23	1.90	280.00	35.17	21.80
4	11590.00	46.39	AV	54.00	-7.61	1.90	280.00	24.59	21.80



<b>ANTENNA POLARITY &amp; TEST DISTANCE: HORIZONTAL AT 3 M (802.11ac-VHT80_5210MHz)</b>									
No.	Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV/m)	Correction Factor (dB/m)
1	5150.00	54.69	PK	68.20	-13.51	1.60	180.00	47.19	7.50
2	5150.00	44.03	AV	54.00	-9.97	1.60	180.00	36.53	7.50
3	10420.00	55.25	PK	68.20	-12.95	1.60	180.00	35.35	19.90
4	10420.00	44.67	AV	54.00	-9.33	1.60	180.00	24.77	19.90

<b>ANTENNA POLARITY &amp; TEST DISTANCE: VERTICAL AT 3 M (802.11ac-VHT80_5210MHz)</b>									
No.	Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV/m)	Correction Factor (dB/m)
1	5150.00	56.95	PK	68.20	-11.25	1.80	90.00	49.45	7.50
2	5150.00	46.97	AV	54.00	-7.03	1.80	90.00	39.47	7.50
3	10420.00	55.74	PK	68.20	-12.46	1.80	90.00	35.84	19.90
4	10420.00	45.89	AV	54.00	-8.11	1.80	90.00	25.99	19.90



<b>ANTENNA POLARITY &amp; TEST DISTANCE: HORIZONTAL AT 3 M (802.11ac-VHT80_5775MHz)</b>									
No.	Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV/m)	Correction Factor (dB/m)
1	5460.00	56.48	PK	68.20	-11.72	1.80	290.00	46.70	9.78
2	5460.00	48.74	AV	54.00	-5.26	1.80	290.00	38.96	9.78
3	11550.00	58.65	PK	68.20	-9.55	1.80	290.00	36.85	21.80
4	11550.00	47.91	AV	54.00	-6.09	1.80	290.00	26.11	21.80
<b>ANTENNA POLARITY &amp; TEST DISTANCE: VERTICAL AT 3 M (802.11ac-VHT80_5775MHz)</b>									
No.	Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV/m)	Correction Factor (dB/m)
1	5460.00	55.65	PK	68.20	-12.55	1.70	320.00	45.87	9.78
2	5460.00	47.00	AV	54.00	-7.00	1.70	320.00	37.22	9.78
3	11550.00	57.36	PK	68.20	-10.84	1.70	320.00	35.56	21.80
4	11550.00	46.78	AV	54.00	-7.22	1.70	320.00	24.98	21.80

**REMARKS:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value

## 2.7. Conducted Emission

### 2.7.1. Limit of Conducted Emission

FCC 15.207,


For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency range (MHz)	Conducted Limit (dB $\mu$ V)	
	Quai-peak	Average
0.15 - 0.50	66 to 56	56 to 46
0.50 - 5	56	46
5 - 30	60	50

### 2.7.2. Measuring Instruments

The measuring equipment is listed in the section 3 of this test report.

### 2.7.3. Test Setup






#### **2.7.4. Test Procedures**


1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.

#### **2.7.5. Test Results of Conducted Emission**

The EUT configuration of the emission tests is 5G WLAN Link + USB Cable (Charging from Adapter)



Frequency (MHz)	QuasiPeak (dB µ V)	Average (dB µ V)	Cabel Loss (dB)	Corr. (dB)	Margin - QPK	Limit - QPK	Margin - AV	Limit - AV (dB µ V)
0.591000	48.95	37.77	0.1	20.1	7.05	56.0	8.23	46.0
1.054500	43.57	32.58	0.1	20.6	12.43	56.0	13.42	46.0
1.347000	49.81	40.96	0.1	20.4	6.19	56.0	5.04	46.0
1.401000	49.82	41.95	0.1	20.3	6.18	56.0	4.05	46.0
1.770000	41.96	35.85	0.2	20.1	14.04	56.0	10.15	46.0
6.382500	39.39	30.44	0.2	19.8	20.61	60.0	19.56	50.0



Frequency (MHz)	QuasiPeak (dB µ V)	CAverage (dB µ V)	Cabel Loss (dB)	Corr. (dB)	Margin - QPK	Limit - QPK	Margin - AV	Limit - AV (dB µ V)
0.609000	45.45	35.14	0.1	20.1	10.55	56.0	10.86	46.0
0.753000	39.75	29.22	0.1	20.2	16.25	56.0	16.78	46.0
1.189500	42.42	35.30	0.1	20.5	13.58	56.0	10.70	46.0
1.396500	46.34	38.12	0.1	20.3	9.66	56.0	7.88	46.0
4.582500	40.49	29.44	0.2	19.9	15.51	56.0	16.56	46.0
6.121500	40.92	30.53	0.2	19.9	19.08	60.0	19.47	50.0

**Test Result: PASS**

**Note: Correction factor=Cabel loss+ attenuation factor  
attenuation factor=10dB**

### 3. List of measuring equipment

Item	Test Equipment	Manufacturer	Model No.	Serial No.	Cal Date	Due Date
1	EMI TEST RECEIVER	R&S	ESIB7	A0501375	2019.07.30	2020.07.29
2	Power Meter	R&S	NRP-Z31	102872	2019.05.05	2020.05.04
3	TURNTABLE	ETS	2088	2149	N/A	N/A
4	ANTENNA MAST	ETS	2075	2346	N/A	N/A
5	EMI TEST Software	R&S	ESK1	N/A	N/A	N/A
6	Horn antenna (18GHz~26.5GHz)	AR	AT4002A	305753	2017.11.10	2020.11.09
7	Amplifer	MILMEGA	80RF1000-250	A140901925	2017.10.09	2020.10.08
8	JS amplifer	AR	25S1G4AM1	A0304248	2017.10.09	2020.10.08
9	High pass filter	Compliance Direction systems	BSU-6	34202	2019.11.10	2020.11.09
13	Horn Antenna	AR	AT4002A	305753	2017.07.12	2020.07.11
14	Horn Antenna	AR	AT4510	325306	2018.07.14	2020.07.13
15	Horn Antenna (26.5-40GHz)	R&S	Oct-60	71688	2018.08.29.	2020.08.28
16	ULTRA-BROADBAND ANTENNA	R&S	HL562	A0304224	2017.07.14	2020.07.13
17	Passive Loop Antenna	R&S	HFH2-Z2	100047	2019.04.26	2022.04.25
18	Temperature chamber	Dongguan gaoda instrument CO.LTD	GD-7005-100	130130101	2019.04.22	2020.04.21
19	Spectrum Analyzer	KEYSIGHT	N9030A	A160702554	2019.06.05	2020.06.04
20	Power Supply	R&S	NGMO1	101037	2019.08.03	2020.08.02
21	EMI TEST RECEIVER	KEYSIGHT	ESIB26	A0304218	2019.05.20	2020.05.19
22	LISN	R&S	ESH2-Z5	A0304221	2019.04.30	2020.04.29

#### 4. Uncertainty of Evaluation

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.10-2013. All the measurement uncertainty value were shown with a coverage  $K=2$  to indicate 95% level of confidence . The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

Uncertainty of Conducted Emission Measurement (150KHz~30MHz)

Measuring Uncertainty for a level of confidence of 95%( $U=2U_c(y)$ )	2.6dB
---	-------

Uncertainty of Radiated Emission Measurement (30MHz~1GHz)

Measuring Uncertainty for a level of confidence of 95%( $U=2U_c(y)$ )	2.4dB
---	-------

Uncertainty of Radiated Emission Measurement (1GHz~40GHz)

Measuring Uncertainty for a level of confidence of 95%( $U=2U_c(y)$ )	2.8dB
---	-------

## Appendix A

### Conducted output power

#### Test results


U-NII-1 AVGSA Output Power				
Mode	Test Frequency (MHz)	Max Conducted Output Power (dBm)	Limit (dBm)	Result
802.11n (20MHz)	5180	12.72	24	Pass
802.11n (20MHz)	5220	12.91	24	Pass
802.11n (20MHz)	5240	12.39	24	Pass
802.11n (40MHz)	5190	12.08	24	Pass
802.11n (40MHz)	5230	11.58	24	Pass
802.11ac (20MHz)	5180	12.52	24	Pass
802.11ac (20MHz)	5220	12.95	24	Pass
802.11ac (20MHz)	5240	12.40	24	Pass
802.11ac (40MHz)	5190	11.90	24	Pass
802.11ac (40MHz)	5230	11.64	24	Pass
802.11ac (80MHz)	5210	11.69	24	Pass
802.11a (20MHz)	5180	13.47	24	Pass
802.11a (20MHz)	5220	12.82	24	Pass
802.11a (20MHz)	5240	12.38	24	Pass




U-NII-3 AVGSA Output Power				
Mode	Test Frequency (MHz)	Max Conducted Output Power (dBm)	Limit (dBm)	Result
802.11n (20MHz)	5745	12.57	30	Pass
802.11n (20MHz)	5785	12.57	30	Pass
802.11n (20MHz)	5825	12.44	30	Pass
802.11n (40MHz)	5755	11.77	30	Pass
802.11n (40MHz)	5795	11.86	30	Pass
802.11ac (20MHz)	5745	12.68	30	Pass
802.11ac (20MHz)	5785	12.50	30	Pass
802.11ac (20MHz)	5825	12.46	30	Pass
802.11ac (40MHz)	5755	11.79	30	Pass
802.11ac (40MHz)	5795	11.67	30	Pass
802.11ac (80MHz)	5775	11.68	30	Pass
802.11a (20MHz)	5745	12.74	30	Pass
802.11a (20MHz)	5785	12.72	30	Pass
802.11a (20MHz)	5825	12.65	30	Pass

### Test Plots


U-NII-1 Output Power-802.11n(20MHz)  
,5180MHz




U-NII-1 Output Power-802.11n(20MHz)  
,5220MHz




U-NII-1 Output Power-802.11n(20MHz)  
,5240MHz




U-NII-1 Output Power-802.11n(40MHz)  
,5190MHz



U-NII-1 Output Power-802.11n(40MHz)  
,5230MHz




U-NII-1 Output Power-802.11a(20MHz)  
,5180MHz







U-NII-1 Output Power-802.11a(20MHz)  
,5220MHz




U-NII-1 Output Power-802.11a(20MHz)  
,5240MHz




U-NII-1 Output Power-802.11ac(20MHz)  
,5180MHz



U-NII-1 Output Power-802.11ac(20MHz)  
,5220MHz




U-NII-1 Output Power-802.11ac(20MHz)  
,5240MHz




U-NII-1 Output Power-802.11ac(40MHz)  
,5190MHz



U-NII-1 Output Power-802.11ac(40MHz)  
,5230MHz




U-NII-1 Output Power-802.11ac(80MHz)  
,5210MHz




U-NII-3 Output Power-802.11n(20MHz)  
,5745MHz




U-NII-3 Output Power-802.11n(20MHz)  
,5785MHz




U-NII-3 Output Power-802.11n(20MHz)  
,5825MHz




U-NII-3 Output Power-802.11n(40MHz)  
,5755MHz




U-NII-3 Output Power-802.11n(40MHz)  
,5795MHz




U-NII-3 Output Power-802.11a(20MHz)  
,5745MHz




U-NII-3 Output Power-802.11a(20MHz)  
,5785MHz




U-NII-3 Output Power-802.11a(20MHz)  
,5825MHz




U-NII-3 Output Power-802.11ac(20MHz)  
,5745MHz




U-NII-3 Output Power-802.11ac(20MHz)  
,5785MHz



U-NII-3 Output Power-802.11ac(20MHz)  
,5825MHz




U-NII-3 Output Power-802.11ac(40MHz)  
,5755MHz



U-NII-3 Output Power-802.11ac(40MHz)  
,5795MHz



U-NII-3 Output Power-802.11ac(80MHz)  
,5775MHz





## AVGSA Power Spectral Density

### Test Result and Data


U-NII-1 AVGSA Power Spectral Density				
Mode	Test Frequency (MHz)	PSD (dBm/1MHz)	Limit (dBm/1MHz)	Result
802.11n (20MHz)	5180	2.624	11	Pass
802.11n (20MHz)	5220	2.756	11	Pass
802.11n (20MHz)	5240	2.062	11	Pass
802.11n (40MHz)	5190	-1.052	11	Pass
802.11n (40MHz)	5230	-1.383	11	Pass
802.11ac (20MHz)	5180	2.272	11	Pass
802.11ac (20MHz)	5220	2.753	11	Pass
802.11ac (20MHz)	5240	2.511	11	Pass
802.11ac (40MHz)	5190	-1.020	11	Pass
802.11ac (40MHz)	5230	-1.406	11	Pass
802.11ac (80MHz)	5210	-4.978	11	Pass
802.11a (20MHz)	5180	3.044	11	Pass
802.11a (20MHz)	5220	2.492	11	Pass
802.11a (20MHz)	5240	2.407	11	Pass



U-NII-3 AVGSA Power Spectral Density				
Mode	Test Frequency (MHz)	PSD (dBm/510KHz)	Limit (dBm/500KHz)	Result
802.11n (20MHz)	5745	-0.255	30	Pass
802.11n (20MHz)	5785	-0.182	30	Pass
802.11n (20MHz)	5825	-0.082	30	Pass
802.11n (40MHz)	5755	-3.356	30	Pass
802.11n (40MHz)	5795	-3.350	30	Pass
802.11ac (20MHz)	5745	0.117	30	Pass
802.11ac (20MHz)	5785	0.362	30	Pass
802.11ac (20MHz)	5825	0.135	30	Pass
802.11ac (40MHz)	5755	-3.533	30	Pass
802.11ac (40MHz)	5795	-3.705	30	Pass
802.11ac (80MHz)	5775	-7.247	30	Pass
802.11a (20MHz)	5745	0.062	30	Pass
802.11a (20MHz)	5785	0.022	30	Pass
802.11a (20MHz)	5825	0.181	30	Pass

### Test Plots


U-NII-1 Power spectral density-802.11  
n(20MHz),5180MHz



U-NII-1 Power spectral density-802.11  
n(20MHz),5220MHz




U-NII-1 Power spectral density-802.11  
n(20MHz),5240MHz




U-NII-1 Power spectral density-802.11  
n(40MHz),5190MHz



U-NII-1 Power spectral density-802.11  
n(40MHz),5230MHz



U-NII-1 Power spectral density-802.11  
a(20MHz),5180MHz



U-NII-1 Power spectral density-802.11  
a(20MHz),5220MHz




U-NII-1 Power spectral density-802.11  
a(20MHz),5240MHz



U-NII-1 Power spectral density-802.11  
ac(20MHz),5180MHz



U-NII-1 Power spectral density-802.11  
ac(20MHz),5220MHz



U-NII-1 Power spectral density-802.11  
ac(20MHz),5240MHz



U-NII-1 Power spectral density-802.11  
ac(40MHz),5190MHz






U-NII-1 Power spectral density-802.11  
ac(40MHz),5230MHz




U-NII-1 Power spectral density-802.11  
ac(80MHz),5210MHz




U-NII-3 Power spectral density-802.11  
n(20MHz),5745MHz




U-NII-3 Power spectral density-802.11  
n(20MHz),5785MHz




U-NII-3 Power spectral density-802.11  
n(20MHz),5825MHz




U-NII-3 Power spectral density-802.11  
n(40MHz),5755MHz




U-NII-3 Power spectral density-802.11  
n(40MHz),5795MHz




U-NII-3 Power spectral density-802.11  
a(20MHz),5745MHz




U-NII-3 Power spectral density-802.11  
a(20MHz),5785MHz




U-NII-3 Power spectral density-802.11  
a(20MHz),5825MHz




U-NII-3 Power spectral density-802.11  
ac(20MHz),5745MHz




U-NII-3 Power spectral density-802.11  
ac(20MHz),5785MHz




U-NII-3 Power spectral density-802.11  
ac(20MHz),5825MHz



U-NII-3 Power spectral density-802.11  
ac(40MHz),5755MHz



U-NII-3 Power spectral density-802.11  
ac(40MHz),5795MHz



U-NII-3 Power spectral density-802.11  
ac(80MHz),5775MHz



**6dB and 26dB Down Bandwidth****Test Result and Data**


U-NII-1 Occupied 26dB Bandwidth			
Mode	Test Frequency (MHz)	Occupied Bandwidth (MHz)	Result
802.11n (20MHz)	5180	19.97	Pass
802.11n (20MHz)	5220	19.92	Pass
802.11n (20MHz)	5240	19.98	Pass
802.11n (40MHz)	5190	40.15	Pass
802.11n (40MHz)	5230	40.22	Pass
802.11ac (20MHz)	5180	19.85	Pass
802.11ac (20MHz)	5220	20.05	Pass
802.11ac (20MHz)	5240	19.78	Pass
802.11ac (40MHz)	5190	40.41	Pass
802.11ac (40MHz)	5230	40.12	Pass
802.11ac (80MHz)	5210	81.63	Pass
802.11a (20MHz)	5180	20.09	Pass
802.11a (20MHz)	5220	19.76	Pass
802.11a (20MHz)	5240	19.72	Pass




U-NII-3 Occupied 6dB Bandwidth				
Mode	Test Frequency (MHz)	Occupied Bandwidth (MHz)	Limit (KHz)	Result
802.11n (20MHz)	5745	15.11	500	Pass
802.11n (20MHz)	5785	15.12	500	Pass
802.11n (20MHz)	5825	15.08	500	Pass
802.11n (40MHz)	5755	35.12	500	Pass
802.11n (40MHz)	5795	35.13	500	Pass
802.11ac (20MHz)	5745	13.84	500	Pass
802.11ac (20MHz)	5785	16.29	500	Pass
802.11ac (20MHz)	5825	14.68	500	Pass
802.11ac (40MHz)	5755	35.18	500	Pass
802.11ac (40MHz)	5795	35.16	500	Pass
802.11ac (80MHz)	5775	75.45	500	Pass
802.11a (20MHz)	5745	15.09	500	Pass
802.11a (20MHz)	5785	13.80	500	Pass
802.11a (20MHz)	5825	14.21	500	Pass

### Test Plots


U-NII-1 26dB Bandwidth-802.11n(20MHz)  
,5180MHz




U-NII-1 26dB Bandwidth-802.11n(20MHz)  
,5220MHz




U-NII-1 26dB Bandwidth-802.11n(20MHz)  
,5240MHz



U-NII-1 26dB Bandwidth-802.11n(40MHz)  
,5190MHz



U-NII-1 26dB Bandwidth-802.11n(40MHz)  
,5230MHz



U-NII-1 26dB Bandwidth-802.11a(20MHz)  
,5180MHz



U-NII-1 26dB Bandwidth-802.11a(20MHz)  
,5220MHz



U-NII-1 26dB Bandwidth-802.11a(20MHz)  
,5240MHz



U-NII-1 26dB Bandwidth-802.11ac(20MHz)  
,5180MHz



U-NII-1 26dB Bandwidth-802.11ac(20MHz)  
,5220MHz




U-NII-1 26dB Bandwidth-802.11ac(20MHz)  
,5240MHz



U-NII-1 26dB Bandwidth-802.11ac(40MHz)  
,5190MHz



U-NII-1 26dB Bandwidth-802.11ac(40MHz)  
,5230MHz



U-NII-1 26dB Bandwidth-802.11ac(80MHz)  
,5210MHz



U-NII-3 6dB Bandwidth-802.11n(20MHz)  
,5745MHz



U-NII-3 6dB Bandwidth-802.11n(20MHz)  
,5785MHz



U-NII-3 6dB Bandwidth-802.11n(20MHz)  
,5825MHz




U-NII-3 6dB Bandwidth-802.11n(40MHz)  
,5755MHz





U-NII-3 6dB Bandwidth-802.11n(40MHz)  
,5795MHz



U-NII-3 6dB Bandwidth-802.11a(20MHz)  
,5745MHz



U-NII-3 6dB Bandwidth-802.11a(20MHz)  
,5785MHz




U-NII-3 6dB Bandwidth-802.11a(20MHz)  
,5825MHz



U-NII-3 6dB Bandwidth-802.11ac(20MHz)  
,5745MHz



U-NII-3 6dB Bandwidth-802.11ac(20MHz)  
,5785MHz




U-NII-3 6dB Bandwidth-802.11ac(20MHz)  
,5825MHz



U-NII-3 6dB Bandwidth-802.11ac(40MHz)  
,5755MHz



U-NII-3 6dB Bandwidth-802.11ac(40MHz)  
,5795MHz



U-NII-3 6dB Bandwidth-802.11ac(80MHz)  
,5775MHz



**Frequency Stability****U-NII-1**

U-NII-1 Centre Frequency							
Mode	Test Frequency (MHz)	Ant	LF (MHz)	HF (MHz)	CF (MHz)	Freq Stability (ppm)	Test Result
802.11n (20MHz)	5180	Ant1	5171.185	5188.795	5179.990	-1.930	Pass
802.11n (20MHz)	5220	Ant1	5211.202	5228.784	5219.993	-1.360	Pass
802.11n (20MHz)	5240	Ant1	5231.206	5248.770	5239.988	-2.310	Pass
802.11n (40MHz)	5190	Ant1	5171.831	5208.146	5189.988	-2.310	Pass
802.11n (40MHz)	5230	Ant1	5171.206	5188.778	5179.992	-1.610	Pass
802.11ac (20MHz)	5180	Ant1	5211.192	5228.783	5219.988	-2.390	Pass
802.11ac (20MHz)	5220	Ant1	5231.190	5248.795	5239.993	-1.430	Pass
802.11ac (20MHz)	5240	Ant1	5171.840	5208.140	5189.990	-2.020	Pass
802.11ac (40MHz)	5190	Ant1	5211.841	5248.138	5229.990	-2.010	Pass
802.11ac (40MHz)	5230	Ant1	5171.800	5248.180	5209.990	-1.920	Pass
802.11ac (80MHz)	5210	Ant1	5171.723	5188.178	5179.950	-9.650	Pass
802.11a (20MHz)	5180	Ant1	5211.822	5228.163	5219.993	-1.440	Pass
802.11a (20MHz)	5220	Ant1	5231.828	5248.162	5239.995	-1.030	Pass
802.11a (20MHz)	5240	Ant1	5231.737	5248.190	5239.963	-7.000	Pass


**U-NII-3**

U-NII-3 Centre Frequency							
Mode	Test Frequency (MHz)	Ant	LF (MHz)	HF (MHz)	CF (MHz)	Freq Stability (ppm)	Test Result
802.11n (20MHz)	5745	Ant1	5736.153	5753.838	5744.995	-0.870	Pass
802.11n (20MHz)	5785	Ant1	5776.191	5793.768	5784.980	-3.530	Pass
802.11n (20MHz)	5825	Ant1	5816.163	5833.873	5825.018	3.080	Pass
802.11n (40MHz)	5755	Ant1	5736.832	5773.123	5754.978	-3.910	Pass
802.11n (40MHz)	5795	Ant1	5776.844	5813.132	5794.988	-2.070	Pass
802.11ac (20MHz)	5745	Ant1	5736.192	5753.762	5744.977	-4.060	Pass
802.11ac (20MHz)	5785	Ant1	5776.199	5793.758	5784.978	-3.750	Pass
802.11ac (20MHz)	5825	Ant1	5816.113	5833.882	5824.997	-0.500	Pass
802.11ac (40MHz)	5755	Ant1	5736.826	5773.110	5754.968	-5.600	Pass
802.11ac (40MHz)	5795	Ant1	5777.074	5813.117	5795.095	16.440	Pass
802.11ac (80MHz)	5775	Ant1	5736.783	5813.187	5774.985	-2.600	Pass
802.11a (20MHz)	5745	Ant1	5736.812	5753.153	5744.982	-3.120	Pass
802.11a (20MHz)	5785	Ant1	5776.805	5793.158	5784.982	-3.170	Pass
802.11a (20MHz)	5825	Ant1	5816.794	5833.184	5824.989	-1.860	Pass


Note: The worst data reported only.

### Bandedge and spurious Emission


U-NII-1 ,Plot 1,Band Edge-802.11n(20M Hz),5180MHz




U-NII-1 ,Plot 1,Band Edge-802.11n(20M Hz),5220MHz




U-NII-1 ,Plot 1,Band Edge-802.11n(20M Hz),5240MHz




U-NII-1 ,Plot 2,30MHz~5000MHz-802.11n (20MHz),5180MHz




U-NII-1 ,Plot 2,30MHz~5000MHz-802.11n (20MHz),5220MHz




U-NII-1 ,Plot 2,30MHz~5000MHz-802.11n (20MHz),5240MHz




U-NII-1 ,Plot 3, 5000MHz~7000MHz -802.1  
1n(20MHz),5180MHz




U-NII-1 ,Plot 3, 5000MHz~7000MHz -802.1  
1n(20MHz),5220MHz




U-NII-1 ,Plot 3, 5000MHz~7000MHz -802.1  
1n(20MHz),5240MHz




U-NII-1 ,Plot 4, 7000MHz~26000MHz-802.  
11n(20MHz),5180MHz




U-NII-1 ,Plot 4, 7000MHz~26000MHz-802.  
11n(20MHz),5220MHz




U-NII-1 ,Plot 4, 7000MHz~26000MHz-802.  
11n(20MHz),5240MHz




U-NII-1 ,Plot 5,26000MHz~40000MHz-802.  
11n(20MHz),5180MHz




U-NII-1 ,Plot 5,26000MHz~40000MHz-802.  
11n(20MHz),5220MHz




U-NII-1 ,Plot 5,26000MHz~40000MHz-802.  
11n(20MHz),5240MHz




U-NII-1 ,Plot 1,Band Edge-802.11n(40M  
Hz),5230MHz




U-NII-1 ,Plot 1,Band Edge-802.11n(40M  
Hz),5190MHz




U-NII-1 ,Plot 2,30MHz~5000MHz-802.11n  
(40MHz),5230MHz




U-NII-1 ,Plot 2,30MHz~5000MHz-802.11n  
(40MHz),5190MHz




U-NII-1 ,Plot 3, 5000MHz~7000MHz -802.11n(40MHz),5230MHz




U-NII-1 ,Plot 3, 5000MHz~7000MHz -802.11n(40MHz),5190MHz




U-NII-1 ,Plot 4,7000MHz~26000MHz-802.11n(40MHz),5230MHz



U-NII-1 ,Plot 4,7000MHz~26000MHz-802.11n(40MHz),5190MHz




U-NII-1 ,Plot 5,26000MHz~40000MHz-802.11n(40MHz),5230MHz







U-NII-1 ,Plot 5,26000MHz~40000MHz-802.  
11n(40MHz),5190MHz




U-NII-1 ,Plot 1,Band Edge-802.11a(20M  
Hz),5220MHz




U-NII-1 ,Plot 1,Band Edge-802.11a(20M  
Hz),5180MHz




U-NII-1 ,Plot 1,Band Edge-802.11ac(20  
MHz),5180MHz




U-NII-1 ,Plot 1,Band Edge-802.11a(20M  
Hz),5240MHz




U-NII-1 ,Plot 1,Band Edge-802.11ac(20  
MHz),5240MHz




U-NII-1 ,Plot 1,Band Edge-802.11ac(20 MHz),5220MHz




U-NII-1 ,Plot 1,Band Edge-802.11ac(40 MHz),5230MHz




U-NII-1 ,Plot 1,Band Edge-802.11ac(40 MHz),5190MHz




U-NII-1 ,Plot 2,30MHz~5000MHz-802.11a (20MHz),5180MHz




U-NII-1 ,Plot 1,Band Edge-802.11ac(80 MHz),5210MHz




U-NII-1 ,Plot 2,30MHz~5000MHz-802.11a (20MHz),5240MHz




U-NII-1 ,Plot 2,30MHz~5000MHz-802.11a  
(20MHz),5220MHz




U-NII-1 ,Plot 2,30MHz~5000MHz-802.11a  
c(20MHz),5220MHz




U-NII-1 ,Plot 2,30MHz~5000MHz-802.11a  
c(20MHz),5180MHz



U-NII-1 ,Plot 2,30MHz~5000MHz-802.11a  
c(40MHz),5190MHz



U-NII-1 ,Plot 2,30MHz~5000MHz-802.11a  
c(20MHz),5240MHz



U-NII-1 ,Plot 2,30MHz~5000MHz-802.11a  
c(80MHz),5210MHz

