

TEST REPORT FOR GSM TESTING

Report No.: SRTC2019-9004(F)-19031203(A)

Product Name: LTE/WCDMA/GSM (GPRS) Multi-Mode Digital Mobile
Phone

Product Model: ZTE Blade A7 2019

Applicant: ZTE Corporation

Manufacturer: ZTE Corporation

Specification: FCC Part 24E, Part 22H, Part 2 (2019)

FCC ID: SRQ-ZTEA72019

The State Radio_monitoring_center Testing Center (SRTC)

15th Building, No.30 Shixing Street, Shijingshan District,

Beijing, P.R.China

Tel: 86-10-57996183 Fax: 86-10-57996388

CONTENTS

1. GENERAL INFORMATION	2
1.1 NOTES OF THE TEST REPORT	2
1.2 INFORMATION ABOUT THE TESTING LABORATORY	2
1.3 APPLICANT’S DETAILS	2
1.4 MANUFACTURER’S DETAILS	2
1.5 TEST ENVIRONMENT	3
2 DESCRIPTION OF THE DEVICE UNDER TEST	4
2.1 FINAL EQUIPMENT BUILD STATUS	4
2.2 SUPPORT EQUIPMENT	5
2.3 CONDUCTED MEASUREMENT PATH LOSS	7
2.4 SUMMARY TABLE	7
3 REFERENCE SPECIFICATION	8
4 KEY TO NOTES AND RESULT CODES	9
5 RESULT SUMMARY	10
6 TEST RESULT	11
6.1 RF POWER OUTPUT-FCC PART 2.1046	11
6.2 EFFECTIVE RADIATED POWER-FCC PART 22.913(A)/PART 24.232(c)	12
6.3 OCCUPIED BANDWIDTH-FCC PART 2.1049	14
6.4 EMISSION BANDWIDTH-FCC PART 22.917(B)/PART 24.238(B)	15
6.5 SPURIOUS EMISSIONS AT ANTENNA TERMINAL-FCC PART 2.1051/ 22.917(A) /PART 24.238(A)	16
6.6 BAND EDGES COMPLIANCE- FCC PART 2.1051/ 22.917(A) /PART 24.238(A)	17
6.7 FREQUENCY STABILITY- FCC PART 2.1055/22.355 /PART 24.235	18
6.8 RADIATED SPURIOUS EMISSIONS-FCC PART 2.1053/ 22.917(A)/PART 24.238(A)	19
6.9 PEAK-AVERAGE RATIO -FCC PART 24.232(D)	23
7 MEASUREMENT UNCERTAINTIES	24
8 TEST EQUIPMENTS	25
APPENDIX A – TEST DATA OF CONDUCTED EMISSION	25
APPENDIX B – TEST DATA OF RADIATED EMISSION	25

1. GENERAL INFORMATION

1.1 Notes of the test report

The test report may only be reproduced or published in full. Reproduction or publication of extracts from the report requires the prior written permission of The State Radio_monitoring_center Testing Center (SRTC).

The test results relate only to individual items of the samples which have been tested.

The certification and accreditation identifiers used in this report shall not be applicable to the tested or calibrated samples thereof. The manufacturer shall not mark the tested samples or items (or a separate part of the item) with the identifiers of certification and accreditation to mislead relevant parties about the tested samples or items.

1.2 Information about the testing laboratory

Company:	The State Radio_monitoring_center Testing Center (SRTC)
Address:	15th Building, No.30 Shixing Street, Shijingshan District, P.R.China
City:	Beijing
Country or Region:	P.R.China
Contacted person:	Liu Jia
Tel:	+86 10 57996183
Fax:	+86 10 57996388
Email:	liujiarf@srtc.org.cn

1.3 Applicant's details

Company:	ZTE Corporation
Address:	ZTE Plaza, #55 Keji Road South, Hi-Tech, Industrial Park, Nanshan District,Guangdong
City:	Shenzhen
Country or Region:	China
Contacted person:	Yang Zhao
Tel:	029-83600770
Fax:	---
Email:	zhao.yangxa@zte.com.cn

1.4 Manufacturer's details

Company:	ZTE Corporation
Address:	ZTE Plaza, #55 Keji Road South, Hi-Tech, Industrial Park, Nanshan District,Guangdong
City:	Shenzhen
Country or Region:	China
Contacted person:	Yang Zhao
Tel:	029-83600770
Fax:	---
Email:	zhao.yangxa@zte.com.cn

1.5 Test Environment

Date of Receipt of test sample at SRTC:	2019-03-12
Testing Start Date:	2019-03-18
Testing End Date:	2019-04-01

Environmental Data:	Temperature (°C)	Humidity (%)
Ambient	25	30
Maximum Extreme	55	---
Minimum Extreme	-10	---

Normal Supply Voltage (V d.c.):	3.85
Maximum Extreme Supply Voltage (V d.c.):	4.40
Minimum Extreme Supply Voltage (V d.c.):	3.46

2 DESCRIPTION OF THE DEVICE UNDER TEST

2.1 Final Equipment Build Status

Frequency Range	GSM850: Tx:824~849MHz Rx:869~894MHz PCS1900: Tx:1850~1910MHz Rx:1930~1990MHz
Modulation Type	GSM/GPRS:GMSK EDGE: GMSK/8PSK
Emission Designator	300KGXW/300KG7W
Duplex Mode	FDD
Duplex Spacing	GSM850:45MHz PCS1900:80MHz
Antenna Type	IFA Antenna
Power Supply	Battery/Charger
HW Version	ukhB
SW Version	TEL_MX_ZTE_Blade_A7_2019V1.0
IMEI	864432040006454

2.2 Support Equipment

The following support equipment was used to exercise the DUT during testing:

Equipment	Battery
Manufacturer	Ningbo Veken Battery Co., Ltd.
Model Number	Li3931T44P8h806139
Serial Number	---

Equipment	Battery
Manufacturer	Zhongshan Tianmao Battery Co., Ltd.
Model Number	Li3931T44P8h806139
Serial Number	---

Equipment	Charger
Manufacturer	RUIJING
Model Number	STC-A515A-Z
Serial Number	---

Equipment	Charger
Manufacturer	CHENYANG
Model Number	STC-A515A-Z
Serial Number	---

Equipment	Charger
Manufacturer	DOKOCOM
Model Number	STC-A515A-A
Serial Number	---

Equipment	Charger
Manufacturer	RUIJING
Model Number	STC-A515A-A
Serial Number	---

Equipment	Charger
Manufacturer	CHENYANG
Model Number	STC-A515A-A
Serial Number	---

Equipment	Headset
Manufacturer	JUWEI ELECTRONICS CO.,LTD
Model Number	JWEP1036-Z01R
Serial Number	---

Equipment	Headset
Manufacturer	ShenZhen FDC Electronic Co.,Ltd
Model Number	DEM-66
Serial Number	---

Equipment	USB Cable
Manufacturer	Dongguan Guojun Plastic Electronic Co.,Ltd
Model Number	USB-MU5-W-70-M-L
Serial Number	---

Equipment	USB Cable
Manufacturer	Shen Zhen Shi Yi HUA XING Electron Co.,Ltd
Model Number	USB-MU5-W-70-M-L
Serial Number	---

2.3 Conducted measurement Path Loss

GSM850 Offset 6.5dB = Power Divider 6dB+ Temporary antenna connector loss 0.2dB+ Cable loss 0.3dB

PCS1900 Offset 6.8dB = Power Divider 6dB+ Temporary antenna connector loss 0.2dB+ Cable loss 0.6dB

2.4 Summary table.

FCC Rule Part	Mode	Frequency Range(MHz)	Conducted (Average)、(dBm)	ERP/ EIRP (W)	Frequency Tolerance (ppm)	Emission Designator
22H	GSM850	824.2-848.8	33.11	0.568	0.014	240KGXW
22H	EDGE850	824.2-848.8	33.08	0.564	0.017	244KG7W
24E	GSM1900	1850.2-1909.8	29.66	1.282	0.015	244KGXW
24E	EDGE1900	1850.2-1909.8	29.64	1.276	0.019	243KG7W

3 REFERENCE SPECIFICATION

Specification	Version	Title
2.1046	2019	Measurements required: RF power output.
2.1049	2019	Measurements required: Occupied bandwidth.
2.1051	2019	Measurements required: Spurious emissions at antenna terminals.
2.1053	2019	Measurements required: Field strength of spurious radiation.
2.1055	2019	Measurements required: Frequency stability.
22.355	2019	Frequency tolerance.
22.913	2019	Effective radiated power limits.
22.917	2019	Emission limitations for cellular equipment.
24.232	2019	Power and antenna height limits.
24.235	2019	Frequency stability.
24.238	2019	Emission limitations for Broadband PCS equipment.
ANSI C63.26	2015	American National Standard for Compliance Testing of Transmitters Used in Licensed Radio Services
KDB 971168 D01	April 9, 2018	MEASUREMENT GUIDANCE FOR CERTIFICATION OF LICENSED DIGITAL TRANSMITTERS




4 KEY TO NOTES AND RESULT CODES

The following are the definition of the test result.

Code	Meaning
PASS	Test result shows that the requirements of the relevant specification have been met.
FAIL	Test result shows that the requirements of the relevant specification have not been met.
N/T	Test case is not tested.
NTC	Nominal voltage, Normal Temperature
HV	High voltage, Normal Temperature
LV	Low voltage, Normal Temperature
HTHV	high voltage, High Temperature
LTHV	High voltage, Low Temperature
HTLV	Low voltage, High Temperature
LTLV	Low voltage, Low Temperature

5 RESULT SUMMARY

No.	Test case	FCC reference	Verdict
1	RF Power Output	2.1046	Pass
2	Effective Radiated Power and Effective Isotropic Radiated Power	22.913(a)/24.232(c)	Pass
3	Occupied Bandwidth	2.1049	Pass
4	Emission Bandwidth	22.917(b)/24.238(b)	Pass
5	Spurious Emissions at antenna terminals	2.1051/22.917(a)/24.238(a)	Pass
6	Band Edges Compliance	2.1051/22.917(a)/24.238(a)	Pass
7	Frequency Stability	2.1055/22.355/24.235	Pass
8	Radiated Spurious Emissions	2.1053/22.917(a)/24.238(a)	Pass
9	Peak-Average Ratio	24.232(d)	Pass

This Test Report Is Issued by: Mr. Peng Zhen 	Checked by: Mr. Li Bin 
Tested by: Tong Daocheng 	Issued date: 20190403


6 TEST RESULT

6.1 RF Power Output-FCC Part 2.1046

Ambient condition:

Temperature	Relative humidity	Pressure
25°C	30%	101.9kPa

Test Setup:



GSM850

Test procedure:

After a radio link has been established between EUT and Tester, the output power of the cell signal of the testing equipment will be decreased until the output power of the EUT reach a maximum value. Then the test data can be read at the tester screen. The loss between RF output port of the EUT and the input port of the tester will be taken into consideration. The measurement will be conducted at three channels No128, No189 and No251 (Bottom, middle and top channels of GSM850 band)

Limits	≤33.0dBm
--------	----------

PCS1900

Test procedure:

After a radio link has been established between EUT and Tester, the output power of the cell signal of the testing equipment will be decreased until the output power of the EUT reach a maximum value. Then the test data can be read at the tester screen. The loss between RF output port of the EUT and the input port of the tester will be taken into consideration. The measurement will be conducted at three channels No512, No661 and No810 (Bottom, middle and top channels of PCS1900 band)

Limits	≤30.0dBm
--------	----------

Test result:


The test results are shown in Appendix A.

6.2 Effective Radiated Power-FCC Part 22.913(a)/Part 24.232(c)

Ambient condition:

Temperature	Relative humidity	Pressure
25°C	30%	101.9kPa

Test Setup:



GSM850

Test procedure:

After a radio link has been established between EUT and Tester, the output power of the cell signal of the testing equipment will be decreased until the output power of the EUT reach a maximum value. Then the test data can be read at the tester screen. The loss between RF output port of the EUT and the input port of the tester will be taken into consideration.

$$\text{Power (EIRP)} = P_{\text{mea}} + G_a$$

This value is EIRP since the measurement is calibrated using an antenna of known gain (2.15dB) and known input power. ERP can be calculated from EIRP by subtracting the gain of the dipole, $\text{ERP} = \text{EIRP} - 2.15 \text{ (dB)}$.

The measurement will be done at three channels No128, No189 and No251 (Bottom, middle and top channels of GSM850 band)

Limits:

Operation Mode	Power Step	E.R.P. (dBm)
GSM	5	≤38.45
GPRS	3	≤38.45
EDGE	6	≤38.45

PCS1900

Test procedure:

After a radio link has been established between EUT and Tester, the output power of the cell signal of the testing equipment will be decreased until the output power of the EUT reach a maximum value. Then the test data can be read at the tester screen. The loss between RF output port of the EUT and the input port of the tester will be taken into consideration.

$$\text{Power (EIRP)} = P_{\text{mea}} + G_a$$

The measurement will be done at three channels No512, No661 and No810 (Bottom, middle and top channels of PCS1900 band)

Limits:

Operation Mode	Power Step	E.I.R.P. (dBm)
GSM	0	≤33
GPRS	3	≤33
EDGE	5	≤33

Test result:


The test results are shown in Appendix A.

6.3 Occupied Bandwidth-FCC Part 2.1049

Ambient condition:

Temperature	Relative humidity	Pressure
25°C	30%	101.9kPa

Test Setup:



GSM850

Test procedure:

After a radio link has been established between EUT and Tester, the output power of the cell signal of the testing equipment will be decreased until the output power of the EUT reach a maximum value. The occupied bandwidth is measured using spectrum analyzer. RBW is set to 3kHz on spectrum analyzer. The bandwidth of 99% power can be read on spectrum analyzer.

The measurement will be conducted at three channels No128, No189 and No251 (Bottom, middle and top channels of GSM850 band)

Limits: No specific occupied bandwidth requirements in part 2.1049

PCS1900

Test procedure:

After a radio link has been established between EUT and Tester, the output power of the cell signal of the testing equipment will be decreased until the output power of the EUT reach a maximum value. The occupied bandwidth is measured using spectrum analyzer. RBW is set to 3kHz on spectrum analyzer. The bandwidth of 99% power can be read on spectrum analyzer.

The measurement will be conducted at three channels No512, No661 and No810 (Bottom, middle and top channels of PCS1900 band)

Limits: No specific occupied bandwidth requirements in part 2.1049

Test result:


The test results are shown in Appendix A.

6.4 Emission Bandwidth-FCC Part 22.917(b)/Part 24.238(b)

Ambient condition:

Temperature	Relative humidity	Pressure
25°C	30%	101.9kPa

Test Setup:



GSM850

Test procedure:

After a radio link has been established between EUT and Tester, the output power of the cell signal of the testing equipment will be decreased until the output power of the EUT reach a maximum value. The emission bandwidth is measured using spectrum analyzer. RBW is set to 3kHz on spectrum analyzer. The bandwidth of -26dB transmitter power can be read on spectrum analyzer.

The measurement will be conducted at three channels No128, No189 and No251 (Bottom, middle and top channels of GSM850 band)

Limits: No specific emission bandwidth requirements in part 22.917(b)

PCS1900

Test procedure:

After a radio link has been established between EUT and Tester, the output power of the cell signal of the testing equipment will be decreased until the output power of the EUT reach a maximum value. The emission bandwidth is measured using spectrum analyzer. RBW is set to 3kHz on spectrum analyzer. The bandwidth of -26dB transmitter power can be read on spectrum analyzer.

The measurement will be conducted at three channels No512, No661 and No810 (Bottom, middle and top channels of PCS1900 band)

Limits: No specific emission bandwidth requirements in part 24.238(b)

Test result:


The test results are shown in Appendix A.

6.5 Spurious Emissions at antenna terminal-FCC Part 2.1051/ 22.917(a) /Part 24.238(a)

Ambient condition:

Temperature	Relative humidity	Pressure
25°C	30%	101.9kPa

Test Setup:



GSM850

Test procedure:

After a radio link has been established between EUT and Tester, the output power of the cell signal of the testing equipment will be decreased until the output power of the EUT reach a maximum value. The measurement is carried out using a spectrum analyzer. The spectrum analyzer scans from 30MHz to 9GHz (higher than the 10th harmonic of the carrier). The peak detector is used and RBW is set to 1MHz on spectrum analyzer.

The measurement will be conducted at one channel No189 (middle channel of GSM850 band)

Limits	≤-13dBm
--------	---------

PCS1900

Test procedure:

After a radio link has been established between EUT and Tester, the output power of the cell signal of the testing equipment will be decreased until the output power of the EUT reach a maximum value. The measurement is carried out using a spectrum analyzer. The spectrum analyzer scans from 30MHz to 20GHz (higher than the 10th harmonic of the carrier). The peak detector is used and RBW is set to 1MHz on spectrum analyzer.

The measurement will be conducted at one channel No661 (middle channel of PCS1900 band)

Limits	≤-13dBm
--------	---------

Test result:


The test results are shown in Appendix A.

6.6 Band Edges Compliance- FCC Part 2.1051/ 22.917(a) /Part 24.238(a)

Ambient condition:

Temperature	Relative humidity	Pressure
25°C	30%	101.9kPa

Test Setup:



GSM850

Test procedure:

After a radio link has been established between EUT and Tester, the output power of the cell signal of the testing equipment will be decreased until the output power of the EUT reach a maximum value. The measurement is carried out using a spectrum analyzer. The peak detector is used and RBW is set to at least 1% of the emission bandwidth on spectrum analyzer.

The measurement will be conducted at two channels No128 and No251 (Bottom and top channels of GSM850 band)

Limits	$\leq -13\text{dBm}$
--------	----------------------

PCS1900

Test procedure:

After a radio link has been established between EUT and Tester, the output power of the cell signal of the testing equipment will be decreased until the output power of the EUT reach a maximum value. The measurement is carried out using a spectrum analyzer. The peak detector is used and RBW is set to at least 1% of the emission bandwidth on spectrum analyzer.

The measurement will be conducted at two channels No512 and No810 (Bottom and top channels of PCS1900 band)

Limits	$\leq -13\text{dBm}$
--------	----------------------

Test result:


The test results are shown in Appendix A.

6.7 Frequency Stability- FCC Part 2.1055/22.355 /Part 24.235

Ambient condition:

Temperature	Relative humidity	Pressure
25°C	30%	101.9kPa

Test setup:



GSM850

Test Procedure:

A radio link shall be established between EUT and Tester. The tester will sample the transmitter RF output signal and measure its frequency. The temperature inside the climate chamber is varied from -30 to +50°C in 10°C step size, and also the DC power supply voltage to the EUT is varied from LV to HV. The measurement will be conducted at three channels No128, No189 and No251 (Bottom, middle and top channels of GSM850 band).

Limits: No specific frequency stability requirements in part 2.1055 and part 22.355.

PCS1900

Test Procedure:

A radio link shall be established between EUT and Tester. The tester will sample the transmitter RF output signal and measure its frequency. The temperature inside the climate chamber is varied from -30 to +50°C in 10°C step size, and also the DC power supply voltage to the EUT is varied from LV to HV. The measurement will be conducted at three channels No512, No661 and No810 (Bottom, middle and top channels of PCS1900 band).

Limits: No specific frequency stability requirements in part 2.1055 and part 24.235.

Test result:


The test results are shown in Appendix A.

6.8 Radiated Spurious Emissions-FCC Part2.1053/ 22.917(a)/Part 24.238(a)

Ambient condition:

Temperature	Relative humidity	Pressure
25°C	30%	101.9kPa

Test Setup:



GSM850

Test procedure:

The measurements procedures in TIA-603C-2004 are used.

The spectrum was scanned from 30MHz to the 10th harmonic of the highest frequency generated within the equipment.

Step 1:

The measurement is carried out in the fully anechoic chamber. EUT was placed on a 2.4 meter high non-conductive table at a 3 meter test distance from the test receive antenna. A receiving antenna was placed on the antenna mast 3 meters from the EUT. The height of receiving antenna is 2.4m and varies in certain range to find the maximum power value. A radio link shall be established between EUT and Tester. The output power of the cell signal of the tester will be decreased until the output power of the EUT reach a maximum value. The measurement is carried out using a spectrum analyzer or receiver. The spectrum analyzer scans from 30MHz to 20GHz (higher than the 10th harmonic of the carrier). The peak detector is used and RBW is set to 1MHz on spectrum analyzer. Then the antenna height and turn table rotation is adjusted till the maximum power value is founded on spectrum analyzer or receiver. A notch filter is necessary in the band near to the carrier frequency. A high pass filter is needed to avoid the distortion of the testing equipment in the band above the carrier frequency.

Step 2:

A log-periodic antenna or double-ridged waveguide horn antenna shall be substituted in place of the EUT. The log-periodic antenna will be driven by a signal generator and the level will be adjusted till the same power value on the spectrum analyzer or receiver. The level of the spurious emissions can be calculated through the level of the signal generator, cable loss, the gain of the substitution antenna and the reading of the spectrum analyzer or receiver.

A power (P_{mea}) is applied to the input of the substitution antenna, and adjusts the level of the signal generator output until the value of the receiver reach the previously recorded (P_r). The power of signal source (P_{mea}) is recorded. The test should be performed by rotating the test item and adjusting the receiving antenna polarization.

A "reference path loss" should be calculated after test. The attenuation of "reference path loss" is the cable loss between the Signal Source with the Substitution Antenna (P_{ca}) and the Substitution Antenna Gain (G_a).

Calculation procedure:

The data of cable loss and antenna gain has been calibrated in full testing frequency range before the testing.

The power of the Radiated Spurious Emissions is calculated by adding the cable loss and antenna gain. The basic equation with a sample calculation is as followed:

$$\text{Power(EIRP)} = P_{mea} + P_{ca} + G_a$$

This value is EIRP since the measurement is calibrated using an antenna of known gain (2.15dB) and known input power. ERP can be calculated from EIRP by subtracting the gain of the dipole, $ERP = EIRP - 2.15 \text{ (dB)}$.

Assumed the power of signal source record is -20dBm. A cable loss of -30dB, and an antenna gain of 11dB are added.

$$P=P_{\text{mea}}+P_{\text{ca}}+G_a=(-20\text{dBm})+(-30\text{dB})+(11\text{dB})= -39\text{dBm}$$

The measurement will be done at carrier frequencies that pertain to bottom (Channel 128), middle (Channel 189) and top (Channel 251) channels of the GSM 850 band.

PCS1900

Test procedure:

The measurements procedures in TIA-603C-2004 are used.

The spectrum was scanned from 30MHz to the 10th harmonic of the highest frequency generated within the equipment.

Step 1:

The measurement is carried out in the fully anechoic chamber. EUT was placed on a 2.4 meter high non-conductive table at a 3 meter test distance from the test receive antenna. A receiving antenna was placed on the antenna mast 3 meters from the EUT. The height of receiving antenna is 2.4m and varies in certain range to find the maximum power value. A radio link shall be established between EUT and Tester. The output power of the cell signal of the tester will be decreased until the output power of the EUT reach a maximum value. The measurement is carried out using a spectrum analyzer or receiver. The spectrum analyzer scans from 30MHz to 20GHz (higher than the 10th harmonic of the carrier). The peak detector is used and RBW is set to 1MHz on spectrum analyzer. Then the antenna height and turn table rotation is adjusted till the maximum power value is founded on spectrum analyzer or receiver. A notch filter is necessary in the band near to the carrier frequency. A high pass filter is needed to avoid the distortion of the testing equipment in the band above the carrier frequency.

Step 2:

A log-periodic antenna or double-ridged waveguide horn antenna shall be substituted in place of the EUT. The log-periodic antenna will be driven by a signal generator and the level will be adjusted till the same power value on the spectrum analyzer or receiver. The level of the spurious emissions can be calculated through the level of the signal generator, cable loss, the gain of the substitution antenna and the reading of the spectrum analyzer or receiver.

A power (P_{mea}) is applied to the input of the substitution antenna, and adjusts the level of the signal generator output until the value of the receiver reach the previously recorded (P_r). The power of signal source (P_{mea}) is recorded. The test should be performed by rotating the test item and adjusting the receiving antenna polarization.

A "reference path loss" should be calculated after test. The attenuation of "reference path loss" is the cable loss between the Signal Source with the Substitution Antenna (P_{ca}) and the Substitution Antenna Gain (G_a).

Calculation procedure:

The data of cable loss and antenna gain has been calibrated in full testing frequency range before the testing.

The power of the Radiated Spurious Emissions is calculated by adding the cable loss and antenna gain. The basic equation with a sample calculation is as followed:

$$\text{Power(EIRP)} = P_{\text{mea}} + P_{\text{ca}} + G_{\text{a}}$$

This value is EIRP since the measurement is calibrated using an antenna of known gain (2.15dB) and known input power. ERP can be calculated from EIRP by subtracting the gain of the dipole, $\text{ERP} = \text{EIRP} - 2.15 \text{ (dB)}$.

Assumed the power of signal source record is -20dBm. A cable loss of -30dB and an antenna gain of 11dB are added.

$$P = P_{\text{mea}} + P_{\text{ca}} + G_{\text{a}} = (-20\text{dBm}) + (-30\text{dB}) + (11\text{dB}) = -39\text{dBm}$$

The measurement will be done at carrier frequencies that pertain to bottom (Channel 512), middle (Channel 661) and top (Channel 810) channels of PCS 1900 band.

Test result:


The test results are shown in Appendix B.

6.9 Peak-Average Ratio -FCC Part 24.232(d)

Ambient condition:

Temperature	Relative humidity	Pressure
25°C	30%	101.9kPa

Test Setup:



Test procedure:

After a radio link has been established between EUT and Tester, the output power of the cell signal of the testing equipment will be decreased until the output power of the EUT reach a maximum value. The Peak-Average Ratio is measured using spectrum analyzer. RBW is set to 30kHz on spectrum analyzer. The Peak-Average Ratio can be read on spectrum analyzer.

Limits: the peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.

Test result:

The test results are shown in Appendix A

7 MEASUREMENT UNCERTAINTIES

Items	Uncertainty	
Occupied Bandwidth	3kHz	
Peak power output	0.67dB	
Band edge compliance	1.20dB	
Spurious emissions	30MHz~1GHz	2.83dB
	1GHz~12.75GHz	2.50dB
	12.75GHz~25GHz	2.75dB

8 TEST EQUIPMENTS

No.	Name/Model	Manufacturer	S/N	Calibration Date	Calibration Due Date
1	E5515C(8960) Mobile Station Tester	Agilent	MY50266302	2018.08.20	2019.08.19
2	N9020A Spectrum Analyzer	Agilent	MY48010771	2018.08.20	2019.08.19
3	6007 Power Divider	Weinschel	6007-GJ-1	2018.08.20	2019.08.19
4	DC Power Supply E3645A	Agilent	MY40000741	2019.03.01	2020.02.28
5	Temperature chamber SH241	ESPEC	92013758	2018.08.20	2019.08.19
6	12.65m×8.03m×7.50m Fully-Anechoic Chamber	FRANKONIA	-----	-----	-----
7	23.18m×16.88m×9.60m Semi-Anechoic Chamber	FRANKONIA	---	-----	-----
8	Turn table Diameter:1m	FRANKONIA	-----	-----	-----
9	Turn table Diameter:5m	FRANKONIA	-----	-----	-----
10	Antenna master FAC(MA4.0)	MATURO	-----	-----	-----
11	Antenna master SAC(MA4.0)	MATURO	-----	-----	-----
12	9.080m×5.255m×3.525m Shielding room	FRANKONIA	-----	-----	-----
13	HF 907 Double-Ridged Waveguide Horn Antenna	R&S	100512	2018.08.20	2019.08.19
14	HF 907 Double-Ridged Waveguide Horn Antenna	R&S	100513	2018.08.20	2019.08.19
15	HL562 Ultra log antenna	R&S	100016	2018.08.20	2019.08.19
16	3160-09 Receive antenna	SCHWARZ-BECK	002058-002	2018.08.20	2019.08.19
17	ESI 40 EMI test receiver	R&S	100015	2018.08.20	2019.08.19
18	ESCS30 EMI test receiver	R&S	100029	2018.08.20	2019.08.19
19	HL562 Receive antenna	R&S	100167	2018.08.20	2019.08.19
20	ENV216 AMN	R&S	3560.6550.12	2018.08.20	2019.08.19

APPENDIX A – TEST DATA OF CONDUCTED EMISSION

Please refer to the attachment.

APPENDIX B – TEST DATA OF RADIATED EMISSION

Please refer to the attachment.

APPENDIX A – TEST DATA OF CONDUCTED EMISSION

RF Power Output-FCC Part2.1046

GSM850

Main Antenna Gain=-3.42dBi

GSM Measured Power:

Carrier frequency (MHz)	Channel No.	RF Power Output (dBm)	ERP (W)
824.2	128	33.03	0.557
836.4	189	33.08	0.564
848.8	251	33.11	0.568

GPRS Measured Power:

Carrier frequency (MHz)	Channel No.	TX Mode	RF Power Output (dBm)	ERP (W)
824.2	128	4Downlink1uplink	33.03	0.557
836.4	189		33.08	0.564
848.8	251		33.11	0.568
824.2	128	3Downlink2uplink	31.03	0.352
836.4	189		31.01	0.350
848.8	251		31.02	0.351
824.2	128	2Downlink3uplink	28.64	0.203
836.4	189		28.61	0.201
848.8	251		28.59	0.200
824.2	128	1Downlink4uplink	27.21	0.146
836.4	189		27.20	0.146
848.8	251		27.18	0.145

EGPRS (GMSK) Measured Power:

Carrier frequency (MHz)	Channel No.	TX Mode	RF Power Output (dBm)	ERP (W)
824.2	128	GMSK 4Downlink1uplink	33.00	0.553
836.4	189		33.05	0.560
848.8	251		33.08	0.564
824.2	128	GMSK 3Downlink2uplink	31.02	0.351
836.4	189		31.01	0.350
848.8	251		30.99	0.348
824.2	128	GMSK 2Downlink3uplink	28.64	0.203
836.4	189		28.61	0.201
848.8	251		28.59	0.200
824.2	128	GMSK 1Downlink4uplink	27.22	0.146
836.4	189		27.20	0.146
848.8	251		27.17	0.145

EGPRS (8DPSK) Measured Power:

Carrier frequency (MHz)	Channel No.	TX Mode	RF Power Output (dBm)	ERP (W)
824.2	128	8DPSK 4Downlink1uplink	25.20	0.092
836.4	189		25.36	0.095
848.8	251		25.47	0.098
824.2	128	8DPSK 3Downlink2uplink	23.84	0.067
836.4	189		24.27	0.074
848.8	251		24.30	0.075
824.2	128	8DPSK 2Downlink3uplink	21.84	0.042
836.4	189		21.95	0.043
848.8	251		22.03	0.044
824.2	128	8DPSK 1Downlink4uplink	19.48	0.025
836.4	189		19.71	0.026
848.8	251		19.62	0.025

PCS1900

Main Antenna Gain=1.42dBi

GSM Measured Power:

Carrier frequency (MHz)	Channel No.	RF Power Output (dBm)	EIRP (W)
1850.2	512	29.64	1.276
1880.0	661	29.39	1.205
1909.8	810	29.41	1.211

GPRS Measured Power:

Carrier frequency (MHz)	Channel No.	TX Mode	RF Power Output (dBm)	EIRP (W)
1850.2	512	4Downlink1uplink	29.66	1.282
1880.0	661		29.49	1.233
1909.8	810		29.43	1.216
1850.2	512	3Downlink2uplink	27.45	0.771
1880.0	661		27.23	0.733
1909.8	810		27.03	0.700
1850.2	512	2Downlink3uplink	25.50	0.492
1880.0	661		25.29	0.469
1909.8	810		25.06	0.445
1850.2	512	1Downlink4uplink	23.41	0.304
1880.0	661		23.20	0.290
1909.8	810		23.02	0.278

EGPRS (GMSK) Measured Power:

Carrier frequency (MHz)	Channel No.	TX Mode	RF Power Output (dBm)	EIRP (W)
1850.2	512	GMSK 4Downlink1uplink	29.64	1.276
1880.0	661		29.47	1.227
1909.8	810		29.42	1.213
1850.2	512	GMSK 3Downlink2uplink	27.45	0.771
1880.0	661		27.23	0.733
1909.8	810		27.04	0.701
1850.2	512	GMSK 2Downlink3uplink	25.51	0.493
1880.0	661		25.29	0.469
1909.8	810		25.05	0.444
1850.2	512	GMSK 1Downlink4uplink	23.41	0.304
1880.0	661		23.20	0.290
1909.8	810		23.00	0.277

EGPRS (8DPSK) Measured Power:

Carrier frequency (MHz)	Channel No.	TX Mode	RF Power Output (dBm)	EIRP (W)
1850.2	512	8DPSK 4Downlink1uplink	24.45	0.386
1880.0	661		24.99	0.438
1909.8	810		24.48	0.389
1850.2	512	8DPSK 3Downlink2uplink	23.11	0.284
1880.0	661		23.77	0.330
1909.8	810		22.90	0.270
1850.2	512	8DPSK 2Downlink3uplink	20.41	0.152
1880.0	661		20.88	0.170
1909.8	810		20.24	0.147
1850.2	512	8DPSK 1Downlink4uplink	17.71	0.082
1880.0	661		17.98	0.087
1909.8	810		17.68	0.081

Occupied Bandwidth-FCC Part2.1049

GSM850

GSM/GPRS MODE:

Carrier frequency (MHz)	Channel No.	Bandwidth of 99% Power (kHz)
824.2	128	239.20
836.4	189	240.39
848.8	251	237.75

EDGE (GMSK) MODE:

Carrier frequency (MHz)	Channel No.	Bandwidth of 99% Power (kHz)
824.2	128	242.13
836.4	189	242.31
848.8	251	243.60

PCS1900

GSM/GPRS MODE:


Carrier frequency (MHz)	Channel No.	Bandwidth of 99% Power (kHz)
1850.2	512	241.31
1880.0	661	236.96
1909.8	810	243.81

EDGE (GMSK) MODE:


Carrier frequency (MHz)	Channel No.	Bandwidth of 99% Power (kHz)
1850.2	512	243.12
1880.0	661	243.23
1909.8	810	241.83

GSM850


GSM/GPRS MODE:



Channel 128




Channel 189




Channel 251


EDGE (GMSK) MODE:



Channel 128




Channel 189




Channel 251

PCS1900


GSM/GPRS MODE:



Channel 512




Channel 661




Channel 810


EDGE (GMSK) MODE:



Channel 512



Channel 661



Channel 810

Emission Bandwidth-FCC Part 22.917(b)/Part 24.238(b)

GSM850

GSM/GPRS MODE:

Carrier frequency (MHz)	Channel No.	Bandwidth of -26dB transmitter power (kHz)
824.2	128	309.9
836.4	189	311.7
848.8	251	313.9

EDGE (GMSK) MODE:

Carrier frequency (MHz)	Channel No.	Bandwidth of -26dB transmitter power (kHz)
824.2	128	319.7
836.4	189	317.4
848.8	251	317.4

PCS1900

GSM/GPRS MODE:


Carrier frequency (MHz)	Channel No.	Bandwidth of -26dB transmitter power (kHz)
1850.2	512	308.2
1880.0	661	306.6
1909.8	810	310.2

EDGE (GMSK) MODE:


Carrier frequency (MHz)	Channel No.	Bandwidth of -26dB transmitter power (kHz)
1850.2	512	315.3
1880.0	661	321.0
1909.8	810	320.2

**Spurious Emissions at antenna terminal- FCC Part 2.1051/ 22.917(a) /Part 24.238(a)
GSM850**

GSM/GPRS MODE:




Channel 189, 30MHz~1GHz




Channel 189, 1GHz~10GHz

Note: The signal beyond the limit is the signal transmitted by EUT.

EDGE (GMSK) MODE:



Channel 189, 30MHz~1GHz




Channel 189, 1GHz~10GHz


Note: The signal beyond the limit is the signal transmitted by EUT.

PCS1900

GSM/GPRS MODE:




Channel 661, 30MHz~1GHz




Channel 661, 1GHz~20GHz

Note: The signal beyond the limit is the signal transmitted by EUT.

EDGE (GMSK) MODE:



Channel 661, 30MHz~1850MHz




Channel 661, 1GHz~20GHz

Note: The signal beyond the limit is the signal transmitted by EUT.


Band Edges Compliance- FCC Part 2.1051/ 22.917(a) /Part 24.238(a)

GSM850

GSM/GPRS MODE:




Channel 128




Channel 251

EDGE (GMSK) MODE:




Channel 128




Channel 251

PCS1900

GSM/GPRS MODE:




Channel 512




Channel 810

EDGE (GMSK) MODE:



Channel 512



Channel 810

Frequency Stability- FCC Part 2.1055/22.355 /Part 24.235

GSM850

GSM/GPRS MODE:

Temperature(°C)	Test Result (ppm)@NV		
	Channel 128	Channel 189	Channel 251
0	0.005	0.000	0.014
+10	0.009	0.003	0.010
+20	-0.003	-0.003	0.000
+30	-0.008	-0.001	-0.006
+40	0.010	0.000	0.013
+50	-0.013	-0.009	0.005
+55	-0.008	0.009	-0.008

Voltage	Test Result (ppm)@NT		
	Channel 128	Channel 189	Channel 251
LV	-0.007	0.009	-0.005
HV	0.008	-0.007	-0.002

EDGE (GMSK) MODE:

Temperature(°C)	Test Result (ppm)@NV		
	Channel 128	Channel 189	Channel 251
0	-0.007	0.001	0.010
+10	0.012	-0.008	0.017
+20	-0.002	0.000	0.005
+30	-0.009	0.013	-0.007
+40	0.013	-0.003	-0.005
+50	-0.012	0.002	-0.005
+55	-0.010	0.005	-0.003

Voltage	Test Result (ppm)@NT		
	Channel 128	Channel 189	Channel 251
LV	0.005	0.001	-0.010
HV	0.008	-0.010	-0.004

PCS1900

GSM/GPRS MODE:

Temperature(°C)	Test Result (ppm)@NV		
	Channel 512	Channel 661	Channel 810
0	0.002	-0.001	-0.012
+10	-0.005	0.012	0.015
+20	0.008	0.006	0.004
+30	0.003	0.004	0.012
+40	0.014	-0.001	-0.010
+50	-0.006	0.009	-0.002
+55	0.015	-0.013	0.012

Voltage	Test Result (ppm)@NT		
	Channel 512	Channel 661	Channel 810
LV	0.001	-0.002	0.006
HV	0.008	-0.008	0.011

EDGE (GMSK) MODE:


Temperature(°C)	Test Result (ppm)@NV		
	Channel 512	Channel 661	Channel 810
0	0.019	-0.006	0.000
+10	0.000	-0.006	0.003
+20	0.013	-0.014	0.004
+30	-0.010	-0.002	0.013
+40	0.002	0.009	0.006
+50	0.013	0.011	-0.012
+55	-0.012	0.000	-0.006

Voltage	Test Result (ppm)@NT		
	Channel 512	Channel 661	Channel 810
LV	0.015	0.001	-0.010
HV	0.010	-0.014	-0.001


Peak-Average Ratio -FCC Part 24.232(d)

GSM850

GSM/GPRS MODE:




EDGE (GMSK) MODE:




PCS1900

GSM/GPRS MODE:



EDGE (GMSK) MODE:



APPENDIX B – TEST DATA OF RADIATED EMISSION

GSM850 Test result:

GSM/GPRS MODE Channel 128:

Frequency (MHz)	Power (dBm)	Limited (dBm)	Polarization
1644.30	-53.12	-13	Vertical
1670.49	-51.15	-13	Vertical
2533.56	-44.38	-13	Vertical
2575.28	-43.27	-13	Vertical
8966.23	-39.87	-13	Vertical
9971.25	-36.34	-13	Vertical

EDGE (GMSK) MODE Channel 128:

Frequency (MHz)	Power (dBm)	Limited (dBm)	Polarization
1644.43	-53.18	-13	Vertical
1670.09	-50.85	-13	Vertical
2533.03	-44.10	-13	Vertical
2575.30	-43.35	-13	Vertical
8963.50	-39.30	-13	Vertical
9969.09	-35.86	-13	Vertical

GSM/GPRS MODE Channel 189:

Frequency (MHz)	Power (dBm)	Limited (dBm)	Polarization
1646.75	-53.05	-13	Vertical
1670.34	-50.92	-13	Vertical
2533.73	-44.13	-13	Vertical
2575.93	-44.12	-13	Vertical
8962.55	-39.45	-13	Vertical
9972.62	-35.93	-13	Horizontal

EDGE (GMSK) MODE Channel 189:

Frequency (MHz)	Power (dBm)	Limited (dBm)	Polarization
1645.81	-53.27	-13	Vertical
1668.94	-51.24	-13	Vertical
2536.28	-44.21	-13	Vertical
2574.95	-43.90	-13	Vertical
8965.97	-39.27	-13	Vertical
9972.49	-36.64	-13	Vertical

GSM/GPRS MODE Channel 251:

Frequency (MHz)	Power (dBm)	Limited (dBm)	Polarization
1647.41	-53.13	-13	Vertical
1669.06	-50.65	-13	Vertical
2536.16	-43.71	-13	Vertical
2575.88	-43.67	-13	Horizontal
8965.72	-39.55	-13	Vertical
9970.20	-36.69	-13	Vertical

EDGE (GMSK) MODE Channel 251:

Frequency (MHz)	Power (dBm)	Limited (dBm)	Polarization
1647.55	-53.11	-13	Vertical
1668.76	-51.57	-13	Vertical
2535.33	-43.81	-13	Vertical
2573.54	-43.18	-13	Vertical
8964.86	-40.00	-13	Vertical
9971.11	-36.07	-13	Vertical

GSM1900 Test result:

GSM/GPRS MODE Channel 512

Frequency (MHz)	Power (dBm)	Limited (dBm)	Polarization
2453.01	-52.40	-13	Vertical
2780.78	-51.37	-13	Vertical
3728.09	-43.95	-13	Horizontal
6678.87	-43.76	-13	Vertical
9965.10	-40.04	-13	Vertical
17820.50	-36.19	-13	Vertical

EDGE (GMSK) MODE Channel 512:

Frequency (MHz)	Power (dBm)	Limited (dBm)	Polarization
2455.65	-53.13	-13	Vertical
2779.65	-52.20	-13	Vertical
3728.76	-43.54	-13	Vertical
6677.57	-43.20	-13	Vertical
9964.31	-40.20	-13	Vertical
17822.18	-35.57	-13	Vertical

GSM/GPRS MODE Channel 661:

Frequency (MHz)	Power (dBm)	Limited (dBm)	Polarization
2455.29	-53.14	-13	Vertical
2779.36	-51.41	-13	Vertical
3729.72	-44.25	-13	Vertical
6676.69	-43.46	-13	Vertical
9964.62	-40.09	-13	Vertical
17823.12	-35.89	-13	Vertical

EDGE (GMSK) MODE Channel 661:

Frequency (MHz)	Power (dBm)	Limited (dBm)	Polarization
2456.07	-53.10	-13	Vertical
2780.74	-52.02	-13	Vertical
3729.05	-44.23	-13	Vertical
6678.15	-43.92	-13	Horizontal
9962.93	-40.07	-13	Vertical
17824.24	-35.97	-13	Vertical

GSM/GPRS MODE Channel 810:

Frequency (MHz)	Power (dBm)	Limited (dBm)	Polarization
2454.92	-52.41	-13	Vertical
2779.58	-51.78	-13	Vertical
3727.60	-43.58	-13	Vertical
6679.23	-43.73	-13	Vertical
9965.16	-39.82	-13	Vertical
17824.35	-35.56	-13	Vertical

EDGE (GMSK) MODE Channel 810:

Frequency (MHz)	Power (dBm)	Limited (dBm)	Polarization
2453.97	-52.70	-13	Vertical
2778.51	-51.51	-13	Vertical
3727.89	-43.70	-13	Vertical
6679.02	-43.72	-13	Vertical
9961.28	-39.54	-13	Vertical
17820.77	-35.53	-13	Vertical

---End of Test Report---