


Right Side	Cheek
<p>Communication System: UID 0, FDD-LTE(QPSK_15M_1RB_low) (0); Communication System Band: BAND4; Frequency: 1732.5 MHz; Communication System PAR: 0 dB Medium parameters used : f = 1732.5 MHz; $\sigma = 1.374$ S/m; $\epsilon_r = 39.262$; $\rho = 1000$ kg/m³ Phantom section: Right Section Measurement Standard: DASYS5 (IEEE1528-2013) DASYS5 Configuration:</p> <ul style="list-style-type: none"> Probe: ES3DV3 - SN3297; ConvF(5.22, 5.22, 5.22); Calibrated: 14/10/2016; Sensor-Surface: 3mm (Mechanical Surface Detection) Electronics: DAE4 Sn1226; Calibrated: 28/09/2016 Phantom: SAM2; Type: SAM; Serial: TP-1575 Measurement SW: DASYS52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331) right/touch mid 15M/Area Scan (91x161x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm Maximum value of SAR = 0.208 W/kg right/touch mid 15M/ Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm Reference Value = 6.179 V/m; Power Drift = 0.14 dB Peak SAR (extrapolated) = 0.386 W/kg SAR(1 g) = 0.171 W/kg; SAR(10 g) = 0.103 W/kg. Maximum value of SAR (measured) = 0.199 W/kg <div data-bbox="199 1205 1385 1657"> </div> <p>0 dB = 0.208 W/kg = -6.82 dBW/kg</p>	



Right Side	Tilt
<p>Communication System: UID 0, FDD-LTE(QPSK_15M_1RB_low) (0); Communication System Band: BAND4; Frequency: 1732.5 MHz; Communication System PAR: 0 dB Medium parameters used : f = 1732.5 MHz; $\sigma = 1.374$ S/m; $\epsilon_r = 39.262$; $\rho = 1000$ kg/m³ Phantom section: Right Section Measurement Standard: DASY5 (IEEE1528-2013) DASY5 Configuration:</p> <ul style="list-style-type: none"> • Probe: ES3DV3 - SN3297; ConvF(5.22, 5.22, 5.22); Calibrated: 14/10/2016; • Sensor-Surface: 3mm (Mechanical Surface Detection) • Electronics: DAE4 Sn1226; Calibrated: 28/09/2016 • Phantom: SAM2; Type: SAM; Serial: TP-1575 • Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331) • right/tilt mid tn02 15M/Area Scan (91x161x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm Maximum value of SAR = 0.0918 W/kg right/tilt mid tn02 15M/ Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm Reference Value = 3.985 V/m; Power Drift = -0.10 dB Peak SAR (extrapolated) = 0.246 W/kg SAR(1 g) = 0.0736 W/kg; SAR(10 g) = 0.0432 W/kg. Maximum value of SAR (measured) = 0.0859 W/kg <div data-bbox="272 1205 1310 1659"> <p>0 dB = 0.0918 W/kg = -10.37 dBW/kg</p> </div>	

LTE (Band 4 15BW-1RB-Low/Flat)


FLAT	Towards phantom
Communication System: UID 0, FDD-LTE(QPSK_15M_1RB) (0); Communication System Band: BAND 4; Frequency: 1732.5 MHz; Communication System PAR: 0 dB	
Medium parameters used (interpolated): $f = 1732.5$ MHz; $\sigma = 1.496$ S/m; $\epsilon_r = 51.908$; $\rho = 1000$ kg/m ³	
Phantom section: Flat Section	
Measurement Standard: DASY5 (IEEE1528-2013)	
DASY5 Configuration:	
<ul style="list-style-type: none"> Probe: EX3DV4 - SN3717; ConvF(7.63, 7.63, 7.63); Calibrated: 19/10/2016; 	
<ul style="list-style-type: none"> Sensor-Surface: 1.4mm (Mechanical Surface Detection) 	
<ul style="list-style-type: none"> Electronics: DAE4 Sn1327; Calibrated: 15/04/2016 	
<ul style="list-style-type: none"> Phantom: SAM 1; Type: SAM; Serial: TP:1702 	
<ul style="list-style-type: none"> Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331) 	
body/towards phantom mid 15M/Area Scan (91x161x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm	
Maximum value of SAR (interpolated) = 0.753 W/kg	
body/towards phantom mid 15M/ Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm	
<ul style="list-style-type: none"> Reference Value = 8.858 V/m; Power Drift = -0.10 dB 	
Peak SAR (extrapolated) = 0.942 W/kg	
SAR(1 g) = 0.526 W/kg; SAR(10 g) = 0.302 W/kg	
Maximum value of SAR (measured) = 0.704 W/kg	
0 dB = 0.753 W/kg = -1.23 dBW/kg	

FLAT	Towards ground
<p>Communication System: UID 0, FDD-LTE(QPSK_15M_1RB) (0); Communication System Band: BAND 4; Frequency: 1732.5 MHz; Communication System PAR: 0 dB Medium parameters used (interpolated): $f = 1732.5$ MHz; $\sigma = 1.496$ S/m; $\epsilon_r = 51.908$; $\rho = 1000$ kg/m³ Phantom section: Flat Section Measurement Standard: DASY5 (IEEE1528-2013) DASY5 Configuration:</p> <ul style="list-style-type: none"> Probe: EX3DV4 - SN3717; ConvF(7.63, 7.63, 7.63); Calibrated: 19/10/2016; Sensor-Surface: 1.4mm (Mechanical Surface Detection) Electronics: DAE4 Sn1327; Calibrated: 15/04/2016 Phantom: SAM 1; Type: SAM; Serial: TP:1702 Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331) <p>body/towards ground mid 15M/Area Scan (91x161x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm Maximum value of SAR (interpolated) = 0.511 W/kg body/towards ground mid 15M/ Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm</p> <ul style="list-style-type: none"> Reference Value = 8.49 V/m; Power Drift = -0.14 dB Peak SAR (extrapolated) = 0.653 W/kg SAR(1 g) = 0.363 W/kg; SAR(10 g) = 0.216 W/kg Maximum value of SAR (measured) = 0.488 W/kg 	
 <p>0 dB = 0.511 W/kg = -2.92 dBW/kg</p>	

LTE (Band 5 10BW-1RB-Low /Head)

Left Side	Cheek
<p>Communication System: UID 0, FDD-LTE(QPSK_10M_1RB_low) (0); Communication System Band: BAND 5; Frequency: 836.5 MHz; Communication System PAR: 0 dB Medium parameters used : $f = 836.5 \text{ MHz}$; $\sigma = 0.883 \text{ S/m}$; $\epsilon_r = 41.293$; $\rho = 1000 \text{ kg/m}^3$ Phantom section: Left Section Measurement Standard: DASYS5 (IEEE1528-2013) DASYS5 Configuration:</p>	
<ul style="list-style-type: none"> • Probe: ES3DV3 - SN3297; ConvF(6.18, 6.18, 6.18); Calibrated: 14/10/2016; • Sensor-Surface: 3mm (Mechanical Surface Detection) • Electronics: DAE4 Sn1226; Calibrated: 28/09/2016 • Phantom: SAM1; Type: SAM; Serial: TP1576 • Measurement SW: DASYS52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331) • left/touch mid/Area Scan (91x161x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm. Maximum value of SAR = 0.208 W/kg left/touch mid/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm Reference Value = 5.930 V/m; Power Drift = 0.09 dB Peak SAR (extrapolated) = 0.242 W/kg SAR(1 g) = 0.189 W/kg; SAR(10 g) = 0.142 W/kg Maximum value of SAR (measured) = 0.211 W/kg 	
<div style="display: flex; align-items: center;"> <div style="margin-right: 20px;"> <p>dB</p>  </div> <div style="flex-grow: 1;">  </div> </div> <p style="text-align: center;">0 dB = 0.208 W/kg = -6.82 dBW/kg</p>	


Left Side	Tilt
<p>Communication System: UID 0, FDD-LTE(QPSK_10M_1RB_low) (0); Communication System Band: BAND 5; Frequency: 836.5 MHz; Communication System PAR: 0 dB Medium parameters used : $f = 836.5 \text{ MHz}$; $\sigma = 0.883 \text{ S/m}$; $\epsilon_r = 41.293$; $\rho = 1000 \text{ kg/m}^3$ Phantom section: Left Section Measurement Standard: DASYS5 (IEEE1528-2013) DASYS5 Configuration:</p> <ul style="list-style-type: none"> • Probe: ES3DV3 - SN3297; ConvF(6.18, 6.18, 6.18); Calibrated: 14/10/2016; • Sensor-Surface: 3mm (Mechanical Surface Detection) • Electronics: DAE4 Sn1226; Calibrated: 28/09/2016 • Phantom: SAM1; Type: SAM; Serial: TP1576 • Measurement SW: DASYS52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331) • left/tilt mid/Area Scan (91x161x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm Maximum value of SAR = 0.0873 W/kg left/tilt mid/ Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm Reference Value = 7.803 V/m; Power Drift = 0.10 dB Peak SAR (extrapolated) = 0.242 W/kg SAR(1 g) = 0.0764 W/kg; SAR(10 g) = 0.0536 W/kg Maximum value of SAR (measured) = 0.0865 W/kg <div data-bbox="274 1144 1310 1599"> </div>	

Right Side	Cheek
<p>Communication System: UID 0, FDD-LTE(QPSK_10M_1RB_low) (0); Communication System Band: BAND 5; Frequency: 836.5 MHz; Communication System PAR: 0 dB Medium parameters used : f = 836.5 MHz; $\sigma = 0.883$ S/m; $\epsilon_r = 41.293$; $\rho = 1000$ kg/m³ Phantom section: Right Section Measurement Standard: DASYS5 (IEEE1528-2013) DASYS5 Configuration:</p> <ul style="list-style-type: none"> • Probe: ES3DV3 - SN3297; ConvF(6.18, 6.18, 6.18); Calibrated: 14/10/2016; • Sensor-Surface: 3mm (Mechanical Surface Detection) • Electronics: DAE4 Sn1226; Calibrated: 28/09/2016 • Phantom: SAM1; Type: SAM; Serial: TP1576 • Measurement SW: DASYS52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331) • right/touch mid/Area Scan (91x161x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm <p>Maximum value of SAR = 0.189 W/kg right/touch mid/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm Reference Value = 5.614 V/m; Power Drift = 0.01 dB Peak SAR (extrapolated) = 0.215 W/kg SAR(1 g) = 0.172 W/kg; SAR(10 g) = 0.130 W/kg Maximum value of SAR (measured) = 0.189 W/kg</p>	
 <p style="text-align: center;">0 dB = 0.189 W/kg = -7.24 dBW/kg</p>	

Right Side	Tilt
<p>Communication System: UID 0, FDD-LTE(QPSK_10M_1RB_low) (0); Communication System Band: BAND 5; Frequency: 836.5 MHz; Communication System PAR: 0 dB Medium parameters used : $f = 836.5 \text{ MHz}$; $\sigma = 0.883 \text{ S/m}$; $\epsilon_r = 41.293$; $\rho = 1000 \text{ kg/m}^3$ Phantom section: Right Section Measurement Standard: DASY5 (IEEE1528-2013) DASY5 Configuration:</p> <ul style="list-style-type: none"> Probe: ES3DV3 - SN3297; ConvF(6.18, 6.18, 6.18); Calibrated: 14/10/2016; Sensor-Surface: 3mm (Mechanical Surface Detection) Electronics: DAE4 Sn1226; Calibrated: 28/09/2016 Phantom: SAM1; Type: SAM; Serial: TP1576 Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331) right/tilt mid/Area Scan (91x161x1): Interpolated grid: $dx=1.000 \text{ mm}$, $dy=1.000 \text{ mm}$. Maximum value of SAR = 0.103 W/kg right/tilt mid/ Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$ Reference Value = 8.247 V/m; Power Drift = 0.12 dB Peak SAR (extrapolated) = 0.146 W/kg SAR(1 g) = 0.0904 W/kg; SAR(10 g) = 0.0628 W/kg Maximum value of SAR (measured) = 0.103 W/kg <div data-bbox="199 1220 1385 1680"> <p>0 dB = 0.103 W/kg = -9.87 dBW/kg</p> </div>	


LTE (Band 5 10BW-1RB-Low/Flat)

FLAT	Towards phantom
<p>Communication System: UID 0, FDD-LTE(QPSK_10M_1RB_low) (0); Communication System Band: BAND 5; Frequency: 836.5 MHz; Communication System PAR: 0 dB Medium parameters used (interpolated): $f = 836.5$ MHz; $\sigma = 0.95$ S/m; $\epsilon_r = 54.245$; $\rho = 1000$ kg/m³ Phantom section: Flat Section Measurement Standard: DASY5 (IEEE1528-2013) DASY5 Configuration:</p> <ul style="list-style-type: none"> Probe: ES3DV3 - SN3297; ConvF(6.08, 6.08, 6.08); Calibrated: 14/10/2016; Sensor-Surface: 3mm (Mechanical Surface Detection) Electronics: DAE4 Sn1226; Calibrated: 28/09/2016 Phantom: SAM1; Type: SAM; Serial: TP1576 Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331) <p>body/towards phantom/Area Scan (91x161x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm Maximum value of SAR (interpolated) = 0.205 W/kg body/towards phantom/ Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm Reference Value = 14.77 V/m; Power Drift = 0.08 dB Peak SAR (extrapolated) = 0.276 W/kg SAR(1 g) = 0.182 W/kg; SAR(10 g) = 0.129 W/kg Maximum value of SAR (measured) = 0.204 W/kg</p> <div data-bbox="188 1238 1401 1691"> </div> <p>0 dB = 0.205 W/kg = -6.88 dBW/kg</p>	

FLAT	Towards ground
<p>Communication System: UID 0, FDD-LTE(QPSK_10M_1RB_low) (0); Communication System Band: BAND 5; Frequency: 836.5 MHz; Communication System PAR: 0 dB Medium parameters used (interpolated): $f = 836.5$ MHz; $\sigma = 0.95$ S/m; $\epsilon_r = 54.245$; $\rho = 1000$ kg/m³ Phantom section: Flat Section Measurement Standard: DASYS (IEEE1528-2013) DASY5 Configuration:</p> <ul style="list-style-type: none"> Probe: ES3DV3 - SN3297; ConvF(6.08, 6.08, 6.08); Calibrated: 14/10/2016; Sensor-Surface: 3mm (Mechanical Surface Detection) Electronics: DAE4 Sn1226; Calibrated: 28/09/2016 Phantom: SAM1; Type: SAM; Serial: TP1576 Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331) <p>body/towards ground/Area Scan (91x161x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm Maximum value of SAR (interpolated) = 0.427 W/kg body/towards ground/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm Reference Value = 21.49 V/m; Power Drift = -0.06 dB Peak SAR (extrapolated) = 0.494 W/kg SAR(1 g) = 0.386 W/kg; SAR(10 g) = 0.294 W/kg Maximum value of SAR (measured) = 0.427 W/kg</p>	
 <p>0 dB = 0.427 W/kg = -3.70 dBW/kg</p>	

FLAT	EDGE2
<p>Communication System: UID 0, FDD-LTE(QPSK_10M_1RB_low) (0); Communication System Band: BAND 5; Frequency: 836.5 MHz; Communication System PAR: 0 dB Medium parameters used (interpolated): $f = 836.5$ MHz; $\sigma = 0.95$ S/m; $\epsilon_r = 54.245$; $\rho = 1000$ kg/m³ Phantom section: Flat Section Measurement Standard: DASY5 (IEEE1528-2013) DASY5 Configuration:</p> <ul style="list-style-type: none"> Probe: ES3DV3 - SN3297; ConvF(6.08, 6.08, 6.08); Calibrated: 14/10/2016; Sensor-Surface: 3mm (Mechanical Surface Detection) Electronics: DAE4 Sn1226; Calibrated: 28/09/2016 Phantom: SAM1; Type: SAM; Serial: TP1576 Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331) <p>body/edge 2 mid/Area Scan (61x101x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm Maximum value of SAR (interpolated) = 0.0759 W/kg body/edge 2 mid/ Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm Reference Value = 7.374 V/m; Power Drift = 0.08 dB Peak SAR (extrapolated) = 0.126 W/kg SAR(1 g) = 0.0639 W/kg; SAR(10 g) = 0.0397 W/kg</p> <p>Maximum value of SAR (measured) = 0.0742 W/kg</p> <div style="display: flex; align-items: flex-start;"> <div style="margin-right: 20px;"> <p>dB</p> <p>0 -2.46 -4.93 -7.39 -9.86 -12.32</p> </div> <div> </div> </div> <p style="text-align: center;">0 dB = 0.0759 W/kg = -11.20 dBW/kg</p>	

FLAT	EDGE3
<p>Communication System: UID 0, FDD-LTE(QPSK_10M_1RB_low) (0); Communication System Band: BAND 5; Frequency: 836.5 MHz; Communication System PAR: 0 dB Medium parameters used (interpolated): $f = 836.5$ MHz; $\sigma = 0.95$ S/m; $\epsilon_r = 54.245$; $\rho = 1000$ kg/m³ Phantom section: Flat Section Measurement Standard: DASYS5 (IEEE1528-2013) DASY5 Configuration:</p> <ul style="list-style-type: none"> Probe: ES3DV3 - SN3297; ConvF(6.08, 6.08, 6.08); Calibrated: 14/10/2016; Sensor-Surface: 3mm (Mechanical Surface Detection) Electronics: DAE4 Sn1226; Calibrated: 28/09/2016 Phantom: SAM1; Type: SAM; Serial: TP1576 Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331) <p>body2/edge3 mid/Area Scan (61x161x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm. Maximum value of SAR (interpolated) = 0.167 W/kg body2/edge3 mid/ Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm Reference Value = 13.52 V/m; Power Drift = 0.09 dB Peak SAR (extrapolated) = 0.213 W/kg SAR(1 g) = 0.146 W/kg; SAR(10 g) = 0.0989 W/kg</p> <p>Maximum value of SAR (measured) = 0.165 W/kg</p> <div style="display: flex; align-items: flex-start;"> <div style="margin-right: 10px;"> <p>dB</p> <p>0 -3.01 -6.01 -9.02 -12.02 -15.03</p> </div> <div> </div> </div> <p style="text-align: center;">0 dB = 0.167 W/kg = -7.77 dBW/kg</p>	

FLAT	EDGE4
<p>Communication System: UID 0, FDD-LTE(QPSK_10M_1RB_low) (0); Communication System Band: BAND 5; Frequency: 836.5 MHz; Communication System PAR: 0 dB Medium parameters used (interpolated): $f = 836.5$ MHz; $\sigma = 0.95$ S/m; $\epsilon_r = 54.245$; $\rho = 1000$ kg/m³ Phantom section: Flat Section Measurement Standard: DASY5 (IEEE1528-2013) DASY5 Configuration:</p> <ul style="list-style-type: none"> Probe: ES3DV3 - SN3297; ConvF(6.08, 6.08, 6.08); Calibrated: 14/10/2016; Sensor-Surface: 3mm (Mechanical Surface Detection) Electronics: DAE4 Sn1226; Calibrated: 28/09/2016 Phantom: SAM1; Type: SAM; Serial: TP1576 Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331) <p>body2/edge4 mid/Area Scan (61x161x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm Maximum value of SAR (interpolated) = 0.263 W/kg body2/edge4 mid/ Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm Reference Value = 17.01 V/m; Power Drift = 0.10 dB Peak SAR (extrapolated) = 0.465 W/kg SAR(1 g) = 0.229 W/kg; SAR(10 g) = 0.155 W/kg Maximum value of SAR (measured) = 0.261 W/kg</p>	
 <p>0 dB = 0.263 W/kg = -5.80 dBW/kg</p>	

LTE (Band 5 10BW-50%RB-Low /Head)

Left Side	Cheek
<p>Communication System: UID 0, FDD-LTE(QPSK_10M_25RB) (0); Communication System Band: BAND 5; Frequency: 836.5 MHz; Communication System PAR: 0 dB Medium parameters used : f = 836.5 MHz; $\sigma = 0.883$ S/m; $\epsilon_r = 41.293$; $\rho = 1000$ kg/m³ Phantom section: Left Section Measurement Standard: DASYS5 (IEEE1528-2013) DASYS5 Configuration:</p> <ul style="list-style-type: none"> Probe: ES3DV3 - SN3297; ConvF(6.18, 6.18, 6.18); Calibrated: 14/10/2016; Sensor-Surface: 3mm (Mechanical Surface Detection) Electronics: DAE4 Sn1226; Calibrated: 28/09/2016 Phantom: SAM1; Type: SAM; Serial: TP1576 Measurement SW: DASYS52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331) left/touch mid 50%RB/Area Scan (91x161x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm Maximum value of SAR = 0.165 W/kg left/touch mid 50%RB/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm Reference Value = 4.952 V/m; Power Drift = -0.06 dB Peak SAR (extrapolated) = 0.197 W/kg SAR(1 g) = 0.151 W/kg; SAR(10 g) = 0.114 W/kg Maximum value of SAR (measured) = 0.168 W/kg <div data-bbox="255 1209 1324 1668"> </div>	

Left Side	Tilt
-----------	------

Communication System: UID 0, FDD-LTE(QPSK_10M_25RB) (0); Communication System Band: BAND 5; Frequency: 836.5 MHz; Communication System PAR: 0 dB

Medium parameters used : $f = 836.5$ MHz; $\sigma = 0.883$ S/m; $\epsilon_r = 41.293$; $\rho = 1000$ kg/m³

Phantom section: Left Section

Measurement Standard: DASYS (IEEE1528-2013)

DASY5 Configuration:

- Probe: ES3DV3 - SN3297; ConvF(6.18, 6.18, 6.18); Calibrated: 14/10/2016;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1226; Calibrated: 28/09/2016
- Phantom: SAM1; Type: SAM; Serial: TP1576
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)
- **left/tilt mid 50%RB/Area Scan (91x161x1):** Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR = 0.0705 W/kg


left/tilt mid 50%RB/ Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 6.947 V/m; Power Drift = 0.10 dB


Peak SAR (extrapolated) = 0.101 W/kg


SAR(1 g) = 0.0615 W/kg; SAR(10 g) = 0.0431 W/kg

Maximum value of SAR (measured) = 0.0699 W/kg





0 dB = 0.0705 W/kg = -11.52 dBW/kg

Right Side	Cheek
<p>Communication System: UID 0, FDD-LTE(QPSK_10M_25RB) (0); Communication System Band: BAND 5; Frequency: 836.5 MHz; Communication System PAR: 0 dB Medium parameters used : f = 836.5 MHz; $\sigma = 0.883$ S/m; $\epsilon_r = 41.293$; $\rho = 1000$ kg/m³ Phantom section: Right Section Measurement Standard: DASYS5 (IEEE1528-2013) DASYS5 Configuration:</p> <ul style="list-style-type: none"> • Probe: ES3DV3 - SN3297; ConvF(6.18, 6.18, 6.18); Calibrated: 14/10/2016; • Sensor-Surface: 3mm (Mechanical Surface Detection) • Electronics: DAE4 Sn1226; Calibrated: 28/09/2016 • Phantom: SAM1; Type: SAM; Serial: TP1576 • Measurement SW: DASYS52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331) • right/touch mid 50%RB/Area Scan (91x161x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm Maximum value of SAR = 0.150 W/kg right/touch mid 50%RB/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm Reference Value = 4.696 V/m; Power Drift = 0.08 dB Peak SAR (extrapolated) = 0.169 W/kg SAR(1 g) = 0.136 W/kg; SAR(10 g) = 0.105 W/kg Maximum value of SAR (measured) = 0.149 W/kg 	
 <p style="text-align: center;">0 dB = 0.150 W/kg = -8.24 dBW/kg</p>	

Right Side	Tilt
<p>Communication System: UID 0, FDD-LTE(QPSK_10M_25RB) (0); Communication System Band: BAND 5; Frequency: 836.5 MHz; Communication System PAR: 0 dB Medium parameters used : f = 836.5 MHz; $\sigma = 0.883$ S/m; $\epsilon_r = 41.293$; $\rho = 1000$ kg/m³ Phantom section: Right Section Measurement Standard: DASYS5 (IEEE1528-2013) DASY5 Configuration:</p> <ul style="list-style-type: none"> Probe: ES3DV3 - SN3297; ConvF(6.18, 6.18, 6.18); Calibrated: 14/10/2016; Sensor-Surface: 3mm (Mechanical Surface Detection) Electronics: DAE4 Sn1226; Calibrated: 28/09/2016 Phantom: SAM1; Type: SAM; Serial: TP1576 Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331) <p>right/tilt mid 50%RB/Area Scan (91x161x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm Maximum value of SAR = 0.0823 W/kg right/tilt mid 50%RB/ Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm Reference Value = 7.355 V/m; Power Drift = 0.06 dB Peak SAR (extrapolated) = 0.104 W/kg SAR(1 g) = 0.0721 W/kg; SAR(10 g) = 0.0501 W/kg</p> <p>Maximum value of SAR (measured) = 0.0819 W/kg</p>  <p>0 dB = 0.0823 W/kg = -10.85 dBW/kg</p>	

LTE (Band 5 10BW-50%RB-Low/Flat)


FLAT	Towards phantom
<p>Communication System: UID 0, FDD-LTE(QPSK_10M_25RB) (0); Communication System Band: BAND 5; Frequency: 836.5 MHz; Communication System PAR: 0 dB</p>	
<p>Medium parameters used (interpolated): $f = 836.5$ MHz; $\sigma = 0.95$ S/m; $\epsilon_r = 54.245$; $\rho = 1000$ kg/m³</p>	
<p>Phantom section: Flat Section</p>	
<p>Measurement Standard: DASY5 (IEEE1528-2013)</p>	
<p>DASY5 Configuration:</p>	
<ul style="list-style-type: none"> • Probe: ES3DV3 - SN3297; ConvF(6.08, 6.08, 6.08); Calibrated: 14/10/2016; • Sensor-Surface: 3mm (Mechanical Surface Detection) • Electronics: DAE4 Sn1226; Calibrated: 28/09/2016 • Phantom: SAM1; Type: SAM; Serial: TP1576 • Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331) <p>body/towards phantom 50%RB/Area Scan (91x161x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm Maximum value of SAR (interpolated) = 0.166 W/kg body/towards phantom 50%RB/ Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm Reference Value = 13.77 V/m; Power Drift = -0.10 dB Peak SAR (extrapolated) = 0.297 W/kg SAR(1 g) = 0.147 W/kg; SAR(10 g) = 0.105 W/kg</p>	
<p>Maximum value of SAR (measured) = 0.165 W/kg</p>	
 <p>0 dB = 0.166 W/kg = -7.80 dBW/kg</p>	

FLAT	Towards ground
<p>Communication System: UID 0, FDD-LTE(QPSK_10M_25RB) (0); Communication System Band: BAND 5; Frequency: 836.5 MHz; Communication System PAR: 0 dB Medium parameters used (interpolated): $f = 836.5$ MHz; $\sigma = 0.95$ S/m; $\epsilon_r = 54.245$; $\rho = 1000$ kg/m³ Phantom section: Flat Section Measurement Standard: DASY5 (IEEE1528-2013) DASY5 Configuration:</p> <ul style="list-style-type: none"> Probe: ES3DV3 - SN3297; ConvF(6.08, 6.08, 6.08); Calibrated: 14/10/2016; Sensor-Surface: 3mm (Mechanical Surface Detection) Electronics: DAE4 Sn1226; Calibrated: 28/09/2016 Phantom: SAM1; Type: SAM; Serial: TP1576 Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331) <p>body/towards ground 50%RB/Area Scan (91x161x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm Maximum value of SAR (interpolated) = 0.339 W/kg body/towards ground 50%RB/ Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm Reference Value = 19.46 V/m; Power Drift = -0.11 dB Peak SAR (extrapolated) = 0.465 W/kg SAR(1 g) = 0.299W/kg; SAR(10 g) = 0.212 W/kg. Maximum value of SAR (measured) = 0.337 W/kg</p>	
 <p>0 dB = 0.339 W/kg = -4.70 dBW/kg</p>	

LTE (Band 12 10BW-1RB-Low /Head)

Left Side	Cheek
<p>Communication System: UID 0, LTE Band 12 (0); Frequency: 707.5 MHz;Duty Cycle: 1:1 Medium parameters used (interpolated): $f = 707.5$ MHz; $\sigma = 0.858$ S/m; $\epsilon_r = 42.446$; $\rho = 1000$ kg/m³ Phantom section: Left Section</p>	
<p>DASY5 Configuration:</p> <ul style="list-style-type: none"> Probe: ES3DV3 - SN3127; ConvF(6.55, 6.55, 6.55); Calibrated: 2016/8/29; Sensor-Surface: 4mm (Mechanical Surface Detection) Electronics: DAE4 Sn720; Calibrated: 2016/10/31 Phantom: 1659; Type: QD 000 P40 CD; Serial: xxxx Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373) Head-Section Left HSL LTE band12/LTE band12 10BW 1RB LOW HSL touch M/Area Scan (8x13x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (measured) = 0.0864 W/kg Head-Section Left HSL LTE band12/LTE band12 10BW 1RB LOW HSL touch M/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm Reference Value = 3.336 V/m; Power Drift = 0.02 dB Peak SAR (extrapolated) = 0.100 W/kg SAR(1 g) = 0.082 W/kg; SAR(10 g) = 0.066 W/kg Maximum value of SAR (measured) = 0.0858 W/kg 	
<div style="display: flex; align-items: center;"> <div style="margin-right: 20px;"> <p>dB</p> <p>0 -1.62 -3.24 -4.86 -6.48 -8.10</p> </div> <div style="flex-grow: 1;"> </div> </div> <p style="text-align: center;">0 dB = 0.0858 W/kg = -10.67 dBW/kg</p>	


Left Side	Tilt
<p>Communication System: UID 0, LTE Band 12 (0); Frequency: 707.5 MHz; Duty Cycle: 1:1 Medium parameters used (interpolated): $f = 707.5$ MHz; $\sigma = 0.858$ S/m; $\epsilon_r = 42.446$; $\rho = 1000$ kg/m³ Phantom section: Left Section</p>	
<p>DASY5 Configuration:</p> <ul style="list-style-type: none"> • Probe: ES3DV3 - SN3127; ConvF(6.55, 6.55, 6.55); Calibrated: 2016/8/29; • Sensor-Surface: 4mm (Mechanical Surface Detection) • Electronics: DAE4 Sn720; Calibrated: 2016/10/31 • Phantom: 1659; Type: QD 000 P40 CD; Serial: xxxx • Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373) • Head-Section Left HSL LTE band12/LTE band12 10BW 1RB LOW HSL tilt M/Area Scan (8x13x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (measured) = 0.0393 W/kg • Head-Section Left HSL LTE band12/LTE band12 10BW 1RB LOW HSL tilt M/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm Reference Value = 4.967 V/m; Power Drift = 0.09 dB Peak SAR (extrapolated) = 0.0480 W/kg SAR(1 g) = 0.040 W/kg; SAR(10 g) = 0.031 W/kg Maximum value of SAR (measured) = 0.0416 W/kg 	
<div style="display: flex; align-items: flex-start;"> <div style="margin-right: 20px;"> <p>dB</p> <p>0 -1.53 -3.06 -4.60 -6.13 -7.66</p> </div> <div> <p style="text-align: center;">0 dB = 0.0416 W/kg = -13.81 dBW/kg</p> </div> </div>	


Right Side	Cheek
<p>Communication System: UID 0, LTE Band 12 (0); Frequency: 707.5 MHz; Duty Cycle: 1:1 Medium parameters used (interpolated): $f = 707.5$ MHz; $\sigma = 0.858$ S/m; $\epsilon_r = 42.446$; $\rho = 1000$ kg/m³ Phantom section: Right Section</p> <p>DASY5 Configuration:</p> <ul style="list-style-type: none"> Probe: ES3DV3 - SN3127; ConvF(6.55, 6.55, 6.55); Calibrated: 2016/8/29; Sensor-Surface: 4mm (Mechanical Surface Detection) Electronics: DAE4 Sn720; Calibrated: 2016/10/31 Phantom: 1659; Type: QD 000 P40 CD; Serial: xxxx Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373) Head-Section Right HSL LTE band12/LTE band12 10BW 1RB LOW HSL touch M/Area Scan (8x13x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (measured) = 0.0214 W/kg Head-Section Right HSL LTE band12/LTE band12 10BW 1RB LOW HSL touch M/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm Reference Value = 1.690 V/m; Power Drift = 0.05 dB Peak SAR (extrapolated) = 0.0240 W/kg SAR(1 g) = 0.021 W/kg; SAR(10 g) = 0.017 W/kg Maximum value of SAR (measured) = 0.0219 W/kg 	
 <p style="text-align: center;">0 dB = 0.0219 W/kg = -16.60 dBW/kg</p>	


Right Side	Tilt
<p>Communication System: UID 0, LTE Band 12 (0); Frequency: 707.5 MHz;Duty Cycle: 1:1 Medium parameters used (interpolated): $f = 707.5$ MHz; $\sigma = 0.858$ S/m; $\epsilon_r = 42.446$; $\rho = 1000$ kg/m³ Phantom section: Right Section</p> <p>DASY5 Configuration:</p> <ul style="list-style-type: none"> Probe: ES3DV3 - SN3127; ConvF(6.55, 6.55, 6.55); Calibrated: 2016/8/29; Sensor-Surface: 4mm (Mechanical Surface Detection) Electronics: DAE4 Sn720; Calibrated: 2016/10/31 Phantom: 1659; Type: QD 000 P40 CD; Serial: xxxx Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373) Head-Section Right HSL LTE band12/LTE band12 10BW 1RB LOW HSL tilt M/Area Scan (8x13x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (measured) = 0.0870 W/kg Head-Section Right HSL LTE band12/LTE band12 10BW 1RB LOW HSL tilt M/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm Reference Value = 3.741 V/m; Power Drift = -0.05 dB Peak SAR (extrapolated) = 0.105 W/kg SAR(1 g) = 0.088 W/kg; SAR(10 g) = 0.069 W/kg Maximum value of SAR (measured) = 0.0918 W/kg <div data-bbox="252 1243 1332 1697"> </div> <p>0 dB = 0.0918 W/kg = -10.37 dBW/kg</p>	

LTE (Band 12 10BW-1RB-Low/Flat)

FLAT	Towards phantom
<p>Communication System: UID 0, LTE Band 12 (0); Frequency: 707.5 MHz; Duty Cycle: 1:1 Medium parameters used (interpolated): $f = 707.5$ MHz; $\sigma = 0.858$ S/m; $\epsilon_r = 42.446$; $\rho = 1000$ kg/m³</p>	
<p>Phantom section: Flat Section</p>	
<p>DASY5 Configuration:</p>	
<ul style="list-style-type: none"> Probe: ES3DV3 - SN3127; ConvF(6.55, 6.55, 6.55); Calibrated: 2016/8/29; Sensor-Surface: 4mm (Mechanical Surface Detection) Electronics: DAE4 Sn720; Calibrated: 2016/10/31 Phantom: 1659; Type: QD 000 P40 CD; Serial: xxxx Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373) Flat-Section MSL LTE band12 TG&TP/LTE band12 TP 10BW 1RB LOW M 10mm/Area Scan (9x13x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (measured) = 0.0505 W/kg Flat-Section MSL LTE band12 TG&TP/LTE band12 TP 10BW 1RB LOW M 10mm/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm Reference Value = 7.266 V/m; Power Drift = 0.07 dB Peak SAR (extrapolated) = 0.0600 W/kg SAR(1 g) = 0.049 W/kg; SAR(10 g) = 0.038 W/kg Maximum value of SAR (measured) = 0.0511 W/kg 	
<p>0 dB = 0.0511 W/kg = -12.92 dBW/kg</p>	

FLAT	Towards ground
<p>Communication System: UID 0, LTE Band 12 (0); Frequency: 707.5 MHz;Duty Cycle: 1:1 Medium parameters used (interpolated): $f = 707.5$ MHz; $\sigma = 0.858$ S/m; $\epsilon_r = 42.446$; $\rho = 1000$ kg/m³ Phantom section: Flat Section</p>	
<p>DASY5 Configuration:</p> <ul style="list-style-type: none"> Probe: ES3DV3 - SN3127; ConvF(6.55, 6.55, 6.55); Calibrated: 2016/8/29; Sensor-Surface: 4mm (Mechanical Surface Detection) Electronics: DAE4 Sn720; Calibrated: 2016/10/31 Phantom: 1659; Type: QD 000 P40 CD; Serial: xxxx Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373) Flat-Section MSL LTE band12 TG&TP/LTE band12 TG 10BW 1RB LOW M 10mm/Area Scan (9x13x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (measured) = 0.161 W/kg Flat-Section MSL LTE band12 TG&TP/LTE band12 TG 10BW 1RB LOW M 10mm/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm Reference Value = 12.41 V/m; Power Drift = 0.14 dB Peak SAR (extrapolated) = 0.190 W/kg SAR(1 g) = 0.155 W/kg; SAR(10 g) = 0.120 W/kg Maximum value of SAR (measured) = 0.164 W/kg 	
 <p>0 dB = 0.164 W/kg = -7.85 dBW/kg</p>	

FLAT	EDGE2
<p>Communication System: UID 0, LTE Band 12 (0); Frequency: 707.5 MHz;Duty Cycle: 1:1 Medium parameters used (interpolated): $f = 707.5$ MHz; $\sigma = 0.858$ S/m; $\epsilon_r = 42.446$; $\rho = 1000$ kg/m³ Phantom section: Flat Section</p>	
<p>DASY5 Configuration:</p> <ul style="list-style-type: none"> Probe: ES3DV3 - SN3127; ConvF(6.55, 6.55, 6.55); Calibrated: 2016/8/29; Sensor-Surface: 4mm (Mechanical Surface Detection) Electronics: DAE4 Sn720; Calibrated: 2016/10/31 Phantom: 1659; Type: QD 000 P40 CD; Serial: xxxx Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373) Flat-Section MSL LTE band12 HOT/LTE Band12 1RB edge2/Area Scan (5x9x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (measured) = 0.0225 W/kg Flat-Section MSL LTE band12 HOT/LTE Band12 1RB edge2/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm Reference Value = 3.748 V/m; Power Drift = -0.02 dB Peak SAR (extrapolated) = 0.0350 W/kg SAR(1 g) = 0.022 W/kg; SAR(10 g) = 0.014 W/kg Maximum value of SAR (measured) = 0.0236 W/kg 	
 <p>0 dB = 0.0236 W/kg = -16.27 dBW/kg</p>	

FLAT	EDGE3
<p>Communication System: UID 0, LTE Band 12 (0); Frequency: 707.5 MHz;Duty Cycle: 1:1 Medium parameters used (interpolated): $f = 707.5$ MHz; $\sigma = 0.858$ S/m; $\epsilon_r = 42.446$; $\rho = 1000$ kg/m³ Phantom section: Flat Section</p>	
<p>DASY5 Configuration:</p> <ul style="list-style-type: none"> Probe: ES3DV3 - SN3127; ConvF(6.55, 6.55, 6.55); Calibrated: 2016/8/29; Sensor-Surface: 4mm (Mechanical Surface Detection) Electronics: DAE4 Sn720; Calibrated: 2016/10/31 Phantom: 1659; Type: QD 000 P40 CD; Serial: xxxx Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373) Flat-Section MSL LTE band12 HOT/LTE Band12 1RB edge3/Area Scan (5x13x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (measured) = 0.0761 W/kg Flat-Section MSL LTE band12 HOT/LTE Band12 1RB edge3/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm Reference Value = 8.746 V/m; Power Drift = 0.09 dB Peak SAR (extrapolated) = 0.101 W/kg SAR(1 g) = 0.074 W/kg; SAR(10 g) = 0.052 W/kg Maximum value of SAR (measured) = 0.0794 W/kg 	
 <p>0 dB = 0.0794 W/kg = -11.00 dBW/kg</p>	

FLAT	EDGE4
<p>Communication System: UID 0, LTE Band 12 (0); Frequency: 707.5 MHz; Duty Cycle: 1:1 Medium parameters used (interpolated): $f = 707.5$ MHz; $\sigma = 0.858$ S/m; $\epsilon_r = 42.446$; $\rho = 1000$ kg/m³ Phantom section: Flat Section</p> <p>DASY5 Configuration:</p> <ul style="list-style-type: none"> Probe: ES3DV3 - SN3127; ConvF(6.55, 6.55, 6.55); Calibrated: 2016/8/29; Sensor-Surface: 4mm (Mechanical Surface Detection) Electronics: DAE4 Sn720; Calibrated: 2016/10/31 Phantom: 1659; Type: QD 000 P40 CD; Serial: xxxx Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373) Flat-Section MSL LTE band12 HOT/LTE Band12 1RB edge4/Area Scan (5x13x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (measured) = 0.101 W/kg Flat-Section MSL LTE band12 HOT/LTE Band12 1RB edge4/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm Reference Value = 9.629 V/m; Power Drift = 0.03 dB Peak SAR (extrapolated) = 0.133 W/kg SAR(1 g) = 0.095 W/kg; SAR(10 g) = 0.067 W/kg Maximum value of SAR (measured) = 0.103 W/kg <div style="display: flex; align-items: center;"> <div style="margin-right: 10px;"> <p style="text-align: center;">dB</p> <p style="text-align: center;">0 -1.78 -3.56 -5.34 -7.12 -8.90</p> </div> <div> </div> </div> <p style="text-align: center;">0 dB = 0.103 W/kg = -9.87 dBW/kg</p>	



LTE (Band 12 10BW-50%RB-Low /Head)

Left Side	Cheek
-----------	-------

Communication System: UID 0, LTE Band 12 (0); Frequency: 707.5 MHz;Duty Cycle: 1:1
 Medium parameters used (interpolated): $f = 707.5$ MHz; $\sigma = 0.858$ S/m; $\epsilon_r = 42.446$; $\rho = 1000$ kg/m³
 Phantom section: Left Section


DASY5 Configuration:

- Probe: ES3DV3 - SN3127; ConvF(6.55, 6.55, 6.55); Calibrated: 2016/8/29;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn720; Calibrated: 2016/10/31
- Phantom: 1659; Type: QD 000 P40 CD; Serial: xxxx
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373)
- **Head-Section Left HSL LTE band12/LTE band12 10BW 50%RB LOW HSL touch M/Area Scan (8x13x1):** Measurement grid: dx=15mm, dy=15mm
 Maximum value of SAR (measured) = 0.0714 W/kg
- **Head-Section Left HSL LTE band12/LTE band12 10BW 50%RB LOW HSL touch M/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm
 Reference Value = 3.002 V/m; Power Drift = 0.11 dB
 Peak SAR (extrapolated) = 0.0830 W/kg
SAR(1 g) = 0.069 W/kg; SAR(10 g) = 0.055 W/kg
 Maximum value of SAR (measured) = 0.0715 W/kg




0 dB = 0.0715 W/kg = -11.46 dBW/kg


Left Side	Tilt
Communication System: UID 0, LTE Band 12 (0); Frequency: 707.5 MHz;Duty Cycle: 1:1 Medium parameters used (interpolated): $f = 707.5$ MHz; $\sigma = 0.858$ S/m; $\epsilon_r = 42.446$; $\rho = 1000$ kg/m ³ Phantom section: Left Section	
DASY5 Configuration: <ul style="list-style-type: none"> • Probe: ES3DV3 - SN3127; ConvF(6.55, 6.55, 6.55); Calibrated: 2016/8/29; • Sensor-Surface: 4mm (Mechanical Surface Detection) • Electronics: DAE4 Sn720; Calibrated: 2016/10/31 • Phantom: 1659; Type: QD 000 P40 CD; Serial: xxxx • Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373) • Head-Section Left HSL LTE band12/LTE band12 10BW 50%RB LOW HSL tilt M/Area Scan (8x13x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (measured) = 0.0332 W/kg • Head-Section Left HSL LTE band12/LTE band12 10BW 50%RB LOW HSL tilt M/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm Reference Value = 4.481 V/m; Power Drift = 0.02 dB Peak SAR (extrapolated) = 0.0390 W/kg SAR(1 g) = 0.032 W/kg; SAR(10 g) = 0.026 W/kg Maximum value of SAR (measured) = 0.0341 W/kg 	
<div style="display: flex; align-items: center;"> <div style="margin-right: 20px;"> <p>dB</p> <p>0 -1.55 -3.10 -4.66 -6.21 -7.76</p> </div> <div style="flex-grow: 1;"> </div> </div> <p style="text-align: center;">0 dB = 0.0341 W/kg = -14.67 dBW/kg</p>	

Right Side	Cheek
<p>Communication System: UID 0, LTE Band 12 (0); Frequency: 707.5 MHz; Duty Cycle: 1:1 Medium parameters used (interpolated): $f = 707.5$ MHz; $\sigma = 0.858$ S/m; $\epsilon_r = 42.446$; $\rho = 1000$ kg/m³ Phantom section: Right Section</p> <p>DASY5 Configuration:</p> <ul style="list-style-type: none"> • Probe: ES3DV3 - SN3127; ConvF(6.55, 6.55, 6.55); Calibrated: 2016/8/29; • Sensor-Surface: 4mm (Mechanical Surface Detection) • Electronics: DAE4 Sn720; Calibrated: 2016/10/31 • Phantom: 1659; Type: QD 000 P40 CD; Serial: xxxx • Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373) • Head-Section Right HSL LTE band12/LTE band12 10BW 50%RB LOW HSL touch M/Area Scan (8x13x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (measured) = 0.0192 W/kg • Head-Section Right HSL LTE band12/LTE band12 10BW 50%RB LOW HSL touch M/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm Reference Value = 1.466 V/m; Power Drift = 0.08 dB Peak SAR (extrapolated) = 0.0210 W/kg SAR(1 g) = 0.018 W/kg; SAR(10 g) = 0.015 W/kg Maximum value of SAR (measured) = 0.0188 W/kg 	
 <p>0 dB = 0.0188 W/kg = -17.26 dBW/kg</p>	

Right Side	Tilt
<p>Communication System: UID 0, LTE Band 12 (0); Frequency: 707.5 MHz;Duty Cycle: 1:1 Medium parameters used (interpolated): $f = 707.5$ MHz; $\sigma = 0.858$ S/m; $\epsilon_r = 42.446$; $\rho = 1000$ kg/m³ Phantom section: Right Section</p> <p>DASY5 Configuration:</p> <ul style="list-style-type: none"> • Probe: ES3DV3 - SN3127; ConvF(6.55, 6.55, 6.55); Calibrated: 2016/8/29; • Sensor-Surface: 4mm (Mechanical Surface Detection) • Electronics: DAE4 Sn720; Calibrated: 2016/10/31 • Phantom: 1659; Type: QD 000 P40 CD; Serial: xxxx • Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373) • Head-Section Right HSL LTE band12/LTE band12 10BW 50%RB LOW HSL tilt M/Area Scan (8x13x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (measured) = 0.0148 W/kg • Head-Section Right HSL LTE band12/LTE band12 10BW 50%RB LOW HSL tilt M/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm Reference Value = 2.741 V/m; Power Drift = 0.07 dB Peak SAR (extrapolated) = 0.0180 W/kg SAR(1 g) = 0.015 W/kg; SAR(10 g) = 0.013 W/kg Maximum value of SAR (measured) = 0.0160 W/kg <div style="display: flex; align-items: flex-start;"> <div style="margin-right: 20px;"> <p>dB</p> <p>0 -1.33 -2.65 -3.98 -5.30 -6.63</p> </div> <div> </div> </div> <p style="text-align: center;">0 dB = 0.0160 W/kg = -17.96 dBW/kg</p>	

LTE (Band 12 10BW-50%RB-Low/Flat)

FLAT	Towards phantom
<p>Communication System: UID 0, LTE Band 12 (0); Frequency: 707.5 MHz; Duty Cycle: 1:1 Medium parameters used (interpolated): $f = 707.5$ MHz; $\sigma = 0.858$ S/m; $\epsilon_r = 42.446$; $\rho = 1000$ kg/m³ Phantom section: Flat Section</p>	
<p>DASY5 Configuration:</p> <ul style="list-style-type: none"> Probe: ES3DV3 - SN3127; ConvF(6.55, 6.55, 6.55); Calibrated: 2016/8/29; Sensor-Surface: 4mm (Mechanical Surface Detection) Electronics: DAE4 Sn720; Calibrated: 2016/10/31 Phantom: 1659; Type: QD 000 P40 CD; Serial: xxxx Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373) Flat-Section MSL LTE band12 TG&TP/LTE band12 TP 10BW 50%RB LOW M 10mm/Area Scan (9x13x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (measured) = 0.0382 W/kg Flat-Section MSL LTE band12 TG&TP/LTE band12 TP 10BW 50%RB LOW M 10mm/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm Reference Value = 6.365 V/m; Power Drift = -0.06 dB Peak SAR (extrapolated) = 0.0450 W/kg SAR(1 g) = 0.037 W/kg; SAR(10 g) = 0.029 W/kg Maximum value of SAR (measured) = 0.0386 W/kg 	
	
<p>0 dB = 0.0386 W/kg = -14.13 dBW/kg</p>	

FLAT	Towards ground
<p>Communication System: UID 0, LTE Band 12 (0); Frequency: 707.5 MHz;Duty Cycle: 1:1 Medium parameters used (interpolated): $f = 707.5$ MHz; $\sigma = 0.858$ S/m; $\epsilon_r = 42.446$; $\rho = 1000$ kg/m³ Phantom section: Flat Section</p>	
<p>DASY5 Configuration:</p> <ul style="list-style-type: none"> Probe: ES3DV3 - SN3127; ConvF(6.55, 6.55, 6.55); Calibrated: 2016/8/29; Sensor-Surface: 4mm (Mechanical Surface Detection) Electronics: DAE4 Sn720; Calibrated: 2016/10/31 Phantom: 1659; Type: QD 000 P40 CD; Serial: xxxx Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373) Flat-Section MSL LTE band12 TG&TP/LTE band12 TG 10BW 50%RB LOW M 10mm/Area Scan (9x13x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (measured) = 0.126 W/kg Flat-Section MSL LTE band12 TG&TP/LTE band12 TG 10BW 50%RB LOW M 10mm/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm Reference Value = 11.10 V/m; Power Drift = -0.01 dB Peak SAR (extrapolated) = 0.148 W/kg SAR(1 g) = 0.121 W/kg; SAR(10 g) = 0.093 W/kg 	
 <p>0 dB = 0.126 W/kg = -9.00 dBW/kg</p>	

LTE (Band 13 10BW-1RB-Low /Head)


Left Side	Cheek
-----------	-------

Communication System: UID 0, LTE band 13 (0); Frequency: 782 MHz; Duty Cycle: 1:1
 Medium parameters used (interpolated): $f = 782$ MHz; $\sigma = 0.926$ S/m; $\epsilon_r = 41.412$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY5 Configuration:

- Probe: ES3DV3 - SN3127; ConvF(6.55, 6.55, 6.55); Calibrated: 2016/8/29;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn720; Calibrated: 2016/10/31
- Phantom: 1659; Type: QD 000 P40 CD; Serial: xxxx
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373)
- **Head-Section Left HSL LTE band13/LTE band13 10BW 1RB LOW HSL touch M/Area Scan (8x13x1):** Measurement grid: dx=15mm, dy=15mm
 Maximum value of SAR (measured) = 0.0928 W/kg
- **Head-Section Left HSL LTE band13/LTE band13 10BW 1RB LOW HSL touch M/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm
 Reference Value = 2.408 V/m; Power Drift = 0.07 dB
 Peak SAR (extrapolated) = 0.115 W/kg
SAR(1 g) = 0.091 W/kg; SAR(10 g) = 0.069 W/kg
 Maximum value of SAR (measured) = 0.0959 W/kg




0 dB = 0.0959 W/kg = -10.18 dBW/kg


Left Side	Tilt
<p>Communication System: UID 0, LTE band 13 (0); Frequency: 782 MHz;Duty Cycle: 1:1 Medium parameters used (interpolated): $f = 782$ MHz; $\sigma = 0.926$ S/m; $\epsilon_r = 41.412$; $\rho = 1000$ kg/m³ Phantom section: Left Section</p>	
<p>DASY5 Configuration:</p> <ul style="list-style-type: none"> Probe: ES3DV3 - SN3127; ConvF(6.55, 6.55, 6.55); Calibrated: 2016/8/29; Sensor-Surface: 4mm (Mechanical Surface Detection) Electronics: DAE4 Sn720; Calibrated: 2016/10/31 Phantom: 1659; Type: QD 000 P40 CD; Serial: xxxx Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373) Head-Section Left HSL LTE band13/LTE band13 10BW 1RB LOW HSL tilt M/Area Scan (8x13x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (measured) = 0.0931 W/kg Head-Section Left HSL LTE band13/LTE band13 10BW 1RB LOW HSL tilt M/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm Reference Value = 6.645 V/m; Power Drift = 0.06 dB Peak SAR (extrapolated) = 0.108 W/kg SAR(1 g) = 0.091 W/kg; SAR(10 g) = 0.074 W/kg Maximum value of SAR (measured) = 0.0949 W/kg 	
<div style="display: flex; align-items: flex-start;"> <div style="margin-right: 20px;"> <p>dB</p> <p>0 -1.53 -3.05 -4.58 -6.10 -7.63</p> </div> <div> </div> </div> <p style="text-align: center;">0 dB = 0.0949 W/kg = -10.23 dBW/kg</p>	

Right Side	Cheek
<p>Communication System: UID 0, LTE band 13 (0); Frequency: 782 MHz;Duty Cycle: 1:1 Medium parameters used (interpolated): $f = 782 \text{ MHz}$; $\sigma = 0.926 \text{ S/m}$; $\epsilon_r = 41.412$; $\rho = 1000 \text{ kg/m}^3$ Phantom section: Right Section</p> <p>DASY5 Configuration:</p> <ul style="list-style-type: none"> • Probe: ES3DV3 - SN3127; ConvF(6.55, 6.55, 6.55); Calibrated: 2016/8/29; • Sensor-Surface: 4mm (Mechanical Surface Detection) • Electronics: DAE4 Sn720; Calibrated: 2016/10/31 • Phantom: 1659; Type: QD 000 P40 CD; Serial: xxxx • Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373) • Head-Section Right HSL LTE band13/LTE band13 10BW 1RB LOW HSL touch M/Area Scan (8x13x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$ Maximum value of SAR (measured) = 0.107 W/kg • Head-Section Right HSL LTE band13/LTE band13 10BW 1RB LOW HSL touch M/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$ Reference Value = 3.040 V/m; Power Drift = -0.07 dB Peak SAR (extrapolated) = 0.128 W/kg SAR(1 g) = 0.105 W/kg; SAR(10 g) = 0.081 W/kg Maximum value of SAR (measured) = 0.110 W/kg <div data-bbox="252 1240 1331 1693"> </div> <p data-bbox="400 1704 898 1738">0 dB = 0.110 W/kg = -9.59 dBW/kg</p>	

Right Side	Tilt
<p>Communication System: UID 0, LTE band 13 (0); Frequency: 782 MHz; Duty Cycle: 1:1 Medium parameters used (interpolated): $f = 782 \text{ MHz}$; $\sigma = 0.926 \text{ S/m}$; $\epsilon_r = 41.412$; $\rho = 1000 \text{ kg/m}^3$ Phantom section: Right Section</p> <p>DASY5 Configuration:</p> <ul style="list-style-type: none"> Probe: ES3DV3 - SN3127; ConvF(6.55, 6.55, 6.55); Calibrated: 2016/8/29; Sensor-Surface: 4mm (Mechanical Surface Detection) Electronics: DAE4 Sn720; Calibrated: 2016/10/31 Phantom: 1659; Type: QD 000 P40 CD; Serial: xxxx Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373) <p>Head-Section Right HSL LTE band13/LTE band13 10BW 1RB LOW HSL tilt M/Area Scan (8x13x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$ Maximum value of SAR (measured) = 0.0544 W/kg</p> <p>Head-Section Right HSL LTE band13/LTE band13 10BW 1RB LOW HSL tilt M/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$ Reference Value = 4.697 V/m; Power Drift = 0.07 dB Peak SAR (extrapolated) = 0.0620 W/kg SAR(1 g) = 0.053 W/kg; SAR(10 g) = 0.043 W/kg Maximum value of SAR (measured) = 0.0557 W/kg</p> <div data-bbox="252 1261 1331 1715"> </div> <p>0 dB = 0.0557 W/kg = -12.54 dBW/kg</p>	

LTE (Band 13 10BW-1RB-Low/Flat)

FLAT	Towards phantom
Communication System: UID 0, LTE band 13 (0); Frequency: 782 MHz;Duty Cycle: 1:1 Medium parameters used (interpolated): f = 782 MHz; $\sigma = 0.926$ S/m; $\epsilon_r = 41.412$; $\rho = 1000$ kg/m ³ Phantom section: Flat Section	
DASY5 Configuration: <ul style="list-style-type: none"> Probe: ES3DV3 - SN3127; ConvF(6.55, 6.55, 6.55); Calibrated: 2016/8/29; Sensor-Surface: 4mm (Mechanical Surface Detection) Electronics: DAE4 Sn720; Calibrated: 2016/10/31 Phantom: 1659; Type: QD 000 P40 CD; Serial: xxxx Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373) Flat-Section MSL LTE band13 TG&TP/LTE band13 TP 10BW 1RB LOW M 10mm/Area Scan (9x13x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (measured) = 0.0846 W/kg Flat-Section MSL LTE band13 TG&TP/LTE band13 TP 10BW 1RB LOW M 10mm/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm Reference Value = 9.182 V/m; Power Drift = 0.06 dB Peak SAR (extrapolated) = 0.101 W/kg SAR(1 g) = 0.082 W/kg; SAR(10 g) = 0.063 W/kg Maximum value of SAR (measured) = 0.0859 W/kg 	
 <p>0 dB = 0.0859 W/kg = -10.66 dBW/kg</p>	


FLAT	Towards ground
<p>Communication System: UID 0, LTE band 13 (0); Frequency: 782 MHz;Duty Cycle: 1:1 Medium parameters used (interpolated): f = 782 MHz; $\sigma = 0.926$ S/m; $\epsilon_r = 41.412$; $\rho = 1000$ kg/m³ Phantom section: Flat Section</p>	
<p>DASY5 Configuration:</p> <ul style="list-style-type: none"> Probe: ES3DV3 - SN3127; ConvF(6.55, 6.55, 6.55); Calibrated: 2016/8/29; Sensor-Surface: 4mm (Mechanical Surface Detection) Electronics: DAE4 Sn720; Calibrated: 2016/10/31 Phantom: 1659; Type: QD 000 P40 CD; Serial: xxxx Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373) Flat-Section MSL LTE band13 TG&TP/LTE band13 TG 10BW 1RB LOW M 10mm/Area Scan (9x13x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (measured) = 0.226 W/kg Flat-Section MSL LTE band13 TG&TP/LTE band13 TG 10BW 1RB LOW M 10mm/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm Reference Value = 13.51 V/m; Power Drift = 0.14 dB Peak SAR (extrapolated) = 0.440 W/kg SAR(1 g) = 0.254 W/kg; SAR(10 g) = 0.147 W/kg Maximum value of SAR (measured) = 0.276 W/kg 	
 <p>0 dB = 0.276 W/kg = -5.59 dBW/kg</p>	

FLAT	EDGE 2
------	--------

Communication System: UID 0, LTE band 13 (0); Frequency: 782 MHz; Duty Cycle: 1:1
 Medium parameters used (interpolated): $f = 782$ MHz; $\sigma = 0.926$ S/m; $\epsilon_r = 41.412$; $\rho = 1000$ kg/m³
 Phantom section: Flat Section

DASY5 Configuration:

- Probe: ES3DV3 - SN3127; ConvF(6.55, 6.55, 6.55); Calibrated: 2016/8/29;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn720; Calibrated: 2016/10/31
- Phantom: 1659; Type: QD 000 P40 CD; Serial: xxxx
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373)
- **Flat-Section MSL LTE band13 HOT/LTE Band13 1RB edge2/Area Scan (5x9x1):** Measurement grid: dx=15mm, dy=15mm
 Maximum value of SAR (measured) = 0.0678 W/kg
- **Flat-Section MSL LTE band13 HOT/LTE Band13 1RB edge2/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm
 Reference Value = 5.050 V/m; Power Drift = 0.11 dB
 Peak SAR (extrapolated) = 0.119 W/kg
SAR(1 g) = 0.070 W/kg; SAR(10 g) = 0.042 W/kg
 Maximum value of SAR (measured) = 0.0779 W/kg




0 dB = 0.0779 W/kg = -11.08 dBW/kg

FLAT	EDGE 3
------	--------


Communication System: UID 0, LTE band 13 (0); Frequency: 782 MHz; Duty Cycle: 1:1
 Medium parameters used (interpolated): $f = 782 \text{ MHz}$; $\sigma = 0.926 \text{ S/m}$; $\epsilon_r = 41.412$; $\rho = 1000 \text{ kg/m}^3$
 Phantom section: Flat Section

DASY5 Configuration:


- Probe: ES3DV3 - SN3127; ConvF(6.55, 6.55, 6.55); Calibrated: 2016/8/29;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn720; Calibrated: 2016/10/31
- Phantom: 1659; Type: QD 000 P40 CD; Serial: xxxx
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373)
- **Flat-Section MSL LTE band13 HOT/LTE Band13 1RB edge3/Area Scan (5x13x1):** Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$
 Maximum value of SAR (measured) = 0.0991 W/kg
- **Flat-Section MSL LTE band13 HOT/LTE Band13 1RB edge3/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$
 Reference Value = 9.643 V/m; Power Drift = 0.08 dB
 Peak SAR (extrapolated) = 0.139 W/kg
SAR(1 g) = 0.099 W/kg; SAR(10 g) = 0.068 W/kg
 Maximum value of SAR (measured) = 0.105 W/kg




0 dB = 0.105 W/kg = -9.79 dBW/kg

FLAT	EDGE 4
<p>Communication System: UID 0, LTE band 13 (0); Frequency: 782 MHz;Duty Cycle: 1:1 Medium parameters used (interpolated): $f = 782$ MHz; $\sigma = 0.926$ S/m; $\epsilon_r = 41.412$; $\rho = 1000$ kg/m³ Phantom section: Flat Section</p>	
<p>DASY5 Configuration:</p> <ul style="list-style-type: none"> Probe: ES3DV3 - SN3127; ConvF(6.55, 6.55, 6.55); Calibrated: 2016/8/29; Sensor-Surface: 4mm (Mechanical Surface Detection) Electronics: DAE4 Sn720; Calibrated: 2016/10/31 Phantom: 1659; Type: QD 000 P40 CD; Serial: xxxx Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373) Flat-Section MSL LTE band13 HOT/LTE Band13 1RB edge4/Area Scan (5x13x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (measured) = 0.146 W/kg Flat-Section MSL LTE band13 HOT/LTE Band13 1RB edge4/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm Reference Value = 11.40 V/m; Power Drift = 0.11 dB Peak SAR (extrapolated) = 0.195 W/kg SAR(1 g) = 0.140 W/kg; SAR(10 g) = 0.096 W/kg Maximum value of SAR (measured) = 0.149 W/kg 	
 <p>0 dB = 0.149 W/kg = -8.27 dBW/kg</p>	

LTE (Band 13 10BW-50%RB-Low /Head)

Left Side	Cheek
Communication System: UID 0, LTE band 13 (0); Frequency: 782 MHz;Duty Cycle: 1:1 Medium parameters used (interpolated): $f = 782 \text{ MHz}$; $\sigma = 0.926 \text{ S/m}$; $\epsilon_r = 41.412$; $\rho = 1000 \text{ kg/m}^3$ Phantom section: Left Section	
DASY5 Configuration: <ul style="list-style-type: none"> Probe: ES3DV3 - SN3127; ConvF(6.55, 6.55, 6.55); Calibrated: 2016/8/29; Sensor-Surface: 4mm (Mechanical Surface Detection) Electronics: DAE4 Sn720; Calibrated: 2016/10/31 Phantom: 1659; Type: QD 000 P40 CD; Serial: xxxx Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373) Head-Section Left HSL LTE band13/LTE band13 10BW 50%RB LOW HSL touch M/Area Scan (8x13x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$ Maximum value of SAR (measured) = 0.0755 W/kg Head-Section Left HSL LTE band13/LTE band13 10BW 50%RB LOW HSL touch M/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$ Reference Value = 2.104 V/m; Power Drift = 0.02 dB Peak SAR (extrapolated) = 0.0910 W/kg SAR(1 g) = 0.072 W/kg; SAR(10 g) = 0.055 W/kg Maximum value of SAR (measured) = 0.0759 W/kg 	
 <p>0 dB = 0.0759 W/kg = -11.20 dBW/kg</p>	



Left Side	Tilt
<p>Communication System: UID 0, LTE band 13 (0); Frequency: 782 MHz;Duty Cycle: 1:1 Medium parameters used (interpolated): $f = 782 \text{ MHz}$; $\sigma = 0.926 \text{ S/m}$; $\epsilon_r = 41.412$; $\rho = 1000 \text{ kg/m}^3$ Phantom section: Left Section</p>	
<p>DASY5 Configuration:</p> <ul style="list-style-type: none"> Probe: ES3DV3 - SN3127; ConvF(6.55, 6.55, 6.55); Calibrated: 2016/8/29; Sensor-Surface: 4mm (Mechanical Surface Detection) Electronics: DAE4 Sn720; Calibrated: 2016/10/31 Phantom: 1659; Type: QD 000 P40 CD; Serial: xxxx Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373) Head-Section Left HSL LTE band13/LTE band13 10BW 50%RB LOW HSL tilt M/Area Scan (8x13x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$ Maximum value of SAR (measured) = 0.0278 W/kg Head-Section Left HSL LTE band13/LTE band13 10BW 50%RB LOW HSL tilt M/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$ Reference Value = 2.884 V/m; Power Drift = 0.01 dB Peak SAR (extrapolated) = 0.0320 W/kg SAR(1 g) = 0.027 W/kg; SAR(10 g) = 0.022 W/kg Maximum value of SAR (measured) = 0.0284 W/kg 	
 <p>0 dB = 0.0284 W/kg = -15.47 dBW/kg</p>	

Right Side	Cheek
------------	-------

Communication System: UID 0, LTE band 13 (0); Frequency: 782 MHz; Duty Cycle: 1:1
 Medium parameters used (interpolated): $f = 782 \text{ MHz}$; $\sigma = 0.926 \text{ S/m}$; $\epsilon_r = 41.412$; $\rho = 1000 \text{ kg/m}^3$
 Phantom section: Right Section

DASY5 Configuration:

- Probe: ES3DV3 - SN3127; ConvF(6.55, 6.55, 6.55); Calibrated: 2016/8/29;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn720; Calibrated: 2016/10/31
- Phantom: 1659; Type: QD 000 P40 CD; Serial: xxxx
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373)
- **Head-Section Right HSL LTE band13/LTE band13 10BW 50%RB LOW HSL touch M/Area Scan (8x13x1):** Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$
 Maximum value of SAR (measured) = 0.0903 W/kg
- **Head-Section Right HSL LTE band13/LTE band13 10BW 50%RB LOW HSL touch M/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$
 Reference Value = 2.087 V/m; Power Drift = 0.13 dB
 Peak SAR (extrapolated) = 0.104 W/kg
SAR(1 g) = 0.086 W/kg; SAR(10 g) = 0.067 W/kg
 Maximum value of SAR (measured) = 0.0896 W/kg




0 dB = 0.0896 W/kg = -10.48 dBW/kg

Right Side	Tilt
------------	------


Communication System: UID 0, LTE band 13 (0); Frequency: 782 MHz; Duty Cycle: 1:1
 Medium parameters used (interpolated): $f = 782 \text{ MHz}$; $\sigma = 0.926 \text{ S/m}$; $\epsilon_r = 41.412$; $\rho = 1000 \text{ kg/m}^3$
 Phantom section: Right Section


DASY5 Configuration:

- Probe: ES3DV3 - SN3127; ConvF(6.55, 6.55, 6.55); Calibrated: 2016/8/29;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn720; Calibrated: 2016/10/31
- Phantom: 1659; Type: QD 000 P40 CD; Serial: xxxx
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373)
- **Head-Section Right HSL LTE band13/LTE band13 10BW 50%RB LOW HSL tilt M/Area Scan (8x13x1):** Measurement grid: dx=15mm, dy=15mm
 Maximum value of SAR (measured) = 0.0470 W/kg
- **Head-Section Right HSL LTE band13/LTE band13 10BW 50%RB LOW HSL tilt M/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm
 Reference Value = 4.363 V/m; Power Drift = 0.09 dB
 Peak SAR (extrapolated) = 0.0540 W/kg
SAR(1 g) = 0.045 W/kg; SAR(10 g) = 0.036 W/kg
 Maximum value of SAR (measured) = 0.0474 W/kg



LTE (Band 13 10BW-50%RB-Low/Flat)

FLAT	Towards phantom
<p>Communication System: UID 0, LTE band 13 (0); Frequency: 782 MHz;Duty Cycle: 1:1 Medium parameters used (interpolated): f = 782 MHz; $\sigma = 0.926$ S/m; $\epsilon_r = 41.412$; $\rho = 1000$ kg/m³ Phantom section: Flat Section</p>	
<p>DASY5 Configuration:</p> <ul style="list-style-type: none"> • Probe: ES3DV3 - SN3127; ConvF(6.55, 6.55, 6.55); Calibrated: 2016/8/29; • Sensor-Surface: 4mm (Mechanical Surface Detection) • Electronics: DAE4 Sn720; Calibrated: 2016/10/31 • Phantom: 1659; Type: QD 000 P40 CD; Serial: xxxx • Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373) • Flat-Section MSL LTE band13 TG&TP/LTE band13 TP 10BW 50%RB LOW M 10mm/Area Scan (9x13x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (measured) = 0.0631 W/kg • Flat-Section MSL LTE band13 TG&TP/LTE band13 TP 10BW 50%RB LOW M 10mm/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm Reference Value = 8.045 V/m; Power Drift = 0.03 dB Peak SAR (extrapolated) = 0.0740 W/kg SAR(1 g) = 0.061 W/kg; SAR(10 g) = 0.047 W/kg Maximum value of SAR (measured) = 0.0635 W/kg 	
 <p>0 dB = 0.0635 W/kg = -11.97 dBW/kg</p>	

FLAT	Towards ground
<p>Communication System: UID 0, LTE band 13 (0); Frequency: 782 MHz;Duty Cycle: 1:1 Medium parameters used (interpolated): $f = 782$ MHz; $\sigma = 0.926$ S/m; $\epsilon_r = 41.412$; $\rho = 1000$ kg/m³ Phantom section: Flat Section</p>	
<p>DASY5 Configuration:</p> <ul style="list-style-type: none"> Probe: ES3DV3 - SN3127; ConvF(6.55, 6.55, 6.55); Calibrated: 2016/8/29; Sensor-Surface: 4mm (Mechanical Surface Detection) Electronics: DAE4 Sn720; Calibrated: 2016/10/31 Phantom: 1659; Type: QD 000 P40 CD; Serial: xxxx Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373) Flat-Section MSL LTE band13 TG&TP/LTE band13 TG 10BW 50%RB LOW M 10mm/Area Scan (9x13x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (measured) = 0.177 W/kg Flat-Section MSL LTE band13 TG&TP/LTE band13 TG 10BW 50%RB LOW M 10mm/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm Reference Value = 12.15 V/m; Power Drift = -0.12 dB Peak SAR (extrapolated) = 0.321 W/kg SAR(1 g) = 0.187 W/kg; SAR(10 g) = 0.108 W/kg Maximum value of SAR (measured) = 0.202 W/kg 	
 <p>0 dB = 0.202 W/kg = -6.95 dBW/kg</p>	


LTE (Band 17 10BW-1RB-Low /Head)

Left Side	Cheek
-----------	-------


Communication System: UID 0, LTE Band 17 (0); Frequency: 710 MHz; Duty Cycle: 1:1
 Medium parameters used (interpolated): $f = 710$ MHz; $\sigma = 0.86$ S/m; $\epsilon_r = 42.412$; $\rho = 1000$ kg/m³
 Phantom section: Left Section

DASY5 Configuration:

- Probe: ES3DV3 - SN3127; ConvF(6.55, 6.55, 6.55); Calibrated: 2016/8/29;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn720; Calibrated: 2016/10/31
- Phantom: 1659; Type: QD 000 P40 CD; Serial: xxxx
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373)
- **Head-Section Left HSL LTE band17/LTE band17 10BW 1RB LOW HSL touch M/Area Scan (8x13x1):** Measurement grid: dx=15mm, dy=15mm
 Maximum value of SAR (measured) = 0.0318 W/kg
Head-Section Left HSL LTE band17/LTE band17 10BW 1RB LOW HSL touch M/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
 Reference Value = 2.058 V/m; Power Drift = 0.09 dB
 Peak SAR (extrapolated) = 0.0380 W/kg
SAR(1 g) = 0.030 W/kg; SAR(10 g) = 0.024 W/kg



0 dB = 0.0318 W/kg = -14.98 dBW/kg

Left Side	Tilt
Communication System: UID 0, LTE Band 17 (0); Frequency: 710 MHz; Duty Cycle: 1:1 Medium parameters used (interpolated): $f = 710$ MHz; $\sigma = 0.86$ S/m; $\epsilon_r = 42.412$; $\rho = 1000$ kg/m ³ Phantom section: Left Section	
DASY5 Configuration: <ul style="list-style-type: none"> • Probe: ES3DV3 - SN3127; ConvF(6.55, 6.55, 6.55); Calibrated: 2016/8/29; • Sensor-Surface: 4mm (Mechanical Surface Detection) • Electronics: DAE4 Sn720; Calibrated: 2016/10/31 • Phantom: 1659; Type: QD 000 P40 CD; Serial: xxxx • Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373) • Head-Section Left HSL LTE band17/LTE band17 10BW 1RB LOW HSL tilt M/Area Scan (8x13x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (measured) = 0.0210 W/kg • Head-Section Left HSL LTE band17/LTE band17 10BW 1RB LOW HSL tilt M/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm Reference Value = 3.238 V/m; Power Drift = 0.14 dB Peak SAR (extrapolated) = 0.0250 W/kg SAR(1 g) = 0.021 W/kg; SAR(10 g) = 0.017 W/kg Maximum value of SAR (measured) = 0.0220 W/kg 	
 <p>0 dB = 0.0220 W/kg = -16.58 dBW/kg</p>	


Right Side	Cheek
------------	-------

Communication System: UID 0, LTE Band 17 (0); Frequency: 710 MHz; Duty Cycle: 1:1
 Medium parameters used (interpolated): $f = 710 \text{ MHz}$; $\sigma = 0.86 \text{ S/m}$; $\epsilon_r = 42.412$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

DASY5 Configuration:


- Probe: ES3DV3 - SN3127; ConvF(6.55, 6.55, 6.55); Calibrated: 2016/8/29;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn720; Calibrated: 2016/10/31
- Phantom: 1659; Type: QD 000 P40 CD; Serial: xxxx
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373)
- **Head-Section Right HSL LTE band17/LTE band17 10BW 1RB LOW HSL touch M/Area Scan (8x13x1):** Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$
 Maximum value of SAR (measured) = 0.0317 W/kg
- **Head-Section Right HSL LTE band17/LTE band17 10BW 1RB LOW HSL touch M/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$
 Reference Value = 1.993 V/m; Power Drift = 0.06 dB
 Peak SAR (extrapolated) = 0.0380 W/kg
SAR(1 g) = 0.031 W/kg; SAR(10 g) = 0.025 W/kg
 Maximum value of SAR (measured) = 0.0329 W/kg




0 dB = 0.0329 W/kg = -14.83 dBW/kg

Right Side	Tilt
<p>Communication System: UID 0, LTE Band 17 (0); Frequency: 710 MHz; Duty Cycle: 1:1 Medium parameters used (interpolated): $f = 710$ MHz; $\sigma = 0.86$ S/m; $\epsilon_r = 42.412$; $\rho = 1000$ kg/m³ Phantom section: Right Section</p> <p>DASY5 Configuration:</p> <ul style="list-style-type: none"> • Probe: ES3DV3 - SN3127; ConvF(6.55, 6.55, 6.55); Calibrated: 2016/8/29; • Sensor-Surface: 4mm (Mechanical Surface Detection) • Electronics: DAE4 Sn720; Calibrated: 2016/10/31 • Phantom: 1659; Type: QD 000 P40 CD; Serial: xxxx • Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373) • Head-Section Right HSL LTE band17/LTE band17 10BW 1RB LOW HSL tilt M/Area Scan (8x13x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (measured) = 0.0202 W/kg • Head-Section Right HSL LTE band17/LTE band17 10BW 1RB LOW HSL tilt M/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm Reference Value = 3.493 V/m; Power Drift = -0.07 dB Peak SAR (extrapolated) = 0.0230 W/kg SAR(1 g) = 0.020 W/kg; SAR(10 g) = 0.016 W/kg Maximum value of SAR (measured) = 0.0208 W/kg <div style="display: flex; align-items: flex-start;"> <div style="margin-right: 20px;"> <p>dB</p> <p>0 -1.36 -2.72 -4.08 -5.44 -6.80</p> </div> <div> </div> </div> <p style="text-align: center;">0 dB = 0.0208 W/kg = -16.82 dBW/kg</p>	

LTE (Band 17 10BW-1RB-Low/Flat)

FLAT	Towards phantom
<p>Communication System: UID 0, LTE Band 17 (0); Frequency: 710 MHz; Duty Cycle: 1:1 Medium parameters used (interpolated): $f = 710$ MHz; $\sigma = 0.86$ S/m; $\epsilon_r = 42.412$; $\rho = 1000$ kg/m³ Phantom section: Flat Section</p>	
<p>DASY5 Configuration:</p> <ul style="list-style-type: none"> Probe: ES3DV3 - SN3127; ConvF(6.55, 6.55, 6.55); Calibrated: 2016/8/29; Sensor-Surface: 4mm (Mechanical Surface Detection) Electronics: DAE4 Sn720; Calibrated: 2016/10/31 Phantom: 1659; Type: QD 000 P40 CD; Serial: xxxx Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373) Flat-Section MSL LTE band17 TG&TP/LTE band17 TP 10BW 1RB LOW M 10mm/Area Scan (9x13x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (measured) = 0.0395 W/kg Flat-Section MSL LTE band17 TG&TP/LTE band17 TP 10BW 1RB LOW M 10mm/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm Reference Value = 6.658 V/m; Power Drift = 0.01 dB Peak SAR (extrapolated) = 0.0470 W/kg SAR(1 g) = 0.039 W/kg; SAR(10 g) = 0.030 W/kg Maximum value of SAR (measured) = 0.0414 W/kg 	
 <p>0 dB = 0.0414 W/kg = -13.83 dBW/kg</p>	

FLAT	Towards ground
<p>Communication System: UID 0, LTE Band 17 (0); Frequency: 710 MHz; Duty Cycle: 1:1 Medium parameters used (interpolated): $f = 710$ MHz; $\sigma = 0.86$ S/m; $\epsilon_r = 42.412$; $\rho = 1000$ kg/m³ Phantom section: Flat Section</p>	
<p>DASY5 Configuration:</p> <ul style="list-style-type: none"> Probe: ES3DV3 - SN3127; ConvF(6.55, 6.55, 6.55); Calibrated: 2016/8/29; Sensor-Surface: 4mm (Mechanical Surface Detection) Electronics: DAE4 Sn720; Calibrated: 2016/10/31 Phantom: 1659; Type: QD 000 P40 CD; Serial: xxxx Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373) Flat-Section MSL LTE band17 TG&TP/LTE band17 TG 10BW 1RB LOW M 10mm/Area Scan (9x13x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (measured) = 0.141 W/kg Flat-Section MSL LTE band17 TG&TP/LTE band17 TG 10BW 1RB LOW M 10mm/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm Reference Value = 12.25 V/m; Power Drift = -0.09 dB Peak SAR (extrapolated) = 0.165 W/kg SAR(1 g) = 0.133 W/kg; SAR(10 g) = 0.102 W/kg Maximum value of SAR (measured) = 0.140 W/kg 	
 <p>0 dB = 0.140 W/kg = -8.54 dBW/kg</p>	


FLAT	EDGE2
------	-------

Communication System: UID 0, LTE Band 17 (0); Frequency: 710 MHz; Duty Cycle: 1:1
Medium parameters used (interpolated): $f = 710$ MHz; $\sigma = 0.86$ S/m; $\epsilon_r = 42.412$; $\rho = 1000$ kg/m³


Phantom section: Flat Section


DASY5 Configuration:

- Probe: ES3DV3 - SN3127; ConvF(6.55, 6.55, 6.55); Calibrated: 2016/8/29;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn720; Calibrated: 2016/10/31
- Phantom: 1659; Type: QD 000 P40 CD; Serial: xxxx
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373)
- **Flat-Section MSL LTE band17 HOT/LTE Band17 1RB edge2/Area Scan (5x9x1):** Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (measured) = 0.0246 W/kg
- **Flat-Section MSL LTE band17 HOT/LTE Band17 1RB edge2/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 4.807 V/m; Power Drift = 0.12 dB
Peak SAR (extrapolated) = 0.0370 W/kg
SAR(1 g) = 0.023 W/kg; SAR(10 g) = 0.015 W/kg
Maximum value of SAR (measured) = 0.0259 W/kg





0 dB = 0.0259 W/kg = -15.87 dBW/kg

FLAT	EDGE3
<p>Communication System: UID 0, LTE Band 17 (0); Frequency: 710 MHz; Duty Cycle: 1:1 Medium parameters used (interpolated): $f = 710$ MHz; $\sigma = 0.86$ S/m; $\epsilon_r = 42.412$; $\rho = 1000$ kg/m³ Phantom section: Flat Section</p>	
<p>DASY5 Configuration:</p> <ul style="list-style-type: none"> Probe: ES3DV3 - SN3127; ConvF(6.55, 6.55, 6.55); Calibrated: 2016/8/29; Sensor-Surface: 4mm (Mechanical Surface Detection) Electronics: DAE4 Sn720; Calibrated: 2016/10/31 Phantom: 1659; Type: QD 000 P40 CD; Serial: xxxx Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373) Flat-Section MSL LTE band17 HOT/LTE Band17 1RB edge3/Area Scan (5x13x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (measured) = 0.0258 W/kg Flat-Section MSL LTE band17 HOT/LTE Band17 1RB edge3/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm Reference Value = 4.808 V/m; Power Drift = -0.09 dB Peak SAR (extrapolated) = 0.0330 W/kg SAR(1 g) = 0.024 W/kg; SAR(10 g) = 0.017 W/kg Maximum value of SAR (measured) = 0.0255 W/kg 	
 <p>0 dB = 0.0255 W/kg = -15.93 dBW/kg</p>	

FLAT	EDGE4
<p>Communication System: UID 0, LTE Band 17 (0); Frequency: 710 MHz; Duty Cycle: 1:1 Medium parameters used (interpolated): $f = 710$ MHz; $\sigma = 0.86$ S/m; $\epsilon_r = 42.412$; $\rho = 1000$ kg/m³ Phantom section: Flat Section</p>	
<p>DASY5 Configuration:</p> <ul style="list-style-type: none"> Probe: ES3DV3 - SN3127; ConvF(6.55, 6.55, 6.55); Calibrated: 2016/8/29; Sensor-Surface: 4mm (Mechanical Surface Detection) Electronics: DAE4 Sn720; Calibrated: 2016/10/31 Phantom: 1659; Type: QD 000 P40 CD; Serial: xxxx Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373) Flat-Section MSL LTE band17 HOT/LTE Band17 1RB edge4/Area Scan (5x13x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (measured) = 0.0461 W/kg Flat-Section MSL LTE band17 HOT/LTE Band17 1RB edge4/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm Reference Value = 6.314 V/m; Power Drift = -0.04 dB Peak SAR (extrapolated) = 0.0590 W/kg SAR(1 g) = 0.043 W/kg; SAR(10 g) = 0.030 W/kg Maximum value of SAR (measured) = 0.0457 W/kg 	
 <p>0 dB = 0.0457 W/kg = -13.40 dBW/kg</p>	

LTE (Band 17 10BW-50RB-Low /Head)


Left Side	Cheek
Communication System: UID 0, LTE Band 17 (0); Frequency: 710 MHz; Duty Cycle: 1:1 Medium parameters used (interpolated): $f = 710$ MHz; $\sigma = 0.86$ S/m; $\epsilon_r = 42.412$; $\rho = 1000$ kg/m ³ Phantom section: Left Section	
DASY5 Configuration: <ul style="list-style-type: none"> • Probe: ES3DV3 - SN3127; ConvF(6.55, 6.55, 6.55); Calibrated: 2016/8/29; • Sensor-Surface: 4mm (Mechanical Surface Detection) • Electronics: DAE4 Sn720; Calibrated: 2016/10/31 • Phantom: 1659; Type: QD 000 P40 CD; Serial: xxxx • Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373) • Head-Section Left HSL LTE band17/LTE band17 10BW 50%RB LOW HSL touch M/Area Scan (8x13x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (measured) = 0.0256 W/kg • Head-Section Left HSL LTE band17/LTE band17 10BW 50%RB LOW HSL touch M/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm Reference Value = 1.704 V/m; Power Drift = 0.16 dB Peak SAR (extrapolated) = 0.0300 W/kg SAR(1 g) = 0.024 W/kg; SAR(10 g) = 0.019 W/kg Maximum value of SAR (measured) = 0.0253 W/kg 	
 <p>0 dB = 0.0253 W/kg = -15.97 dBW/kg</p>	


Left Side	Tilt
Communication System: UID 0, LTE Band 17 (0); Frequency: 710 MHz; Duty Cycle: 1:1 Medium parameters used (interpolated): $f = 710$ MHz; $\sigma = 0.86$ S/m; $\epsilon_r = 42.412$; $\rho = 1000$ kg/m ³ Phantom section: Left Section	
DASY5 Configuration: <ul style="list-style-type: none"> Probe: ES3DV3 - SN3127; ConvF(6.55, 6.55, 6.55); Calibrated: 2016/8/29; Sensor-Surface: 4mm (Mechanical Surface Detection) Electronics: DAE4 Sn720; Calibrated: 2016/10/31 Phantom: 1659; Type: QD 000 P40 CD; Serial: xxxx Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373) Head-Section Left HSL LTE band17/LTE band17 10BW 50%RB LOW HSL tilt M/Area Scan (8x13x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (measured) = 0.0154 W/kg Head-Section Left HSL LTE band17/LTE band17 10BW 50%RB LOW HSL tilt M/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm Reference Value = 2.703 V/m; Power Drift = 0.11 dB Peak SAR (extrapolated) = 0.0180 W/kg SAR(1 g) = 0.015 W/kg; SAR(10 g) = 0.012 W/kg Maximum value of SAR (measured) = 0.0160 W/kg 	
 <p>0 dB = 0.0160 W/kg = -17.96 dBW/kg</p>	

Right Side	Cheek
<p>Communication System: UID 0, LTE Band 17 (0); Frequency: 710 MHz; Duty Cycle: 1:1 Medium parameters used (interpolated): $f = 710 \text{ MHz}$; $\sigma = 0.86 \text{ S/m}$; $\epsilon_r = 42.412$; $\rho = 1000 \text{ kg/m}^3$ Phantom section: Right Section</p> <p>DASY5 Configuration:</p> <ul style="list-style-type: none"> • Probe: ES3DV3 - SN3127; ConvF(6.55, 6.55, 6.55); Calibrated: 2016/8/29; • Sensor-Surface: 4mm (Mechanical Surface Detection) • Electronics: DAE4 Sn720; Calibrated: 2016/10/31 • Phantom: 1659; Type: QD 000 P40 CD; Serial: xxxx • Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373) • Head-Section Right HSL LTE band17/LTE band17 10BW 50%RB LOW HSL touch M/Area Scan (8x13x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$ Maximum value of SAR (measured) = 0.0250 W/kg • Head-Section Right HSL LTE band17/LTE band17 10BW 50%RB LOW HSL touch M/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$ Reference Value = 1.743 V/m; Power Drift = 0.00 dB Peak SAR (extrapolated) = 0.0290 W/kg SAR(1 g) = 0.024 W/kg; SAR(10 g) = 0.019 W/kg Maximum value of SAR (measured) = 0.0256 W/kg <div data-bbox="252 1240 1331 1693"> </div> <p data-bbox="400 1700 936 1738">0 dB = 0.0256 W/kg = -15.92 dBW/kg</p>	


Right Side	Tilt
<p>Communication System: UID 0, LTE Band 17 (0); Frequency: 710 MHz; Duty Cycle: 1:1 Medium parameters used (interpolated): $f = 710$ MHz; $\sigma = 0.86$ S/m; $\epsilon_r = 42.412$; $\rho = 1000$ kg/m³ Phantom section: Right Section</p> <p>DASY5 Configuration:</p> <ul style="list-style-type: none"> Probe: ES3DV3 - SN3127; ConvF(6.55, 6.55, 6.55); Calibrated: 2016/8/29; Sensor-Surface: 4mm (Mechanical Surface Detection) Electronics: DAE4 Sn720; Calibrated: 2016/10/31 Phantom: 1659; Type: QD 000 P40 CD; Serial: xxxx Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373) Head-Section Right HSL LTE band17/LTE band17 10BW 50%RB LOW HSL tilt M/Area Scan (8x13x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (measured) = 0.0144 W/kg Head-Section Right HSL LTE band17/LTE band17 10BW 50%RB LOW HSL tilt M/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm Reference Value = 2.974 V/m; Power Drift = 0.03 dB Peak SAR (extrapolated) = 0.0170 W/kg SAR(1 g) = 0.014 W/kg; SAR(10 g) = 0.012 W/kg Maximum value of SAR (measured) = 0.0149 W/kg <div style="display: flex; align-items: center;"> <div style="margin-right: 20px;"> <p>dB</p> <p>0 -1.33 -2.66 -3.98 -5.31 -6.64</p> </div> <div> </div> </div> <p style="text-align: center;">0 dB = 0.0149 W/kg = -18.27 dBW/kg</p>	

LTE (Band 17 10BW-50RB-Low/Flat)

FLAT	Towards phantom
<p>Communication System: UID 0, LTE Band 17 (0); Frequency: 710 MHz; Duty Cycle: 1:1 Medium parameters used (interpolated): $f = 710$ MHz; $\sigma = 0.86$ S/m; $\epsilon_r = 42.412$; $\rho = 1000$ kg/m³ Phantom section: Flat Section</p>	
<p>DASY5 Configuration:</p> <ul style="list-style-type: none"> • Probe: ES3DV3 - SN3127; ConvF(6.55, 6.55, 6.55); Calibrated: 2016/8/29; • Sensor-Surface: 4mm (Mechanical Surface Detection) • Electronics: DAE4 Sn720; Calibrated: 2016/10/31 • Phantom: 1659; Type: QD 000 P40 CD; Serial: xxxx • Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373) • Flat-Section MSL LTE band17 TG&TP/LTE band17 TP 10BW 50%RB LOW M 10mm/Area Scan (9x13x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (measured) = 0.0311 W/kg • Flat-Section MSL LTE band17 TG&TP/LTE band17 TP 10BW 50%RB LOW M 10mm/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm Reference Value = 5.820 V/m; Power Drift = 0.03 dB Peak SAR (extrapolated) = 0.0370 W/kg SAR(1 g) = 0.030 W/kg; SAR(10 g) = 0.024 W/kg Maximum value of SAR (measured) = 0.0313 W/kg 	
 <p>0 dB = 0.0313 W/kg = -15.04 dBW/kg</p>	

FLAT	Towards ground
<p>Communication System: UID 0, LTE Band 17 (0); Frequency: 710 MHz; Duty Cycle: 1:1 Medium parameters used (interpolated): $f = 710$ MHz; $\sigma = 0.86$ S/m; $\epsilon_r = 42.412$; $\rho = 1000$ kg/m³ Phantom section: Flat Section</p>	
<p>DASY5 Configuration:</p> <ul style="list-style-type: none"> Probe: ES3DV3 - SN3127; ConvF(6.55, 6.55, 6.55); Calibrated: 2016/8/29; Sensor-Surface: 4mm (Mechanical Surface Detection) Electronics: DAE4 Sn720; Calibrated: 2016/10/31 Phantom: 1659; Type: QD 000 P40 CD; Serial: xxxx Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373) Flat-Section MSL LTE band17 TG&TP/LTE band17 TG 10BW 50%RB LOW M 10mm/Area Scan (9x13x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (measured) = 0.102 W/kg Flat-Section MSL LTE band17 TG&TP/LTE band17 TG 10BW 50%RB LOW M 10mm/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm Reference Value = 10.51 V/m; Power Drift = -0.12 dB Peak SAR (extrapolated) = 0.121 W/kg SAR(1 g) = 0.098 W/kg; SAR(10 g) = 0.076 W/kg Maximum value of SAR (measured) = 0.103 W/kg 	
 <p>0 dB = 0.103 W/kg = -9.87 dBW/kg</p>	

GSM 850 (GSM)

FLAT	Towards ground
<p>Communication System: UID 10021 - DAB, GSM-FDD (TDMA, GMSK); Frequency: 836.6 MHz; Duty Cycle: 1:8.6896 Medium parameters used (interpolated): $f = 836.6$ MHz; $\sigma = 0.96$ S/m; $\epsilon_r = 55.858$; $\rho = 1000$ kg/m³ Phantom section: Flat Section</p> <p>DASY5 Configuration:</p> <ul style="list-style-type: none"> Probe: EX3DV4 - SN3708; ConvF(9.1, 9.1, 9.1); Calibrated: 2016/11/10; Sensor-Surface: 4mm (Mechanical Surface Detection) Electronics: DAE4 Sn720; Calibrated: 2016/10/31 Phantom: 1659; Type: QD 000 P40 CD; Serial: xxxx Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373) <p>GSM 850 TG/850GSM TG M 10mm/Area Scan (9x13x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (measured) = 0.211 W/kg GSM 850 TG/850GSM TG M 10mm/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm Reference Value = 13.40 V/m; Power Drift = 0.16 dB Peak SAR (extrapolated) = 0.267 W/kg SAR(1 g) = 0.206 W/kg; SAR(10 g) = 0.155 W/kg Maximum value of SAR (measured) = 0.216 W/kg</p> <div style="display: flex; align-items: center;">  </div> <p style="text-align: center;">0 dB = 0.216 W/kg = -6.66 dBW/kg</p>	

WCDMA band5 (DATA)

FLAT	Towards ground
------	----------------

Communication System: UID 10011 - CAB, UMTS-FDD (WCDMA); Frequency: 836.6 MHz; Duty Cycle: 1:1.95434

Medium parameters used (interpolated): $f = 836.6$ MHz; $\sigma = 0.96$ S/m; $\epsilon_r = 55.858$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3708; ConvF(9.1, 9.1, 9.1); Calibrated: 2016/11/10;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn720; Calibrated: 2016/10/31
- Phantom: 1659; Type: QD 000 P40 CD; Serial: xxxx
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373)

WCDMA BADN5 TG/wcdma band5 TG DATA M 10mm/Area Scan (9x13x1):

Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.202 W/kg

WCDMA BADN5 TG/wcdma band5 TG DATA M 10mm/Zoom Scan (7x7x7)/Cube 0:


Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 13.06 V/m; Power Drift = 0.00 dB

Peak SAR (extrapolated) = 0.246 W/kg

SAR(1 g) = 0.191 W/kg; SAR(10 g) = 0.144 W/kg

Maximum value of SAR (measured) = 0.201 W/kg



0 dB = 0.201 W/kg = -6.97 dBW/kg

LTE band4 (15BW 1RB)

FLAT	Towards phantom
------	-----------------

Communication System: UID 0, LTE band 4 (0); Frequency: 1732.5 MHz; Duty Cycle: 1:1
 Medium parameters used (interpolated): $f = 1732.5$ MHz; $\sigma = 1.459$ S/m; $\epsilon_r = 53.239$; $\rho = 1000$ kg/m³
 Phantom section: Flat Section

DASY5 Configuration:

- Probe: ES3DV3 - SN3127; ConvF(4.9, 4.9, 4.9); Calibrated: 2016/8/29;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn720; Calibrated: 2016/10/31
- Phantom: 1660; Type: QD 000 P40 CD; Serial: xxxx
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373)

LTE BAND4 TP retest/LTE band4 TG 15BW 1RB LOW M 10mm/Area Scan (9x13x1):

Measurement grid: dx=15mm, dy=15mm
 Maximum value of SAR (measured) = 0.338 W/kg

LTE BAND4 TP retest/LTE band4 TG 15BW 1RB LOW M 10mm/Zoom Scan (7x7x7)/Cube 0:


Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 7.165 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 0.453 W/kg


SAR(1 g) = 0.309 W/kg; SAR(10 g) = 0.204 W/kg

Maximum value of SAR (measured) = 0.329 W/kg



0 dB = 0.329 W/kg = -4.83 dBW/kg

LTE band5 (10BW 1RB)

FLAT	Towards ground
<p>Communication System: UID 0, LTE Band 5 (0); Frequency: 836.5 MHz;Duty Cycle: 1:1 Medium parameters used (interpolated): f = 836.5 MHz; $\sigma = 0.96$ S/m; $\epsilon_r = 55.859$; $\rho = 1000$ kg/m³ Phantom section: Flat Section</p>	
<p>DASY5 Configuration:</p> <ul style="list-style-type: none"> Probe: EX3DV4 - SN3708; ConvF(9.1, 9.1, 9.1); Calibrated: 2016/11/10; Sensor-Surface: 4mm (Mechanical Surface Detection) Electronics: DAE4 Sn720; Calibrated: 2016/10/31 Phantom: 1659; Type: QD 000 P40 CD; Serial: xxxx Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373) 	
<p>LTE BAND5 TG retest/LTE band5 TG 20BW 1RB LOW M 10mm/Area Scan (9x13x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (measured) = 0.418 W/kg</p>	
<p>LTE BAND5 TG retest/LTE band5 TG 20BW 1RB LOW M 10mm/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm Reference Value = 19.59 V/m; Power Drift = 0.09 dB Peak SAR (extrapolated) = 0.534 W/kg SAR(1 g) = 0.412 W/kg; SAR(10 g) = 0.309 W/kg Maximum value of SAR (measured) = 0.433 W/kg</p>	
 <p>0 dB = 0.433 W/kg = -3.64 dBW/kg</p>	

WLAN (DSSS, 1 Mbps)

Right Side	Cheek
------------	-------

Communication System: UID 10012 - CAB, IEEE 802.11b WiFi 2.4 GHz (DSSS, 1 Mbps);
 Frequency: 2462 MHz; Duty Cycle: 1:1.53815
 Medium parameters used (interpolated): $f = 2462$ MHz; $\sigma = 1.908$ S/m; $\epsilon_r = 37.862$; $\rho = 1000$ kg/m³
 Phantom section: Right Section

DASY5 Configuration:



- Probe: ES3DV3 - SN3127; ConvF(4.61, 4.61, 4.61); Calibrated: 2016/8/29;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn720; Calibrated: 2016/10/31
- Phantom: 1660; Type: QD 000 P40 CD; Serial: xxxx
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373)

Head-Section Right HSL LTE WIFI/WIFI 2.4 LOW HSL touch H 2/Area Scan (8x13x1):

Measurement grid: dx=15mm, dy=15mm
 Maximum value of SAR (measured) = 0.975 W/kg

Head-Section Right HSL LTE WIFI/WIFI 2.4 LOW HSL touch H 2/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm













Reference Value = 9.409 V/m; Power Drift = 0.06 dB
 Peak SAR (extrapolated) = 1.63 W/kg
SAR(1 g) = 0.841 W/kg; SAR(10 g) = 0.416 W/kg
 Maximum value of SAR (measured) = 0.962 W/kg




0 dB = 0.962 W/kg = -0.17 dBW/kg

ANNEX B - RELEVANT PAGES FROM CALIBRATION REPORTS

DAE4 Sn:1226

<div style="text-align: center;">  <p>In Collaboration with TTL Speag CALIBRATION LABORATORY</p> <p>Address: No. 51 Xueyuan Road, Haidian District, Beijing, 100191, China Tel: +86-10-62304633-2218 Fax: +86-10-62304633-2209 E-mail: ctt@chinaetl.com Http://www.chinaetl.cn</p> </div> <div style="text-align: center;">  <p>JAG-IRTA CNAS CALIBRATION No. L8970</p> </div> <p>Client: Tejet Certificate No: Z16-97168</p> <div style="border: 1px solid black; padding: 5px;"> <p>CALIBRATION CERTIFICATE</p> <p>Object: DAE4 - SN: 1226</p> <p>Calibration Procedure(s): FD-Z11-002-01 Calibration Procedure for the Data Acquisition Electronics (DAE4)</p> <p>Calibration date: September 28, 2016</p> <p>This calibration Certificate documents the traceability to national standards, which realize the physical units of measurements(SI). The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.</p> <p>All calibrations have been conducted in the closed laboratory facility; environment temperature(22±5)°C and humidity<70%.</p> <p>Calibration Equipment used (M&E critical for calibration)</p> <table border="1" style="width:100%; border-collapse: collapse;"> <thead> <tr> <th>Primary Standards</th> <th>ID #</th> <th>Cal Date(Calibrated by, Certificate No.)</th> <th>Scheduled Calibration</th> </tr> </thead> <tbody> <tr> <td>Process Calibrator 753</td> <td>1971018</td> <td>27-June-16 (CTTL, No.J16X04778)</td> <td>June-17</td> </tr> </tbody> </table> <table border="1" style="width:100%; border-collapse: collapse;"> <thead> <tr> <th>Calibrated by:</th> <th>Name</th> <th>Function</th> <th>Signature</th> </tr> </thead> <tbody> <tr> <td></td> <td>Zhao Jing</td> <td>SAR Test Engineer</td> <td></td> </tr> <tr> <td>Reviewed by:</td> <td>Qi Dianyuan</td> <td>SAR Project Leader</td> <td></td> </tr> <tr> <td>Approved by:</td> <td>Lu Bingsong</td> <td>Deputy Director of the laboratory</td> <td></td> </tr> </tbody> </table> <p style="text-align: right;">Issued: September 28, 2016</p> <p style="font-size: small;">This calibration certificate shall not be reproduced except in full without written approval of the laboratory.</p> </div> <p style="font-size: x-small;">Certificate No: Z16-97168 Page 1 of 3</p>	Primary Standards	ID #	Cal Date(Calibrated by, Certificate No.)	Scheduled Calibration	Process Calibrator 753	1971018	27-June-16 (CTTL, No.J16X04778)	June-17	Calibrated by:	Name	Function	Signature		Zhao Jing	SAR Test Engineer		Reviewed by:	Qi Dianyuan	SAR Project Leader		Approved by:	Lu Bingsong	Deputy Director of the laboratory		<div style="text-align: center;">  <p>In Collaboration with TTL Speag CALIBRATION LABORATORY</p> <p>Address: No. 51 Xueyuan Road, Haidian District, Beijing, 100191, China Tel: +86-10-62304633-2218 Fax: +86-10-62304633-2209 E-mail: ctt@chinaetl.com Http://www.chinaetl.cn</p> </div> <p>Glossary:</p> <p>DAE: data acquisition electronics Connector angle: information used in DASY system to align probe sensor X to the robot coordinate system.</p> <p>Methods Applied and Interpretation of Parameters:</p> <ul style="list-style-type: none"> DC Voltage Measurement: Calibration Factor assessed for use in DASY system by comparison with a calibrated instrument traceable to national standards. The figure given corresponds to the full scale range of the voltmeter in the respective range. Connector angle: The angle of the connector is assessed measuring the angle mechanically by a tool inserted. Uncertainty is not required. The report provide only calibration results for DAE, it does not contain other performance test results. <p style="font-size: x-small;">Certificate No: Z16-97168 Page 2 of 3</p>
Primary Standards	ID #	Cal Date(Calibrated by, Certificate No.)	Scheduled Calibration																						
Process Calibrator 753	1971018	27-June-16 (CTTL, No.J16X04778)	June-17																						
Calibrated by:	Name	Function	Signature																						
	Zhao Jing	SAR Test Engineer																							
Reviewed by:	Qi Dianyuan	SAR Project Leader																							
Approved by:	Lu Bingsong	Deputy Director of the laboratory																							



In Collaboration with
TTL Speag
CALIBRATION LABORATORY

Address: No. 51 Xueyuan Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62304633-2218 Fax: +86-10-62304633-2209
E-mail: ctt@chinaetl.com Http://www.chinaetl.cn

DC Voltage Measurement

A/D - Converter Resolution nominal
High Range: 1LSB = 61µV full range = -100...+300 mV
Low Range: 1LSB = 61nV full range = -1...+3mV
DASY measurement parameters: Auto Zero Time: 3 sec; Measuring time: 3 sec

Calibration Factors	X	Y	Z
High Range	404.633 ± 0.15% (k=2)	404.399 ± 0.15% (k=2)	404.123 ± 0.15% (k=2)
Low Range	3.97867 ± 0.7% (k=2)	4.00359 ± 0.7% (k=2)	3.98540 ± 0.7% (k=2)

Connector Angle

Connector Angle to be used in DASY system	114° ± 1°
---	-----------

Certificate No: Z16-97168 Page 3 of 3

DAE4 Sn:1327

In Collaboration with
TTL S P e a g
CALIBRATION LABORATORY

Address: No. 51 Xuyuan Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62304633-2218 Fax: +86-10-62304633-2209
E-mail: cti@china.ttl.com http://www.china.ttl.com

Client: Tejet Certificate No: J16-97048

CALIBRATION CERTIFICATE

Object: DAE4-SN: 1327

Calibration Procedure(s): FD-Z11-2-002-01
Calibration Procedure for the Data Acquisition Electronics (DAEx)

Calibration date: April 15, 2016

This calibration Certificate documents the traceability to national standards, which realize the physical units of measurements(SI). The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature(22±3)°C and humidity<70%.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID #	Cal Date(Calibrated by, Certificate No.)	Scheduled Calibration
Process Calibrator 753	1971018	01-July-14 (CTTL, No.J14X02147)	July-15

Calibrated by: Zhao Jing SAR Test Engineer

Reviewed by: Qi Dianyuan SAR Project Leader

Approved by: Lu Bingsong Deputy Director of the laboratory

Issued: April 18, 2016

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.

Certificate No: J16-97048

Page 1 of 3

In Collaboration with
TTL S P e a g
CALIBRATION LABORATORY

Address: No. 51 Xuyuan Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62304633-2218 Fax: +86-10-62304633-2209
E-mail: cti@china.ttl.com http://www.china.ttl.com

Glossary:

DAE: data acquisition electronics

Connector angle: information used in DASY system to align probe sensor X to the robot coordinate system.

Methods Applied and Interpretation of Parameters:

- DC Voltage Measurement: Calibration Factor assessed for use in DASY system by comparison with a calibrated instrument traceable to national standards. The figure given corresponds to the full scale range of the voltmeter in the respective range.
- Connector angle: The angle of the connector is assessed measuring the angle mechanically by a tool inserted. Uncertainty is not required.
- The report provide only calibration results for DAE, it does not contain other performance test results.

Certificate No: J16-97048

Page 2 of 3

In Collaboration with
TTL S P e a g
CALIBRATION LABORATORY

Address: No. 51 Xuyuan Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62304633-2218 Fax: +86-10-62304633-2209
E-mail: cti@china.ttl.com http://www.china.ttl.com

DC Voltage Measurement
A/D Converter Resolution nominal

High Range: 1LSB = 0.1µV, full range = -100...+300 mV
Low Range: 1LSB = 0.1mV, full range = -1...+3mV
DASY measurement parameters: Auto Zero Time: 3 sec, Measuring time: 3 sec

Calibration Factors	X	Y	Z
High Range	404.880 ± 0.15% (k=2)	404.737 ± 0.15% (k=2)	404.934 ± 0.15% (k=2)
Low Range	3.99344 ± 0.7% (k=2)	3.99268 ± 0.7% (k=2)	3.99828 ± 0.7% (k=2)

Connector Angle

Connector Angle to be used in DASY system	180° ± 1°
---	-----------

Certificate No: J16-97048

Page 3 of 3

ES3DV3 Sn:3297

In Collaboration with
TTL Speaq
CALIBRATION LABORATORY

中国认可
国际互认
校准
CNAS 15170

Client: Tejet Certificate No: Z16-97170

CALIBRATION CERTIFICATE

Object: ES3DV3 - SN:3297

Calibration Procedure(s): FD-Z11-004-01
Calibration Procedures for Dosimetric E-field Probes

Calibration date: October 14, 2016

This calibration Certificate documents the traceability to national standards, which realize the physical units of measurements(SI). The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature:(23±3) °C and humidity<70%.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID #	Cal Date/Calibrated by, Certificate No.	Scheduled Calibration
Power Meter NRP2	101919	27-Jun-16 (CTTL, No.J16X04777)	Jun-17
Power sensor NRP-Z91	101547	27-Jun-16 (CTTL, No.J16X04777)	Jun-17
Power sensor NRP-Z91	101548	27-Jun-16 (CTTL, No.J16X04777)	Jun-17
Reference10dBAttenuator	18NS0W-10dB	13-Mar-16(CTTL, No.J16X01547)	Mar-18
Reference20dBAttenuator	18NS0W-20dB	13-Mar-16(CTTL, No.J16X01548)	Mar-18
Reference Probe EX3DV4	SN 7307	19-Feb-16(SPEAQ, No. EX3-7307, Feb16)	Feb-17
DAE4	SN 1331	21-Jan-16(SPEAQ, No. DAE4-1331, Jan16)	Jan-17
Secondary Standards	ID #	Cal Date/Calibrated by, Certificate No.	Scheduled Calibration
SignalGeneratorMG3700A	6201052605	27-Jun-16 (CTTL, No.J16X04778)	Jun-17
Network Analyzer E5071C	MY48110673	26-Jan-16 (CTTL, No.J16X00894)	Jan-17

Calibrated by: Yu Zongying SAR Test Engineer

Reviewed by: Qi Dianyuan SAR Project Leader

Approved by: Liu Wei Deputy Director of SEM Department

Issued: October 15, 2016

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.

Certificate No: Z16-97170 Page 1 of 11

In Collaboration with
TTL Speaq
CALIBRATION LABORATORY

Client: Tejet Certificate No: Z16-97170

Glossary:

TSL: Issue simulating liquid

NORM_{x,y,z}: sensitivity in free space

ConvF: sensitivity in TSL / NORM_{x,y,z}

DCP: diode compression point

CF: crest factor (1/6 duty cycle) of the RF signal

A,B,C,D: modulation dependent linearization parameters

Polarization Φ : Φ rotation around probe axis

Polarization θ : θ rotation around an axis that is in the plane normal to probe axis (at measurement center), i

$\theta=0$ is normal to probe axis

Connector Angle: information used in DASY system to align probe sensor X to the robot coordinate system

Calibration is Performed According to the Following Standards:

a) IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013

b) IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300MHz to 3GHz)", February 2005

c) IEC 62209-2, "Procedure to determine the Specific Absorption Rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz)", March 2010

d) KDB 865654, "SAR Measurement Requirements for 100 MHz to 6 GHz"

Methods Applied and Interpretation of Parameters:

- NORM_{x,y,z}: Assessed for E-field polarization (E) (f>100MHz in TEM-cell; f>1800MHz: waveguide). NORM_{x,y,z} are only intermediate values, i.e., the uncertainties of NORM_{x,y,z} does not effect the E²-field uncertainty inside TSL (see below ConvF)
- NORM_{(h),y,z} = NORM_{x,y,z} frequency response (see Frequency Response Chart). This linearization is implemented in DASY4 software versions later than 4.2. The uncertainty of the frequency response is included in the stated uncertainty of ConvF.
- DCP_{x,y,z}: DCP are numerical linearization parameters assessed based on the data of power sweep (no uncertainty required). DCP does not depend on frequency nor media.
- PAR: PAR is the Peak to Average Ratio that is not calibrated but determined based on the signal characteristics.
- A_{x,y,z}; B_{x,y,z}; C_{x,y,z}; V_{R,x,y,z}: A,B,C are numerical linearization parameters assessed based on the data of power sweep for specific modulation signal. The parameters do not depend on frequency nor media. V_R is the maximum calibration range expressed in RMS voltage across the diode.
- ConvF and Boundary Effect Parameters: Assessed in flat phantom using E-field (or Temperature Transfer Standard for f<300MHz) and inside waveguide using analytical field distributions based on power measurements for f>800MHz. The same setup are used for assessment of the parameters applied for boundary compensation (alpha, depth) of which typical uncertainty valued are given. These parameters are used in DASY4 software to improve probe accuracy close to the boundary. The sensitivity in TSL corresponds to NORM_{x,y,z} ConvF whereby the uncertainty corresponds to that given for ConvF. A frequency dependent ConvF is used in DASY version 4.4 and higher which allows extending the validity from 50MHz to 100MHz.
- Spherical isotropy (3D deviation from isotropy): in a field of low gradients realized using a flat phantom exposed by a patch antenna.
- Sensor Offset: The sensor offset corresponds to the offset of virtual measurement center from the probe tip (on probe axis). No tolerance required.
- Connector Angle: The angle is assessed using the information gained by determining the NORM_x (no uncertainty required).

Certificate No: Z16-97170 Page 2 of 11



Address: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62396633-2218 Fax: +86-10-62396633-2209
E-mail: cti@china.ttl.com Http://www.china.ttl.com

Probe ES3DV3

SN: 3297

Calibrated: October 14, 2016
Calibrated for DASY/EASY Systems
(Note: non-compatible with DASY2 system!)

Certificate No: Z16-97170 Page 3 of 11



Address: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62396633-2218 Fax: +86-10-62396633-2209
E-mail: cti@china.ttl.com Http://www.china.ttl.com

DASY/EASY – Parameters of Probe: ES3DV3 - SN: 3297

Basic Calibration Parameters

	Sensor X	Sensor Y	Sensor Z	Unc (k=2)
Norm($\mu\text{V}/\text{Vim}^2$) ^A	0.94	1.03	1.26	±10.8%
DCP(mV) ^B	103.8	103.8	102.4	

Modulation Calibration Parameters

UID	Communication System Name	A dB	B dB μV	C	D dB	VR mV	Unc ^C (k=2)
0	CW	X	0.0	0.0	1.0	0.00	230.2 ±2.8%
		Y	0.0	0.0	1.0		242.0
		Z	0.0	0.0	1.0		271.4

The reported uncertainty of measurement is stated as the standard uncertainty of Measurement multiplied by the coverage factor k=2, which for a normal distribution Corresponds to a coverage probability of approximately 95%.

^A The uncertainties of Norm X, Y, Z do not affect the E²-field uncertainty inside TSL (see Page 5 and Page 6).
^B Numerical linearization parameter: uncertainty not required.
^C Uncertainty is determined using the max. deviation from linear response applying rectangular distribution and is expressed for the square of the field value.

Certificate No: Z16-97170 Page 4 of 11

ES3DV3 Sn:3297



In Collaboration with
TTL Speaq
CALIBRATION LABORATORY
Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62396633-2218 Fax: +86-10-62396633-2209
E-mail: cti@china.ttl.com Http://www.china.ttl.com

DASY/EASY – Parameters of Probe: ES3DV3 - SN: 3297

Calibration Parameter Determined in Head Tissue Simulating Media

f [MHz] ^c	Relative Permittivity ^f	Conductivity (S/m) ^f	ConvF X	ConvF Y	ConvF Z	Alpha ^g	Depth ^h (mm)	Unc. (k=2)
835	41.5	0.90	6.18	6.18	6.18	0.43	1.45	±12%
900	41.5	0.97	6.21	6.21	6.21	0.40	1.55	±12%
1750	40.1	1.37	5.22	5.22	5.22	0.56	1.49	±12%
1900	40.0	1.40	5.09	5.09	5.09	0.60	1.44	±12%
2000	40.0	1.40	4.93	4.93	4.93	0.45	1.77	±12%
2450	39.2	1.80	4.53	4.53	4.53	0.83	1.26	±12%

^c Frequency validity above 300 MHz of ±100MHz only applies for DASY v4.4 and higher (Page 2), else it is restricted to ±50MHz. The uncertainty is the RSS of ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band. Frequency validity below 300 MHz is ± 10, 25, 40, 50 and 70 MHz for ConvF assessments at 30, 64, 128, 150 and 220 MHz respectively. Above 5 GHz frequency validity can be extended to ± 110 MHz.
^f At frequency below 3 GHz, the validity of tissue parameters (ε and σ) can be relaxed to ±10%, if liquid compensation formula is applied to measured SAR values. At frequencies above 3 GHz, the validity of tissue parameters (ε and σ) is restricted to ±5%. The uncertainty is the RSS of the ConvF uncertainty for indicated target tissue parameters.
^g Alpha/Depth are determined during calibration. SPEAG warrants that the remaining deviation due to the boundary effect after compensation is always less than ± 1% for frequencies below 3 GHz and below ± 2% for the frequencies between 3-6 GHz at any distance larger than half the probe lip diameter from the boundary.

Certificate No: Z16-97170

Page 5 of 11



In Collaboration with
TTL Speaq
CALIBRATION LABORATORY
Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62396633-2218 Fax: +86-10-62396633-2209
E-mail: cti@china.ttl.com Http://www.china.ttl.com

DASY/EASY – Parameters of Probe: ES3DV3 - SN: 3297

Calibration Parameter Determined in Body Tissue Simulating Media

f [MHz] ^c	Relative Permittivity ^f	Conductivity (S/m) ^f	ConvF X	ConvF Y	ConvF Z	Alpha ^g	Depth ^h (mm)	Unc. (k=2)
835	55.2	0.97	6.08	6.08	6.08	0.43	1.56	±12%
900	55.0	1.05	6.08	6.08	6.08	0.42	1.64	±12%
1750	53.4	1.49	4.99	4.99	4.99	0.56	1.59	±12%
1900	53.3	1.52	4.82	4.82	4.82	0.52	1.62	±12%
2000	53.3	1.52	4.65	4.65	4.65	0.44	2.03	±12%
2450	52.7	1.95	4.46	4.46	4.46	0.90	1.25	±12%

^c Frequency validity above 300 MHz of ±100MHz only applies for DASY v4.4 and higher (Page 2), else it is restricted to ±50MHz. The uncertainty is the RSS of ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band. Frequency validity below 300 MHz is ± 10, 25, 40, 50 and 70 MHz for ConvF assessments at 30, 64, 128, 150 and 220 MHz respectively. Above 5 GHz frequency validity can be extended to ± 110 MHz.
^f At frequency below 3 GHz, the validity of tissue parameters (ε and σ) can be relaxed to ±10%, if liquid compensation formula is applied to measured SAR values. At frequencies above 3 GHz, the validity of tissue parameters (ε and σ) is restricted to ±5%. The uncertainty is the RSS of the ConvF uncertainty for indicated target tissue parameters.
^g Alpha/Depth are determined during calibration. SPEAG warrants that the remaining deviation due to the boundary effect after compensation is always less than ± 1% for frequencies below 3 GHz and below ± 2% for the frequencies between 3-6 GHz at any distance larger than half the probe lip diameter from the boundary.


Certificate No: Z16-97170

Page 6 of 11



In Collaboration with
TTL Speaq
CALIBRATION LABORATORY
Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62396633-2218 Fax: +86-10-62396633-2209
E-mail: cti@china.ttl.com Http://www.china.ttl.com

Frequency Response of E-Field
(TEM-Cell: if110 EXX, Waveguide: R22)



Uncertainty of Frequency Response of E-field: ±7.5% (k=2)


Certificate No: Z16-97170

Page 7 of 11



In Collaboration with
TTL Speaq
CALIBRATION LABORATORY
Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62396633-2218 Fax: +86-10-62396633-2209
E-mail: cti@china.ttl.com Http://www.china.ttl.com

Receiving Pattern (Φ), θ=0°




Uncertainty of Axial Isotropy Assessment: ±0.9% (k=2)

Certificate No: Z16-97170

Page 8 of 11

ES3DV3 Sn:3297




Certificate No: Z16-97170


Page 9 of 11



Conversion Factor Assessment



Deviation from Isotropy in Liquid



Certificate No: Z16-97170

Page 10 of 11



DASY/EASY – Parameters of Probe: ES3DV3 - SN: 3297

Other Probe Parameters

Sensor Arrangement	Triangular
Connector Angle (°)	15,5
Mechanical Surface Detection Mode	enabled
Optical Surface Detection Mode	disable
Probe Overall Length	337mm
Probe Body Diameter	10mm
Tip Length	10mm
Tip Diameter	4mm
Probe Tip to Sensor X Calibration Point	2mm
Probe Tip to Sensor Y Calibration Point	2mm
Probe Tip to Sensor Z Calibration Point	2mm
Recommended Measurement Distance from Surface	3mm

Certificate No: Z16-97170

Page 11 of 11

EX3DV4 Sn:3717

In Collaboration with
TTL Calibration Laboratory
S p e a g
Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China
Tel: +86-10-42304633-2218 Fax: +86-10-42304633-2209
E-mail: cti@china.ttl.com Http://www.china.ttl.com

In Collaboration with
IRG-MRA CNAS
中国认可
国际互认
校准
CNAS L0570

Client: **Ttjet** Certificate No: **Z16-97169**

CALIBRATION CERTIFICATE

Object: EX3DV4 - SN:3717

Calibration Procedure(s): FD-Z11-004-01
Calibration Procedures for Dosimetric E-field Probes

Calibration date: October 19, 2016

This calibration Certificate documents the traceability to national standards, which realize the physical units of measurements(S). The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature(22±3)°C and humidity<70%.

Calibration Equipment used (MATE critical for calibration)

Primary Standards	ID #	Cal Date(Calibrated by, Certificate No.)	Scheduled Calibration
Power Meter NRP2	101919	27-Jun-16 (CTTL No.J16X04777)	Jun-17
Power sensor NRP-Z01	101547	27-Jun-16 (CTTL No.J16X04777)	Jun-17
Power sensor NRP-Z01	101548	27-Jun-16 (CTTL No.J16X04777)	Jun-17
Reference10dBAttenuator	18N50W-10dB	13-Mar-16(CTTL No.J16X01547)	Mar-18
Reference20dBAttenuator	18N50W-20dB	13-Mar-16(CTTL No.J16X01548)	Mar-18
Reference Probe EX3DV4	SN 7307	19-Feb-16(SPEAG.No.EX-7307_Feb16)	Feb-17
DAE4	SN 1331	21-Jan-16(SPEAG.No.DAE4-1331_Jan16)	Jan-17
Secondary Standards	ID #	Cal Date(Calibrated by, Certificate No.)	Scheduled Calibration
SignalGeneratorMG3700A	6201052605	27-Jun-16 (CTTL No.J16X04778)	Jun-17
Network Analyzer E5071C	MY46110873	28-Jan-16 (CTTL No.J16X00894)	Jan-17

Calibrated by:	Name	Function	Signature
	Yu Zongying	SAR Test Engineer	
Reviewed by:	Qi Dianyuan	SAR Project Leader	
Approved by:	Liu Wei	Deputy Director of SEM Department	

issued: October 21, 2016

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.

Certificate No: Z16-97169 Page 1 of 11

In Collaboration with
TTL Calibration Laboratory
S p e a g
Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China
Tel: +86-10-42304633-2218 Fax: +86-10-42304633-2209
E-mail: cti@china.ttl.com Http://www.china.ttl.com

Glossary:

TSL: tissue simulating liquid
NORM_{x,y,z}: sensitivity in free space
ConvF: sensitivity in TSL / NORM_{x,y,z}
DCP: diode compression point
CF: crest factor (1/duty_cycle) of the RF signal
A,B,C,D: modulation dependent linearization parameters
Polarization φ: φ rotation around probe axis
Polarization θ: θ rotation around an axis that is in the plane normal to probe axis (at measurement center). θ=0 is normal to probe axis
Connector Angle: information used in DASY system to align probe sensor X to the robot coordinate system

Calibration is Performed According to the Following Standards:

a) IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
b) IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300MHz to 3GHz)", February 2005
c) IEC 62209-2, "Procedure to determine the Specific Absorption Rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz)", March 2010
d) K08 85664, "SAR Measurement Requirements for 100 MHz to 6 GHz"

Methods Applied and Interpretation of Parameters:

- NORM_{x,y,z}: Assessed for E-field polarization θ=0 (fs900MHz in TEM-cell; f>1800MHz: waveguide). NORM_{x,y,z} are only intermediate values, i.e. the uncertainties of NORM_{x,y,z} do not affect the E² field uncertainty inside TSL (see below ConvF).
- NORM(f)_{x,y,z} = NORM_{x,y,z} * frequency_response (see Frequency Response Chart). This linearization is implemented in DASY4 software versions later than 4.2. The uncertainty of the frequency response is included in the stated uncertainty of ConvF.
- DCP_{x,y,z}: DCP are numerical linearization parameters assessed based on the data of power sweep (no uncertainty required). DCP does not depend on frequency nor media.
- PAR: PAR is the Peak to Average Ratio that is not calibrated but determined based on the signal characteristics.
- A_{x,y,z}; B_{x,y,z}; C_{x,y,z}; VR_{x,y,z}; A,B,C are numerical linearization parameters assessed based on the data of power sweep for specific modulation signal. The parameters do not depend on frequency nor media. VR is the maximum calibration range expressed in RMS voltage across the diode.
- ConvF and Boundary Effect Parameters: Assessed in flat phantom using E-field (or Temperature Transfer Standard for fs900MHz) and inside waveguide using analytical field distributions based on power measurements for f<900MHz. The same setups are used for assessment of the parameters applied for boundary compensation (alpha, depth) of which typical uncertainty value are given. These parameters are used in DASY4 software to improve probe accuracy close to the boundary. The sensitivity in TSL corresponds to NORM_{x,y,z} * ConvF whereby the uncertainty corresponds to that given for ConvF. A frequency dependent ConvF is used in DASY version 4.4 and higher which allows extending the validity from 50MHz to 100MHz.
- Spherical isotropy (3D deviation from isotropy): in a field of low gradients realized using a flat phantom exposed by a patch antenna.
- Sensor Offset: The sensor offset corresponds to the offset of virtual measurement center from the probe tip (on probe axis). No tolerance required.
- Connector Angle: The angle is assessed using the information gained by determining the NORM_x (no uncertainty required).

Certificate No: Z16-97169 Page 2 of 11



Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China
Tel: +86-10-42304633-2218 Fax: +86-10-42304633-2209
E-mail: cti@china.ttl.com Http://www.china.ttl.com

Probe EX3DV4

SN: 3717

Calibrated: October 19, 2016
Calibrated for DASY/EASY Systems
(Note: non-compatible with DASY2 system!)

Certificate No: Z16-97169 Page 3 of 11



Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China
Tel: +86-10-42304633-2218 Fax: +86-10-42304633-2209
E-mail: cti@china.ttl.com Http://www.china.ttl.com

DASY/EASY – Parameters of Probe: EX3DV4 – SN: 3717

Basic Calibration Parameters

	Sensor X	Sensor Y	Sensor Z	Unc (k=2)
Norm(μV/(Vm) ^{1/2}) ^A	0.50	0.49	0.55	±10.8%
DCP(mV) ^B	99.6	102.5	100.8	

Modulation Calibration Parameters

UID	Communication System Name	B						
		A	B	C	D	VR	Unc ^C	
0	CW	X	0.0	0.0	1.0	0.00	203.0	±2.2%
		Y	0.0	0.0	1.0		197.5	
		Z	0.0	0.0	1.0		219.8	

The reported uncertainty of measurement is stated as the standard uncertainty of Measurement multiplied by the coverage factor k=2, which for a normal distribution Corresponds to a coverage probability of approximately 95%.

^A The uncertainties of Norm X, Y, Z do not affect the E²-field uncertainty inside TSL (see Page 5 and Page 6).
^B Numerical linearization parameter: uncertainty not required.
^C Uncertainty is determined using the max. deviation from linear response applying rectangular distribution and is expressed for the square of the field value.

Certificate No: Z16-97169 Page 4 of 11

EX3DV4 Sn:3717



DASY/EASY – Parameters of Probe: EX3DV4 – SN: 3717

Calibration Parameter Determined in Head Tissue Simulating Media

f [MHz] ²	Relative Permittivity ¹	Conductivity (S/m) ¹	ConvF X	ConvF Y	ConvF Z	Alpha ³	Depth ⁴ (mm)	Unc ⁵ (k=2)
750	41.9	0.89	9.27	9.27	9.27	0.30	0.80	±12%
835	41.5	0.90	8.93	8.93	8.93	0.14	1.39	±12%
900	41.5	0.97	8.94	8.94	8.94	0.12	1.60	±12%
1750	40.1	1.37	7.70	7.70	7.70	0.17	1.61	±12%
1900	40.0	1.40	7.65	7.65	7.65	0.20	1.49	±12%
2300	39.5	1.97	7.15	7.15	7.15	0.58	0.70	±12%
2450	39.2	1.80	6.96	6.96	6.96	0.40	0.91	±12%
2600	39.0	1.98	6.70	6.70	6.70	0.52	0.80	±12%
5200	36.0	4.68	5.25	5.25	5.25	0.40	1.25	±13%
5300	35.9	4.78	4.98	4.98	4.98	0.40	1.25	±13%
5500	35.6	4.96	4.80	4.80	4.80	0.40	1.28	±13%
5600	35.5	5.07	4.67	4.67	4.67	0.40	1.45	±13%
5800	35.3	5.27	4.57	4.57	4.57	0.44	1.45	±13%

² Frequency validity above 300 MHz of ±100MHz only applies for DASY v4.4 and higher (Page 2), else it is restricted to ±50MHz. The uncertainty is the RSS of ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band. Frequency validity below 300 MHz is ± 10, 25, 40, 50 and 70 MHz for ConvF assessments at 30, 64, 128, 150 and 220 MHz respectively. Above 5 GHz frequency validity can be extended to ± 110 MHz.

³ At frequency below 3 GHz, the validity of tissue parameters (ε and σ) can be relaxed to ±10% if liquid compensation formula is applied to measured SAR values. At frequencies above 3 GHz, the validity of tissue parameters (ε and σ) is restricted to ±5%. The uncertainty is the RSS of the ConvF uncertainty for indicated target tissue parameters.

⁴ Alpha/Depth are determined during calibration. SPEAG warrants that the remaining deviation due to the boundary effect after compensation is always less than ± 1% for frequencies below 3 GHz and below ± 2% for the frequencies between 3-6 GHz at any distance larger than half the probe tip diameter from the boundary.

Certificate No: Z16-97169

Page 5 of 11



DASY/EASY – Parameters of Probe: EX3DV4 – SN: 3717

Calibration Parameter Determined in Body Tissue Simulating Media

f [MHz] ²	Relative Permittivity ¹	Conductivity (S/m) ¹	ConvF X	ConvF Y	ConvF Z	Alpha ³	Depth ⁴ (mm)	Unc ⁵ (k=2)
750	55.5	0.96	9.25	9.25	9.25	0.50	0.82	±12%
835	55.2	0.97	8.99	8.99	8.99	0.16	1.54	±12%
900	55.0	1.05	8.93	8.93	8.93	0.23	1.12	±12%
1750	53.4	1.49	7.63	7.63	7.63	0.17	1.79	±12%
1900	53.3	1.52	7.44	7.44	7.44	0.20	1.71	±12%
2300	52.9	1.81	7.06	7.06	7.06	0.55	0.79	±12%
2450	52.7	1.95	7.04	7.04	7.04	0.38	1.12	±12%
2600	52.5	2.16	6.86	6.86	6.86	0.37	1.11	±12%
5200	49.0	5.30	4.47	4.47	4.47	0.45	1.50	±13%
5300	48.9	5.42	4.19	4.19	4.19	0.45	1.55	±13%
5500	48.6	5.65	3.90	3.90	3.90	0.50	1.50	±13%
5600	48.5	5.77	3.68	3.68	3.68	0.50	1.55	±13%
5800	48.2	6.00	3.83	3.83	3.83	0.50	1.70	±13%

² Frequency validity above 300 MHz of ±100MHz only applies for DASY v4.4 and higher (Page 2), else it is restricted to ±50MHz. The uncertainty is the RSS of ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band. Frequency validity below 300 MHz is ± 10, 25, 40, 50 and 70 MHz for ConvF assessments at 30, 64, 128, 150 and 220 MHz respectively. Above 5 GHz frequency validity can be extended to ± 110 MHz.

³ At frequency below 3 GHz, the validity of tissue parameters (ε and σ) can be relaxed to ±10% if liquid compensation formula is applied to measured SAR values. At frequencies above 3 GHz, the validity of tissue parameters (ε and σ) is restricted to ±5%. The uncertainty is the RSS of the ConvF uncertainty for indicated target tissue parameters.


⁴ Alpha/Depth are determined during calibration. SPEAG warrants that the remaining deviation due to the boundary effect after compensation is always less than ± 1% for frequencies below 3 GHz and below ± 2% for the frequencies between 3-6 GHz at any distance larger than half the probe tip diameter from the boundary.

Certificate No: Z16-97169

Page 6 of 11



Frequency Response of E-Field
(TEM-Cell: ifi110 EXX, Waveguide: R22)





Uncertainty of Frequency Response of E-field: ±7.5% (k=2)

Certificate No: Z16-97169

Page 7 of 11



Receiving Pattern (Φ, θ=0°)




Uncertainty of Axial Isotropy Assessment: ±0.9% (k=2)

Certificate No: Z16-97169


Page 8 of 11

EX3DV4 Sn:3717



Certificate No: Z16-97169

Page 9 of 11



Certificate No: Z16-97169

Page 10 of 11



DASY/EASY – Parameters of Probe: EX3DV4 – SN: 3717

Other Probe Parameters

Sensor Arrangement	Triangular
Connector Angle (°)	158.3
Mechanical Surface Detection Mode	enabled
Optical Surface Detection Mode	disable
Probe Overall Length	337mm
Probe Body Diameter	10mm
Tip Length	9mm
Tip Diameter	2.5mm
Probe Tip to Sensor X Calibration Point	1mm
Probe Tip to Sensor Y Calibration Point	1mm
Probe Tip to Sensor Z Calibration Point	1mm
Recommended Measurement Distance from Surface	1.4mm

Certificate No: Z16-97169

Page 11 of 11

D835V2 Sn:4d100

In Collaboration with
TTL CALIBRATION LABORATORY
Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62394633-2079 Fax: +86-10-62394633-2504
E-mail: ctt@china.ttl.com Http://www.china.ttl.com

In Collaboration with
SPEAG CALIBRATION LABORATORY
Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62394633-2079 Fax: +86-10-62394633-2504
E-mail: ctt@china.ttl.com Http://www.china.ttl.com

Client: **Tejet** Certificate No: **Z16-97171**

CALIBRATION CERTIFICATE

Object: D835V2 - SN: 4d100

Calibration Procedure(s): FD-Z11-003-01
Calibration Procedures for dipole validation kits

Calibration date: October 10, 2016

This calibration Certificate documents the traceability to national standards, which realize the physical units of measurements(SI). The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature(22±3)°C and humidity<70%.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID #	Cal Date(Calibrated by, Certificate No.)	Scheduled Calibration
Power Meter NRP2	101919	27-Jun-16 (CTTL_No.J16X04777)	Jun-17
Power sensor NRP-Z91	101547	27-Jun-16 (CTTL_No.J16X04777)	Jun-17
Reference Probe ES30V3	SN 3149	15-Apr-16(CTTL-SPEAG.No.J16-97035)	Apr-17
D4E4	SN 777	22-Aug-16(CTTL-SPEAG.No.Z16-97136)	Aug-17
Secondary Standards	ID #	Cal Date(Calibrated by, Certificate No.)	Scheduled Calibration
Signal Generator E4438C	MY49071430	01-Feb-16 (CTTL_No.J16X00893)	Jan-17
Network Analyzer E5071C	MY46110673	26-Jan-16 (CTTL_No.J16X00894)	Jan-17

Calibrated by:	Name	Function	Signature
	Zhao Jing	SAR Test Engineer	[Signature]
Reviewed by:	Qi Diaryuan	SAR Project Leader	[Signature]
Approved by:	Liu Wei	Deputy Director of SEM Department	[Signature]

Issued: October 14, 2016
This calibration certificate shall not be reproduced except in full without written approval of the laboratory.

Certificate No: Z16-97171 Page 1 of 8

In Collaboration with
TTL CALIBRATION LABORATORY
Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62394633-2079 Fax: +86-10-62394633-2504
E-mail: ctt@china.ttl.com Http://www.china.ttl.com

In Collaboration with
SPEAG CALIBRATION LABORATORY
Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62394633-2079 Fax: +86-10-62394633-2504
E-mail: ctt@china.ttl.com Http://www.china.ttl.com

Glossary:
TSL: tissue simulating liquid
ConvF: sensitivity in TSL / NORMx,y,z
N/A: not applicable or not measured

Calibration is Performed According to the Following Standards:
a) IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
b) IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) For hand-held devices used in close proximity to the ear (frequency range of 300MHz to 3GHz)", February 2005
c) IEC 62209-2, "Procedure to measure the Specific Absorption Rate (SAR) For wireless communication devices used in close proximity to the human body (frequency range of 30MHz to 6GHz)", March 2010
d) KDB655664, SAR Measurement Requirements for 100 MHz to 6 GHz

Additional Documentation:
e) DAST4/5 System Handbook

Methods Applied and Interpretation of Parameters:
• Measurement Conditions: Further details are available from the Validation Report at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated.
• Antenna Parameters with TSL: The dipole is mounted with the spacer to position its feed point exactly below the center marking of the flat phantom section, with the arms oriented parallel to the body axis.
• Feed Point Impedance and Return Loss: The parameters are measured with the dipole positioned under the liquid filled phantom. The impedance stated is transformed from the measurement at the SMA connector to the feed point. The Return Loss ensures low reflected power. No uncertainty required.
• Electrical Delay: One-way delay between the SMA connector and the antenna feed point. No uncertainty required.
• SAR measured: SAR measured at the stated antenna input power.
• SAR normalized: SAR as measured, normalized to an input power of 1 W at the antenna connector.
• SAR for nominal TSL parameters: The measured TSL parameters are used to calculate the nominal SAR result.

The reported uncertainty of measurement is stated as the standard uncertainty of Measurement multiplied by the coverage factor k=2, which for a normal distribution corresponds to a coverage probability of approximately 95%.

Certificate No: Z16-97171 Page 2 of 8

In Collaboration with
TTL CALIBRATION LABORATORY
Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62394633-2079 Fax: +86-10-62394633-2504
E-mail: ctt@china.ttl.com Http://www.china.ttl.com

In Collaboration with
SPEAG CALIBRATION LABORATORY
Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62394633-2079 Fax: +86-10-62394633-2504
E-mail: ctt@china.ttl.com Http://www.china.ttl.com

Measurement Conditions
DASY system configuration, as far as not given on page 1.

DASY Version	DASY02	52.8.8.1258
Extrapolation	Advanced Extrapolation	
Phantom	Triple Flat Phantom 5.1C	
Distance Dipole Center - TSL	15 mm	with Spacer
Zoom Scan Resolution	dx, dy, dz = 5 mm	
Frequency	835 MHz ± 1 MHz	

Head TSL parameters
The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Head TSL parameters	22.0 °C	41.5	0.90 mho/m
Measured Head TSL parameters	(22.0 ± 0.2) °C	41.3 ± 6 %	0.89 mho/m ± 6 %
Head TSL temperature change during test	<1.0 °C	---	---

SAR result with Head TSL

SAR averaged over 1 cm ² (1 g) of Head TSL	Condition
SAR measured	250 mW input power 2.37 mW / g
SAR for nominal Head TSL parameters	normalized to 1W 9.54 mW (g ± 20.8 % (k=2))
SAR averaged over 10 cm ² (10 g) of Head TSL	Condition
SAR measured	250 mW input power 1.55 mW / g
SAR for nominal Head TSL parameters	normalized to 1W 6.23 mW (g ± 20.4 % (k=2))

Body TSL parameters
The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Body TSL parameters	22.0 °C	55.2	0.97 mho/m
Measured Body TSL parameters	(22.0 ± 0.2) °C	55.4 ± 6 %	0.96 mho/m ± 6 %
Body TSL temperature change during test	<1.0 °C	---	---

SAR result with Body TSL

SAR averaged over 1 cm ² (1 g) of Body TSL	Condition
SAR measured	250 mW input power 2.39 mW / g
SAR for nominal Body TSL parameters	normalized to 1W 9.61 mW (g ± 20.8 % (k=2))
SAR averaged over 10 cm ² (10 g) of Body TSL	Condition
SAR measured	250 mW input power 1.59 mW / g
SAR for nominal Body TSL parameters	normalized to 1W 6.39 mW (g ± 20.4 % (k=2))

Certificate No: Z16-97171 Page 3 of 8

In Collaboration with
TTL CALIBRATION LABORATORY
Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62394633-2079 Fax: +86-10-62394633-2504
E-mail: ctt@china.ttl.com Http://www.china.ttl.com

In Collaboration with
SPEAG CALIBRATION LABORATORY
Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62394633-2079 Fax: +86-10-62394633-2504
E-mail: ctt@china.ttl.com Http://www.china.ttl.com

Appendix

Antenna Parameters with Head TSL

Impedance, transformed to feed point	52.50 + 1.37jΩ
Return Loss	-31.2dB

Antenna Parameters with Body TSL

Impedance, transformed to feed point	47.50 - 1.58jΩ
Return Loss	-30.5dB

General Antenna Parameters and Design

Electrical Delay (one direction)	1.500 ns
----------------------------------	----------

After long term use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured.

The dipole is made of standard semi-rigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals. On some of the dipoles, small end caps are added to the dipole arms in order to improve matching when loaded according to the position as explained in the "Measurement Conditions" paragraph. The SAR data are not affected by this change. The overall dipole length is still according to the Standard. No excessive force must be applied to the dipole arms, because they might bend or the soldered connections near the feedpoint may be damaged.

Additional EUT Data

Manufactured by	SPEAG
-----------------	-------

Certificate No: Z16-97171 Page 4 of 8

D835V2 Sn:4d100


In Collaboration with
TTL **speag**
CALIBRATION LABORATORY

Address: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62964633-2079 Fax: +86-10-62964633-2504
E-mail: ctt@china.ttl.com Http://www.chinatitl.com

DASY5 Validation Report for Head TSL Date: 10.10.2016
Test Laboratory: CTTI, Beijing, China
DUT: Dipole 835 MHz; Type: D835V2; Serial: D835V2 - SN: 4d100
Communication System: UID 0, CW; Frequency: 835 MHz; Duty Cycle: 1:1
Medium parameters used: $f = 835$ MHz; $\sigma = 0.892$ S/m; $\epsilon_r = 41.33$; $\rho = 1000$ kg/m³
Phantom section: Center Section
Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)
DASY5 Configuration:

- Probe: ES3DV3 - SN3149; ConvF(6.13, 6.13, 6.13); Calibrated: 4/15/2016;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn777; Calibrated: 2016-08-22
- Phantom: Triple Flat Phantom 5.1C; Type: QD 000 P51 CA; Serial: 1161/1
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7372)

Dipole Calibration/Zoom Scan (7x7x7) (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 56.12V/m; Power Drift = 0.01 dB
Peak SAR (extrapolated) = 3.53 W/kg
SAR(1g) = 2.37 W/kg; SAR(10g) = 1.55 W/kg
Maximum value of SAR (measured) = 2.77 W/kg




Certificate No: Z16-97171 Page 3 of 8

In Collaboration with
TTL **speag**
CALIBRATION LABORATORY

Address: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62964633-2079 Fax: +86-10-62964633-2504
E-mail: ctt@china.ttl.com Http://www.chinatitl.com

Impedance Measurement Plot for Head TSL



Certificate No: Z16-97171 Page 6 of 8


In Collaboration with
TTL **speag**
CALIBRATION LABORATORY

Address: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62964633-2079 Fax: +86-10-62964633-2504
E-mail: ctt@china.ttl.com Http://www.chinatitl.com

DASY5 Validation Report for Body TSL Date: 10.10.2016
Test Laboratory: CTTI, Beijing, China
DUT: Dipole 835 MHz; Type: D835V2; Serial: D835V2 - SN: 4d100
Communication System: UID 0, CW; Frequency: 835 MHz; Duty Cycle: 1:1
Medium parameters used: $f = 835$ MHz; $\sigma = 0.964$ S/m; $\epsilon_r = 55.42$; $\rho = 1000$ kg/m³
Phantom section: Left Section
Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)
DASY5 Configuration:

- Probe: ES3DV3 - SN3149; ConvF(6.13, 6.13, 6.13); Calibrated: 4/15/2016;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn777; Calibrated: 2016-08-22
- Phantom: Triple Flat Phantom 5.1C; Type: QD 000 P51 CA; Serial: 1161/1
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7372)

Dipole Calibration/Zoom Scan (7x7x7) (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 54.07 V/m; Power Drift = -0.01 dB
Peak SAR (extrapolated) = 3.46 W/kg
SAR(1g) = 2.39 W/kg; SAR(10g) = 1.59 W/kg
Maximum value of SAR (measured) = 2.78 W/kg




Certificate No: Z16-97171 Page 7 of 8

In Collaboration with
TTL **speag**
CALIBRATION LABORATORY

Address: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62964633-2079 Fax: +86-10-62964633-2504
E-mail: ctt@china.ttl.com Http://www.chinatitl.com

Impedance Measurement Plot for Body TSL



Certificate No: Z16-97171 Page 8 of 8

D1750V2 Sn:1034

In Collaboration with
TTL **S P E A G**
CALIBRATION LABORATORY

中国认可
国际互认
校准
CNAS 10670

Address: No. 51 Xueyuan Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62304633-2079 Fax: +86-10-62304633-2504
E-mail: cti@chinaul.com Http://www.chinaul.com

Client: Tejet Certificate No: Z16-97173

CALIBRATION CERTIFICATE

Object: D1750V2 - SN: 1034

Calibration Procedure(s): FD-Z11-003-01
Calibration Procedures for dipole validation kits

Calibration date: October 11, 2016

This calibration Certificate documents the traceability to national standards, which realize the physical units of measurements(SI). The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature:(22±3) °C and humidity<70%.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID #	Cal Date(Calibrated by, Certificate No.)	Scheduled Calibration
Power Meter NRP2	101919	27-Jun-16 (CTTL No.J16X04777)	Jun-17
Power sensor NRP-291	101547	27-Jun-16 (CTTL No.J16X04777)	Jun-17
Reference Probe E530V3 DA4E	SN 3149	15-Apr-16(CTTL-SPEAG.No.J16-97035)	Apr-17
	SN 777	22-Aug-16(CTTL-SPEAG.No.Z16-97138)	Aug-17

Secondary Standards	ID #	Cal Date(Calibrated by, Certificate No.)	Scheduled Calibration
Signal Generator E4438C	MY49071430	01-Feb-16 (CTTL No.J16X00893)	Jan-17
Network Analyzer E5071C	MY46110673	26-Jan-16 (CTTL No.J16X00894)	Jan-17

Calibrated by:	Name	Function	Signature
	Zhao Jing	SAR Test Engineer	
Reviewed by:	Qi Dianyuan	SAR Project Leader	
Approved by:	Liu Wei	Deputy Director of SEM Department	

issued: October 14, 2016

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.

Certificate No: Z16-97173 Page 1 of 8

In Collaboration with
TTL **S P E A G**
CALIBRATION LABORATORY

Address: No. 51 Xueyuan Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62304633-2079 Fax: +86-10-62304633-2504
E-mail: cti@chinaul.com Http://www.chinaul.com

Glossary:

TSL tissue simulating liquid
ConvF sensitivity in TSL / NORMx,y,z
N/A not applicable or not measured

Calibration is Performed According to the Following Standards:

- IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
- IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) For hand-held devices used in close proximity to the ear (frequency range of 300MHz to 3GHz)", February 2005
- IEC 62209-2, "Procedure to measure the Specific Absorption Rate (SAR) For wireless communication devices used in close proximity to the human body (frequency range of 30MHz to 6GHz)", March 2010
- KDB885984, SAR Measurement Requirements for 100 MHz to 6 GHz

Additional Documentation:

- DA5Y4/5 System Handbook

Methods Applied and Interpretation of Parameters:

- Measurement Conditions:** Further details are available from the Validation Report at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- Antenna Parameters with TSL:** The dipole is mounted with the spacer to position its feed point exactly below the center marking of the flat phantom section, with the arms oriented parallel to the body axis.
- Feed Point Impedance and Return Loss:** These parameters are measured with the dipole positioned under the liquid filled phantom. The impedance stated is transformed from the measurement at the SMA connector to the feed point. The Return Loss ensures low reflected power. No uncertainty required.
- Electrical Delay:** One-way delay between the SMA connector and the antenna feed point. No uncertainty required.
- SAR measured:** SAR measured at the stated antenna input power.
- SAR normalized:** SAR as measured, normalized to an input power of 1 W at the antenna connector.
- SAR for nominal TSL parameters:** The measured TSL parameters are used to calculate the nominal SAR result.

The reported uncertainty of measurement is stated as the standard uncertainty of Measurement multiplied by the coverage factor k=2, which for a normal distribution Corresponds to a coverage probability of approximately 95%.

Certificate No: Z16-97173 Page 2 of 8

In Collaboration with
TTL **S P E A G**
CALIBRATION LABORATORY

Address: No. 51 Xueyuan Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62304633-2079 Fax: +86-10-62304633-2504
E-mail: cti@chinaul.com Http://www.chinaul.com

Measurement Conditions

DASY system configuration, as far as not given on page 1.

DASY Version	DASY52	52.8.1258
Extrapolation	Advanced Extrapolation	
Phantom	Triple Flat Phantom 5.1C	
Distance Dipole Center - TSL	10 mm	with Spacer
Zoom Scan Resolution	dx, dy, dz = 5 mm	
Frequency	1750 MHz ± 1 MHz	

Head TSL parameters

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Head TSL parameters	22.0 °C	40.1	1.37 mho/m
Measured Head TSL parameters	(22.0 ± 0.2) °C	40.2 ± 6 %	1.39 mho/m ± 6 %
Head TSL temperature change during test	<1.0 °C	---	---

SAR result with Head TSL

SAR averaged over 1 cm ² (1 g) of Head TSL	Condition	
SAR measured	250 mW input power	9.30 mW / g
SAR for nominal Head TSL parameters	normalized to 1W	36.9 mW / g ± 20.8 % (k=2)
SAR averaged over 10 cm ² (10 g) of Head TSL	Condition	
SAR measured	250 mW input power	5.08 mW / g
SAR for nominal Head TSL parameters	normalized to 1W	20.2 mW / g ± 20.4 % (k=2)

Body TSL parameters

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Body TSL parameters	22.0 °C	53.4	1.46 mho/m
Measured Body TSL parameters	(22.0 ± 0.2) °C	53.5 ± 6 %	1.50 mho/m ± 6 %
Body TSL temperature change during test	<1.0 °C	---	---

SAR result with Body TSL

SAR averaged over 1 cm ² (1 g) of Body TSL	Condition	
SAR measured	250 mW input power	9.32 mW / g
SAR for nominal Body TSL parameters	normalized to 1W	37.1 mW / g ± 20.8 % (k=2)
SAR averaged over 10 cm ² (10 g) of Body TSL	Condition	
SAR measured	250 mW input power	5.15 mW / g
SAR for nominal Body TSL parameters	normalized to 1W	20.6 mW / g ± 20.4 % (k=2)

Certificate No: Z16-97173 Page 3 of 8

In Collaboration with
TTL **S P E A G**
CALIBRATION LABORATORY

Address: No. 51 Xueyuan Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62304633-2079 Fax: +86-10-62304633-2504
E-mail: cti@chinaul.com Http://www.chinaul.com

Appendix

Antenna Parameters with Head TSL

Impedance, transformed to feed point	49.00- 0.90jΩ
Return Loss	- 37.3dB

Antenna Parameters with Body TSL

Impedance, transformed to feed point	48.30+ 0.28jΩ
Return Loss	- 28.3dB

General Antenna Parameters and Design

Electrical Delay (one direction)	1.318 ns
----------------------------------	----------

After long term use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured.

The dipole is made of standard semirigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals. On some of the dipoles, small end caps are added to the dipole arms in order to improve matching when loaded according to the position as explained in the "Measurement Conditions" paragraph. The SAR data are not affected by this change. The overall dipole length is still according to the Standard. No excessive force must be applied to the dipole arms, because they might bend or the soldered connections near the feedpoint may be damaged.

Additional EUT Data

Manufactured by	SPEAG
-----------------	-------

Certificate No: Z16-97173 Page 4 of 8

D1750V2 Sn:1034



Address: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62306633-2079 Fax: +86-10-62306633-2504
E-mail: cttl@china.ttl.com Http://www.china.ttl.com

DASY5 Validation Report for Head TSL

Date: 10.11.2016

Test Laboratory: CTTI, Beijing, China

DUT: Dipole 1750 MHz; Type: D1750V2; Serial: D1750V2 - SN: 1034

Communication System: UID 0, CW; Frequency: 1750 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1750$ MHz; $\sigma = 1.392$ S/m; $\epsilon_r = 40.23$; $\rho = 1000$ kg/m³

Phantom section: Center Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: ES3DV3 - SN3149; ConvF(5.19, 5.19, 5.19); Calibrated: 4/15/2016;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DA64 Ss777; Calibrated: 2016-08-22
- Phantom: Triple Flat Phantom 5.1C; Type: QD 000 P51 CA; Serial: 1161/1
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7372)

System Performance Check/Zoom Scan (7x7x7) (7x7x7)/Cube 0; Measurement grid:


$dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 92.35V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 16.1 W/kg

SAR(1 g) = 9.3 W/kg; SAR(10 g) = 5.08 W/kg

Maximum value of SAR (measured) = 11.7 W/kg




Certificate No: Z16-97173

Page 5 of 8



Address: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62306633-2079 Fax: +86-10-62306633-2504
E-mail: cttl@china.ttl.com Http://www.china.ttl.com

Impedance Measurement Plot for Head TSL



Certificate No: Z16-97173

Page 6 of 8



Address: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62306633-2079 Fax: +86-10-62306633-2504
E-mail: cttl@china.ttl.com Http://www.china.ttl.com

DASY5 Validation Report for Body TSL

Date: 10.11.2016

Test Laboratory: CTTI, Beijing, China

DUT: Dipole 1750 MHz; Type: D1750V2; Serial: D1750V2 - SN: 1034

Communication System: UID 0, CW; Frequency: 1750 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1750$ MHz; $\sigma = 1.503$ S/m; $\epsilon_r = 53.51$; $\rho = 1000$ kg/m³

Phantom section: Left Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: ES3DV3 - SN3149; ConvF(4.95, 4.95, 4.95); Calibrated: 4/15/2016;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DA64 Ss777; Calibrated: 2016-08-22
- Phantom: Triple Flat Phantom 5.1C; Type: QD 000 P51 CA; Serial: 1161/1
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7372)

System Performance Check/Zoom Scan (7x7x7) (7x7x7)/Cube 0; Measurement grid:


$dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 91.04 V/m; Power Drift = -0.06 dB

Peak SAR (extrapolated) = 15.4 W/kg

SAR(1 g) = 9.32 W/kg; SAR(10 g) = 5.15 W/kg

Maximum value of SAR (measured) = 11.6 W/kg




Certificate No: Z16-97173

Page 7 of 8



Address: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62306633-2079 Fax: +86-10-62306633-2504
E-mail: cttl@china.ttl.com Http://www.china.ttl.com

Impedance Measurement Plot for Body TSL



Certificate No: Z16-97173

Page 8 of 8

D1900V2 Sn:5d155

In Collaboration with
TTL Calibration Laboratory
Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62386633-2079 Fax: +86-10-62386633-2504
E-mail: cti@china.ttl.com Http://www.china.ttl.com

In Collaboration with
SPEAG Calibration Laboratory
中国认可 国际互认
校准 CALIBRATION
CNAS L0570

Client: **Ttjel** Certificate No: **Z16-97050**

CALIBRATION CERTIFICATE

Object: **D1900V2 - SN: 5d155**

Calibration Procedure(s): **FD-Z11-2-003-01**
Calibration Procedures for dipole validation kits

Calibration date: **April 14, 2016**

This calibration Certificate documents the traceability to national standards, which realize the physical units of measurements(S). The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility; environment temperature(2±3)°C and humidity<70%.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID #	Cal Date/Calibrated by, Certificate No.	Scheduled Calibration
Power Meter NRP2	101919	01-Jul-15 (CTTL No.J15X04256)	Jun-16
Power sensor NRP-Z91	101547	01-Jul-15 (CTTL No.J15X04256)	Jun-16
Reference Probe EX3DV4	SN 3617	26-Aug-16(SPEAG No. EX3-3617_Aug16)	Aug-16
DAIE4	SN 1331	21-Jan-16(SPEAG No.DAIE4-1331_Jan16)	Jan-17

Secondary Standards	ID #	Cal Date/Calibrated by, Certificate No.	Scheduled Calibration
Signal Generator E4438C	MY49071430	01-Feb-16 (CTTL No.J16X00893)	Jan-17
Network Analyzer E5071C	MY46110673	26-Jan-16 (CTTL No.J16X00894)	Jan-17

Calibrated by:	Name	Function	Signature
	Zhao Jing	SAR Test Engineer	
Reviewed by:	Qi Danyuan	SAR Project Leader	
Approved by:	Lu Bingsong	Deputy Director of the laboratory	

Issued: April 18, 2016

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.

Certificate No: Z16-97050 Page 1 of 8

In Collaboration with
TTL Calibration Laboratory
Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62386633-2079 Fax: +86-10-62386633-2504
E-mail: cti@china.ttl.com Http://www.china.ttl.com

In Collaboration with
SPEAG Calibration Laboratory

Glossary:
TSL: tissue simulating liquid
ConvF: sensitivity in TSL / NORM y,z
N/A: not applicable or not measured

Calibration is Performed According to the Following Standards:
a) IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
b) IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) For hand-held devices used in close proximity to the ear (frequency range of 300MHz to 3GHz)", February 2005
c) IEC 62209-2, "Procedure to measure the Specific Absorption Rate (SAR) For wireless communication devices used in close proximity to the human body (frequency range of 30MHz to 6GHz)", March 2010
d) KDB865664, SAR Measurement Requirements for 100 MHz to 6 GHz

Additional Documentation:
e) DAS4/5 System Handbook

Methods Applied and Interpretation of Parameters:

- Measurement Conditions: Further details are available from the Validation Report at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- Antenna Parameters with TSL: The dipole is mounted with the spacer to position its feed point exactly below the center marking of the flat phantom section, with the arms oriented parallel to the body axis.
- Feed Point Impedance and Return Loss: These parameters are measured with the dipole positioned under the liquid filled phantom. The impedance stated is transformed from the measurement at the SMA connector to the feed point. The Return Loss ensures low reflected power. No uncertainty required.
- Electrical Delay: One-way delay between the SMA connector and the antenna feed point. No uncertainty required.
- SAR measured: SAR measured at the stated antenna input power.
- SAR normalized: SAR as measured, normalized to an input power of 1 W at the antenna connector.
- SAR for nominal TSL parameters: The measured TSL parameters are used to calculate the nominal SAR result.

The reported uncertainty of measurement is stated as the standard uncertainty of Measurement multiplied by the coverage factor k=2, which for a normal distribution Corresponds to a coverage probability of approximately 95%.

Certificate No: Z16-97050 Page 2 of 8

In Collaboration with
TTL Calibration Laboratory
Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62386633-2079 Fax: +86-10-62386633-2504
E-mail: cti@china.ttl.com Http://www.china.ttl.com

In Collaboration with
SPEAG Calibration Laboratory

Measurement Conditions

DASY system configuration, as far as not given on page 1.

DASY Version	DASY52	52.8.8.1258
Extrapolation	Advanced Extrapolation	
Phantoms	Triple Flat Phantom 5.1C	
Distance Dipole Center - TSL	10 mm	with Spacer
Zoom Scan Resolution	dx, dy, dz = 5 mm	
Frequency	1900 MHz ± 1 MHz	

Head TSL parameters

The following parameters and calculations were applied:

	Temperature	Permittivity	Conductivity
Nominal Head TSL parameters	22.0 °C	40.0	1.40 mho/m
Measured Head TSL parameters	(22.0 ± 0.2) °C	39.6 ± 6 %	1.39 mho/m ± 6 %
Head TSL temperature change during test	<1.0 °C	---	---

SAR result with Head TSL

SAR averaged over 1 cm ² (1 g) of Head TSL	Condition	
SAR measured	250 mW input power	10.2 mW / g
SAR for nominal Head TSL parameters	normalized to 1W	41.0 mW / g ± 20.8 % (k=2)

SAR averaged over 10 cm ² (10 g) of Head TSL	Condition	
SAR measured	250 mW input power	5.31 mW / g
SAR for nominal Head TSL parameters	normalized to 1W	21.3 mW / g ± 20.4 % (k=2)

Body TSL parameters

The following parameters and calculations were applied:

	Temperature	Permittivity	Conductivity
Nominal Body TSL parameters	22.0 °C	53.3	1.52 mho/m
Measured Body TSL parameters	(22.0 ± 0.2) °C	54.2 ± 6 %	1.50 mho/m ± 6 %
Body TSL temperature change during test	<1.0 °C	---	---

SAR result with Body TSL

SAR averaged over 1 cm ² (1 g) of Body TSL	Condition	
SAR measured	250 mW input power	9.87 mW / g
SAR for nominal Body TSL parameters	normalized to 1W	39.9 mW / g ± 20.5 % (k=2)

SAR averaged over 10 cm ² (10 g) of Body TSL	Condition	
SAR measured	250 mW input power	5.21 mW / g
SAR for nominal Body TSL parameters	normalized to 1W	21.0 mW / g ± 20.4 % (k=2)

Certificate No: Z16-97050 Page 3 of 8

In Collaboration with
TTL Calibration Laboratory
Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62386633-2079 Fax: +86-10-62386633-2504
E-mail: cti@china.ttl.com Http://www.china.ttl.com

In Collaboration with
SPEAG Calibration Laboratory

Appendix

Antenna Parameters with Head TSL

Impedance, transformed to feed point	51.60- j8.24jΩ
Return Loss	-24.0dB

Antenna Parameters with Body TSL

Impedance, transformed to feed point	49.60- j5.79jΩ
Return Loss	-24.7dB

General Antenna Parameters and Design

Electrical Delay (one direction)	1.310 ns
----------------------------------	----------

After long term use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured.

The dipole is made of standard semirigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals. On some of the dipoles, small end caps are added to the dipole arms in order to improve matching when loaded according to the position as explained in the "Measurement Conditions" paragraph. The SAR data are not affected by this change. The overall dipole length is still according to the Standard. No excessive force must be applied to the dipole arms, because they might bend or the soldered connections near the feedpoint may be damaged.

Additional EUT Data

Manufactured by	SPEAG
-----------------	-------

Certificate No: Z16-97050 Page 4 of 8

D1900V2 Sn:5d155

In Collaboration with
TTL CALIBRATION LABORATORY

Address: No. 51 Xueyuan Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62386633-2079 Fax: +86-10-62386633-2504
E-mail: ent@china.ttl.com Http://www.china.ttl.com

Date: 04.14.2016

DASY5 Validation Report for Head TSL
Test Laboratory: CTTI, Beijing, China
DUT: Dipole 1900 MHz; Type: D1900V2; Serial: D1900V2 - SN: 5d155
Communication System: UTD 0, CW; Frequency: 1900 MHz; Duty Cycle: 1:1
Medium parameters used: $f = 1900$ MHz; $\sigma = 1.386$ S/m; $\epsilon_r = 39.58$; $\rho = 1000$ kg/m³
Phantom section: Center Section
Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)
DASY5 Configuration:

- Probe: EX3DV4 - SN3617; ConvF(8.07, 8.07, 8.07); Calibrated: 8/26/2015;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Ser1331; Calibrated: 2016-01-21
- Phantom: Triple Flat Phantom 5.1C; Type: QD 000 P51 CA; Serial: 1161/1
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7372)

System Performance Check/Zoom Scan (7x7x7) (7x7x7) Cube 0; Measurement grid:
 $d_x=5$ mm, $d_y=5$ mm, $d_z=5$ mm
Reference Value = 103.1V/m; Power Drift = -0.05 dB
Peak SAR (extrapolated) = 19.1W/kg
SAR(1g) = 10.2 W/kg; SAR(10g) = 5.31 W/kg
Maximum value of SAR (measured) = 14.8 W/kg

Certificate No: Z16-97050 Page 5 of 8

In Collaboration with
TTL CALIBRATION LABORATORY

Address: No. 51 Xueyuan Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62386633-2079 Fax: +86-10-62386633-2504
E-mail: ent@china.ttl.com Http://www.china.ttl.com

Impedance Measurement Plot for Head TSL

Certificate No: Z16-97050 Page 6 of 8

In Collaboration with
TTL CALIBRATION LABORATORY

Address: No. 51 Xueyuan Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62386633-2079 Fax: +86-10-62386633-2504
E-mail: ent@china.ttl.com Http://www.china.ttl.com

Date: 04.14.2016

DASY5 Validation Report for Body TSL
Test Laboratory: CTTI, Beijing, China
DUT: Dipole 1900 MHz; Type: D1900V2; Serial: D1900V2 - SN: 5d155
Communication System: UTD 0, CW; Frequency: 1900 MHz; Duty Cycle: 1:1
Medium parameters used: $f = 1900$ MHz; $\sigma = 1.501$ S/m; $\epsilon_r = 54.22$; $\rho = 1000$ kg/m³
Phantom section: Left Section
Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)
DASY5 Configuration:

- Probe: EX3DV4 - SN3617; ConvF(7.74, 7.74, 7.74); Calibrated: 8/26/2015;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Ser1331; Calibrated: 2016-01-21
- Phantom: Triple Flat Phantom 5.1C; Type: QD 000 P51 CA; Serial: 1161/1
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7372)

System Performance Check/Zoom Scan (7x7x7) (7x7x7) Cube 0; Measurement grid:
 $d_x=5$ mm, $d_y=5$ mm, $d_z=5$ mm
Reference Value = 98.40 V/m; Power Drift = -0.07 dB
Peak SAR (extrapolated) = 17.6 W/kg
SAR(1g) = 9.87 W/kg; SAR(10g) = 5.21 W/kg
Maximum value of SAR (measured) = 14.0 W/kg

Certificate No: Z16-97050 Page 7 of 8

In Collaboration with
TTL CALIBRATION LABORATORY

Address: No. 51 Xueyuan Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62386633-2079 Fax: +86-10-62386633-2504
E-mail: ent@china.ttl.com Http://www.china.ttl.com

Impedance Measurement Plot for Body TSL

Certificate No: Z16-97050 Page 8 of 8

D2450V2 Sn:845

In Collaboration with
TTL **s p e a g**
CALIBRATION LABORATORY

中国认可
国际互认
校准
CNAS 10670

Address: No. 51 Xueyuan Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62394633-2079 Fax: +86-10-62394633-2504
E-mail: cti@chinaeui.com Http://www.chinaeui.com

Client: Tejet Certificate No: Z16-97175

CALIBRATION CERTIFICATE

Object: D2450V2 - SN: 845

Calibration Procedure(s): FD-Z11-003-01
Calibration Procedures for dipole validation kits

Calibration date: October 12, 2016

This calibration Certificate documents the traceability to national standards, which realize the physical units of measurements(SI). The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature(22±3)°C and humidity<70%.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID #	Cal Date(Calibrated by, Certificate No.)	Scheduled Calibration
Power Meter NRP2	101919	27-Jun-16 (CTTL, No.J16X04777)	Jun-17
Power sensor NRP-Z91	101547	27-Jun-16 (CTTL, No.J16X04777)	Jun-17
Reference Probe ES3DV3	SN 3149	15-Apr-16(CTTL-SPEAG.No.J16-87035)	Apr-17
DAE4	SN 777	22-Aug-16(CTTL-SPEAG.No.Z16-97138)	Aug-17
Secondary Standards	ID #	Cal Date(Calibrated by, Certificate No.)	Scheduled Calibration
Signal Generator E4438C	MY49071430	01-Feb-16 (CTTL, No.J16X00893)	Jan-17
Network Analyzer E5071C	MY46110673	26-Jan-16 (CTTL, No.J16X00894)	Jan-17

Calibrated by:	Name	Function	Signature
	Zhao Jing	SAR Test Engineer	
Reviewed by:	Qi Diqiyuan	SAR Project Leader	
Approved by:	Liu Wei	Deputy Director of SEM Department	

Issued: October 14, 2016

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.

In Collaboration with
TTL **s p e a g**
CALIBRATION LABORATORY

中国认可
国际互认
校准
CNAS 10670

Address: No. 51 Xueyuan Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62394633-2079 Fax: +86-10-62394633-2504
E-mail: cti@chinaeui.com Http://www.chinaeui.com

Glossary:

TSL: tissue simulating liquid
ConvF: sensitivity in TSL / NORM_{x,y,z}
N/A: not applicable or not measured

Calibration is Performed According to the Following Standards:

- IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
- IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) For hand-held devices used in close proximity to the ear (frequency range of 300MHz to 3GHz)", February 2005
- IEC 62209-2, "Procedure to measure the Specific Absorption Rate (SAR) For wireless communication devices used in close proximity to the human body (frequency range of 30MHz to 6GHz)", March 2010
- KDB865684, SAR Measurement Requirements for 100 MHz to 6 GHz.

Additional Documentation:

e) DASY4/5 System Handbook

Methods Applied and Interpretation of Parameters:

- Measurement Conditions:** Further details are available from the Validation Report at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- Antenna Parameters with TSL:** The dipole is mounted with the spacer to position its feed point exactly below the center marking of the flat phantom section, with the arms oriented parallel to the body axis.
- Feed Point Impedance and Return Loss:** These parameters are measured with the dipole positioned under the liquid filled phantom. The impedance stated is transformed from the measurement at the SMA connector to the feed point. The Return Loss ensures low reflected power. No uncertainty required.
- Electrical Delay:** One-way delay between the SMA connector and the antenna feed point. No uncertainty required.
- SAR measured:** SAR measured at the stated antenna input power.
- SAR normalized:** SAR as measured, normalized to an input power of 1 W at the antenna connector.
- SAR for nominal TSL parameters:** The measured TSL parameters are used to calculate the nominal SAR result.

The reported uncertainty of measurement is stated as the standard uncertainty of Measurement, multiplied by the coverage factor k=2, which for a normal distribution Corresponds to a coverage probability of approximately 95%.

Certificate No: Z16-97175 Page 1 of 8

In Collaboration with
TTL **s p e a g**
CALIBRATION LABORATORY

中国认可
国际互认
校准
CNAS 10670

Address: No. 51 Xueyuan Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62394633-2079 Fax: +86-10-62394633-2504
E-mail: cti@chinaeui.com Http://www.chinaeui.com

Measurement Conditions

DASY system configuration, as far as not given on page 1.

DASY Version	DASY52	52.8.8.1258
Extrapolation	Advanced Extrapolation	
Phantom	Triple Flat Phantom 5.1C	
Distance Dipole Center - TSL	10 mm	with Spacer
Zoom Scan Resolution	dx, dy, dz = 5 mm	
Frequency	2450 MHz ± 1 MHz	

Head TSL parameters

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Head TSL parameters	22.0 °C	39.2	1.80 mho/m
Measured Head TSL parameters	(22.0 ± 0.2) °C	39.0 ± 0.6	1.79 mho/m ± 6 %
Head TSL temperature change during test	<1.0 °C	---	---

SAR result with Head TSL

SAR averaged over 1 cm ³ (1 g) of Head TSL	Condition	
SAR measured	250 mW input power	13.0 mW / g
SAR for nominal Head TSL parameters	normalized to 1W	82.3 mW (g ± 20.8 % (k=2))
SAR averaged over 10 cm ³ (10 g) of Head TSL	Condition	
SAR measured	250 mW input power	6.09 mW / g
SAR for nominal Head TSL parameters	normalized to 1W	24.4 mW (g ± 20.4 % (k=2))

Body TSL parameters

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Body TSL parameters	22.0 °C	52.7	1.95 mho/m
Measured Body TSL parameters	(22.0 ± 0.2) °C	52.9 ± 0.6	1.92 mho/m ± 6 %
Body TSL temperature change during test	<1.0 °C	---	---

SAR result with Body TSL

SAR averaged over 1 cm ³ (1 g) of Body TSL	Condition	
SAR measured	250 mW input power	12.7 mW / g
SAR for nominal Body TSL parameters	normalized to 1W	51.2 mW (g ± 20.8 % (k=2))
SAR averaged over 10 cm ³ (10 g) of Body TSL	Condition	
SAR measured	250 mW input power	5.99 mW / g
SAR for nominal Body TSL parameters	normalized to 1W	24.1 mW (g ± 20.4 % (k=2))

In Collaboration with
TTL **s p e a g**
CALIBRATION LABORATORY

中国认可
国际互认
校准
CNAS 10670

Address: No. 51 Xueyuan Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62394633-2079 Fax: +86-10-62394633-2504
E-mail: cti@chinaeui.com Http://www.chinaeui.com

Appendix

Antenna Parameters with Head TSL

Impedance, transformed to feed point	51.90+ j 4.93Ω
Return Loss	- 25.7dB

Antenna Parameters with Body TSL

Impedance, transformed to feed point	50.50+ j 6.56Ω
Return Loss	- 23.7dB

General Antenna Parameters and Design

Electrical Delay (one direction)	1.270 ns
----------------------------------	----------

After long term use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured.

The dipole is made of standard semi-rigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals. On some of the dipoles, small end caps are added to the dipole arms in order to improve matching when loaded according to the position as explained in the "Measurement Conditions" paragraph. The SAR data are not affected by this change. The overall dipole length is still according to the Standard. No excessive force must be applied to the dipole arms, because they might bend or the soldered connections near the feedpoint may be damaged.

Additional EUT Data

Manufactured by	SPEAG
-----------------	-------

D2450V2 Sn:845

TTL In Collaboration with **s p e a g**
CALIBRATION LABORATORY

Address: No. 51 Xueyuan Road, Haidian District, Beijing, 100191, China
Tel: +86-10-42394633-2079 Fax: +86-10-42394633-2504
E-mail: cti@china.ttl.com Http://www.chinatitl.com

Date: 10.12.2016

DASY5 Validation Report for Head TSL
Test Laboratory: TTL, Beijing, China
DUT: Dipole 2450 MHz; Type: D2450V2; Serial: D2450V2 - SN: 845
Communication System: UTD 0, CW; Frequency: 2450 MHz; Duty Cycle: 1:1
Medium parameters used: $f = 2450$ MHz; $\sigma = 1.777$ S/m; $\epsilon_r = 39.03$; $\rho = 1000$ kg/m³
Phantom section: Center Section
Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)
DASY5 Configuration:

- Probe: ES3DV3 - SN3149; ConvF(4.51, 4.51, 4.51); Calibrated: 4/15/2016;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Ser77; Calibrated: 8/22/2016
- Phantom: Triple Flat Phantom S.1C; Type: QD 000 P51 CA; Serial: 1161/1
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7372)

Dipole Calibration/Zoom Scan (7x7x7) (7x7x7) Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 99.63 V/m; Power Drift = -0.03 dB
Peak SAR (extrapolated) = 26.7 W/kg
SAR(1 g) = 13 W/kg; SAR(10 g) = 6.09 W/kg
Maximum value of SAR (measured) = 17.1 W/kg

0 dB = 17.1 W/kg = 12.33 dBW/kg

TTL In Collaboration with **s p e a g**
CALIBRATION LABORATORY

Address: No. 51 Xueyuan Road, Haidian District, Beijing, 100191, China
Tel: +86-10-42394633-2079 Fax: +86-10-42394633-2504
E-mail: cti@china.ttl.com Http://www.chinatitl.com

Impedance Measurement Plot for Head TSL

TTL In Collaboration with **s p e a g**
CALIBRATION LABORATORY

Address: No. 51 Xueyuan Road, Haidian District, Beijing, 100191, China
Tel: +86-10-42394633-2079 Fax: +86-10-42394633-2504
E-mail: cti@china.ttl.com Http://www.chinatitl.com

Date: 10.12.2016

DASY5 Validation Report for Body TSL
Test Laboratory: TTL, Beijing, China
DUT: Dipole 2450 MHz; Type: D2450V2; Serial: D2450V2 - SN: 845
Communication System: UTD 0, CW; Frequency: 2450 MHz; Duty Cycle: 1:1
Medium parameters used: $f = 2450$ MHz; $\sigma = 1.923$ S/m; $\epsilon_r = 52.91$; $\rho = 1000$ kg/m³
Phantom section: Left Section
Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)
DASY5 Configuration:

- Probe: ES3DV3 - SN3149; ConvF(4.23, 4.23, 4.23); Calibrated: 4/15/2016;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Ser77; Calibrated: 8/22/2016
- Phantom: Triple Flat Phantom S.1C; Type: QD 000 P51 CA; Serial: 1161/1
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7372)

Dipole Calibration/Zoom Scan (7x7x7) (7x7x7) Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 97.85 V/m; Power Drift = -0.01 dB
Peak SAR (extrapolated) = 24.8 W/kg
SAR(1 g) = 12.7 W/kg; SAR(10 g) = 5.99 W/kg
Maximum value of SAR (measured) = 16.7 W/kg

0 dB = 16.7 W/kg = 12.23 dBW/kg

TTL In Collaboration with **s p e a g**
CALIBRATION LABORATORY

Address: No. 51 Xueyuan Road, Haidian District, Beijing, 100191, China
Tel: +86-10-42394633-2079 Fax: +86-10-42394633-2504
E-mail: cti@china.ttl.com Http://www.chinatitl.com

Impedance Measurement Plot for Body TSL

D2600V2 Sn:1059

In Collaboration with
TTL **SPEAG**
CALIBRATION LABORATORY

中国认可
国际互认
校准
CALIBRATION
CNAS 15070

Address: No. 51 Xueyuan Road, Haidian District, Beijing, 100191, China
Tel: +86-10-4236613-3079 Fax: +86-10-4236613-2504
E-mail: csl@chinaetl.com Http://www.chinaetl.com

Client: Tejet Certificate No: Z16-97051

CALIBRATION CERTIFICATE

Object: D2600V2 - SN: 1059

Calibration Procedure(s): FD-Z11-2-003-01
Calibration Procedures for dipole validation kits

Calibration date: April 14, 2016

This calibration Certificate documents the traceability to national standards, which realize the physical units of measurements(S). The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature(22±3)°C and humidity<70%.

Calibration Equipment used (MATE critical for calibration)

Primary Standards	ID #	Cal Date/Calibrated by, Certificate No.)	Scheduled Calibration
Power Meter NRP2	101919	01-Jul-15 (CTTL No.J15X04295)	Jun-16
Power sensor NRP-ZB1	101547	01-Jul-15 (CTTL No.J15X04295)	Jun-16
Reference Probe EX3DVA	SN 3817	28-Aug-15(SPEAG.No.EX3-3817_Aug15)	Aug-16
DAE4	SN 1331	21-Jan-16(SPEAG.No.DAE4-1331_Jan16)	Jan-17

Secondary Standards	ID #	Cal Date/Calibrated by, Certificate No.)	Scheduled Calibration
Signal Generator E4438C	MY49071430	01-Feb-16 (CTTL No.J16X00993)	Jan-17
Network Analyzer E5071C	MY48110673	26-Jan-16 (CTTL No.J16X00994)	Jan-17

Calibrated by:	Name	Function	Signature
	Zhao Jing	SAR Test Engineer	
Reviewed by:	Qi Dianyuan	SAR Project Leader	
Approved by:	Lu Bingcong	Deputy Director of the laboratory	

Issued: April 15, 2016
This calibration certificate shall not be reproduced except in full without written approval of the laboratory.

In Collaboration with
TTL **SPEAG**
CALIBRATION LABORATORY

中国认可
国际互认
校准
CALIBRATION
CNAS 15070

Address: No. 51 Xueyuan Road, Haidian District, Beijing, 100191, China
Tel: +86-10-4236613-3079 Fax: +86-10-4236613-2504
E-mail: csl@chinaetl.com Http://www.chinaetl.com

Client: Tejet Certificate No: Z16-97051

Glossary:

TSL: tissue simulating liquid
ConvF: sensitivity in TSL / NORM_{x,y,z}
N/A: not applicable or not measured

Calibration is Performed According to the Following Standards:

- IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
- IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) For hand-held devices used in close proximity to the ear (frequency range of 300MHz to 3GHz)", February 2005
- IEC 62209-2, "Procedure to measure the Specific Absorption Rate (SAR) For wireless communication devices used in close proximity to the human body (frequency range of 30MHz to 6GHz)", March 2010
- KDB85694, SAR Measurement Requirements for 100 MHz to 6 GHz

Additional Documentation:
e) DASY4/5 System Handbook

Methods Applied and Interpretation of Parameters:

- Measurement Conditions: Further details are available from the Validation Report at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- Antenna Parameters with TSL: The dipole is mounted with the spacer to position its feed point exactly below the center marking of the flat phantom section, with the arms oriented parallel to the body axis.
- Feed Point Impedance and Return Loss: These parameters are measured with the dipole positioned under the liquid filled phantom. The impedance stated is transformed from the measurement at the SMA connector to the feed point. The Return Loss ensures low reflected power. No uncertainty required.
- Electrical Delay: One-way delay between the SMA connector and the antenna feed point. No uncertainty required.
- SAR measured: SAR measured at the stated antenna input power.
- SAR normalized: SAR as measured, normalized to an input power of 1 W at the antenna connector.
- SAR for nominal TSL parameters: The measured TSL parameters are used to calculate the nominal SAR result.

The reported uncertainty of measurement is stated as the standard uncertainty of Measurement multiplied by the coverage factor k=2, which for a normal distribution corresponds to a coverage probability of approximately 95%.

Certificate No: Z16-97051 Page 1 of 8

Certificate No: Z16-97051 Page 2 of 8

In Collaboration with
TTL **SPEAG**
CALIBRATION LABORATORY

中国认可
国际互认
校准
CALIBRATION
CNAS 15070

Address: No. 51 Xueyuan Road, Haidian District, Beijing, 100191, China
Tel: +86-10-4236613-3079 Fax: +86-10-4236613-2504
E-mail: csl@chinaetl.com Http://www.chinaetl.com

Client: Tejet Certificate No: Z16-97051

Measurement Conditions

DASY system configuration, as far as not given on page 1

DASY Version	DASY52	52.8.8.1258
Extrapolation	Advanced Extrapolation	
Phantom	Triple Flat Phantom 5.1C	
Distance Dipole Center - TSL	10 mm	with Spacer
Zoom Scan Resolution	dx, dy, dz = 5 mm	
Frequency	2600 MHz ± 1 MHz	

Head TSL parameters

The following parameters and calculations were applied:

Temperature	Permittivity	Conductivity	
Nominal Head TSL parameters	22.0 °C	39.0	1.96 mho/m
Measured Head TSL parameters	(22.0 ± 0.2) °C	39.4 ± 0.6 %	1.94 mho/m ± 6 %
Head TSL temperature change during test	<1.0 °C	—	—

SAR result with Head TSL

SAR averaged over 1 cm ² (1 g) of Head TSL	Condition	
SAR measured	250 mW input power	14.0 mW / g
SAR for nominal Head TSL parameters	normalized to 1W	56.4 mW / g ± 20.8 % (k=2)
SAR averaged over 10 cm ² (10 g) of Head TSL	Condition	
SAR measured	250 mW input power	6.28 mW / g
SAR for nominal Head TSL parameters	normalized to 1W	25.2 mW / g ± 20.4 % (k=2)

Body TSL parameters

The following parameters and calculations were applied:

Temperature	Permittivity	Conductivity	
Nominal Body TSL parameters	22.0 °C	52.5	2.18 mho/m
Measured Body TSL parameters	(22.0 ± 0.2) °C	52.1 ± 0.6 %	2.18 mho/m ± 6 %
Body TSL temperature change during test	<1.0 °C	—	—

SAR result with Body TSL

SAR averaged over 1 cm ² (1 g) of Body TSL	Condition	
SAR measured	250 mW input power	14.5 mW / g
SAR for nominal Body TSL parameters	normalized to 1W	57.6 mW / g ± 20.8 % (k=2)
SAR averaged over 10 cm ² (10 g) of Body TSL	Condition	
SAR measured	250 mW input power	6.52 mW / g
SAR for nominal Body TSL parameters	normalized to 1W	26.0 mW / g ± 20.4 % (k=2)

Certificate No: Z16-97051 Page 3 of 8

In Collaboration with
TTL **SPEAG**
CALIBRATION LABORATORY

中国认可
国际互认
校准
CALIBRATION
CNAS 15070

Address: No. 51 Xueyuan Road, Haidian District, Beijing, 100191, China
Tel: +86-10-4236613-3079 Fax: +86-10-4236613-2504
E-mail: csl@chinaetl.com Http://www.chinaetl.com

Client: Tejet Certificate No: Z16-97051

Appendix

Antenna Parameters with Head TSL

Impedance, transformed to feed point	50.80-5.47jΩ
Return Loss	-26.2dB

Antenna Parameters with Body TSL

Impedance, transformed to feed point	47.60-3.75jΩ
Return Loss	-27.2dB

General Antenna Parameters and Design

Electrical Delay (one direction)	1.256 ns
----------------------------------	----------

After long term use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured.

The dipole is made of standard semirigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals. On some of the dipoles, small end caps are added to the dipole arms in order to improve matching when loaded according to the position as explained in the "Measurement Conditions" paragraph. The SAR data are not affected by this change. The overall dipole length is still according to the Standard. No excessive force must be applied to the dipole arms, because they might bend or the soldered connections near the feedpoint may be damaged.

Additional EUT Data

Manufactured by	SPEAG
-----------------	-------

Certificate No: Z16-97051 Page 4 of 8

D2600V2 Sn:1059


TTL In Collaboration with **S P E A G**
CALIBRATION LABORATORY
Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62366433-2079 Fax: +86-10-62366433-2504
E-mail: csl@chinaatl.com Http://www.chinaatl.com

DASYS Validation Report for Head TSL Date: 04.14.2016
Test Laboratory: TTL, Beijing, China
DUT: Dipole 2600 MHz; Type: D2600V2; Serial: D2600V2 - SN: 1059
Communication System: UTD 0, CW; Frequency: 2600 MHz; Duty Cycle: 1:1
Medium parameters used: $f = 2600$ MHz; $\sigma = 1.938$ S/m; $\alpha = 39.38$; $\rho = 1000$ kg/m³
Phantom section: Center Section
Measurement Standard: DASYS (IEEE/EC/ANSI C63.19-2007)

DASYS Configuration:

- Probe: EX3DV4 - SN3617; ConvF(7.21, 7.21, 7.21); Calibrated: 8/26/2015;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Ssl1331; Calibrated: 2016-01-21
- Phantom: Triple Flat Phantom 5.1C; Type: QD 000 P51 CA; Serial: 1161/1
- Measurement SW: DASYS2, Version 52.8 (8); SEMCAD X Version 14.6.10 (7372)

Dipole Calibration/Zoom Scan (7x7x7) (7x7x7) Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 104.7 V/m; Power Drift = 0.02 dB
Peak SAR (extrapolated) = 29.9 W/kg
SAR(1 g) = 14 W/kg; SAR(10 g) = 6.28 W/kg
Maximum value of SAR (measured) = 21.7 W/kg




Certificate No: Z16-97051

Page 5 of 8

TTL In Collaboration with **S P E A G**
CALIBRATION LABORATORY
Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62366433-2079 Fax: +86-10-62366433-2504
E-mail: csl@chinaatl.com Http://www.chinaatl.com

Impedance Measurement Plot for Head TSL



Certificate No: Z16-97051

Page 6 of 8


TTL In Collaboration with **S P E A G**
CALIBRATION LABORATORY
Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62366433-2079 Fax: +86-10-62366433-2504
E-mail: csl@chinaatl.com Http://www.chinaatl.com

DASYS Validation Report for Body TSL Date: 04.14.2016
Test Laboratory: TTL, Beijing, China
DUT: Dipole 2600 MHz; Type: D2600V2; Serial: D2600V2 - SN: 1059
Communication System: UTD 0, CW; Frequency: 2600 MHz; Duty Cycle: 1:1
Medium parameters used: $f = 2600$ MHz; $\sigma = 2.184$ S/m; $\alpha = 52.07$; $\rho = 1000$ kg/m³
Phantom section: Left Section
Measurement Standard: DASYS (IEEE/EC/ANSI C63.19-2007)

DASYS Configuration:

- Probe: EX3DV4 - SN3617; ConvF(7.2, 7.2, 7.2); Calibrated: 8/26/2015;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Ssl1331; Calibrated: 2016-01-21
- Phantom: Triple Flat Phantom 5.1C; Type: QD 000 P51 CA; Serial: 1161/1
- Measurement SW: DASYS2, Version 52.8 (8); SEMCAD X Version 14.6.10 (7372)

Dipole Calibration/Zoom Scan (7x7x7) (7x7x7) Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 96.85 V/m; Power Drift = 0.05 dB
Peak SAR (extrapolated) = 30.7 W/kg
SAR(1 g) = 14.5 W/kg; SAR(10 g) = 6.52 W/kg
Maximum value of SAR (measured) = 22.2 W/kg




Certificate No: Z16-97051

Page 7 of 8

TTL In Collaboration with **S P E A G**
CALIBRATION LABORATORY
Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62366433-2079 Fax: +86-10-62366433-2504
E-mail: csl@chinaatl.com Http://www.chinaatl.com


Impedance Measurement Plot for Body TSL




Certificate No: Z16-97051

Page 8 of 8


ANNEX C - PHOTOGRAPH




Cheek position, left side




Tilt position, left side



Cheek position, Right side



Tilt position, Right side



FLAT position, Towards phantom



FLAT position, Towards ground



FLAT position, EDGE1



FLAT position, EDGE2



FLAT position, EDGE3



FLAT position, EDGE4



10mm Spacer

---End of Test Report---