
TEST REPORT FOR RF TESTING

Report No.: SRTC2019-9004(F)-19010203(C)

Product Name: LTE Ufi

Product Model: 802ZT

Applicant: ZTE Corporation

Manufacturer: ZTE Corporation

Specification: FCC CFR47 PART 2, 22H, 24E, 27L (2019)

FCC ID: SRQ-MF993

The State Radio_monitoring_center Testing Center (SRTC)

15th Building, No.30, Shixing Street, Shijingshan District,

Beijing, P.R.China

Tel: 86-10-57996183 Fax: 86-10-57996388

CONTENTS

1. GENERAL INFORMATION.....	2
1.1 Notes of the test report	2
1.2 Information about the testing laboratory.....	2
1.3 Applicant's details	2
1.4 Manufacturer's details	2
1.5 Test Environment	3
2 DESCRIPTION OF THE EQUIPMENT UNDER TEST	4
2.1 Final Equipment Build Status	4
2.2 Summary table	5
2.3 Support Equipment	6
3 REFERENCE SPECIFICATION.....	7
4 KEY TO NOTES AND RESULT CODES	8
5 RESULT SUMMARY	9
6 TEST RESULT	10
6.1 RF Power Output	10
6.2 Effective Radiated Power.....	11
6.3 Occupied Bandwidth	12
6.4 Emission Bandwidth.....	13
6.5 Peak-Average Ratio	14
6.6 Spurious Emissions at antenna terminal.....	15
6.7 Band Edges Compliance	16
6.8 Frequency Stability	17
6.9 Radiated Spurious Emissions	18
7 MEASUREMENT UNCERTAINTIES	20
8 TEST EQUIPMENTS.....	21
APPENDIX A – TEST DATA OF CONDUCTED EMISSION	22
APPENDIX B – TEST DATA OF RADIATED EMISSION.....	180

1. GENERAL INFORMATION

1.1 Notes of the test report

The test report may only be reproduced or published in full. Reproduction or publication of extracts from the report requires the prior written permission of The State Radio_monitoring_center Testing Center (SRTC).

The test results relate only to individual items of the samples which have been tested.

The certification and accreditation identifiers used in this report shall not be applicable to the tested or calibrated samples thereof. The manufacturer shall not mark the tested samples or items (or a separate part of the item) with the identifiers of certification and accreditation to mislead relevant parties about the tested samples or items.

1.2 Information about the testing laboratory

Company:	The State Radio_monitoring_center Testing Center (SRTC)
Address:	15th Building, No.30 Shixing Street, Shijingshan District, P.R.China
City:	Beijing
Country or Region:	P.R.China
Contacted person:	Liu Jia
Tel:	+86 10 57996183
Fax:	+86 10 57996388
Email:	liujiat@srtc.org.cn

1.3 Applicant's details

Company:	ZTE Corporation
Address:	ZTE Plaza, #55 Keji Road South, Hi-Tech, Industrial Park, Nanshan District,Guangdong
City:	Shenzhen
Country or Region:	P.R.China
Contacted person:	Yang Zhao
Tel:	029-83600770
Fax:	---
Email:	zhao.yangxa@zte.com.cn

1.4 Manufacturer's details

Company:	ZTE Corporation
Address:	ZTE Plaza, #55 Keji Road South, Hi-Tech, Industrial Park, Nanshan District,Guangdong
City:	Shenzhen
Country or Region:	P.R.China
Contacted person:	Yang Zhao
Tel:	029-83600770
Fax:	---
Email:	zhao.yangxa@zte.com.cn

1.5 Test Environment

Date of Receipt of test sample at SRTC:	2019-01-02
Testing Start Date:	2019-01-02
Testing End Date:	2019-03-05

Environmental Data:	Temperature (°C)	Humidity (%)
Ambient	25	30
Maximum Extreme	55	---
Minimum Extreme	-10	---

Normal Supply Voltage (V d.c.):	3.730
Maximum Extreme Supply Voltage (V d.c.):	4.103
Minimum Extreme Supply Voltage (V d.c.):	3.357

2 DESCRIPTION OF THE EQUIPMENT UNDER TEST

2.1 Final Equipment Build Status

Frequency Range	LTE Band 2: Tx:1850~1910MHz Rx:1930~1990MHz LTE Band 4: Tx:1710~1755MHz Rx:2110~2155MHz LTE Band 12: Tx:699~716 MHz Rx:729~746 MHz LTE Band 17: Tx:704~716 MHz Rx:734~746 MHz LTE Band 41: Tx:2496~2690 MHz Rx:2496~2690 MHz
CA Combination	NA
Modulation Type	QPSK 16QAM 64QAM
Duplex Mode	FDD/TDD
Antenna Type	Fixed Internal Antenna
Power Supply	Battery/AC adapter
HW Version	Battery/AC adapter
SW Version	MF993H01
IMEI	MF993S01

2.2 Summary table

FCC Rule Part	Frequency Range(MHz)	EIRP/ERP (W)	Frequency Tolerance (ppm)	Emission Designator	Emission Bandwidth (MHz)	Measured 26dBC Bandwidth (MHz)	Communication Type
LTE BAND2							
24E	1850.7-1909.3	0.314	0.019	1M11G7D	1.4M	1.230	QPSK
	1850.7-1909.3	0.293	0.019	1M11D7W	1.4M	1.248	16QAM
	1850.7-1909.3	0.293	0.019	1M11W7D	1.4M	1.244	64QAM
	1851.5-1908.5	0.329	0.020	2M74G7D	3M	2.972	QPSK
	1851.5-1908.5	0.293	0.020	2M73D7W	3M	2.962	16QAM
	1851.5-1908.5	0.293	0.020	2M72W7D	3M	2.952	64QAM
	1852.5-1907.5	0.321	0.019	4M49G7D	5M	4.810	QPSK
	1852.5-1907.5	0.286	0.019	4M50D7W	5M	4.803	16QAM
	1852.5-1907.5	0.293	0.019	4M50W7D	5M	4.785	64QAM
	1855-1905	0.321	0.018	9M0G7D	10M	9.756	QPSK
	1855-1905	0.286	0.018	9M0D7W	10M	9.685	16QAM
	1855-1905	0.293	0.018	9M0W7D	10M	9.681	64QAM
	1857.5-1902.5	0.329	0.019	13M5G7D	15M	14.230	QPSK
	1857.5-1902.5	0.300	0.019	13M5D7W	15M	14.210	16QAM
	1857.5-1902.5	0.300	0.019	13M5W7D	15M	14.300	64QAM
	1860-1900	0.337	0.020	17M9G7D	20M	18.730	QPSK
	1860-1900	0.300	0.020	17M9D7W	20M	18.690	16QAM
	1860-1900	0.300	0.020	17M9W7D	20M	18.720	64QAM
LTE BAND4							
27L	1710.7-1754.3	0.217	0.019	1M10G7D	1.4M	1.228	QPSK
	1710.7-1754.3	0.212	0.019	1M10D7W	1.4M	1.241	16QAM
	1710.7-1754.3	0.212	0.019	1M11W7D	1.4M	1.248	64QAM
	1711.5-1753.5	0.217	0.017	2M73G7D	3M	3.022	QPSK
	1711.5-1753.5	0.212	0.017	2M73D7W	3M	2.960	16QAM
	1711.5-1753.5	0.212	0.017	2M73W7D	3M	2.960	64QAM
	1712.5-1752.5	0.222	0.020	4M50G7D	5M	4.776	QPSK
	1712.5-1752.5	0.212	0.020	4M50D7W	5M	4.776	16QAM
	1712.5-1752.5	0.212	0.020	4M50W7D	5M	4.771	64QAM
	1715-1750	0.233	0.019	9M0G7D	10M	9.675	QPSK
	1715-1750	0.212	0.019	9M0D7W	10M	9.685	16QAM
	1715-1750	0.212	0.019	9M0W7D	10M	9.707	64QAM
	1717.5-1747.5	0.238	0.014	13M4G7D	15M	14.230	QPSK
	1717.5-1747.5	0.212	0.014	13M5D7W	15M	14.280	16QAM
	1717.5-1747.5	0.212	0.014	13M5W7D	15M	14.190	64QAM
	1720-1745	0.244	0.018	17M9G7D	20M	18.720	QPSK
	1720-1745	0.222	0.018	17M9D7W	20M	18.690	16QAM
	1720-1745	0.222	0.018	17M9W7D	20M	18.740	64QAM

LTE BAND12							
27H	699.7-715.3	0.177	0.020	1M10G7D	1.4M	1.224	QPSK
	699.7-715.3	0.158	0.020	1M10D7W	1.4M	1.223	16QAM
	699.7-715.3	0.162	0.020	1M10W7D	1.4M	1.214	64QAM
	700.5-714.5	0.182	0.018	2M72G7D	3M	2.973	QPSK
	700.5-714.5	0.162	0.018	2M71D7W	3M	2.999	16QAM
	700.5-714.5	0.166	0.018	2M73W7D	3M	2.980	64QAM
	701.5-713.5	0.182	0.020	4M49G7D	5M	4.745	QPSK
	701.5-713.5	0.162	0.020	4M50D7W	5M	4.768	16QAM
	701.5-713.5	0.166	0.020	4M50W7D	5M	4.821	64QAM
	704-711	0.190	0.019	9M0G7D	10M	9.674	QPSK
	704-711	0.166	0.019	9M0D7W	10M	9.674	16QAM
	704-711	0.169	0.019	9M0W7D	10M	9.677	64QAM
LTE BAND17							
27H	706.5-713.5	0.177	0.017	4M49G7D	5M	4.769	QPSK
	706.5-713.5	0.162	0.017	4M50D7W	5M	4.774	16QAM
	706.5-713.5	0.166	0.017	4M50W7D	5M	4.778	64QAM
	709-711	0.182	0.020	9M0G7D	10M	9.467	QPSK
	709-711	0.162	0.020	9M0D7W	10M	9.464	16QAM
	709-711	0.166	0.020	9M0W7D	10M	9.462	64QAM
LTE BAND41							
27M	2498.5-2687.5	0.711	0.020	4M49G7D	5M	4.774	QPSK
	2498.5-2687.5	0.634	0.020	4M48D7W	5M	4.823	16QAM
	2498.5-2687.5	0.664	0.020	4M49W7D	5M	4.768	64QAM
	2501-2685	0.664	0.019	9M0G7D	10M	9.704	QPSK
	2501-2685	0.578	0.019	9M1D7W	10M	9.695	16QAM
	2501-2685	0.664	0.019	9M0W7D	10M	9.610	64QAM
	2503.5-2682.5	0.711	0.017	13M5G7D	15M	14.320	QPSK
	2503.5-2682.5	0.619	0.017	13M5D7W	15M	14.200	16QAM
	2503.5-2682.5	0.695	0.017	13M5W7D	15M	14.300	64QAM
	2506-2680	0.745	0.020	17M9G7D	20M	18.760	QPSK
	2506-2680	0.649	0.020	17M9D7W	20M	18.640	16QAM
	2506-2680	0.695	0.020	17M9W7D	20M	18.950	64QAM

2.3 Support Equipment

The following support equipment was used to exercise the EUT during testing:

Equipment	Battery
Manufacturer	Jiade Energy Technology(Zhuhai)Co.,Ltd.
Model Number	Li3730T43P4h794667
Serial Number	---

3 REFERENCE SPECIFICATION

The tests documented in this report were performed in accordance with ANSI C63.26:2015, FCC CFR 47 Part 2, FCC KDB 971168 D01 v02r02, KDB 971168 D02 v01, Part 22, Part 24, Part 27.

Specification	Version	Title
ANSI C63.26:2015	11 December 2015	American National Standard for Compliance Testing of Transmitters Used in Licensed Radio Services
FCC CFR 47 Part 2	2019	FREQUENCY ALLOCATIONS AND RADIO TREATY MATTERS; GENERAL RULES AND REGULATIONS
FCC CFR 47 Part 22	2019	PUBLIC MOBILE SERVICES
FCC CFR 47 Part 24	2019	PERSONAL COMMUNICATIONS SERVICES
FCC CFR 47 Part 27	2019	MISCELLANEOUS WIRELESS COMMUNICATIONS SERVICES
KDB 971168 D01	v03r01	MEASUREMENT GUIDANCE FOR CERTIFICATION OF LICENSED DIGITAL TRANSMITTERS
KDB 971168 D02	v02r01	MISCELLANEOUS AND BASIC REVIEW AND APPROVAL ITEMS FOR TRANSMITTING EQUIPMENT USED IN LICENSED RADIO SERVICES
ANSI C63.26	2015	American National Standard for Compliance Testing of Transmitters Used in Licensed Radio Services
KDB 971168 D01	April 9, 2018	MEASUREMENT GUIDANCE FOR CERTIFICATION OF LICENSED DIGITAL TRANSMITTERS

4 KEY TO NOTES AND RESULT CODES



The following are the definition of the test result.

Code	Meaning
PASS	Test result shows that the requirements of the relevant specification have been met.
FAIL	Test result shows that the requirements of the relevant specification have not been met.
N/T	Test case is not tested.
NTNV	Nominal voltage, Normal Temperature
HV	High voltage, Normal Temperature
LV	Low voltage, Normal Temperature
HTHV	high voltage, High Temperature
LTHV	High voltage, Low Temperature
HTLV	Low voltage, High Temperature
LTLV	Low voltage, Low Temperature

5 RESULT SUMMARY

The following table summarizes the test results obtained.

No.	Test case	FCC reference	Verdict
1	RF Power Output	2.1046	Pass
2	Effective Radiated Power and Effective Isotropic Radiated Power	22.913, 24.232, 27.50	Pass
3	Occupied Bandwidth	2.1049	Pass
4	Peak-Average Ratio	22.913, 24.232, 27.50	Pass
5	Emission Bandwidth	2.1049	Pass
6	Spurious Emissions at antenna terminals	2.1051, 22.901, 22.917, 24.238, 27.53	Pass
7	Band Edges Compliance	2.1051, 22.359, 22.917, 24.238, 27.53	Pass
8	Frequency Stability	2.1055, 22.355, 24.235, 27.54	Pass
9	Radiated Spurious Emissions	2.1053, 22.917, 24.238, 27.53	Pass

This Test Report Is Issued by: Mr. Peng Zhen 	Checked by: Mr. Li Bin 
Tested by: Mr. He Dengshun 	Issued date: 20190305

6 TEST RESULT


6.1 RF Power Output

Rule Part(s)
FCC: 2.1046

Ambient condition:

Temperature	Relative humidity	Pressure
23°C	42%	101.9kPa

Test Setup:



Test procedure:

After a radio link has been established between EUT and Tester, the output power of the cell signal of the testing equipment will be decreased until the output power of the EUT reach a maximum value. Then the test data can be read at the tester screen. The loss between RF output port of the EUT and the input port of the tester will be taken into consideration.

Limits	≤30dBm
--------	--------

Test result:

The test results are shown in Appendix A.

6.2 Effective Radiated Power


Rule Part(s)

FCC: 22.913, 24.232, 27.50

Ambient condition:

Temperature	Relative humidity	Pressure
20.8°C	36.5%	100.9kPa

Test setup:



ERP/EIRP LIMIT

This value is EIRP since the measurement is calibrated using an antenna of known gain (2.15dB) and known input power. ERP can be calculated from EIRP by subtracting the gain of the dipole, $ERP = EIRP - 2.15 \text{ (dB)}$.

22.913(a) - The ERP of mobile transmitters and auxiliary test transmitters must not exceed 7Watts.

24.232(c) - Mobile/portable stations are limited to 2 watts e.i.r.p. peak power and the equipment must employ means to limit the power to the minimum necessary for successful communications.

27.50 (c) (10) the following power and antenna height requirements apply to stations transmitting in the 698–746 MHz band, the portable stations (hand-held devices) are limited to 3 watts ERP.

27.50 (b)(10) Portable stations (hand-held devices) transmitting in the 746–757 MHz, 758–763 MHz, 776–793 MHz, and 805–806 MHz bands are limited to 3 watts ERP.

27.50 (d)(4) The following power and antenna height requirements apply to stations transmitting in the 1710–1755 MHz and 2110–2155 MHz bands: Fixed, mobile, and portable (hand-held) stations operating in the 1710–1755 MHz band are limited to 1 watt EIRP

27.50 (h) The following power limits shall apply in the BRS and EBS: (2) Mobile and other user stations. Mobile stations are limited to 2.0 watts EIRP. All user stations are limited to 2.0 watts transmitter output power.

Test result:

The test results are shown in Appendix A.


6.3 Occupied Bandwidth

Rule Part(s)
FCC: 2.1049

Ambient condition:

Temperature	Relative humidity	Pressure
23°C	42%	101.9kPa

Test Setup:



Test procedure:

After a radio link has been established between EUT and Tester, the output power of the cell signal of the testing equipment will be decreased until the output power of the EUT reach a maximum value. The occupied bandwidth is measured using spectrum analyzer. RBW is set to 30kHz on spectrum analyzer. The bandwidth of 99% power can be read on spectrum analyzer.

The measurement will be conducted at three channels (Bottom, middle and top channels of LTE band)

Limits: No specific occupied bandwidth requirements in part 2.1049

Test result:

The test results are shown in Appendix A.


6.4 Emission Bandwidth

Rule Part(s)
FCC: 2.1049

Ambient condition:

Temperature	Relative humidity	Pressure
23℃	42%	101.9kPa

Test Setup:



Test procedure:

After a radio link has been established between EUT and Tester, the output power of the cell signal of the testing equipment will be decreased until the output power of the EUT reach a maximum value. The emission bandwidth is measured using spectrum analyzer. RBW is set to 3 kHz on spectrum analyzer. The bandwidth of -26dB transmitter power can be read on spectrum analyzer.

Limits: No specific emission bandwidth requirements in part 22.917(b)

Test result:
The test results are shown in Appendix A.

6.5 Peak-Average Ratio


Rule Part(s)

FCC: 22.913, 24.232, 27.50

Ambient condition:

Temperature	Relative humidity	Pressure
23°C	42%	101.9kPa

Test Setup:



Test procedure:

After a radio link has been established between EUT and Tester, the output power of the cell signal of the testing equipment will be decreased until the output power of the EUT reach a maximum value. The Peak-Average Ratio is measured using spectrum analyzer. RBW is set to 30 kHz on spectrum analyzer. The Peak-Average Ratio can be read on spectrum analyzer.

Limits	≤13dB
--------	-------

Test result:


The test results are shown in Appendix A.

6.6 Spurious Emissions at antenna terminal

Ambient condition:

Temperature	Relative humidity	Pressure
23°C	42%	101.9kPa

Test Setup:



Test procedure:

After a radio link has been established between EUT and Tester, the output power of the cell signal of the testing equipment will be decreased until the output power of the EUT reach a maximum value. The measurement is carried out using a spectrum analyzer. The spectrum analyzer scans from 30MHz to 20GHz (higher than the 10th harmonic of the carrier). The peak detector is used and RBW is set to 1MHz on spectrum analyzer.

Limits	≤-13dBm
--------	---------

Test result:

The test results are shown in Appendix A.

6.7 Band Edges Compliance


Rule Part(s)

FCC: 2.1051, 22.359, 22.917, 24.238, 27.53

Ambient condition:

Temperature	Relative humidity	Pressure
23°C	42%	101.9kPa

Test Setup:



Test procedure:

After a radio link has been established between EUT and Tester, the output power of the cell signal of the testing equipment will be decreased until the output power of the EUT reach a maximum value. The measurement is carried out using a spectrum analyzer. The peak detector is used and RBW is set to at least 1% of the emission bandwidth on spectrum analyzer.

Limits	$\leq -13\text{dBm}$
--------	----------------------

Test result:

The test results are shown in Appendix A.

6.8 Frequency Stability


Rule Part(s)

FCC: 2.1055, 22.355, 24.235, 27.54

Ambient condition:

Temperature	Relative humidity	Pressure
23°C	42%	101.9kPa

Test setup:



Test Procedure:

A radio link shall be established between EUT and Tester. The tester will sample the transmitter RF output signal and measure its frequency. The temperature inside the climate chamber is varied from -30 to +50°C in 10°C step size, and also the DC power supply voltage to the EUT is varied from LV to HV. The measurement will be conducted at three channels No18100, No18300 and No18500 (Bottom, middle and top channels of LTE band I).

Limits: No specific frequency stability requirements in part 2.1055 and part 22.355.

Test result:

The test results are shown in Appendix A.

6.9 Radiated Spurious Emissions


Rule Part(s)

FCC: 2.1053, 22.917, 24.238, 27.53

Ambient condition:

Temperature	Relative humidity	Pressure
20.8°C	36.5%	100.9kPa

Test Setup:



Test procedure:

The measurements procedures in TIA-603C-2004 are used.

The spectrum was scanned from 30MHz to the 10th harmonic of the highest frequency generated within the equipment.

Step 1:

The measurement is carried out in the fully anechoic chamber. EUT was placed on a 2.4 meter high non-conductive table at a 3 meter test distance from the test receive antenna. A receiving antenna was placed on the antenna mast 3 meters from the EUT. The height of receiving antenna is 2.4m and varies in certain range to find the maximum power value. A radio link shall be established between EUT and Tester. The output power of the cell signal of the tester will be decreased until the output power of the EUT reach a maximum value. The measurement is carried out using a spectrum analyzer or receiver. The spectrum analyzer scans from 30MHz to 20GHz (higher than the 10th harmonic of the carrier). The peak detector is used and RBW is set to 1MHz on spectrum analyzer. Then the antenna height and turn table rotation is adjusted till the maximum power value is founded on spectrum analyzer or receiver. A notch filter is necessary in the band near to the carrier frequency. A high pass filter is needed to avoid the distortion of the testing equipment in the band above the carrier frequency.

Step 2:

A log-periodic antenna or double-ridged waveguide horn antenna shall be substituted in place of the EUT. The log-periodic antenna will be driven by a signal generator and the level will be adjusted till the same power value on the spectrum analyzer or receiver. The level of the spurious emissions can be calculated through the level of the signal generator, cable loss, the gain of the substitution antenna and the reading of the spectrum analyzer or receiver.

A power (P_{mea}) is applied to the input of the substitution antenna, and adjusts the level of the signal generator output until the value of the receiver reach the previously recorded (P_r). The power of signal source (P_{mea}) is recorded. The test should be performed by rotating the test item and adjusting the receiving antenna polarization.

A "reference path loss" should be calculated after test. The attenuation of "reference path loss" is the cable loss between the Signal Source with the Substitution Antenna (P_{ca}) and the Substitution Antenna Gain (G_a).

Calculation procedure:

The data of cable loss and antenna gain has been calibrated in full testing frequency range before the testing.

The power of the Radiated Spurious Emissions is calculated by adding the cable loss and antenna gain. The basic equation with a sample calculation is as followed:

$$\text{Power(EIRP)} = P_{mea} + P_{ca} + G_a$$

This value is EIRP since the measurement is calibrated using an antenna of known gain (2.15dB) and known input power. ERP can be calculated from EIRP by subtracting the gain of the dipole, $ERP = EIRP - 2.15 \text{ (dB)}$.

Assumed the power of signal source record is -20dBm. A cable loss of -30dB, and an antenna gain of 11dB are added.

$$P = P_{mea} + P_{ca} + G_a = (-20\text{dBm}) + (-30\text{dB}) + (11\text{dB}) = -39\text{dBm}$$

Test result:

The test results are shown in Appendix B.

7 MEASUREMENT UNCERTAINTIES

Items	Uncertainty	
RF Power Output	0.6 dB	
Occupied Bandwidth	3 kHz	
Spurious Emissions	30MHz~1GHz	2.83 dB
	1GHz~12.75GHz	2.50 dB
	12.75GHz~25GHz	2.75 dB
Band Edges Compliance	1.2dB	
Frequency Stability	4 Hz	

8 TEST EQUIPMENTS

No.	Name/Model	Manufacturer	S/N	Calibration Date	Calibration Due Date
1	MT8820C Mobile Station Tester	Anritsu	6201300660	2018.8.20	2019.8.19
2	FSV40 Spectrum Analyzer	R&S	101065	2018.8.20	2019.8.19
2	N9020A Spectrum Analyzer	Agilent	MY48010771	2018.08.20	2019.08.19
3	6007 Power Divider	Weinschel	6007-GJ-1	2018.08.20	2019.08.19
4	DC Power Supply E3645A	Agilent	MY40000741	2018.3.01	2019.2.28
5	Temperature chamber SH241	ESPEC	92013758	2018.8.20	2019.8.19
6	12.65m×8.03m×7.50m Fully-Anechoic Chamber	FRANKONIA	-----	-----	-----
7	23.18m×16.88m×9.60m Semi-Anechoic Chamber	FRANKONIA	---	-----	-----
8	Turn table Diameter:1m	FRANKONIA	-----	-----	-----
9	Turn table Diameter:5m	FRANKONIA	-----	-----	-----
10	Antenna master FAC(MA4.0)	MATURO	-----	-----	-----
11	Antenna master SAC(MA4.0)	MATURO	-----	-----	-----
12	9.080m×5.255m×3.525m Shielding room	FRANKONIA	-----	-----	-----
13	HF 907 Double-Ridged Waveguide Horn Antenna	R&S	100512	2018.08.20	2019.08.19
14	HF 907 Double-Ridged Waveguide Horn Antenna	R&S	100513	2018.08.20	2019.08.19
15	HL562 Ultra log antenna	R&S	100016	2018.08.20	2019.08.19
16	3160-09 Receive antenna	SCHWARZ-BECK	002058-002	2018.08.20	2019.08.19
17	ESI 40 EMI test receiver	R&S	100015	2018.08.20	2019.08.19
18	ESCS30 EMI test receiver	R&S	100029	2018.08.20	2019.08.19
19	HL562 Receive antenna	R&S	100167	2018.08.20	2019.08.19
20	ENV216 AMN	R&S	3560.6550.12	2018.08.20	2019.08.19

APPENDIX A – TEST DATA OF CONDUCTED EMISSION

Please refer to the attachment.

APPENDIX B – TEST DATA OF RADIATED EMISSION

Please refer to the attachment.