

FCC RF Test Report


APPLICANT : ZTE CORPORATION
EQUIPMENT : HSPA+ uFi
BRAND NAME : ZTE
MODEL NAME : R206-Z
FCC ID : SRQR206-Z
STANDARD : FCC 47 CFR Part 2, 22(H), 24(E)
CLASSIFICATION : PCS Licensed Transmitter (PCB)

The product was received on Jun. 14, 2013 and completely tested on Jun. 21, 2013. We, SPORTON INTERNATIONAL (KUNSHAN) INC., would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI / TIA / EIA-603-C-2004 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL (KUNSHAN) INC., the test report shall not be reproduced except in full.



Reviewed by: Joseph Lin / Supervisor



Approved by: Jones Tsai / Manager



SPORTON INTERNATIONAL (KUNSHAN) INC.
No. 3-2, PingXiang Road, Kunshan, Jiangsu Province, P.R.C.

TABLE OF CONTENTS

REVISION HISTORY.....	3
SUMMARY OF TEST RESULT	4
1 GENERAL DESCRIPTION	5
1.1 Applicant.....	5
1.2 Manufacturer	5
1.3 Feature of Equipment Under Test.....	5
1.4 Product Specification of Equipment Under Test	5
1.5 Modification of EUT	5
1.6 Maximum ERP/EIRP Power, Frequency Tolerance, and Emission Designator	6
1.7 Testing Site	6
1.8 Applied Standards.....	6
2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST	7
2.1 Test Mode.....	7
2.2 Connection Diagram of Test System	8
2.3 Support Unit used in test configuration and system.....	8
2.4 Measurement Results Explanation Example	8
3 TEST RESULT.....	9
3.1 Conducted Output Power Measurement.....	9
3.2 Peak-to-Average Ratio	11
3.3 Effective Radiated Power and Effective Isotropic Radiated Power Measurement	17
3.4 99% Occupied Bandwidth and 26dB Bandwidth Measurement.....	21
3.5 Band Edge Measurement.....	35
3.6 Conducted Spurious Emission Measurement.....	44
3.7 Field Strength of Spurious Radiation Measurement	55
3.8 Frequency Stability Measurement.....	65
4 LIST OF MEASURING EQUIPMENT	69
5 UNCERTAINTY OF EVALUATION	70
APPENDIX A. PHOTOGRAPHS OF EUT	
APPENDIX B. SETUP PHOTOGRAPHS	

REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FG361407	Rev. 01	Initial issue of report	Jul. 03, 2013

SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	§2.1046	Conducted Output Power	N/A	PASS	-
3.2	§24.232(d)	Peak-to-Average Ratio	< 13 dB	PASS	-
3.3	§22.913(a)(2)	Effective Radiated Power	< 7 Watts	PASS	-
3.3	§24.232(c)	Equivalent Isotropic Radiated Power	< 2 Watts	PASS	-
3.4	§2.1049 §22.917(a) §24.238(b)	99% Occupied Bandwidth and 26dB Bandwidth	N/A	PASS	-
3.5	§2.1051 §22.917(a) §24.238(a)	Band Edge Measurement	$< 43 + 10\log_{10}(P[\text{Watts}])$	PASS	-
3.6	§2.1051 §22.917(a) §24.238(a)	Conducted Spurious Emission	$< 43 + 10\log_{10}(P[\text{Watts}])$	PASS	-
3.7	§2.1053 §22.917(a) §24.238(a)	Field Strength of Spurious Radiation	$< 43 + 10\log_{10}(P[\text{Watts}])$	PASS	Under limit 23.63 dB at 1674.000 MHz
3.8	§2.1055 §22.355 §24.235	Frequency Stability for Temperature & Voltage	< 2.5 ppm	PASS	-

1 General Description

1.1 Applicant

ZTE CORPORATION

ZTE Plaza, Keji Road South, Hi-Tech Industrial Park, Nanshan District, Shenzhen, Guangdong, 518057, P.R.China

1.2 Manufacturer

ZTE CORPORATION

ZTE Plaza, Keji Road South, Hi-Tech Industrial Park, Nanshan District, Shenzhen, Guangdong, 518057, P.R.China

1.3 Feature of Equipment Under Test

Product Feature	
Equipment	HSPA+ uFi
Brand Name	ZTE
Model Name	R206-Z
FCC ID	SRQR206-Z
EUT supports Radios application	GPRS/EGPRS/WLAN 11bgn
HW Version	T01
SW Version	BD_R206V1.0
EUT Stage	Identical Prototype

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.4 Product Specification of Equipment Under Test

Product Specification subjective to this standard	
Tx Frequency	GSM850: 824.2 MHz ~ 848.8 MHz GSM1900: 1850.2 MHz ~ 1909.8MHz
Rx Frequency	GSM850: 869.2 MHz ~ 893.8 MHz GSM1900: 1930.2 MHz ~ 1989.8 MHz
Maximum Output Power to Antenna	GSM850 : 31.98 dBm GSM1900 : 28.18 dBm
Antenna Type	PCB Antenna
Antenna Gain	GSM850: -0.4 dBi GSM1900: 1.4 dBi
Type of Modulation	GPRS: GMSK EDGE: GMSK / 8PSK

1.5 Modification of EUT

No modifications are made to the EUT during all test items.

1.6 Maximum ERP/EIRP Power, Frequency Tolerance, and Emission Designator

FCC Rule	System	Type of Modulation	Maximum ERP/EIRP (W)	Frequency Tolerance (% , Hz, ppm)	Emission Designator
Part 22	GSM850 GPRS class 8	GMSK	0.8017	0.03 ppm	242KGXW
Part 22	GSM850 EDGE class 8	8PSK	0.2825	0.03 ppm	248KG7W
Part 24	GSM1900 GPRS class 8	GMSK	0.5970	0.02 ppm	246KGXW
Part 24	GSM1900 EDGE class 8	8PSK	0.3013	0.02 ppm	248KG7W

1.7 Testing Site

Test Site	SPORTON INTERNATIONAL (KUNSHAN) INC.		
Test Site Location	No. 3-2, PingXiang Road, Kunshan, Jiangsu Province, P.R.C. TEL: +86-0512-5790-0158 FAX: +86-0512-5790-0958		
Test Site No.	Sporton Site No.		FCC/IC Registration No.
	TH01-KS	03CH01-KS	149928/4086E-1

1.8 Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC 47 CFR Part 2, 22(H), 24(E)
- ♦ ANSI / TIA / EIA-603-C-2004
- ♦ FCC KDB 971168 D01 Power Meas. License Digital Systems v02

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2 Test Configuration of Equipment Under Test

2.1 Test Mode

During all testing, EUT is in link mode with base station emulator at maximum power level. The spurious emission measurements were carried out in semi-anechoic chamber with 3-meter test range, and EUT is rotated on three test planes to find out the worst emission (X plane for 22H and X plane for 24E).

Frequency range investigated for radiated emission is as follows:

1. 30 MHz to 9000 MHz for GSM850.
2. 30 MHz to 19000 MHz for GSM1900.

Test Modes		
Band	Radiated TCs	Conducted TCs
GSM 850	■ GPRS class 8 Link	■ GPRS class 8 Link
	■ EDGE class 8 Link	■ EDGE class 8 Link
GSM 1900	■ GPRS class 8 Link	■ GPRS class 8 Link
	■ EDGE class 8 Link	■ EDGE class 8 Link


Note:

1. The maximum power levels are GPRS multi-slot class 8 mode for GMSK link, EDGE multi-slot class 8 mode for 8PSK link, only these modes were used for all tests.
2. Because there are individual antennas for each WWAN and WLAN, the co-location test modes are not required.

The conducted power tables are as follows:

Conducted Power (*Unit: dBm)						
Band	GSM850			GSM1900		
Channel	128	189	251	512	661	810
Frequency	824.2	836.4	848.8	1850.2	1880.0	1909.8
GPRS class 8	31.76	31.92	31.98	28.18	28.08	28.00
GPRS class 10	28.83	28.97	29.03	26.17	26.11	26.03
EGPRS class 8	26.87	26.99	27.03	25.23	25.16	25.07
EGPRS class 10	24.36	24.48	24.52	22.72	22.66	22.58
EGPRS class 11	22.39	22.50	22.51	20.84	20.78	20.70
EGPRS class 12	21.23	21.34	21.35	19.67	19.55	19.53

2.2 Connection Diagram of Test System



2.3 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model No.	FCC ID	Data Cable	Power Cord
1.	System Simulator	R&S	CMU 200	N/A	N/A	Unshielded, 1.8 m
2.	DC Power Supply	GWINSTEK	GPS-3030D	N/A	N/A	Unshielded, 1.8 m

2.4 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 4.2 dB and 10dB attenuator.

Example :

$$\begin{aligned}
 \text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)} \\
 &= 4.2 + 10 = 14.2 \text{ (dB)}
 \end{aligned}$$

3 Test Result

3.1 Conducted Output Power Measurement

3.1.1 Description of the Conducted Output Power Measurement

A base station simulator was used to establish communication with the EUT. Its parameters were set to transmit the maximum power on the EUT. The measured power in the radio frequency on the transmitter output terminals shall be reported.


3.1.2 Measuring Instruments

See list of measuring instruments of this test report.

3.1.3 Test Procedures

1. The transmitter output port was connected to base station.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set EUT at maximum power through base station.
4. Select lowest, middle, and highest channels for each band and different modulation.
5. Measure the maximum burst average power for GSM and maximum average power for other modulation signal.

3.1.4 Test Setup



3.1.5 Test Result of Conducted Output Power

Cellular Band						
Modes	GSM850 (GPRS class 8)			GSM850 (EDGE class 8)		
Channel	128 (Low)	189 (Mid)	251 (High)	128 (Low)	189 (Mid)	251 (High)
Frequency (MHz)	824.2	836.4	848.8	824.2	836.4	848.8
Conducted Power (dBm)	31.76	31.92	31.98	26.87	26.99	27.03
Conducted Power (Watts)	1.50	1.56	1.58	0.49	0.50	0.50

PCS Band						
Modes	GSM1900 (GPRS class 8)			GSM1900 (EDGE class 8)		
Channel	512 (Low)	661 (Mid)	810 (High)	512 (Low)	661 (Mid)	810 (High)
Frequency (MHz)	1850.2	1880	1909.8	1850.2	1880	1909.8
Conducted Power (dBm)	28.18	28.08	28.00	25.23	25.16	25.07
Conducted Power (Watts)	0.66	0.64	0.63	0.33	0.33	0.32

Note: maximum burst average power for GPRS.

3.2 Peak-to-Average Ratio

3.2.1 Description of the PAR Measurement

The peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.


3.2.2 Measuring Instruments

See list of measuring instruments of this test report.

3.2.3 Test Procedures

1. The EUT was connected to Spectrum Analyzer and System Simulator via power divider.
2. For GSM/EGPRS operating modes:
 - a. Set EUT in maximum power output.
 - b. Set the RBW = 1MHz, VBW = 3MHz, Peak detector in spectrum analyzer for first trace.
 - c. Set the RBW = 1MHz, VBW = 3MHz, RMS detector in spectrum analyzer for second trace.
 - d. The wanted burst signal is triggered by spectrum analyzer, and measured respectively the peak level and Mean level without burst-off time, after system simulator synchronized with the spectrum analyzer.
3. For UMTS operating modes:
 - a. Set the CCDF (Complementary Cumulative Distribution Function) option in spectrum analyzer.
 - b. The highest RF powers were measured and recorded the maximum PAPR level associated with a probability of 0.1 %.
4. Record the deviation as Peak to Average Ratio.

3.2.4 Test Setup




3.2.5 Test Result of Peak-to-Average Ratio

PCS Band						
Modes	GSM1900 (GPRS class 8)			GSM1900 (EDGE class 8)		
Channel	512 (Low)	661 (Mid)	810 (High)	512 (Low)	661 (Mid)	810 (High)
Frequency (MHz)	1850.2	1880	1909.8	1850.2	1880	1909.8
Peak-to-Average Ratio (dB)	0.25	0.25	0.25	2.83	2.89	3.07


3.2.6 Test Result (Plots) of Peak-to-Average Ratio

Band :	GSM 1900	Test Mode :	GPRS class 8 Link (GMSK)
--------	----------	-------------	--------------------------

Peak-to-Average Ratio on Channel 512 (1850.2 MHz)




Peak-to-Average Ratio on Channel 661 (1880.0 MHz)






Peak-to-Average Ratio on Channel 810 (1909.8 MHz)




Band :	GSM 1900	Test Mode :	EDGE class 8 Link (8PSK)
--------	----------	-------------	--------------------------

Peak-to-Average Ratio on Channel 512 (1850.2 MHz)




Peak-to-Average Ratio on Channel 661 (1880.0 MHz)





Peak-to-Average Ratio on Channel 810 (1909.8 MHz)



3.3 Effective Radiated Power and Effective Isotropic Radiated Power Measurement

3.3.1 Description of the ERP/EIRP Measurement

The substitution method, in ANSI / TIA / EIA-603-C-2004, was used for ERP/EIRP measurement, and the spectrum analyzer configuration follows KDB 971168 D01 Power Meas. License Digital Systems v02. The ERP of mobile transmitters must not exceed 7 Watts and the EIRP of mobile transmitters are limited to 2 Watts.


3.3.2 Measuring Instruments

See list of measuring instruments of this test report.

3.3.3 Test Procedures

1. The EUT was placed on a turntable with 1.5 meter height in a fully anechoic chamber.
2. The EUT was set at 3 meters from the receiving antenna, which was mounted on the antenna tower.
3. GSM operating modes: Set RBW= 1MHz, VBW= 3MHz, RMS detector over burst;
UMTS operating modes: Set RBW= 100 kHz, VBW= 300 kHz, RMS detector over frame, and use channel power option with bandwidth=5MHz, per KDB 971168 D01.
4. The table was rotated 360 degrees to determine the position of the highest radiated power.
5. The height of the receiving antenna is adjusted to look for the maximum ERP/EIRP.
6. Taking the record of maximum ERP/EIRP.
7. A dipole antenna was substituted in place of the EUT and was driven by a signal generator.
8. The conducted power at the terminal of the dipole antenna is measured.
9. Repeat step 3 to step 5 to get the maximum ERP/EIRP of the substitution antenna.
10. $ERP/EIRP = P_s + E_t - E_s + G_s = P_s + R_t - R_s + G_s$
 P_s (dBm) : Input power to substitution antenna.
 G_s (dBi or dBd) : Substitution antenna Gain.
 $E_t = R_t + AF$
 $E_s = R_s + AF$
 AF (dB/m) : Receive antenna factor
 R_t : The highest received signal in spectrum analyzer for EUT.
 R_s : The highest received signal in spectrum analyzer for substitution antenna.

3.3.4 Test Setup



3.3.5 Test Result of ERP

GSM850 (GPRS class 8) Radiated Power ERP						
Horizontal Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBd)	ERP (dBm)	ERP (W)
824.20	-18.23	-48.12	0.00	-1.08	28.81	0.7603
836.40	-18.48	-48.28	0.00	-0.93	28.87	0.7709
848.80	-18.55	-48.35	0.00	-0.76	29.04	0.8017
Vertical Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBd)	ERP (dBm)	ERP (W)
824.20	-31.86	-47.97	0.00	-1.08	15.03	0.0318
836.40	-31.79	-48.01	0.00	-0.93	15.29	0.0338
848.80	-31.50	-48.05	0.00	-0.76	15.79	0.0379

GSM850 (EDGE class 8) Radiated Power ERP						
Horizontal Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBd)	ERP (dBm)	ERP (W)
824.20	-23.10	-48.12	0.00	-1.08	23.94	0.2477
836.40	-23.33	-48.28	0.00	-0.93	24.02	0.2523
848.80	-23.08	-48.35	0.00	-0.76	24.51	0.2825
Vertical Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBd)	ERP (dBm)	ERP (W)
824.20	-36.74	-47.97	0.00	-1.08	10.15	0.0104
836.40	-36.73	-48.01	0.00	-0.93	10.35	0.0108
848.80	-36.39	-48.05	0.00	-0.76	10.90	0.0123

3.3.6 Test Result of EIRP

GSM1900 (GPRS class 8) Radiated Power EIRP						
Horizontal Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBi)	EIRP (dBm)	EIRP (W)
1850.20	-26.31	-51.88	0.00	1.96	27.53	0.5662
1880.00	-27.28	-52.99	0.00	2.00	27.71	0.5902
1909.80	-28.50	-54.28	0.00	1.98	27.76	0.5970
Vertical Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBi)	EIRP (dBm)	EIRP (W)
1850.20	-28.02	-52.13	0.00	1.96	26.07	0.4046
1880.00	-29.43	-53.17	0.00	2.00	25.74	0.3750
1909.80	-29.98	-54.13	0.00	1.98	26.13	0.4102

GSM1900 (EDGE class 8) Radiated Power EIRP						
Horizontal Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBi)	EIRP (dBm)	EIRP (W)
1850.20	-29.30	-51.88	0.00	1.96	24.54	0.2844
1880.00	-30.36	-52.99	0.00	2.00	24.63	0.2904
1909.80	-31.47	-54.28	0.00	1.98	24.79	0.3013
Vertical Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBi)	EIRP (dBm)	EIRP (W)
1850.20	-31.10	-52.13	0.00	1.96	22.99	0.1991
1880.00	-32.48	-53.17	0.00	2.00	22.69	0.1858
1909.80	-32.88	-54.13	0.00	1.98	23.23	0.2104

3.4 99% Occupied Bandwidth and 26dB Bandwidth Measurement

3.4.1 Description of 99% Occupied Bandwidth and 26dB Bandwidth Measurement

The 99% occupied bandwidth is the width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean transmitted power.

The emission bandwidth is defined as the width of the signal between two points, located at the 2 sides of the carrier frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.


3.4.2 Measuring Instruments

See list of measuring instruments of this test report.

3.4.3 Test Procedures

1. The EUT was connected to Spectrum Analyzer and Base Station via power divider.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. The 99% occupied bandwidth were measured, set RBW= 1% of span, VBW= 3*RBW, sample detector, trace maximum hold.
4. The 26dB bandwidth were measured, set RBW= 1% of EBW, VBW= 3*RBW, peak detector, trace maximum hold.

3.4.4 Test Setup



3.4.5 Test Result of Occupied Bandwidth and 26dB Bandwidth


Cellular Band						
Modes	GSM850 (GPRS class 8)			GSM850 (EDGE class 8)		
Channel	128 (Low)	189 (Mid)	251 (High)	128 (Low)	189 (Mid)	251 (High)
Frequency (MHz)	824.2	836.4	848.8	824.2	836.4	848.8
99% OBW (kHz)	240.00	240.00	242.00	246.00	236.00	248.00
26dB BW (kHz)	302.00	302.00	302.00	300.00	298.00	304.00

PCS Band						
Modes	GSM1900 (GPRS class 8)			GSM1900 (EDGE class 8)		
Channel	512 (Low)	661 (Mid)	810 (High)	512 (Low)	661 (Mid)	810 (High)
Frequency (MHz)	1850.2	1880	1909.8	1850.2	1880	1909.8
99% OBW (kHz)	246.00	246.00	244.00	242.00	248.00	242.00
26dB BW (kHz)	302.00	302.00	300.00	316.00	304.00	302.00

3.4.6 Test Result (Plots) of Occupied Bandwidth and 26dB Bandwidth


Band :	GSM 850	Test Mode :	GPRS class 8 Link (GMSK)
--------	---------	-------------	--------------------------

99% Occupied Bandwidth Plot on Channel 128 (824.2 MHz)




Date: 14.JUN.2013 15:41:25

26dB Bandwidth Plot on Channel 128 (824.2 MHz)




Date: 14.JUN.2013 15:40:06

99% Occupied Bandwidth Plot on Channel 189 (836.4 MHz)




Date: 14.JUN.2013 15:41:51

26dB Bandwidth Plot on Channel 189 (836.4 MHz)




Date: 14.JUN.2013 15:40:33

99% Occupied Bandwidth Plot on Channel 251 (848.8 MHz)



Date: 14.JUN.2013 16:09:27

26dB Bandwidth Plot on Channel 251 (848.8 MHz)




Date: 14.JUN.2013 15:40:59




Band :	GSM 850	Test Mode :	EDGE class 8 Link (8PSK)
--------	---------	-------------	--------------------------

99% Occupied Bandwidth Plot on Channel 128 (824.2 MHz)




Date: 14.JUN.2013 18:28:43


26dB Bandwidth Plot on Channel 128 (824.2 MHz)



Date: 14.JUN.2013 18:04:21


99% Occupied Bandwidth Plot on Channel 189 (836.4 MHz)


Date: 14.JUN.2013 18:29:08

26dB Bandwidth Plot on Channel 189 (836.4 MHz)



Date: 14.JUN.2013 18:18:11

99% Occupied Bandwidth Plot on Channel 251 (848.8 MHz)



Date: 14.JUN.2013 19:16:42


26dB Bandwidth Plot on Channel 251 (848.8 MHz)



Date: 14.JUN.2013 19:21:11


Band :	GSM 1900	Test Mode :	GPRS class 8 Link (GMSK)
--------	----------	-------------	--------------------------

99% Occupied Bandwidth Plot on Channel 512 (1850.2 MHz)




Date: 14.JUN.2013 16:15:52

26dB Bandwidth Plot on Channel 512 (1850.2 MHz)




Date: 14.JUN.2013 16:14:33

99% Occupied Bandwidth Plot on Channel 661 (1880.0 MHz)




Date: 14.JUN.2013 16:53:15


26dB Bandwidth Plot on Channel 661 (1880.0 MHz)



Date: 14.JUN.2013 16:14:59

99% Occupied Bandwidth Plot on Channel 810 (1909.8 MHz)


Date: 14.JUN.2013 16:16:44


26dB Bandwidth Plot on Channel 810 (1909.8 MHz)


Date: 14.JUN.2013 16:15:26




Band :	GSM 1900	Test Mode :	EDGE class 8 Link (8PSK)
--------	----------	-------------	--------------------------

99% Occupied Bandwidth Plot on Channel 512 (1850.2 MHz)




Date: 14.JUN.2013 19:57:29

26dB Bandwidth Plot on Channel 512 (1850.2 MHz)




Date: 14.JUN.2013 19:56:11

99% Occupied Bandwidth Plot on Channel 661 (1880.0 MHz)




Date: 14.JUN.2013 19:57:54


26dB Bandwidth Plot on Channel 661 (1880.0 MHz)



Date: 14.JUN.2013 20:23:07

99% Occupied Bandwidth Plot on Channel 810 (1909.8 MHz)


Date: 14.JUN.2013 20:24:51

26dB Bandwidth Plot on Channel 810 (1909.8 MHz)


Date: 14.JUN.2013 19:57:02

3.5 Band Edge Measurement

3.5.1 Description of Band Edge Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.


3.5.2 Measuring Instruments

See list of measuring instruments of this test report.

3.5.3 Test Procedures

1. The EUT was connected to Spectrum Analyzer and Base Station via power divider.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. The band edges of low and high channels for the highest RF powers were measured. Setting RBW as roughly BW/100.
4. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
5. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)
 $= P(W) - [43 + 10\log(P)] \text{ (dB)}$
 $= [30 + 10\log(P)] \text{ (dBm)} - [43 + 10\log(P)] \text{ (dB)}$
 $= -13\text{dBm}.$


3.5.4 Test Setup



3.5.5 Test Result (Plots) of Conducted Band Edge

Band :	GSM850	Test Mode :	GPRS class 8 Link (GMSK)
Correction Factor :	0.03dB	Maximum 26dB Bandwidth :	0.302MHz
Band Edge :	-17.36dBm	Measurement Value :	-17.39dBm


Lower Band Edge Plot on Channel 128 (824.2 MHz)



Date: 14.JUN.2013 15:43:44

1. Correction Factor(dB)= $10\log(1\% \text{ Emission BW/RBW})$
 2. Band Edge= Measurement Value + Correction Factor(dB)
- For example, $-17.39\text{dBm} + 0.03\text{dB} = -17.36\text{dBm}$


Band :	GSM850	Test Mode :	GPRS class 8 Link (GMSK)
Correction Factor :	0.03dB	Maximum 26dB Bandwidth :	0.302MHz
Band Edge :	-17.56dBm	Measurement Value :	-17.59dBm

Higher Band Edge Plot on Channel 251 (848.8 MHz)


Date: 14.JUN.2013 15:44:10

1. Correction Factor(dB)= $10\log(1\% \text{ Emission BW/RBW})$
2. Band Edge= Measurement Value + Correction Factor(dB)

Band :	GSM850	Test Mode :	EDGE class 8 Link (8PSK)
Correction Factor :	0.06dB	Maximum 26dB Bandwidth :	0.304MHz
Band Edge :	-25.56dBm	Measurement Value :	-25.62dBm

Lower Band Edge Plot on Channel 128 (824.2 MHz)


Date: 14.JUN.2013 18:07:55

1. Correction Factor(dB)= 10log(1% Emission BW/RBW)
2. Band Edge= Measurement Value + Correction Factor(dB)


Band :	GSM850	Test Mode :	EDGE class 8 Link (8PSK)
Correction Factor :	0.06dB	Maximum 26dB Bandwidth :	0.304MHz
Band Edge :	-19.50dBm	Measurement Value :	-19.56dBm

Higher Band Edge Plot on Channel 251 (848.8 MHz)


Date: 14.JUN.2013 18:08:21

1. Correction Factor(dB)= $10\log(1\% \text{ Emission BW/RBW})$
2. Band Edge= Measurement Value + Correction Factor(dB)


Band :	GSM1900	Test Mode :	GPRS class 8 Link (GMSK)
Correction Factor :	0.03dB	Maximum 26dB Bandwidth :	0.302MHz
Band Edge :	-22.92dBm	Measurement Value :	-22.95dBm

Lower Band Edge Plot on Channel 512 (1850.2 MHz)


Date: 14.JUN.2013 16:18:10

1. Correction Factor(dB)= 10log(1% Emission BW/RBW)
2. Band Edge= Measurement Value + Correction Factor(dB)


Band :	GSM1900	Test Mode :	GPRS class 8 Link (GMSK)
Correction Factor :	0.03dB	Maximum 26dB Bandwidth :	0.302MHz
Band Edge :	-22.15dBm	Measurement Value :	-22.18dBm

Higher Band Edge Plot on Channel 810 (1909.8 MHz)


Date: 14.JUN.2013 16:18:36

1. Correction Factor(dB)= 10log(1% Emission BW/RBW)
2. Band Edge= Measurement Value + Correction Factor(dB)


Band :	GSM1900	Test Mode :	EDGE class 8 Link (8PSK)
Correction Factor :	0.23dB	Maximum 26dB Bandwidth :	0.316MHz
Band Edge :	-26.03dBm	Measurement Value :	-26.26dBm

Lower Band Edge Plot on Channel 512 (1850.2 MHz)


Date: 14.JUN.2013 20:31:55

1. Correction Factor(dB)= 10log(1% Emission BW/RBW)
2. Band Edge= Measurement Value + Correction Factor(dB)

Band :	GSM1900	Test Mode :	EDGE class 8 Link (8PSK)
Correction Factor :	0.23dB	Maximum 26dB Bandwidth :	0.316MHz
Band Edge :	-27.08dBm	Measurement Value :	-27.31dBm

Higher Band Edge Plot on Channel 810 (1909.8 MHz)


Date: 14.JUN.2013 20:32:21

1. Correction Factor(dB)= 10log(1% Emission BW/RBW)
2. Band Edge= Measurement Value + Correction Factor(dB)

3.6 Conducted Spurious Emission Measurement

3.6.1 Description of Conducted Spurious Emission Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.

It is measured by means of a calibrated spectrum analyzer and scanned from 30 MHz up to a frequency including its 10th harmonic.

3.6.2 Measuring Instruments

See list of measuring instruments of this test report.

3.6.3 Test Procedures


1. The EUT was connected to spectrum analyzer and base station via power divider.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. The middle channel for the highest RF power within the transmitting frequency was measured.
4. The conducted spurious emission for the whole frequency range was taken.
5. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
6. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)

$$= P(W) - [43 + 10\log(P)] \text{ (dB)}$$

$$= [30 + 10\log(P)] \text{ (dBm)} - [43 + 10\log(P)] \text{ (dB)}$$


$$= -13\text{dBm}$$

3.6.4 Test Setup




3.6.5 Test Result (Plots) of Conducted Spurious Emission

Band :	GSM850	Channel :	CH189
Test Mode :	GPRS class 8 Link (GMSK)	Frequency :	836.4 MHz


Conducted Spurious Emission Plot between 30MHz ~ 1GHz


Date: 14.JUN.2013 15:52:38

Conducted Spurious Emission Plot between 1GHz ~ 3GHz



Date: 14.JUN.2013 15:56:22

Conducted Spurious Emission Plot between 3GHz ~ 7GHz



Date: 14.JUN.2013 16:05:23

Conducted Spurious Emission Plot between 7GHz ~ 9GHz




Date: 14.JUN.2013 16:03:21




Band :	GSM850	Channel :	CH189
Test Mode :	EDGE class 8 Link (8PSK)	Frequency :	836.4 MHz

Conducted Spurious Emission Plot between 30MHz ~ 1GHz




Date: 14.JUN.2013 19:24:17

Conducted Spurious Emission Plot between 1GHz ~ 3GHz




Date: 14.JUN.2013 19:25:29

Conducted Spurious Emission Plot between 3GHz ~ 7GHz




Date: 14.JUN.2013 19:26:11

Conducted Spurious Emission Plot between 7GHz ~ 9GHz




Date: 14.JUN.2013 19:26:43

Band :	GSM1900	Channel :	CH661
Test Mode :	GPRS class 8 Link (GMSK)	Frequency :	1880.0 MHz


Conducted Spurious Emission Plot between 30MHz ~ 1GHz


Date: 14.JUN.2013 16:47:28

Conducted Spurious Emission Plot between 1GHz ~ 3GHz



Date: 14.JUN.2013 16:31:22

Conducted Spurious Emission Plot between 3GHz ~ 7GHz




Date: 14.JUN.2013 16:35:48

Conducted Emission Plot between 7GHz ~ 13.6GHz



Date: 21.JUN.2013 10:02:35

Conducted Spurious Emission Plot between 13.6GHz ~ 19.1GHz




Date: 14.JUN.2013 16:41:33




Band :	GSM1900	Channel :	CH661
Test Mode :	EDGE class 8 Link (8PSK)	Frequency :	1880.0 MHz

Conducted Spurious Emission Plot between 30MHz ~ 1GHz




Date: 14.JUN.2013 20:42:28

Conducted Spurious Emission Plot between 1GHz ~ 3GHz




Date: 14.JUN.2013 20:43:25

Conducted Spurious Emission Plot between 3GHz ~ 7GHz




Date: 21.JUN.2013 10:16:42

Conducted Spurious Emission Plot between 7GHz ~ 13.6GHz



Date: 14.JUN.2013 20:50:31

Conducted Spurious Emission Plot between 13.6GHz ~ 19.1GHz



Date: 14.JUN.2013 20:51:04

3.7 Field Strength of Spurious Radiation Measurement

3.7.1 Description of Field Strength of Spurious Radiated Measurement

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB. The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

3.7.2 Measuring Instruments


See list of measuring instruments of this test report.

3.7.3 Test Procedures


1. The EUT was placed on a rotatable wooden table with 0.8 meter above ground.
2. The EUT was set 3 meters from the receiving antenna, which was mounted on the antenna tower.
3. The table was rotated 360 degrees to determine the position of the highest spurious emission.
4. The height of the receiving antenna is varied between one meter and four meters to search the maximum spurious emission for both horizontal and vertical polarizations.
5. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking the record of maximum spurious emission.
6. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
7. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
8. Taking the record of output power at antenna port.
9. Repeat step 7 to step 8 for another polarization.
10. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
11. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)
 $= P(W) - [43 + 10\log(P)] \text{ (dB)}$
 $= [30 + 10\log(P)] \text{ (dBm)} - [43 + 10\log(P)] \text{ (dB)}$
 $= -13\text{dBm}.$
12. $\text{EIRP (dBm)} = \text{S.G. Power} - \text{Tx Cable Loss} + \text{Tx Antenna Gain}$
13. $\text{ERP (dBm)} = \text{EIRP} - 2.15$

3.7.4 Test Setup

For radiated emissions from 30MHz to 1GHz




For radiated emissions above 1GHz



3.7.5 Test Result of Field Strength of Spurious Radiated


Band :	GSM850	Temperature :	23~24°C
Test Mode :	GPRS class 8 Link (GMSK)	Relative Humidity :	43~44%
Test Engineer :	Stone Gu	Polarization :	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Site : 03CH01-KS
Condition : FCC PART22 24 : HF EIRP FACTOR HORIZONTAL
EUT : (FG)361407

Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1674	-36.63	-13	-23.63	-41.22	-36.99	0.86	3.37	H	Pass
2510	-45.95	-13	-32.95	-53.01	-47.81	1.15	5.16	H	Pass
3346	-55.83	-13	-42.83	-62.47	-59.28	1.06	6.66	H	Pass


Band :	GSM850	Temperature :	23~24°C
Test Mode :	GPRS class 8 Link (GMSK)	Relative Humidity :	43~44%
Test Engineer :	Stone Gu	Polarization :	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Site : 03CH01-KS
 Condition : FCC PART22 24 : HF EIRP FACTOR VERTICAL
 EUT : (FG)361407

Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1674	-41.70	-13	-28.70	-48.68	-42.06	0.86	3.37	V	Pass
2510	-46.87	-13	-33.87	-56.27	-48.73	1.15	5.16	V	Pass
3346	-56.40	-13	-43.40	-64.85	-59.85	1.06	6.66	V	Pass


Band :	GSM850	Temperature :	23~24°C
Test Mode :	EDGE class 8 Link (8PSK)	Relative Humidity :	43~44%
Test Engineer :	Stone Gu	Polarization :	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Site : 03CH01-KS
 Condition : FCC PART22 24 : HF EIRP FACTOR HORIZONTAL
 EUT : (FG)361407

Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1674	-44.90	-13	-31.90	-48.26	-45.26	0.86	3.37	H	Pass
2510	-55.46	-13	-42.46	-61.17	-57.32	1.15	5.16	H	Pass
3346	-56.69	-13	-43.69	-63.33	-60.14	1.06	6.66	H	Pass


Band :	GSM850	Temperature :	23~24°C
Test Mode :	EDGE class 8 Link (8PSK)	Relative Humidity :	43~44%
Test Engineer :	Stone Gu	Polarization :	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Site : 03CH01-KS
Condition : FCC PART22 24 : HF EIRP FACTOR VERTICAL
EUT : (FG)361407

Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1674	-48.65	-13	-35.65	-54.00	-49.01	0.86	3.37	V	Pass
2510	-53.55	-13	-40.55	-61.74	-55.41	1.15	5.16	V	Pass
3344	-56.61	-13	-43.61	-65.06	-60.06	1.06	6.66	V	Pass


Band :	GSM1900	Temperature :	23~24°C
Test Mode :	GPRS class 8 Link (GMSK)	Relative Humidity :	43~44%
Test Engineer :	Stone Gu	Polarization :	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Site : 03CH01-KS
 Condition : FCC PART22 24 : HF EIRP FACTOR HORIZONTAL
 EUT : (FG)361407

Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3760	-56.03	-13	-43.03	-62.93	-62.23	0.96	7.16	H	Pass
5640	-54.79	-13	-41.79	-63.47	-63.30	1.07	9.58	H	Pass
7520	-49.22	-13	-36.22	-64.32	-59.22	1.46	11.46	H	Pass


Band :	GSM1900	Temperature :	23~24°C
Test Mode :	GPRS class 8 Link (GMSK)	Relative Humidity :	43~44%
Test Engineer :	Stone Gu	Polarization :	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Site : 03CH01-KS
Condition : FCC PART22 24 : HF EIRP FACTOR VERTICAL
EUT : (FG)361407

Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3760	-54.90	-13	-41.90	-62.72	-61.10	0.96	7.16	V	Pass
5640	-54.40	-13	-41.40	-63.26	-62.91	1.07	9.58	V	Pass
7520	-46.59	-13	-33.59	-63.8	-56.59	1.46	11.46	V	Pass

Band :	GSM1900	Temperature :	23~24°C
Test Mode :	EDGE class 8 Link (8PSK)	Relative Humidity :	43~44%
Test Engineer :	Stone Gu	Polarization :	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH01-KS
 Condition : FCC PART22 24 : HF EIRP FACTOR HORIZONTAL
 EUT : (FG)361407

Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3760	-57.23	-13	-44.23	-64.13	-63.43	0.96	7.16	H	Pass
5640	-55.59	-13	-42.59	-64.27	-64.10	1.07	9.58	H	Pass
7520	-49.24	-13	-36.24	-64.34	-59.24	1.46	11.46	H	Pass



Band :	GSM1900	Temperature :	23~24°C
Test Mode :	EDGE class 8 Link (8PSK)	Relative Humidity :	43~44%
Test Engineer :	Stone Gu	Polarization :	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Site : 03CH01-KS
Condition : FCC PART22 24.1 HF EIRP FACTOR VERTICAL
EUT : (FG)361407

Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3760	-55.43	-13	-42.43	-63.25	-61.63	0.96	7.16	V	Pass
5640	-55.26	-13	-42.26	-64.12	-63.77	1.07	9.58	V	Pass
7520	-46.27	-13	-33.27	-63.48	-56.27	1.46	11.46	V	Pass

3.8 Frequency Stability Measurement

3.8.1 Description of Frequency Stability Measurement

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within $\pm 0.00025\%$ ($\pm 2.5\text{ppm}$) of the center frequency.

3.8.2 Measuring Instruments

See list of measuring instruments of this test report.


3.8.3 Test Procedures for Temperature Variation

1. The EUT was set up in the thermal chamber and connected with the base station.
2. With power OFF, the temperature was decreased to -30°C and the EUT was stabilized before testing. Power was applied and the maximum change in frequency was recorded within one minute.
3. With power OFF, the temperature was raised in 10°C step up to 50°C . The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.
4. If the EUT cannot be turned on at -30°C , the testing lowest temperature will be raised in 10°C step until the EUT can be turned on.

3.8.4 Test Procedures for Voltage Variation

1. The EUT was placed in a temperature chamber at $25\pm 5^{\circ}\text{C}$ and connected with the base station.
2. The power supply voltage to the EUT was varied from BEP to 115% of the nominal value measured at the input to the EUT.
3. The variation in frequency was measured for the worst case.

3.8.5 Test Setup



3.8.6 Test Result of Temperature Variation

Band :	GSM 850	Channel :	189
Limit (ppm) :	2.5	Frequency :	836.4 MHz

Temperature (°C)	GPRS class 8		EDGE class 8		Result
	Freq. Dev. (Hz)	Deviation (ppm)	Freq. Dev. (Hz)	Deviation (ppm)	
-30	12	+0.01	26	+0.03	PASS
-20	7	+0.01	23	+0.03	
-10	8	+0.01	20	+0.02	
0	5	+0.01	19	+0.02	
10	9	+0.01	18	+0.02	
20	13	+0.02	13	+0.02	
30	16	+0.02	16	+0.02	
40	19	+0.02	11	+0.01	
50	22	+0.03	15	+0.02	
55	21	+0.02	10	+0.01	

Note: The manufacturer declared that the EUT could work properly at temperature 55°C.

Band :	GSM 1900	Channel :	661
Limit (ppm) :	2.5	Frequency :	1880.0 MHz

Temperature (°C)	GPRS class 8		EDGE class 8		Result
	Freq. Dev. (Hz)	Deviation (ppm)	Freq. Dev. (Hz)	Deviation (ppm)	
-30	36	+0.02	42	+0.02	PASS
-20	33	+0.02	37	+0.02	
-10	28	+0.01	34	+0.02	
0	22	+0.01	31	+0.02	
10	26	+0.01	30	+0.02	
20	29	+0.02	39	+0.02	
30	25	+0.01	38	+0.02	
40	23	+0.01	36	+0.02	
50	20	+0.01	42	+0.02	
55	-13	-0.01	46	+0.02	

3.8.7 Test Result of Voltage Variation

Band & Channel	Mode	Voltage (Volt)	Freq. Dev. (Hz)	Deviation (ppm)	Limit (ppm)	Result
GSM 850 CH189	GPRS class 8	3.7	6	+0.01	2.5	PASS
		BEP	9	+0.01		
		4.2	13	+0.02		
	EDGE class 8	3.7	16	+0.02		
		BEP	17	+0.02		
		4.2	19	+0.02		
GSM 1900 CH661	GPRS class 8	3.7	37	+0.02		
		BEP	26	+0.01		
		4.2	29	+0.02		
	EDGE class 8	3.7	39	+0.02		
		BEP	40	+0.02		
		4.2	42	+0.02		

Note:

1. Normal Voltage = 3.7V.
2. Battery End Point (BEP) = 3.5 V.

4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSP40	100319	9kHz~40GHz	Dec. 29, 2012	Jun. 14, 2013~ Jun. 21, 2013	Dec. 28, 2013	Conducted (TH01-KS)
Thermal Chamber	Ten Billion	TTC-B3S	TBN-960502	N/A	Dec. 29, 2012	Jun. 14, 2013~ Jun. 21, 2013	Dec. 28, 2013	Conducted (TH01-KS)
EMI Test Receiver	R&S	ESCI	100534	9kHz~3GHz	Nov. 08, 2012	Jun. 19, 2013	Nov. 07, 2013	Radiation (03CH01-KS)
Spectrum Analyzer	R&S	FSP30	100400	9kHz~30GHz	May 23, 2013	Jun. 19, 2013	May 22, 2014	Radiation (03CH01-KS)
Bilog Antenna	SCHAFFNER	CBL6112D	23182	25MHz~2GHz	Dec. 07, 2012	Jun. 19, 2013	Dec. 06, 2013	Radiation (03CH01-KS)
Double Ridge Horn Antenna	EMCO	3117	00075959	1GHz~18GHz	Jan. 06, 2013	Jun. 19, 2013	Jan. 05, 2014	Radiation (03CH01-KS)
Amplifier	com-power	PA-103A	161069	1MHz~1GHz	May 23, 2013	Jun. 19, 2013	May 22, 2014	Radiation (03CH01-KS)
Amplifier	Agilent	8449B	3008A02370	1GHz~26.5GHz	Dec. 29, 2012	Jun. 19, 2013	Dec. 28, 2013	Radiation (03CH01-KS)
SHF-EHF Horn	Schwarzbeck	BBHA 9170	9170249	15GHz~40GHz	Nov. 23, 2012	Jun. 19, 2013	Nov. 22, 2013	Radiation (03CH01-KS)
Turn Table	MF	MF7802	N/A	0 ~ 360 degree	N/A	Jun. 19, 2013	N/A	Radiation (03CH01-KS)
Antenna Mast	MF	MF7802	N/A	1 m - 4 m	N/A	Jun. 19, 2013	N/A	Radiation (03CH01-KS)

5 Uncertainty of Evaluation

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	2.54
---	------

Uncertainty of Radiated Emission Measurement (1 GHz ~ 40 GHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	4.72
---	------



Appendix A. Photographs of EUT

Please refer to Sporton report number EP361407 as below.