

---

# TEST REPORT

---

Report No.: SRTC2020-9003(F)-0097  
Product Name: WCDMA/LTE Multi-mode Digital Mobile Phone  
Model Name: ZTE 9030  
Applicant: ZTE CORPORATION  
Manufacturer: ZTE CORPORATION  
Specification: FCC Part15B (Certification)  
(2020 edition)  
FCC ID: SRQ-ZTE9030

The State Radio\_monitoring\_center Testing Center (SRTC)  
15th Building, No.30 Shixing Street, Shijingshan District,  
Beijing, China

Tel: 86-10-57996183 Fax: 86-10-57996388

---

## CONTENTS

1. General information .....	3
1.1 Notes of the test report .....	3
1.2 Information about the testing laboratory .....	3
1.3 Applicant's details .....	3
1.4 Manufacturer's details .....	3
1.5 Application details .....	4
1.6 Reference specification .....	4
1.7 Information of EUT .....	4
1.7.1 General information .....	4
1.7.2 EUT details .....	5
1.7.3 Auxiliary equipment details .....	5
2. Test information .....	7
2.1 Summary of the test results .....	7
2.2 Test result .....	8
2.2.1 Conducted Emissions-FCC Part15.107 .....	8
2.2.2 Radiated Emissions-FCC Part15.109 .....	14
2.3. List of test equipments .....	23

## 1. General information

### 1.1 Notes of the test report

The test report may only be reproduced or published in full. Reproduction or publication of extracts from the report requires the prior written permission of The State Radio\_monitoring\_center Testing Center (SRTC).

The test results relate only to individual items of the samples which have been tested.

### 1.2 Information about the testing laboratory

Company: The State Radio\_monitoring\_center Testing Center (SRTC)  
Address: 15th Building, No.30 Shixing Street, Shijingshan District  
Testing location: No.80, Zhaojiachang, BeizangCun, Daxing District, Beijing, China.  
City: Beijing  
Country or Region: China  
Contacted person: Liu Jia  
Tel: +86 10 57996183  
Fax: +86 10 57996388  
Email: liujiaf@srtc.org.cn

### 1.3 Applicant's details

Company: ZTE CORPORATION  
Address: ZTE Plaza, #55 Keji Road South, Hi-Tech, Industrial Park, Nanshan District,Guangdong, China.  
City: Shenzhen  
Country or Region: China  
Contacted person: Gong Yu  
Tel: 86-21-68895397  
Email: gongyu@zte.com.cn

### 1.4 Manufacturer's details

Company: ZTE CORPORATION  
Address: ZTE Plaza, #55 Keji Road South, Hi-Tech, Industrial Park, Nanshan District,Guangdong,China.  
City: Shenzhen  
Country or Region: China  
Contacted person: Gong Yu  
Tel: 86-21-68895397  
Email: gongyu@zte.com.cn

## 1.5 Application details

Date of reception of test sample: 11<sup>th</sup> Mar. 2021

Date of test: 11<sup>th</sup> Mar. 2021 to 31<sup>th</sup> Mar. 2021

## 1.6 Reference specification

FCC Part 15B, 2020 (Certification)

## 1.7 Information of EUT

### 1.7.1 General information

Name of EUT	WCDMA/LTE Multi-mode Digital Mobile Phone
Model Name	ZTE 9030
FCC ID	SRQ-ZTE9030
Frequency Range	GSM: GSM850/PCS1900 WCDMA: FDD II / FDD IV / FDD V LTE:FDD 2/ FDD 4/ FDD 5/ FDD 7/ FDD 12/ FDD 13 FDD 17/ FDD 26/ TDD 38 / FDD 66 Bluetooth: 2.4~2.4835GHz WiFi: 2.4~2.4835GHz/
Equipment Class	Class B
Power Supply	Battery or Charger
Rated Power Supply Voltage	3.85V
Extreme Temperature	Lowest: -10°C Highest: +55°C
Extreme Voltage	Minimum: 3.4V Maximum: 4.4V
HW Version	zh2B
SW Version	TEL_MX_ZTE_9030V1.0

### 1.7.2 EUT details

	Product Name	Model Name	IMEI
EUT1	WCDMA/LTE Multi-mode Digital Mobile Phone	ZTE 9030	867552050001777
EUT2	WCDMA/LTE Multi-mode Digital Mobile Phone	ZTE 9030	867552050001587

### 1.7.3 Auxiliary equipment details

AE (Auxiliary Equipment) 1#: Laptop

Manufacturer	Lenovo
Model Number	E40-70
S/N	MP06WE9U
Input Voltage	100V-240V AC

AE (Auxiliary Equipment) 2#: USB Cable

Manufacturer	Luxshare Precision Industry Co.,Ltd.
Model Number	USB-TC20-W-100-M-L-HF

AE (Auxiliary Equipment) 3#: USB Cable

Manufacturer	Dongguan City King Power Electronics Co.,Ltd.
Model Number	USB-TC20-W-100-M-L-HF

AE (Auxiliary Equipment) 4#: Battery

Type	Li-Lon
Manufacturer	SCUD (FUJIAN) ELECTRONICS CO.,LTD
Model Number	Li3949T44P8h906450

AE (Auxiliary Equipment) 5#: Battery

Type	Li-Lon
Manufacturer	Ningde Amperex Technology Ltd.
Model Number	Li3949T44P8h906450

AE (Auxiliary Equipment) 6#: Headset

Manufacturer	JUWEI ELECTRONICS CO.,LTDTechnology Co., Ltd
Model Number	JWEP1036-Z01R

AE (Auxiliary Equipment) 7#: Headset

Manufacturer	ShenZhen FDC Electronic Co.,Ltd
Model Number	DEM-66

AE (Auxiliary Equipment) 8#: Charger

Manufacturer	Jiangsu Chenyang Electronics Co.,Ltd.
Model Number	STC-A5930A1-Z
S/N	/
Input Voltage	100V-240VAC 0.5A
Output Voltage	5.0VDC 3.0A or 9.0VDC 2.0A or 12.0VDC 1.5A

AE (Auxiliary Equipment) 9#: Charger

Manufacturer	Shenzhen Ruijing Industrial CO.,LTD.
Model Number	STC-A5930A1-Z
S/N	/
Input Voltage	100V-240VAC 0.5A
Output Voltage	5.0VDC 3.0A or 9.0VDC 2.0A or 12.0VDC 1.5A


Note2: As the information described in these above tables, the relevant tests have been performed in order to verify in which supply would have the worst features. When the EUT1 exercised with 2# USB Cable, 4# Battery, 6# Headset, 8# Charger is the worst feature, and record the results in the test report.

Note3: AE1# Laptop was selected by testing laboratory and was only cooperated with this test, not for sale.

## 2. Test information

### 2.1 Summary of the test results

No.	Test case	FCC reference	Verdict
1	Conducted emissions	15.107	Pass
2	Radiated emissions	15.109	Pass

Approved By: Mr. Liu Wei Director of the test department  	Checked By: Mr. Guo Yu Vice director of the test department  
Tested by: Mr. Liu Jian Test engineer  	Issued date:  2021.3.31

## 2.2 Test result

### 2.2.1 Conducted Emissions-FCC Part15.107

Ambient condition:

Temperature	Relative humidity	Pressure
24.0°C	41.1%	101.2kPa

Test Setup with laptop:




Figure 1

Test Procedure:

The EUT is placed on a non-metallic table 0.8m above the horizontal metal reference ground plane. The accessories of the EUT are connected with the EUT such as headset etc. The EUT was connected with a laptop via the USB cable and transferred the data by copying large files from laptop to the EUT. The laptop's LAN port is connected with another laptop via cable. And the data transferring between two laptops is maintained.

The AC main power supply of the laptop is connected to LISN and LISN is connected to the reference ground. The test set-up and the test methods are performed according to ANSI C63.4:2014.

Then start the test software EMC32. Sweep the whole frequency band through the range from 150 KHz to 30 MHz with RBW 9kHz, VBW 30kHz. The measurement should be done for both L line and N line. During pre-test, the receiver uses both peak detector and average detector. And the final test, the receiver uses both average detector and Quasi-peak detector.

The data of cable loss has been calibrated in full testing frequency range before the testing.

Test Setup with charger:




Figure 2

Test Procedure:

The EUT is placed on a non-metallic table 0.8m above the horizontal metal reference ground plane. The EUT is connected with LISN via the charger. The LISN is connected to the reference ground. The accessories of the EUT are connected with the EUT such as headset etc. Open the following functions of EUT: Camera, flash lamp, FM, GPS and video.

The test set-up and the test methods are performed according to ANSI C63.4:2014. Then start the test software EMC32. Sweep the whole frequency band through the range from 150 KHz to 30 MHz with RBW 9kHz, VBW 30kHz. The measurement should be done for both L line and N line. During pre-test, the receiver uses both peak detector and average detector. And the final test, the receiver uses both average detector and Quasi-peak detector.

The data of cable loss has been calibrated in full testing frequency range before the testing.

A "reference path loss" Corr.(dB) is established and the  $L_{cable} + ATT + VDF$  is the attenuation of "reference path loss", and including the cable loss, the attenuation of the attenuator, the voltage division factor of AMN.

The measurement results are obtained as described below:

$$P_{result} = P_{mea} + Corr.(dB)$$

Sample calculation:  $(48.51dB\mu V) = (18.81dB\mu V) + (29.7dB)$ , the corresponding frequency is 0.171321MHz.


Limit:

Frequency of Emission(MHz)	Limits(dB $\mu$ V)	
	Quasi-peak	Average
0.15~0.5	66 to 56*	56 to 46*
0.5~5	56	46
5~30	60	50

Note: \* Decreases with the logarithm of the frequency


Test result:

Noise Level of the Measuring Instrument



Pic1. Conducted emission L and N Line


EUT + Charger: AC240V



Pic2. Conducted emission L&N Line

Frequency (MHz)	QuasiPeak (dBμV)	Average (dBμV)	Limit (dBμV)	Margin (dB)	Line	Corr. (dB)	Pmea QuasiPeak (dBμV)	Pmea Average (dBμV)
0.171321	48.51	---	65.77	17.26	L1	29.7	18.81	---
0.171321	---	24.95	55.54	30.59	L1	29.7	---	-4.75
0.546579	42.43	---	65.32	22.89	L1	29.7	12.73	---
0.546579	41.00	---	63.92	22.92	L1	29.7	11.3	---
0.900514	33.76	---	58.09	24.33	L1	29.7	4.06	---
0.973007	---	19.83	46.00	26.17	N	29.8	---	-9.97
2.171271	---	29.78	50.00	20.22	N	29.8	---	-0.02
2.269350	---	30.07	50.00	19.93	L1	29.8	---	0.27
7.288414	36.84	---	60.00	23.16	L1	29.8	7.04	---
7.808657	38.39	---	60.00	21.61	L1	29.8	8.59	---
17.497114	---	21.66	50.00	28.34	L1	29.8	---	-8.14
21.501279	---	26.03	50.00	23.97	L1	29.8	---	-3.77


EUT + Charger: AC120V



Pic3. Conducted emission L&N Line

Frequency (MHz)	QuasiPeak (dB $\mu$ V)	Average (dB $\mu$ V)	Limit (dB $\mu$ V)	Margin (dB)	Line	Corr. (dB)	Pmea QuasiPeak (dB $\mu$ V)	Pmea Average (dB $\mu$ V)
0.154264	41.20	---	65.77	24.57	L1	29.7	11.5	---
0.162793	44.41	---	65.32	20.91	L1	29.7	14.71	---
0.555107	---	20.39	46.00	25.61	L1	29.7	---	-9.31
0.555107	32.12	---	56.00	23.88	L1	29.7	2.42	---
0.572164	33.86	---	56.00	22.14	L1	29.7	4.16	---
0.576429	---	25.27	46.00	20.73	L1	29.7	---	-4.43
5.070986	---	28.33	50.00	21.67	N	29.8	---	-1.47
6.435557	34.56	---	60.00	25.44	L1	29.8	4.76	---
6.435557	---	28.60	50.00	21.40	L1	29.8	---	-1.2
7.301207	36.01	---	60.00	23.99	L1	29.9	6.11	---
8.998393	---	23.81	50.00	26.19	N	29.9	---	-6.09
12.563336	---	25.85	50.00	24.15	L1	30.0	---	-4.15

EUT + Laptop:



Pic4. Conducted emission L&N Line

Frequency (MHz)	QuasiPeak (dB $\mu$ V)	Average (dB $\mu$ V)	Limit (dB $\mu$ V)	Margin (dB)	Line	Corr. (dB)	Pmea QuasiPeak (dB $\mu$ V)	Pmea Average (dB $\mu$ V)
0.580693	---	27.04	46.00	18.96	L1	29.7	---	-2.66
0.584957	45.68	---	56.00	10.32	L1	29.7	15.98	---
0.670243	41.42	---	56.00	14.58	L1	29.7	11.72	---
0.674507	---	24.48	46.00	21.52	N	29.7	---	-5.22
0.896250	---	25.57	46.00	20.43	N	29.8	---	-4.23
1.800279	37.53	---	56.00	18.47	L1	29.8	7.73	---
1.800279	---	25.72	46.00	20.28	N	29.8	---	-4.08
1.825864	36.59	---	56.00	19.41	L1	29.8	6.79	---
3.036921	---	28.16	46.00	17.84	L1	29.8	---	-1.64
3.045450	37.55	---	56.00	18.45	L1	29.8	7.75	---
3.083829	---	27.52	46.00	18.48	L1	29.8	---	-2.28
3.160586	37.66	---	56.00	18.34	L1	29.8	7.86	---

## 2.2.2 Radiated Emissions-FCC Part15.109

Ambient condition:

Temperature	Relative humidity	Pressure
24.2°C	41.5%	101.2kPa

Test Setup:




Figure 3

Test Procedure:

EUT+Laptop:

The EUT should be placed on a non-metallic table 80cm above the ground plane. The receive antennas shall be moved from 1 to 4 meters. The distance between EUT and receive antenna should be 3 meters.

The accessories of the EUT are connected with the EUT such as headset etc. The EUT was connected with a laptop via the USB cable and transferred the data by copying large files from laptop to the EUT. The test set-up and the test methods are performed according to ANSI C63.4:2014

Then start the test software EMC32. Sweep the whole frequency band through the range from 30MHz to 1GHz, using receive log period antenna VULB 9163.

During the test, the height of receive antenna shall be moved from 1 to 4 meters, and the antenna shall be performed under horizontal and vertical polarization. The turn table shall be rotated from 0 to 360 degrees for detecting the maximum of radiated spurious signal level. The measurements shall be repeated with orthogonal polarization of the test antenna. The EUT is laid in two modes as follow:  
1. put the EUT in horizontal direction; 2. put the EUT in vertical direction.

The data of cable loss and antenna factor have been calibrated in full testing frequency range before the testing.

#### EUT + Charger:

The EUT should be placed on a non-metallic table 80cm above the ground plane. The receive antennas shall be moved from 1 to 4 meters. The distance between EUT and receive antenna should be 3 meters.

The EUT should work in idle mode. The accessories of the EUT are connected with the EUT such as headset etc. Open the following functions of EUT: Camera, flash lamp, FM, GPS and video. The test set-up and the test methods are performed according to ANSI C63.4:2014.

Then start the test software EMC32. Sweep the whole frequency band through the range from 30MHz to 1GHz, using receive log period antenna VULB 9163.

During the test, the height of receive antenna shall be moved from 1 to 4 meters, and the antenna shall be performed under horizontal and vertical polarization. The turn table shall be rotated from 0 to 360 degrees for detecting the maximum of radiated spurious signal level. The measurements shall be repeated with orthogonal polarization of the test antenna. The EUT is laid in two modes as follow:  
1. put the EUT in horizontal direction; 2. put the EUT in vertical direction.

The data of cable loss and antenna factor have been calibrated in full testing frequency range before the testing. All test results are performed with max hold at the horizontal and vertical polarity.

RBW=120kHz, VBW=300kHz, when the test frequency: 30MHz<f<1GHz

RBW=1MHz, VBW=3MHz, when the test frequency: f>1GHz

A “reference path loss” is established and the  $A_{Rpl}$  is the attenuation of “reference path loss”, and including the gain of receive antenna, the gain of the preamplifier, the cable loss.

The measurement results are obtained as described below:

$$\text{Result} = P_{\text{mea}} + A_{Rpl}$$

#### Limit:

Frequency of Emission(MHz)	Limits	
	Detector	Unit (dB $\mu$ V/m)
30~88	Quasi-peak	40
88~216	Quasi-peak	43.5
216~960	Quasi-peak	46
960~1000	Quasi-peak	54
1000~5th harmonic of the highest frequency or 40GHz, whichever is lower	Average	54
	Peak	74

Test result:

Sample calculation:  $(19.86\text{dB}\mu\text{V}/\text{m}) = (34.46\text{dB}\mu\text{V}/\text{m}) + (-14.6\text{dB})$ , the corresponding frequency is 34.85MHz.


EUT + Laptop:

Frequency(MHz)	Result( dB $\mu$ V/m )	Limit (dB $\mu$ V/m)	ARpl (dB)	Pmea ( dB $\mu$ V/m )	Polarity
34.85	19.86	40.00	-14.6	34.46	V
60.4095	17.14	40.00	-26.2	43.34	V
144.072	18.57	43.50	-22.3	40.87	V
280.1145	25.13	46.00	-18.6	43.73	V
350.1	13.84	46.00	-16.4	30.24	V
832.675	16.66	46.00	-5.3	21.96	V

EUT + Charger:


Frequency(MHz)	Result( dB $\mu$ V/m )	Limit (dB $\mu$ V/m)	ARpl (dB)	Pmea ( dB $\mu$ V/m )	Polarity
48.4785	36.09	40.00	-22.8	58.89	V
86.745	29.37	40.00	-22.5	51.87	V
98.773	28.58	43.50	-21.6	50.18	V
173.657	24.46	43.50	-22.3	46.76	V
443.123	20.83	46.00	-13.4	34.23	V
573.3455	20.54	46.00	-10.2	30.74	V

EUT + Laptop: refer to Pic5, Pic6, Pic7, Pic8, Pic9



Pic5. Radiated emission(30MHz – 1GHz)


Note: The test data in the graph includes two polarizations: horizontal and vertical



Pic6. Radiated emission (1GHz –3GHz)

Note: The test data in the graph includes two polarizations: horizontal and vertical.


Full Spectrum



Pic7. Radiated emission (3GHz –6GHz)

Note: The test data in the graph includes two polarizations: horizontal and vertical.


Full Spectrum



Pic8. Radiated emission (6GHz –18GHz)

Note: The test data in the graph includes two polarizations: horizontal and vertical.

Full Spectrum




Pic9. Radiated emission (18GHz – 40GHz)

Note: The test data in the graph includes two polarizations: horizontal and vertical.

EUT + Charger: refer to Pic10, Pic11, Pic12, Pic13, Pic14


Full Spectrum



Pic10. Radiated emission(30MHz – 1GHz)

Note: The test data in the graph includes two polarizations: horizontal and vertical


Full Spectrum



Pic11. Radiated emission (1GHz –3GHz)

Note: The test data in the graph includes two polarizations: horizontal and vertical.


Full Spectrum



Pic12. Radiated emission (3GHz –6GHz)

Note: The test data in the graph includes two polarizations: horizontal and vertical.


Full Spectrum



Pic13. Radiated emission (6GHz –18GHz)

Note: The test data in the graph includes two polarizations: horizontal and vertical.

Full Spectrum



Pic14. Radiated emission (18GHz – 40GHz)

Note: The test data in the graph includes two polarizations: horizontal and vertical.

### 2.3. List of test equipments

No.	Name/Model	Manufacturer	S/N	Calibration Due Date	Calibration Date
1	23.18m×16.88m×9.60mS emi-AnechoicChamber	FRANKONIA	-----	5th Sep. 2021	6th Sep. 2016
2	ESW EMI test receiver	R&S	101574	20th Aug. 2021	20th Aug. 2020
3	ESR3EMI test receiver	R&S	102361	21th Apr. 2021	21th Apr. 2020
4	9.080m×5.255m×3.525m Shielding room	FRANKONIA	-----	5th Sep. 2021	6th Sep. 2016
5	VULB 9163 Ultra log test antenna	schwarzbeck	867	25th Mar. 2022	25th Mar. 2021
6	HF 907 Double-Ridged Waveguide Horn Antenna	R&S	100512	25th Mar. 2022	25th Mar. 2021
7	SAS-574 Horn Antenna	schwarzbeck	535	20th Aug. 2021	20th Aug. 2020
8	ENV216 AMN	R&S	3560.6550. 12	20th Aug. 2021	20th Aug. 2020
9	EMC32EMI test software	R&S	-----	-----	-----