



Registration  
No.910917

---

# TEST REPORT FOR SAR TESTING

---

Report No.: SRTC2017-9004(F)-0055

Product Name: LTE/WCDMA/GSM(GPRS) Mutil-Mode Digital Mobile Phone

Product Model: ZTE BLADE A320/BLADE A320

Applicant: ZTE Corporation

Manufacturer: ZTE Corporation

Specification: FCC Part 2.1093

IEEE Std 1528-2013

FCC RF Exposure KDB Procedures

FCC ID: SRQ-ZTEBLADEA320A

The State Radio\_monitoring\_center Testing Center (SRTC)

No.80 Beilishi Road Xicheng District Beijing, China

Tel: 86-10-57996181 Fax: 86-10-57996288

## Contents

<b>1. GENERAL INFORMATION.....</b>	<b>2</b>
1.1 NOTES OF THE TEST REPORT.....	2
1.2 INFORMATION ABOUT THE TESTING LABORATORY.....	2
1.3 APPLICANT’S DETAILS.....	2
1.4 MANUFACTURER’S DETAILS.....	2
1.5 TEST ENVIRONMENT.....	3
<b>2. DESCRIPTION OF THE DEVICE UNDER TEST.....</b>	<b>4</b>
2.1 FINAL EQUIPMENT BUILD STATUS.....	4
2.2 SUPPORT EQUIPMENT.....	5
<b>3. REFERENCE SPECIFICATION.....</b>	<b>6</b>
<b>4. TEST CONDITIONS.....</b>	<b>7</b>
4.1 PICTURE TO DEMONSTRATE THE REQUIRED LIQUID DEPTH.....	7
4.2 TEST SIGNAL, FREQUENCIES AND OUTPUT POWER.....	7
4.3 SAR MEASUREMENT SET-UP.....	7
4.4 PHANTOMS.....	8
4.5 TISSUE SIMULANTS.....	8
4.6 DESCRIPTION OF THE TEST PROCEDURE.....	9
<b>5 RESULT SUMMAR.....</b>	<b>11</b>
<b>6 TEST RESULT.....</b>	<b>13</b>
6.1 MANUFACTURING TOLERANCE.....	13
6.2 GSM MEASUREMENT RESULT.....	21
6.3 WCDMA MEASUREMENT RESULT.....	23
6.4 LTE MEASUREMENT RESULT.....	25
<b>BAND 12.....</b>	<b>49</b>
<b>BAND 13.....</b>	<b>55</b>
6.5 BLUETOOTH MEASUREMENT RESULT.....	61
6.6 WI-FI MEASUREMENT RESULT.....	62
6.7 STANDALONE SAR TEST EXCLUSION CONSIDERATIONS.....	64
6.8 RF EXPOSURE CONDITIONS.....	66
6.9 SYSTEM CHECKING.....	68
6.10 SAR TEST RESULT.....	70
6.11 SAR MEASUREMENT VARIABILITY.....	93
6.12 SIMULTANEOUS TRANSMISSION SAR ANALYSIS.....	95
<b>7 MEASUREMENT UNCERTAINTY.....</b>	<b>97</b>
<b>8 TEST EQUIPMENTS.....</b>	<b>98</b>
<b>ANNEX A – TEST PLOTS.....</b>	<b>99</b>
<b>ANNEX B – RELEVANT PAGES FROM CALIBRATION REPORTS.....</b>	<b>99</b>
<b>ANNEX C – PHOTOGRAPH.....</b>	<b>99</b>
<b>ANNEX A – TEST PLOTS.....</b>	<b>100</b>
<i>Communication System: UID 10000, CW; Communication System Band: D835 (835.0 MHz); Frequency: 835 MHz; Communication System PAR: 0 dBMedium parameters used: <math>f = 835 \text{ MHz}</math>; <math>\sigma = 0.956 \text{ S/m}</math>; <math>\epsilon_r = 54.875</math>; <math>\rho = 1000 \text{ kg/m}^3</math> Phantom section: Flat Section Measurement Standard: DASY5 (IEEE 1528-2013).....</i>	
<b>ANNEX B - RELEVANT PAGES FROM CALIBRATION REPORTS.....</b>	<b>279</b>
<b>ANNEX C - PHOTOGRAPH.....</b>	<b>298</b>

## 1. GENERAL INFORMATION

### 1.1 Notes of the test report

The test report may only be reproduced or published in full. Reproduction or publication of extracts from the report requires the prior written permission of The State Radio\_monitoring\_center Testing Center (SRTC).

The test results relate only to individual items of the samples which have been tested.

### 1.2 Information about the testing laboratory

Company:	The State Radio_monitoring_center Testing Center (SRTC)
Address:	No.80 Beilishi Road, Xicheng District
City:	Beijing
Country or Region:	P.R.China
Contacted person:	Liu Jia
Tel:	+86 10 5799 6181
Fax:	+86 10 5799 6288
Email:	liujiaf@srtc.org.cn

### 1.3 Applicant's details

Company:	ZTE Corporation
Address:	ZTE Plaza, #55 Keji Road South, Hi-Tech, Industrial Park,Nanshan District,Guangdong
City:	Shenzhen
Country or Region:	P.R.China
Grantee Code:	SRQ
Contacted person:	Min Zhang
Tel:	021-68897867
Fax:	021-50801070
Email:	zhang.min13@zte.com.cn

### 1.4 Manufacturer's details

Company:	ZTE Corporation
Address:	ZTE Plaza, #55 Keji Road South, Hi-Tech, Industrial Park,Nanshan District,Guangdong
City:	Shenzhen
Country or Region:	P.R.China
Contacted person:	Min Zhang
Tel:	021-68897867
Fax:	021-50801070
Email:	zhang.min13@zte.com.cn

### 1.5 Test Environment

Date of Receipt of test sample at SRTC:	2017.05.16
Testing Start Date:	2017.05.17
Testing End Date:	2017.06.05

Environmental Data:	Temperature (°C)	Humidity (%)
Ambient	25.0	38.0

Normal Supply Voltage (V d.c.):	3.80
---------------------------------	------

## 2. DESCRIPTION OF THE DEVICE UNDER TEST

### 2.1 Final Equipment Build Status

Wireless Technology and Frequency Bands	GSM Band : GSM850/PCS1900 WCDMA Band: FDD2/FDD5 LTE Band: FDD2/FDD4/FDD5/FDD12/FDD13/FDD17 Wi-Fi Band: 2400MHz~2483.5MHz Bluetooth Band: 2400MHz~2483.5MHz
Mode	GSM <input checked="" type="checkbox"/> Voice (GMSK) <input checked="" type="checkbox"/> GPRS (GMSK) <input checked="" type="checkbox"/> EGPRS (GMSK/8PSK) WCDMA <input checked="" type="checkbox"/> UMTS Rel. 99 (Voice & Data) <input checked="" type="checkbox"/> HSDPA (Rel. 5) <input checked="" type="checkbox"/> HSUPA (Rel. 6) <input type="checkbox"/> HSPA+ (Rel. ) <input type="checkbox"/> DC-HSDPA (Rel. ) LTE <input checked="" type="checkbox"/> QPSK <input checked="" type="checkbox"/> 16QAM Wi-Fi 2.4GHz (802.11b/g/n) <input checked="" type="checkbox"/> 802.11b <input checked="" type="checkbox"/> 802.11g <input checked="" type="checkbox"/> 802.11n (20MHz) <input type="checkbox"/> 802.11n (40MHz) Bluetooth <input checked="" type="checkbox"/> BR(GFSK) <input checked="" type="checkbox"/> EDR( $\pi/4$ DQPSK , 8-DPSK) <input checked="" type="checkbox"/> BLE(GFSK)
Duty Cycle	GSM Voice: 12.5%; GPRS: 12.5% (1 Slot), 25% (2 Slots), 37.5% (3 Slots), 50% (4 Slots) WCDMA: 100% Wi-Fi 802.11b/g/n: 100% Bluetooth: 32.25% (DH1), 66.68% (DH3), 77.52% (DH5)
GPRS Multi-Slot Class	<input type="checkbox"/> Class 8 - One Up <input type="checkbox"/> Class 10 - Two Up <input checked="" type="checkbox"/> Class 12 - Four Up
Mobile Phone Capability	<input type="checkbox"/> Class A - Mobile phones can be connected to both GPRS and GSM services simultaneously. <input checked="" type="checkbox"/> Class B - Mobile phones can be attached to both GPRS and GSM services, using one service at a time. <input type="checkbox"/> Class C - Mobile phones are attached to either GPRS or GSM voice service. You need to switch manually between services
DTM (Dual Transfer Mode)	Not Supported

## 2.2 Support Equipment

The following support equipment was used to exercise the DUT during testing:

State of sample	Production unit
Headset	DEM-79/Shen zhen FDC Electronic Co.,Ltd.
	QZESDM1532001A00/Dongle GuanKanTsang Industrial Co., LTD
Batteries	Li3822T43P3h716043/ Zhengzhou BAK Battery Co.,Ltd
	Li3822T43P3h716043/ Zhongshan Tianmao Battery CO.LTD
H/W Version	u4jB
S/W Version	FLOW_CW_BA320_V1.0
IMEI	863916030021516
Notes	As the information described above, there are two batteries with same model which manufactured by two companies. The relevant tests have been performed in order to verify in which combination case (EUT exercised by one models of battery manufactured by two companies) the EUT would have the worst features. So all the tests shown in this test report are performed when the EUT exercised by the battery 1 manufactured by Zhengzhou BAK Battery Co.,Ltd

Note: The original test data of Band2/Band4/Band5 derive from the report: SRTC2017-9004(F)-0021  
Re-test add Band12\Band13\Band17

### 3. REFERENCE SPECIFICATION

Specification	Version	Title
Part 2.1093	Nov. 14, 2016	Radiofrequency radiation exposure evaluation: portable devices.
IEEE Std 1528	2013	IEEE Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques
IEEE Std 1528a	2005	IEEE Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques Amendment 1: CAD File for Human Head Model (SAM Phantom)
KDB 447498 D01	v06	General RF Exposure Guidance
KDB 648474 D04	v01r03	Handset SAR
KDB 941225 D01	v03r01	3G SAR Procedures
KDB 941225 D06	v02r01	Hotspot Mode
KDB 248227 D01	v02r02	SAR meas for 802 11 a b g
KDB 865664 D01	v01r04	SAR Measurement 100 MHz to 6 GHz
KDB 865664 D02	v01r02	RF Exposure Reporting
KDB 941225 D05	v02r05	SAR for LTE Devices

## 4. TEST CONDITIONS

### 4.1 Picture to demonstrate the required liquid depth

The liquid depth in the used SAM phantoms



Liquid depth for SAR Measurement

### 4.2 Test Signal, Frequencies and Output Power

The device was put into operation by using a call tester. Communication between the device and the call tester was established by air link.

The device output power was set to maximum power level for all tests; a fully charged battery was used for every test sequence.

In all operating bands the measurements were performed on lowest, middle and highest channels.

### 4.3 SAR Measurement Set-up

The system is based on a high precision robot (working range greater than 0.9m), which positions the probes with a positional repeatability of better than  $\pm 0.02\text{mm}$ . Special E- and H-field probes have been developed for measurements close to material discontinuity, the sensors of which are directly loaded with a Schottky diode and connected via highly resistive lines (length =300mm) to the data acquisition unit. A cell controller system contains the power supply, robot controller, teaches pendant (Joystick), and remote control, is used to drive the robot motors.

The PC consists of the Micron Pentium IV computer with Win7 system and SAR Measurement Software DASY5 Professional, A/D interface card, monitor, mouse, and keyboard. The Stäubli Robot is connected to the cell controller to allow software manipulation of the robot.

A data acquisition electronic (DAE) circuit performs the signal amplification, signal



multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. is connected to the Electro-optical coupler (EOC). The EOC performs the conversion from the optical into digital electric signal of the DAE and transfers data to the PC plug-in card. The DAE consists of a highly sensitive electrometer-grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16 bit AD-converter and a command decoder and control logic unit. Transmission to the PC-card is accomplished through an optical downlink for data and status information and an optical uplink for commands and clock lines.

The mechanical probe mounting device includes two different sensor systems for frontal and sidewise probe contacts. They are also used for mechanical surface detection and probe collision detection

The robot uses its own controller with a built in VME-bus computer.

#### 4.4 Phantoms

The phantom used for all tests i.e. for both system checks and device testing, was the twin headed "SAM Phantom", manufactured by SPEAG. The phantom conforms to the requirements of IEEE 1528 - 2013.

System checking was performed using the flat section, whilst Head SAR tests used the left and right head profile sections. Body SAR testing also used the flat section between the head profiles.

The SPEAG device holder (see Section 5.1) was used to position the device in all tests whilst a tripod was used to position the validation dipoles against the flat section of phantom.

#### 4.5 Tissue Simulants

Recommended values for the dielectric parameters of the tissue simulants are given in IEEE 1528 - 2013 and FCC Supplement C to OET Bulletin 65. All tests were carried out using simulants whose dielectric parameters were within  $\pm 5\%$  of the recommended values. All tests were carried out within 24 hours of measuring the dielectric parameters.

The depth of the tissue simulant was  $15.0 \pm 0.5$  cm measured from the ear reference point during system checking and device measurements.

### 4.5.1 Tissue Simulant Recipes

The following recipe(s) were used for Head and Body tissue stimulant(s):

#### 835MHz band

Ingredient	Head (% by weight)	Body (% by weight)
Water	41.45	52.50
Sugar	56.00	45.0
Nacl	1.45	1.40
Cellulose	1.00	1.00
Preventol	0.10	0.10

#### 1900MHz band

Ingredient	Head (% by weight)	Body (% by weight)
Water	44.45	70.17
DGBE	55.24	29.44
Nacl	0.31	0.39

#### 2450MHz band

Ingredient	Head (% by weight)	Body (% by weight)
Water	55.00	68.64
DGBE	45.00	31.37
Nacl	0.00	0.00

#### 5GHz band

Ingredient	Head (% by weight)	Body (% by weight)
Water	65.52	---
Triton X-100	17.24	---
Diethylenglycol monohexylether	17.24	---

## 4.6 DESCRIPTION OF THE TEST PROCEDURE

### 4.6.1 Device Holder

The device was placed in the device holder (illustrated below) that is supplied by SPEAG as an integral part of the Dasy system.



**Device holder supplied by SPEAG**

## **4.6.2 Test positions**

### **4.6.2.1 Against Phantom Head**

Measurements were made in “cheek” and “tilt” positions on both the left hand and right hand sides of the phantom.

The positions used in the measurements were according to IEEE 1528 - 2013 "IEEE Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques".

### **4.6.2.2 Body Worn Configuration**

The device was placed in the SPEAG holder below the flat section of the phantom. The distance between the device and the phantom was kept at the separation distance using a separate flat spacer that was removed before the start of the measurements. And the distance is 10mm. The device was oriented with its antenna facing the phantom since this orientation gives higher results.

## **4.6.3 Scan Procedure**

First, area scans were used for determination of the field distribution and the approximate location of the local peak SAR values. The SAR distribution is scanned along the inside surface, at least for an area larger than the projection of the handset and antenna. The angle between the probe axis and the surface normal line is recommended but not required to be less than 30°. The SAR distribution is first measured on a 2-D coarse grid. The scan region should cover all areas that are exposed and encompassed by the projection of the handset. It is a 15 mm × 15 mm measurement grid used when two staggered one-dimensional cubic splines are used to estimate the maximum SAR location. Next, a zoom scan, a minimum of 7 x 7x7 points covering a volume of at least 30x30x30mm, was performed around the highest E-field value to determine the averaged SAR value. Drift was determined by measuring the same point at the start of the area scan and again at the end of the zoom scan.

## **4.6.4 SAR Averaging Methods**

The maximum SAR value was averaged over a cube of tissue using interpolation and extrapolation.

The interpolation, extrapolation and maximum search routines within DASY5 are all based on the modified Quadratic Shepard's method (Robert J. Renka, "Multivariate Interpolation of Large Sets of Scattered Data", University of North Texas ACM Transactions on Mathematical Software, vol. 14, no. 2, June 1988, pp. 139-148).

The interpolation scheme combines a least-square fitted function method with a weighted average method. A trivariate 3-D / bivariate 2-D quadratic function is computed for each measurement point and fitted to neighbouring points by a least-square method. For the zoom scan, inverse distance weighting is incorporated to fit distant points more accurately. The interpolating function is finally calculated as a weighted average of the quadratics. In the zoom scan, the interpolation function is used to extrapolate the Peak SAR from the deepest measurement points to the inner surface of the phantom.




## 5 RESULT SUMMAR

The maximum reported SAR values for Head configuration and Body Worn configuration are given as follows. The device conforms to the requirements of the standard(s) when the maximum reported SAR value is less than or equal to the limit.

Exposure Position	Frequency Band	1g-SAR Reported Result (W/kg)	Highest 1g-SAR Reported Result (W/kg)		Limit (W/kg)/1g	Result
Head	GSM 850	0.170	1.060	1.268	1.60	PASS
	GSM 1900	0.154				
	WCDMA Band 2	0.270				
	WCDMA Band 5	0.263				
	WLAN 2.4GHz Band	1.060				
	LTE Band 2	0.184				
	LTE Band 4	0.251				
	LTE Band 5	0.273				
	LTE Band 12	0.109				
	LTE Band 13	0.110				
	LTE Band 17	0.036				
Body	GSM 850	0.317	1.268	1.268	1.60	PASS
	GSM 1900	0.706				
	WCDMA Band 2	1.268				
	WCDMA Band 5	0.444				
	WLAN 2.4GHz Band	0.138				
	LTE Band 2	1.045				
	LTE Band 4	0.670				
	LTE Band 5	0.558				
	LTE Band 12	0.192				
	LTE Band 13	0.266				
	LTE Band 17	0.153				

**Simultaneous Transmission Summary**

Exposure Position	Frequency Band	1g-SAR Result(W/kg)	Highest 1g-SAR Result(W/kg)		Limit (W/kg)/1g	Result
Head	GSM & Wi-Fi	1.240	1.330	1.475	1.60	PASS
	WCDMA & Wi-Fi	1.330				
	LTE& Wi-Fi	1.311				
	GSM & Bluetooth	0.387				
	WCDMA & Bluetooth	0.477				
	LTE& Bluetooth	0.480				
Body	GSM & Wi-Fi	0.844	1.475	1.475	1.60	PASS
	WCDMA & Wi-Fi	1.406				
	LTE& Wi-Fi	1.183				
	GSM & Bluetooth	0.913				
	WCDMA & Bluetooth	1.475				
	LTE& Bluetooth	1.252				

This Test Report Is Issued by: Mr. Peng Zhen 	Checked by: Ms. Liu Jia 
Tested by: Mr. Li Bin 	Issued date:  20170613

## 6 TEST RESULT

### 6.1 Manufacturing Tolerance

(Unit: dBm)

#### GSM

GSM 850			
Channel	Channel 128	Channel 189	Channel 251
Tolerance (dBm)	30.0~33.5	30.0~33.5	30.0~33.5
GSM 1900			
Channel	Channel 512	Channel 661	Channel 810
Tolerance (dBm)	27.0~31.0	27.0~31.0	27.0~31.0

GSM 850 GPRS				
Channel		128	189	251
1 Txslot	Tolerance (dBm)	30.0~33.5	30.0~33.5	30.0~33.5
2 Txslot	Tolerance (dBm)	28.0~32.5	28.0~32.5	28.0~32.5
3 Txslot	Tolerance (dBm)	26.0~31.5	26.0~31.5	26.0~31.5
4 Txslot	Tolerance (dBm)	24.0~29.5	24.0~29.5	24.0~29.5
GSM 850 EGPRS (GMSK)				
Channel		128	189	251
1 Txslot	Tolerance (dBm)	30.0~33.5	30.0~33.5	30.0~33.5
2 Txslot	Tolerance (dBm)	28.0~32.5	28.0~32.5	28.0~32.5
3 Txslot	Tolerance (dBm)	26.0~31.5	26.0~31.5	26.0~31.5
4 Txslot	Tolerance (dBm)	24.0~29.5	24.0~29.5	24.0~29.5

GSM 1900 GPRS				
Channel		512	661	810
1 Txslot	Tolerance (dBm)	27.0~31.0	27.0~31.0	27.0~31.0
2 Txslot	Tolerance (dBm)	24.0~28.0	24.0~28.0	24.0~28.0
3 Txslot	Tolerance (dBm)	22.0~26.0	22.0~26.0	22.0~26.0
4 Txslot	Tolerance (dBm)	21.0~25.0	21.0~25.0	21.0~25.0
GSM 1900 EGPRS (GMSK)				
Channel		512	661	810
1 Txslot	Tolerance (dBm)	27.0~31.0	27.0~31.0	27.0~31.0
2 Txslot	Tolerance (dBm)	24.0~28.0	24.0~28.0	24.0~28.0
3 Txslot	Tolerance (dBm)	23.0~27.0	23.0~27.0	23.0~27.0
4 Txslot	Tolerance (dBm)	21.0~25.0	21.0~25.0	21.0~25.0

### WCDMA

WCDMA Band2			
Channel	9662	9800	9938
Tolerance (dBm)	20.0~23.5	20.0~23.5	20.0~23.5
WCDMA Band5			
Channel	1312	1413	1513
Tolerance (dBm)	20.0~24.0	20.0~24.0	20.0~24.0

HSDPA Band2				
Channel		9662	9800	9938
Sub test 1	Tolerance (dBm)	18.0~21.5	18.0~21.5	18.0~21.5
Sub test 2	Tolerance (dBm)	18.0~21.5	18.0~21.5	18.0~21.5
Sub test 3	Tolerance (dBm)	18.0~21.5	18.0~21.5	18.0~21.5
Sub test 4	Tolerance (dBm)	18.0~21.5	18.0~21.5	18.0~21.5
HSDPA Band5				
Channel		4357	4408	4458
Sub test 1	Tolerance (dBm)	18.0~22.0	18.0~22.0	18.0~22.0
Sub test 2	Tolerance (dBm)	18.0~22.0	18.0~22.0	18.0~22.0
Sub test 3	Tolerance (dBm)	18.0~22.0	18.0~22.0	18.0~22.0
Sub test 4	Tolerance (dBm)	18.0~22.0	18.0~22.0	18.0~22.0

HSUPA Band2				
Channel		9662	9800	9938
Sub test 1	Tolerance (dBm)	18.0~21.5	18.0~21.5	18.0~21.5
Sub test 2	Tolerance (dBm)	18.0~21.5	18.0~21.5	18.0~21.5
Sub test 3	Tolerance (dBm)	18.0~21.5	18.0~21.5	18.0~21.5
Sub test 4	Tolerance (dBm)	17.0~20.5	17.0~20.5	17.0~20.5
Sub test 5	Tolerance (dBm)	18.5~23.0	18.5~23.0	18.5~23.0
HSUPA Band5				
Channel		4357	4408	4458
Sub test 1	Tolerance (dBm)	18.0~22.0	18.0~22.0	18.0~22.0
Sub test 2	Tolerance (dBm)	18.0~22.0	18.0~22.0	18.0~22.0
Sub test 3	Tolerance (dBm)	18.0~22.0	18.0~22.0	18.0~22.0
Sub test 4	Tolerance (dBm)	17.0~21.0	17.0~21.0	17.0~21.0
Sub test 5	Tolerance (dBm)	19.0~23.5	19.0~23.5	19.0~23.5

**Bluetooth**

GFSK			
Channel	0	39	78
Tolerance (dBm)	6.0~10.0	6.0~10.0	6.0~10.0
π/4DQPSK			
Channel	0	39	78
Tolerance (dBm)	6.0~10.0	6.0~10.0	6.0~10.0
8DPSK			
Channel	0	39	78
Tolerance (dBm)	6.0~10.0	6.0~10.0	6.0~10.0

**Bluetooth (BLE)**

GFSK			
Channel	0	19	39
Tolerance (dBm)	-4.0~1.0	-4.0~1.0	-4.0~1.0

**Wi-Fi(2.4GHz)**

802.11b			
Channel	1	6	11
Tolerance (dBm)	13.0~16.0	13.0~16.0	13.0~16.0
802.11g			
Channel	1	6	11
Tolerance (dBm)	7.0~13.0	7.0~13.0	7.0~13.0
802.11n HT20			
Channel	1	6	11
Tolerance (dBm)	7.0~12.0	7.0~12.0	7.0~12.0



**LTE**

**Band 2**

20BW 100%RB			
Channel	Channel 18700	Channel 18900	Channel 19100
Tolerance (dBm)	19.0~23.0	19.0~23.0	19.0~23.0
20BW 50%RB			
Channel	Channel 18700	Channel 18900	Channel 19100
Tolerance (dBm)	19.0~23.0	19.0~23.0	19.0~23.0
20BW 1RB			
Channel	Channel 18700	Channel 18900	Channel 19100
Tolerance (dBm)	19.0~23.0	19.0~23.0	19.0~23.0
15BW 100%RB			
Channel	Channel 18675	Channel 18900	Channel 19125
Tolerance (dBm)	19.0~23.0	19.0~23.0	19.0~23.0
15BW 50%RB			
Channel	Channel 18675	Channel 18900	Channel 19125
Tolerance (dBm)	19.0~23.0	19.0~23.0	19.0~23.0
15BW 1RB			
Channel	Channel 18675	Channel 18900	Channel 19125
Tolerance (dBm)	19.0~23.0	19.0~23.0	19.0~23.0
10BW 100%RB			
Channel	Channel 18650	Channel 18900	Channel 19150
Tolerance (dBm)	19.0~23.0	19.0~23.0	19.0~23.0
10BW 50%RB			
Channel	Channel 18650	Channel 18900	Channel 19150
Tolerance (dBm)	19.0~23.0	19.0~23.0	19.0~23.0
10BW 1RB			
Channel	Channel 18650	Channel 18900	Channel 19150
Tolerance (dBm)	19.0~23.0	19.0~23.0	19.0~23.0
5BW 100%RB			
Channel	Channel 18625	Channel 18900	Channel 19175
Tolerance (dBm)	19.0~23.0	19.0~23.0	19.0~23.0
5BW 50%RB			
Channel	Channel 18625	Channel 18900	Channel 19175
Tolerance (dBm)	19.0~23.0	19.0~23.0	19.0~23.0
5BW 1RB			
Channel	Channel 18625	Channel 18900	Channel 19175
Tolerance (dBm)	19.0~23.0	19.0~23.0	19.0~23.0
3BW 100%RB			
Channel	Channel 18615	Channel 18900	Channel 19185
Tolerance (dBm)	19.0~23.0	19.0~23.0	19.0~23.0
3BW 50%RB			
Channel	Channel 18615	Channel 18900	Channel 19185
Tolerance (dBm)	19.0~23.0	19.0~23.0	19.0~23.0
3BW 1RB			
Channel	Channel 18615	Channel 18900	Channel 19185
Tolerance (dBm)	19.0~23.0	19.0~23.0	19.0~23.0
1.4BW 100%RB			
Channel	Channel 18607	Channel 18900	Channel 19193
Tolerance (dBm)	19.0~23.0	19.0~23.0	19.0~23.0
1.4BW 50%RB			
Channel	Channel 18607	Channel 18900	Channel 19193
Tolerance (dBm)	19.0~23.0	19.0~23.0	19.0~23.0
1.4BW 1RB			
Channel	Channel 18607	Channel 18900	Channel 19193
Tolerance (dBm)	19.0~23.0	19.0~23.0	19.0~23.0

Band 4

20BW 100%RB			
Channel	Channel 20050	Channel 20175	Channel 20300
Tolerance (dBm)	20.0~24.0	20.0~24.0	20.0~24.0
20BW 50%RB			
Channel	Channel 20050	Channel 20175	Channel 20300
Tolerance (dBm)	20.0~24.0	20.0~24.0	20.0~24.0
20BW 1RB			
Channel	Channel 20050	Channel 20175	Channel 20300
Tolerance (dBm)	20.0~24.0	20.0~24.0	20.0~24.0
15BW 100%RB			
Channel	Channel 20250	Channel 20175	Channel 20325
Tolerance (dBm)	20.0~24.0	20.0~24.0	20.0~24.0
15BW 50%RB			
Channel	Channel 20250	Channel 20175	Channel 20325
Tolerance (dBm)	20.0~24.0	20.0~24.0	20.0~24.0
15BW 1RB			
Channel	Channel 20250	Channel 20175	Channel 20325
Tolerance (dBm)	20.0~24.0	20.0~24.0	20.0~24.0
10BW 100%RB			
Channel	Channel 20000	Channel 20175	Channel 20350
Tolerance (dBm)	20.0~24.0	20.0~24.0	20.0~24.0
10BW 50%RB			
Channel	Channel 20000	Channel 20175	Channel 20350
Tolerance (dBm)	20.0~24.0	20.0~24.0	20.0~24.0
10BW 1RB			
Channel	Channel 20000	Channel 20175	Channel 20350
Tolerance (dBm)	20.0~24.0	20.0~24.0	20.0~24.0
5BW 100%RB			
Channel	Channel 19975	Channel 20175	Channel 20375
Tolerance (dBm)	20.0~24.0	20.0~24.0	20.0~24.0
5BW 50%RB			
Channel	Channel 19975	Channel 20175	Channel 20375
Tolerance (dBm)	20.0~24.0	20.0~24.0	20.0~24.0
5BW 1RB			
Channel	Channel 19975	Channel 20175	Channel 20375
Tolerance (dBm)	20.0~24.0	20.0~24.0	20.0~24.0
3BW 100%RB			
Channel	Channel 19965	Channel 20175	Channel 20385
Tolerance (dBm)	20.0~24.0	20.0~24.0	20.0~24.0
3BW 50%RB			
Channel	Channel 19965	Channel 20175	Channel 20385
Tolerance (dBm)	20.0~24.0	20.0~24.0	20.0~24.0
3BW 1RB			
Channel	Channel 19965	Channel 20175	Channel 20385
Tolerance (dBm)	20.0~24.0	20.0~24.0	20.0~24.0
1.4BW 100%RB			
Channel	Channel 19957	Channel 20175	Channel 20393
Tolerance (dBm)	20.0~24.0	20.0~24.0	20.0~24.0
1.4BW 50%RB			
Channel	Channel 19957	Channel 20175	Channel 20393
Tolerance (dBm)	20.0~24.0	20.0~24.0	20.0~24.0
1.4BW 1RB			
Channel	Channel 19957	Channel 20175	Channel 20393
Tolerance (dBm)	20.0~24.0	20.0~24.0	20.0~24.0

**Band 5**

10BW 100%RB			
Channel	Channel 20000	Channel 20175	Channel 20350
Tolerance (dBm)	20.0~24.0	20.0~24.0	20.0~24.0
10BW 50%RB			
Channel	Channel 20000	Channel 20175	Channel 20350
Tolerance (dBm)	20.0~24.0	20.0~24.0	20.0~24.0
10BW 1RB			
Channel	Channel 20000	Channel 20175	Channel 20350
Tolerance (dBm)	20.0~24.0	20.0~24.0	20.0~24.0
5BW 100%RB			
Channel	Channel 19975	Channel 20175	Channel 20375
Tolerance (dBm)	20.0~24.0	20.0~24.0	20.0~24.0
5BW 50%RB			
Channel	Channel 19975	Channel 20175	Channel 20375
Tolerance (dBm)	20.0~24.0	20.0~24.0	20.0~24.0
5BW 1RB			
Channel	Channel 19975	Channel 20175	Channel 20375
Tolerance (dBm)	20.0~24.0	20.0~24.0	20.0~24.0
3BW 100%RB			
Channel	Channel 19965	Channel 20175	Channel 20385
Tolerance (dBm)	20.0~24.0	20.0~24.0	20.0~24.0
3BW 50%RB			
Channel	Channel 19965	Channel 20175	Channel 20385
Tolerance (dBm)	20.0~24.0	20.0~24.0	20.0~24.0
3BW 1RB			
Channel	Channel 19965	Channel 20175	Channel 20385
Tolerance (dBm)	20.0~24.0	20.0~24.0	20.0~24.0
1.4BW 100%RB			
Channel	Channel 19957	Channel 20175	Channel 20393
Tolerance (dBm)	20.0~24.0	20.0~24.0	20.0~24.0
1.4BW 50%RB			
Channel	Channel 19957	Channel 20175	Channel 20393
Tolerance (dBm)	20.0~24.0	20.0~24.0	20.0~24.0
1.4BW 1RB			
Channel	Channel 19957	Channel 20175	Channel 20393
Tolerance (dBm)	20.0~24.0	20.0~24.0	20.0~24.0

Band 12

10BW 100%RB			
Channel	Channel 23060	Channel 23095	Channel 23130
Tolerance (dBm)	20.0~24.0	20.0~24.0	20.0~24.0
10BW 50%RB			
Channel	Channel 23060	Channel 23095	Channel 23130
Tolerance (dBm)	20.0~24.0	20.0~24.0	20.0~24.0
10BW 1RB			
Channel	Channel 23060	Channel 23095	Channel 23130
Tolerance (dBm)	20.0~24.0	20.0~24.0	20.0~24.0
5BW 100%RB			
Channel	Channel 23035	Channel 23095	Channel 23155
Tolerance (dBm)	20.0~24.0	20.0~24.0	20.0~24.0
5BW 50%RB			
Channel	Channel 23035	Channel 23095	Channel 23155
Tolerance (dBm)	20.0~24.0	20.0~24.0	20.0~24.0
5BW 1RB			
Channel	Channel 23035	Channel 23095	Channel 23155
Tolerance (dBm)	20.0~24.0	20.0~24.0	20.0~24.0
3BW 100%RB			
Channel	Channel 23025	Channel 23095	Channel 23165
Tolerance (dBm)	20.0~24.0	20.0~24.0	20.0~24.0
3BW 50%RB			
Channel	Channel 23025	Channel 23095	Channel 23165
Tolerance (dBm)	20.0~24.0	20.0~24.0	20.0~24.0
3BW 1RB			
Channel	Channel 23025	Channel 23095	Channel 23165
Tolerance (dBm)	20.0~24.0	20.0~24.0	20.0~24.0
1.4BW 100%RB			
Channel	Channel 23017	Channel 23095	Channel 23173
Tolerance (dBm)	20.0~24.0	20.0~24.0	20.0~24.0
1.4BW 50%RB			
Channel	Channel 23017	Channel 23095	Channel 23173
Tolerance (dBm)	20.0~24.0	20.0~24.0	20.0~24.0
1.4BW 1RB			
Channel	Channel 23017	Channel 23095	Channel 23173
Tolerance (dBm)	20.0~24.0	20.0~24.0	20.0~24.0

**Band 13**

10BW 100%RB			
Channel	Channel 23230	Channel 23230	Channel 23230
Tolerance (dBm)	20.0~24.0	20.0~24.0	20.0~24.0
10BW 50%RB			
Channel	Channel 23230	Channel 23230	Channel 23230
Tolerance (dBm)	20.0~24.0	20.0~24.0	20.0~24.0
10BW 1RB			
Channel	Channel 23230	Channel 23230	Channel 23230
Tolerance (dBm)	20.0~24.0	20.0~24.0	20.0~24.0
5BW 100%RB			
Channel	Channel 23205	Channel 23230	Channel 23255
Tolerance (dBm)	20.0~24.0	20.0~24.0	20.0~24.0
5BW 50%RB			
Channel	Channel 23205	Channel 23230	Channel 23255
Tolerance (dBm)	20.0~24.0	20.0~24.0	20.0~24.0
5BW 1RB			
Channel	Channel 23205	Channel 23230	Channel 23255
Tolerance (dBm)	20.0~24.0	20.0~24.0	20.0~24.0

**Band 17**

10BW 100%RB			
Channel	Channel 23780	Channel 23790	Channel 23800
Tolerance (dBm)	19.0~23.0	19.0~23.0	19.0~23.0
10BW 50%RB			
Channel	Channel 23780	Channel 23790	Channel 23800
Tolerance (dBm)	19.0~23.0	19.0~23.0	19.0~23.0
10BW 1RB			
Channel	Channel 23780	Channel 23790	Channel 23800
Tolerance (dBm)	19.0~23.0	19.0~23.0	19.0~23.0
5BW 100%RB			
Channel	Channel 23755	Channel 23790	Channel 23825
Tolerance (dBm)	19.0~23.0	19.0~23.0	19.0~23.0
5BW 50%RB			
Channel	Channel 23755	Channel 23790	Channel 23825
Tolerance (dBm)	19.0~23.0	19.0~23.0	19.0~23.0
5BW 1RB			
Channel	Channel 23755	Channel 23790	Channel 23825
Tolerance (dBm)	19.0~23.0	19.0~23.0	19.0~23.0

## 6.2 GSM Measurement result

### GSM Measured Power

Mode	GSM850			GSM1900		
Channel	128	189	251	512	661	810
Frequency(MHz)	824.2	836.4	848.8	1850.2	1880.0	1909.8
Measured Power(dBm)	32.72	32.74	32.71	30.95	30.93	30.84

### GPRS Measured Power

Mode	GPRS850			GPRS1900		
Channel	128	189	251	512	661	810
Frequency(MHz)	824.2	836.4	848.8	1850.2	1880.0	1909.8
4Downlink1uplinkPower(dBm)	32.71	32.74	32.72	30.17	30.15	30.14
3Downlink2uplinkPower(dBm)	30.77	30.65	30.62	27.69	27.66	27.22
2Downlink3uplinkPower(dBm)	28.96	28.83	28.78	25.94	25.95	25.30
1Downlink4uplinkPower(dBm)	27.98	27.85	27.79	24.75	24.77	24.31

### GPRS Averaged Power

Mode	GPRS850			GPRS1900		
Channel	128	189	251	512	661	810
Frequency(MHz)	824.2	836.4	848.8	1850.2	1880.0	1909.8
4Downlink1uplinkPower(dBm)	23.68	23.71	23.69	21.14	21.12	21.11
3Downlink2uplinkPower(dBm)	24.75	24.63	24.60	21.67	21.64	21.20
2Downlink3uplinkPower(dBm)	24.70	24.57	24.52	21.68	21.69	21.04
1Downlink4uplinkPower(dBm)	24.97	24.84	24.78	21.74	21.76	21.30

### Division Factors (for Measured Power and Averaged Power):

To average the power, the division factor is as follows:

1TX-slot (4Downlink1uplink) = 1 transmit time slot out of 8 time slots=> conducted power divided by (8/1) => -9.03dB

2TX-slots(3Downlink2uplink) = 2 transmit time slots out of 8 time slots=> conducted power divided by (8/2) => -6.02dB

3TX-slots (2Downlink3uplink)= 3 transmit time slots out of 8 time slots=> conducted power divided by (8/3) => -4.26dB

4TX-slots (1Downlink4uplink)= 4 transmit time slots out of 8 time slots=> conducted power divided by (8/4) => -3.01dB

According to the conducted power as above, the body measurements are performed with 4Txslots (1Downlink4uplink) for GPRS.

### EGPRS Measured Power

Mode	EGPRS850 (GMSK)			EGPRS1900 (GMSK)		
	EGPRS850 (8PSK)			EGPRS1900 (8PSK)		
Channel	128	189	251	512	661	810
Frequency(MHz)	824.2	836.4	848.8	1850.2	1880.0	1909.8
4Downlink1uplinkPower(dBm)	32.70	32.72	32.71	30.14	30.18	30.16
	32.72	32.73	32.67	26.72	26.25	26.34
3Downlink2uplinkPower(dBm)	32.06	32.05	32.02	27.81	27.82	27.87
	32.03	32.06	32.01	24.53	24.55	24.59
2Downlink3uplinkPower(dBm)	30.31	30.27	30.27	26.11	26.11	26.14
	30.32	30.32	30.28	23.64	23.77	23.16
1Downlink4uplinkPower(dBm)	29.30	29.20	29.15	24.93	24.70	24.82
	29.29	29.25	29.12	21.32	20.80	20.78

### EGPRS Averaged Power

Mode	EGPRS850 (GMSK)			EGPRS1900 (GMSK)		
	EGPRS850 (8PSK)			EGPRS1900 (8PSK)		
Channel	128	189	251	512	661	810
Frequency(MHz)	824.2	836.4	848.8	1850.2	1880.0	1909.8
4Downlink1uplinkPower(dBm)	23.67	23.69	23.68	21.11	21.15	21.13
	23.69	23.70	23.64	17.69	17.22	17.31
3Downlink2uplinkPower(dBm)	26.04	26.03	26.00	21.79	21.80	21.85
	26.01	26.04	25.99	18.51	18.53	18.57
2Downlink3uplinkPower(dBm)	26.05	26.01	26.01	21.85	21.85	21.88
	26.06	26.06	26.02	19.38	19.51	18.90
1Downlink4uplinkPower(dBm)	26.29	26.19	26.14	21.92	21.69	21.81
	26.28	26.24	26.11	18.31	17.79	17.77

### Division Factors (for Measured Power and Averaged Power):

To average the power, the division factor is as follows:

1TX-slot (4Downlink1uplink) = 1 transmit time slot out of 8 time slots=> conducted power divided by (8/1) => -9.03dB

2TX-slots(3Downlink2uplink) = 2 transmit time slots out of 8 time slots=> conducted power divided by (8/2) => -6.02dB

3TX-slots (2Downlink3uplink) = 3 transmit time slots out of 8 time slots=> conducted power divided by (8/3) => -4.26dB

4TX-slots (1Downlink4uplink) = 4 transmit time slots out of 8 time slots=> conducted power divided by (8/4) => -3.01dB

According to the conducted power as above, the body measurements are performed with 4Txslots (1Downlink4uplink) for EGPRS (GMSK).



### 6.3 WCDMA Measurement result

The following procedures are according to FCC KDB Publication 941225 D01.  
Release 99

The following tests were completed according to the test requirements outlined in section 5.2 of the 3GPP TS34.121-1 specification. The DUT supports power Class 3, which has a nominal maximum output power of 24 dBm (+1.7/-3.7).

Mode	Subtest	Rel99
WCDMA General Settings	Loopback Mode	Test Mode 1
	Rel99 RMC	12.2kbps RMC
	Power Control Algorithm	Algorithm2
	$\beta_c/\beta_d$	8/15

#### Measured Results

Mode	Band2			Band5		
Channel	9262	9400	9538	4132	4183	4233
Frequency(MHz)	1852.4	1880	1907.6	826.4	836.4	846.6
RB test mode1+64kRMC(dBm)	22.81	22.92	23.07	22.24	22.30	22.37
RB test mode1+12.2kRMC(dBm)	22.95	23.08	23.15	22.36	22.43	22.41
RB test mode1+144kRMC(dBm)	22.78	22.87	23.02	22.26	22.21	22.22
RB test mode1+384kRMC(dBm)	22.88	22.95	23.12	22.23	22.23	22.26
AMR Voice test mode+12.2kRMC(dBm)	22.90	23.04	23.15	22.23	22.21	22.18

#### HSDPA

The following 4 Sub-tests were completed according to Release 5 procedures in section 5.2 of 3GPP TS34.121.

Sub-test	$\beta_c$	$\beta_d$	$\beta_d$ (SF)	$\beta_c\beta_d$	$\beta_{hs}^{(1)}$	CM(dB) <sup>(2)</sup>
1	2/15	15/15	64	2/15	4/15	0.0
2	12/15 <sup>(3)</sup>	15/15 <sup>(3)</sup>	64	12/15 <sup>(3)</sup>	24/15	1.0
3	15/15	8/15	64	15/18	30/15	1.5
4	15/15	4/15	64	15/4	30/15	1.5

Note1:  $\Delta_{ACK}$ ,  $\Delta_{NACK}$  and  $\Delta_{CQI} = 8 \Leftrightarrow A_{hs} = \beta_{hs}/\beta_c = 30/15 \Leftrightarrow \beta_{hs} = 30/15 * \beta_c$ .

Note2: CM=1 for  $\beta_c\beta_d = 12/15$ ,  $\beta_{hs}/\beta_c = 24/15$ .

Note3: For subtest 2 the  $\beta_c/\beta_d$  ratio of 12/15 for the TFC during the measurement period(TF1,TF0) is achieved by setting the signaled gain factors for the reference TFC(TF1,TF1) to  $\beta_c = 11/15$  and  $\beta_d = 15/15$ .

#### Measured Results

Mode	HSDPA Band 2			HSDPA Band 5		
Channel	9262	9400	9538	4132	4183	4233
Frequency(MHz)	1852.4	1880	1907.6	826.4	836.4	846.6
sub-test1(dBm)	21.30	21.40	21.30	20.70	20.70	20.70
sub-test2(dBm)	21.20	21.20	21.30	20.70	20.80	20.80
sub-test3(dBm)	21.40	21.30	21.20	20.10	20.30	20.30
sub-test4(dBm)	21.40	21.30	21.40	20.30	20.30	20.30



## HSPA (HSDPA & HSUPA)

The following 5 Sub-tests were completed according to Release 6 procedures in section 5.2 of 3GPP TS34.121.

Sub-test	$\beta_c$	$\beta_d$	$\beta_d$ (SF)	$\beta_c/\beta_d$	$\beta_{hs}^{(1)}$	$\beta_{ec}$	$\beta_{ed}$	$\beta_{ed}$ (SF)	$\beta_{ed}$ (codes)	CM <sup>(2)</sup> (dB)	MPR (dB)	AG <sup>(4)</sup> Index	E-TFCI
1	11/15 <sup>(3)</sup>	15/15 <sup>(3)</sup>	64	11/15 <sup>(3)</sup>	22/15	209/225	1039/225	4	1	1.0	2.0	20	75
2	6/15	15/15	64	6/15	12/15	12/15	94/75	4	1	3.0	2.0	12	67
3	15/15	9/15	64	15/9	30/15	30/15	$\beta_{ed1}:47/15$ $\beta_{ed2}:47/15$	4	2	2.0	2.0	15	92
4	2/15	15/15	64	2/15	4/15	2/15	56/75	4	1	3.0	2.0	17	71
5	15/15 <sup>(4)</sup>	15/15 <sup>(4)</sup>	64	15/15 <sup>(4)</sup>	30/15	24/15	134/15	4	1	1.0	2.0	21	81

Note1:  $\Delta_{ACK}$ ,  $\Delta_{NACK}$  and  $\Delta_{CQI} = 8 \Leftrightarrow A_{hs} = \beta_{hs}/\beta_c = 30/15 \Leftrightarrow \beta_{hs} = 30/15 * \beta_c$ .

Note2: CM=1 for  $\beta_c/\beta_d = 12/15, \beta_{hs}/\beta_c = 24/15$ . For all other combinations of DPDCH, DPCCH, HS-DPCCH, E-DPDCH and E-DPCCH the MPR is based on the relative CM difference.

Note3: For subtest 1 the  $\beta_c/\beta_d$  ratio of 11/15 for the TFC during the measurement period(TF1,TF0) is achieved by setting the signaled gain factors for the reference TFC(TF1,TF1) to  $\beta_c=10/15$  and  $\beta_d=15/15$ .

Note4: For subtest 5 the  $\beta_c/\beta_d$  ratio of 15/15 for the TFC during the measurement period(TF1,TF0) is achieved by setting the signaled gain factors for the reference TFC(TF1,TF1) to  $\beta_c=14/15$  and  $\beta_d=15/15$ .

NOTE5: Testing UE using E-DPDCH Physical layer category 1 Sub-test 3 is not required according to TS 25.306 Table 5.1g.

NOTE6:  $\beta_{ed}$  can not be set directly; it is set by Absolute Grant Value.

## Measured Results

Mode	HSUPA Band 2			HSUPA Band 5		
	Channel	9262	9400	9538	4132	4183
Frequency(MHz)	1852.4	1880	1907.6	826.4	836.4	846.6
sub-test1(dBm)	19.70	19.80	19.80	18.90	19.00	18.50
sub-test2(dBm)	19.70	19.70	19.90	18.90	19.00	18.40
sub-test3(dBm)	19.80	19.90	19.90	18.80	19.00	18.70
sub-test4(dBm)	19.60	19.60	19.70	18.40	18.40	18.00
sub-test5(dBm)	22.00	22.10	22.10	20.80	20.40	20.90

UMTS SAR was tested under RMC 12.2 kbps with HSPA Inactive per KDB Publication 941225 D01.

HSPA SAR was not required since the average output power of the HSPA subtests was not more than 0.25 dB higher than the RMC level and SAR was less than 1.2 W/kg.

## 6.4 LTE Measurement result

### Band 2

Test Frequency ID	Bandwidth (MHz)	N <sub>UL</sub>	Frequency of Uplink(MHz)	Modulation	RB Size	RB Offset	Test results (dBm)
Low Range	1.4	18607	1850.7	QPSK	1	Low	21.37
						Mid	21.49
						High	21.32
					50%	Low	21.31
						Mid	21.02
						High	21.22
				100%	---	21.31	
				16QAM	1	Low	21.21
						Mid	21.64
						High	21.19
					50%	Low	21.17
						Mid	21.90
	High	21.07					
	100%	---	21.31				
	3	18615	1851.5	QPSK	1	Low	21.09
						Mid	21.74
						High	21.10
					50%	Low	21.03
						Mid	21.10
						High	21.08
				100%	---	21.04	
				16QAM	1	Low	21.95
						Mid	21.73
						High	21.92
50%					Low	21.06	
					Mid	21.12	
	High	21.08					
100%	---	21.11					

Test Frequency ID	Bandwidth (MHz)	N <sub>UL</sub>	Frequency of Uplink(MHz)	Modulation	RB Size	RB Offset	Test results (dBm)
Low Range	5	18625	1852.5	QPSK	1	Low	21.14
						Mid	21.75
						High	21.04
					50%	Low	21.07
						Mid	21.03
						High	21.09
				100%	---	21.99	
				16QAM	1	Low	21.99
						Mid	21.75
						High	21.84
					50%	Low	21.05
						Mid	21.00
	High	21.03					
	100%	---	21.01				
	10	18650	1855	QPSK	1	Low	21.24
						Mid	21.25
						High	21.16
					50%	Low	21.06
						Mid	21.97
						High	21.03
				100%	---	21.99	
				16QAM	1	Low	21.06
						Mid	21.31
						High	21.93
50%					Low	21.09	
					Mid	21.00	
	High	21.03					
100%	---	20.96					

Test Frequency ID	Bandwidth (MHz)	N <sub>UL</sub>	Frequency of Uplink(MHz)	Modulation	RB Size	RB Offset	Test results (dBm)
Low Range	15	18675	1857.5	QPSK	1	Low	21.30
						Mid	21.95
						High	21.18
					50%	Low	21.02
						Mid	21.98
						High	21.96
				100%	---	21.04	
				16QAM	1	Low	21.10
						Mid	21.05
						High	21.98
					50%	Low	21.01
						Mid	20.97
	High	20.96					
	100%	---	21.00				
	20	18700	1860	QPSK	1	Low	22.50
						Mid	22.21
						High	22.17
					50%	Low	22.20
						Mid	21.96
						High	21.98
				100%	---	21.99	
				16QAM	1	Low	21.12
						Mid	21.32
						High	21.94
50%					Low	20.97	
					Mid	20.95	
	High	20.93					
100%	---	21.01					

Test Frequency ID	Bandwidth (MHz)	N <sub>UL</sub>	Frequency of Uplink(MHz)	Modulation	RB Size	RB Offset	Test results (dBm)
Mid Range	1.4	18900	1880	QPSK	1	Low	21.02
						Mid	21.11
						High	21.03
					50%	Low	21.80
						Mid	21.70
						High	21.88
				100%	---	21.92	
				16QAM	1	Low	21.89
						Mid	21.28
						High	21.91
					50%	Low	21.89
						Mid	21.54
	High	21.78					
	100%	---	20.97				
	3	18900	1880	QPSK	1	Low	21.06
						Mid	21.50
						High	21.97
					50%	Low	21.93
						Mid	21.87
						High	21.88
				100%	---	21.88	
				16QAM	1	Low	21.90
						Mid	21.76
						High	21.87
50%					Low	20.98	
					Mid	21.02	
	High	21.03					
100%	---	20.96					

Test Frequency ID	Bandwidth (MHz)	N <sub>UL</sub>	Frequency of Uplink(MHz)	Modulation	RB Size	RB Offset	Test results (dBm)
Mid Range	5	18900	1880	QPSK	1	Low	21.06
						Mid	21.60
						High	21.97
					50%	Low	21.93
						Mid	21.87
						High	21.88
				100%	---	21.80	
				16QAM	1	Low	21.94
						Mid	21.73
						High	21.85
					50%	Low	20.91
						Mid	20.87
	High	20.89					
	100%	---	20.92				
	10	18900	1880	QPSK	1	Low	21.15
						Mid	21.18
						High	21.07
					50%	Low	21.88
						Mid	21.86
						High	21.89
				100%	---	21.92	
				16QAM	1	Low	21.97
						Mid	21.34
						High	21.91
50%					Low	21.00	
					Mid	20.95	
	High	20.97					
100%	---	20.95					

Test Frequency ID	Bandwidth (MHz)	N <sub>UL</sub>	Frequency of Uplink(MHz)	Modulation	RB Size	RB Offset	Test results (dBm)
Mid Range	15	18900	1880	QPSK	1	Low	21.17
						Mid	21.85
						High	21.06
					50%	Low	21.97
						Mid	21.93
						High	21.92
				100%	---	21.92	
				16QAM	1	Low	21.99
						Mid	21.01
						High	21.89
					50%	Low	20.97
						Mid	20.95
	High	20.96					
	100%	---	20.96				
	20	18900	1880	QPSK	1	Low	22.50
						Mid	22.51
						High	22.50
					50%	Low	21.40
						Mid	21.50
						High	21.30
				100%	---	21.40	
				16QAM	1	Low	21.99
						Mid	21.28
						High	21.84
50%					Low	20.92	
					Mid	20.91	
	High	20.88					
100%	---	20.95					

Test Frequency ID	Bandwidth (MHz)	N <sub>UL</sub>	Frequency of Uplink(MHz)	Modulation	RB Size	RB Offset	Test results (dBm)	
High Range	5	19175	1907.5	QPSK	1	Low	21.87	
						Mid	21.49	
						High	21.79	
					50%	Low	21.81	
						Mid	21.73	
						High	21.79	
Test Frequency ID	Bandwidth (MHz)	N <sub>UL</sub>	Frequency of Uplink(MHz)	Modulation	RB Size	RB Offset	Test results (dBm)	
High Range	1.4	19193	1909.3	QPSK	1	Low	21.83	
						Mid	21.93	
						High	21.83	
					50%	Low	21.76	
						Mid	21.50	
						High	21.69	
				100%	---	21.81		
				16QAM	1	Low	21.67	
						Mid	21.09	
						High	21.69	
					50%	Low	21.63	
						Mid	21.37	
	High	21.53						
	100%	---	20.82					
	3	19185	1908.5	QPSK	1	Low	21.72	
						Mid	21.47	
						High	21.78	
					50%	Low	21.72	
						Mid	21.79	
						High	21.68	
					100%	---	21.71	
					16QAM	1	Low	21.59
							Mid	21.48
							High	21.62
50%						Low	20.71	
						Mid	20.83	
	High	20.75						
100%	---	20.78						



					100%	---	21.70	
				16QAM	1	Low	21.64	
						Mid	21.50	
						High	21.63	
				50%	Low	20.77		
					Mid	20.70		
					High	20.76		
				100%	---	20.73		
				10	19150	1905		QPSK
	Mid	21.97						
	High	21.86						
	50%	Low	21.85					
		Mid	21.78					
		High	21.79					
	100%	---	21.71					
	16QAM	1	Low					21.65
			Mid					21.03
			High	21.68				
50%	Low	20.82						
	Mid	20.76						
	High	20.77						
100%	---	20.68						

Test Frequency ID	Bandwidth (MHz)	N <sub>UL</sub>	Frequency of Uplink(MHz)	Modulation	RB Size	RB Offset	Test results (dBm)
High Range	15	19125	1902.5	QPSK	1	Low	21.99
						Mid	21.78
						High	21.90
					50%	Low	21.73
						Mid	21.66
						High	21.71
				100%	---	21.80	
				16QAM	1	Low	21.78
						Mid	21.79
						High	21.73
					50%	Low	20.70
						Mid	20.63
	High	20.71					
	100%	---	20.73				
	20	19100	1900	QPSK	1	Low	22.20
						Mid	21.99
						High	21.90
					50%	Low	22.00
						Mid	21.74
						High	21.70
				100%	---	21.71	
				16QAM	1	Low	21.88
						Mid	21.02
						High	21.66
50%					Low	20.74	
					Mid	20.68	
	High	20.69					
100%	---	20.73					

Band 4

Test Frequency ID	Bandwidth (MHz)	N <sub>UL</sub>	Frequency of Uplink(MHz)	Modulation	RB Size	RB Offset	Test results (dBm)
Low Range	1.4	19957	1710.7	QPSK	1	Low	22.47
						Mid	22.58
						High	22.45
					50%	Low	22.41
						Mid	22.10
						High	22.25
				100%	---	21.47	
				16QAM	1	Low	21.31
						Mid	21.73
						High	21.31
					50%	Low	21.27
						Mid	20.99
	High	21.19					
	100%	---	20.43				
	3	19965	1711.5	QPSK	1	Low	22.36
						Mid	23.03
						High	22.41
					50%	Low	21.36
						Mid	21.43
						High	21.37
				100%	---	21.38	
				16QAM	1	Low	21.26
						Mid	22.13
						High	21.26
50%					Low	20.31	
					Mid	20.39	
	High	20.40					
100%	---	20.42					

Test Frequency ID	Bandwidth (MHz)	N <sub>UL</sub>	Frequency of Uplink(MHz)	Modulation	RB Size	RB Offset	Test results (dBm)
Low Range	5	19975	1712.5	QPSK	1	Low	22.47
						Mid	23.10
						High	22.39
					50%	Low	21.39
						Mid	21.33
						High	21.38
				100%	---	21.27	
				16QAM	1	Low	21.32
						Mid	22.18
						High	21.31
					50%	Low	20.32
						Mid	20.26
	High	20.30					
	100%	---	20.28				
	10	20000	1715	QPSK	1	Low	22.45
						Mid	22.51
						High	22.45
					50%	Low	21.32
						Mid	21.26
						High	21.31
				100%	---	21.29	
				16QAM	1	Low	21.30
						Mid	21.68
						High	21.33
50%					Low	20.32	
					Mid	20.28	
	High	20.26					
100%	---	20.25					

Test Frequency ID	Bandwidth (MHz)	N <sub>UL</sub>	Frequency of Uplink(MHz)	Modulation	RB Size	RB Offset	Test results (dBm)
Low Range	15	20025	1717.5	QPSK	1	Low	22.43
						Mid	22.23
						High	22.49
					50%	Low	21.35
						Mid	21.31
						High	21.29
				100%	---	21.32	
				16QAM	1	Low	21.33
						Mid	21.41
	High	21.36					
	50%	Low	20.35				
		Mid	20.36				
		High	20.31				
	100%	---	20.30				
	20	20050	1720	QPSK	1	Low	22.46
						Mid	22.45
						High	22.46
					50%	Low	22.21
Mid						22.31	
High						22.29	
100%				---	22.26		
16QAM				1	Low	21.35	
					Mid	21.70	
	High	21.31					
	50%	Low	20.27				
		Mid	20.26				
		High	20.28				
100%	---	20.28					

Test Frequency ID	Bandwidth (MHz)	N <sub>UL</sub>	Frequency of Uplink(MHz)	Modulation	RB Size	RB Offset	Test results (dBm)
Mid Range	1.4	20175	1732.5	QPSK	1	Low	22.27
						Mid	22.39
						High	22.20
					50%	Low	22.21
						Mid	21.94
						High	22.10
				100%	---	21.23	
				16QAM	1	Low	21.13
						Mid	21.54
						High	21.12
					50%	Low	21.08
						Mid	20.80
	High	20.99					
	100%	---	20.21				
	3	20175	1732.5	QPSK	1	Low	22.25
						Mid	22.85
						High	22.24
					50%	Low	21.20
						Mid	21.27
						High	21.25
				100%	---	21.20	
				16QAM	1	Low	21.14
						Mid	21.96
						High	21.10
50%					Low	20.21	
					Mid	20.31	
	High	20.25					
100%	---	20.26					

Test Frequency ID	Bandwidth (MHz)	N <sub>UL</sub>	Frequency of Uplink(MHz)	Modulation	RB Size	RB Offset	Test results (dBm)
Mid Range	5	20175	1732.5	QPSK	1	Low	22.31
						Mid	22.82
						High	22.23
					50%	Low	21.25
						Mid	21.14
						High	21.23
				100%	---	21.14	
				16QAM	1	Low	21.19
						Mid	21.95
						High	21.07
					50%	Low	20.17
						Mid	20.10
	High	20.14					
	100%	---	20.16				
	10	20175	1732.5	QPSK	1	Low	22.40
						Mid	22.37
						High	22.31
					50%	Low	21.18
						Mid	21.11
						High	21.19
				100%	---	21.16	
				16QAM	1	Low	21.26
						Mid	21.54
						High	21.12
50%					Low	20.21	
					Mid	20.14	
	High	20.18					
100%	---	20.12					

Test Frequency ID	Bandwidth (MHz)	N <sub>UL</sub>	Frequency of Uplink(MHz)	Modulation	RB Size	RB Offset	Test results (dBm)
Mid Range	15	20175	1732.5	QPSK	1	Low	22.86
						Mid	22.06
						High	22.32
					50%	Low	21.18
						Mid	21.13
						High	21.14
				100%	---	21.16	
				16QAM	1	Low	21.23
						Mid	21.22
						High	21.11
					50%	Low	20.14
						Mid	20.12
	High	20.09					
	100%	---	20.14				
	20	20175	1732.5	QPSK	1	Low	22.66
						Mid	22.36
						High	22.39
					50%	Low	22.59
						Mid	22.57
						High	22.58
				100%	---	22.54	
				16QAM	1	Low	21.30
						Mid	21.52
						High	21.13
50%					Low	20.18	
					Mid	20.13	
	High	20.09					
100%	---	20.19					



Test Frequency ID	Bandwidth (MHz)	N <sub>UL</sub>	Frequency of Uplink(MHz)	Modulation	RB Size	RB Offset	Test results (dBm)
High Range	1.4	20393	1754.3	QPSK	1	Low	22.38
						Mid	22.45
						High	22.37
					50%	Low	22.30
						Mid	22.02
						High	22.21
				100%	---	21.33	
				16QAM	1	Low	21.25
						Mid	21.63
						High	21.23
					50%	Low	21.20
						Mid	20.88
	High	21.08					
	100%	---	20.34				
	3	20385	1753.5	QPSK	1	Low	22.37
						Mid	23.00
						High	22.40
					50%	Low	21.30
						Mid	21.34
						High	21.30
				100%	---	21.34	
				16QAM	1	Low	21.27
						Mid	22.09
						High	21.26
50%					Low	20.32	
					Mid	20.39	
	High	20.36					
100%	---	20.38					

Test Frequency ID	Bandwidth (MHz)	N <sub>UL</sub>	Frequency of Uplink(MHz)	Modulation	RB Size	RB Offset	Test results (dBm)
High Range	5	20375	1752.5	QPSK	1	Low	22.40
						Mid	22.99
						High	22.36
					50%	Low	21.38
						Mid	21.30
						High	21.29
				100%	---	21.20	
				16QAM	1	Low	21.22
						Mid	22.09
						High	21.20
					50%	Low	20.27
						Mid	20.23
	High	20.25					
	100%	---	20.26				
	10	20350	1750	QPSK	1	Low	22.38
						Mid	22.46
						High	22.51
					50%	Low	21.23
						Mid	21.24
						High	21.23
				100%	---	21.25	
				16QAM	1	Low	21.27
						Mid	21.62
						High	21.30
50%					Low	20.29	
					Mid	20.27	
	High	20.33					
100%	---	20.26					

Test Frequency ID	Bandwidth (MHz)	N <sub>UL</sub>	Frequency of Uplink(MHz)	Modulation	RB Size	RB Offset	Test results (dBm)
High Range	15	20325	1747.5	QPSK	1	Low	22.73
						Mid	22.21
						High	22.53
					50%	Low	21.27
						Mid	21.25
						High	21.31
				100%	---	21.30	
				16QAM	1	Low	21.21
						Mid	21.36
	High	21.37					
	50%	Low	20.21				
		Mid	20.23				
		High	20.32				
	100%	---	20.29				
	20	20300	1745	QPSK	1	Low	22.60
						Mid	22.47
						High	22.50
					50%	Low	22.51
Mid						22.29	
High						22.34	
100%				---	22.29		
16QAM				1	Low	21.25	
					Mid	21.63	
	High	21.34					
	50%	Low	20.21				
		Mid	20.23				
		High	20.27				
100%	---	20.25					

Band 5

Test Frequency ID	Bandwidth (MHz)	N <sub>UL</sub>	Frequency of Uplink(MHz)	Modulation	RB Size	RB Offset	Test results (dBm)
Low Range	1.4	20407	824.7	QPSK	1	Low	22.20
						Mid	22.20
						High	22.20
					50%	Low	22.20
						Mid	22.20
						High	22.20
				100%	---	22.20	
				16QAM	1	Low	21.20
						Mid	21.20
						High	21.20
					50%	Low	21.20
						Mid	21.20
	High	21.10					
	100%	---	21.10				
	3	20415	825.5	QPSK	1	Low	23.30
						Mid	22.00
						High	22.00
					50%	Low	22.00
						Mid	22.00
						High	22.00
				100%	---	22.00	
				16QAM	1	Low	21.00
						Mid	21.00
						High	21.00
50%					Low	21.00	
					Mid	21.00	
	High	21.00					
100%	---	21.00					

Test Frequency ID	Bandwidth (MHz)	N <sub>UL</sub>	Frequency of Uplink(MHz)	Modulation	RB Size	RB Offset	Test results (dBm)
Low Range	5	29425	826.5	QPSK	1	Low	22.10
						Mid	22.10
						High	22.10
					50%	Low	22.10
						Mid	22.10
						High	22.10
				100%	---	22.10	
				16QAM	1	Low	21.30
						Mid	21.30
						High	21.30
					50%	Low	21.30
						Mid	21.30
	High	21.20					
	100%	---	21.20				
	10	20450	829	QPSK	1	Low	22.20
						Mid	22.20
						High	22.10
					50%	Low	22.20
						Mid	22.10
						High	22.10
				100%	---	22.10	
				16QAM	1	Low	21.10
						Mid	21.10
						High	21.10
50%					Low	21.10	
					Mid	21.10	
	High	21.10					
100%	---	21.10					

Test Frequency ID	Bandwidth (MHz)	N <sub>UL</sub>	Frequency of Uplink(MHz)	Modulation	RB Size	RB Offset	Test results (dBm)
Mid Range	1.4	20525	836.5	QPSK	1	Low	22.20
						Mid	22.10
						High	22.10
					50%	Low	22.20
						Mid	22.10
						High	22.10
				100%	---	22.10	
				16QAM	1	Low	21.20
						Mid	21.20
						High	21.20
					50%	Low	21.20
						Mid	21.20
	High	21.20					
	100%	---	21.20				
	3	20525	836.5	QPSK	1	Low	22.10
						Mid	22.10
						High	22.10
					50%	Low	22.10
						Mid	22.10
						High	22.10
				100%	---	22.10	
				16QAM	1	Low	21.10
						Mid	21.10
						High	21.10
50%					Low	21.10	
					Mid	21.10	
	High	21.10					
100%	---	21.10					

Test Frequency ID	Bandwidth (MHz)	N <sub>UL</sub>	Frequency of Uplink(MHz)	Modulation	RB Size	RB Offset	Test results (dBm)
Mid Range	5	20525	836.5	QPSK	1	Low	22.30
						Mid	22.30
						High	22.30
					50%	Low	22.30
						Mid	22.30
						High	22.30
				100%	---	22.30	
				16QAM	1	Low	21.50
						Mid	21.50
						High	21.50
					50%	Low	21.40
						Mid	21.40
	High	21.40					
	100%	---	21.40				
	10	20525	836.5	QPSK	1	Low	22.20
						Mid	22.40
						High	22.10
					50%	Low	22.20
						Mid	22.38
						High	22.10
				100%	---	22.10	
				16QAM	1	Low	21.00
						Mid	21.10
						High	21.10
50%					Low	21.10	
					Mid	21.00	
	High	21.10					
100%	---	21.10					

Test Frequency ID	Bandwidth (MHz)	N <sub>UL</sub>	Frequency of Uplink(MHz)	Modulation	RB Size	RB Offset	Test results (dBm)
High Range	1.4	20643	848.3	QPSK	1	Low	22.50
						Mid	23.00
						High	22.60
					50%	Low	22.00
						Mid	22.10
						High	22.00
				100%	---	22.00	
				16QAM	1	Low	21.10
						Mid	21.10
	High	21.10					
	50%	Low	21.10				
		Mid	21.10				
		High	21.10				
	100%	---	21.10				
	3	20635	847.5	QPSK	1	Low	23.00
						Mid	22.50
						High	22.60
					50%	Low	23.00
Mid						22.70	
High						22.70	
100%				---	22.10		
16QAM				1	Low	21.00	
					Mid	21.00	
	High	21.00					
	50%	Low	21.00				
		Mid	21.00				
		High	21.00				
100%	---	21.00					



Test Frequency ID	Bandwidth (MHz)	N <sub>UL</sub>	Frequency of Uplink(MHz)	Modulation	RB Size	RB Offset	Test results (dBm)	
High Range	5	20625	846.5	QPSK	1	Low	22.20	
						Mid	22.10	
						High	22.10	
					50%	Low	22.10	
						Mid	22.10	
						High	22.10	
				100%	---	22.10		
				16QAM	1	Low	21.20	
						Mid	21.20	
	High	21.20						
	50%	Low	21.20					
		Mid	21.20					
		High	21.20					
	100%	---	21.20					
	10	20600	844	QPSK	1	Low	22.10	
						Mid	22.10	
						High	22.10	
					50%	Low	22.10	
						Mid	22.10	
						High	22.10	
					100%	---	22.10	
					16QAM	1	Low	21.10
							Mid	21.10
				High			21.10	
50%				Low		21.10		
				Mid		21.00		
				High		21.10		
100%				---	21.10			

**Band 12**

Test Frequency ID	Bandwidth (MHz)	N <sub>UL</sub>	Frequency of Uplink(MHz)	Modulation	RB Size	RB Offset	Test results (dBm)
Low Range	1.4	23017	699.7	QPSK	1	Low	23.00
						Mid	23.00
						High	23.00
					50%	Low	23.00
						Mid	23.00
						High	23.00
				100%	---	23.00	
				16QAM	1	Low	22.00
						Mid	22.00
						High	22.00
					50%	Low	21.90
						Mid	22.00
	High	21.90					
	100%	---	21.90				
	3	23025	700.5	QPSK	1	Low	23.70
						Mid	22.30
						High	22.30
					50%	Low	22.30
						Mid	22.20
						High	22.30
				100%	---	22.20	
				16QAM	1	Low	21.20
						Mid	21.20
						High	21.20
50%					Low	21.20	
					Mid	21.20	
	High	21.20					
100%	---	21.20					

Test Frequency ID	Bandwidth (MHz)	N <sub>UL</sub>	Frequency of Uplink(MHz)	Modulation	RB Size	RB Offset	Test results (dBm)
Low Range	5	23035	701.5	QPSK	1	Low	23.10
						Mid	23.10
						High	23.10
					50%	Low	23.10
						Mid	23.10
						High	23.10
				100%	---	23.10	
				16QAM	1	Low	22.20
						Mid	22.20
						High	22.20
					50%	Low	22.20
						Mid	22.20
	High	22.20					
	100%	---	22.20				
	10	23060	704	QPSK	1	Low	22.80
						Mid	22.80
						High	22.80
					50%	Low	22.80
						Mid	22.80
						High	22.80
				100%	---	22.80	
				16QAM	1	Low	21.70
						Mid	21.70
						High	21.70
50%					Low	21.70	
					Mid	21.70	
	High	21.70					
100%	---	21.70					

Test Frequency ID	Bandwidth (MHz)	N <sub>UL</sub>	Frequency of Uplink(MHz)	Modulation	RB Size	RB Offset	Test results (dBm)
Mid Range	1.4	23095	707.5	QPSK	1	Low	23.10
						Mid	23.10
						High	23.10
					50%	Low	23.10
						Mid	23.10
						High	23.10
				100%	---	23.10	
				16QAM	1	Low	22.10
						Mid	22.10
	High	22.10					
	50%	Low	22.10				
		Mid	22.10				
		High	22.10				
	100%	---	22.10				
	3	23095	707.5	QPSK	1	Low	23.00
						Mid	23.00
						High	23.00
					50%	Low	23.00
Mid						23.00	
High						23.00	
100%				---	23.00		
16QAM				1	Low	22.00	
					Mid	22.00	
	High	22.00					
	50%	Low	22.00				
		Mid	22.00				
		High	22.00				
100%	---	22.00					

Test Frequency ID	Bandwidth (MHz)	N <sub>UL</sub>	Frequency of Uplink(MHz)	Modulation	RB Size	RB Offset	Test results (dBm)
Mid Range	5	23095	707.5	QPSK	1	Low	23.40
						Mid	23.40
						High	23.40
					50%	Low	23.40
						Mid	23.40
						High	23.40
				100%	---	23.40	
				16QAM	1	Low	22.60
						Mid	22.60
						High	22.60
					50%	Low	22.60
						Mid	22.60
	High	22.60					
	100%	---	22.60				
	10	23095	707.5	QPSK	1	Low	23.20
						Mid	23.20
						High	23.20
					50%	Low	23.20
						Mid	23.20
						High	23.20
				100%	---	23.20	
				16QAM	1	Low	22.10
						Mid	22.20
						High	22.10
50%					Low	22.10	
					Mid	22.10	
	High	22.10					
100%	---	22.10					

Test Frequency ID	Bandwidth (MHz)	N <sub>UL</sub>	Frequency of Uplink(MHz)	Modulation	RB Size	RB Offset	Test results (dBm)
High Range	1.4	23173	715.3	QPSK	1	Low	23.00
						Mid	22.90
						High	22.90
					50%	Low	22.90
						Mid	22.90
						High	22.90
				100%	---	22.90	
				16QAM	1	Low	22.00
						Mid	22.00
						High	22.00
					50%	Low	22.00
						Mid	22.00
	High	22.00					
	100%	---	22.00				
	3	23165	714.5	QPSK	1	Low	23.00
						Mid	22.90
						High	22.90
					50%	Low	22.90
						Mid	22.90
						High	23.00
				100%	---	22.90	
				16QAM	1	Low	21.90
						Mid	21.90
						High	21.90
50%					Low	21.90	
					Mid	21.90	
	High	21.90					
100%	---	21.90					

Test Frequency ID	Bandwidth (MHz)	N <sub>UL</sub>	Frequency of Uplink(MHz)	Modulation	RB Size	RB Offset	Test results (dBm)
High Range	5	23155	713.5	QPSK	1	Low	23.50
						Mid	23.50
						High	23.50
					50%	Low	23.50
						Mid	23.50
						High	23.50
				100%	---	23.50	
				16QAM	1	Low	22.60
						Mid	22.60
						High	22.60
					50%	Low	22.60
						Mid	22.60
	High	22.60					
	100%	---	22.60				
	10	23130	711	QPSK	1	Low	23.20
						Mid	23.20
						High	23.20
					50%	Low	23.20
						Mid	23.20
						High	23.20
				100%	---	23.20	
				16QAM	1	Low	22.10
						Mid	22.10
						High	22.10
50%					Low	22.10	
					Mid	22.10	
	High	22.10					
100%	---	22.20					

Band 13

Test Frequency ID	Bandwidth (MHz)	N <sub>UL</sub>	Frequency of Uplink(MHz)	Modulation	RB Size	RB Offset	Test results (dBm)
Low Range	5	23205	779.5	QPSK	1	Low	23.00
						Mid	23.00
						High	23.00
					50%	Low	23.00
						Mid	23.00
						High	23.00
				100%	---	23.00	
				16QAM	1	Low	22.20
						Mid	22.20
						High	22.20
					50%	Low	22.20
						Mid	22.20
	High	22.20					
	100%	---	23.00				
	10	23230	782	QPSK	1	Low	22.90
						Mid	22.80
						High	22.80
					50%	Low	22.80
						Mid	22.80
						High	22.80
				100%	---	22.80	
				16QAM	1	Low	21.80
						Mid	21.80
						High	21.80
50%					Low	21.80	
					Mid	21.80	
	High	21.80					
100%	---	21.80					



Test Frequency ID	Bandwidth (MHz)	N <sub>UL</sub>	Frequency of Uplink(MHz)	Modulation	RB Size	RB Offset	Test results (dBm)
Mid Range	5	23230	782	QPSK	1	Low	23.50
						Mid	23.50
						High	23.50
					50%	Low	23.50
						Mid	23.50
						High	23.50
				100%	---	23.50	
				16QAM	1	Low	22.70
						Mid	22.70
						High	22.70
					50%	Low	22.70
						Mid	22.70
	High	22.70					
	100%	---	22.70				
	10	23230	782	QPSK	1	Low	22.80
						Mid	22.80
						High	22.80
					50%	Low	22.80
						Mid	22.80
						High	22.80
				100%	---	22.80	
				16QAM	1	Low	21.80
						Mid	21.80
						High	21.80
50%					Low	21.80	
					Mid	21.80	
	High	21.90					
100%	---	21.80					

Test Frequency ID	Bandwidth (MHz)	N <sub>UL</sub>	Frequency of Uplink(MHz)	Modulation	RB Size	RB Offset	Test results (dBm)
High Range	5	23255	784.5	QPSK	1	Low	23.50
						Mid	23.50
						High	23.50
					50%	Low	23.50
						Mid	23.50
						High	23.50
				100%	---	23.50	
				16QAM	1	Low	22.70
						Mid	22.70
						High	22.70
					50%	Low	22.70
						Mid	22.70
	High	22.70					
	100%	---	22.70				
	10	23230	782	QPSK	1	Low	22.80
						Mid	22.80
						High	22.80
					50%	Low	22.80
						Mid	22.80
						High	22.80
				100%	---	22.80	
				16QAM	1	Low	21.80
						Mid	21.80
						High	21.80
50%					Low	21.80	
					Mid	21.80	
	High	21.80					
100%	---	21.80					

**Band 17**

Test Frequency ID	Bandwidth (MHz)	N <sub>UL</sub>	Frequency of Uplink(MHz)	Modulation	RB Size	RB Offset	Test results (dBm)
Low Range	5	23755	706.5	QPSK	1	Low	22.10
						Mid	22.10
						High	22.10
					50%	Low	22.10
						Mid	22.10
						High	22.10
				100%	---	22.10	
				16QAM	1	Low	21.20
						Mid	21.20
						High	21.20
					50%	Low	21.20
						Mid	21.20
	High	21.20					
	100%	---	21.20				
	10	23780	709	QPSK	1	Low	22.30
						Mid	22.30
						High	22.30
					50%	Low	22.30
						Mid	22.30
						High	22.30
				100%	---	22.30	
				16QAM	1	Low	21.20
						Mid	21.20
						High	21.20
50%					Low	21.20	
					Mid	21.20	
	High	21.20					
100%	---	21.20					

Test Frequency ID	Bandwidth (MHz)	N <sub>UL</sub>	Frequency of Uplink(MHz)	Modulation	RB Size	RB Offset	Test results (dBm)	
Mid Range	5	23790	710	QPSK	1	Low	22.70	
						Mid	22.70	
						High	22.70	
					50%	Low	22.70	
						Mid	22.70	
						High	22.70	
					100%	---	22.70	
					16QAM	1	Low	21.90
							Mid	21.90
				High			21.90	
				50%		Low	21.90	
						Mid	21.90	
	High	21.90						
	100%	---	21.90					
	10	23790	710	QPSK		1	Low	22.40
							Mid	22.40
					High		22.40	
					50%	Low	22.40	
						Mid	22.40	
						High	22.40	
					100%	---	22.40	
					16QAM	1	Low	21.40
							Mid	21.40
				High			21.40	
50%				Low		21.40		
				Mid		21.40		
	High	21.40						
100%	---	21.40						

Test Frequency ID	Bandwidth (MHz)	N <sub>UL</sub>	Frequency of Uplink(MHz)	Modulation	RB Size	RB Offset	Test results (dBm)	
High Range	5	23825	713.5	QPSK	1	Low	22.60	
						Mid	22.60	
						High	22.60	
					50%	Low	22.60	
						Mid	22.60	
						High	22.60	
					100%	---	22.60	
					16QAM	1	Low	21.80
							Mid	21.80
				High			21.80	
				50%		Low	21.80	
						Mid	21.80	
	High	21.80						
	100%	---	21.80					
	10	23800	711	QPSK		1	Low	22.50
							Mid	22.50
					High		22.50	
					50%	Low	22.50	
						Mid	22.50	
						High	22.50	
					100%	---	22.50	
					16QAM	1	Low	21.50
							Mid	21.50
				High			21.50	
50%				Low		21.50		
				Mid		21.50		
	High	21.50						
100%	---	21.50						

### 6.5 Bluetooth Measurement result

Modulation type	Test Result (dBm)		
	2402MHz(Ch0)	2441MHz(Ch39)	2480MHz(Ch78)
GFSK	8.24	9.14	6.25
$\pi/4$ DQPSK	9.13	9.36	7.42
8DPSK	8.95	9.88	7.66
GFSK(BLE)	2402MHz(Ch0)	2440MHz(Ch19)	2480MHz(Ch39)
	-0.42	0.02	-0.91

Modulation type	Test Result (mW)		
	2402MHz(Ch0)	2441MHz(Ch39)	2480MHz(Ch78)
GFSK	6.67	8.20	4.22
$\pi/4$ DQPSK	8.18	8.63	5.52
8DPSK	7.85	9.73	5.83
GFSK(BLE)	2402MHz(Ch0)	2440MHz(Ch19)	2480MHz(Ch39)
	0.91	1.00	0.81

## 6.6 Wi-Fi Measurement result

Modulation type		Average power output (dBm)		
		2412MHz (Ch1)	2437MHz (Ch6)	2462MHz (Ch11)
11b	1 Mbps	<b>14.15</b>	<b>15.62</b>	<b>15.45</b>
	2 Mbps	14.05	15.47	15.13
	5.5 Mbps	13.82	15.32	14.99
	11 Mbps	13.74	15.22	14.75
11g	6 Mbps	<b>10.8</b>	<b>12.19</b>	<b>11.25</b>
	9 Mbps	10.42	11.92	10.92
	12 Mbps	10.04	11.45	10.47
	18 Mbps	9.76	11.11	10.02
	24 Mbps	9.31	10.74	9.65
	36 Mbps	9.02	10.42	9.12
	48 Mbps	8.67	10.01	9.01
	54 Mbps	8.52	9.8	8.95
11n HT20	6.5 Mbps	<b>9.83</b>	<b>11.12</b>	<b>10.32</b>
	13 Mbps	9.43	10.87	10.01
	19.5 Mbps	9.12	10.32	9.64
	26 Mbps	8.72	9.94	9.13
	39 Mbps	8.44	9.39	8.77
	52 Mbps	8.03	9.02	8.21
	58.5 Mbps	7.87	8.99	8.03
	65 Mbps	7.37	8.73	7.86

Modulation type		Average power output (mW)		
		2412MHz (Ch1)	2437MHz (Ch6)	2462MHz (Ch11)
11b	1 Mbps	26.00	36.48	35.08
	2 Mbps	25.41	35.24	32.58
	5.5 Mbps	24.10	34.04	31.55
	11 Mbps	23.66	33.27	29.85
11g	6 Mbps	12.02	16.56	13.34
	9 Mbps	11.02	15.56	12.36
	12 Mbps	10.09	13.96	11.14
	18 Mbps	9.46	12.91	10.05
	24 Mbps	8.53	11.86	9.23
	36 Mbps	7.98	11.02	8.17
	48 Mbps	7.36	10.02	7.96
	54 Mbps	7.11	9.55	7.85
11n HT20	6.5 Mbps	9.62	12.94	10.76
	13 Mbps	8.77	12.22	10.02
	19.5 Mbps	8.17	10.76	9.20
	26 Mbps	7.45	9.86	8.18
	39 Mbps	6.98	8.69	7.53
	52 Mbps	6.35	7.98	6.62
	58.5 Mbps	6.12	7.93	6.35
	65 Mbps	5.46	7.46	6.11



## 6.7 Standalone SAR Test Exclusion Considerations

Standalone 1-g head or body SAR evaluation by measurement or numerical simulation is not required when the corresponding SAR Exclusion Threshold condition, listed below, is satisfied.

### **SAR Test Exclusion Thresholds for 100 MHz – 6 GHz and $\leq 50$ mm**

According to the KDB447498 4.3.1 (1)

For 100 MHz to 6 GHz and test separation distances  $\leq 50$  mm, the 1-g and 10-g SAR test exclusion thresholds are determined by the following:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f} (\text{GHz})] \leq 3.0$  for 1-g SAR, where

- $f(\text{GHz})$  is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is  $\leq 50$  mm, and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is  $< 5$  mm, a distance of 5 mm is applied to determine SAR test exclusion.

This is equivalent to  $[(\text{max. power of channel, including tune-up tolerance, mW}) / (60 / \sqrt{f} (\text{GHz}) \text{ mW})] \cdot [20 \text{ mm} / (\text{min. test separation distance, mm})] \leq 1.0$  for 1-g SAR; also see Appendix A for approximate exclusion threshold values at selected frequencies and distances.

According to the KDB447498 appendix A

Approximate SAR Test Exclusion Power Thresholds at Selected Frequencies and Test Separation Distances are illustrated in the following Table.

MHz	5	10	15	20	25	mm
150	39	77	116	155	194	<i>SAR Test Exclusion Threshold (mW)</i>
300	27	55	82	110	137	
450	22	45	67	89	112	
835	16	33	49	66	82	
900	16	32	47	63	79	
1500	12	24	37	49	61	
1900	11	22	33	44	54	
2450	10	19	29	38	48	
3600	8	16	24	32	40	
5200	7	13	20	26	33	
5400	6	13	19	26	32	
5800	6	12	19	25	31	

#### Summary of Transmitters

Band/Mode	Max.RF output power (mW)	SAR test exclusion Threshold (mW)	SAR Required
(2.4~2.4835)GHz Bluetooth	9.73	10	No
(2.4~2.4835)GHz WLAN	36.48	10	Yes

## 6.8 RF exposure conditions

Refer to the follow picture“Antenna Locations & Separation Distances” for the specific details of the antenna-to-antenna and antenna-to-edge(s) distances.



### 6.8.1 Head Exposure Conditions

#### For WWAN,

Test Configurations	SAR Required	Note
Left Touch	yes	/
Left Tilt (15°)	yes	/
Right Touch	yes	/
Right Tilt (15°)	yes	/

### 6.8.2 Body-worn Accessory Exposure conditions

#### For WWAN

Test Configurations	SAR Required	Note
Rear	yes	/
Front	yes	/

#### For WiFi

Test Configurations	SAR Required	Note
Rear	yes	/
Front	yes	/

### 6.8.3 Hotspot Exposure Conditions

#### For WWAN

Test Configurations	Antenna-to-edge/surface	SAR Required
Rear	<25 mm	Yes
Front	<25 mm	Yes
Edge 1 (top)	122 mm	No
Edge 2 (Bottom)	0 mm	Yes
Edge 3(Right)	0 mm	Yes
Edge 4(Left )	0 mm	Yes

#### For Wi-Fi

Test Configurations	Antenna-to-edge/surface	SAR Required
Rear	<25 mm	Yes
Front	<25 mm	Yes
Edge 1 (top)	0 mm	Yes
Edge 2 (Bottom)	126 mm	No
Edge 3(Right)	0 mm	Yes
Edge 4(Left )	35 mm	No

## 6.9 System Checking

The manufacturer calibrates the probes annully. Dielectric parameters of the tissue simulants were measured every day using the dielectric probe kit and the network analyser. A system check measurement was made following the determination of the dielectric parameters of the simulant, using the dipole validation kit. A power level of 250 mW was supplied to the dipole antenna, which was placed under the flat section of the twin SAM phantom. The system checking results (dielectric parameters and SAR values) are given in the table below.

Date Tested	System dipole	T.S. Liquid	SAR measured (normalized to 1W)		Target (Ref.Value)	Delta (%)	Tolerance (%)
2017.04.05	D835V2	Head	1g	9.28	9.54	2.73	±10
2017.04.08	D835V2	Body	1g	9.52	9.61	0.94	±10
2017.04.08	D1750V2	Head	1g	37.76	36.90	2.33	±10
2017.04.06	D1750V2	Body	1g	37.84	37.10	1.99	±10
2017.04.01	D1900V2	Head	1g	39.98	41.00	2.73	±10
2017.04.06	D1900V2	Body	1g	39.08	39.90	2.06	±10
2017.04.09	D2450V2	Head	1g	53.60	52.30	2.49	±10
2017.04.09	D2450V2	Body	1g	50.40	51.20	1.56	±10
2017.04.09	D2600V2	Head	1g	57.20	58.40	2.05	±10
2017.04.05	D2600V2	Body	1g	56.80	57.60	1.39	±10

Plots of the system checking scans are given in Appendix A.

Tissue Simulants used in the Measurements

For the measurement of the following parameters the SPEAG DAKS-3.5 dielectric parameter probe is used, representing the open-ended coaxial probe measurement procedure.

Date Tested	Freq.(MHz)	Liquid parameters	measured	Target	Delta(%)	Tolerance(%)
2017.04.05	Head 835	$\epsilon_r$	41.41	41.50	0.22	$\pm 5$
		$\sigma$ [S/m]	0.89	0.90	1.11	$\pm 5$
2017.04.08	Body 835	$\epsilon_r$	54.88	55.20	0.58	$\pm 5$
		$\sigma$ [S/m]	0.96	0.97	1.03	$\pm 5$
2017.04.08	Head 1750	$\epsilon_r$	39.75	40.10	0.63	$\pm 5$
		$\sigma$ [S/m]	1.38	1.37	1.43	$\pm 5$
2017.04.06	Body 1750	$\epsilon_r$	52.36	53.4	1.95	$\pm 5$
		$\sigma$ [S/m]	1.46	1.49	2.01	$\pm 5$
2017.04.01	Head 1900	$\epsilon_r$	39.57	40.00	1.08	$\pm 5$
		$\sigma$ [S/m]	1.38	1.40	1.43	$\pm 5$
2017.04.06	Body 1900	$\epsilon_r$	52.59	53.30	1.33	$\pm 5$
		$\sigma$ [S/m]	1.49	1.52	1.97	$\pm 5$
2017.04.09	Head 2450	$\epsilon_r$	38.67	39.20	1.35	$\pm 5$
		$\sigma$ [S/m]	1.78	1.80	1.11	$\pm 5$
2017.04.09	Body 2450	$\epsilon_r$	51.98	52.70	1.37	$\pm 5$
		$\sigma$ [S/m]	1.93	1.95	1.03	$\pm 5$
2017.04.09	Head 2600	$\epsilon_r$	38.90	39.00	0.26	$\pm 5$
		$\sigma$ [S/m]	1.97	1.96	0.51	$\pm 5$
2017.04.05	Body 2600	$\epsilon_r$	52.23	52.50	0.51	$\pm 5$
		$\sigma$ [S/m]	2.13	2.16	1.39	$\pm 5$

## 6.10 SAR TEST RESULT

In order to determine the largest value of the peak spatial-average SAR of a handset, all device positions, configurations, and operational modes should be tested for each frequency band according to Steps 1 to 3 below.

Step 1: The tests should be performed at the channel that is closest to the center of the transmit frequency band.

a) All device positions (cheek and tilt, for both left and right sides of the SAM phantom),  
b) All configurations for each device position in a), e.g., antenna extended and retracted, and  
c) All operational modes for each device position in item a) and configuration in item b) in each frequency band, e.g., analog and digital, If more than three frequencies need to be tested (i.e.,  $N_c > 3$ ), then all frequencies, configurations and modes shall be tested for all of the above test conditions.

Step 2: For the condition providing the highest peak spatial-average SAR determined in Step 1 for each frequency, perform all tests at all other test frequency channels, e.g., lowest and highest frequencies. In addition, for all other conditions (device position, configuration, and operational mode) where the peak spatial-average SAR value determined in Step 1 is within 3 dB of the applicable SAR limit, it is recommended that all other test frequencies should be tested as well.

Step 3: Examine all data to determine the largest value of the peak.

Note:

1. Per KDB 447498 D01v05, the reported SAR is the measured SAR value adjusted for maximum tune-up tolerance.

Scaling Factor = tune-up limit power (mW) / EUT RF power (mW), where tune-up limit is the maximum rated power among all production units.

Reported SAR (W/kg) = Measured SAR (W/kg)\* Scaling Factor

2. Per KDB 447498 D01v05, for each exposure position, if the highest output channel reported SAR  $\leq 0.8$ W/kg, other channels SAR testing are not necessary.

3. In the report the test position "Mobile phone screen Towards Ground" abbreviated as "TG", and "Mobile phone screen Towards Phantom" abbreviated as "TP".

The measured and reported Head/body SAR values for the test device are tabulated below:

**Mode: GSM 850**

fL(MHz)=824.2MHz

fM(MHz)=836.5MHz

fH(MHz)= 848.8MHz

SAR Values ( Head , 850MHz Band )

**Limit of SAR (W/kg) : <1.6W/kg (1g Average)**

Test Case		Ch	Measure Conducted Power (dBm)	Tune-up limit (dBm)	Scaling Factor	Measure Results ( W/kg)	Reported Results ( W/kg)
position	mode					1g Average	1g Average
Left cheek	GSM	L	32.72	33.50	---	---	---
		M	32.74	33.50	1.19	0.143	0.170
		H	32.71	33.50	---	---	---
Left Tilted		L	32.72	33.50	---	---	---
		M	32.74	33.50	1.19	0.092	0.110
		H	32.71	33.50	---	---	---
Right cheek		L	32.72	33.50	---	---	---
		M	32.74	33.50	1.19	0.151	0.180
		H	32.71	33.50	---	---	---
Right Tilted	L	32.72	33.50	---	---	---	
	M	32.74	33.50	1.19	0.081	0.096	
	H	32.71	33.50	---	---	---	



**Mode: GSM850 (GSM/GPRS/EGPRS)**

fL(MHz)=824.2MHz      fM(MHz)=836.5MHz      fH(MHz)= 848.8MHz

SAR Values ( body , 850MHz Band

**Limit of SAR (W/kg) : <1.6W/kg (1g Average)**

Test Case		Ch	Measure Conducted Power (dBm)	Tune-up limit (dBm)	Scaling Factor	Measure Results ( W/kg)	Reported Results ( W/kg)
position	mode					1 g Average	1g Average
TG	GSM With headset	L	32.72	33.50	---	---	---
		M	32.74	33.50	1.19	0.266	0.317
		M(retest)	32.74	33.50	1.19	0.206	0.245
		H	32.71	33.50	---	---	---
	GPRS	L	27.98	29.50	---	---	---
		M	27.85	29.50	1.46	0.209	0.306
		H	27.79	29.50	---	---	---
	EGPRS	L	29.29	29.50	---	---	---
		M	29.25	29.50	1.06	0.214	0.227
		H	29.12	29.50	---	---	---
TP	GSM With headset	L	32.72	33.50	---	---	---
		M	32.74	33.50	1.19	0.148	0.176
		H	32.71	33.50	---	---	---
	GPRS	L	27.98	29.50	---	---	---
		M	27.85	29.50	1.46	0.126	0.184
		H	27.79	29.50	---	---	---
	EGPRS	L	29.29	29.50	---	---	---
		M	29.25	29.50	1.06	0.127	0.135
H		29.12	29.50	---	---	---	
Hotspot EDGE 2	GSM With headset	M	32.74	33.50	1.19	0.044	0.052
Hotspot EDGE 3		M	32.74	33.50	1.19	0.107	0.127
Hotspot EDGE 4		M	32.74	33.50	1.19	0.138	0.164

Note: The distance between the EUT and the phantom bottom is 10mm.

**Mode: GSM1900**

fL(MHz)=1850.2MHz      fM(MHz)=1880.0MHz      fH(MHz)=1909.8MHz

SAR Values ( Head , 1900MHz Band )

**Limit of SAR (W/kg) : <1.6W/kg(1g Average)**

Test Case		CH	Measure Conducted Power (dBm)	Tune-up limit (dBm)	Scaling Factor	Measure Results ( W/kg)	Reported Results ( W/kg)
position	mode					1g Average	1g Average
Left cheek	GSM	L	30.95	31.00	1.01	---	---
		M	30.93	31.00	1.02	0.112	0.114
		H	30.84	31.00	1.04	---	---
Left Tilted		L	30.95	31.00	1.01	---	---
		M	30.93	31.00	1.02	0.049	0.050
		H	30.84	31.00	1.04	---	---
Right cheek		L	30.95	31.00	1.01	---	---
		M	30.93	31.00	1.02	0.152	0.154
		H	30.84	31.00	1.04	---	---
Right Tilted	L	30.95	31.00	1.01	---	---	
	M	30.93	31.00	1.02	0.058	0.059	
	H	30.84	31.00	1.04	---	---	

**Mode: GSM1900 (GSM/GPRS/EGPRS)**

fL(MHz)=1850.2MHz      fM(MHz)=1880.0MHz      fH(MHz)=1909.8MHz

SAR Values ( body , 1900MHz Band )

**Limit of SAR (W/kg) :<1.6W/kg(1g Average)**

Test Case		CH	Measure Conducted Power (dBm)	Tune-up limit (dBm)	Scaling Factor	Measure Results ( W/kg)	Reported Results ( W/kg)
position	mode					1 g Average	1g Average
TG	GSM With headset	L	30.95	31.00	1.01	---	---
		M	30.93	31.00	1.02	0.695	0.706
		H	30.84	31.00	1.04	---	---
	GPRS	L	24.75	25.00	1.06	---	---
		M	24.77	25.00	1.05	0.518	0.546
		H	24.31	25.00	1.17	---	---
	EGPRS	L	24.93	25.00	1.02	---	---
		M	24.70	25.00	1.07	0.539	0.578
		H	24.82	25.00	1.04	---	---
TP	GSM With headset	L	30.95	31.00	1.01	---	---
		M	30.93	31.00	1.02	0.231	0.235
		H	30.84	31.00	1.04	---	---
	GPRS	L	24.75	25.00	1.06	---	---
		M	24.77	25.00	1.05	0.166	0.175
		H	24.31	25.00	1.17	---	---
	EGPRS	L	24.93	25.00	1.02	---	---
		M	24.70	25.00	1.07	0.169	0.181
		H	24.82	25.00	1.04	---	---
Hotspot EDGE 2	GPRS	M	24.77	25.00	1.05	0.439	0.463
Hotspot EDGE 3		M	24.77	25.00	1.05	0.043	0.045
Hotspot EDGE 4		M	24.77	25.00	1.05	0.090	0.095

Note: The distance between the EUT and the phantom bottom is 10mm.

**Mode: WCDMA BAND2**

fL(MHz)=1852.4MHz      fM(MHz)=1880MHz      fH(MHz)= 1907.6MHz

SAR Values (Head, WCDMA BAND2)

**Limit of SAR (W/kg):<1.6W/kg(1g Average)**

Test Case		CH	Measure Conducted Power (dBm)	Tune-up limit (dBm)	Scaling Factor	Measure Results ( W/kg)	Reported Results ( W/kg)
position	mode					1 g Average	1g Average
Left cheek	RB test mode1+ 12.2kRMC	L	22.95	23.50	1.14	---	---
		M	23.08	23.50	1.10	0.164	0.181
		H	23.15	23.50	1.08	---	---
Left Tilted		L	22.95	23.50	1.14	---	---
		M	23.08	23.50	1.10	0.076	0.084
		H	23.15	23.50	1.08	---	---
Right cheek		L	22.95	23.50	1.14	---	---
		M	23.08	23.50	1.10	0.245	0.270
		H	23.15	23.50	1.08	---	---
Right Tilted	L	22.95	23.50	1.14	---	---	
	M	23.08	23.50	1.10	0.080	0.088	
	H	23.15	23.50	1.08	---	---	

**Mode: WCDMA BAND2**

fL(MHz)=1852.4MHz      fM(MHz)=1880MHz      fH(MHz)= 1907.6MHz

SAR Values (body, WCDMA BAND2)

**Limit of SAR (W/kg): <1.6W/kg(1g Average)**

Test Case		CH	Measure Conducted Power (dBm)	Tune-up limit (dBm)	Scaling Factor	Measure Results (W/kg)	Reported Results (W/kg)
Position	mode					1 g Average	1g Average
TG (Voice)	RB test mode1+12.2kRMC with headset	L	22.95	23.50	1.14	0.827	0.939
		L	22.95	23.50	1.14	0.810	0.919
		M	23.08	23.50	1.10	1.050	1.157
		M	23.08	23.50	1.10	1.020	1.124
		H	23.15	23.50	1.08	1.170	1.268
		H	23.15	23.50	1.08	1.160	1.257
TG (Data)		L	22.95	23.50	1.14	0.785	0.891
		M	23.08	23.50	1.10	0.853	0.940
		M	23.08	23.50	1.10	0.844	0.930
		H	23.15	23.50	1.08	1.090	1.181
		H	23.15	23.50	1.08	1.080	1.171
TP (Voice)		RB test mode1+12.2kRMC with headset	L	22.95	23.50	1.14	---
	M		23.08	23.50	1.10	0.378	0.416
	H		23.15	23.50	1.08	---	---
TP (Data)	L		22.95	23.50	1.14	---	---
	M		23.08	23.50	1.10	0.351	0.387
	H		23.15	23.50	1.08	---	---
Hotspot EDGE 2	Data	M	23.08	23.50	1.10	0.776	0.855
Hotspot EDGE 3		M	23.08	23.50	1.10	0.122	0.134
Hotspot EDGE 4		M	23.08	23.50	1.10	0.175	0.193

Note: The distance between the EUT and the phantom bottom is 10mm.

**Mode: WCDMA BAND5**

fL(MHz)=826.4MHz    fM(MHz)=836.4MHz    fH(MHz)= 846.6MHz

SAR Values (Head, WCDMA BAND5)

**Limit of SAR (W/kg): <1.6W/kg(1g Average)**

Test Case		CH	Measure Conducted Power (dBm)	Tune-uplimit (dBm)	Scaling Factor	Measure Results ( W/kg)	Reported Results ( W/kg)
Position	mode					1 g Average	1g Average
Left cheek	RB test mode1+ 12.2kRMC	L	22.36	24.00	---	---	---
		M	22.43	24.00	1.44	0.175	0.251
		H	22.41	24.00	---	---	---
Left Tilted		L	22.36	24.00	---	---	---
		M	22.43	24.00	1.44	0.111	0.159
		H	22.41	24.00	---	---	---
Right cheek		L	22.36	24.00	---	---	---
		M	22.43	24.00	1.44	0.183	0.263
		H	22.41	24.00	---	---	---
Right Tilted	L	22.36	24.00	---	---	---	
	M	22.43	24.00	1.44	0.109	0.156	
	H	22.41	24.00	---	---	---	

**Mode: WCDMA BAND5**

fL(MHz)=826.4MHz fM(MHz)=836.5MHz fH(MHz)= 846.6MHz

SAR Values (body, WCDMA BAND5)

**Limit of SAR (W/kg): <1.6W/kg(1g Average)**

Test Case		CH	Measure e Conduct ed Power (dBm)	Tune-up limit (dBm)	Scaling Factor	Measure Results (W/kg)	Reported Results (W/kg)
Position	mode					1 g Average	1g Average
TG (Voice)	RB test mode1+12.2k RMC with headset	L	22.36	24.00	---	---	---
		M	22.43	24.00	1.44	0.302	0.434
		H	22.41	24.00	---	---	---
TG (Data)		L	22.36	24.00	---	---	---
		M	22.43	24.00	1.44	0.309	0.444
		M(retest)	22.43	24.00	1.44	0.191	0.274
TP (Voice)	RB test mode1+12.2k RMC with headset	H	22.41	24.00	---	---	---
		L	22.36	24.00	---	---	---
		M	22.43	24.00	1.44	0.178	0.256
TP (Data)		L	22.36	24.00	---	---	---
		M	22.43	24.00	1.44	0.181	0.260
		H	22.41	24.00	---	---	---
Hotspot EDGE 2	Data	M	22.43	24.00	1.44	0.065	0.093
Hotspot EDGE 3		M	22.43	24.00	1.44	0.165	0.237
Hotspot EDGE 4		M	22.43	24.00	1.44	0.213	0.306

Note: The distance between the EUT and the phantom bottom is 10mm.

**Mode: WiFi**  
**SAR Values (WIFI 802.11b - Head)**  
**Limit of SAR (W/kg):<1.6W/kg(1g Average)**

Test Case		CH	Measure Conduc ted Power (dBm)	Tune-up limit (dBm)	Scaling Factor	Measure Result (W/kg)	Reported Result (W/kg)
Position	mode					1 g Average	1g Average
Leftcheek	1Mbps	1	14.15	16.00	----	----	----
		6	15.62	16.00	1.09	0.236	0.258
		11	15.45	16.00	----	----	----
Left Tilt	1Mbps	1	14.15	16.00	----	----	----
		6	15.62	16.00	1.09	0.164	0.179
		11	15.45	16.00	----	----	----
Rightcheek	1Mbps	1	14.15	16.00	1.53	0.525	0.804
		6	15.62	16.00	1.09	0.644	0.703
		11	15.45	16.00	1.14	0.931	1.057
		11	15.45	16.00	1.14	0.934	1.060
		11(retest)	15.45	16.00	1.14	0.841	0.955
Right Tilt	1Mbps	1	14.15	16.00	----	----	----
		6	15.62	16.00	1.09	0.402	0.439
		11	15.45	16.00	----	----	----

**SAR Values (WIFI 802.11b - Body)**  
**Limit of SAR (W/kg):<1.6W/kg(1g Average)**

Test Case		CH	Measure Conducted Power (dBm)	Tune-up limit (dBm)	Scaling Factor	Measure Result (W/kg)	Reported Result ( W/kg)
Position	mode					1 g Average	1g Average
TG	1Mbps	1	14.15	16.00	---	---	---
		6	15.62	16.00	1.14	0.126	0.138
		11	15.45	16.00	---	---	---
TP	1Mbps	1	14.15	16.00	---	---	---
		6	15.62	16.00	1.14	0.11	0.120
		11	15.45	16.00	---	---	---
Hotspot Edge 1	1Mbps	1	14.15	16.00	---	---	---
		6	15.62	16.00	1.14	0.055	0.060
		11	15.45	16.00	---	---	---
Hotspot Edge 4	1Mbps	1	14.15	16.00	---	---	---
		6	15.62	16.00	1.09	0.012	0.013
		11	15.45	16.00	---	---	---

Note: The distance between the EUT and the phantom bottom is 10mm.



**Mode: LTE BAND2- 20BW-1RB (1880MHz/Head)**

fL(MHz)=1860MHz fM(MHz)=1880MHz fH(MHz)= 1900MHz

SAR Values (Head, LTE BAND2)

**Limit of SAR (W/kg): <1.6W/kg(1g Average)**

Test Case		CH	Measure Conducted Power (dBm)	Tune-up limit (dBm)	Scaling Factor	Measure Results (W/kg)	Reported Results (W/kg)
Position	mode					1 g Average	1g Average
Left cheek	20 BW 1RB	L	22.50	23.00	1.12	---	---
		M	22.51	23.00	1.12	0.164	0.184
		H	22.50	23.00	1.12	---	---
Left Tilted		L	22.50	23.00	1.12	---	---
		M	22.51	23.00	1.12	0.055	0.062
		H	22.50	23.00	1.12	---	---
Right cheek		L	22.50	23.00	1.12	---	---
		M	22.51	23.00	1.12	0.144	0.161
		H	22.50	23.00	1.12	---	---
Right Tilted	L	22.50	23.00	1.12	---	---	
	M	22.51	23.00	1.12	0.054	0.060	
	H	22.50	23.00	1.12	---	---	

**Mode: LTE BAND2- 20BW-1RB (1880MHz/Flat)**

fL(MHz)=1860MHz fM(MHz)=1880MHz fH(MHz)= 1900MHz

SAR Values (body, LTE BAND2)

**Limit of SAR (W/kg): <1.6W/kg(1g Average)**

Test Case		CH	Measure Conducted Power (dBm)	Tune-up limit (dBm)	Scaling Factor	Measure Results (W/kg)	Reported Results (W/kg)
Position	mode					1 g Average	1g Average
TG	20 BW 1RB	L	22.50	23.00	1.12	---	---
		M	22.51	23.00	1.12	0.739	0.827
		H	22.50	23.00	1.12	---	---
TP		L	22.50	23.00	1.12	---	---
		M	22.51	23.00	1.12	0.300	0.336
		H	22.50	23.00	1.12	---	---

Note: The distance between the EUT and the phantom bottom is 10mm.

**Mode: LTE BAND2- 20BW-50%RB (1880MHz/Head)**

fL(MHz)=1860MHz fM(MHz)=1880MHz fH(MHz)= 1900MHz

SAR Values (Head, LTE BAND2)

**Limit of SAR (W/kg): <1.6W/kg(1g Average)**

Test Case		CH	Measure Conducted Power (dBm)	Tune-up limit (dBm)	Scaling Factor	Measure Results (W/kg)	Reported Results (W/kg)
Position	mode					1 g Average	1g Average
Left cheek	20 BW 50%RB	L	21.40	23.00	1.45	---	---
		M	21.50	23.00	1.41	0.130	0.184
		H	21.30	23.00	1.48	---	---
Left Tilted		L	21.40	23.00	1.45	---	---
		M	21.50	23.00	1.41	0.048	0.068
		H	21.30	23.00	1.48	---	---
Right cheek		L	21.40	23.00	1.45	---	---
		M	21.50	23.00	1.41	0.115	0.162
		H	21.30	23.00	1.48	---	---
Right Tilted	L	21.40	23.00	1.45	---	---	
	M	21.50	23.00	1.41	0.043	0.061	
	H	21.30	23.00	1.48	---	---	

**Mode: LTE BAND2- 20BW-50%RB (1880MHz/Flat)**

fL(MHz)=1860MHz fM(MHz)=1880MHz fH(MHz)= 1900MHz

SAR Values (body, LTE BAND2)

**Limit of SAR (W/kg): <1.6W/kg(1g Average)**

Test Case		CH	Measure Conducted Power (dBm)	Tune-up limit (dBm)	Scaling Factor	Measure Results (W/kg)	Reported Results (W/kg)
Position	mode					1 g Average	1g Average
TG	20 BW 50%RB	L	21.40	23.00	1.45	---	---
		M	21.50	23.00	1.41	0.740	1.045
		H	21.30	23.00	1.48	---	---
TP		L	21.40	23.00	1.45	---	---
		M	21.50	23.00	1.41	0.287	0.405
		H	21.30	23.00	1.48	---	---
Hotspot EDGE 2		M	21.50	23.00	1.41	0.477	0.674
Hotspot EDGE 3		M	21.50	23.00	1.41	0.135	0.191
Hotspot EDGE 4		M	21.50	23.00	1.41	0.134	0.189

Note: The distance between the EUT and the phantom bottom is 10mm.

**Mode: LTE BAND4- 20BW-1RB (1732.5MHz/Head)**

fL(MHz)=1720 MHz fM(MHz)=1732.5MHz fH(MHz)= 1745MHz

SAR Values (Head, LTE BAND4)

**Limit of SAR (W/kg): <1.6W/kg(1g Average)**

Test Case		CH	Measure Conducted Power (dBm)	Tune-uplimit (dBm)	Scaling Factor	Measure Results ( W/kg)	Reported Results ( W/kg)
Position	mode					1 g Average	1g Average
Left cheek	20 BW 1RB	L	22.46	24.00	---	---	---
		M	22.66	24.00	1.36	0.196	0.267
		H	22.60	24.00	---	---	---
Left Tilted		L	22.46	24.00	---	---	---
		M	22.66	24.00	1.36	0.075	0.102
		H	22.60	24.00	---	---	---
Right cheek		L	22.46	24.00	---	---	---
		M	22.66	24.00	1.36	0.184	0.251
		H	22.60	24.00	---	---	---
Right Tilted	L	22.46	24.00	---	---	---	
	M	22.66	24.00	1.36	0.062	0.084	
	H	22.60	24.00	---	---	---	

**Mode: LTE BAND4- 20BW-1RB (1732.5MHz/ Flat)**

fL(MHz)=1720 MHz fM(MHz)=1732.5MHz fH(MHz)= 1745MHz

SAR Values (body, LTE BAND4)

**Limit of SAR (W/kg): <1.6W/kg(1g Average)**

Test Case		CH	Measure Conducted Power (dBm)	Tune-up limit (dBm)	Scaling Factor	Measure Results (W/kg)	Reported Results (W/kg)
Position	mode					1 g Average	1g Average
TG	20 BW 1RB	L	22.46	24.00	---	---	---
		M	22.66	24.00	1.36	0.492	0.670
		H	22.60	24.00	---	---	---
TP		L	22.46	24.00	---	---	---
		M	22.66	24.00	1.36	0.370	0.504
		H	22.60	24.00	---	---	---
Hotspot EDGE 2		L	22.66	24.00	1.36	0.320	0.436
Hotspot EDGE 3		M	22.66	24.00	1.36	0.120	0.163
Hotspot EDGE 4		M	22.66	24.00	1.36	0.139	0.189

Note: The distance between the EUT and the phantom bottom is 10mm.

**Mode: LTE BAND4- 20BW-50%RB (1732.5MHz/Head)**

fL(MHz)=1720 MHz fM(MHz)=1732.5MHz fH(MHz)= 1745MHz

SAR Values (Head, LTE BAND4)

**Limit of SAR (W/kg): <1.6W/kg(1g Average)**

Test Case		CH	Measure Conducted Power (dBm)	Tune-up limit (dBm)	Scaling Factor	Measure Results (W/kg)	Reported Results (W/kg)
Position	mode					1 g Average	1g Average
Left cheek	20 BW 50%RB	L	22.21	24.00	---	---	---
		M	22.59	24.00	1.38	0.173	0.239
		H	22.51	24.00	---	---	---
Left Tilted		L	22.21	24.00	---	---	---
		M	22.59	24.00	1.38	0.061	0.084
		H	22.51	24.00	---	---	---
Right cheek		L	22.21	24.00	---	---	---
		M	22.59	24.00	1.38	0.174	0.241
		H	22.51	24.00	---	---	---
Right Tilted	L	22.21	24.00	---	---	---	
	M	22.59	24.00	1.38	0.059	0.082	
	H	22.51	24.00	---	---	---	

**Mode: LTE BAND4- 20BW-50%RB (1732.5MHz/ Flat)**

fL(MHz)=1720 MHz fM(MHz)=1732.5MHz fH(MHz)= 1745MHz

SAR Values (body, LTE BAND4)

**Limit of SAR (W/kg): <1.6W/kg(1g Average)**

Test Case		CH	Measure Conducted Power (dBm)	Tune-up limit (dBm)	Scaling Factor	Measure Results (W/kg)	Reported Results (W/kg)
Position	mode					1 g Average	1g Average
TG	20 BW 50%RB	L	22.21	24.00	---	---	---
		M	22.59	24.00	1.38	0.418	0.578
		H	22.51	24.00	---	---	---
TP		L	22.21	24.00	---	---	---
		M	22.59	24.00	1.38	0.285	0.394
		H	22.51	24.00	---	---	---

Note: The distance between the EUT and the phantom bottom is 10mm.

**Mode: LTE BAND4-15BW-1RB (1732.5MHz/Head)**

fL(MHz)=1717.5 MHz      fM(MHz)=1732.5 MHz      fH(MHz)= 1747.5 MHz

SAR Values (Head, LTE BAND4)

**Limit of SAR (W/kg): <1.6W/kg(1g Average)**

Test Case		CH	Measure Conducted Power (dBm)	Tune-up limit (dBm)	Scaling Factor	Measure Results (W/kg)	Reported Results (W/kg)
Position	mode					1 g Average	1g Average
Left cheek	15 BW 1 RB	L	22.46	24.00	---	---	---
		M	22.86	24.00	1.30	0.178	0.231
		H	22.73	24.00	---	---	---
Left Tilted		L	22.46	24.00	---	---	---
		M	22.86	24.00	1.30	0.076	0.099
		H	22.73	24.00	---	---	---
Right cheek		L	22.46	24.00	---	---	---
		M	22.86	24.00	1.30	0.171	0.222
		H	22.73	24.00	---	---	---
Right Tilted	L	22.46	24.00	---	---	---	
	M	22.86	24.00	1.30	0.074	0.096	
	H	22.73	24.00	---	---	---	

**Mode: LTE BAND4-15BW-1RB (1732.5MHz/Head)**

fL(MHz)=1717.5 MHz      fM(MHz)=1732.5 MHz      fH(MHz)= 1747.5 MHz

SAR Values (body, LTE BAND4)

**Limit of SAR (W/kg) : <1.6W/kg(1g Average)**

Test Case		CH	Measure Conducted Power (dBm)	Tune-up limit (dBm)	Scaling Factor	Measure Results (W/kg)	Reported Results (W/kg)
Position	mode					1 g Average	1g Average
TG	15 BW 1RB	L	22.46	24.00	---	---	---
		M	22.86	24.00	1.30	0.363	0.472
		H	22.73	24.00	---	---	---
TP		L	22.46	24.00	---	---	---
		M	22.86	24.00	1.30	0.526	0.684
		M(retest)	22.86	24.00	1.30	0.309	0.402
	H	22.73	24.00	---	---	---	

Note: The distance between the EUT and the phantom bottom is 10mm.

**Mode: LTE BAND5- 10BW-1RB (836.5MHz/Head)**

fL(MHz)=829 MHz      fM(MHz)=836.5MHz      fH(MHz)= 844MHz

SAR Values (Head, LTE BAND5)

**Limit of SAR (W/kg): <1.6W/kg(1g Average)**

Test Case		CH	Measure Conducted Power (dBm)	Tune-up limit (dBm)	Scaling Factor	Measure Results (W/kg)	Reported Results (W/kg)
Position	mode					1 g Average	1g Average
Left cheek	10 BW 1RB	L	22.20	24.00	1.20	---	---
		M	22.40	24.00	1.15	0.189	0.273
		H	22.10	24.00	1.23	---	---
Left Tilted		L	22.20	24.00	1.20	---	---
		M	22.40	24.00	1.15	0.076	0.110
		H	22.10	24.00	1.23	---	---
Right cheek		L	22.20	24.00	1.20	---	---
		M	22.40	24.00	1.15	0.172	0.249
		H	22.10	24.00	1.23	---	---
Right Tilted	L	22.20	24.00	1.20	---	---	
	M	22.40	24.00	1.15	0.090	0.130	
	H	22.10	24.00	1.23	---	---	

**Mode: LTE BAND5- 10BW-1RB (836.5MHz/ Flat)**

fL(MHz)=829 MHz      fM(MHz)=836.5MHz      fH(MHz)= 844MHz

SAR Values (body, LTE BAND5)

**Limit of SAR (W/kg): <1.6W/kg(1g Average)**

Test Case		CH	Measure Conducted Power (dBm)	Tune-up limit (dBm)	Scaling Factor	Measure Results (W/kg)	Reported Results (W/kg)
Position	mode					1 g Average	1g Average
TG	10 BW 1RB	L	22.20	24.00	---	---	---
		M	22.40	24.00	1.15	0.386	0.558
		M(retest)	22.40	24.00	1.15	0.366	0.529
		H	22.10	24.00	---	---	---
TP		L	22.20	24.00	---	---	---
		M	22.40	24.00	1.15	0.182	0.263
		H	22.10	24.00	---	---	---
Hotspot EDGE 2		M	22.40	24.00	1.15	0.064	0.093
Hotspot EDGE 3		M	22.40	24.00	1.15	0.146	0.211
Hotspot EDGE 4		M	22.40	24.00	1.15	0.229	0.331

Note: The distance between the EUT and the phantom bottom is 10mm.

**Mode: LTE BAND5- 10BW-50%RB (836.5MHz/Head)**

fL(MHz)=829 MHz      fM(MHz)=836.5MHz      fH(MHz)= 844MHz

SAR Values (Head, LTE BAND5)

**Limit of SAR (W/kg): <1.6W/kg(1g Average)**

Test Case		CH	Measure Conducted Power (dBm)	Tune-up limit (dBm)	Scaling Factor	Measure Results (W/kg)	Reported Results (W/kg)
Position	mode					1 g Average	1g Average
Left cheek	10 BW 50%RB	L	22.20	24.00	---	---	---
		M	22.38	24.00	1.48	0.151	0.219
		H	22.10	24.00	---	---	---
Left Tilted		L	22.20	24.00	---	---	---
		M	22.38	24.00	1.48	0.062	0.090
		H	22.10	24.00	---	---	---
Right cheek		L	22.20	24.00	---	---	---
		M	22.38	24.00	1.48	0.136	0.197
		H	22.10	24.00	---	---	---
Right Tilted	L	22.20	24.00	---	---	---	
	M	22.38	24.00	1.48	0.072	0.105	
	H	22.10	24.00	---	---	---	

**Mode: LTE BAND5- 10BW-50%RB (836.5MHz/ Flat)**

fL(MHz)=829 MHz      fM(MHz)=836.5MHz      fH(MHz)= 844MHz

SAR Values (body, LTE BAND5)

**Limit of SAR (W/kg): <1.6W/kg(1g Average)**

Test Case		CH	Measure Conducted Power (dBm)	Tune-up limit (dBm)	Scaling Factor	Measure Results (W/kg)	Reported Results (W/kg)
Position	mode					1 g Average	1g Average
TG	10 BW 50%RB	L	22.20	24.00	---	---	---
		M	22.38	24.00	1.48	0.147	0.213
		H	22.10	24.00	---	---	---
TP		L	22.20	24.00	---	---	---
		M	22.38	24.00	1.48	0.299	0.434
		H	22.10	24.00	---	---	---

Note: The distance between the EUT and the phantom bottom is 10mm.

**Mode: LTE BAND12- 10BW-1RB (707.5MHz/Head)**

fL(MHz)=704 MHz      fM(MHz)=707.5MHz      fH(MHz)= 711MHz

SAR Values (Head, LTE BAND12)

**Limit of SAR (W/kg): <1.6W/kg(1g Average)**

Test Case		CH	Measure Conducted Power (dBm)	Tune-up limit (dBm)	Scaling Factor	Measure Results ( W/kg)	Reported Results ( W/kg)
Position	mode					1 g Average	1g Average
Left cheek	10 BW 1RB	L	23.20	24.00	1.20	---	---
		M	23.20	24.00	1.20	0.082	0.099
		H	23.20	24.00	1.20	---	---
Left Tilted		L	23.20	24.00	1.20	---	---
		M	23.20	24.00	1.20	0.040	0.048
		H	23.20	24.00	1.20	---	---
Right cheek		L	23.20	24.00	1.20	---	---
		M	23.20	24.00	1.20	0.021	0.025
		H	23.20	24.00	1.20	---	---
Right Tilted	L	23.20	24.00	1.20	---	---	
	M	23.20	24.00	1.20	0.088	0.106	
	H	23.20	24.00	1.20	---	---	

**Mode: LTE BAND12- 10BW-1RB (707.5MHz/ Flat)**

fL(MHz)=704 MHz      fM(MHz)=707.5MHz      fH(MHz)= 711MHz

SAR Values (body, LTE BAND12)

**Limit of SAR (W/kg): <1.6W/kg(1g Average)**

Test Case		CH	Measure Conducted Power (dBm)	Tune-up limit (dBm)	Scaling Factor	Measure Results (W/kg)	Reported Results (W/kg)
Position	mode					1 g Average	1g Average
TG	10 BW 1RB	L	23.20	24.00	1.20	---	---
		M	23.20	24.00	1.20	0.155	0.186
		H	23.20	24.00	1.20	---	---
TP		L	23.20	24.00	1.20	---	---
		M	23.20	24.00	1.20	0.049	0.059
		H	23.20	24.00	1.20	---	---
Hotspot EDGE 2		L	23.20	24.00	1.20	0.022	0.026
Hotspot EDGE 3		M	23.20	24.00	1.20	0.074	0.089
Hotspot EDGE 4		M	23.20	24.00	1.20	0.095	0.114

Note: The distance between the EUT and the phantom bottom is 10mm.



**Mode: LTE BAND12- 10BW-50%RB (707.5MHz/Head)**

fL(MHz)=704 MHz      fM(MHz)=707.5MHz      fH(MHz)= 711MHz

SAR Values (Head, LTE BAND12)

**Limit of SAR (W/kg): <1.6W/kg(1g Average)**

Test Case		CH	Measure Conducted Power (dBm)	Tune-uplimit (dBm)	Scaling Factor	Measure Results ( W/kg)	Reported Results ( W/kg)
Position	mode					1 g Average	1g Average
Left cheek	10 BW 50%RB	L	22.00	24.00	1.58	---	---
		M	22.00	24.00	1.58	0.069	0.109
		H	22.00	24.00	1.58	---	---
Left Tilted		L	22.00	24.00	1.58	---	---
		M	22.00	24.00	1.58	0.033	0.052
		H	22.00	24.00	1.58	---	---
Right cheek		L	22.00	24.00	1.58	---	---
		M	22.00	24.00	1.58	0.018	0.029
		H	22.00	24.00	1.58	---	---
Right Tilted	L	22.00	24.00	1.58	---	---	
	M	22.00	24.00	1.58	0.016	0.025	
	H	22.00	24.00	1.58	---	---	

**Mode: LTE BAND12- 10BW-50%RB (707.5MHz/ Flat)**

fL(MHz)=704 MHz      fM(MHz)=707.5MHz      fH(MHz)= 711MHz

SAR Values (body, LTE BAND12)

**Limit of SAR (W/kg): <1.6W/kg(1g Average)**

Test Case		CH	Measure Conducted Power (dBm)	Tune-up limit (dBm)	Scaling Factor	Measure Results (W/kg)	Reported Results (W/kg)
Position	mode					1 g Average	1g Average
TG	10 BW 50%RB	L	22.00	24.00	1.58	---	---
		M	22.00	24.00	1.58	0.121	0.192
		H	22.00	24.00	1.58	---	---
TP		L	22.00	24.00	1.58	---	---
		M	22.00	24.00	1.58	0.037	0.059
		H	22.00	24.00	1.58	---	---

Note: The distance between the EUT and the phantom bottom is 10mm.

**Mode: LTE BAND13- 10BW-1RB (782MHz/Head)**

fL(MHz)=782 MHz fM(MHz)=782MHz fH(MHz)= 782MHz

SAR Values (Head, LTE BAND13)

**Limit of SAR (W/kg): <1.6W/kg(1g Average)**

Test Case		CH	Measure Conducted Power (dBm)	Tune-uplimit (dBm)	Scaling Factor	Measure Results ( W/kg)	Reported Results ( W/kg)
Position	mode					1 g Average	1g Average
Left cheek	10 BW 1RB	L	22.80	23.00	1.05	---	---
		M	22.80	23.00	1.05	0.091	0.095
		H	22.80	23.00	1.05	---	---
Left Tilted		L	22.80	23.00	1.05	---	---
		M	22.80	23.00	1.05	0.091	0.095
		H	22.80	23.00	1.05	---	---
Right cheek		L	22.80	23.00	1.05	---	---
		M	22.80	23.00	1.05	0.105	0.110
		H	22.80	23.00	1.05	---	---
Right Tilted	L	22.80	23.00	1.05	---	---	
	M	22.80	23.00	1.05	0.053	0.055	
	H	22.80	23.00	1.05	---	---	

**Mode: LTE BAND13- 10BW-1RB (782MHz/ Flat)**

fL(MHz)=782 MHz fM(MHz)=782MHz fH(MHz)= 782MHz

SAR Values (body, LTE BAND13)

**Limit of SAR (W/kg): <1.6W/kg(1g Average)**

Test Case		CH	Measure Conducted Power (dBm)	Tune-up limit (dBm)	Scaling Factor	Measure Results (W/kg)	Reported Results (W/kg)
Position	mode					1 g Average	1g Average
TG	10 BW 1RB	L	22.80	23.00	1.05	---	---
		M	22.80	23.00	1.05	0.254	0.266
		H	22.80	23.00	1.05	---	---
TP		L	22.80	23.00	1.05	---	---
		M	22.80	23.00	1.05	0.082	0.086
		H	22.80	23.00	1.05	---	---
Hotspot EDGE 2		L	22.80	23.00	1.05	0.070	0.073
Hotspot EDGE 3		M	22.80	23.00	1.05	0.099	0.104
Hotspot EDGE 4		M	22.80	23.00	1.05	0.140	0.147

Note: The distance between the EUT and the phantom bottom is 10mm.

**Mode: LTE BAND13- 10BW-50%RB (782MHz/Head)**

fL(MHz)=782 MHz fM(MHz)=782MHz fH(MHz)= 782MHz

SAR Values (Head, LTE BAND13)

**Limit of SAR (W/kg): <1.6W/kg(1g Average)**

Test Case		CH	Measure Conducted Power (dBm)	Tune-uplimit (dBm)	Scaling Factor	Measure Results ( W/kg)	Reported Results ( W/kg)
Position	mode					1 g Average	1g Average
Left cheek	10 BW 50%RB	L	22.80	23.00	1.05	---	---
		M	22.80	23.00	1.05	0.072	0.075
		H	22.80	23.00	1.05	---	---
Left Tilted		L	22.80	23.00	1.05	---	---
		M	22.80	23.00	1.05	0.027	0.028
		H	22.80	23.00	1.05	---	---
Right cheek		L	22.80	23.00	1.05	---	---
		M	22.80	23.00	1.05	0.086	0.090
		H	22.80	23.00	1.05	---	---
Right Tilted	L	22.80	23.00	1.05	---	---	
	M	22.80	23.00	1.05	0.045	0.047	
	H	22.80	23.00	1.05	---	---	

**Mode: LTE BAND13- 10BW-50%RB (782MHz/ Flat)**

fL(MHz)=782 MHz fM(MHz)=782MHz fH(MHz)= 782MHz

SAR Values (body, LTE BAND13)

**Limit of SAR (W/kg): <1.6W/kg(1g Average)**

Test Case		CH	Measure Conducted Power (dBm)	Tune-up limit (dBm)	Scaling Factor	Measure Results (W/kg)	Reported Results (W/kg)
Position	mode					1 g Average	1g Average
TG	10 BW 50%RB	L	22.80	23.00	1.05	---	---
		M	22.80	23.00	1.05	0.187	0.196
		H	22.80	23.00	1.05	---	---
TP		L	22.80	23.00	1.05	---	---
		M	22.80	23.00	1.05	0.061	0.064
		H	22.80	23.00	1.05	---	---

Note: The distance between the EUT and the phantom bottom is 10mm.

**Mode: LTE BAND17- 10BW-1RB (710MHz/Head)**

fL(MHz)=709 MHz fM(MHz)=710MHz fH(MHz)= 711MHz

SAR Values (Head, LTE BAND17)

**Limit of SAR (W/kg): <1.6W/kg(1g Average)**

Test Case		CH	Measure Conducted Power (dBm)	Tune-uplimit (dBm)	Scaling Factor	Measure Results ( W/kg)	Reported Results ( W/kg)
Position	mode					1 g Average	1g Average
Left cheek	10 BW 1RB	L	22.40	23.00	1.15	---	---
		M	22.40	23.00	1.15	0.030	0.034
		H	22.40	23.00	1.15	---	---
Left Tilted		L	22.40	23.00	1.15	---	---
		M	22.40	23.00	1.15	0.021	0.024
		H	22.40	23.00	1.15	---	---
Right cheek		L	22.40	23.00	1.15	---	---
		M	22.40	23.00	1.15	0.031	0.036
		H	22.40	23.00	1.15	---	---
Right Tilted	L	22.40	23.00	1.15	---	---	
	M	22.40	23.00	1.15	0.020	0.023	
	H	22.40	23.00	1.15	---	---	

**Mode: LTE BAND17- 10BW-1RB (710MHz/ Flat)**

fL(MHz)=709 MHz fM(MHz)=710MHz fH(MHz)= 711MHz

SAR Values (body, LTE BAND17)

**Limit of SAR (W/kg): <1.6W/kg(1g Average)**

Test Case		CH	Measure Conducted Power (dBm)	Tune-up limit (dBm)	Scaling Factor	Measure Results (W/kg)	Reported Results (W/kg)
Position	mode					1 g Average	1g Average
TG	10 BW 1RB	L	22.40	23.00	1.15	---	---
		M	22.40	23.00	1.15	0.133	0.153
		H	22.40	23.00	1.15	---	---
TP		L	22.40	23.00	1.15	---	---
		M	22.40	23.00	1.15	0.039	0.045
		H	22.40	23.00	1.15	---	---
Hotspot EDGE 2		L	22.40	23.00	1.15	0.023	0.026
Hotspot EDGE 3		M	22.40	23.00	1.15	0.024	0.028
Hotspot EDGE 4		M	22.40	23.00	1.15	0.043	0.049

Note: The distance between the EUT and the phantom bottom is 10mm.

**Mode: LTE BAND17- 10BW-50%RB (710MHz/Head)**

fL(MHz)=709 MHz fM(MHz)=710MHz fH(MHz)= 711MHz

SAR Values (Head, LTE BAND17)

**Limit of SAR (W/kg): <1.6W/kg(1g Average)**

Test Case		CH	Measure Conducted Power (dBm)	Tune-uplimit (dBm)	Scaling Factor	Measure Results ( W/kg)	Reported Results ( W/kg)
Position	mode					1 g Average	1g Average
Left cheek	10 BW 50%RB	L	22.40	23.00	1.15	---	---
		M	22.40	23.00	1.15	0.024	0.028
		H	22.40	23.00	1.15	---	---
Left Tilted		L	22.40	23.00	1.15	---	---
		M	22.40	23.00	1.15	0.015	0.017
		H	22.40	23.00	1.15	---	---
Right cheek		L	22.40	23.00	1.15	---	---
		M	22.40	23.00	1.15	0.024	0.028
		H	22.40	23.00	1.15	---	---
Right Tilted	L	22.40	23.00	1.15	---	---	
	M	22.40	23.00	1.15	0.014	0.016	
	H	22.40	23.00	1.15	---	---	

**Mode: LTE BAND17- 10BW-50%RB (710MHz/ Flat)**

fL(MHz)=709 MHz fM(MHz)=710MHz fH(MHz)= 711MHz

SAR Values (body, LTE BAND17)

**Limit of SAR (W/kg): <1.6W/kg(1g Average)**

Test Case		CH	Measure Conducted Power (dBm)	Tune-up limit (dBm)	Scaling Factor	Measure Results (W/kg)	Reported Results (W/kg)
Position	mode					1 g Average	1g Average
TG	10 BW 50%RB	L	22.40	23.00	1.15	---	---
		M	22.40	23.00	1.15	0.098	0.113
		H	22.40	23.00	1.15	---	---
TP		L	22.40	23.00	1.15	---	---
		M	22.40	23.00	1.15	0.030	0.034
		H	22.40	23.00	1.15	---	---

Note: The distance between the EUT and the phantom bottom is 10mm.

## 6.11 SAR Measurement Variability

SAR measurement variability must be assessed for each frequency band, which is determined by the SAR probe calibration point and tissue-equivalent medium used for the device measurements. When both head and body tissue-equivalent media are required for SAR measurements in a frequency band, the variability measurement procedures should be applied to the tissue medium with the highest measured SAR, using the highest measured SAR configuration for that tissue-equivalent medium.

The following procedures are applied to determine if repeated measurements are required.

- 1) Repeated measurement is not required when the original highest measured SAR is  $< 0.80$  W/kg; steps 2) through 4) do not apply.
- 2) When the original highest measured SAR is  $\geq 0.80$  W/kg, repeat that measurement once.
- 3) Perform a second repeated measurement only if the ratio of largest to smallest SAR for the original and first repeated measurements is  $> 1.20$  or when the original or repeated measurement is  $\geq 1.45$  W/kg ( $\sim 10\%$  from the 1-g SAR limit).
- 4) Perform a third repeated measurement only if the original, first or second repeated measurement is  $\geq 1.5$  W/kg and the ratio of largest to smallest SAR for the original, first and second repeated measurements is  $> 1.20$ .

### 6.11.1 The Highest Measured SAR configuration in Each Frequency Band

Frequency band(MHz)	Air interface	Head(w/kg)	Body(w/kg)
750	LTE Band 12 LTE Band 13 LTE Band 17	$<0.8$	$<0.8$
850	GSM 850 WCDMA Band 5 LTE Band 5	$<0.8$	$<0.8$
1900	GSM 1900 WCDMA Band 2 LTE Band 4	$<0.8$	$>0.8$
1950	LTE Band 2	$<0.8$	$<0.8$
2450	WiFi 802.11b/g/n	$>0.8$	$<0.8$

### 6.11.2 Repeated Measurement Results

#### SAR Measurement Variability

Test Position	Original SAR (W/kg)	First Repeated SAR (W/kg)	The Ratio
WCDMA Band2	0.827	0.810	1.021
WCDMA Band2	1.050	1.020	1.029
WCDMA Band2	1.170	1.160	1.008
WCDMA Band2	0.853	0.844	1.010
WCDMA Band2	1.090	1.080	1.009
WiFi 802.11b/g/n	0.931	0.934	1.003

## 6.12 Simultaneous Transmission SAR Analysis

### The sum of SAR values for GSM & WiFi

	MAXIMUM SAR VALUE FOR HEAD	MAXIMUM SAR VALUE FOR BODY
<b>GSM</b>	0.180	0.706
<b>WiFi</b>	1.060	0.138
<b>Sum</b>	<b>1.240</b>	<b>0.844</b>
<b>Note</b>	<b>GSM850 + WIFI Right cheek</b>	<b>GPRS1900 + WIFI TG</b>

According to the above tables, the sum of SAR values for GSM and WiFi < 1.6W/kg. So simultaneous transmission SAR are not required for WiFi transmitter.

### The sum of SAR values for WCDMA & WiFi

	MAXIMUM SAR VALUE FOR HEAD	MAXIMUM SAR VALUE FOR BODY
<b>WCDMA</b>	0.270	1.268
<b>WiFi</b>	1.060	0.138
<b>Sum</b>	<b>1.330</b>	<b>1.406</b>
<b>Note</b>	<b>WCDMA B2 + WIFI Right cheek</b>	<b>WCDMA B2 + WIFI TG</b>

According to the above tables, the sum of SAR values for WCDMA and WiFi < 1.6W/kg. So simultaneous transmission SAR are not required for WiFi transmitter.

### The sum of SAR values for LTE & WiFi

	MAXIMUM SAR VALUE FOR HEAD	MAXIMUM SAR VALUE FOR BODY
<b>LTE</b>	0.251	1.045
<b>WiFi</b>	1.060	0.138
<b>Sum</b>	<b>1.311</b>	<b>1.183</b>
<b>Note</b>	<b>LTE B4 + WIFI Right cheek</b>	<b>LTE B2 + WIFI TG</b>

According to the above tables, the sum of SAR values for LTE and WiFi < 1.6W/kg. So simultaneous transmission SAR are not required for WiFi transmitter.



According to the formula (KDB447498 4.3.2) the Bluetooth SAR as follow:  

$$\left[ \frac{\text{(max.power of channel, including tune-up tolerance, mw)}}{\sqrt{f(\text{GHz}) \times x}} \right] \text{ W/kg for test separation distances} \leq 50\text{mm.}$$

Head:

min. test separation distance = 5mm

Body:

min. test separation distance = 10mm

Where  $x=7.5$  for 1-g SAR, and  $x=18.75$  for 10-g SAR.

#### The sum of SAR values for GSM & Bluetooth

	MAXIMUM SAR VALUE FOR HEAD	MAXIMUM SAR VALUE FOR BODY
<b>GSM</b>	0.180	0.706
<b>Bluetooth</b>	0.207	0.207
<b>Sum</b>	<b>0.387</b>	<b>0.913</b>
<b>Note</b>	<b>GSM850 + BT Right cheek</b>	<b>GPRS1900 + BT TG</b>

According to the above tables, the sum of SAR values for GSM and Bluetooth < 1.6W/kg. So simultaneous transmission SAR are not required for Bluetooth transmitter.

#### The sum of SAR values for WCDMA & Bluetooth

	MAXIMUM SAR VALUE FOR HEAD	MAXIMUM SAR VALUE FOR BODY
<b>WCDMA</b>	0.270	1.268
<b>Bluetooth</b>	0.207	0.207
<b>Sum</b>	<b>0.477</b>	<b>1.475</b>
<b>Note</b>	<b>WCDMA B2 + BT Right cheek</b>	<b>WCDMA B2 + BT TG</b>

According to the above tables, the sum of SAR values for WCDMA and Bluetooth < 1.6W/kg. So simultaneous transmission SAR are not required for Bluetooth transmitter.

#### The sum of SAR values for LTE & Bluetooth

	MAXIMUM SAR VALUE FOR HEAD	MAXIMUM SAR VALUE FOR BODY
<b>LTE</b>	0.267	1.045
<b>Bluetooth</b>	0.207	0.207
<b>Sum</b>	<b>0.474</b>	<b>1.252</b>
<b>Note</b>	<b>LTE B4 + BT Left cheek</b>	<b>LTE B2 + BT TG</b>

According to the above tables, the sum of SAR values for LTE and Bluetooth < 1.6W/kg. So simultaneous transmission SAR are not required for Bluetooth transmitter.

## 7 MEASUREMENT UNCERTAINTY

DASY5 Uncertainty Budget								
Error description	Uncertainty value	Prob. Dist.	Div.	( $c_i$ ) 1g	( $c_i$ ) 10g	Std.Un c (1g).	Std.Unc (10g)	(vi) Veff
<b>Measurement system</b>								
Probe calibration	±6.0%	N	1	1	1	±6.0%	±6.0%	∞
Axial isotropy	±4.7%	R	$\sqrt{3}$	0.7	0.7	±1.9%	±1.9%	∞
Hemispherical isotropy	±9.6%	R	$\sqrt{3}$	0.7	0.7	±3.9%	±3.9%	∞
Boundary Effects	±1.0%	R	$\sqrt{3}$	1	1	±0.6%	±0.6%	∞
Linearity	±4.7%	R	$\sqrt{3}$	1	1	±2.7%	±2.7%	∞
System detection limits	±1.0%	R	$\sqrt{3}$	1	1	±0.6%	±0.6%	∞
Readout electronics	±0.3%	N	1	1	1	±0.3%	±0.3%	∞
Response time	±0.8%	R	$\sqrt{3}$	1	1	±0.5%	±0.5%	∞
Integration time	±2.6%	R	$\sqrt{3}$	1	1	±1.5%	±1.5%	∞
RF ambient noise	±3.0%	R	$\sqrt{3}$	1	1	±1.7%	±1.7%	∞
RF ambient reflections	±3.0%	R	$\sqrt{3}$	1	1	±1.7%	±1.7%	∞
Probe positioned	±0.4%	R	$\sqrt{3}$	1	1	±0.2%	±0.2%	∞
Probe positioning	±2.9%	R	$\sqrt{3}$	1	1	±1.7%	±1.7%	∞
Max.SAR Eval.	±1.0%	R	$\sqrt{3}$	1	1	±0.6%	±0.6%	∞
<b>Test Sample Related</b>								
Device holder	±3.6%	N	1	1	1	±3.6%	±3.6%	5
Device Positioning	±2.9%	N	1	1	1	±2.9%	±2.9%	145
Power drift	±5.0%	R	$\sqrt{3}$	1	1	±2.9%	±2.9%	∞
<b>Phantom and Setup</b>								
Phantom uncertainty	±4.0%	R	$\sqrt{3}$	1	1	±2.3%	±2.3%	∞
Liquid conductivity (target.)	±5.0%	R	$\sqrt{3}$	0.64	0.43	±1.8%	±1.2%	∞
Liquid conductivity (mea.)	±2.5%	R	$\sqrt{3}$	0.64	0.43	±0.9%	±0.6%	∞
Liquid Permittivity (target.)	±5.0%	R	$\sqrt{3}$	0.60	0.49	±1.7%	±1.4%	∞
Liquid Permittivity (mea.)	±2.5%	R	$\sqrt{3}$	0.60	0.49	±0.9%	±0.7%	∞
Combined std. Uncertainty						±10.9%	±10.7%	387
<b>Expanded STD Uncertainty</b>						<b>±21.7%</b>	<b>±21.4%</b>	

## 8 TEST EQUIPMENTS

The measurements were performed using an automated near-field scanning system, DASY5, manufactured by Schmid & Partner Engineering AG (SPEAG) in Switzerland. The SAR extrapolation algorithm used in all measurements was the 'advanced extrapolation' algorithm.

The following table lists calibration dates of SPEAG components:

Test Equipment	Model	Serial Number	Calibration date	Calibration Due data
DAE	DAE4	1226	2016.04.14	2017.04.13
DAE	DAE4	1327	2016.04.15	2017.04.14
Dosimetric E-field Probe	EX3DV4	3717	2016.10.19	2017.10.18
Dosimetric E-field Probe	ES3DV3	3297	2016.10.14	2017.10.13
Dipole Validation Kit	D835V2	4d100	2016.10.16	2017.10.15
Dipole Validation Kit	D1750V2	1034	2016.10.11	2017.10.10
Dipole Validation Kit	D1900V2	5d155	2016.04.16	2017.04.15
Dipole Validation Kit	D2450V2	845	2016.10.12	2017.10.11
Dipole Validation Kit	D2600V2	1059	2016.04.14	2017.04.13

Additional test equipment used in testing:

No.	Name	Type	S/N	Calibration Date	Valid Period
01	Network analyzer	Agilent E5071E	MY46109425	Oct 28th , 2016	One year
02	Dielectric Probe Kit	Agilent 85070E	MY44300524	N/A	
03	Power meter	Agilent E4419B	GB42420229	May 18th , 2016	One year
05	Power sensor A	Agilent 8482A	MY41091903	May 18th , 2016	One year
06	Power sensor B	Agilent 8485D	MY41090532	May 18th , 2016	One year
07	Signal Generator	Agilent N5182A	MY49071248	Oct 28th , 2016	One year
08	Amplifier	ZHL-42W	QA1020005	N/A	
10	BTS	MT8820C	6201107310	May 31th , 2016	One year

#### Detailed information of Isotropic E-field Probe Type ES3DV3

Construction	Symmetrical design with triangular core Interleaved sensors Built-in shielding against static charges PEEK enclosure material (resistant to organic solvents, e.g., DGBE)
Calibration	Calibration certificate in Appendix C
Frequency	10 MHz to 4 GHz; Linearity: $\pm 0.2$ dB (30 MHz to 4 GHz)
Optical Surface Detection	$\pm 0.2$ mm repeatability in air and clear liquids over diffuse reflecting surfaces
Dimensions	Overall length: 337 mm (Tip: 20 mm) Tip diameter: 3.9 mm (Body: 12 mm) Distance from probe tip to dipole centers: 2.0 mm
Dynamic Range	5 $\mu$ W/g to > 100 W/kg; Linearity: $\pm 0.2$ dB
Application	General dosimetry up to 4 GHz Dosimetry in strong gradient fields Compliance tests of mobile phones

#### Detailed information of Isotropic E-field Probe Type EX3DV4

Construction	Symmetrical design with triangular core Built-in shielding against static charges PEEK enclosure material (resistant to organic solvents, e.g., DGBE)
Calibration	Calibration certificate in Appendix C
Frequency	10 MHz to > 6 GHz Linearity: $\pm 0.2$ dB (30 MHz to 6 GHz)
Optical Surface Detection	$\pm 0.3$ mm repeatability in air and clear liquids over diffuse reflecting surfaces
Dimensions	Overall length: 337 mm (Tip: 20 mm) Tip diameter: 2.5 mm (Body: 12 mm) Typical distance from probe tip to dipole centers: 1 mm
Dynamic Range	10 $\mu$ W/g to > 100 W/kg Linearity: $\pm 0.2$ dB (noise: typically < 1 $\mu$ W/g)
Application	High precision dosimetric measurements in any exposure scenario (e.g., very strong gradient fields); the only probe that enables compliance testing for frequencies up to 6 GHz with precision of better 30%.

#### ANNEX A – TEST PLOTS

Please refer to the attachment.


#### ANNEX B – RELEVANT PAGES FROM CALIBRATION REPORTS


Please refer to the attachment.


#### ANNEX C – PHOTOGRAPH

Please refer to the attachment.


ANNEX A – TEST PLOTS

SYSTEM CHECKING SCANS	835MHz Head
Communication System: UID 10000, CW; Communication System Band: D835 (835.0 MHz); Frequency: 835 MHz; Communication System PAR: 0 dB Medium parameters used (interpolated): $f = 835 \text{ MHz}$ ; $\sigma = 0.891 \text{ S/m}$ ; $\epsilon_r = 41.412$ ; $\rho = 1000 \text{ kg/m}^3$ Phantom section: Flat Section Measurement Standard: DASYS5 (IEEE 1528-2013) DASYS5 Configuration: <ul style="list-style-type: none"> <li>Probe: ES3DV3 - SN3297; ConvF(6.08, 6.08, 6.08); Calibrated: 14/10/2016;</li> <li>Sensor-Surface: 3mm (Mechanical Surface Detection)</li> <li>Electronics: DAE4 Sn1226; Calibrated: 28/09/2016</li> <li>Phantom: SAM1; Type: SAM; Serial: TP1576</li> <li>Measurement SW: DASYS52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)</li> </ul>	
<b>835head/d=15mm, Pin=250 mW/Area Scan (61x121x1):</b> Measurement grid: dx=10mm, dy=10mm Maximum value of SAR (measured) = 2.40 W/kg <b>835head/d=15mm, Pin=250 mW/Zoom Scan (7x7x7) (7x7x7)/Cube 0:</b> Measurement grid: dx=5mm, dy=5mm, dz=5mm Reference Value = 55.873 V/m; Power Drift = 0.01 dB Peak SAR (extrapolated) = 3.43 W/kg <b>SAR(1 g) = 2.32 W/kg; SAR(10 g) = 1.53 W/kg</b> Maximum value of SAR (measured) = 2.64 W/kg	
	
<p>0 dB = 2.40 W/kg = 3.80 dBW/kg</p>	

SYSTEM CHECKING SCANS	835MHz Flat
<p>Communication System: UID 10000, CW; Communication System Band: D835 (835.0 MHz);            Frequency: 835 MHz; Communication System PAR: 0 dB            Medium parameters used: <math>f = 835 \text{ MHz}</math>; <math>\sigma = 0.956 \text{ S/m}</math>; <math>\epsilon_r = 54.875</math>; <math>\rho = 1000 \text{ kg/m}^3</math>            Phantom section: Flat Section            Measurement Standard: DASY5 (IEEE 1528-2013)            DASY5 Configuration:</p> <ul style="list-style-type: none"> <li>Probe: ES3DV3 - SN3297; ConvF(6.08, 6.08, 6.08); Calibrated: 14/10/2016;</li> <li>Sensor-Surface: 3mm (Mechanical Surface Detection)</li> <li>Electronics: DAE4 Sn1226; Calibrated: 28/09/2016</li> <li>Phantom: SAM1; Type: SAM; Serial: TP1576</li> <li>Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)</li> </ul> <p><b>835body/d=15mm, Pin=250 mW/Area Scan (7x13x1):</b> Measurement grid: dx=10mm, dy=10mm            Maximum value of SAR (measured) = 2.55 W/kg  <b>835body/d=15mm, Pin=250 mW/Zoom Scan (7x7x7) (7x7x7)/Cube 0:</b>            Measurement grid: dx=5mm, dy=5mm, dz=5mm            Reference Value = 53.557 V/m; Power Drift = 0.05 dB            Peak SAR (extrapolated) = 3.69 W/kg  <b>SAR(1 g) = 2.38 W/kg; SAR(10 g) = 1.56 W/kg</b>            Maximum value of SAR (measured) = 2.82 W/kg</p>	
 <p>0 dB = 2.55 W/kg = 4.07 dBW/kg</p>	

SYSTEM CHECKING SCANS	1750MHz Head
<p>Communication System: UID 10000, CW; Communication System Band: D1750 (1750.0 MHz); Frequency: 1750 MHz; Communication System PAR: 0 dB            Medium parameters used: <math>f = 1750</math> MHz; <math>\sigma = 1.38</math> S/m; <math>\epsilon_r = 39.746</math>; <math>\rho = 1000</math> kg/m<sup>3</sup>            Phantom section: Flat Section            Measurement Standard: DASYS5 (IEEE 1528-2013)            DASYS5 Configuration:</p> <ul style="list-style-type: none"> <li>Probe: ES3DV3 - SN3297; ConvF(5.22, 5.22, 5.22); Calibrated: 14/10/2016;</li> <li>Sensor-Surface: 3mm (Mechanical Surface Detection)</li> <li>Electronics: DAE4 Sn1226; Calibrated: 28/09/2016</li> <li>Phantom: SAM2; Type: SAM; Serial: TP-1575</li> <li>Measurement SW: DASYS52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)</li> </ul> <p><b>1750head/d=10mm, Pin=250 mW/Area Scan (41x61x1):</b> Measurement grid: dx=10mm, dy=10mm            Maximum value of SAR (measured) = 12.2 W/kg  <b>1750head/d=10mm, Pin=250 mW/Zoom Scan (7x7x7) (7x7x7)/Cube 0:</b>            Measurement grid: dx=5mm, dy=5mm, dz=5mm            Reference Value = 74.331 V/m; Power Drift = 0.01 dB            Peak SAR (extrapolated) = 17.4 W/kg  <b>SAR(1 g) = 9.44 W/kg; SAR(10 g) = 4.95 W/kg</b>            Maximum value of SAR (measured) = 12.0 W/kg</p>	
 <p>0 dB = 12.2 W/kg = 10.86 dBW/kg</p>	



SYSTEM CHECKING SCANS	1750MHz Flat
<p>Communication System: UID 10000, CW; Communication System Band: D1750 (17500.0 MHz); Frequency: 1750 MHz; Communication System PAR: 0 dB            Medium parameters used: <math>f = 1750</math> MHz; <math>\sigma = 1.463</math> S/m; <math>\epsilon_r = 52.358</math>; <math>\rho = 1000</math> kg/m<sup>3</sup>            Phantom section: Flat Section            Measurement Standard: DASYS5 (IEEE 1528-2013)            DASYS5 Configuration:</p> <ul style="list-style-type: none"> <li>Probe: EX3DV4 - SN3717; ConvF(7.63, 7.63, 7.63); Calibrated: 19/10/2016;</li> <li>Sensor-Surface: 1.4mm (Mechanical Surface Detection)</li> <li>Electronics: DAE4 Sn1327; Calibrated: 15/04/2016</li> <li>Phantom: ELI v4.0; Type: ELI4; Serial: TP:1086</li> <li>Measurement SW: DASYS52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)</li> </ul> <p><b>1750 body/d=10mm, Pin=250 mW/Area Scan (41x61x1):</b> Measurement grid: dx=10mm, dy=10mm            Maximum value of SAR (measured) = 11.5 W/kg  <b>1750 body/d=10mm, Pin=250 mW/Zoom Scan (7x7x7) (7x7x7)/Cube 0:</b>            Measurement grid: dx=5mm, dy=5mm, dz=5mm            Reference Value = 57.887 V/m; Power Drift = 0.09 dB            Peak SAR (extrapolated) = 18.1 W/kg  <b>SAR(1 g) = 9.46 W/kg; SAR(10 g) = 4.93 W/kg</b>            Maximum value of SAR (measured) = 10.7 W/kg</p>	
 <p>The figure displays a color scale for SAR field distribution in dB, ranging from 0 dB (yellow) to -33.49 dB (black). The scale includes intermediate values: -6.70, -13.39, -20.09, and -26.79. To the right, a 3D visualization shows a central high-intensity region (yellow/red) with a grid overlay, indicating the measurement area. A small 3D coordinate system is visible in the bottom left corner of the visualization.</p>	
<p>0 dB = 10.7 W/kg = 10.29 dBW/kg</p>	



<b>SYSTEM CHECKING SCANS</b>	<b>1900MHz Head</b>
------------------------------	---------------------

Communication System: UID 10000, CW; Communication System Band: D1900 (1900.0 MHz); Frequency: 1900 MHz; Communication System PAR: 0 dB  
 Medium parameters used:  $f = 1900 \text{ MHz}$ ;  $\sigma = 1.383 \text{ S/m}$ ;  $\epsilon_r = 39.568$ ;  $\rho = 1000 \text{ kg/m}^3$   
 Phantom section: Flat Section  
 Measurement Standard: DASYS5 (IEEE 1528-2013)  
 DASYS5 Configuration:

- Probe: ES3DV3 - SN3297; ConvF(5.09, 5.09, 5.09); Calibrated: 14/10/2016;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1226; Calibrated: 28/09/2016
- Phantom: SAM2; Type: SAM; Serial: TP-1575
- Measurement SW: DASYS52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**1900head/d=10mm, Pin=250 mW/Area Scan (41x61x1):** Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 12.0 W/kg

**1900head/d=10mm, Pin=250 mW/Zoom Scan (7x7x7) (7x7x7)/Cube 0:**


Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 57.925 V/m; Power Drift = 0.11 dB

Peak SAR (extrapolated) = 19.1 W/kg


**SAR(1 g) = 9.97 W/kg; SAR(10 g) = 5.24 W/kg**


Maximum value of SAR (measured) = 11.3 W/kg




0 dB = 12.0 W/kg = 10.79 dBW/kg

SYSTEM CHECKING SCANS	1900MHz Flat
<p>Communication System: UID 0, CW (0); Communication System Band: D1900 (1900.0 MHz); Frequency: 1900 MHz; Communication System PAR: 0 dB            Medium parameters used: <math>f = 1900 \text{ MHz}</math>; <math>\sigma = 1.492 \text{ S/m}</math>; <math>\epsilon_r = 52.586</math>; <math>\rho = 1000 \text{ kg/m}^3</math>            Phantom section: Flat Section            Measurement Standard: DASYS5 (IEEE 1528-2013)            DASYS5 Configuration:</p> <ul style="list-style-type: none"> <li>Probe: EX3DV4 - SN3717; ConvF(7.44, 7.44, 7.44); Calibrated: 19/10/2016;</li> <li>Sensor-Surface: 1.4mm (Mechanical Surface Detection)</li> <li>Electronics: DAE4 Sn1327; Calibrated: 15/04/2016</li> <li>Phantom: ELI v4.0; Type: ELI4; Serial: TP:1086</li> <li>Measurement SW: DASYS52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)</li> </ul> <p><b>1900body/d=10mm, Pin=250 mW/Area Scan (61x71x1):</b> Measurement grid: dx=10mm, dy=10mm            Maximum value of SAR (measured) = 12.6 W/kg  <b>1900body/d=10mm, Pin=250 mW/Zoom Scan (7x7x7) (7x7x7)/Cube 0:</b>            Measurement grid: dx=5mm, dy=5mm, dz=5mm            Reference Value = 70.500 V/m; Power Drift = 0.13 dB            Peak SAR (extrapolated) = 16.0 W/kg  <b>SAR(1 g) = 9.77 W/kg; SAR(10 g) = 5.16 W/kg</b>            Maximum value of SAR (measured) = 11.7 W/kg</p> <div data-bbox="279 1169 1305 1624"> <p>The figure displays a color scale for SAR values in dB, ranging from 0 dB (yellow) to -34.29 dB (black). The scale includes intermediate values: -6.86, -13.72, -20.58, and -27.43. To the right, a 3D visualization shows a phantom with a central rectangular area highlighted in a grid, representing the measurement region. A coordinate system (x, y, z) is visible in the bottom left corner of the 3D view.</p> </div> <p style="text-align: center;">0 dB = 12.6 W/kg = 11.01 dBW/kg</p>	

SYSTEM CHECKING SCANS	2450 MHz Head
<p>Communication System: UID 0, CW (0); Communication System Band: D2450 (2450.0 MHz); Frequency: 2450 MHz; Communication System PAR: 0 dB            Medium parameters used: <math>f = 2450</math> MHz; <math>\sigma = 1.782</math> S/m; <math>\epsilon_r = 38.672</math>; <math>\rho = 1000</math> kg/m<sup>3</sup>            Phantom section: Flat Section            Measurement Standard: DASYS5 (IEEE 1528-2013)            DASYS5 Configuration:</p> <ul style="list-style-type: none"> <li>Probe: EX3DV4 - SN3717; ConvF(6.96, 6.96, 6.96); Calibrated: 19/10/2016;</li> <li>Sensor-Surface: 1.4mm (Mechanical Surface Detection)</li> <li>Electronics: DAE4 Sn1327; Calibrated: 15/04/2016</li> <li>Phantom: SAM 1; Type: SAM; Serial: TP:1702</li> <li>Measurement SW: DASYS52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)</li> </ul> <p><b>2450head/d=10mm, Pin=250 mW/Area Scan (41x61x1):</b> Measurement grid: dx=10mm, dy=10mm            Maximum value of SAR (measured) = 17.0 W/kg  <b>2450head/d=10mm, Pin=250 mW/Zoom Scan (7x7x7) (7x7x7)/Cube 0:</b>            Measurement grid: dx=5mm, dy=5mm, dz=5mm            Reference Value = 96.244 V/m; Power Drift = 0.03 dB            Peak SAR (extrapolated) = 28.1 W/kg  <b>SAR(1 g) = 13.4 W/kg; SAR(10 g) = 6.13 W/kg</b>            Maximum value of SAR (measured) = 16.8 W/kg</p>	
 <p style="text-align: center;">0 dB = 17.0 W/kg = 12.30 dBW/kg</p>	

SYSTEM CHECKING SCANS	2450MHz Flat
<p>Communication System: UID 10000, CW; Communication System Band: D2450 (2450.0 MHz); Frequency: 2450 MHz; Communication System PAR: 0 dB            Medium parameters used: <math>f = 2450</math> MHz; <math>\sigma = 1.932</math> S/m; <math>\epsilon_r = 51.984</math>; <math>\rho = 1000</math> kg/m<sup>3</sup>            Phantom section: Flat Section            Measurement Standard: DASYS5 (IEEE 1528-2013)            DASYS5 Configuration:</p> <ul style="list-style-type: none"> <li>Probe: EX3DV4 - SN3717; ConvF(7.04, 7.04, 7.04); Calibrated: 19/10/2016;</li> <li>Sensor-Surface: 1.4mm (Mechanical Surface Detection)</li> <li>Electronics: DAE4 Sn1327; Calibrated: 15/04/2016</li> <li>Phantom: ELI v4.0; Type: ELI4; Serial: TP:1086</li> <li>Measurement SW: DASYS52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)</li> </ul> <p><b>2450body/d=10mm, Pin=250 mW/Area Scan (41x61x1):</b> Measurement grid: dx=10mm, dy=10mm            Maximum value of SAR (measured) = 16.3 W/kg  <b>2450body/d=10mm, Pin=250 mW/Zoom Scan (7x7x7) (7x7x7)/Cube 0:</b>            Measurement grid: dx=5mm, dy=5mm, dz=5mm            Reference Value = 67.342 V/m; Power Drift = -0.01 dB            Peak SAR (extrapolated) = 26.2 W/kg  <b>SAR(1 g) = 12.6 W/kg; SAR(10 g) = 5.86 W/kg</b>            Maximum value of SAR (measured) = 16.8 W/kg</p>	
	
<p>0 dB = 16.3 W/kg = 12.12 dBW/kg</p>	

SYSTEM CHECKING SCANS	2600 MHz Head
<p>Communication System: UID 0, CW; Communication System Band: D2600 (2600.0 MHz);                      Frequency: 2600 MHz; Communication System PAR: 0 dB                      Medium parameters used: <math>f = 2600</math> MHz; <math>\sigma = 1.971</math> S/m; <math>\epsilon_r = 38.9</math>; <math>\rho = 1000</math> kg/m<sup>3</sup>                      Phantom section: Flat Section                      Measurement Standard: DASYS5 (IEEE 1528-2013)                      DASYS5 Configuration:</p> <ul style="list-style-type: none"> <li>Probe: EX3DV4 - SN3717; ConvF(6.7, 6.7, 6.7); Calibrated: 19/10/2016;</li> <li>Sensor-Surface: 1.4mm (Mechanical Surface Detection)</li> <li>Electronics: DAE4 Sn1327; Calibrated: 15/04/2016</li> <li>Phantom: SAM 1; Type: SAM; Serial: TP:1702</li> <li>Measurement SW: DASYS52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)</li> </ul> <p><b>2600head/d=10mm, Pin=250 mW/Area Scan (61x101x1):</b> Measurement grid: dx=10mm, dy=10mm                      Maximum value of SAR (measured) = 18.8 W/kg  <b>2600head/d=10mm, Pin=250 mW/Zoom Scan (7x7x7) (7x7x7)/Cube 0:</b>                      Measurement grid: dx=5mm, dy=5mm, dz=5mm                      Reference Value = 93.316 V/m; Power Drift = 0.05 dB                      Peak SAR (extrapolated) = 36.2 W/kg  <b>SAR(1 g) = 14.3 W/kg; SAR(10 g) = 6.32 W/kg</b>                      Maximum value of SAR (measured) = 18.4 W/kg</p>	
	
<p>0 dB = 18.8 W/kg = 12.74 dBW/kg</p>	

SYSTEM CHECKING SCANS	2600MHz Flat
<p>Communication System: UID 0, CW; Communication System Band: D2600 (2600.0 MHz);            Frequency: 2600 MHz; Communication System PAR: 0 dB            Medium parameters used: <math>f = 2600</math> MHz; <math>\sigma = 2.131</math> S/m; <math>\epsilon_r = 52.232</math>; <math>\rho = 1000</math> kg/m<sup>3</sup>            Phantom section: Flat Section            Measurement Standard: DASYS5 (IEEE 1528-2013)            DASYS5 Configuration:</p> <ul style="list-style-type: none"> <li>Probe: EX3DV4 - SN3717; ConvF(6.86, 6.86, 6.86); Calibrated: 19/10/2016;</li> <li>Sensor-Surface: 1.4mm (Mechanical Surface Detection)</li> <li>Electronics: DAE4 Sn1327; Calibrated: 15/04/2016</li> <li>Phantom: ELI v4.0; Type: ELI4; Serial: TP:1086</li> <li>Measurement SW: DASYS52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)</li> </ul> <p><b>2600body/d=10mm, Pin=250 mW/Area Scan (41x61x1):</b> Measurement grid: dx=10mm, dy=10mm            Maximum value of SAR (measured) = 17.6 W/kg  <b>2600body/d=10mm, Pin=250 mW/Zoom Scan (7x7x7) (7x7x7)/Cube 0:</b>            Measurement grid: dx=5mm, dy=5mm, dz=5mm            Reference Value = 71.463 V/m; Power Drift = 0.01 dB            Peak SAR (extrapolated) = 26.2 W/kg  <b>SAR(1 g) = 14.2 W/kg; SAR(10 g) = 6.42 W/kg</b>            Maximum value of SAR (measured) = 16.8 W/kg</p> <div data-bbox="279 1169 1308 1624"> </div> <p style="text-align: center;">0 dB = 17.6 W/kg = 12.46 dBW/kg</p>	

**GSM (850MHz/Head)**

Left Side	Cheek
-----------	-------

Communication System: UID 0, GSM (0); Communication System Band: GSM850(824.0-849.0MHz); Frequency: 836.6 MHz; Communication System PAR: 9.191 dB  
Medium parameters used:  $f = 836.6$  MHz;  $\sigma = 0.883$  S/m;  $\epsilon_r = 41.292$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Left Section

Measurement Standard: DASY5 (IEEE1528-2013)

DASY5 Configuration:

- Probe: ES3DV3 - SN3297; ConvF(6.18, 6.18, 6.18); Calibrated: 14/10/2016;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1226; Calibrated: 28/09/2016
- Phantom: SAM1; Type: SAM; Serial: TP1576
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**left/touch mid/Area Scan (91x161x1):** Interpolated grid: dx=1.000 mm, dy=1.000 mm.

Maximum value of SAR = 0.163 W/kg


**left/touch mid/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 6.394 V/m; Power Drift = -0.11 dB

Peak SAR (extrapolated) = 0.185 W/kg

**SAR(1 g) = 0.143 W/kg; SAR(10 g) = 0.108 W/kg**

Maximum value of SAR (measured) = 0.157 W/kg



0 dB = 0.167 W/kg = -7.77 dBW/kg

Left Side	Tilt
Communication System: UID 0, GSM (0); Communication System Band: GSM850(824.0-849.0MHz); Frequency: 836.6 MHz; Communication System PAR: 9.191 dB Medium parameters used : $f = 836.6$ MHz; $\sigma = 0.883$ S/m; $\epsilon_r = 41.292$ ; $\rho = 1000$ kg/m <sup>3</sup>	



Phantom section: Left Section

Measurement Standard: DASYS (IEEE1528-2013)


DASY5 Configuration:


- Probe: ES3DV3 - SN3297; ConvF(6.18, 6.18, 6.18); Calibrated: 14/10/2016;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1226; Calibrated: 28/09/2016
- Phantom: SAM1; Type: SAM; Serial: TP1576
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)  
**left/tilt mid/Area Scan (91x161x1):** Interpolated grid: dx=1.000 mm, dy=1.000 mm  
Maximum value of SAR = 0.120 W/kg  
**left/tilt mid /Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm  
Reference Value = 6.394 V/m; Power Drift = -0.02 dB  
Peak SAR (extrapolated) = 0.105 W/kg  
**SAR(1 g) = 0.0918 W/kg; SAR(10 g) = 0.0550 W/kg**  
Maximum value of SAR (measured) = 0.111 W/kg




0 dB = 0.120 W/kg = -9.21 dBW/kg



Right Side	Cheek
<p>Communication System: UID 0, GSM (0); Communication System Band: GSM850(824.0-849.0MHz); Frequency: 836.6 MHz; Communication System PAR: 9.191 dB                      Medium parameters used: <math>f = 836.6 \text{ MHz}</math>; <math>\sigma = 0.883 \text{ S/m}</math>; <math>\epsilon_r = 41.292</math>; <math>\rho = 1000 \text{ kg/m}^3</math>                      Phantom section: Right Section                      Measurement Standard: DASYS (IEEE1528-2013)                      DASYS Configuration:</p> <ul style="list-style-type: none"> <li>• Probe: ES3DV3 - SN3297; ConvF(6.18, 6.18, 6.18); Calibrated: 14/10/2016;</li> <li>• Sensor-Surface: 3mm (Mechanical Surface Detection)</li> <li>• Electronics: DAE4 Sn1226; Calibrated: 28/09/2016</li> <li>• Phantom: SAM1; Type: SAM; Serial: TP1576</li> <li>• Measurement SW: DASYS2, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)</li> </ul> <p><b>right/touch mid/Area Scan (91x161x1):</b> Interpolated grid: <math>dx=1.000 \text{ mm}</math>, <math>dy=1.000 \text{ mm}</math>                      Maximum value of SAR = 0.167 W/kg  <b>right/touch mid/Zoom Scan (7x7x7)/Cube 0:</b> Measurement grid: <math>dx=5\text{mm}</math>, <math>dy=5\text{mm}</math>, <math>dz=5\text{mm}</math>                      Reference Value = 6.553 V/m; Power Drift = 0.06 dB                      Peak SAR (extrapolated) = 0.188 W/kg  <b>SAR(1 g) = 0.151 W/kg; SAR(10 g) = 0.115 W/kg.</b>                      Maximum value of SAR (measured) = 0.165 W/kg</p>	
 <p style="text-align: center;">0 dB = 0.167 W/kg = -7.77 dBW/kg</p>	

Right Side	Tilt
<p>Communication System: UID 0, GSM (0); Communication System Band: GSM850(824.0-849.0MHz); Frequency: 836.6 MHz; Communication System PAR: 9.191 dB                      Medium parameters used : f = 836.6 MHz; <math>\sigma = 0.883</math> S/m; <math>\epsilon_r = 41.292</math>; <math>\rho = 1000</math> kg/m<sup>3</sup>                      Phantom section: Right Section                      Measurement Standard: DASYS (IEEE1528-2013)                      DASYS Configuration:</p> <ul style="list-style-type: none"> <li>Probe: ES3DV3 - SN3297; ConvF(6.18, 6.18, 6.18); Calibrated: 14/10/2016;</li> <li>Sensor-Surface: 3mm (Mechanical Surface Detection)</li> <li>Electronics: DAE4 Sn1226; Calibrated: 28/09/2016</li> <li>Phantom: SAM1; Type: SAM; Serial: TP1576</li> <li>Measurement SW: DASYS2, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)</li> </ul> <p><b>right/tilt mid/Area Scan (91x161x1):</b> Interpolated grid: dx=1.000 mm, dy=1.000 mm                      Maximum value of SAR = 0.0921 W/kg  <b>right/tilt mid/ Zoom Scan (7x7x7)/Cube 0:</b> Measurement grid: dx=5mm, dy=5mm, dz=5mm                      Reference Value = 5.503 V/m; Power Drift = -0.09 dB                      Peak SAR (extrapolated) = 0.108 W/kg  <b>SAR(1 g) = 0.0809 W/kg; SAR(10 g) = 0.0563 W/kg.</b>                      Maximum value of SAR (measured) = 0.0905 W/kg</p>	
 <p style="text-align: center;">0 dB = 0.0921 W/kg = -10.36 dBW/kg</p>	


**GSM with headset (850MHz/Flat)**

FLAT	Towards phantom
Communication System: UID 0, GSM (0); Communication System Band: GSM850(824.0-849.0MHz); Frequency: 836.6 MHz; Communication System PAR: 9.191 dB Medium parameters used: $f = 837 \text{ MHz}$ ; $\sigma = 0.951 \text{ S/m}$ ; $\epsilon_r = 54.241$ ; $\rho = 1000 \text{ kg/m}^3$ Phantom section: Flat Section Measurement Standard: DASY5 (IEEE1528-2013) DASY5 Configuration:	
<ul style="list-style-type: none"> <li>• Probe: ES3DV3 - SN3297; ConvF(6.08, 6.08, 6.08); Calibrated: 14/10/2016;</li> <li>• Sensor-Surface: 3mm (Mechanical Surface Detection)</li> <li>• Electronics: DAE4 Sn1226; Calibrated: 28/09/2016</li> <li>• Phantom: SAM1; Type: SAM; Serial: TP1576</li> <li>• Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)</li> </ul>	
<p><b>body/towards phantom headset/Area Scan (91x161x1):</b> Interpolated grid:  <math>dx=1.000 \text{ mm}</math>, <math>dy=1.000 \text{ mm}</math>                      Maximum value of SAR = 0.167 W/kg</p> <p><b>body/towards phantom headset/Zoom Scan (7x7x7)/Cube 0:</b> Measurement grid:  <math>dx=5\text{mm}</math>, <math>dy=5\text{mm}</math>, <math>dz=5\text{mm}</math>                      Reference Value = 13.59 V/m; Power Drift = 0.08 dB                      Peak SAR (extrapolated) = 0.237 W/kg  <b>SAR(1 g) = 0.148 W/kg; SAR(10 g) = 0.105 W/kg</b></p>	
Maximum value of SAR (measured) = 0.166 W/kg	
 <p>0 dB = 0.167 W/kg = -7.77 dBW/kg</p>	

FLAT	Towards ground
------	----------------


Communication System: UID 0, GSM (0); Communication System Band: GSM850(824.0-849.0MHz); Frequency: 836.6 MHz; Communication System PAR: 9.191 dB  
Medium parameters used:  $f = 837 \text{ MHz}$ ;  $\sigma = 0.951 \text{ S/m}$ ;  $\epsilon_r = 54.241$ ;  $\rho = 1000 \text{ kg/m}^3$   
Phantom section: Flat Section  
Measurement Standard: DASY5 (IEEE 1528-2013)  
DASY5 Configuration:


- Probe: ES3DV3 - SN3297; ConvF(6.08, 6.08, 6.08); Calibrated: 14/10/2016;
  - Sensor-Surface: 3mm (Mechanical Surface Detection)
  - Electronics: DAE4 Sn1226; Calibrated: 28/09/2016
  - Phantom: SAM1; Type: SAM; Serial: TP1576
  - Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)
- body/towards ground headset/Area Scan (91x161x1):** Interpolated grid:  $dx=1.000 \text{ mm}$ ,  $dy=1.000 \text{ mm}$   
Maximum value of SAR = 0.290 W/kg  
**body/towards ground headset/Zoom Scan (7x7x7)/Cube 0:** Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=5\text{mm}$   
Reference Value = 17.88 V/m; Power Drift = 0.08 dB  
Peak SAR (extrapolated) = 0.338 W/kg  
**SAR(1 g) = 0.266 W/kg; SAR(10 g) = 0.206 W/kg**  
Maximum value of SAR (measured) = 0.291 W/kg



0 dB = 0.290 W/kg = -5.38 dBW/kg

**GSM (850MHz with GPRS/Flat)**

FLAT	Towards phantom
Communication System: UID 0, GPRS/EGPRS(4UP) (0); Communication System Band: GSM850; Frequency: 836.6 MHz; Communication System PAR: 3.18 dB Medium parameters used: f = 837 MHz; $\sigma = 0.951$ S/m; $\epsilon_r = 54.241$ ; $\rho = 1000$ kg/m <sup>3</sup> Phantom section: Flat Section Measurement Standard: DASY5 (IEEE1528-2013) DASY5 Configuration:	
<ul style="list-style-type: none"> <li>• Probe: ES3DV3 - SN3297; ConvF(6.08, 6.08, 6.08); Calibrated: 14/10/2016;</li> <li>• Sensor-Surface: 3mm (Mechanical Surface Detection)</li> <li>• Electronics: DAE4 Sn1226; Calibrated: 28/09/2016</li> <li>• Phantom: SAM1; Type: SAM; Serial: TP1576</li> <li>• Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)</li> </ul>	
<p><b>body/towards phantom GPRS/Area Scan (91x161x1):</b> Interpolated grid: dx=1.000 mm, dy=1.000 mm                      Maximum value of SAR = 0.142 W/kg</p> <p><b>body/towards phantom GPRS/Zoom Scan (7x7x7)/Cube 0:</b> Measurement grid: dx=5mm, dy=5mm, dz=5mm                      Reference Value = 12.43 V/m; Power Drift = -0.01 dB                      Peak SAR (extrapolated) = 0.201 W/kg  <b>SAR(1 g) = 0.126 W/kg; SAR(10 g) = 0.0899 W/kg</b></p>	
Maximum value of SAR (measured) = 0.142 W/kg	
	
<p style="text-align: center;">0 dB = 0.142 W/kg = -8.48 dBW/kg</p>	

FLAT	Towards ground
<p>Communication System: UID 0, GPRS/EGPRS(4UP) (0); Communication System Band: GSM850; Frequency: 836.6 MHz; Communication System PAR: 3.18 dB            Medium parameters used: <math>f = 837</math> MHz; <math>\sigma = 0.951</math> S/m; <math>\epsilon_r = 54.241</math>; <math>\rho = 1000</math> kg/m<sup>3</sup>            Phantom section: Flat Section            Measurement Standard: DASYS5 (IEEE1528-2013)            DASYS5 Configuration:</p> <ul style="list-style-type: none"> <li>Probe: ES3DV3 - SN3297; ConvF(6.08, 6.08, 6.08); Calibrated: 14/10/2016;</li> <li>Sensor-Surface: 3mm (Mechanical Surface Detection)</li> <li>Electronics: DAE4 Sn1226; Calibrated: 28/09/2016</li> <li>Phantom: SAM1; Type: SAM; Serial: TP1576</li> <li>Measurement SW: DASYS52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)</li> </ul> <p><b>body/towards ground GPRS/Area Scan (91x161x1):</b> Interpolated grid: dx=1.000 mm, dy=1.000 mm            Maximum value of SAR = 0.236 W/kg</p> <p><b>body/towards ground GPRS/Zoom Scan (7x7x7)/Cube 0:</b> Measurement grid: dx=5mm, dy=5mm, dz=5mm            Reference Value = 16.06 V/m; Power Drift = -0.02 dB            Peak SAR (extrapolated) = 0.237 W/kg  <b>SAR(1 g) = 0.209 W/kg; SAR(10 g) = 0.148 W/kg</b></p> <p>Maximum value of SAR (measured) = 0.236 W/kg</p>	
 <p style="text-align: center;">0 dB = 0.236 W/kg = -6.27 dBW/kg</p>	

### GSM (850MHz with EGPRS/Flat)



FLAT	Towards phantom
<p>Communication System: UID 0, GPRS/EGPRS(4UP) (0); Communication System Band: GSM850; Frequency: 836.6 MHz; Communication System PAR: 3.18 dB            Medium parameters used: <math>f = 837 \text{ MHz}</math>; <math>\sigma = 0.951 \text{ S/m}</math>; <math>\epsilon_r = 54.241</math>; <math>\rho = 1000 \text{ kg/m}^3</math>            Phantom section: Flat Section            Measurement Standard: DASY5 (IEEE 1528-2013)            DASY5 Configuration:</p> <ul style="list-style-type: none"> <li>Probe: ES3DV3 - SN3297; ConvF(6.08, 6.08, 6.08); Calibrated: 14/10/2016;</li> <li>Sensor-Surface: 3mm (Mechanical Surface Detection)</li> <li>Electronics: DAE4 Sn1226; Calibrated: 28/09/2016</li> <li>Phantom: SAM1; Type: SAM; Serial: TP1576</li> <li>Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)</li> </ul> <p><b>body/towards phantom EGPRS/Area Scan (91x161x1):</b> Interpolated grid:  <math>dx=1.000 \text{ mm}</math>, <math>dy=1.000 \text{ mm}</math>            Maximum value of SAR = 0.143 W/kg  <b>body/towards phantom EGPRS/Zoom Scan (7x7x7)/Cube 0:</b> Measurement grid:  <math>dx=5\text{mm}</math>, <math>dy=5\text{mm}</math>, <math>dz=5\text{mm}</math>            Reference Value = 12.63 V/m; Power Drift = -0.09 dB            Peak SAR (extrapolated) = 0.295 W/kg  <b>SAR(1 g) = 0.127 W/kg; SAR(10 g) = 0.0904 W/kg</b></p> <p>Maximum value of SAR (measured) = 0.143 W/kg</p> <div data-bbox="181 1227 1402 1680"> </div> <p>0 dB = 0.143 W/kg = -8.45 dBW/kg</p>	

FLAT	Towards ground
------	----------------

Communication System: UID 0, GPRS/EGPRS(4UP) (0); Communication System Band: GSM850; Frequency: 836.6 MHz; Communication System PAR: 3.18 dB

Medium parameters used:  $f = 837$  MHz;  $\sigma = 0.951$  S/m;  $\epsilon_r = 54.241$ ;  $\rho = 1000$  kg/m<sup>3</sup>


Phantom section: Flat Section

Measurement Standard: DASYS5 (IEEE1528-2013)

DASY5 Configuration:


- Probe: ES3DV3 - SN3297; ConvF(6.08, 6.08, 6.08); Calibrated: 14/10/2016;
  - Sensor-Surface: 3mm (Mechanical Surface Detection)
  - Electronics: DAE4 Sn1226; Calibrated: 28/09/2016
  - Phantom: SAM1; Type: SAM; Serial: TP1576
  - Measurement SW: DASYS2, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)
- body/towards ground EGPRS/Area Scan (91x161x1):** Interpolated grid: dx=1.000 mm, dy=1.000 mm  
 Maximum value of SAR = 0.242 W/kg  
**body/towards ground EGPRS/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm  
 Reference Value = 16.18 V/m; Power Drift = -0.05 dB  
 Peak SAR (extrapolated) = 0.415 W/kg  
**SAR(1 g) = 0.214 W/kg; SAR(10 g) = 0.152 W/kg**


Maximum value of SAR (measured) = 0.241 W/kg



0 dB = 0.242 W/kg = -6.16 dBW/kg



FLAT	EDGE2
<p>Communication System: UID 0, FDD-LTE(QPSK_10M_1RB_low) (0); Communication System Band: BAND 5; Frequency: 836.5 MHz; Communication System PAR: 0 dB            Medium parameters used : f = 836.5 MHz; <math>\sigma = 0.95</math> S/m; <math>\epsilon_r = 54.245</math>; <math>\rho = 1000</math> kg/m<sup>3</sup>            Phantom section: Flat Section            Measurement Standard: DASYS (IEEE1528-2013)            DASYS Configuration:</p> <ul style="list-style-type: none"> <li>Probe: ES3DV3 - SN3297; ConvF(6.08, 6.08, 6.08); Calibrated: 14/10/2016;</li> <li>Sensor-Surface: 3mm (Mechanical Surface Detection)</li> <li>Electronics: DAE4 Sn1226; Calibrated: 28/09/2016</li> <li>Phantom: SAM1; Type: SAM; Serial: TP1576</li> <li>Measurement SW: DASYS2, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)</li> </ul> <p><b>body/edge 2 mid/Area Scan (61x101x1):</b> Interpolated grid: dx=1.000 mm, dy=1.000 mm            Maximum value of SAR = 0.0526 W/kg  <b>body/edge 2 mid/Zoom Scan (7x7x7)/Cube 0:</b> Measurement grid: dx=5mm, dy=5mm, dz=5mm            Reference Value = 5.792 V/m; Power Drift = 0.12 dB            Peak SAR (extrapolated) = 0.186 W/kg  <b>SAR(1 g) = 0.0443 W/kg; SAR(10 g) = 0.0277 W/kg.</b>            Maximum value of SAR (measured) = 0.0491 W/kg</p>	
 <p style="text-align: center;">0 dB = 0.0526 W/kg = -12.79 dBW/kg</p>	

FLAT	EDGE3
<p>Communication System: UID 0, FDD-LTE(QPSK_10M_1RB_low) (0); Communication System Band: BAND 5; Frequency: 836.5 MHz; Communication System PAR: 0 dB            Medium parameters used : <math>f = 836.5 \text{ MHz}</math>; <math>\sigma = 0.95 \text{ S/m}</math>; <math>\epsilon_r = 54.245</math>; <math>\rho = 1000 \text{ kg/m}^3</math>            Phantom section: Flat Section            Measurement Standard: DASY5 (IEEE1528-2013)            DASY5 Configuration:</p> <ul style="list-style-type: none"> <li>Probe: ES3DV3 - SN3297; ConvF(6.08, 6.08, 6.08); Calibrated: 14/10/2016;</li> <li>Sensor-Surface: 3mm (Mechanical Surface Detection)</li> <li>Electronics: DAE4 Sn1226; Calibrated: 28/09/2016</li> <li>Phantom: SAM1; Type: SAM; Serial: TP1576</li> <li>Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)</li> </ul> <p><b>body2/edge3 mid/Area Scan (61x161x1):</b> Interpolated grid: <math>dx=1.000 \text{ mm}</math>, <math>dy=1.000 \text{ mm}</math>            Maximum value of SAR = 0.122 W/kg  <b>body2/edge3 mid/Zoom Scan (7x7x7)/Cube 0:</b> Measurement grid: <math>dx=5\text{mm}</math>, <math>dy=5\text{mm}</math>, <math>dz=5\text{mm}</math>            Reference Value = 11.4 V/m; Power Drift = 0.02 dB            Peak SAR (extrapolated) = 0.264 W/kg  <b>SAR(1 g) = 0.107 W/kg; SAR(10 g) = 0.0722 W/kg</b>            Maximum value of SAR (measured) = 0.120 W/kg</p>	
 <p style="text-align: center;">0 dB = 0.122 W/kg = -9.14 dBW/kg</p>	

FLAT	EDGE4
<p>Communication System: UID 0, FDD-LTE(QPSK_10M_1RB_low) (0); Communication System Band: BAND 5; Frequency: 836.5 MHz; Communication System PAR: 0 dB Medium parameters used : f = 836.5 MHz; <math>\sigma = 0.95</math> S/m; <math>\epsilon_r = 54.245</math>; <math>\rho = 1000</math> kg/m<sup>3</sup> Phantom section: Flat Section Measurement Standard: DASY5 (IEEE1528-2013) DASY5 Configuration:</p> <ul style="list-style-type: none"> <li>Probe: ES3DV3 - SN3297; ConvF(6.08, 6.08, 6.08); Calibrated: 14/10/2016;</li> <li>Sensor-Surface: 3mm (Mechanical Surface Detection)</li> <li>Electronics: DAE4 Sn1226; Calibrated: 28/09/2016</li> <li>Phantom: SAM1; Type: SAM; Serial: TP1576</li> <li>Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)</li> </ul> <p><b>body2/edge4 mid/Area Scan (61x161x1):</b> Interpolated grid: dx=1.000 mm, dy=1.000 mm Maximum value of SAR = 0.158 W/kg <b>body2/edge4 mid/ Zoom Scan (7x7x7)/Cube 0:</b> Measurement grid: dx=5mm, dy=5mm, dz=5mm Reference Value = 13.14 V/m; Power Drift = 0.02 dB Peak SAR (extrapolated) = 0.257 W/kg <b>SAR(1 g) = 0.138 W/kg; SAR(10 g) = 0.0927 W/kg</b></p> <p>Maximum value of SAR (measured) = 0.157 W/kg</p> <div style="display: flex; align-items: center;"> <div style="margin-right: 20px;"> <p><b>dB</b></p> <p>0 -3.37 -6.74 -10.11 -13.48 -16.85</p> </div> <div> </div> </div> <p style="text-align: center;">0 dB = 0.158 W/kg = -8.01 dBW/kg</p>	


**GSM (1900MHz/Head)**

Left Side	Cheek
-----------	-------


Communication System: UID 10021 - DAB, GSM-FDD (TDMA, GMSK); Frequency: 1880 MHz; Duty Cycle: 1:8.6896  
 Medium parameters used:  $f = 1880$  MHz;  $\sigma = 1.45$  S/m;  $\epsilon_r = 39.74$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
 Phantom section: Left Section


DASY5 Configuration:

- Probe: EX3DV4 - SN3708; ConvF(7.84, 7.84, 7.84); Calibrated: 2016/11/10;
  - Sensor-Surface: 4mm (Mechanical Surface Detection)
  - Electronics: DAE4 Sn720; Calibrated: 2016/10/31
  - Phantom: 1660; Type: QD 000 P40 CD; Serial: xxxx
  - Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373)
- Head-Section HSL 1900 LEFT/1900GSM HSL touch M/Area Scan (8x13x1):**  
 Measurement grid: dx=15mm, dy=15mm  
 Maximum value of SAR (measured) = 0.104 W/kg
- Head-Section HSL 1900 LEFT/1900GSM HSL touch M/Zoom Scan (7x7x7)/Cube 0:**  
 Measurement grid: dx=5mm, dy=5mm, dz=5mm  
 Reference Value = 4.405 V/m; Power Drift = 0.10 dB  
 Peak SAR (extrapolated) = 0.177 W/kg  
**SAR(1 g) = 0.112 W/kg; SAR(10 g) = 0.070 W/kg**  
 Maximum value of SAR (measured) = 0.122 W/kg




0 dB = 0.122 W/kg = -9.14 dBW/kg


Left Side	Tilt
Communication System: UID 10021 - DAB, GSM-FDD (TDMA, GMSK); Frequency: 1880 MHz; Duty Cycle: 1:8.6896 Medium parameters used: $f = 1880 \text{ MHz}$ ; $\sigma = 1.45 \text{ S/m}$ ; $\epsilon_r = 39.74$ ; $\rho = 1000 \text{ kg/m}^3$ Phantom section: Left Section	
DASY5 Configuration:	
<ul style="list-style-type: none"> <li>• Probe: EX3DV4 - SN3708; ConvF(7.84, 7.84, 7.84); Calibrated: 2016/11/10;</li> <li>• Sensor-Surface: 4mm (Mechanical Surface Detection)</li> <li>• Electronics: DAE4 Sn720; Calibrated: 2016/10/31</li> <li>• Phantom: 1660; Type: QD 000 P40 CD; Serial: xxxx</li> <li>• Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373)</li> </ul> <p><b>Head-Section HSL 1900 LEFT/1900GSM HSL tilt M/Area Scan (8x13x1):</b>                      Measurement grid: <math>dx=15\text{mm}</math>, <math>dy=15\text{mm}</math>                      Maximum value of SAR (measured) = 0.0521 W/kg</p> <p><b>Head-Section HSL 1900 LEFT/1900GSM HSL tilt M/Zoom Scan (7x7x7)/Cube 0:</b>                      Measurement grid: <math>dx=5\text{mm}</math>, <math>dy=5\text{mm}</math>, <math>dz=5\text{mm}</math>                      Reference Value = 6.099 V/m; Power Drift = 0.13 dB                      Peak SAR (extrapolated) = 0.0820 W/kg  <b>SAR(1 g) = 0.049 W/kg; SAR(10 g) = 0.028 W/kg</b>                      Maximum value of SAR (measured) = 0.0550 W/kg</p>	
 <p style="text-align: center;">0 dB = 0.0550 W/kg = -12.60 dBW/kg</p>	

Right Side	Cheek
<p>Communication System: UID 10021 - DAB, GSM-FDD (TDMA, GMSK); Frequency: 1880 MHz; Duty Cycle: 1:8.6896 Medium parameters used: <math>f = 1880</math> MHz; <math>\sigma = 1.45</math> S/m; <math>\epsilon_r = 39.74</math>; <math>\rho = 1000</math> kg/m<sup>3</sup> Phantom section: Right Section</p>	
<p>DASY5 Configuration:</p>	
<ul style="list-style-type: none"> <li>Probe: EX3DV4 - SN3708; ConvF(7.84, 7.84, 7.84); Calibrated: 2016/11/10;</li> <li>Sensor-Surface: 4mm (Mechanical Surface Detection)</li> <li>Electronics: DAE4 Sn720; Calibrated: 2016/10/31</li> <li>Phantom: 1660; Type: QD 000 P40 CD; Serial: xxxx</li> <li>Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373)</li> </ul> <p><b>Head-Section HSL 1900 RIGHT/1900GSM HSL touch M/Area Scan (8x13x1):</b> Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (measured) = 0.158 W/kg</p> <p><b>Head-Section HSL 1900 RIGHT/1900GSM HSL touch M/Zoom Scan (7x7x7)/Cube 0:</b> Measurement grid: dx=5mm, dy=5mm, dz=5mm Reference Value = 4.306 V/m; Power Drift = 0.50 dB Peak SAR (extrapolated) = 0.243 W/kg <b>SAR(1 g) = 0.152 W/kg; SAR(10 g) = 0.091 W/kg</b> Maximum value of SAR (measured) = 0.163 W/kg</p>	
 <p>0 dB = 0.163 W/kg = -7.88 dBW/kg</p>	




Right Side	Tilt
Communication System: UID 10021 - DAB, GSM-FDD (TDMA, GMSK); Frequency: 1880 MHz; Duty Cycle: 1:8.6896 Medium parameters used: $f = 1880$ MHz; $\sigma = 1.45$ S/m; $\epsilon_r = 39.74$ ; $\rho = 1000$ kg/m <sup>3</sup> Phantom section: Right Section	
DASY5 Configuration:	
<ul style="list-style-type: none"> <li>• Probe: EX3DV4 - SN3708; ConvF(7.84, 7.84, 7.84); Calibrated: 2016/11/10;</li> <li>• Sensor-Surface: 4mm (Mechanical Surface Detection)</li> <li>• Electronics: DAE4 Sn720; Calibrated: 2016/10/31</li> <li>• Phantom: 1660; Type: QD 000 P40 CD; Serial: xxxx</li> <li>• Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373)</li> </ul> <p><b>Head-Section HSL 1900 RIGHT/1900GSM HSL tilt M/Area Scan (8x13x1):</b>                      Measurement grid: dx=15mm, dy=15mm                      Maximum value of SAR (measured) = 0.0522 W/kg</p> <p><b>Head-Section HSL 1900 RIGHT/1900GSM HSL tilt M/Zoom Scan (7x7x7)/Cube 0:</b>                      Measurement grid: dx=5mm, dy=5mm, dz=5mm                      Reference Value = 6.724 V/m; Power Drift = 0.13 dB                      Peak SAR (extrapolated) = 0.0970 W/kg  <b>SAR(1 g) = 0.057 W/kg; SAR(10 g) = 0.033 W/kg</b>                      Maximum value of SAR (measured) = 0.0649 W/kg</p>	
 <p>0 dB = 0.0649 W/kg = -11.88 dBW/kg</p>	


**GSM with headset (1900MHz/Flat)**

FLAT	Towards phantom
Communication System: UID 10021 - DAB, GSM-FDD (TDMA, GMSK); Frequency: 1880 MHz; Duty Cycle: 1:8.6896 Medium parameters used: $f = 1880$ MHz; $\sigma = 1.57$ S/m; $\epsilon_r = 51.14$ ; $\rho = 1000$ kg/m <sup>3</sup> Phantom section: Flat Section	
DASY5 Configuration: <ul style="list-style-type: none"> <li>Probe: EX3DV4 - SN3708; ConvF(7.79, 7.79, 7.79); Calibrated: 2016/11/10;</li> <li>Sensor-Surface: 4mm (Mechanical Surface Detection)</li> <li>Electronics: DAE4 Sn720; Calibrated: 2016/10/31</li> <li>Phantom: 1659; Type: QD 000 P40 CD; Serial: xxxx</li> <li>Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373)</li> </ul> <b>Flat-Section MSL 1900 TP/1900GSM TP M 10mm/Area Scan (9x13x1):</b> Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (measured) = 0.254 W/kg <b>Flat-Section MSL 1900 TP/1900GSM TP M 10mm/Zoom Scan (7x7x7)/Cube 0:</b> Measurement grid: dx=5mm, dy=5mm, dz=5mm Reference Value = 5.485 V/m; Power Drift = 0.06 dB Peak SAR (extrapolated) = 0.375 W/kg <b>SAR(1 g) = 0.231 W/kg; SAR(10 g) = 0.137 W/kg</b> Maximum value of SAR (measured) = 0.256 W/kg	
 <p>0 dB = 0.256 W/kg = -5.92 dBW/kg</p>	



FLAT	Towards ground
Communication System: UID 10021 - DAB, GSM-FDD (TDMA, GMSK); Frequency: 1880 MHz; Duty Cycle: 1:8.6896 Medium parameters used: $f = 1880$ MHz; $\sigma = 1.57$ S/m; $\epsilon_r = 51.14$ ; $\rho = 1000$ kg/m <sup>3</sup> Phantom section: Flat Section	
DASY5 Configuration:	
<ul style="list-style-type: none"> <li>• Probe: EX3DV4 - SN3708; ConvF(7.79, 7.79, 7.79); Calibrated: 2016/11/10;</li> <li>• Sensor-Surface: 4mm (Mechanical Surface Detection)</li> <li>• Electronics: DAE4 Sn720; Calibrated: 2016/10/31</li> <li>• Phantom: 1659; Type: QD 000 P40 CD; Serial: xxxx</li> <li>• Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373)</li> </ul> <p><b>Flat-Section MSL 1900 TG/1900GSM TG M 10mm 2/Area Scan (9x13x1):</b>            Measurement grid: dx=15mm, dy=15mm            Maximum value of SAR (measured) = 0.601 W/kg</p> <p><b>Flat-Section MSL 1900 TG/1900GSM TG M 10mm 2/Zoom Scan (7x7x7)/Cube 0:</b>            Measurement grid: dx=5mm, dy=5mm, dz=5mm            Reference Value = 6.577 V/m; Power Drift = -0.15 dB            Peak SAR (extrapolated) = 1.26 W/kg  <b>SAR(1 g) = 0.695 W/kg; SAR(10 g) = 0.364 W/kg</b>            Maximum value of SAR (measured) = 0.773 W/kg</p>	
 <p>0 dB = 0.773 W/kg = -1.12 dBW/kg</p>	

**GSM (1900MHz with GPRS/Flat)**


FLAT	Towards phantom
Communication System: UID 10021 - DAB, GSM-FDD (TDMA, GMSK); Frequency: 1880 MHz; Duty Cycle: 1:8.6896 Medium parameters used: $f = 1880$ MHz; $\sigma = 1.57$ S/m; $\epsilon_r = 51.14$ ; $\rho = 1000$ kg/m <sup>3</sup> Phantom section: Flat Section	
DASY5 Configuration: <ul style="list-style-type: none"> <li>Probe: EX3DV4 - SN3708; ConvF(7.79, 7.79, 7.79); Calibrated: 2016/11/10;</li> <li>Sensor-Surface: 4mm (Mechanical Surface Detection)</li> <li>Electronics: DAE4 Sn720; Calibrated: 2016/10/31</li> <li>Phantom: 1659; Type: QD 000 P40 CD; Serial: xxxx</li> <li>Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373)</li> </ul> <b>Flat-Section MSL 1900 TP/1900GPRS TP M 10mm/Area Scan (9x13x1):</b> Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (measured) = 0.175 W/kg <b>Flat-Section MSL 1900 TP/1900GPRS TP M 10mm/Zoom Scan (7x7x7)/Cube 0:</b> Measurement grid: dx=5mm, dy=5mm, dz=5mm Reference Value = 4.700 V/m; Power Drift = -0.12 dB Peak SAR (extrapolated) = 0.272 W/kg <b>SAR(1 g) = 0.166 W/kg; SAR(10 g) = 0.099 W/kg</b> Maximum value of SAR (measured) = 0.182 W/kg	
 <p>0 dB = 0.182 W/kg = -7.40 dBW/kg</p>	

FLAT	Towards ground
Communication System: UID 10021 - DAB, GSM-FDD (TDMA, GMSK); Frequency: 1880 MHz; Duty Cycle: 1:8.6896 Medium parameters used: $f = 1880$ MHz; $\sigma = 1.57$ S/m; $\epsilon_r = 51.14$ ; $\rho = 1000$ kg/m <sup>3</sup>	

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3708; ConvF(7.79, 7.79, 7.79); Calibrated: 2016/11/10;
  - Sensor-Surface: 4mm (Mechanical Surface Detection)
  - Electronics: DAE4 Sn720; Calibrated: 2016/10/31
  - Phantom: 1659; Type: QD 000 P40 CD; Serial: xxxx
  - Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373)
- Flat-Section MSL 1900 TG/1900GPRS TG M 10mm 2/Area Scan (9x13x1):**  
Measurement grid: dx=15mm, dy=15mm  
Maximum value of SAR (measured) = 0.396 W/kg
- Flat-Section MSL 1900 TG/1900GPRS TG M 10mm 2/Zoom Scan (7x7x7)/Cube 0:**  
Measurement grid: dx=5mm, dy=5mm, dz=5mm  
Reference Value = 5.251 V/m; Power Drift = 0.11 dB  
Peak SAR (extrapolated) = 1.33 W/kg  
**SAR(1 g) = 0.518 W/kg; SAR(10 g) = 0.269 W/kg**  
Maximum value of SAR (measured) = 0.592 W/kg




0 dB = 0.592 W/kg = -2.28 dBW/kg

**GSM (1900MHz with EGPRS/Flat)**

FLAT	Towards phantom
Communication System: UID 10021 - DAB, GSM-FDD (TDMA, GMSK); Frequency: 1880 MHz; Duty Cycle: 1:8.6896 Medium parameters used: f = 1880 MHz; $\sigma = 1.57$ S/m; $\epsilon_r = 51.14$ ; $\rho = 1000$ kg/m <sup>3</sup> Phantom section: Flat Section	
DASY5 Configuration:	


- Probe: EX3DV4 - SN3708; ConvF(7.79, 7.79, 7.79); Calibrated: 2016/11/10;
  - Sensor-Surface: 4mm (Mechanical Surface Detection)
  - Electronics: DAE4 Sn720; Calibrated: 2016/10/31
  - Phantom: 1659; Type: QD 000 P40 CD; Serial: xxxx
  - Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373)
- Flat-Section MSL 1900 TP/1900EDGE TP M 10mm/Area Scan (9x13x1):**  
Measurement grid: dx=15mm, dy=15mm  
Maximum value of SAR (measured) = 0.181 W/kg
- Flat-Section MSL 1900 TP/1900EDGE TP M 10mm/Zoom Scan (7x7x7)/Cube 0:**  
Measurement grid: dx=5mm, dy=5mm, dz=5mm  
Reference Value = 4.552 V/m; Power Drift = -0.17 dB  
Peak SAR (extrapolated) = 0.279 W/kg  
**SAR(1 g) = 0.169 W/kg; SAR(10 g) = 0.100 W/kg**  
Maximum value of SAR (measured) = 0.186 W/kg



0 dB = 0.186 W/kg = -7.30 dBW/kg

FLAT	Towards ground
Communication System: UID 10021 - DAB, GSM-FDD (TDMA, GMSK); Frequency: 1880 MHz; Duty Cycle: 1:8.6896 Medium parameters used: $f = 1880$ MHz; $\sigma = 1.57$ S/m; $\epsilon_r = 51.14$ ; $\rho = 1000$ kg/m <sup>3</sup> Phantom section: Flat Section	
DASY5 Configuration:	
<ul style="list-style-type: none"> <li>• Probe: EX3DV4 - SN3708; ConvF(7.79, 7.79, 7.79); Calibrated: 2016/11/10;</li> <li>• Sensor-Surface: 4mm (Mechanical Surface Detection)</li> <li>• Electronics: DAE4 Sn720; Calibrated: 2016/10/31</li> <li>• Phantom: 1659; Type: QD 000 P40 CD; Serial: xxxx</li> <li>• Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373)</li> </ul> <p><b>Flat-Section MSL 1900 TG/1900EGPRS TG M 10mm 2/Area Scan (9x13x1):</b></p>	


Measurement grid: dx=15mm, dy=15mm  
 Maximum value of SAR (measured) = 0.436 W/kg  
**Flat-Section MSL 1900 TG/1900EGPRS TG M 10mm 2/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm  
 Reference Value = 5.546 V/m; Power Drift = 0.09 dB  
 Peak SAR (extrapolated) = 0.977 W/kg  
**SAR(1 g) = 0.539 W/kg; SAR(10 g) = 0.280 W/kg**  
 Maximum value of SAR (measured) = 0.594 W/kg



0 dB = 0.594 W/kg = -2.26 dBW/kg

FLAT	EDGE2
Communication System: UID 10021 - DAB, GSM-FDD (TDMA, GMSK); Frequency: 1880 MHz; Duty Cycle: 1:8.6896 Medium parameters used: f = 1880 MHz; $\sigma = 1.57$ S/m; $\epsilon_r = 51.14$ ; $\rho = 1000$ kg/m <sup>3</sup> Phantom section: Flat Section	
DASY5 Configuration:	
<ul style="list-style-type: none"> <li>• Probe: EX3DV4 - SN3708; ConvF(7.79, 7.79, 7.79); Calibrated: 2016/11/10;</li> <li>• Sensor-Surface: 4mm (Mechanical Surface Detection)</li> <li>• Electronics: DAE4 Sn720; Calibrated: 2016/10/31</li> <li>• Phantom: 1659; Type: QD 000 P40 CD; Serial: xxxx</li> <li>• Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373)</li> </ul> <b>Flat-Section MSL 1900 HOTSPOT/1900GPRS TP H edge 2/Area Scan (6x15x1):</b> Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (measured) = 0.494 W/kg <b>Flat-Section MSL 1900 HOTSPOT/1900GPRS TP H edge 2/Zoom Scan (7x7x7)/Cube 0:</b> Measurement grid: dx=5mm, dy=5mm, dz=5mm	

Reference Value = 16.42 V/m; Power Drift = 0.03 dB  
Peak SAR (extrapolated) = 0.736 W/kg  
**SAR(1 g) = 0.439 W/kg; SAR(10 g) = 0.244 W/kg**  
Maximum value of SAR (measured) = 0.500 W/kg



0 dB = 0.500 W/kg = -3.01 dBW/kg


FLAT	EDGE3
<p>Communication System: UID 10021 - DAB, GSM-FDD (TDMA, GMSK); Frequency: 1880 MHz; Duty Cycle: 1:8.6896            Medium parameters used: <math>f = 1880</math> MHz; <math>\sigma = 1.57</math> S/m; <math>\epsilon_r = 51.14</math>; <math>\rho = 1000</math> kg/m<sup>3</sup>            Phantom section: Flat Section</p> <p>DASY5 Configuration:</p> <ul style="list-style-type: none"> <li>Probe: EX3DV4 - SN3708; ConvF(7.79, 7.79, 7.79); Calibrated: 2016/11/10;</li> <li>Sensor-Surface: 4mm (Mechanical Surface Detection)</li> <li>Electronics: DAE4 Sn720; Calibrated: 2016/10/31</li> <li>Phantom: 1659; Type: QD 000 P40 CD; Serial: xxxx</li> <li>Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373)</li> </ul> <p><b>Flat-Section MSL 1900 HOTSPOT/1900GPRS TP H edge 3/Area Scan (6x15x1):</b>            Measurement grid: dx=15mm, dy=15mm            Maximum value of SAR (measured) = 0.0405 W/kg</p> <p><b>Flat-Section MSL 1900 HOTSPOT/1900GPRS TP H edge 3/Zoom Scan (7x7x7)/Cube 0:</b> Measurement grid: dx=5mm, dy=5mm, dz=5mm            Reference Value = 2.531 V/m; Power Drift = 0.12 dB            Peak SAR (extrapolated) = 0.0740 W/kg  <b>SAR(1 g) = 0.043 W/kg; SAR(10 g) = 0.026 W/kg</b>            Maximum value of SAR (measured) = 0.0480 W/kg</p> <div style="display: flex; align-items: center;"> <div style="margin-right: 10px;"> <p>dB</p> <p>0 -3.53 -7.07 -10.60 -14.14 -17.67</p> </div> <div> </div> </div> <p style="text-align: center;">0 dB = 0.0480 W/kg = -13.19 dBW/kg</p>	




FLAT	EDGE4
<p>Communication System: UID 10021 - DAB, GSM-FDD (TDMA, GMSK); Frequency: 1880 MHz; Duty Cycle: 1:8.6896            Medium parameters used: <math>f = 1880</math> MHz; <math>\sigma = 1.57</math> S/m; <math>\epsilon_r = 51.14</math>; <math>\rho = 1000</math> kg/m<sup>3</sup>            Phantom section: Flat Section</p> <p>DASY5 Configuration:</p> <ul style="list-style-type: none"> <li>Probe: EX3DV4 - SN3708; ConvF(7.79, 7.79, 7.79); Calibrated: 2016/11/10;</li> <li>Sensor-Surface: 4mm (Mechanical Surface Detection)</li> <li>Electronics: DAE4 Sn720; Calibrated: 2016/10/31</li> <li>Phantom: 1659; Type: QD 000 P40 CD; Serial: xxxx</li> <li>Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373)</li> </ul> <p><b>Flat-Section MSL 1900 HOTSPOT/1900GPRS TP H edge 4/Area Scan (6x15x1):</b>            Measurement grid: dx=15mm, dy=15mm            Maximum value of SAR (measured) = 0.0927 W/kg</p> <p><b>Flat-Section MSL 1900 HOTSPOT/1900GPRS TP H edge 4/Zoom Scan (7x7x7)/Cube 0:</b> Measurement grid: dx=5mm, dy=5mm, dz=5mm            Reference Value = 3.431 V/m; Power Drift = -0.03 dB            Peak SAR (extrapolated) = 0.152 W/kg  <b>SAR(1 g) = 0.090 W/kg; SAR(10 g) = 0.055 W/kg</b>            Maximum value of SAR (measured) = 0.0981 W/kg</p> <div style="display: flex; align-items: center;"> <div style="margin-right: 10px;"> <p>dB</p> <p>0 -2.99 -5.97 -8.96 -11.94 -14.93</p> </div> <div> </div> </div> <p style="text-align: center;">0 dB = 0.0981 W/kg = -10.08 dBW/kg</p>	



## WCDMA Band 2

Left Side	Cheek
<p>Communication System: UID 10011 - CAB, UMTS-FDD (WCDMA); Frequency: 1880 MHz; Duty Cycle: 1:1.95434            Medium parameters used: <math>f = 1880</math> MHz; <math>\sigma = 1.45</math> S/m; <math>\epsilon_r = 39.74</math>; <math>\rho = 1000</math> kg/m<sup>3</sup>            Phantom section: Left Section</p>	
<p>DASY5 Configuration:</p> <ul style="list-style-type: none"> <li>Probe: EX3DV4 - SN3708; ConvF(7.84, 7.84, 7.84); Calibrated: 2016/11/10;</li> <li>Sensor-Surface: 4mm (Mechanical Surface Detection)</li> <li>Electronics: DAE4 Sn720; Calibrated: 2016/10/31</li> <li>Phantom: 1660; Type: QD 000 P40 CD; Serial: xxxx</li> <li>Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373)</li> </ul> <p><b>Head-Section HSL wcdma band2 Left/wcdma band2 HSL touch M/Area Scan (8x13x1):</b> Measurement grid: dx=15mm, dy=15mm            Maximum value of SAR (measured) = 0.152 W/kg</p> <p><b>Head-Section HSL wcdma band2 Left/wcdma band2 HSL touch M/Zoom Scan (7x7x7)/Cube 0:</b> Measurement grid: dx=5mm, dy=5mm, dz=5mm            Reference Value = 4.902 V/m; Power Drift = 0.15 dB            Peak SAR (extrapolated) = 0.254 W/kg  <b>SAR(1 g) = 0.164 W/kg; SAR(10 g) = 0.103 W/kg</b>            Maximum value of SAR (measured) = 0.178 W/kg</p>	
	
<p>0 dB = 0.178 W/kg = -7.50 dBW/kg</p>	


Left Side	Tilt
<p>Communication System: UID 10011 - CAB, UMTS-FDD (WCDMA); Frequency: 1880 MHz; Duty Cycle: 1:1.95434            Medium parameters used: <math>f = 1880</math> MHz; <math>\sigma = 1.45</math> S/m; <math>\epsilon_r = 39.74</math>; <math>\rho = 1000</math> kg/m<sup>3</sup>            Phantom section: Left Section</p>	
<p>DASY5 Configuration:</p> <ul style="list-style-type: none"> <li>Probe: EX3DV4 - SN3708; ConvF(7.84, 7.84, 7.84); Calibrated: 2016/11/10;</li> <li>Sensor-Surface: 4mm (Mechanical Surface Detection)</li> <li>Electronics: DAE4 Sn720; Calibrated: 2016/10/31</li> <li>Phantom: 1660; Type: QD 000 P40 CD; Serial: xxxx</li> <li>Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373)</li> </ul> <p><b>Head-Section HSL wcdma band2 Left/wcdma band2 HSL tilt M/Area Scan (8x13x1):</b> Measurement grid: dx=15mm, dy=15mm            Maximum value of SAR (measured) = 0.0725 W/kg</p> <p><b>Head-Section HSL wcdma band2 Left/wcdma band2 HSL tilt M/Zoom Scan (7x7x7)/Cube 0:</b> Measurement grid: dx=5mm, dy=5mm, dz=5mm            Reference Value = 7.902 V/m; Power Drift = 0.08 dB            Peak SAR (extrapolated) = 0.126 W/kg  <b>SAR(1 g) = 0.076 W/kg; SAR(10 g) = 0.043 W/kg</b>            Maximum value of SAR (measured) = 0.0844 W/kg</p>	
	
<p>0 dB = 0.0844 W/kg = -10.74 dBW/kg</p>	

Right Side	Cheek
------------	-------


Communication System: UID 10011 - CAB, UMTS-FDD (WCDMA); Frequency: 1880 MHz; Duty Cycle: 1:1.95434  
 Medium parameters used:  $f = 1880$  MHz;  $\sigma = 1.45$  S/m;  $\epsilon_r = 39.74$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
 Phantom section: Right Section


**DASY5 Configuration:**


- Probe: EX3DV4 - SN3708; ConvF(7.84, 7.84, 7.84); Calibrated: 2016/11/10;
  - Sensor-Surface: 4mm (Mechanical Surface Detection)
  - Electronics: DAE4 Sn720; Calibrated: 2016/10/31
  - Phantom: 1660; Type: QD 000 P40 CD; Serial: xxxx
  - Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373)
- Head-Section HSL wcdma band2 Right/wcdma band2 HSL touch M/Area Scan (8x13x1):** Measurement grid: dx=15mm, dy=15mm  
 Maximum value of SAR (measured) = 0.264 W/kg
- Head-Section HSL wcdma band2 Right/wcdma band2 HSL touch M/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm  
 Reference Value = 5.547 V/m; Power Drift = -0.10 dB  
 Peak SAR (extrapolated) = 0.389 W/kg  
**SAR(1 g) = 0.245 W/kg; SAR(10 g) = 0.147 W/kg**  
 Maximum value of SAR (measured) = 0.263 W/kg




0 dB = 0.263 W/kg = -5.80 dBW/kg


Right Side	Tilt
Communication System: UID 10011 - CAB, UMTS-FDD (WCDMA); Frequency: 1880 MHz; Duty Cycle: 1:1.95434 Medium parameters used: $f = 1880$ MHz; $\sigma = 1.45$ S/m; $\epsilon_r = 39.74$ ; $\rho = 1000$ kg/m <sup>3</sup> Phantom section: Right Section  DASY5 Configuration: <ul style="list-style-type: none"> <li>• Probe: EX3DV4 - SN3708; ConvF(7.84, 7.84, 7.84); Calibrated: 2016/11/10;</li> <li>• Sensor-Surface: 4mm (Mechanical Surface Detection)</li> <li>• Electronics: DAE4 Sn720; Calibrated: 2016/10/31</li> <li>• Phantom: 1660; Type: QD 000 P40 CD; Serial: xxxx</li> <li>• Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373)</li> </ul> <p><b>Head-Section HSL wcdma band2 Right/wcdma band2 HSL tilt/Area Scan (8x13x1):</b> Measurement grid: dx=15mm, dy=15mm                      Maximum value of SAR (measured) = 0.0809 W/kg</p> <p><b>Head-Section HSL wcdma band2 Right/wcdma band2 HSL tilt/Zoom Scan (7x7x7)/Cube 0:</b> Measurement grid: dx=5mm, dy=5mm, dz=5mm                      Reference Value = 7.992 V/m; Power Drift = 0.09 dB                      Peak SAR (extrapolated) = 0.128 W/kg  <b>SAR(1 g) = 0.080 W/kg; SAR(10 g) = 0.046 W/kg</b>                      Maximum value of SAR (measured) = 0.0889 W/kg</p>	
	
<p>0 dB = 0.0889 W/kg = -10.51 dBW/kg</p>	

FLAT(VIOCE)	Towards phantom
Communication System: UID 10011 - CAB, UMTS-FDD (WCDMA); Frequency: 1880 MHz; Duty Cycle: 1:1.95434 Medium parameters used: $f = 1880$ MHz; $\sigma = 1.57$ S/m; $\epsilon_r = 51.14$ ; $\rho = 1000$ kg/m <sup>3</sup> Phantom section: Flat Section	
DASY5 Configuration:	
<ul style="list-style-type: none"> <li>Probe: EX3DV4 - SN3708; ConvF(7.79, 7.79, 7.79); Calibrated: 2016/11/10;</li> <li>Sensor-Surface: 4mm (Mechanical Surface Detection)</li> <li>Electronics: DAE4 Sn720; Calibrated: 2016/10/31</li> <li>Phantom: 1659; Type: QD 000 P40 CD; Serial: xxxx</li> <li>Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373)</li> </ul> <p><b>Flat-Section MSL wcdma band2 TG&amp;TP/wcdma band2 TP voice M 10mm/Area Scan (9x13x1):</b> Measurement grid: dx=15mm, dy=15mm            Maximum value of SAR (measured) = 0.357 W/kg</p> <p><b>Flat-Section MSL wcdma band2 TG&amp;TP/wcdma band2 TP voice M 10mm/Zoom Scan (7x7x7)/Cube 0:</b> Measurement grid: dx=5mm, dy=5mm, dz=5mm            Reference Value = 6.596 V/m; Power Drift = -0.08 dB            Peak SAR (extrapolated) = 0.611 W/kg  <b>SAR(1 g) = 0.378 W/kg; SAR(10 g) = 0.218 W/kg</b>            Maximum value of SAR (measured) = 0.412 W/kg</p>	
 <p>0 dB = 0.412 W/kg = -3.85 dBW/kg</p>	


FLAT(VIOCE)	Towards ground
Communication System: UID 10011 - CAB, UMTS-FDD (WCDMA); Frequency: 1852.4 MHz; Duty Cycle: 1:1.95434 Medium parameters used (interpolated): $f = 1852.4$ MHz; $\sigma = 1.533$ S/m; $\epsilon_r = 51.233$ ; $\rho = 1000$ kg/m <sup>3</sup> Phantom section: Flat Section	
DASY5 Configuration: <ul style="list-style-type: none"> <li>• Probe: EX3DV4 - SN3708; ConvF(7.79, 7.79, 7.79); Calibrated: 2016/11/10;</li> <li>• Sensor-Surface: 4mm (Mechanical Surface Detection)</li> <li>• Electronics: DAE4 Sn720; Calibrated: 2016/10/31</li> <li>• Phantom: 1659; Type: QD 000 P40 CD; Serial: xxxx</li> <li>• Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373)</li> </ul> <b>Flat-Section MSL wcdma band2 TG&amp;TP/wcdma band2 TG voice L 10mm/Area Scan (9x13x1):</b> Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (measured) = 0.729 W/kg <b>Flat-Section MSL wcdma band2 TG&amp;TP/wcdma band2 TG voice L 10mm/Zoom Scan (7x7x7)/Cube 0:</b> Measurement grid: dx=5mm, dy=5mm, dz=5mm Reference Value = 7.753 V/m; Power Drift = -0.02 dB Peak SAR (extrapolated) = 1.45 W/kg <b>SAR(1 g) = 0.827 W/kg; SAR(10 g) = 0.444 W/kg</b> Maximum value of SAR (measured) = 0.918 W/kg	
 <p style="text-align: center;">0 dB = 0.918 W/kg = -0.37 dBW/kg</p>	


FLAT(VIOCE)	Towards ground
Communication System: UID 10011 - CAB, UMTS-FDD (WCDMA); Frequency: 1852.4 MHz; Duty Cycle: 1:1.95434 Medium parameters used (interpolated): $f = 1852.4$ MHz; $\sigma = 1.533$ S/m; $\epsilon_r = 51.233$ ; $\rho = 1000$ kg/m <sup>3</sup> Phantom section: Flat Section	
DASY5 Configuration: <ul style="list-style-type: none"> <li>• Probe: EX3DV4 - SN3708; ConvF(7.79, 7.79, 7.79); Calibrated: 2016/11/10;</li> <li>• Sensor-Surface: 4mm (Mechanical Surface Detection)</li> <li>• Electronics: DAE4 Sn720; Calibrated: 2016/10/31</li> <li>• Phantom: 1659; Type: QD 000 P40 CD; Serial: xxxx</li> <li>• Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373)</li> </ul> <b>Flat-Section MSL wcdma band2 TG&amp;TP/wcdma band2 TG voice L 10mm/Area Scan (9x13x1):</b> Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (measured) = 0.698 W/kg <b>Flat-Section MSL wcdma band2 TG&amp;TP/wcdma band2 TG voice L 10mm/Zoom Scan (7x7x7)/Cube 0:</b> Measurement grid: dx=5mm, dy=5mm, dz=5mm Reference Value = 7.633 V/m; Power Drift = -0.01 dB Peak SAR (extrapolated) = 1.35 W/kg <b>SAR(1 g) = 0.810 W/kg; SAR(10 g) = 0.434 W/kg</b> Maximum value of SAR (measured) = 0.908 W/kg	
 <p style="text-align: center;">0 dB = 0.908 W/kg = -0.36 dBW/kg</p>	





FLAT(VIOCE)	Towards ground
<p>Communication System: UID 10011 - CAB, UMTS-FDD (WCDMA); Frequency: 1880 MHz; Duty Cycle: 1:1.95434            Medium parameters used: <math>f = 1880</math> MHz; <math>\sigma = 1.57</math> S/m; <math>\epsilon_r = 51.14</math>; <math>\rho = 1000</math> kg/m<sup>3</sup>            Phantom section: Flat Section</p>	
<p>DASY5 Configuration:</p> <ul style="list-style-type: none"> <li>Probe: EX3DV4 - SN3708; ConvF(7.79, 7.79, 7.79); Calibrated: 2016/11/10;</li> <li>Sensor-Surface: 4mm (Mechanical Surface Detection)</li> <li>Electronics: DAE4 Sn720; Calibrated: 2016/10/31</li> <li>Phantom: 1659; Type: QD 000 P40 CD; Serial: xxxx</li> <li>Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373)</li> </ul> <p><b>Flat-Section MSL wcdma band2 TG&amp;TP/wcdma band2 TG voice M 10mm/Area Scan (9x13x1):</b> Measurement grid: dx=15mm, dy=15mm            Maximum value of SAR (measured) = 1.06 W/kg</p> <p><b>Flat-Section MSL wcdma band2 TG&amp;TP/wcdma band2 TG voice M 10mm/Zoom Scan (7x7x7)/Cube 0:</b> Measurement grid: dx=5mm, dy=5mm, dz=5mm            Reference Value = 6.406 V/m; Power Drift = -0.15 dB            Peak SAR (extrapolated) = 1.84 W/kg  <b>SAR(1 g) = 1.05 W/kg; SAR(10 g) = 0.552 W/kg</b>            Maximum value of SAR (measured) = 1.18 W/kg</p>	
 <p>0 dB = 1.18 W/kg = 0.72 dBW/kg</p>	





FLAT(VIOCE)	Towards ground
Communication System: UID 10011 - CAB, UMTS-FDD (WCDMA); Frequency: 1880 MHz; Duty Cycle: 1:1.95434 Medium parameters used: $f = 1880$ MHz; $\sigma = 1.57$ S/m; $\epsilon_r = 51.14$ ; $\rho = 1000$ kg/m <sup>3</sup> Phantom section: Flat Section	
DASY5 Configuration: <ul style="list-style-type: none"> <li>• Probe: EX3DV4 - SN3708; ConvF(7.79, 7.79, 7.79); Calibrated: 2016/11/10;</li> <li>• Sensor-Surface: 4mm (Mechanical Surface Detection)</li> <li>• Electronics: DAE4 Sn720; Calibrated: 2016/10/31</li> <li>• Phantom: 1659; Type: QD 000 P40 CD; Serial: xxxx</li> <li>• Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373)</li> </ul> <p><b>Flat-Section MSL wcdma band2 TG&amp;TP/wcdma band2 TG voice M 10mm 2/Area Scan (9x13x1):</b> Measurement grid: dx=15mm, dy=15mm                      Maximum value of SAR (measured) = 1.04 W/kg</p> <p><b>Flat-Section MSL wcdma band2 TG&amp;TP/wcdma band2 TG voice M 10mm 2/Zoom Scan (7x7x7)/Cube 0:</b> Measurement grid: dx=5mm, dy=5mm, dz=5mm                      Reference Value = 6.293 V/m; Power Drift = -0.05 dB                      Peak SAR (extrapolated) = 1.78 W/kg  <b>SAR(1 g) = 1.02 W/kg; SAR(10 g) = 0.542 W/kg</b>                      Maximum value of SAR (measured) = 1.15 W/kg</p>	
 <p>0 dB = 1.15 W/kg = 0.61 dBW/kg</p>	


FLAT(VIOCE)	Towards ground
<p>Communication System: UID 10011 - CAB, UMTS-FDD (WCDMA); Frequency: 1907.6 MHz; Duty Cycle: 1:1.95434            Medium parameters used (interpolated): <math>f = 1907.6</math> MHz; <math>\sigma = 1.593</math> S/m; <math>\epsilon_r = 51.042</math>; <math>\rho = 1000</math> kg/m<sup>3</sup>            Phantom section: Flat Section</p>	
<p>DASY5 Configuration:</p> <ul style="list-style-type: none"> <li>Probe: EX3DV4 - SN3708; ConvF(7.79, 7.79, 7.79); Calibrated: 2016/11/10;</li> <li>Sensor-Surface: 4mm (Mechanical Surface Detection)</li> <li>Electronics: DAE4 Sn720; Calibrated: 2016/10/31</li> <li>Phantom: 1659; Type: QD 000 P40 CD; Serial: xxxx</li> <li>Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373)</li> </ul> <p><b>Flat-Section MSL wcdma band2 TG&amp;TP/wcdma band2 TG voice H 10mm/Area Scan (9x13x1):</b> Measurement grid: dx=15mm, dy=15mm            Maximum value of SAR (measured) = 1.03 W/kg</p> <p><b>Flat-Section MSL wcdma band2 TG&amp;TP/wcdma band2 TG voice H 10mm/Zoom Scan (7x7x7)/Cube 0:</b> Measurement grid: dx=5mm, dy=5mm, dz=5mm            Reference Value = 7.897 V/m; Power Drift = -0.08 dB            Peak SAR (extrapolated) = 2.09 W/kg  <b>SAR(1 g) = 1.17 W/kg; SAR(10 g) = 0.611 W/kg</b>            Maximum value of SAR (measured) = 1.28 W/kg</p>	
 <p>0 dB = 1.28 W/kg = 1.07 dBW/kg</p>	

FLAT(VIOCE)	Towards ground
Communication System: UID 10011 - CAB, UMTS-FDD (WCDMA); Frequency: 1907.6 MHz; Duty Cycle: 1:1.95434 Medium parameters used (interpolated): $f = 1907.6$ MHz; $\sigma = 1.593$ S/m; $\epsilon_r = 51.042$ ; $\rho = 1000$ kg/m <sup>3</sup> Phantom section: Flat Section	
DASY5 Configuration: <ul style="list-style-type: none"> <li>• Probe: EX3DV4 - SN3708; ConvF(7.79, 7.79, 7.79); Calibrated: 2016/11/10;</li> <li>• Sensor-Surface: 4mm (Mechanical Surface Detection)</li> <li>• Electronics: DAE4 Sn720; Calibrated: 2016/10/31</li> <li>• Phantom: 1659; Type: QD 000 P40 CD; Serial: xxxx</li> <li>• Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373)</li> </ul> <b>Flat-Section MSL wcdma band2 TG&amp;TP/wcdma band2 TG voice H 10mm 2/Area Scan (9x13x1):</b> Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (measured) = 1.05 W/kg <b>Flat-Section MSL wcdma band2 TG&amp;TP/wcdma band2 TG voice H 10mm 2/Zoom Scan (7x7x7)/Cube 0:</b> Measurement grid: dx=5mm, dy=5mm, dz=5mm Reference Value = 7.888 V/m; Power Drift = 0.09 dB Peak SAR (extrapolated) = 2.09 W/kg <b>SAR(1 g) = 1.16 W/kg; SAR(10 g) = 0.610 W/kg</b> Maximum value of SAR (measured) = 1.27 W/kg	
 <p style="text-align: center;">0 dB = 1.27 W/kg = 1.04 dBW/kg</p>	


FLAT(DATA)	Towards phantom
Communication System: UID 10011 - CAB, UMTS-FDD (WCDMA); Frequency: 1880 MHz; Duty Cycle: 1:1.95434 Medium parameters used: $f = 1880$ MHz; $\sigma = 1.57$ S/m; $\epsilon_r = 51.14$ ; $\rho = 1000$ kg/m <sup>3</sup> Phantom section: Flat Section	
DASY5 Configuration:	
<ul style="list-style-type: none"> <li>Probe: EX3DV4 - SN3708; ConvF(7.79, 7.79, 7.79); Calibrated: 2016/11/10;</li> <li>Sensor-Surface: 4mm (Mechanical Surface Detection)</li> <li>Electronics: DAE4 Sn720; Calibrated: 2016/10/31</li> <li>Phantom: 1659; Type: QD 000 P40 CD; Serial: xxxx</li> <li>Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373)</li> </ul> <p><b>Flat-Section MSL wcdma band2 TG&amp;TP/wcdma band2 TP DATA M 10mm/Area Scan (9x13x1):</b> Measurement grid: dx=15mm, dy=15mm            Maximum value of SAR (measured) = 0.385 W/kg</p> <p><b>Flat-Section MSL wcdma band2 TG&amp;TP/wcdma band2 TP DATA M 10mm/Zoom Scan (7x7x7)/Cube 0:</b> Measurement grid: dx=5mm, dy=5mm, dz=5mm            Reference Value = 6.056 V/m; Power Drift = 0.00 dB            Peak SAR (extrapolated) = 0.570 W/kg  <b>SAR(1 g) = 0.351 W/kg; SAR(10 g) = 0.209 W/kg</b>            Maximum value of SAR (measured) = 0.379 W/kg</p>	
 <p>0 dB = 0.379 W/kg = -4.21 dBW/kg</p>	

FLAT(DATA)	Towards ground
<p>Communication System: UID 0, WCDMA BAND2 (0); Frequency: 1852.4 MHz;Duty Cycle: 1:1            Medium parameters used (interpolated): f = 1852.4 MHz; <math>\sigma = 1.533</math> S/m; <math>\epsilon_r = 51.233</math>; <math>\rho = 1000</math> kg/m<sup>3</sup>            Phantom section: Flat Section</p>	
<p>DASY5 Configuration:</p> <ul style="list-style-type: none"> <li>Probe: ES3DV3 - SN3127; ConvF(4.9, 4.9, 4.9); Calibrated: 2016/8/29;</li> <li>Sensor-Surface: 4mm (Mechanical Surface Detection)</li> <li>Electronics: DAE4 Sn720; Calibrated: 2016/10/31</li> <li>Phantom: 1659; Type: QD 000 P40 CD; Serial: xxxx</li> <li>Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373)</li> </ul> <p><b>Flat-Section MSL wcdma band2 TG&amp;TP/wcdma band2 TG DATA L 10mm 2/Area Scan (9x13x1):</b> Measurement grid: dx=15mm, dy=15mm            Maximum value of SAR (measured) = 0.729 W/kg  <b>Flat-Section MSL wcdma band2 TG&amp;TP/wcdma band2 TG DATA L 10mm 2/Zoom Scan (7x7x7)/Cube 0:</b> Measurement grid: dx=5mm, dy=5mm, dz=5mm            Reference Value = 7.799 V/m; Power Drift = -0.01 dB            Peak SAR (extrapolated) = 1.38 W/kg  <b>SAR(1 g) = 0.785 W/kg; SAR(10 g) = 0.416 W/kg</b>            Maximum value of SAR (measured) = 0.855 W/kg</p>	
 <p>0 dB = 0.855 W/kg = -0.68 dBW/kg</p>	


FLAT(DATA)	Towards ground
Communication System: UID 0, WCDMA BAND2 (0); Frequency: 1880 MHz;Duty Cycle: 1:1 Medium parameters used: $f = 1880 \text{ MHz}$ ; $\sigma = 1.57 \text{ S/m}$ ; $\epsilon_r = 51.14$ ; $\rho = 1000 \text{ kg/m}^3$ Phantom section: Flat Section	
DASY5 Configuration:	
<ul style="list-style-type: none"> <li>• Probe: ES3DV3 - SN3127; ConvF(4.9, 4.9, 4.9); Calibrated: 2016/8/29;</li> <li>• Sensor-Surface: 4mm (Mechanical Surface Detection)</li> <li>• Electronics: DAE4 Sn720; Calibrated: 2016/10/31</li> <li>• Phantom: 1659; Type: QD 000 P40 CD; Serial: xxxx</li> <li>• Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373)</li> </ul> <p><b>Flat-Section MSL wcdma band2 TG&amp;TP/wcdma band2 TG DATA M 10mm 2/Area Scan (9x13x1):</b> Measurement grid: <math>dx=15\text{mm}</math>, <math>dy=15\text{mm}</math>            Maximum value of SAR (measured) = 0.660 W/kg</p> <p><b>Flat-Section MSL wcdma band2 TG&amp;TP/wcdma band2 TG DATA M 10mm 2/Zoom Scan (7x7x7)/Cube 0:</b> Measurement grid: <math>dx=5\text{mm}</math>, <math>dy=5\text{mm}</math>, <math>dz=5\text{mm}</math>            Reference Value = 8.473 V/m; Power Drift = 0.05 dB            Peak SAR (extrapolated) = 1.48 W/kg  <b>SAR(1 g) = 0.853 W/kg; SAR(10 g) = 0.450 W/kg</b>            Maximum value of SAR (measured) = 0.966 W/kg</p>	
 <p style="text-align: center;">0 dB = 0.966 W/kg = -0.15 dBW/kg</p>	

FLAT(DATA)	Towards ground
Communication System: UID 10011 - CAB, UMTS-FDD (WCDMA); Frequency: 1880 MHz; Duty Cycle: 1:1.95434 Medium parameters used: $f = 1880$ MHz; $\sigma = 1.57$ S/m; $\epsilon_r = 51.14$ ; $\rho = 1000$ kg/m <sup>3</sup> Phantom section: Flat Section	
DASY5 Configuration:	
<ul style="list-style-type: none"> <li>• Probe: EX3DV4 - SN3708; ConvF(7.79, 7.79, 7.79); Calibrated: 2016/11/10;</li> <li>• Sensor-Surface: 4mm (Mechanical Surface Detection)</li> <li>• Electronics: DAE4 Sn720; Calibrated: 2016/10/31</li> <li>• Phantom: 1659; Type: QD 000 P40 CD; Serial: xxxx</li> <li>• Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373)</li> </ul> <p><b>Flat-Section MSL wcdma band2 TG&amp;TP/wcdma band2 TG DATA M 10mm/Area Scan (9x13x1):</b> Measurement grid: dx=15mm, dy=15mm                      Maximum value of SAR (measured) = 0.89 W/kg</p> <p><b>Flat-Section MSL wcdma band2 TG&amp;TP/wcdma band2 TG DATA M 10mm/Zoom Scan (7x7x7)/Cube 0:</b> Measurement grid: dx=5mm, dy=5mm, dz=5mm                      Reference Value = 8.241 V/m; Power Drift = -0.01 dB                      Peak SAR (extrapolated) = 2.04 W/kg  <b>SAR(1 g) = 0.844 W/kg; SAR(10 g) = 0.465 W/kg</b>                      Maximum value of SAR (measured) = 1.01 W/kg</p>	
 <p style="text-align: center;">0 dB = 1.08 W/kg = 0.97 dBW/kg</p>	





FLAT(DATA)	Towards ground
<p>Communication System: UID 0, WCDMA BAND2 (0); Frequency: 1907.6 MHz;Duty Cycle: 1:1            Medium parameters used (interpolated): <math>f = 1907.6</math> MHz; <math>\sigma = 1.593</math> S/m; <math>\epsilon_r = 51.042</math>; <math>\rho = 1000</math> kg/m<sup>3</sup>            Phantom section: Flat Section</p>	
<p>DASY5 Configuration:</p> <ul style="list-style-type: none"> <li>Probe: ES3DV3 - SN3127; ConvF(4.9, 4.9, 4.9); Calibrated: 2016/8/29;</li> <li>Sensor-Surface: 4mm (Mechanical Surface Detection)</li> <li>Electronics: DAE4 Sn720; Calibrated: 2016/10/31</li> <li>Phantom: 1659; Type: QD 000 P40 CD; Serial: xxxx</li> <li>Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373)</li> </ul> <p><b>Flat-Section MSL wcdma band2 TG&amp;TP/wcdma band2 TG DATA H 10mm 2/Area Scan (9x13x1):</b> Measurement grid: dx=15mm, dy=15mm            Maximum value of SAR (measured) = 1.02 W/kg</p> <p><b>Flat-Section MSL wcdma band2 TG&amp;TP/wcdma band2 TG DATA H 10mm 2/Zoom Scan (7x7x7)/Cube 0:</b> Measurement grid: dx=5mm, dy=5mm, dz=5mm            Reference Value = 8.938 V/m; Power Drift = -0.03 dB            Peak SAR (extrapolated) = 1.97 W/kg  <b>SAR(1 g) = 1.09 W/kg; SAR(10 g) = 0.569 W/kg</b>            Maximum value of SAR (measured) = 1.20 W/kg</p>	
 <p>0 dB = 1.20 W/kg = 0.79 dBW/kg</p>	





FLAT(DATA)	Towards ground
<p>Communication System: UID 0, WCDMA BAND2 (0); Frequency: 1907.6 MHz;Duty Cycle: 1:1            Medium parameters used (interpolated): <math>f = 1907.6</math> MHz; <math>\sigma = 1.593</math> S/m; <math>\epsilon_r = 51.042</math>; <math>\rho = 1000</math> kg/m<sup>3</sup>            Phantom section: Flat Section</p> <p>DASY5 Configuration:</p> <ul style="list-style-type: none"> <li>Probe: ES3DV3 - SN3127; ConvF(4.9, 4.9, 4.9); Calibrated: 2016/8/29;</li> <li>Sensor-Surface: 4mm (Mechanical Surface Detection)</li> <li>Electronics: DAE4 Sn720; Calibrated: 2016/10/31</li> <li>Phantom: 1659; Type: QD 000 P40 CD; Serial: xxxx</li> <li>Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373)</li> </ul> <p><b>Flat-Section MSL wcdma band2 TG&amp;TP/wcdma band2 TG DATA H 10mm 2/Area Scan (9x13x1):</b> Measurement grid: dx=15mm, dy=15mm            Maximum value of SAR (measured) = 1.00 W/kg</p> <p><b>Flat-Section MSL wcdma band2 TG&amp;TP/wcdma band2 TG DATA H 10mm 2/Zoom Scan (7x7x7)/Cube 0:</b> Measurement grid: dx=5mm, dy=5mm, dz=5mm            Reference Value = 8.944 V/m; Power Drift = -0.03 dB            Peak SAR (extrapolated) = 1.97 W/kg  <b>SAR(1 g) = 1.08 W/kg; SAR(10 g) = 0.558 W/kg</b>            Maximum value of SAR (measured) = 1.08 W/kg</p>	
 <p>0 dB = 1.19 W/kg = 0.77 dBW/kg</p>	

FLAT	EDGE2
Communication System: UID 10011 - CAB, UMTS-FDD (WCDMA); Frequency: 1880 MHz; Duty Cycle: 1:1.95434 Medium parameters used: $f = 1880$ MHz; $\sigma = 1.57$ S/m; $\epsilon_r = 51.14$ ; $\rho = 1000$ kg/m <sup>3</sup> Phantom section: Flat Section	
DASY5 Configuration:	
<ul style="list-style-type: none"> <li>• Probe: EX3DV4 - SN3708; ConvF(7.79, 7.79, 7.79); Calibrated: 2016/11/10;</li> <li>• Sensor-Surface: 4mm (Mechanical Surface Detection)</li> <li>• Electronics: DAE4 Sn720; Calibrated: 2016/10/31</li> <li>• Phantom: 1659; Type: QD 000 P40 CD; Serial: xxxx</li> <li>• Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373)</li> </ul> <p><b>Flat-Section MSL wcdma band2 HOT/wcdma band2 10mm M edge 2/Area Scan (6x11x1):</b> Measurement grid: dx=15mm, dy=15mm            Maximum value of SAR (measured) = 0.683 W/kg</p> <p><b>Flat-Section MSL wcdma band2 HOT/wcdma band2 10mm M edge 2/Zoom Scan (7x7x7)/Cube 0:</b> Measurement grid: dx=5mm, dy=5mm, dz=5mm            Reference Value = 22.59 V/m; Power Drift = 0.09 dB            Peak SAR (extrapolated) = 1.29 W/kg  <b>SAR(1 g) = 0.776 W/kg; SAR(10 g) = 0.446 W/kg</b>            Maximum value of SAR (measured) = 0.873 W/kg</p>	
<p>0 dB = 0.873 W/kg = -0.59 dBW/kg</p>	


FLAT	EDGE3
<p>Communication System: UID 10011 - CAB, UMTS-FDD (WCDMA); Frequency: 1880 MHz; Duty Cycle: 1:1.95434 Medium parameters used: <math>f = 1880</math> MHz; <math>\sigma = 1.57</math> S/m; <math>\epsilon_r = 51.14</math>; <math>\rho = 1000</math> kg/m<sup>3</sup> Phantom section: Flat Section</p>	
<p>DASY5 Configuration:</p> <ul style="list-style-type: none"> <li>Probe: EX3DV4 - SN3708; ConvF(7.79, 7.79, 7.79); Calibrated: 2016/11/10;</li> <li>Sensor-Surface: 4mm (Mechanical Surface Detection)</li> <li>Electronics: DAE4 Sn720; Calibrated: 2016/10/31</li> <li>Phantom: 1659; Type: QD 000 P40 CD; Serial: xxxx</li> <li>Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373)</li> </ul> <p><b>Flat-Section MSL wcdma band2 HOT/wcdma band2 10mm M edge 3/Area Scan (6x15x1):</b> Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (measured) = 0.119 W/kg</p> <p><b>Flat-Section MSL wcdma band2 HOT/wcdma band2 10mm M edge 3/Zoom Scan (7x7x7)/Cube 0:</b> Measurement grid: dx=5mm, dy=5mm, dz=5mm Reference Value = 3.925 V/m; Power Drift = 0.16 dB Peak SAR (extrapolated) = 0.205 W/kg <b>SAR(1 g) = 0.122 W/kg; SAR(10 g) = 0.071 W/kg</b> Maximum value of SAR (measured) = 0.134 W/kg</p>	
 <p style="text-align: center;">0 dB = 0.134 W/kg = -8.73 dBW/kg</p>	

FLAT	EDGE4
<p>Communication System: UID 10011 - CAB, UMTS-FDD (WCDMA); Frequency: 1880 MHz; Duty Cycle: 1:1.95434            Medium parameters used: <math>f = 1880</math> MHz; <math>\sigma = 1.57</math> S/m; <math>\epsilon_r = 51.14</math>; <math>\rho = 1000</math> kg/m<sup>3</sup>            Phantom section: Flat Section</p> <p>DASY5 Configuration:</p> <ul style="list-style-type: none"> <li>Probe: EX3DV4 - SN3708; ConvF(7.79, 7.79, 7.79); Calibrated: 2016/11/10;</li> <li>Sensor-Surface: 4mm (Mechanical Surface Detection)</li> <li>Electronics: DAE4 Sn720; Calibrated: 2016/10/31</li> <li>Phantom: 1659; Type: QD 000 P40 CD; Serial: xxxx</li> <li>Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373)</li> </ul> <p><b>Flat-Section MSL wcdma band2 HOT/wcdma band2 10mm M edge 4/Area Scan (6x15x1):</b> Measurement grid: dx=15mm, dy=15mm            Maximum value of SAR (measured) = 0.178 W/kg</p> <p><b>Flat-Section MSL wcdma band2 HOT/wcdma band2 10mm M edge 4/Zoom Scan (7x7x7)/Cube 0:</b> Measurement grid: dx=5mm, dy=5mm, dz=5mm            Reference Value = 4.960 V/m; Power Drift = -0.09 dB            Peak SAR (extrapolated) = 0.281 W/kg  <b>SAR(1 g) = 0.175 W/kg; SAR(10 g) = 0.107 W/kg</b>            Maximum value of SAR (measured) = 0.190 W/kg</p>	
 <p style="text-align: center;">0 dB = 0.190 W/kg = -7.21 dBW/kg</p>	

**WCDMA Band 5**

Left Side	Cheek
<p>Communication System: UID 0, WCDMA (0); Communication System Band: BAND 5;            Frequency: 836.6 MHz; Communication System PAR: 0 dB            Medium parameters used : f = 836.6 MHz; <math>\sigma = 0.883</math> S/m; <math>\epsilon_r = 41.292</math>; <math>\rho = 1000</math> kg/m<sup>3</sup>            Phantom section: Left Section            Measurement Standard: DASY5 (IEEE1528-2013)            DASY5 Configuration:</p>	
<ul style="list-style-type: none"> <li>• Probe: ES3DV3 - SN3297; ConvF(6.18, 6.18, 6.18); Calibrated: 14/10/2016;</li> <li>• Sensor-Surface: 3mm (Mechanical Surface Detection)</li> <li>• Electronics: DAE4 Sn1226; Calibrated: 28/09/2016</li> <li>• Phantom: SAM1; Type: SAM; Serial: TP1576</li> <li>• Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)</li> <li>• <b>left/touch mid/Area Scan (91x161x1):</b> Interpolated grid: dx=1.000 mm, dy=1.000 mm              Maximum value of SAR = 0.194 W/kg  <b>left/touch mid/Zoom Scan (7x7x7)/Cube 0:</b> Measurement grid: dx=5mm, dy=5mm, dz=5mm              Reference Value = 7.997 V/m; Power Drift = 0.07 dB              Peak SAR (extrapolated) = 0.224 W/kg  <b>SAR(1 g) = 0.175 W/kg; SAR(10 g) = 0.132 W/kg</b>              Maximum value of SAR (measured) = 0.194 W/kg</li> </ul>	
<div style="display: flex; align-items: center;"> <div style="margin-right: 20px;"> <p>dB</p>  </div> <div style="flex-grow: 1;">  </div> </div> <p style="text-align: center; margin-top: 20px;">0 dB = 0.194 W/kg = -7.12 dBW/kg</p>	

Left Side	Tilt
<p>Communication System: UID 0, WCDMA (0); Communication System Band: BAND 5; Frequency: 836.6 MHz; Communication System PAR: 0 dB Medium parameters used : f = 836.6 MHz; <math>\sigma = 0.883</math> S/m; <math>\epsilon_r = 41.292</math>; <math>\rho = 1000</math> kg/m<sup>3</sup> Phantom section: Left Section Measurement Standard: DASYS (IEEE1528-2013) DASY5 Configuration:</p> <ul style="list-style-type: none"> <li>Probe: ES3DV3 - SN3297; ConvF(6.18, 6.18, 6.18); Calibrated: 14/10/2016;</li> <li>Sensor-Surface: 3mm (Mechanical Surface Detection)</li> <li>Electronics: DAE4 Sn1226; Calibrated: 28/09/2016</li> <li>Phantom: SAM1; Type: SAM; Serial: TP1576</li> <li>Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)</li> </ul> <p>• <b>left/tilt mid/Area Scan (91x161x1):</b> Interpolated grid: dx=1.000 mm, dy=1.000 mm Maximum value of SAR = 0.137 W/kg <b>left/tilt mid/ Zoom Scan (7x7x7)/Cube 0:</b> Measurement grid: dx=5mm, dy=5mm, dz=5mm Reference Value = 5.779 V/m; Power Drift = 0.07 dB Peak SAR (extrapolated) = 0.168 W/kg <b>SAR(1 g) = 0.111 W/kg; SAR(10 g) = 0.0695 W/kg</b> Maximum value of SAR (measured) = 0.132 W/kg</p> <div data-bbox="279 1294 1308 1751"> </div> <p style="text-align: center;">0 dB = 0.137 W/kg = -8.63 dBW/kg</p>	


Right Side	Cheek
<p>Communication System: UID 0, WCDMA (0); Communication System Band: BAND 5;            Frequency: 836.6 MHz; Communication System PAR: 0 dB            Medium parameters used : f = 836.6 MHz; <math>\sigma = 0.883</math> S/m; <math>\epsilon_r = 41.292</math>; <math>\rho = 1000</math> kg/m<sup>3</sup>            Phantom section: Right Section            Measurement Standard: DASYS (IEEE1528-2013)            DASYS Configuration:</p> <ul style="list-style-type: none"> <li>• Probe: ES3DV3 - SN3297; ConvF(6.18, 6.18, 6.18); Calibrated: 14/10/2016;</li> <li>• Sensor-Surface: 3mm (Mechanical Surface Detection)</li> <li>• Electronics: DAE4 Sn1226; Calibrated: 28/09/2016</li> <li>• Phantom: SAM1; Type: SAM; Serial: TP1576</li> <li>• Measurement SW: DASYS2, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)</li> </ul> <p><b>right/touch mid/Area Scan (91x161x1):</b> Interpolated grid: dx=1.000 mm, dy=1.000 mm            Maximum value of SAR = 0.205 W/kg  <b>right/touch mid/Zoom Scan (7x7x7)/Cube 0:</b> Measurement grid: dx=5mm, dy=5mm, dz=5mm            Reference Value = 7.607 V/m; Power Drift = -0.05 dB            Peak SAR (extrapolated) = 0.231 W/kg  <b>SAR(1 g) = 0.183 W/kg; SAR(10 g) = 0.139 W/kg</b>            Maximum value of SAR (measured) = 0.201 W/kg</p>	
	
<p>0 dB = 0.205 W/kg = -6.88 dBW/kg</p>	



Right Side	Tilt
<p>Communication System: UID 0, WCDMA (0); Communication System Band: BAND 5;                      Frequency: 836.6 MHz; Communication System PAR: 0 dB                      Medium parameters used : f = 836.6 MHz; <math>\sigma = 0.883</math> S/m; <math>\epsilon_r = 41.292</math>; <math>\rho = 1000</math> kg/m<sup>3</sup>                      Phantom section: Right Section                      Measurement Standard: DASYS5 (IEEE1528-2013)                      DASYS5 Configuration:</p> <ul style="list-style-type: none"> <li>Probe: ES3DV3 - SN3297; ConvF(6.18, 6.18, 6.18); Calibrated: 14/10/2016;</li> <li>Sensor-Surface: 3mm (Mechanical Surface Detection)</li> <li>Electronics: DAE4 Sn1226; Calibrated: 28/09/2016</li> <li>Phantom: SAM1; Type: SAM; Serial: TP1576</li> <li>Measurement SW: DASYS52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)</li> </ul> <p>• <b>right/tilt mid/Area Scan (91x161x1):</b> Interpolated grid: dx=1.000 mm, dy=1.000 mm                      Maximum value of SAR = 0.124 W/kg  <b>right/tilt mid/Zoom Scan (7x7x7)/Cube 0:</b> Measurement grid: dx=5mm, dy=5mm, dz=5mm                      Reference Value = 5.421 V/m; Power Drift = -0.05 dB                      Peak SAR (extrapolated) = 0.168 W/kg  <b>SAR(1 g) = 0.109 W/kg; SAR(10 g) = 0.076 W/kg</b>                      Maximum value of SAR (measured) = 0.122 W/kg</p>	
<p>0 dB = 0.124 W/kg = -9.07 dBW/kg</p>	



FLAT(VIOCE)	Towards phantom
<p>Communication System: UID 0, WCDMA (0); Communication System Band: BAND 5; Frequency: 836.6 MHz; Communication System PAR: 0 dB Medium parameters used: <math>f = 837 \text{ MHz}</math>; <math>\sigma = 0.951 \text{ S/m}</math>; <math>\epsilon_r = 54.241</math>; <math>\rho = 1000 \text{ kg/m}^3</math> Phantom section: Flat Section Measurement Standard: DASY5 (IEEE1528-2013) DASY5 Configuration:</p> <ul style="list-style-type: none"> <li>Probe: ES3DV3 - SN3297; ConvF(6.08, 6.08, 6.08); Calibrated: 14/10/2016;</li> <li>Sensor-Surface: 3mm (Mechanical Surface Detection)</li> <li>Electronics: DAE4 Sn1226; Calibrated: 28/09/2016</li> <li>Phantom: SAM1; Type: SAM; Serial: TP1576</li> <li>Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)</li> </ul> <p><b>body/towards phantom voice/Area Scan (91x161x1):</b> Interpolated grid: <math>dx=1.000 \text{ mm}</math>, <math>dy=1.000 \text{ mm}</math> Maximum value of SAR = 0.201 W/kg <b>body/towards phantom voice/ Zoom Scan (7x7x7)/Cube 0:</b> Measurement grid: <math>dx=5\text{mm}</math>, <math>dy=5\text{mm}</math>, <math>dz=5\text{mm}</math> Reference Value = 14.9 V/m; Power Drift = -0.07 dB Peak SAR (extrapolated) = 0.271 W/kg <b>SAR(1 g) = 0.178 W/kg; SAR(10 g) = 0.126 W/kg</b></p> <p>Maximum value of SAR (measured) = 0.201 W/kg</p> <div data-bbox="188 1265 1401 1720"> </div> <p>0 dB = 0.201 W/kg = -6.97 dBW/kg</p>	

FLAT(VIOCE )	Towards ground
<p>Communication System: UID 0, WCDMA (0); Communication System Band: BAND 5;                      Frequency: 836.6 MHz; Communication System PAR: 0 dB                      Medium parameters used: <math>f = 837 \text{ MHz}</math>; <math>\sigma = 0.951 \text{ S/m}</math>; <math>\epsilon_r = 54.241</math>; <math>\rho = 1000 \text{ kg/m}^3</math>                      Phantom section: Flat Section                      Measurement Standard: DASY5 (IEEE 1528-2013)                      DASY5 Configuration:</p> <ul style="list-style-type: none"> <li>Probe: ES3DV3 - SN3297; ConvF(6.08, 6.08, 6.08); Calibrated: 14/10/2016;</li> <li>Sensor-Surface: 3mm (Mechanical Surface Detection)</li> <li>Electronics: DAE4 Sn1226; Calibrated: 28/09/2016</li> <li>Phantom: SAM1; Type: SAM; Serial: TP1576</li> <li>Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)</li> </ul> <p><b>body/towards ground voice/Area Scan (91x161x1):</b> Interpolated grid: <math>dx=1.000 \text{ mm}</math>, <math>dy=1.000 \text{ mm}</math>                      Maximum value of SAR = 0.330 W/kg</p> <p><b>body/towards ground voice/Zoom Scan (7x7x7)/Cube 0:</b> Measurement grid: <math>dx=5\text{mm}</math>, <math>dy=5\text{mm}</math>, <math>dz=5\text{mm}</math>                      Reference Value = 19.00 V/m; Power Drift = 0.01 dB                      Peak SAR (extrapolated) = 0.380 W/kg  <b>SAR(1 g) = 0.302 W/kg; SAR(10 g) = 0.234 W/kg</b>                      Maximum value of SAR (measured) = 0.330 W/kg</p>	
 <p style="text-align: center;">0 dB = 0.330 W/kg = -4.81 dBW/kg</p>	

FLAT(DATA)	Towards phantom
<p>Communication System: UID 0, WCDMA (0); Communication System Band: BAND 5;                      Frequency: 836.6 MHz; Communication System PAR: 0 dB                      Medium parameters used: <math>f = 837 \text{ MHz}</math>; <math>\sigma = 0.951 \text{ S/m}</math>; <math>\epsilon_r = 54.241</math>; <math>\rho = 1000 \text{ kg/m}^3</math>                      Phantom section: Flat Section                      Measurement Standard: DASYS (IEEE1528-2013)                      DASYS Configuration:</p> <ul style="list-style-type: none"> <li>Probe: ES3DV3 - SN3297; ConvF(6.08, 6.08, 6.08); Calibrated: 14/10/2016;</li> <li>Sensor-Surface: 3mm (Mechanical Surface Detection)</li> <li>Electronics: DAE4 Sn1226; Calibrated: 28/09/2016</li> <li>Phantom: SAM1; Type: SAM; Serial: TP1576</li> <li>Measurement SW: DASYS2, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)</li> </ul> <p><b>body/towards phantom data/Area Scan (91x161x1):</b> Interpolated grid: <math>dx=1.000 \text{ mm}</math>, <math>dy=1.000 \text{ mm}</math>                      Maximum value of SAR = 0.205 W/kg  <b>body/towards phantom data/Zoom Scan (7x7x7)/Cube 0:</b> Measurement grid: <math>dx=5\text{mm}</math>, <math>dy=5\text{mm}</math>, <math>dz=5\text{mm}</math>                      Reference Value = 15.08 V/m; Power Drift = 0.01 dB                      Peak SAR (extrapolated) = 0.389 W/kg  <b>SAR(1 g) = 0.181 W/kg; SAR(10 g) = 0.129 W/kg</b></p> <p>Maximum value of SAR (measured) = 0.204 W/kg</p> <div data-bbox="188 1263 1401 1720"> </div> <p>0 dB = 0.205 W/kg = -6.88 dBW/kg</p>	


FLAT(DATA)	Towards ground
<p>Communication System: UID 0, WCDMA (0); Communication System Band: BAND 5;                      Frequency: 836.6 MHz; Communication System PAR: 0 dB                      Medium parameters used: <math>f = 837 \text{ MHz}</math>; <math>\sigma = 0.951 \text{ S/m}</math>; <math>\epsilon_r = 54.241</math>; <math>\rho = 1000 \text{ kg/m}^3</math>                      Phantom section: Flat Section                      Measurement Standard: DASYS (IEEE1528-2013)                      DASYS Configuration:</p> <ul style="list-style-type: none"> <li>Probe: ES3DV3 - SN3297; ConvF(6.08, 6.08, 6.08); Calibrated: 14/10/2016;</li> <li>Sensor-Surface: 3mm (Mechanical Surface Detection)</li> <li>Electronics: DAE4 Sn1226; Calibrated: 28/09/2016</li> <li>Phantom: SAM1; Type: SAM; Serial: TP1576</li> <li>Measurement SW: DASYS2, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)</li> </ul> <p><b>body/towards ground data/Area Scan (91x161x1):</b> Interpolated grid: <math>dx=1.000 \text{ mm}</math>, <math>dy=1.000 \text{ mm}</math>                      Maximum value of SAR = 0.338 W/kg  <b>body/towards ground data/Zoom Scan (7x7x7)/Cube 0:</b> Measurement grid: <math>dx=5\text{mm}</math>, <math>dy=5\text{mm}</math>, <math>dz=5\text{mm}</math>                      Reference Value = 19.27 V/m; Power Drift = -0.01 dB                      Peak SAR (extrapolated) = 0.389 W/kg  <b>SAR(1 g) = 0.309 W/kg; SAR(10 g) = 0.239 W/kg</b>                      Maximum value of SAR (measured) = 0.338 W/kg</p> <div data-bbox="156 1265 1433 1720"> </div> <p style="text-align: center;">0 dB = 0.338 W/kg = -4.71 dBW/kg</p>	

FLAT	EDGE2
<p>Communication System: UID 0, WCDMA (0); Communication System Band: BAND 5; Frequency: 836.6 MHz; Communication System PAR: 0 dB Medium parameters used: <math>f = 837</math> MHz; <math>\sigma = 0.951</math> S/m; <math>\epsilon_r = 54.241</math>; <math>\rho = 1000</math> kg/m<sup>3</sup> Phantom section: Flat Section Measurement Standard: DASYS (IEEE1528-2013) DASY5 Configuration:</p> <ul style="list-style-type: none"> <li>Probe: ES3DV3 - SN3297; ConvF(6.08, 6.08, 6.08); Calibrated: 14/10/2016;</li> <li>Sensor-Surface: 3mm (Mechanical Surface Detection)</li> <li>Electronics: DAE4 Sn1226; Calibrated: 28/09/2016</li> <li>Phantom: SAM1; Type: SAM; Serial: TP1576</li> <li>Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)</li> </ul> <p><b>body/edge 2 mid/Area Scan (61x101x1):</b> Interpolated grid: dx=1.000 mm, dy=1.000 mm Maximum value of SAR = 0.0766 W/kg <b>body/edge 2 mid/ Zoom Scan (7x7x7)/Cube 0:</b> Measurement grid: dx=5mm, dy=5mm, dz=5mm Reference Value = 6.561 V/m; Power Drift = 0.03 dB Peak SAR (extrapolated) = 0.389 W/kg <b>SAR(1 g) = 0.0649 W/kg; SAR(10 g) = 0.0406 W/kg</b> Maximum value of SAR (measured) = 0.0710 W/kg</p> <div data-bbox="188 1263 1401 1720"> </div> <p>0 dB = 0.0766 W/kg = -11.16 dBW/kg</p>	


FLAT	EDGE3
------	-------

Frequency: 836.6 MHz; Communication System PAR: 0 dB  
 Medium parameters used:  $f = 837 \text{ MHz}$ ;  $\sigma = 0.951 \text{ S/m}$ ;  $\epsilon_r = 54.241$ ;  $\rho = 1000 \text{ kg/m}^3$   
 Phantom section: Flat Section  
 Measurement Standard: DASY5 (IEEE 1528-2013)  
 DASY5 Configuration:

- Probe: ES3DV3 - SN3297; ConvF(6.08, 6.08, 6.08); Calibrated: 14/10/2016;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1226; Calibrated: 28/09/2016
- Phantom: SAM1; Type: SAM; Serial: TP1576
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)  
**body2/edge3 mid/Area Scan (61x161x1):** Interpolated grid:  $dx=1.000 \text{ mm}$ ,  $dy=1.000 \text{ mm}$   
 Maximum value of SAR = 0.189 W/kg  
**body2/edge3 mid/Zoom Scan (7x7x7)/Cube 0:** Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=5\text{mm}$   
 Reference Value = 13.94 V/m; Power Drift = 0.08 dB  
 Peak SAR (extrapolated) = 0.389 W/kg  
**SAR(1 g) = 0.165 W/kg; SAR(10 g) = 0.0111 W/kg**  
 Maximum value of SAR (measured) = 0.182 W/kg





0 dB = 0.189 W/kg = -7.24 dBW/kg



FLAT	EDGE4
<p>Communication System: UID 0, WCDMA (0); Communication System Band: BAND 5;                      Frequency: 836.6 MHz; Communication System PAR: 0 dB                      Medium parameters used: <math>f = 837 \text{ MHz}</math>; <math>\sigma = 0.951 \text{ S/m}</math>; <math>\epsilon_r = 54.241</math>; <math>\rho = 1000 \text{ kg/m}^3</math>                      Phantom section: Flat Section                      Measurement Standard: DASY5 (IEEE1528-2013)                      DASY5 Configuration:</p> <ul style="list-style-type: none"> <li>Probe: ES3DV3 - SN3297; ConvF(6.08, 6.08, 6.08); Calibrated: 14/10/2016;</li> <li>Sensor-Surface: 3mm (Mechanical Surface Detection)</li> <li>Electronics: DAE4 Sn1226; Calibrated: 28/09/2016</li> <li>Phantom: SAM1; Type: SAM; Serial: TP1576</li> <li>Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)</li> </ul> <p><b>body2/edge4 mid/Area Scan (61x161x1):</b> Interpolated grid: <math>dx=1.000 \text{ mm}</math>, <math>dy=1.000 \text{ mm}</math>                      Maximum value of SAR = 0.245 W/kg  <b>body2/edge4 mid/Zoom Scan (7x7x7)/Cube 0:</b> Measurement grid: <math>dx=5\text{mm}</math>, <math>dy=5\text{mm}</math>, <math>dz=5\text{mm}</math>                      Reference Value = 16.4 V/m; Power Drift = -0.00 dB                      Peak SAR (extrapolated) = 0.389 W/kg  <b>SAR(1 g) = 0.213 W/kg; SAR(10 g) = 0.144 W/kg</b>                      Maximum value of SAR (measured) = 0.243 W/kg</p>	
 <p style="text-align: center;">0 dB = 0.245 W/kg = -6.11 dBW/kg</p>	



**WLAN**

Left Side	Cheek
<p>Communication System: UID 0, 802.11b/g/n 2.45GHz (0); Communication System Band: 2.4G; Frequency: 2437 MHz; Communication System PAR: 0 dB            Medium parameters used: <math>f = 2437</math> MHz; <math>\sigma = 1.776</math> S/m; <math>\epsilon_r = 37.832</math>; <math>\rho = 1000</math> kg/m<sup>3</sup>            Phantom section: Left Section            Measurement Standard: DASY5 (IEEE1528-2013)            DASY5 Configuration:</p> <ul style="list-style-type: none"> <li>• Probe: EX3DV4 - SN3717; ConvF(6.96, 6.96, 6.96); Calibrated: 19/10/2016;</li> <li>• Sensor-Surface: 1.4mm (Mechanical Surface Detection)</li> <li>• Electronics: DAE4 Sn1327; Calibrated: 15/04/2016</li> <li>• Phantom: SAM 1; Type: SAM; Serial: TP:1702</li> <li>• Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)</li> </ul> <p><b>left/touch mid/Area Scan (91x161x1):</b> Interpolated grid: dx=1.000 mm, dy=1.000 mm            Maximum value of SAR (interpolated) = 0.370 W/kg  <b>left/touch mid/Zoom Scan (7x7x7)/Cube 0:</b> Measurement grid: dx=5mm, dy=5mm, dz=5mm            Reference Value = 8.450 V/m; Power Drift = -0.02 dB            Peak SAR (extrapolated) = 0.451 W/kg  <b>SAR(1 g) = 0.236 W/kg; SAR(10 g) = 0.120 W/kg</b>            Maximum value of SAR (measured) = 0.371 W/kg</p> <div style="display: flex; align-items: center;"> <div style="margin-right: 20px;"> <p>dB</p>  </div> <div>  </div> </div> <p style="text-align: center;">0 dB = 0.370 W/kg = -4.32 dBW/kg</p>	



Left Side	Tilt
<p>Communication System: UID 0, 802.11b/g/n 2.45GHz (0); Communication System Band: 2.4G; Frequency: 2437 MHz; Communication System PAR: 0 dB            Medium parameters used: <math>f = 2437 \text{ MHz}</math>; <math>\sigma = 1.776 \text{ S/m}</math>; <math>\epsilon_r = 37.832</math>; <math>\rho = 1000 \text{ kg/m}^3</math>            Phantom section: Left Section            Measurement Standard: DASY5 (IEEE1528-2013)            DASY5 Configuration:</p> <ul style="list-style-type: none"> <li>Probe: EX3DV4 - SN3717; ConvF(6.96, 6.96, 6.96); Calibrated: 19/10/2016;</li> <li>Sensor-Surface: 1.4mm (Mechanical Surface Detection)</li> <li>Electronics: DAE4 Sn1327; Calibrated: 15/04/2016</li> <li>Phantom: SAM 1; Type: SAM; Serial: TP:1702</li> <li>Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)  <b>left/tilt mid/Area Scan (91x161x1):</b> Interpolated grid: <math>dx=1.000 \text{ mm}</math>, <math>dy=1.000 \text{ mm}</math>            Maximum value of SAR (interpolated) = 0.273 W/kg  <b>left/tilt mid/ Zoom Scan (7x7x7)/Cube 0:</b> Measurement grid: <math>dx=5\text{mm}</math>, <math>dy=5\text{mm}</math>, <math>dz=5\text{mm}</math></li> <li>Reference Value = 8.483 V/m; Power Drift = 0.06 dB            Peak SAR (extrapolated) = 0.342 W/kg  <b>SAR(1 g) = 0.164 W/kg; SAR(10 g) = 0.0823 W/kg</b>            Maximum value of SAR (measured) = 0.263 W/kg</li> </ul>	
<div style="display: flex; align-items: center;"> <div style="margin-right: 20px;"> <p><b>dB</b></p>  </div> <div>  </div> </div> <p style="text-align: center; margin-top: 20px;"><math>0 \text{ dB} = 0.273 \text{ W/kg} = -5.64 \text{ dBW/kg}</math></p>	

Right Side	Cheek
<p>Communication System: UID 0, 802.11b/g/n 2.45GHz (0); Communication System Band: 2.4G; Frequency: 2437 MHz; Communication System PAR: 0 dB            Medium parameters used: <math>f = 2437 \text{ MHz}</math>; <math>\sigma = 1.776 \text{ S/m}</math>; <math>\epsilon_r = 37.832</math>; <math>\rho = 1000 \text{ kg/m}^3</math>            Phantom section: Right Section            Measurement Standard: DASYS (IEEE1528-2013)            DASYS Configuration:</p> <ul style="list-style-type: none"> <li>Probe: EX3DV4 - SN3717; ConvF(6.96, 6.96, 6.96); Calibrated: 19/10/2016;</li> <li>Sensor-Surface: 1.4mm (Mechanical Surface Detection)</li> <li>Electronics: DAE4 Sn1327; Calibrated: 15/04/2016</li> <li>Phantom: SAM 1; Type: SAM; Serial: TP:1702</li> <li>Measurement SW: DASYS2, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)</li> </ul> <p><b>right/touch mid/Area Scan (91x161x1):</b> Interpolated grid: <math>dx=1.000 \text{ mm}</math>, <math>dy=1.000 \text{ mm}</math>            Maximum value of SAR (interpolated) = 1.08 W/kg  <b>right/touch mid/Zoom Scan (7x7x7)/Cube 0:</b> Measurement grid: <math>dx=5\text{mm}</math>, <math>dy=5\text{mm}</math>, <math>dz=5\text{mm}</math>            Reference Value = 7.552 V/m; Power Drift = -0.02 dB            Peak SAR (extrapolated) = 1.35 W/kg  <b>SAR(1 g) = 0.644 W/kg; SAR(10 g) = 0.294 W/kg</b>            Maximum value of SAR (measured) = 1.10 W/kg</p> <div data-bbox="279 1265 1305 1720"> </div> <p style="text-align: center;">0 dB = 1.08 W/kg = 0.34 dBW/kg</p>	

Right Side	Cheek
------------	-------

Communication System: UID 0, 802.11b/g/n 2.45GHz (0); Communication System Band: 2.4G; Frequency: 2412 MHz; Communication System PAR: 0 dB

Medium parameters used:  $f = 2412$  MHz;  $\sigma = 1.74$  S/m;  $\epsilon_r = 37.907$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Right Section

Measurement Standard: DASY5 (IEEE1528-2013)

DASY5 Configuration:

- Probe: ES3DV3 - SN3297; ConvF(4.53, 4.53, 4.53); Calibrated: 14/10/2016;
  - Sensor-Surface: 3mm (Mechanical Surface Detection)
  - Electronics: DAE4 Sn1226; Calibrated: 28/09/2016
  - Phantom: SAM2; Type: SAM; Serial: TP-1575
  - Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)
- right/touch low/Area Scan (91x161x1):** Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 0.720 W/kg


**right/touch low/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 7.514 V/m; Power Drift = -0.07 dB


Peak SAR (extrapolated) = 1.12 W/kg

**SAR(1 g) = 0.525 W/kg; SAR(10 g) = 0.237 W/kg**

Maximum value of SAR (measured) = 0.710 W/kg




0 dB = 0.710 W/kg = -1.49 dBW/kg

Right Side	Cheek
<p>Communication System: UID 0, 802.11b/g/n 2.45GHz (0); Communication System Band: 2.4G; Frequency: 2462 MHz; Communication System PAR: 0 dB                      Medium parameters used: <math>f = 2462</math> MHz; <math>\sigma = 1.789</math> S/m; <math>\epsilon_r = 37.883</math>; <math>\rho = 1000</math> kg/m<sup>3</sup>                      Phantom section: Right Section                      Measurement Standard: DASY5 (IEEE1528-2013)                      DASY5 Configuration:</p> <ul style="list-style-type: none"> <li>• Probe: ES3DV3 - SN3297; ConvF(4.53, 4.53, 4.53); Calibrated: 14/10/2016;</li> <li>• Sensor-Surface: 3mm (Mechanical Surface Detection)</li> <li>• Electronics: DAE4 Sn1226; Calibrated: 28/09/2016</li> <li>• Phantom: SAM2; Type: SAM; Serial: TP-1575</li> <li>• Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)</li> </ul> <p><b>right/touch high/Area Scan (91x161x1):</b> Interpolated grid: dx=1.000 mm, dy=1.000 mm                      Maximum value of SAR (interpolated) = 1.19 W/kg  <b>right/touch high/Zoom Scan (7x7x7)/Cube 0:</b> Measurement grid: dx=5mm, dy=5mm, dz=5mm                      Reference Value = 11.42 V/m; Power Drift = 0.02 dB                      Peak SAR (extrapolated) = 2.04 W/kg  <b>SAR(1 g) = 0.931 W/kg; SAR(10 g) = 0.414 W/kg</b>                      Maximum value of SAR (measured) = 1.23 W/kg</p>	
 <p style="text-align: center;">0 dB = 1.19 W/kg = 0.76 dBW/kg</p>	


Right Side	Cheek
------------	-------

Communication System: UID 0, 802.11b/g/n 2.45GHz (0); Communication System Band: 2.4G; Frequency: 2462 MHz; Communication System PAR: 0 dB  
 Medium parameters used:  $f = 2462$  MHz;  $\sigma = 1.789$  S/m;  $\epsilon_r = 37.883$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
 Phantom section: Right Section  
 Measurement Standard: DASYS (IEEE1528-2013)  
 DASYS Configuration:

- Probe: ES3DV3 - SN3297; ConvF(4.53, 4.53, 4.53); Calibrated: 14/10/2016;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1226; Calibrated: 28/09/2016
- Phantom: SAM2; Type: SAM; Serial: TP-1575
- Measurement SW: DASYS2, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)  
**right/touch high 2/Area Scan (91x161x1):** Interpolated grid: dx=1.000 mm, dy=1.000 mm  
 Maximum value of SAR (interpolated) = 1.19 W/kg  
**right/touch high 2/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm  
 Reference Value = 11.37 V/m; Power Drift = 0.06 dB  
 Peak SAR (extrapolated) = 2.05 W/kg  
**SAR(1 g) = 0.934 W/kg; SAR(10 g) = 0.415 W/kg**  
 Maximum value of SAR (measured) = 1.24 W/kg



0 dB = 1.19 W/kg = 0.76 dBW/kg

Right Side	Tilt
<p>Communication System: UID 0, 802.11b/g/n 2.45GHz (0); Communication System Band: 2.4G; Frequency: 2437 MHz; Communication System PAR: 0 dB            Medium parameters used: <math>f = 2437</math> MHz; <math>\sigma = 1.776</math> S/m; <math>\epsilon_r = 37.832</math>; <math>\rho = 1000</math> kg/m<sup>3</sup>            Phantom section: Right Section            Measurement Standard: DASY5 (IEEE1528-2013)            DASY5 Configuration:</p> <ul style="list-style-type: none"> <li>Probe: EX3DV4 - SN3717; ConvF(6.96, 6.96, 6.96); Calibrated: 19/10/2016;</li> <li>Sensor-Surface: 1.4mm (Mechanical Surface Detection)</li> <li>Electronics: DAE4 Sn1327; Calibrated: 15/04/2016</li> <li>Phantom: SAM 1; Type: SAM; Serial: TP:1702</li> <li>Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)  <b>right/tilt mid/Area Scan (91x161x1):</b> Interpolated grid: dx=1.000 mm, dy=1.000 mm            Maximum value of SAR (interpolated) = 0.727 W/kg  <b>right/tilt mid/ Zoom Scan (7x7x7)/Cube 0:</b> Measurement grid: dx=5mm, dy=5mm, dz=5mm</li> <li>Reference Value = 7.654 V/m; Power Drift = 0.10 dB            Peak SAR (extrapolated) = 0.751 W/kg  <b>SAR(1 g) = 0.402 W/kg; SAR(10 g) = 0.190 W/kg</b>            Maximum value of SAR (measured) = 0.629 W/kg</li> </ul>	
	
<p>0 dB = 0.727 W/kg = -1.38 dBW/kg</p>	



FLAT	Towards phantom
<p>Communication System: UID 0, 802.11b/g/n 2.45GHz (0); Communication System Band: 2.4G; Frequency: 2437 MHz; Communication System PAR: 0 dB            Medium parameters used: <math>f = 2437</math> MHz; <math>\sigma = 1.906</math> S/m; <math>\epsilon_r = 51.957</math>; <math>\rho = 1000</math> kg/m<sup>3</sup>            Phantom section: Flat Section            Measurement Standard: DASY5 (IEEE1528-2013)            DASY5 Configuration:</p> <ul style="list-style-type: none"> <li>Probe: EX3DV4 - SN3717; ConvF(7.04, 7.04, 7.04); Calibrated: 19/10/2016;</li> <li>Sensor-Surface: 1.4mm (Mechanical Surface Detection)</li> <li>Electronics: DAE4 Sn1327; Calibrated: 15/04/2016</li> <li>Phantom: ELI v4.0; Type: ELI4; Serial: TP:1086</li> <li>Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)</li> </ul> <p><b>body/towards phantom mid/Area Scan (91x161x1):</b> Interpolated grid: dx=1.000 mm, dy=1.000 mm            Maximum value of SAR (interpolated) = 0.164 W/kg  <b>body/towards phantom mid/ Zoom Scan (7x7x7)/Cube 0:</b> Measurement grid: dx=5mm, dy=5mm, dz=5mm</p> <ul style="list-style-type: none"> <li>Reference Value = 5.269 V/m; Power Drift = 0.03 dB            Peak SAR (extrapolated) = 0.272 W/kg  <b>SAR(1 g) = 0.110 W/kg; SAR(10 g) = 0.0623 W/kg</b>            Maximum value of SAR (measured) = 0.160 W/kg</li> </ul>	
<div style="display: flex; align-items: center;"> <div style="margin-right: 20px;"> <p>dB</p> <p>0 -3.56 -7.11 -10.67 -14.23 -17.78</p> </div> <div> </div> </div> <p style="text-align: center; margin-top: 20px;">0 dB = 0.164 W/kg = -7.85 dBW/kg</p>	

FLAT	Towards ground
------	----------------

Communication System: UID 0, 802.11b/g/n 2.45GHz (0); Communication System Band: 2.4G; Frequency: 2437 MHz; Communication System PAR: 0 dB

Medium parameters used:  $f = 2437$  MHz;  $\sigma = 1.906$  S/m;  $\epsilon_r = 51.957$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE1528-2013)

DASY5 Configuration:

- Probe: EX3DV4 - SN3717; ConvF(7.04, 7.04, 7.04); Calibrated: 19/10/2016;
  - Sensor-Surface: 1.4mm (Mechanical Surface Detection)
  - Electronics: DAE4 Sn1327; Calibrated: 15/04/2016
  - Phantom: ELI v4.0; Type: ELI4; Serial: TP:1086
  - Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)
- body/towards ground mid/Area Scan (91x161x1):** Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 0.190 W/kg


**body/towards ground mid/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 4.424 V/m; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 0.243 W/kg

**SAR(1 g) = 0.126 W/kg; SAR(10 g) = 0.069 W/kg**

Maximum value of SAR (measured) = 0.196 W/kg



$0 \text{ dB} = 0.190 \text{ W/kg} = -7.21 \text{ dBW/kg}$




FLAT	EDGE1
------	-------

Communication System: UID 0, 802.11b/g/n 2.45GHz (0); Communication System Band: 2.4G; Frequency: 2437 MHz; Communication System PAR: 0 dB  
 Medium parameters used:  $f = 2437$  MHz;  $\sigma = 1.906$  S/m;  $\epsilon_r = 51.957$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
 Phantom section: Flat Section  
 Measurement Standard: DASY5 (IEEE1528-2013)

DASY5 Configuration:

- Probe: EX3DV4 - SN3717; ConvF(7.04, 7.04, 7.04); Calibrated: 19/10/2016;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1327; Calibrated: 15/04/2016
- Phantom: ELI v4.0; Type: ELI4; Serial: TP:1086
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)  
**body/edge 1 mid/Area Scan (61x101x1):** Interpolated grid: dx=1.000 mm, dy=1.000 mm  
 Maximum value of SAR (interpolated) = 0.0842 W/kg  
**body/edge 1 mid/ Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm
- Reference Value = 5.184 V/m; Power Drift = -0.01 dB  
 Peak SAR (extrapolated) = 0.121 W/kg  
**SAR(1 g) = 0.0548 W/kg; SAR(10 g) = 0.0287 W/kg**  
 Maximum value of SAR (measured) = 0.0809 W/kg




0 dB = 0.0842 W/kg = -10.75 dBW/kg

FLAT	EDGE3
------	-------

Communication System: UID 0, 802.11b/g/n 2.45GHz (0); Communication System Band: 2.4G; Frequency: 2437 MHz; Communication System PAR: 0 dB  
 Medium parameters used:  $f = 2437$  MHz;  $\sigma = 1.906$  S/m;  $\epsilon_r = 51.957$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
 Phantom section: Flat Section  
 Measurement Standard: DASY5 (IEEE1528-2013)

DASY5 Configuration:

- Probe: EX3DV4 - SN3717; ConvF(7.04, 7.04, 7.04); Calibrated: 19/10/2016;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1327; Calibrated: 15/04/2016
- Phantom: ELI v4.0; Type: ELI4; Serial: TP:1086
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)  
**body2/edge3 mid/Area Scan (61x161x1):** Interpolated grid: dx=1.000 mm, dy=1.000 mm  
 Maximum value of SAR (interpolated) = 0.0188 W/kg  
**body2/edge3 mid/ Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm
- Reference Value = 2.226 V/m; Power Drift = -0.04 dB  
 Peak SAR (extrapolated) = 0.051 W/kg  
**SAR(1 g) = 0.0123 W/kg; SAR(10 g) = 0.0671 W/kg**  
 Maximum value of SAR (measured) = 0.0172 W/kg



0 dB = 0.0188 W/kg = -17.26 dBW/kg


**LTE (Band 2 20BW-1RB-Low /Head)**

Left Side	Cheek
-----------	-------


Communication System: UID 10169 - CAB, LTE-FDD (SC-FDMA, 1 RB, 20 MHz, QPSK);  
 Frequency: 1880 MHz; Duty Cycle: 1:3.74111  
 Medium parameters used:  $f = 1880$  MHz;  $\sigma = 1.45$  S/m;  $\epsilon_r = 39.74$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
 Phantom section: Left Section


**DASY5 Configuration:**

- Probe: ES3DV3 - SN3127; ConvF(5.15, 5.15, 5.15); Calibrated: 2016/8/29;
  - Sensor-Surface: 4mm (Mechanical Surface Detection)
  - Electronics: DAE4 Sn546; Calibrated: 2016/8/22
  - Phantom: SAM 1559 classical; Type: QD000P40CC; Serial: TP:xxxx
  - Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373)
- Head-Section HSL LTE band2 Left/LTE band2 20MHz 1RB Low HSL touch M/Area Scan (9x13x1):** Measurement grid: dx=15mm, dy=15mm  
 Maximum value of SAR (measured) = 0.177 W/kg
- Head-Section HSL LTE band2 Left/LTE band2 20MHz 1RB Low HSL touch M/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm  
 Reference Value = 4.158 V/m; Power Drift = 0.07 dB  
 Peak SAR (extrapolated) = 0.254 W/kg  
**SAR(1 g) = 0.164 W/kg; SAR(10 g) = 0.103 W/kg**



0 dB = 0.177 W/kg = -7.52 dBW/kg

Left Side	Tilt
<p>Communication System: UID 10169 - CAB, LTE-FDD (SC-FDMA, 1 RB, 20 MHz, QPSK); Frequency: 1880 MHz; Duty Cycle: 1:3.74111 Medium parameters used: <math>f = 1880 \text{ MHz}</math>; <math>\sigma = 1.45 \text{ S/m}</math>; <math>\epsilon_r = 39.74</math>; <math>\rho = 1000 \text{ kg/m}^3</math> Phantom section: Left Section</p>	
<p>DASY5 Configuration:</p> <ul style="list-style-type: none"> <li>Probe: ES3DV3 - SN3127; ConvF(5.15, 5.15, 5.15); Calibrated: 2016/8/29;</li> <li>Sensor-Surface: 4mm (Mechanical Surface Detection)</li> <li>Electronics: DAE4 Sn546; Calibrated: 2016/8/22</li> <li>Phantom: SAM 1559 classical; Type: QD000P40CC; Serial: TP:xxxx</li> <li>Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373)</li> </ul> <p><b>Head-Section HSL LTE band2 Left/LTE band2 20MHz 1RB Low HSL tilt M/Area Scan (9x13x1):</b> Measurement grid: <math>dx=15\text{mm}</math>, <math>dy=15\text{mm}</math> Maximum value of SAR (measured) = 0.0663 W/kg</p> <p><b>Head-Section HSL LTE band2 Left/LTE band2 20MHz 1RB Low HSL tilt M/Zoom Scan (7x7x7)/Cube 0:</b> Measurement grid: <math>dx=5\text{mm}</math>, <math>dy=5\text{mm}</math>, <math>dz=5\text{mm}</math> Reference Value = 6.644 V/m; Power Drift = -0.13 dB Peak SAR (extrapolated) = 0.105 W/kg <b>SAR(1 g) = 0.055 W/kg; SAR(10 g) = 0.034 W/kg</b> Maximum value of SAR (measured) = 0.0640 W/kg</p>	
 <p>0 dB = 0.0640 W/kg = -11.94 dBW/kg</p>	

Right Side	Cheek
<p>Communication System: UID 10169 - CAB, LTE-FDD (SC-FDMA, 1 RB, 20 MHz, QPSK);                      Frequency: 1880 MHz; Duty Cycle: 1:3.74111                      Medium parameters used: <math>f = 1880</math> MHz; <math>\sigma = 1.45</math> S/m; <math>\epsilon_r = 39.74</math>; <math>\rho = 1000</math> kg/m<sup>3</sup>                      Phantom section: Right Section</p> <p>DASY5 Configuration:</p> <ul style="list-style-type: none"> <li>Probe: ES3DV3 - SN3127; ConvF(5.15, 5.15, 5.15); Calibrated: 2016/8/29;</li> <li>Sensor-Surface: 4mm (Mechanical Surface Detection)</li> <li>Electronics: DAE4 Sn546; Calibrated: 2016/8/22</li> <li>Phantom: SAM 1559 classical; Type: QD000P40CC; Serial: TP:xxxx</li> <li>Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373)</li> </ul> <p><b>Head-Section HSL LTE band2 Right/LTE band2 20MHz 1RB Low HSL touch M/Area Scan (8x13x1):</b> Measurement grid: dx=15mm, dy=15mm                      Maximum value of SAR (measured) = 0.135 W/kg</p> <p><b>Head-Section HSL LTE band2 Right/LTE band2 20MHz 1RB Low HSL touch M/Zoom Scan (7x7x7)/Cube 0:</b> Measurement grid: dx=5mm, dy=5mm, dz=5mm                      Reference Value = 3.494 V/m; Power Drift = 0.02 dB                      Peak SAR (extrapolated) = 0.226 W/kg  <b>SAR(1 g) = 0.144 W/kg; SAR(10 g) = 0.089 W/kg</b>                      Maximum value of SAR (measured) = 0.157 W/kg</p>	
 <p style="text-align: center;">0 dB = 0.157 W/kg = -8.04 dBW/kg</p>	

Right Side	Tilt
<p>Communication System: UID 10169 - CAB, LTE-FDD (SC-FDMA, 1 RB, 20 MHz, QPSK);                      Frequency: 1880 MHz; Duty Cycle: 1:3.74111                      Medium parameters used: <math>f = 1880</math> MHz; <math>\sigma = 1.45</math> S/m; <math>\epsilon_r = 39.74</math>; <math>\rho = 1000</math> kg/m<sup>3</sup>                      Phantom section: Right Section</p> <p>DASY5 Configuration:</p> <ul style="list-style-type: none"> <li>Probe: ES3DV3 - SN3127; ConvF(5.15, 5.15, 5.15); Calibrated: 2016/8/29;</li> <li>Sensor-Surface: 4mm (Mechanical Surface Detection)</li> <li>Electronics: DAE4 Sn546; Calibrated: 2016/8/22</li> <li>Phantom: SAM 1559 classical; Type: QD000P40CC; Serial: TP:xxxx</li> <li>Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373)</li> </ul> <p><b>Head-Section HSL LTE band2 Right/LTE band2 20MHz 1RB Low HSL tilt M/Area Scan (8x13x1):</b> Measurement grid: dx=15mm, dy=15mm                      Maximum value of SAR (measured) = 0.0543 W/kg</p> <p><b>Head-Section HSL LTE band2 Right/LTE band2 20MHz 1RB Low HSL tilt M/Zoom Scan (7x7x7)/Cube 0:</b> Measurement grid: dx=5mm, dy=5mm, dz=5mm                      Reference Value = 5.023 V/m; Power Drift = 0.03 dB                      Peak SAR (extrapolated) = 0.0900 W/kg  <b>SAR(1 g) = 0.054 W/kg; SAR(10 g) = 0.031 W/kg</b>                      Maximum value of SAR (measured) = 0.0595 W/kg</p> <div data-bbox="279 1243 1305 1697"> </div> <p>0 dB = 0.0595 W/kg = -12.25 dBW/kg</p>	

**LTE (Band 2 20BW-1RB-Low/Flat)**

FLAT	Towards phantom
------	-----------------

Communication System: UID 0, LTE band 2 (0); Frequency: 1880 MHz; Duty Cycle: 1:1  
Medium parameters used:  $f = 1880$  MHz;  $\sigma = 1.57$  S/m;  $\epsilon_r = 51.14$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
Phantom section: Flat Section

**DASY5 Configuration:**

- Probe: ES3DV3 - SN3127; ConvF(4.9, 4.9, 4.9); Calibrated: 2016/8/29;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn546; Calibrated: 2016/8/22
- Phantom: Twin-SAM 1560; Type: QD 000 P40 CD; Serial: 1560
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373)

**Flat-Section MSL LTE band2 TP/LTE band2 TP 20MHz 1RB M 10mm/Area Scan (9x13x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.306 W/kg


**Flat-Section MSL LTE band2 TP/LTE band2 TP 20MHz 1RB M 10mm/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 6.804 V/m; Power Drift = -0.05 dB

Peak SAR (extrapolated) = 0.489 W/kg

**SAR(1 g) = 0.300 W/kg; SAR(10 g) = 0.175 W/kg**

Maximum value of SAR (measured) = 0.333 W/kg



0 dB = 0.333 W/kg = -4.78 dBW/kg




**FLAT**

**Towards ground**

Communication System: UID 0, LTE band 2 (0); Frequency: 1880 MHz; Duty Cycle: 1:1  
Medium parameters used:  $f = 1880$  MHz;  $\sigma = 1.57$  S/m;  $\epsilon_r = 51.14$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
Phantom section: Flat Section

DASY5 Configuration:

- Probe: ES3DV3 - SN3127; ConvF(4.9, 4.9, 4.9); Calibrated: 2016/8/29;
  - Sensor-Surface: 4mm (Mechanical Surface Detection)
  - Electronics: DAE4 Sn546; Calibrated: 2016/8/22
  - Phantom: Twin-SAM 1560; Type: QD 000 P40 CD; Serial: 1560
  - Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373)
- Flat-Section MSL LTE band2 TG/LTE band2 TG 20MHz 1RB M 10mm/Area Scan (9x13x1):** Measurement grid: dx=15mm, dy=15mm  
Maximum value of SAR (measured) = 0.772 W/kg
- Flat-Section MSL LTE band2 TG/LTE band2 TG 20MHz 1RB M 10mm/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm  
Reference Value = 7.061 V/m; Power Drift = -0.02 dB  
Peak SAR (extrapolated) = 1.28 W/kg  
**SAR(1 g) = 0.739 W/kg; SAR(10 g) = 0.397 W/kg**  
Maximum value of SAR (measured) = 0.816 W/kg



0 dB = 0.816 W/kg = -0.88 dBW/kg





**LTE (Band 2 20BW-50%RB-Low /Head)**

Left Side	Cheek
-----------	-------


Communication System: UID 10297 - AAA, LTE-FDD (SC-FDMA, 50% RB, 20 MHz, QPSK);  
Frequency: 1880 MHz; Duty Cycle: 1:3.81066  
Medium parameters used:  $f = 1880$  MHz;  $\sigma = 1.45$  S/m;  $\epsilon_r = 39.74$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
Phantom section: Left Section

**DASY5 Configuration:**

- Probe: ES3DV3 - SN3127; ConvF(5.15, 5.15, 5.15); Calibrated: 2016/8/29;
  - Sensor-Surface: 4mm (Mechanical Surface Detection)
  - Electronics: DAE4 Sn546; Calibrated: 2016/8/22
  - Phantom: SAM 1559 classical; Type: QD000P40CC; Serial: TP:xxxx
  - Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373)
- Head-Section HSL LTE band2 Left/LTE band2 20MHz 50RB Low HSL touch M/Area Scan (9x13x1):** Measurement grid: dx=15mm, dy=15mm  
Maximum value of SAR (measured) = 0.138 W/kg
- Head-Section HSL LTE band2 Left/LTE band2 20MHz 50RB Low HSL touch M/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm  
Reference Value = 3.592 V/m; Power Drift = 0.03 dB  
Peak SAR (extrapolated) = 0.202 W/kg  
**SAR(1 g) = 0.130 W/kg; SAR(10 g) = 0.081 W/kg**  
Maximum value of SAR (measured) = 0.141 W/kg



0 dB = 0.141 W/kg = -8.51 dBW/kg

Left Side	Tilt
<p>Communication System: UID 0, LTE band 2 (0); Frequency: 1880 MHz; Duty Cycle: 1:1 Medium parameters used: <math>f = 1880</math> MHz; <math>\sigma = 1.45</math> S/m; <math>\epsilon_r = 39.74</math>; <math>\rho = 1000</math> kg/m<sup>3</sup> Phantom section: Left Section</p>	
<p>DASY5 Configuration:</p>	
<ul style="list-style-type: none"> <li>• Probe: ES3DV3 - SN3127; ConvF(5.15, 5.15, 5.15); Calibrated: 2016/8/29;</li> <li>• Sensor-Surface: 4mm (Mechanical Surface Detection)</li> <li>• Electronics: DAE4 Sn546; Calibrated: 2016/8/22</li> <li>• Phantom: SAM 1559 classical; Type: QD000P40CC; Serial: TP:xxxx</li> <li>• Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373)</li> </ul> <p><b>Head-Section HSL LTE band2 Left/LTE band2 20MHz 50RB Low HSL tilt M/Area Scan (9x13x1):</b> Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (measured) = 0.0475 W/kg</p> <p><b>Head-Section HSL LTE band2 Left/LTE band2 20MHz 50RB Low HSL tilt M/Zoom Scan (7x7x7)/Cube 0:</b> Measurement grid: dx=5mm, dy=5mm, dz=5mm Reference Value = 5.321 V/m; Power Drift = 0.02 dB Peak SAR (extrapolated) = 0.0790 W/kg <b>SAR(1 g) = 0.048 W/kg; SAR(10 g) = 0.028 W/kg</b> Maximum value of SAR (measured) = 0.0544 W/kg</p>	
 <p>0 dB = 0.0544 W/kg = -12.64 dBW/kg</p>	

Right Side	Cheek
<p>Communication System: UID 10297 - AAA, LTE-FDD (SC-FDMA, 50% RB, 20 MHz, QPSK);                      Frequency: 1880 MHz; Duty Cycle: 1:3.81066                      Medium parameters used: <math>f = 1880 \text{ MHz}</math>; <math>\sigma = 1.45 \text{ S/m}</math>; <math>\epsilon_r = 39.74</math>; <math>\rho = 1000 \text{ kg/m}^3</math>                      Phantom section: Right Section</p> <p>DASY5 Configuration:</p> <ul style="list-style-type: none"> <li>Probe: ES3DV3 - SN3127; ConvF(5.15, 5.15, 5.15); Calibrated: 2016/8/29;</li> <li>Sensor-Surface: 4mm (Mechanical Surface Detection)</li> <li>Electronics: DAE4 Sn546; Calibrated: 2016/8/22</li> <li>Phantom: SAM 1559 classical; Type: QD000P40CC; Serial: TP:xxxx</li> <li>Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373)</li> </ul> <p><b>Head-Section HSL LTE band2 Right/LTE band2 20MHz 50RB Low HSL touch M/Area Scan (8x13x1):</b> Measurement grid: <math>dx=15\text{mm}</math>, <math>dy=15\text{mm}</math>                      Maximum value of SAR (measured) = 0.105 W/kg</p> <p><b>Head-Section HSL LTE band2 Right/LTE band2 20MHz 50RB Low HSL touch M/Zoom Scan (7x7x7)/Cube 0:</b> Measurement grid: <math>dx=5\text{mm}</math>, <math>dy=5\text{mm}</math>, <math>dz=5\text{mm}</math>                      Reference Value = 3.312 V/m; Power Drift = 0.11 dB                      Peak SAR (extrapolated) = 0.177 W/kg  <b>SAR(1 g) = 0.115 W/kg; SAR(10 g) = 0.073 W/kg</b>                      Maximum value of SAR (measured) = 0.124 W/kg</p> <div style="display: flex; align-items: flex-start;"> <div style="margin-right: 20px;"> <p><b>dB</b></p> <p>0 -2.82 -5.65 -8.47 -11.30 -14.12</p> </div> <div> </div> </div> <p style="text-align: center;">0 dB = 0.124 W/kg = -9.07 dBW/kg</p>	

Right Side	Tilt
<p>Communication System: UID 10297 - AAA, LTE-FDD (SC-FDMA, 50% RB, 20 MHz, QPSK); Frequency: 1880 MHz; Duty Cycle: 1:3.81066 Medium parameters used: <math>f = 1880</math> MHz; <math>\sigma = 1.45</math> S/m; <math>\epsilon_r = 39.74</math>; <math>\rho = 1000</math> kg/m<sup>3</sup> Phantom section: Right Section</p> <p>DASY5 Configuration:</p> <ul style="list-style-type: none"> <li>Probe: ES3DV3 - SN3127; ConvF(5.15, 5.15, 5.15); Calibrated: 2016/8/29;</li> <li>Sensor-Surface: 4mm (Mechanical Surface Detection)</li> <li>Electronics: DAE4 Sn546; Calibrated: 2016/8/22</li> <li>Phantom: SAM 1559 classical; Type: QD000P40CC; Serial: TP:xxxx</li> <li>Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373)</li> </ul> <p><b>Head-Section HSL LTE band2 Right/LTE band2 20MHz 50RB Low HSL tilt M/Area Scan (8x13x1):</b> Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (measured) = 0.0453 W/kg</p> <p><b>Head-Section HSL LTE band2 Right/LTE band2 20MHz 50RB Low HSL tilt M/Zoom Scan (7x7x7)/Cube 0:</b> Measurement grid: dx=5mm, dy=5mm, dz=5mm Reference Value = 4.519 V/m; Power Drift = 0.05 dB Peak SAR (extrapolated) = 0.0730 W/kg <b>SAR(1 g) = 0.043 W/kg; SAR(10 g) = 0.025 W/kg</b> Maximum value of SAR (measured) = 0.0477 W/kg</p> <div data-bbox="279 1243 1305 1697"> </div> <p>0 dB = 0.0477 W/kg = -13.21 dBW/kg</p>	

**LTE (Band 2 20BW-50%RB-Low/Flat)**

FLAT	Towards phantom
------	-----------------

Communication System: UID 0, LTE band 2 (0); Frequency: 1880 MHz; Duty Cycle: 1:1  
Medium parameters used:  $f = 1880 \text{ MHz}$ ;  $\sigma = 1.57 \text{ S/m}$ ;  $\epsilon_r = 51.14$ ;  $\rho = 1000 \text{ kg/m}^3$   
Phantom section: Flat Section

**DASY5 Configuration:**

- Probe: ES3DV3 - SN3127; ConvF(4.9, 4.9, 4.9); Calibrated: 2016/8/29;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn546; Calibrated: 2016/8/22
- Phantom: Twin-SAM 1560; Type: QD 000 P40 CD; Serial: 1560
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373)

**Flat-Section MSL LTE band2 TP/LTE band2 TP 20MHz 50RB M 10mm/Area Scan (9x13x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$

Maximum value of SAR (measured) = 0.296 W/kg


**Flat-Section MSL LTE band2 TP/LTE band2 TP 20MHz 50RB M 10mm/Zoom Scan (7x7x7)/Cube 0:** Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=5\text{mm}$

Reference Value = 6.535 V/m; Power Drift = 0.01 dB


Peak SAR (extrapolated) = 0.467 W/kg

**SAR(1 g) = 0.287 W/kg; SAR(10 g) = 0.170 W/kg**

Maximum value of SAR (measured) = 0.322 W/kg



0 dB = 0.322 W/kg = -4.92 dBW/kg

FLAT	Towards ground
Communication System: UID 0, LTE band 2 (0); Frequency: 1880 MHz;Duty Cycle: 1:1 Medium parameters used: $f = 1880 \text{ MHz}$ ; $\sigma = 1.57 \text{ S/m}$ ; $\epsilon_r = 51.14$ ; $\rho = 1000 \text{ kg/m}^3$ Phantom section: Flat Section	
DASY5 Configuration:	
<ul style="list-style-type: none"> <li>Probe: ES3DV3 - SN3127; ConvF(4.9, 4.9, 4.9); Calibrated: 2016/8/29;</li> <li>Sensor-Surface: 4mm (Mechanical Surface Detection)</li> <li>Electronics: DAE4 Sn546; Calibrated: 2016/8/22</li> <li>Phantom: Twin-SAM 1560; Type: QD 000 P40 CD; Serial: 1560</li> <li>Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373)</li> </ul> <p><b>Flat-Section MSL LTE band2 TG/LTE band2 TG 20MHz 50RB M 10mm/Area Scan (9x13x1):</b> Measurement grid: <math>dx=15\text{mm}</math>, <math>dy=15\text{mm}</math>            Maximum value of SAR (measured) = 0.782 W/kg</p> <p><b>Flat-Section MSL LTE band2 TG/LTE band2 TG 20MHz 50RB M 10mm/Zoom Scan (7x7x7)/Cube 0:</b> Measurement grid: <math>dx=5\text{mm}</math>, <math>dy=5\text{mm}</math>, <math>dz=5\text{mm}</math>            Reference Value = 6.914 V/m; Power Drift = -0.10 dB            Peak SAR (extrapolated) = 1.31 W/kg  <b>SAR(1 g) = 0.740 W/kg; SAR(10 g) = 0.390 W/kg</b>            Maximum value of SAR (measured) = 0.866 W/kg</p>	
 <p>0 dB = 0.866 W/kg = -0.62 dBW/kg</p>	


FLAT	EDGE2
------	-------




Communication System: UID 0, LTE band 2 (0); Frequency: 1880 MHz; Duty Cycle: 1:1  
 Medium parameters used:  $f = 1880$  MHz;  $\sigma = 1.57$  S/m;  $\epsilon_r = 51.14$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
 Phantom section: Flat Section

DASY5 Configuration:


- Probe: ES3DV3 - SN3127; ConvF(4.9, 4.9, 4.9); Calibrated: 2016/8/29;
  - Sensor-Surface: 4mm (Mechanical Surface Detection)
  - Electronics: DAE4 Sn546; Calibrated: 2016/8/22
  - Phantom: Twin-SAM 1560; Type: QD 000 P40 CD; Serial: 1560
  - Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373)
- Flat-Section MSL LTE band2 HOT/LTE band2 20MHz 50RB 10mm M edge 2/Area Scan (6x11x1):** Measurement grid: dx=15mm, dy=15mm  
 Maximum value of SAR (measured) = 0.407 W/kg
- Flat-Section MSL LTE band2 HOT/LTE band2 20MHz 50RB 10mm M edge 2/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm  
 Reference Value = 17.64 V/m; Power Drift = 0.11 dB  
 Peak SAR (extrapolated) = 0.783 W/kg  
**SAR(1 g) = 0.477 W/kg; SAR(10 g) = 0.267 W/kg**  
 Maximum value of SAR (measured) = 0.527 W/kg




0 dB = 0.527 W/kg = -2.78 dBW/kg


FLAT	EDGE3
Communication System: UID 0, LTE band 2 (0); Frequency: 1880 MHz; Duty Cycle: 1:1 Medium parameters used: $f = 1880 \text{ MHz}$ ; $\sigma = 1.57 \text{ S/m}$ ; $\epsilon_r = 51.14$ ; $\rho = 1000 \text{ kg/m}^3$ Phantom section: Flat Section	
DASY5 Configuration: <ul style="list-style-type: none"> <li>Probe: ES3DV3 - SN3127; ConvF(4.9, 4.9, 4.9); Calibrated: 2016/8/29;</li> <li>Sensor-Surface: 4mm (Mechanical Surface Detection)</li> <li>Electronics: DAE4 Sn546; Calibrated: 2016/8/22</li> <li>Phantom: Twin-SAM 1560; Type: QD 000 P40 CD; Serial: 1560</li> <li>Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373)</li> </ul> <p><b>Flat-Section MSL LTE band2 HOT/LTE band2 20MHz 50RB 10mm M edge 3/Area Scan (6x11x1):</b> Measurement grid: <math>dx=15\text{mm}</math>, <math>dy=15\text{mm}</math>                      Maximum value of SAR (measured) = 0.130 W/kg</p> <p><b>Flat-Section MSL LTE band2 HOT/LTE band2 20MHz 50RB 10mm M edge 3/Zoom Scan (7x7x7)/Cube 0:</b> Measurement grid: <math>dx=5\text{mm}</math>, <math>dy=5\text{mm}</math>, <math>dz=5\text{mm}</math>                      Reference Value = 4.180 V/m; Power Drift = 0.02 dB                      Peak SAR (extrapolated) = 0.215 W/kg  <b>SAR(1 g) = 0.135 W/kg; SAR(10 g) = 0.082 W/kg</b>                      Maximum value of SAR (measured) = 0.147 W/kg</p>  <p style="text-align: center;">0 dB = 0.147 W/kg = -8.33 dBW/kg</p>	




FLAT	EDGE4
<p>Communication System: UID 0, LTE band 2 (0); Frequency: 1880 MHz;Duty Cycle: 1:1 Medium parameters used: f = 1880 MHz; <math>\sigma = 1.57</math> S/m; <math>\epsilon_r = 51.14</math>; <math>\rho = 1000</math> kg/m<sup>3</sup> Phantom section: Flat Section</p>	
<p>DASY5 Configuration:</p>	
<ul style="list-style-type: none"> <li>Probe: ES3DV3 - SN3127; ConvF(4.9, 4.9, 4.9); Calibrated: 2016/8/29;</li> <li>Sensor-Surface: 4mm (Mechanical Surface Detection)</li> <li>Electronics: DAE4 Sn546; Calibrated: 2016/8/22</li> <li>Phantom: Twin-SAM 1560; Type: QD 000 P40 CD; Serial: 1560</li> <li>Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373)</li> </ul> <p><b>Flat-Section MSL LTE band2 HOT/LTE band2 20MHz 50RB 10mm M edge 4/Area Scan (6x11x1):</b> Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (measured) = 0.131 W/kg</p> <p><b>Flat-Section MSL LTE band2 HOT/LTE band2 20MHz 50RB 10mm M edge 4/Zoom Scan (7x7x7)/Cube 0:</b> Measurement grid: dx=5mm, dy=5mm, dz=5mm Reference Value = 4.151 V/m; Power Drift = 0.14 dB Peak SAR (extrapolated) = 0.212 W/kg <b>SAR(1 g) = 0.134 W/kg; SAR(10 g) = 0.081 W/kg</b> Maximum value of SAR (measured) = 0.146 W/kg</p>	
 <p>0 dB = 0.146 W/kg = -8.36 dBW/kg</p>	

**LTE (Band 4 20BW-1RB-Low /Head)**


Left Side	Cheek
<p>Communication System: UID 0, FDD-LTE(QPSK_20M_1RB_low) (0); Communication System Band: BAND 4; Frequency: 1732.5 MHz; Communication System PAR: 0 dB                      Medium parameters used : <math>f = 1732.5 \text{ MHz}</math>; <math>\sigma = 1.374 \text{ S/m}</math>; <math>\epsilon_r = 39.262</math>; <math>\rho = 1000 \text{ kg/m}^3</math>                      Phantom section: Left Section                      Measurement Standard: DASYS5 (IEEE1528-2013)                      DASYS5 Configuration:</p> <ul style="list-style-type: none"> <li>• Probe: ES3DV3 - SN3297; ConvF(5.22, 5.22, 5.22); Calibrated: 14/10/2016;</li> <li>• Sensor-Surface: 3mm (Mechanical Surface Detection)</li> <li>• Electronics: DAE4 Sn1226; Calibrated: 28/09/2016</li> <li>• Phantom: SAM2; Type: SAM; Serial: TP-1575</li> <li>• Measurement SW: DASYS52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)</li> <li>• <b>left/touch mid/Area Scan (91x161x1)</b>: Interpolated grid: dx=1.000 mm, dy=1.000 mm.</li> </ul> <p>Maximum value of SAR = 0.240 W/kg  <b>left/touch mid/Zoom Scan (7x7x7)/Cube 0</b>: Measurement grid: dx=5mm, dy=5mm, dz=5mm                      Reference Value = 4.883 V/m; Power Drift = -0.07 dB                      Peak SAR (extrapolated) = 0.336 W/kg  <b>SAR(1 g) = 0.196 W/kg; SAR(10 g) = 0.114 W/kg</b>                      Maximum value of SAR (measured) = 0.239 W/kg</p>	
 <p>0 dB = 0.240 W/kg = -6.20 dBW/kg</p>	

Left Side	Tilt
<p>Communication System: UID 0, FDD-LTE(QPSK_20M_1RB_low) (0); Communication System Band: BAND 4; Frequency: 1732.5 MHz; Communication System PAR: 0 dB Medium parameters used : f = 1732.5 MHz; <math>\sigma = 1.374</math> S/m; <math>\epsilon_r = 39.262</math>; <math>\rho = 1000</math> kg/m<sup>3</sup> Phantom section: Left Section Measurement Standard: DASYS5 (IEEE1528-2013) DASY5 Configuration:</p> <ul style="list-style-type: none"> <li>Probe: ES3DV3 - SN3297; ConvF(5.22, 5.22, 5.22); Calibrated: 14/10/2016;</li> <li>Sensor-Surface: 3mm (Mechanical Surface Detection)</li> <li>Electronics: DAE4 Sn1226; Calibrated: 28/09/2016</li> <li>Phantom: SAM2; Type: SAM; Serial: TP-1575</li> <li>Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)</li> <li><b>left/tilt mid/Area Scan (91x161x1):</b> Interpolated grid: dx=1.000 mm, dy=1.000 mm Maximum value of SAR = 0.0955 W/kg <b>left/tilt mid/Zoom Scan (7x7x7)/Cube 0:</b> Measurement grid: dx=5mm, dy=5mm, dz=5mm Reference Value = 2.968 V/m; Power Drift = 0.02 dB Peak SAR (extrapolated) = 0.184 W/kg <b>SAR(1 g) = 0.0754 W/kg; SAR(10 g) = 0.0408 W/kg</b> Maximum value of SAR (measured) = 0.0952 W/kg</li> </ul>	
	
<p>0 dB = 0.0955 W/kg = -10.20 dBW/kg</p>	


Right Side	Cheek
<p>Communication System: UID 0, FDD-LTE(QPSK_20M_1RB_low) (0); Communication System Band: BAND 4; Frequency: 1732.5 MHz; Communication System PAR: 0 dB Medium parameters used: <math>f = 1732.5</math> MHz; <math>\sigma = 1.374</math> S/m; <math>\epsilon_r = 39.262</math>; <math>\rho = 1000</math> kg/m<sup>3</sup> Phantom section: Right Section Measurement Standard: DASYS5 (IEEE1528-2013) DASY5 Configuration:</p> <ul style="list-style-type: none"> <li>• Probe: ES3DV3 - SN3297; ConvF(5.22, 5.22, 5.22); Calibrated: 14/10/2016;</li> <li>• Sensor-Surface: 3mm (Mechanical Surface Detection)</li> <li>• Electronics: DAE4 Sn1226; Calibrated: 28/09/2016</li> <li>• Phantom: SAM2; Type: SAM; Serial: TP-1575</li> <li>• Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)</li> </ul> <p>• <b>right/touch mid/Area Scan (91x161x1):</b> Interpolated grid: dx=1.000 mm, dy=1.000 mm Maximum value of SAR = 0.209 W/kg <b>right/touch mid/Zoom Scan (7x7x7)/Cube 0:</b> Measurement grid: dx=5mm, dy=5mm, dz=5mm Reference Value = 5.027 V/m; Power Drift = 0.08 dB Peak SAR (extrapolated) = 0.277 W/kg <b>SAR(1 g) = 0.184 W/kg; SAR(10 g) = 0.116 W/kg</b> Maximum value of SAR (measured) = 0.216 W/kg</p> <div data-bbox="252 1256 1334 1713"> </div>	

Right Side	Tilt
<p>Communication System: UID 0, FDD-LTE(QPSK_20M_1RB_low) (0); Communication System Band: BAND 4; Frequency: 1732.5 MHz; Communication System PAR: 0 dB Medium parameters used: <math>f = 1732.5</math> MHz; <math>\sigma = 1.374</math> S/m; <math>\epsilon_r = 39.262</math>; <math>\rho = 1000</math> kg/m<sup>3</sup> Phantom section: Right Section Measurement Standard: DASYS5 (IEEE1528-2013) DASY5 Configuration:</p> <ul style="list-style-type: none"> <li>Probe: ES3DV3 - SN3297; ConvF(5.22, 5.22, 5.22); Calibrated: 14/10/2016;</li> <li>Sensor-Surface: 3mm (Mechanical Surface Detection)</li> <li>Electronics: DAE4 Sn1226; Calibrated: 28/09/2016</li> <li>Phantom: SAM2; Type: SAM; Serial: TP-1575</li> <li>Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)</li> </ul> <p><b>right/tilt mid/Area Scan (91x161x1):</b> Interpolated grid: dx=1.000 mm, dy=1.000 mm Maximum value of SAR = 0.0780 W/kg <b>right/tilt mid/ Zoom Scan (7x7x7)/Cube 0:</b> Measurement grid: dx=5mm, dy=5mm, dz=5mm Reference Value = 4.534 V/m; Power Drift = -0.01 dB Peak SAR (extrapolated) = 0.231 W/kg <b>SAR(1 g) = 0.0618 W/kg; SAR(10 g) = 0.0365 W/kg</b> Maximum value of SAR (measured) = 0.0723 W/kg</p>  <p>0 dB = 0.0780 W/kg = -11.08 dBW/kg</p>	

**LTE (Band 4 20BW-1RB-Low/Flat)**

FLAT	Towards phantom
<p>Communication System: UID 0, FDD-LTE(QPSK_20M_1RB) (0); Communication System Band: BAND 4; Frequency: 1732.5 MHz; Communication System PAR: 0 dB            Medium parameters used (interpolated): <math>f = 1732.5</math> MHz; <math>\sigma = 1.496</math> S/m; <math>\epsilon_r = 51.908</math>; <math>\rho = 1000</math> kg/m<sup>3</sup>            Phantom section: Flat Section            Measurement Standard: DASYS5 (IEEE1528-2013)            DASYS5 Configuration:</p> <ul style="list-style-type: none"> <li>Probe: EX3DV4 - SN3717; ConvF(7.63, 7.63, 7.63); Calibrated: 19/10/2016;</li> <li>Sensor-Surface: 1.4mm (Mechanical Surface Detection)</li> <li>Electronics: DAE4 Sn1327; Calibrated: 15/04/2016</li> <li>Phantom: SAM 1; Type: SAM; Serial: TP:1702</li> <li>Measurement SW: DASYS52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)</li> </ul> <p><b>body/towards phantom mid/Area Scan (91x161x1):</b> Interpolated grid: dx=1.000 mm, dy=1.000 mm            Maximum value of SAR (interpolated) = 0.521 W/kg  <b>body/towards phantom mid/Zoom Scan (7x7x7)/Cube 0:</b> Measurement grid: dx=5mm, dy=5mm, dz=5mm            Reference Value = 9.190 V/m; Power Drift = 0.13 dB            Peak SAR (extrapolated) = 0.588 W/kg  <b>SAR(1 g) = 0.370 W/kg; SAR(10 g) = 0.227 W/kg</b>            Maximum value of SAR (measured) = 0.511 W/kg</p>	
	




FLAT	Towards ground
<p>Communication System: UID 0, FDD-LTE(QPSK_20M_1RB) (0); Communication System Band: BAND 4; Frequency: 1732.5 MHz; Communication System PAR: 0 dB            Medium parameters used (interpolated): <math>f = 1732.5</math> MHz; <math>\sigma = 1.496</math> S/m; <math>\epsilon_r = 51.908</math>; <math>\rho = 1000</math> kg/m<sup>3</sup>            Phantom section: Flat Section            Measurement Standard: DASY5 (IEEE1528-2013)            DASY5 Configuration:</p> <ul style="list-style-type: none"> <li>• Probe: EX3DV4 - SN3717; ConvF(7.63, 7.63, 7.63); Calibrated: 19/10/2016;</li> <li>• Sensor-Surface: 1.4mm (Mechanical Surface Detection)</li> <li>• Electronics: DAE4 Sn1327; Calibrated: 15/04/2016</li> <li>• Phantom: SAM 1; Type: SAM; Serial: TP:1702</li> <li>• Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)</li> </ul> <p><b>body/towards ground mid/Area Scan (91x161x1):</b> Interpolated grid: dx=1.000 mm, dy=1.000 mm            Maximum value of SAR (interpolated) = 0.721 W/kg  <b>body/towards ground mid/Zoom Scan (7x7x7)/Cube 0:</b> Measurement grid: dx=5mm, dy=5mm, dz=5mm            Reference Value = 8.885 V/m; Power Drift = 0.12 dB            Peak SAR (extrapolated) = 0.856 W/kg  <b>SAR(1 g) = 0.492 W/kg; SAR(10 g) = 0.290 W/kg</b>            Maximum value of SAR (measured) = 0.727 W/kg</p>	
 <p>0 dB = 0.721 W/kg = -1.42 dBW/kg</p>	

FLAT	EDGE 2
<p>Communication System: UID 0, FDD-LTE(QPSK_20M_1RB) (0); Communication System Band: BAND 4; Frequency: 1732.5 MHz; Communication System PAR: 0 dB            Medium parameters used (interpolated): <math>f = 1732.5</math> MHz; <math>\sigma = 1.496</math> S/m; <math>\epsilon_r = 51.908</math>; <math>\rho = 1000</math> kg/m<sup>3</sup>            Phantom section: Flat Section            Measurement Standard: DASY5 (IEEE1528-2013)            DASY5 Configuration:</p> <ul style="list-style-type: none"> <li>Probe: EX3DV4 - SN3717; ConvF(7.63, 7.63, 7.63); Calibrated: 19/10/2016;</li> <li>Sensor-Surface: 1.4mm (Mechanical Surface Detection)</li> <li>Electronics: DAE4 Sn1327; Calibrated: 15/04/2016</li> <li>Phantom: SAM 1; Type: SAM; Serial: TP:1702</li> <li>Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)</li> </ul> <p><b>body/edge 2 mid/Area Scan (61x101x1):</b> Interpolated grid: dx=1.000 mm, dy=1.000 mm            Maximum value of SAR (interpolated) = 0.474 W/kg  <b>body/edge 2 mid/ Zoom Scan (7x7x7)/Cube 0:</b> Measurement grid: dx=5mm, dy=5mm, dz=5mm            Reference Value = 12.590 V/m; Power Drift = 0.01 dB            Peak SAR (extrapolated) = 0.598 W/kg            SAR(1 g) = 0.320 W/kg; SAR(10 g) = 0.178 W/kg            Maximum value of SAR (measured) = 0.418 W/kg</p> <div style="display: flex; align-items: center;"> <div style="margin-right: 20px;"> <p style="text-align: center;">dB</p> <p style="text-align: center;">0 -2.34 -4.68 -7.02 -9.36 -11.70</p> </div> <div> </div> </div> <p style="text-align: center;">0 dB = 0.474 W/kg = -3.24 dBW/kg</p>	



FLAT	EDGE 3
<p>Communication System: UID 0, FDD-LTE(QPSK_20M_1RB) (0); Communication System Band: BAND 4; Frequency: 1732.5 MHz; Communication System PAR: 0 dB Medium parameters used (interpolated): <math>f = 1732.5</math> MHz; <math>\sigma = 1.496</math> S/m; <math>\epsilon_r = 51.908</math>; <math>\rho = 1000</math> kg/m<sup>3</sup> Phantom section: Flat Section Measurement Standard: DASYS5 (IEEE1528-2013) DASY5 Configuration:</p> <ul style="list-style-type: none"> <li>Probe: EX3DV4 - SN3717; ConvF(7.63, 7.63, 7.63); Calibrated: 19/10/2016;</li> <li>Sensor-Surface: 1.4mm (Mechanical Surface Detection)</li> <li>Electronics: DAE4 Sn1327; Calibrated: 15/04/2016</li> <li>Phantom: SAM 1; Type: SAM; Serial: TP:1702</li> <li>Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)</li> </ul> <p><b>body2/edge3 mid/Area Scan (61x161x1):</b> Interpolated grid: dx=1.000 mm, dy=1.000 mm Maximum value of SAR (interpolated) = 0.170 W/kg <b>body2/edge3 mid/ Zoom Scan (7x7x7)/Cube 0:</b> Measurement grid: dx=5mm, dy=5mm, dz=5mm</p> <ul style="list-style-type: none"> <li>Reference Value = 6.144 V/m; Power Drift = 0.11 dB Peak SAR (extrapolated) = 0.288 W/kg <b>SAR(1 g) = 0.120 W/kg; SAR(10 g) = 0.0706 W/kg</b> Maximum value of SAR (measured) = 0.166 W/kg</li> </ul> <div data-bbox="279 1126 1313 1579"> </div> <p>0 dB = 0.170 W/kg = -7.69 dBW/kg</p>	


FLAT	EDGE 4
<p>Communication System: UID 0, FDD-LTE(QPSK_20M_1RB) (0); Communication System Band: BAND 4; Frequency: 1732.5 MHz; Communication System PAR: 0 dB                      Medium parameters used (interpolated): <math>f = 1732.5</math> MHz; <math>\sigma = 1.496</math> S/m; <math>\epsilon_r = 51.908</math>; <math>\rho = 1000</math> kg/m<sup>3</sup>                      Phantom section: Flat Section                      Measurement Standard: DASYS5 (IEEE1528-2013)                      DASYS5 Configuration:</p> <ul style="list-style-type: none"> <li>Probe: EX3DV4 - SN3717; ConvF(7.63, 7.63, 7.63); Calibrated: 19/10/2016;</li> <li>Sensor-Surface: 1.4mm (Mechanical Surface Detection)</li> <li>Electronics: DAE4 Sn1327; Calibrated: 15/04/2016</li> <li>Phantom: SAM 1; Type: SAM; Serial: TP:1702</li> <li>Measurement SW: DASYS52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)</li> </ul> <p><b>body2/edge4 mid/Area Scan (61x161x1):</b> Interpolated grid: dx=1.000 mm, dy=1.000 mm                      Maximum value of SAR (interpolated) = 0.194 W/kg  <b>body2/edge4 mid/ Zoom Scan (7x7x7)/Cube 0:</b> Measurement grid: dx=5mm, dy=5mm, dz=5mm</p> <ul style="list-style-type: none"> <li>Reference Value = 5.324 V/m; Power Drift = 0.12 dB                      Peak SAR (extrapolated) = 0.322 W/kg  <b>SAR(1 g) = 0.139 W/kg; SAR(10 g) = 0.0823 W/kg</b>                      Maximum value of SAR (measured) = 0.182 W/kg</li> </ul>	
 <p style="text-align: center;">0 dB = 0.194 W/kg = -7.12 dBW/kg</p>	

**LTE (Band 4 20BW-50%RB-Low /Head)**

Left Side	Cheek
<p>Communication System: UID 0, FDD-LTE(QPSK_20M_50RB_low) (0); Communication System Band: BAND 4; Frequency: 1732.5 MHz; Communication System PAR: 0 dB            Medium parameters used: <math>f = 1732.5</math> MHz; <math>\sigma = 1.374</math> S/m; <math>\epsilon_r = 39.262</math>; <math>\rho = 1000</math> kg/m<sup>3</sup>            Phantom section: Left Section            Measurement Standard: DASYS5 (IEEE1528-2013)            DASYS5 Configuration:</p> <ul style="list-style-type: none"> <li>• Probe: ES3DV3 - SN3297; ConvF(5.22, 5.22, 5.22); Calibrated: 14/10/2016;</li> <li>• Sensor-Surface: 3mm (Mechanical Surface Detection)</li> <li>• Electronics: DAE4 Sn1226; Calibrated: 28/09/2016</li> <li>• Phantom: SAM2; Type: SAM; Serial: TP-1575</li> <li>• Measurement SW: DASYS52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)</li> <li>• <b>left/touch mid 50RB_low/Area Scan (91x161x1):</b> Interpolated grid: dx=1.000 mm, dy=1.000 mm.</li> </ul> <p>Maximum value of SAR = 0.217 W/kg  <b>left/touch mid 50RB_low/Zoom Scan (7x7x7)/Cube 0:</b> Measurement grid: dx=5mm, dy=5mm, dz=5mm            Reference Value = 4.756 V/m; Power Drift = 0.03 dB            Peak SAR (extrapolated) = 0.364 W/kg  <b>SAR(1 g) = 0.173 W/kg; SAR(10 g) = 0.0996 W/kg</b>            Maximum value of SAR (measured) = 0.205 W/kg</p> <div data-bbox="272 1144 1310 1597"> </div> <p>0 dB = 0.217 W/kg = -6.64 dBW/kg</p>	

Left Side	Tilt
<p>Communication System: UID 0, FDD-LTE(QPSK_20M_50RB_low) (0); Communication System Band: BAND 4; Frequency: 1732.5 MHz; Communication System PAR: 0 dB Medium parameters used: <math>f = 1732.5</math> MHz; <math>\sigma = 1.374</math> S/m; <math>\epsilon_r = 39.262</math>; <math>\rho = 1000</math> kg/m<sup>3</sup> Phantom section: Left Section Measurement Standard: DASYS5 (IEEE1528-2013) DASY5 Configuration:</p> <ul style="list-style-type: none"> <li>Probe: ES3DV3 - SN3297; ConvF(5.22, 5.22, 5.22); Calibrated: 14/10/2016;</li> <li>Sensor-Surface: 3mm (Mechanical Surface Detection)</li> <li>Electronics: DAE4 Sn1226; Calibrated: 28/09/2016</li> <li>Phantom: SAM2; Type: SAM; Serial: TP-1575</li> <li>Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)</li> <li><b>left/tilt mid 50RB_low/Area Scan (91x161x1):</b> Interpolated grid: dx=1.000 mm, dy=1.000 mm Maximum value of SAR = 0.0758 W/kg</li> <li><b>left/tilt mid 50RB_low/Zoom Scan (7x7x7)/Cube 0:</b> Measurement grid: dx=5mm, dy=5mm, dz=5mm Reference Value = 2.931 V/m; Power Drift = 0.13 dB Peak SAR (extrapolated) = 0.179 W/kg <b>SAR(1 g) = 0.0607 W/kg; SAR(10 g) = 0.0333 W/kg.</b> Maximum value of SAR (measured) = 0.0754 W/kg</li> </ul> <div data-bbox="272 1106 1310 1563"> </div> <p>0 dB = 0.0758 W/kg = -11.20 dBW/kg</p>	


Right Side	Cheek
<p>Communication System: UID 0, FDD-LTE(QPSK_20M_50RB_low) (0); Communication System Band: BAND 4; Frequency: 1732.5 MHz; Communication System PAR: 0 dB                      Medium parameters used: <math>f = 1732.5</math> MHz; <math>\sigma = 1.374</math> S/m; <math>\epsilon_r = 39.262</math>; <math>\rho = 1000</math> kg/m<sup>3</sup>                      Phantom section: Right Section                      Measurement Standard: DASYS5 (IEEE1528-2013)                      DASYS5 Configuration:</p> <ul style="list-style-type: none"> <li>Probe: ES3DV3 - SN3297; ConvF(5.22, 5.22, 5.22); Calibrated: 14/10/2016;</li> <li>Sensor-Surface: 3mm (Mechanical Surface Detection)</li> <li>Electronics: DAE4 Sn1226; Calibrated: 28/09/2016</li> <li>Phantom: SAM2; Type: SAM; Serial: TP-1575</li> <li>Measurement SW: DASYS52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)</li> <li><b>right/touch mid 50RB_low/Area Scan (91x161x1):</b> Interpolated grid: dx=1.000 mm, dy=1.000 mm.</li> </ul> <p>Maximum value of SAR = 0.213 W/kg  <b>right/touch mid 50RB_low/Zoom Scan (7x7x7)/Cube 0:</b> Measurement grid: dx=5mm, dy=5mm, dz=5mm                      Reference Value = 6.324 V/m; Power Drift = 0.09 dB                      Peak SAR (extrapolated) = 0.375 W/kg  <b>SAR(1 g) = 0.174 W/kg; SAR(10 g) = 0.105 W/kg</b>                      Maximum value of SAR (measured) = 0.201 W/kg</p> <div style="display: flex; align-items: flex-start;"> <div style="margin-right: 10px;"> <p>dB</p> <p>0 -10.00 -20.00 -30.00 -40.00 -50.00</p> </div> <div> </div> </div> <p style="text-align: center;">0 dB = 0.213 W/kg = -6.72 dBW/kg</p>	

Right Side	Tilt
<p>Communication System: UID 0, FDD-LTE(QPSK_20M_50RB_low) (0); Communication System Band: BAND 4; Frequency: 1732.5 MHz; Communication System PAR: 0 dB Medium parameters used : f = 1732.5 MHz; <math>\sigma = 1.374</math> S/m; <math>\epsilon_r = 39.262</math>; <math>\rho = 1000</math> kg/m<sup>3</sup> Phantom section: Right Section Measurement Standard: DASYS5 (IEEE1528-2013) DASY5 Configuration:</p> <ul style="list-style-type: none"> <li>• Probe: ES3DV3 - SN3297; ConvF(5.22, 5.22, 5.22); Calibrated: 14/10/2016;</li> <li>• Sensor-Surface: 3mm (Mechanical Surface Detection)</li> <li>• Electronics: DAE4 Sn1226; Calibrated: 28/09/2016</li> <li>• Phantom: SAM2; Type: SAM; Serial: TP-1575</li> <li>• Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)</li> <li>• <b>right/tilt mid 50RB_low/Area Scan (91x161x1):</b> Interpolated grid: dx=1.000 mm, dy=1.000 mm.</li> </ul> <p>Maximum value of SAR = 0.0729 W/kg <b>right/tilt mid 50RB_low/ Zoom Scan (7x7x7)/Cube 0:</b> Measurement grid: dx=5mm, dy=5mm, dz=5mm Reference Value = 4.067 V/m; Power Drift = 0.05 dB Peak SAR (extrapolated) = 0.218 W/kg <b>SAR(1 g) = 0.0591 W/kg; SAR(10 g) = 0.0345 W/kg.</b> Maximum value of SAR (measured) = 0.0705 W/kg</p>  <p>0 dB = 0.0729 W/kg = -11.37 dBW/kg</p>	




**LTE (Band 4 20BW-50%RB-Low/Flat)**

FLAT	Towards phantom
<p>Communication System: UID 0, FDD-LTE(QPSK_20M_50RB) (0); Communication System Band: BAND 4; Frequency: 1732.5 MHz; Communication System PAR: 0 dB</p>	
<p>Medium parameters used (interpolated): <math>f = 1732.5</math> MHz; <math>\sigma = 1.496</math> S/m; <math>\epsilon_r = 51.908</math>; <math>\rho = 1000</math> kg/m<sup>3</sup></p>	
<p>Phantom section: Flat Section</p>	
<p>Measurement Standard: DASYS5 (IEEE1528-2013)</p>	
<p>DASY5 Configuration:</p>	
<ul style="list-style-type: none"> <li>Probe: EX3DV4 - SN3717; ConvF(7.63, 7.63, 7.63); Calibrated: 19/10/2016;</li> </ul>	
<ul style="list-style-type: none"> <li>Sensor-Surface: 1.4mm (Mechanical Surface Detection)</li> </ul>	
<ul style="list-style-type: none"> <li>Electronics: DAE4 Sn1327; Calibrated: 15/04/2016</li> </ul>	
<ul style="list-style-type: none"> <li>Phantom: SAM 1; Type: SAM; Serial: TP:1702</li> </ul>	
<ul style="list-style-type: none"> <li>Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)</li> </ul>	
<p><b>body/towards phantom mid 50%RB/Area Scan (91x161x1):</b> Interpolated grid: dx=1.000 mm, dy=1.000 mm</p>	
<p>Maximum value of SAR (interpolated) = 0.399 W/kg</p>	
<p><b>body/towards phantom mid 50%RB/Zoom Scan (7x7x7)/Cube 0:</b> Measurement grid: dx=5mm, dy=5mm, dz=5mm</p>	
<p>Reference Value = 7.614 V/m; Power Drift = 0.08 dB</p>	
<p>Peak SAR (extrapolated) = 0.455 W/kg</p>	
<p><b>SAR(1 g) = 0.285 W/kg; SAR(10 g) = 0.173 W/kg</b></p>	
<p>Maximum value of SAR (measured) = 0.395 W/kg</p>	

FLAT	Towards ground
<p>Communication System: UID 0, FDD-LTE(QPSK_20M_50RB) (0); Communication System Band: BAND 4; Frequency: 1732.5 MHz; Communication System PAR: 0 dB            Medium parameters used (interpolated): <math>f = 1732.5</math> MHz; <math>\sigma = 1.496</math> S/m; <math>\epsilon_r = 51.908</math>; <math>\rho = 1000</math> kg/m<sup>3</sup>            Phantom section: Flat Section            Measurement Standard: DASY5 (IEEE1528-2013)            DASY5 Configuration:</p> <ul style="list-style-type: none"> <li>Probe: EX3DV4 - SN3717; ConvF(7.63, 7.63, 7.63); Calibrated: 19/10/2016;</li> <li>Sensor-Surface: 1.4mm (Mechanical Surface Detection)</li> <li>Electronics: DAE4 Sn1327; Calibrated: 15/04/2016</li> <li>Phantom: SAM 1; Type: SAM; Serial: TP:1702</li> <li>Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)</li> </ul> <p><b>body/towards ground mid 50%RB/Area Scan (91x161x1):</b> Interpolated grid: dx=1.000 mm, dy=1.000 mm            Maximum value of SAR (interpolated) = 0.600 W/kg  <b>body/towards ground mid 50%RB/ Zoom Scan (7x7x7)/Cube 0:</b> Measurement grid: dx=5mm, dy=5mm, dz=5mm</p> <ul style="list-style-type: none"> <li>Reference Value = 7.711 V/m; Power Drift = -0.03 dB            Peak SAR (extrapolated) = 0.788 W/kg  <b>SAR(1 g) = 0.418 W/kg; SAR(10 g) = 0.240 W/kg</b>            Maximum value of SAR (measured) = 0.563 W/kg</li> </ul>	
 <p style="text-align: center;">0 dB = 0.600 W/kg = -2.22 dBW/kg</p>	



**LTE (Band 4 15BW-1RB-Low /Head)**

Left Side	Cheek
<p>Communication System: UID 0, FDD-LTE(QPSK_15M_1RB_low) (0); Communication System Band: BAND4; Frequency: 1732.5 MHz; Communication System PAR: 0 dB                      Medium parameters used: <math>f = 1732.5</math> MHz; <math>\sigma = 1.374</math> S/m; <math>\epsilon_r = 39.262</math>; <math>\rho = 1000</math> kg/m<sup>3</sup>                      Phantom section: Left Section                      Measurement Standard: DASYS5 (IEEE1528-2013)                      DASYS5 Configuration:</p> <ul style="list-style-type: none"> <li>• Probe: ES3DV3 - SN3297; ConvF(5.22, 5.22, 5.22); Calibrated: 14/10/2016;</li> <li>• Sensor-Surface: 3mm (Mechanical Surface Detection)</li> <li>• Electronics: DAE4 Sn1226; Calibrated: 28/09/2016</li> <li>• Phantom: SAM2; Type: SAM; Serial: TP-1575</li> <li>• Measurement SW: DASYS52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)</li> <li>• <b>left/touch mid 15M/Area Scan (91x161x1):</b> Interpolated grid: dx=1.000 mm, dy=1.000 mm                      Maximum value of SAR = 0.221 W/kg  <b>left/touch mid 15M/ Zoom Scan (7x7x7)/Cube 0:</b> Measurement grid: dx=5mm, dy=5mm, dz=5mm                      Reference Value = 6.745 V/m; Power Drift = 0.08 dB                      Peak SAR (extrapolated) = 0.421 W/kg  <b>SAR(1 g) = 0.178 W/kg; SAR(10 g) = 0.104 W/kg.</b>                      Maximum value of SAR (measured) = 0.213 W/kg</li> </ul>	
 <p style="text-align: center;">0 dB = 0.221 W/kg = -6.56 dBW/kg</p>	