

<b>Prüfbericht-Nr.:</b> <i>Test report no.:</i>	<b>CN239IAV 002</b>	<b>Auftrags-Nr.:</b> <i>Order no.:</i>	168413420	Seite 1 von 23 <i>Page 1 of 23</i>
<b>Kunden-Referenz-Nr.:</b> <i>Client reference no.:</i>	N/A	<b>Auftragsdatum:</b> <i>Order date:</i>	2023-02-07	
<b>Auftraggeber:</b> <i>Client:</i>	SZ DJI TECHNOLOGY CO., LTD. Lobby of T2, DJI Sky City, No. 53 Xianyuan Road, Xili Community, Xili Street, Nanshan District, Shenzhen, China			
<b>Prüfgegenstand:</b> <i>Test item:</i>	Matrice 350 RTK			
<b>Bezeichnung / Typ-Nr.:</b> <i>Identification / Type no.:</i>	M350 RTK (Trademark: DJI)			
<b>Auftrags-Inhalt:</b> <i>Order content:</i>	Test Report			
<b>Prüfgrundlage:</b> <i>Test specification:</i>	CFR47 FCC Part 15: Subpart C Section 15.247 CFR47 FCC Part 15: Subpart C Section 15.209			
<b>Wareneingangsdatum:</b> <i>Date of sample receipt:</i>	2023-02-23	Please refer to photo documents		
<b>Prüfmuster-Nr.:</b> <i>Test sample no.:</i>	A003417729-004 A003419622-002			
<b>Prüfzeitraum:</b> <i>Testing period:</i>	2023-03-09 - 2023-03-28			
<b>Ort der Prüfung:</b> <i>Place of testing:</i>	TÜV Rheinland (Shenzhen) Co., Ltd.			
<b>Prüflaboratorium:</b> <i>Testing laboratory:</i>	TÜV Rheinland (Shenzhen) Co., Ltd.			
<b>Prüfergebnis*:</b> <i>Test result*:</i>	Pass			
<b>geprüft von:</b> <i>tested by:</i>		<b>genehmigt von:</b> <i>authorized by:</i>		
<b>Datum:</b> <i>Date:</i>	2023-04-20 <small>Signed by: Breeze Jiang</small>	<b>Ausstellungsdatum:</b> <i>Issue date:</i>	2023-04-20 <small>Signed by: Lin Lin</small>	
<b>Stellung / Position:</b>	Sachverständige(r)/Expert	<b>Stellung / Position:</b>	Sachverständige(r)/Expert	
<b>Sonstiges /</b> <i>Other:</i>	FCC ID: SS3-M3502301 This report is for 2.4GHz SDR.			
<b>Zustand des Prüfgegenstandes bei Anlieferung:</b> <i>Condition of the test item at delivery:</i>	Prüfmuster vollständig und unbeschädigt <i>Test item complete and undamaged</i>			
<small>* Legende:</small>	<small>P(ass) = entspricht o.g. Prüfgrundlage(n)</small>	<small>F(ail) = entspricht nicht o.g. Prüfgrundlage(n)</small>	<small>N/A = nicht anwendbar</small>	<small>N/T = nicht getestet</small>
<small>* Legend:</small>	<small>P(ass) = passed a.m. test specification(s)</small>	<small>F(ail) = failed a.m. test specification(s)</small>	<small>N/A = not applicable</small>	<small>N/T = not tested</small>
<b>Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens.</b> <i>This test report only relates to the above mentioned test sample. Without permission of the test center this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any test mark.</i>				

V05

## **Test Summary**

**5.1.1 ANTENNA REQUIREMENT**

*RESULT: Pass*

**5.1.2 MAXIMUM PEAK CONDUCTED OUTPUT POWER**

*RESULT: Pass*

**5.1.3 CONDUCTED POWER SPECTRAL DENSITY**

*RESULT: Pass*

**5.1.4 6DB BANDWIDTH**

*RESULT: Pass*

**5.1.5 99% BANDWIDTH**

*RESULT: Pass*

**5.1.6 CONDUCTED SPURIOUS EMISSIONS MEASURED IN 100 KHZ BANDWIDTH**

*RESULT: Pass*

**5.1.7 RADIATED SPURIOUS EMISSION**

*RESULT: Pass*

## Contents

<b>1</b>	<b>GENERAL REMARKS .....</b>	<b>4</b>
<b>1.1</b>	<b>COMPLEMENTARY MATERIALS .....</b>	<b>4</b>
<b>2</b>	<b>TEST SITES .....</b>	<b>5</b>
<b>2.1</b>	<b>TEST FACILITIES .....</b>	<b>5</b>
<b>2.2</b>	<b>LIST OF TEST AND MEASUREMENT INSTRUMENTS.....</b>	<b>5</b>
<b>2.3</b>	<b>TRACEABILITY .....</b>	<b>6</b>
<b>2.4</b>	<b>CALIBRATION .....</b>	<b>6</b>
<b>2.5</b>	<b>MEASUREMENT UNCERTAINTY.....</b>	<b>6</b>
<b>2.6</b>	<b>LOCATION OF ORIGINAL DATA.....</b>	<b>6</b>
<b>2.7</b>	<b>STATUS OF FACILITY USED FOR TESTING.....</b>	<b>6</b>
<b>3</b>	<b>GENERAL PRODUCT INFORMATION .....</b>	<b>7</b>
<b>3.1</b>	<b>PRODUCT FUNCTION AND INTENDED USE.....</b>	<b>7</b>
<b>3.2</b>	<b>RATINGS AND SYSTEM DETAILS .....</b>	<b>7</b>
<b>3.3</b>	<b>INDEPENDENT OPERATION MODES .....</b>	<b>11</b>
<b>3.4</b>	<b>NOISE GENERATING AND NOISE SUPPRESSING PARTS .....</b>	<b>11</b>
<b>3.5</b>	<b>SUBMITTED DOCUMENTS.....</b>	<b>11</b>
<b>4</b>	<b>TEST SET-UP AND OPERATION MODES .....</b>	<b>12</b>
<b>4.1</b>	<b>PRINCIPLE OF CONFIGURATION SELECTION .....</b>	<b>12</b>
<b>4.2</b>	<b>TEST OPERATION AND TEST SOFTWARE .....</b>	<b>12</b>
<b>4.3</b>	<b>SPECIAL ACCESSORIES AND AUXILIARY EQUIPMENT .....</b>	<b>12</b>
<b>4.4</b>	<b>COUNTERMEASURES TO ACHIEVE EMC COMPLIANCE .....</b>	<b>12</b>
<b>4.5</b>	<b>TEST SETUP DIAGRAM .....</b>	<b>13</b>
<b>5</b>	<b>TEST RESULTS .....</b>	<b>14</b>
<b>5.1</b>	<b>TRANSMITTER REQUIREMENT &amp; TEST SUITES .....</b>	<b>14</b>
<b>5.1.1</b>	<i>Antenna Requirement .....</i>	<i>14</i>
<b>5.1.2</b>	<i>Maximum Peak Conducted Output Power .....</i>	<i>15</i>
<b>5.1.3</b>	<i>Conducted Power Spectral Density .....</i>	<i>18</i>
<b>5.1.4</b>	<i>6dB Bandwidth .....</i>	<i>19</i>
<b>5.1.5</b>	<i>99% Bandwidth .....</i>	<i>20</i>
<b>5.1.6</b>	<i>Conducted Spurious Emissions Measured in 100 kHz Bandwidth .....</i>	<i>21</i>
<b>5.1.7</b>	<i>Radiated Spurious Emission .....</i>	<i>22</i>
<b>6</b>	<b>PHOTOGRAPHS OF THE TEST SET-UP .....</b>	<b>23</b>
<b>7</b>	<b>LIST OF TABLES.....</b>	<b>23</b>

# 1 General Remarks

## 1.1 Complementary Materials

All attachments are integral parts of this test report. This applies especially to the following appendix:

Appendix A: Test Results of 2.4GHz SDR

Appendix B: Photographs of the Test Set-up

## 2 Test Sites

### 2.1 Test Facilities

**TÜV Rheinland (Shenzhen) Co., Ltd.**

362 Huanguan Road Middle Longhua District, Shenzhen 518110 People's Republic of China

FCC Registration No.: 694916

ISED wireless device testing laboratory: 25069

A2LA Certificate Number: 5162.01

### 2.2 List of Test and Measurement Instruments

**Table 1: List of Test and Measurement Equipment**

<b>Radio Spectrum Testing (SRD-Tonscend)</b>				
<b>Equipment</b>	<b>Manufacturer</b>	<b>Model</b>	<b>Serial No.</b>	<b>Cal. until</b>
EXA Signal Analyzer, Multi-touch	Keysight	N9010B	MY60241175	2023-10-10
MXG X-Series RF Vector Signal Generator	Keysight	N5182B	MY61250137	2023-10-10
EXG X-Series Microwave Analog Signal Generator	Keysight	N5173B	MY61250141	2023-10-10
DC power supply	Keysight	E3642A	MY61276100	2023-10-10
Power Control Unit	Tonscend	JS0806-4ADC	N/A	2023-10-10
Automation Control Unit	Tonscend	JS0806-2	21C8060396	2023-10-10
Test Software	Tonscend	JS1120-3	N/A	N/A
Control PC	Lenovo	TianYi510S-071MB	Y LX23JMF	N/A
Shielding Room 8#	Albatross	SR8	APC17151-SR8	2024-06-22
<b>Unwanted Emission Testing (TS9975)</b>				
<b>Equipment</b>	<b>Manufacturer</b>	<b>Model</b>	<b>Serial No.</b>	<b>Cal. until</b>
EMI Test Receiver	R&S	ESR 7	102021	2023-08-02
Signal Analyzer	R&S	FSV 40	101439	2023-08-01
System Controller Interface	R&S	SCI-100	S10010038	N/A
Filterbank	R&S	Wlan	100759	2023-08-01
OSP	R&S	OSP 120	102040	N/A
Pre-amplifier	R&S	SCU08F1	08320031	2023-08-02
Amplifier	R&S	SCU-18F	180070	2023-08-02
Amplifier	R&S	SCU40A	100475	2023-08-02
Trilog Broadband Antenna (30 MHz - 7 GHz)	Schwarzbeck	VULB 9162	193	2024-08-06
Double-Ridged Antenna (1 -18 GHz)	ETS-LINDGREN	3117	00218717	2024-08-06
Wideband Ridged Horn Antenna (18-40 GHz)	Steatite	QMS-00880	19067	2024-08-27
Active Loop Antenna	Schwarzbeck	FMZB 1513	302	2023-08-06
Test software	R&S	EMC32 (V10.60.10)	N/A	N/A

Control PC	Dell	OptiPlex 7050	36NV9P2	N/A
3m Semi-Anechoic Chamber	Albatross	SAC-3m	APC17151-SAC	2024-06-22

## 2.3 Traceability

All measurement equipment calibrations are traceable to NIM (National Institute of Metrology) or where calibration is performed in other countries, to equivalent nationally recognized standards organizations.

## 2.4 Calibration

Equipment requiring calibration is calibrated periodically by the manufacturer or according to manufacturer's specifications. Additionally all equipment is verified for proper performance on a regular basis using in house standards or comparisons.

## 2.5 Measurement Uncertainty

The estimated combined standard uncertainty for radiated emissions and conducted emissions measurements as below table.

Parameter	Uncertainty
RF output power, conducted	± 0.99 dB
Occupied Channel Bandwidth	± 2.08 %
RF power density, conducted	± 0.99 dB
Unwanted Emissions, conducted	± 0.89 dB
Radiated Emission of Transmitter, valid up to 26.5 GHz	± 4.17 dB
Radiated Emission of Receiver, valid up to 26.5 GHz	± 4.17 dB

## 2.6 Location of Original Data

The original copies of all test data taken during actual testing were attached at Appendix A & B of this report and delivered to the applicant. A copy has been retained in the TÜV Rheinland (Shenzhen) Co., Ltd. file for certification follow-up purposes.

## 2.7 Status of Facility Used for Testing

The TÜV Rheinland (Shenzhen) Co., Ltd. Test facility located at 362 Huanguan Road Middle Longhua District, Shenzhen 518110 People's Republic of China is listed on the US Federal Communications Commission list of facilities approved to perform measurements.

## 3 General Product Information

### 3.1 Product Function and Intended Use

The EUT (Equipment Under Test) is an Aircraft. It supports 2.4GHz SDR, 5.2GHz SDR, 5.8GHz SDR, GNSS and ADS-B functions.

\*remark: SDR means specific defined radio, and cannot changes radio specification via software/firmware by end-users.

For details refer to the User Manual, Technical Description and Circuit Diagram.

### 3.2 Ratings and System Details

**Table 2: Technical Specification of EUT**

General Information of EUT	Value
Kind of Equipment	Matrice 350 RTK
Type Designation	M350 RTK
Trademark	DJI
Operating Temperature Range	-20 °C ~ +50 °C
Operating Voltage	Battery operated (DC 44.76V@5880mAh, Li-ion battery)
Testing Voltage	Fully charged battery
Radiofrequency operating mode	1) 2.4GHz SDR: operating within 2400-2483.5MHz, supports 1.4MHz/3MHz/10MHz/20MHz/40MHz Bandwidth 2) 5.2GHz SDR: operating within 5150-5250MHz, supports 10MHz/20MHz/40MHz Bandwidth 3) 5.8GHz SDR: operating within 5725-5850MHz, supports 1.4MHz/3MHz/10MHz/20MHz/40MHz Bandwidth 4) G GPS & BDS & Galileo & Glonass (receiver): operating within 1559-1610MHz 5) ADS-B (receiver): operating at 978MHz (1MHz Bandwidth) and 1090MHz (2MHz Bandwidth)
<b>Technical Specification of 2.4GHz SDR</b>	
Operating Frequency	2403.5-2469.5MHz for 1.4MHz Bandwidth 2405.12-2471.12MHz for 1.4MHz Bandwidth (CA mode) 2405.5-2468.5MHz for 3MHz Bandwidth 2408.2-2471.2MHz for 3MHz Bandwidth (CA mode) 2407.5-2467.5MHz for 10MHz Bandwidth 2412.5-2462.5MHz for 20MHz Bandwidth 2422.5-2452.5MHz for 40MHz Bandwidth
Type of Modulation	OFDM (QPSK, 16QAM, 64QAM)
Channel Number	34 channels for 1.4MHz Bandwidth 34 channels for 1.4MHz Bandwidth (CA mode) 22 channels for 3MHz Bandwidth 22 channels for 3MHz Bandwidth (CA mode) 61 channels for 10MHz Bandwidth 51 channels for 20MHz Bandwidth 31 channels for 40MHz Bandwidth
Channel Separation	2MHz for 1.4MHz Bandwidth

	2MHz for 1.4MHz Bandwidth (CA mode) 3MHz for 3MHz Bandwidth 3MHz for 3MHz Bandwidth (CA mode) 1MHz for 10MHz Bandwidth 1MHz for 20MHz Bandwidth 1MHz for 40MHz Bandwidth
Antenna Type	Integral Antenna
Antenna Number	1Tx4Rx for SISO mode (ANT0 or ANT1 or ANT2 or ANT3) 2Tx4Rx for MIMO mode (ANT0+ANT1 or ANT0+ANT3 or ANT2+ANT1 or ANT2+ANT3), Un-correlated signals.
Antenna Gain	4.0dBi for ANT0 4.0dBi for ANT1 4.5dBi for ANT2 4.5dBi for ANT3
The type of wideband data transmission equipment	Non-FHSS

**Table 3: RF Channel and Frequency of 2.4GHz SDR**

2.4GHz 1.4MHz Bandwidth (2403.5MHz-2469.5MHz)			
RF Channel	Frequency (MHz)	RF Channel	Frequency (MHz)
1	2403.5	18	2437.5
2	2405.5	19	2439.5
3	2407.5	20	2441.5
4	2409.5	21	2443.5
5	2411.5	22	2445.5
6	2413.5	23	2447.5
7	2415.5	24	2449.5
8	2417.5	25	2451.5
9	2419.5	26	2453.5
10	2421.5	27	2455.5
11	2423.5	28	2457.5
12	2425.5	29	2459.5
13	2427.5	30	2461.5
14	2429.5	31	2463.5
15	2431.5	32	2465.5
16	2433.5	33	2467.5
17	2435.5	34	2469.5

2.4GHz 1.4MHz Bandwidth (CA Mode) (2405.12MHz-2471.12MHz)			
RF Channel	Frequency (MHz)	RF Channel	Frequency (MHz)
1	2405.12	18	2439.12
2	2407.12	19	2441.12
3	2409.12	20	2443.12
4	2411.12	21	2445.12



5	2413.12	22	2447.12
6	2415.12	23	2449.12
7	2417.12	24	2451.12
8	2419.12	25	2453.12
9	2421.12	26	2455.12
10	2423.12	27	2457.12
11	2425.12	28	2459.12
12	2427.12	29	2461.12
13	2429.12	30	2463.12
14	2431.12	31	2465.12
15	2433.12	32	2467.12
16	2435.12	33	2469.12
17	2437.12	34	2471.12

**2.4GHz 3MHz Bandwidth  
(2405.5MHz-2468.5MHz)**

RF Channel	Frequency (MHz)	RF Channel	Frequency (MHz)
1	2405.5	12	2438.5
2	2408.5	13	2441.5
3	2411.5	14	2444.5
4	2414.5	15	2447.5
5	2417.5	16	2450.5
6	2420.5	17	2453.5
7	2423.5	18	2456.5
8	2426.5	19	2459.5
9	2429.5	20	2462.5
10	2432.5	21	2465.5
11	2435.5	22	2468.5

**2.4GHz 3MHz Bandwidth (CA mode)  
(2408.2MHz-2471.2MHz)**

RF Channel	Frequency (MHz)	RF Channel	Frequency (MHz)
1	2408.2	12	2441.2
2	2411.2	13	2444.2
3	2414.2	14	2447.2
4	2417.2	15	2450.2
5	2420.2	16	2453.2
6	2423.2	17	2456.2
7	2426.2	18	2459.2
8	2429.2	19	2462.2
9	2432.2	20	2465.2
10	2435.2	21	2468.2
11	2438.2	22	2471.2

2.4GHz 10MHz Bandwidth (2407.5MHz-2467.5MHz)							
RF Channel	Frequency (MHz)	RF Channel	Frequency (MHz)	RF Channel	Frequency (MHz)	RF Channel	Frequency (MHz)
1	2407.5	17	2423.5	33	2439.5	49	2455.5
2	2408.5	18	2424.5	34	2440.5	50	2456.5
3	2409.5	19	2425.5	35	2441.5	51	2457.5
4	2410.5	20	2426.5	36	2442.5	52	2458.5
5	2411.5	21	2427.5	37	2443.5	53	2459.5
6	2412.5	22	2428.5	38	2444.5	54	2460.5
7	2413.5	23	2429.5	39	2445.5	55	2461.5
8	2414.5	24	2430.5	40	2446.5	56	2462.5
9	2415.5	25	2431.5	41	2447.5	57	2463.5
10	2416.5	26	2432.5	42	2448.5	58	2464.5
11	2417.5	27	2433.5	43	2449.5	59	2465.5
12	2418.5	28	2434.5	44	2450.5	60	2466.5
13	2419.5	29	2435.5	45	2451.5	61	2467.5
14	2420.5	30	2436.5	46	2452.5		
15	2421.5	31	2437.5	47	2453.5		
16	2422.5	32	2438.5	48	2454.5		

2.4GHz 20MHz Bandwidth (2412.5MHz-2462.5MHz)					
RF Channel	Frequency (MHz)	RF Channel	Frequency (MHz)	RF Channel	Frequency (MHz)
1	2412.5	18	2429.5	35	2446.5
2	2413.5	19	2430.5	36	2447.5
3	2414.5	20	2431.5	37	2448.5
4	2415.5	21	2432.5	38	2449.5
5	2416.5	22	2433.5	39	2450.5
6	2417.5	23	2434.5	40	2451.5
7	2418.5	24	2435.5	41	2452.5
8	2419.5	25	2436.5	42	2453.5
9	2420.5	26	2437.5	43	2454.5
10	2421.5	27	2438.5	44	2455.5
11	2422.5	28	2439.5	45	2456.5
12	2423.5	29	2440.5	46	2457.5
13	2424.5	30	2441.5	47	2458.5
14	2425.5	31	2442.5	48	2459.5
15	2426.5	32	2443.5	49	2460.5
16	2427.5	33	2444.5	50	2461.5
17	2428.5	34	2445.5	51	2462.5

2.4GHz 40MHz Bandwidth (2422.5MHz-2452.5MHz)					
RF Channel	Frequency (MHz)	RF Channel	Frequency (MHz)	RF Channel	Frequency (MHz)
1	2422.5	12	2433.5	23	2444.5
2	2423.5	13	2434.5	24	2445.5
3	2424.5	14	2435.5	25	2446.5
4	2425.5	15	2436.5	26	2447.5
5	2426.5	16	2437.5	27	2448.5
6	2427.5	17	2438.5	28	2449.5
7	2428.5	18	2439.5	29	2450.5
8	2429.5	19	2440.5	30	2451.5
9	2430.5	20	2441.5	31	2452.5
10	2431.5	21	2442.5		
11	2432.5	22	2443.5		

### 3.3 Independent Operation Modes

The basic operation modes are:

- A. On, 2.4GHz SDR wireless transmitting mode
  - 1) Low Channel
  - 2) Middle Channel
  - 3) High Channel
- B. On, Normal Operation
- C. Off

### 3.4 Noise Generating and Noise Suppressing Parts

Refer to Circuit Diagram for further details.

### 3.5 Submitted Documents

- Circuit Diagram
- Bill of Material
- Instruction Manual
- Rating Label

## 4 Test Set-up and Operation Modes

### 4.1 Principle of Configuration Selection

**Radio Spectrum:** The equipment under test (EUT) was configured at its highest power output in order to measure its highest possible radiation and conducted level. The test modes were adapted accordingly in reference to the instructions for use.

**Emission:** The equipment under test (EUT) was configured to measure its highest possible radiation level. The test modes were adapted accordingly in reference to the instructions for use.

### 4.2 Test Operation and Test Software

Test operation refers to test setup in chapter 5. All tests were performed according to the procedures in ANSI C63.10: 2013.

According to clause 3.1, all tests were performed on model M350 RTK in this report.

*Note: All testing were carried out on SISO mode and MIMO mode, but only the worst case(Ant0+3) was presented in this report.*

### 4.3 Special Accessories and Auxiliary Equipment

Table 4: Auxiliary Equipment Used during Test

Description	Manufacturer	Model	S/N
Laptop	Lenovo	T480	PF-16A6N8

### 4.4 Countermeasures to Achieve EMC Compliance

The test sample which has been tested contained the noise suppression parts as described in the Technical Construction File (TCF).

No additional measures were employed to achieve compliance.

### 4.5 Test Setup Diagram

Diagram of Measurement Configuration for Radiation Test (Below 1GHz)




Diagram of Measurement Configuration for Radiation Test (Above 1GHz)





Diagram of Measurement Configuration for Conducted Transmitter Measurement



## 5 Test Results

### 5.1 Transmitter Requirement & Test Suites

#### 5.1.1 Antenna Requirement

**RESULT:****Pass****Test Specification**

Test standard : FCC Part 15.247(b)(4) and Part 15.203

According to the manufacturer declared, the EUT has Integral antennas, the maximum antenna gain of SISO is 4.5dBi for 2.4GHz SDR, the maximum uncorrelated antenna gain of MIMO is 4.26dBi for 2.4GHz SDR, and the antenna connector is designed unique, prefer to EUT photos for details.

Therefore the EUT is considered sufficient to comply with the provision.

## 5.1.2 Maximum Conducted Output Power

**RESULT:****Pass****Test Specification**

Test standard	: FCC Part 15.247(b)(3)
Basic standard	: ANSI C63.10: 2013
Limits	: 1.0 Watts
Kind of test site	: Shielded Room

**Test Setup**

Date of testing	: 2023-03-09 to 2023-03-14
Input voltage	: Full Battery
Operation mode	: A
Test channel	: Low / Middle / High
Ambient temperature	: 23 °C
Relative humidity	: 47 %
Atmospheric pressure	: 101 kPa

For details refer to following test result.

**Table 5: Test Result of Maximum Conducted Output Power**

Worst case for SISO mode (Ant 0)

Test Mode	Test Channel (MHz)	Measured Average Power		Limit (W)
		(dBm)	(W)	
1.4MHz BW	2403.5	17.56	0.0570	< 1.0
	2435.5	17.69	0.0587	
	2469.5	17.28	0.0535	
1.4MHz BW CA	2405.12	17.65	0.0582	
	2437.12	17.76	0.0597	
	2471.12	17.30	0.0537	
3MHz BW	2405.5	17.20	0.0525	
	2435.5	17.77	0.0598	
	2468.5	17.36	0.0545	
3MHz BW CA	2408.2	17.25	0.0531	
	2438.2	17.79	0.0601	
	2471.2	17.30	0.0537	
10MHz BW	2407.5	24.09	0.2564	
	2410.5	26.15	0.4121	
	2437.5	<b>27.21</b>	<b>0.5260</b>	
	2450.5	26.31	0.4276	
	2460.5	25.37	0.3443	
	2463.5	24.49	0.2812	
	2465.5	23.65	0.2317	
2467.5	22.61	0.1824		
20MHz BW	2412.5	23.01	0.2000	
	2417.5	24.78	0.3006	
	2424.5	24.89	0.3083	
	2425.5	26.21	0.4178	
	2437.5	27.20	0.5248	
	2450.5	25.31	0.3396	
	2455.5	23.87	0.2438	
	2458.5	22.07	0.1611	
2462.5	20.09	0.1021		
40MHz BW	2422.5	20.36	0.1086	
	2427.5	21.75	0.1496	
	2428.5	22.21	0.1663	
	2430.5	23.13	0.2056	
	2431.5	24.34	0.2716	
	2437.5	26.09	0.4064	
	2442.5	23.58	0.2280	
	2446.5	21.16	0.1306	
	2449.5	20.53	0.1130	
	2452.5	18.39	0.0690	

Max. e.i.r.p.=27.21dBm+4.0dBi=31.21dBm, which is less than 36dBm=4W.

Note:

- 1) The cable loss is taken into account in results.
- 2) Antenna gain(G) of 2.4GHz SDR: 4.0dBi (Ant 0)



Worst case for MIMO mode (Ant 0+3)

Test Mode	Test Channel (MHz)	Measured Average Power		Limit (W)
		(dBm)	(W)	
1.4MHz BW	2403.5	17.31	0.0538	< 1.0
	2435.5	17.55	0.0569	
	2469.5	17.61	0.0577	
1.4MHz BW CA	2405.12	17.28	0.0535	
	2437.12	17.81	0.0604	
	2471.12	17.85	0.0610	
3MHz BW	2405.5	17.65	0.0582	
	2435.5	17.83	0.0607	
	2468.5	17.97	0.0627	
3MHz BW CA	2408.2	17.59	0.0574	
	2438.2	17.64	0.0581	
	2471.2	17.78	0.0600	
10MHz BW	2407.5	24.43	0.2773	
	2410.5	26.09	0.4064	
	2437.5	<b>27.50</b>	<b>0.5623</b>	
	2463.5	24.94	0.3119	
	2465.5	24.20	0.2630	
	2467.5	22.86	0.1932	
20MHz BW	2412.5	23.26	0.2118	
	2415.5	24.01	0.2518	
	2417.5	25.13	0.3258	
	2437.5	27.42	0.5521	
	2450.5	25.65	0.3673	
	2455.5	24.33	0.2710	
	2458.5	21.84	0.1528	
	2462.5	20.43	0.1104	
40MHz BW	2422.5	20.58	0.1143	
	2427.5	22.01	0.1589	
	2428.5	22.77	0.1892	
	2430.5	23.78	0.2388	
	2431.5	25.07	0.3214	
	2437.5	26.19	0.4159	
	2442.5	23.86	0.2432	
	2446.5	21.70	0.1479	
	2449.5	20.20	0.1047	
	2452.5	18.59	0.0723	

Max. e.i.r.p.=27.50dBm+4.26dBi=31.76dBm, which is less than 36dBm=4W.

Note:

- 1) The cable loss is taken into account in results.
- 2) Antenna gain(G) of 2.4GHz SDR: 4.26dBi (uncorrelated antenna gain MIMO)

### 5.1.3 Conducted Power Spectral Density

**RESULT:****Pass****Test Specification**

Test standard	: FCC Part 15.247(e)
Basic standard	: ANSI C63.10: 2013
Limits	: < 8 dBm / 3kHz
Kind of test site	: Shielded Room

**Test Setup**

Date of testing	: 2023-03-09 to 2023-03-14
Input voltage	: Full Battery
Operation mode	: A
Test channel	: Low / Middle / High
Ambient temperature	: 23 °C
Relative humidity	: 47 %
Atmospheric pressure	: 101 kPa

For the measurement records, refer to the appendix A.

### 5.1.4 6dB Bandwidth

**RESULT:****Pass****Test Specification**

Test standard	:	FCC Part 15.247(a)(2)
Basic standard	:	ANSI C63.10: 2013
Limits	:	> 500 KHz
Kind of test site	:	Shielded Room

**Test Setup**

Date of testing	:	2023-03-09 to 2023-03-14
Input voltage	:	Full Battery
Operation mode	:	A
Test channel	:	Low / Middle / High
Ambient temperature	:	23 °C
Relative humidity	:	47 %
Atmospheric pressure	:	101 kPa

For the measurement records, refer to the appendix A.

**Prüfbericht - Nr.: CN239IAV 002**

Test Report No.:

Seite 20 von 23

Page 20 of 23

### 5.1.5 99% Bandwidth

**RESULT:****Pass****Test Specification**

Test standard : FCC Part 15.247(a)  
Basic standard : ANSI C63.10: 2013  
Kind of test site : Shielded Room

**Test Setup**

Date of testing : 2023-03-09 to 2023-03-14  
Input voltage : Full Battery  
Operation mode : A  
Test channel : Low / Middle / High  
Ambient temperature : 23 °C  
Relative humidity : 47 %  
Atmospheric pressure : 101 kPa

For the measurement records, refer to the appendix A.

## 5.1.6 Conducted Spurious Emissions Measured in 100 kHz Bandwidth

**RESULT:****Pass****Test Specification**

Test standard	: FCC Part 15.247(d)
Basic standard	: ANSI C63.10: 2013
Limits	: 20dB (below that in the 100kHz bandwidth within the band that contains the highest level of the desired power); In addition, radiated emissions which fall in the restricted bands, must also comply with the radiated emission limits specified in 15.209(a)
Kind of test site	: Shielded Room

**Test Setup**

Date of testing	: 2023-03-09 to 2023-03-14
Input voltage	: Full Battery
Operation mode	: A
Test channel	: Low / Middle / High
Ambient temperature	: 23 °C
Relative humidity	: 47 %
Atmospheric pressure	: 101 kPa

Test results of 100kHz Bandwidth of Frequency Band Edge by Conducted method refer to test plots, and compliance is achieved as well.

For the measurement records, refer to the appendix A.

## 5.1.7 Radiated Spurious Emission

**RESULT:****Pass****Test Specification**

Test standard	:	FCC Part 15.247(d) & FCC Part 15.205
Basic standard	:	ANSI C63.10: 2013
Limits	:	Refer to 15.209(a) of FCC part 15.247(d)
Kind of test site	:	3m Semi-anechoic Chamber

**Test Setup**

Date of testing	:	2023-03-23 to 2023-03-28
Input voltage	:	Full Battery
Operation mode	:	A
Test channel	:	Low / Middle / High
Ambient temperature	:	Refer to test result
Relative humidity	:	Refer to test result
Atmospheric pressure	:	101 kPa

**Remark:**

Testing was carried out within frequency range 9kHz to the tenth harmonics. Only the worst case spurious emissions configuration of the each mode were reported.

For the measurement records, refer to the appendix A.

## 6 Photographs of the Test Set-Up

For photographs of the test set-up, refer to the appendix B.

## 7 List of Tables

Table 1: List of Test and Measurement Equipment.....	5
Table 2: Technical Specification of EUT .....	7
Table 3: RF Channel and Frequency of 2.4GHz SDR.....	8
Table 4: Auxiliary Equipment Used during Test .....	12
Table 5: Test Result of Maximum Peak Conducted Output Power.....	16