

Prüfbericht-Nr.: <i>Test report no.:</i>	CN22ROS3 003	Auftrags-Nr.: <i>Order no.:</i>	168341845	Seite 1 von 11 <i>Page 1 of 11</i>	
Kunden-Referenz-Nr.: <i>Client reference no.:</i>	N/A	Auftragsdatum: <i>Order date:</i>	2021-11-02		
Auftraggeber: <i>Client:</i>	SZ DJI TECHNOLOGY CO., LTD. 14th Floor, West Wing, Skyworth Semiconductor Design Building No.18 Gaoxin South 4th Ave Nanshan District, Shenzhen, P.R. China				
Prüfgegenstand: <i>Test item:</i>	DJI Mini 2				
Bezeichnung / Typ-Nr.: <i>Identification / Type no.:</i>	MT2WD				
Auftrags-Inhalt: <i>Order content:</i>	FCC and IC approval				
Prüfgrundlage: <i>Test specification:</i>	47 CFR FCC Part 2.1091		RSS-102 Issue 5		
Wareneingangsdatum: <i>Date of sample receipt:</i>	2022-01-11		Please refer to Photo Document		
Prüfmuster-Nr.: <i>Test sample no.:</i>	A003199792-008~011 A003199792-026~031				
Prüfzeitraum: <i>Testing period:</i>	2022-01-17 to 2022-01-28				
Ort der Prüfung: <i>Place of testing:</i>	TÜV Rheinland (Shenzhen) Co., Ltd.				
Prüflaboratorium: <i>Testing laboratory:</i>	TÜV Rheinland (Shenzhen) Co., Ltd.				
Prüfergebnis*: <i>Test result*:</i>	Pass				
geprüft von: <i>tested by:</i>	<u>X Bell Hu</u>		genehmigt von: <i>authorized by:</i>	<u>X Lin Lin</u>	
Datum: <i>Date:</i>	2022-03-28		Ausstellungsdatum: <i>Issue date:</i>	2022-03-28	
	<small>Signed by: Bell Hu</small>			<small>Signed by: Lin Lin</small>	
Stellung / Position:	Project Manager		Stellung / Position:	Reviewer	
Sonstiges / Other:	FCC ID: SS3-MT2WD2007, IC: 11805A-MT2WD2007, HVIN: MT2WD, PMN: DJI Mini 2				
Zustand des Prüfgegenstandes bei Anlieferung: <i>Condition of the test item at delivery:</i>	Prüfmuster vollständig und unbeschädigt <i>Test item complete and undamaged</i>				
* Legende:	1 = sehr gut	2 = gut	3 = befriedigend	4 = ausreichend	5 = mangelhaft
	P(ass) = entspricht o.g. Prüfgrundlage(n)	F(ail) = entspricht nicht o.g. Prüfgrundlage(n)	N/A = nicht anwendbar	N/T = nicht getestet	
* Legend:	1 = very good	2 = good	3 = satisfactory	4 = sufficient	5 = poor
	P(ass) = passed a.m. test specification(s)	F(ail) = failed a.m. test specification(s)	N/A = not applicable	N/T = not tested	
Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens. <i>This test report only relates to the a. m. test sample. Without permission of the test center this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any test mark.</i>					

V05

TEST SUMMARY

3.1.1 RF EXPOSURE COMPLIANCE

RESULT: Pass

CONTENTS

1.	TEST SITES.....	4
1.1	TEST FACILITIES	4
1.2	LIST OF TEST AND MEASUREMENT INSTRUMENTS	4
1.3	TRACEABILITY	4
1.4	CALIBRATION.....	4
1.5	LOCATION OF ORIGINAL DATA.....	4
1.6	STATUS OF FACILITY USED FOR TESTING	4
2.	GENERAL PRODUCT INFORMATION	5
2.1	GENERAL DESCRIPTION	5
2.2	RATING AND SYSTEM DETAILS	5
3.	TEST RESULTS	8
3.1	TRANSMITTER REQUIREMENTS & TEST SUITES.....	8
3.1.1	<i>RF Exposure Compliance.....</i>	<i>8</i>
3.1.1.1	FCC Part 1.1310, Part 2.1091	9
3.1.1.2	RSS-102 Exemption Limits for Routine Evaluation – RF Exposure Evaluation	10
4.	LIST OF TABLES.....	11

1. TEST SITES

1.1 TEST FACILITIES

TÜV Rheinland (Shenzhen) Co., Ltd.

Address: No. 362 Huanguan Road Middle, Longhua District, Shenzhen 518110, P.R. China

FCC Registration No.: 694916

ISED Wireless Device Testing Laboratory: 25069

1.2 LIST OF TEST AND MEASUREMENT INSTRUMENTS

Table 1: List of Test and Measurement Equipment

Radio Spectrum Testing				
Equipment	Manufacturer	Model	Serial No.	Cal. until
Wireless Connectivity Tester	R&S	CMW270	101375	2022-08-09
Signal Analyzer	R&S	FSV 40	101441	2022-08-09

1.3 Traceability

All measurement equipment calibrations are traceable to NIST or where calibration is performed outside the United States, to equivalent nationally recognized standards organizations.

1.4 Calibration

Equipment requiring calibration is calibrated periodically by the manufacturer or according to manufacturer's specifications. Additionally all equipment is verified for proper performance on a regular basis using in house standards or comparisons.

1.5 Location of Original Data

The original copies of all test data taken during actual testing were attached at Appendixes of this report and delivered to the applicant. A copy has been retained in the TÜV Rheinland (Shenzhen) file for certification follow-up purposes.

1.6 Status of Facility Used for Testing

The TÜV Rheinland (Shenzhen) Co., Ltd. facility located at No. 362 Huanguan Road Middle, Longhua District, Shenzhen 518110, P.R. China is listed on the US Federal Communications Commission list of facilities approved to perform measurements.

2. GENERAL PRODUCT INFORMATION

2.1 GENERAL DESCRIPTION

The EUT (**E**quipment **U**nder **T**est) is a DJI Mini 2. It supports Bluetooth, 2.4GHz SDR, 2.4GHz Wi-Fi, 5.8GHz Wi-Fi, 5.8GHz SDR and GNSS functions.

*remark: SDR means specific defined radio, and cannot changes radio specification via software/firmware by end-users.

Note: When the EUT is charged, other functions cannot be used.

For details refer to the User Manual, Technical Description and Circuit Diagram.

2.2 RATING AND SYSTEM DETAILS

Table 2: Rating of EUT

General Information of EUT	Value
Kind of Equipment:	DJI Mini 2
Type Designation	MT2WD
Operating Temperature Range	0 °C ~ 40 °C
Operating Voltage	AC 100-240V, 50/60Hz input via AC/DC adapter or Battery operated (Max 7.7V, 2250 mAh)
Testing Voltage	Full battery
Radiofrequency operating mode	1) Bluetooth: operating within 2400-2483.5MHz, Bluetooth BLE, 1Mbps&2Mbps 2) 2.4GHz SDR: operating within 2400-2483.5MHz, supports 1.4MHz/3MHz/10MHz/20MHz Bandwidth 3) 2.4GHz Wi-Fi: operating within 2400-2483.5MHz, supports 20MHz/40MHz Bandwidth and IEEE 802.11 b/g/n20/n40 4) 5.8GHz SDR: operating within 5725-5850MHz, supports 1.4MHz/3MHz/10MHz/20MHz Bandwidth 5) 5.8GHz Wi-Fi: operating within 5725-5850MHz, supports 20MHz/40MHz/80MHz Bandwidth and IEEE 802.11 a/n20/n40/ac20/ac40/ac80
Adapter	Model: QC18-US Input: 100-240V, 50/60Hz, 0.5A Output: 5V,3A / 9V,2A / 12V,1.5A

Table 3: Technical Specification of EUT

Technical Specification of Bluetooth	
Operating Frequency	2402-2480MHz
Type of Modulation	GFSK
Data Rate	1Mbps, 2Mbps
Channel Number	40 channels for Bluetooth BLE
Channel Separation	1MHz and 2MHz

Antenna Type	Integral Antenna
Antenna Number	1Tx1Rx
Antenna Gain	2.5 dBi
Technical Specification of 2.4GHz SDR	
Operating Frequency	2407.5-2465.5MHz for 1.4MHz Bandwidth 2409.12-2467.12MHz for 1.4MHz Bandwidth (CA mode) 2417.5-2456.5MHz for 3MHz Bandwidth 2405.5-2476.5MHz for 10MHz Bandwidth 2410.5-2472.5MHz for 20MHz Bandwidth
Type of Modulation	OFDM (QPSK, 16QAM, 64QAM)
Channel Number	30 channels for 1.4MHz Bandwidth 30 channels for 1.4MHz Bandwidth (CA mode) 14 channels for 3MHz Bandwidth 72 channels for 10MHz Bandwidth 63 channels for 20MHz Bandwidth
Channel Separation	2MHz for 1.4MHz Bandwidth 2MHz for 1.4MHz Bandwidth (CA mode) 3MHz for 3MHz Bandwidth 1MHz for 10MHz Bandwidth 1MHz for 20MHz Bandwidth
Antenna Type	Integral Antenna
Antenna Number	2 Antennas, only 1TX2RX mode supported.
Antenna Gain	2.5 dBi
Technical Specification of 2.4GHz Wi-Fi	
Operating Frequency	2412 - 2462MHz for 802.11b/g/n(HT20) 2422 - 2452MHz for 802.11n(HT40)
Type of Modulation	DSSS(DBPSK/DQPSK/CCK) OFDM(BPSK/QPSK/16QAM/64QAM)
Data Rate	1/2/5.5/11 Mbps for 802.11b 6/9/12/18/24/36/48/54 Mbps for 802.11g MCS0 ~ MCS7 for 802.11n
Channel Number	11 channels for 802.11b/g/n(HT20) 7 channels for 802.11n(HT40)
Channel Separation	5 MHz
Antenna Type	Integral Antenna
Antenna Number	1Tx1Rx
Antenna Gain	2.5 dBi
Technical Specification of 5.8GHz SDR	
Operating Frequency	5728.5-5844.5MHz for 1.4MHz Bandwidth 5730.12-5846.12MHz for 1.4MHz Bandwidth (CA mode) 5730.5-5844.5MHz for 3MHz Bandwidth 5732.5-5844.5MHz for 10MHz Bandwidth 5735.5-5839.5MHz for 20MHz Bandwidth
Type of Modulation	OFDM (QPSK, 16QAM, 64QAM)
Channel Number	59 channels for 1.4MHz Bandwidth 59 channels for 1.4MHz Bandwidth (CA mode) 39 channels for 3MHz Bandwidth 113 channels for 10MHz Bandwidth 105 channels for 20MHz Bandwidth

Channel Separation	2MHz for 1.4MHz Bandwidth 2MHz for 1.4MHz Bandwidth (CA mode) 3MHz for 3MHz Bandwidth 1MHz for 10MHz Bandwidth 1MHz for 20MHz Bandwidth
Antenna Type	Integral Antenna
Antenna Number	2 Antennas, only 1TX2RX mode supported.
Antenna Gain	3.5dBi
Technical Specification of 5.8GHz Wi-Fi	
Operating Frequency	5745–5825MHz for 802.11 a/n20/n40/ac20/ac40/ac80
Type of Modulation	OFDM(BPSK/QPSK/16QAM/64QAM/256QAM)
Data Rate	6/9/12/18/24/36/48/54 Mbps for 802.11a MCS 0 ~ MCS 7 for 802.11 n20/n40 VHT-MCS 0 ~ VHT-MCS 8 for 802.11 ac20 VHT-MCS 0 ~ VHT-MCS 9 for 802.11 ac40 VHT-MCS 0 ~ VHT-MCS 9 for 802.11 ac80
Channel Number	5 channels for 802.11a/n20/ac20 2 channels for 802.11n40/ac40 1 channels for 802.11ac80
Channel Separation	20MHz, 40MHz, 80MHz
Antenna Type	Integral Antenna
Antenna Number	1Tx1Rx
Antenna Gain	3.5dBi

3. Test Results

3.1 Transmitter Requirements & Test Suites

3.1.1 RF Exposure Compliance

RESULT:**Pass**

Test standard	:	RSS-102 Issue 5 FCC Part 1.1091
Limit	:	Table 1 of 47 CFR FCC Part 1.1310 Section 2.5.2 of RSS-102 Issue 5
Kind of test site	:	Shielded room

This device is mobile device, and the applicant declares that the minimum separation distance is greater than 20cm. Therefore MPE measurement or computational modelling should be used to determine compliance.

MPE Calculation is based on the conducted power, and considering maximum power and Antenna gain. The following formula is used to MPE evaluation.

$$Pd = \frac{P_{out} * G}{4R^2\pi}$$

Where

P_d = power density in mW/cm² or W/m²

P_{out} = output power to antenna in mW or W

G_{num} = Antenna gain in numeric

π = 3.14159

R = Distance between observation point and the center of radiator in cm or m

3.1.1.1 FCC Part 1.1310, Part 2.1091

According to ANSI/IEEE C95.1-1992, the criteria listed in Table 1 shall be used to evaluate the environmental impact of human exposure to radio frequency (RF) radiation as specified in §1.1310.

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3-3.0	614	1.63	*(100)	6
3.0-30	1842/f	4.89/f	*(900/f ²)	6
30-300	61.4	0.163	1.0	6
300-1500			f/300	6
1500-100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500			f/1500	30
1500-100,000			1.0	30

Table 4: Test Results of RF Exposure Calculations for FCC, stand-alone mode

Operating Mode	Max. EIRP incl. tune-up (dBm)	Distance (cm)	MPE (mW/cm ²)	Limit (mW/cm ²)	Verdict
Bluetooth	6.98	20	0.001	1.0	Pass
2.4G Wi-Fi	18.44	20	0.014	1.0	Pass
2.4GHz SDR	25.15	20	0.065	1.0	Pass
5.8G Wi-Fi	19.45	20	0.018	1.0	Pass
5.8GHz SDR	27.51	20	0.112	1.0	Pass

Note: simultaneous mode not supported.

3.1.1.2 RSS-102 Exemption Limits for Routine Evaluation – RF Exposure Evaluation

RF exposure evaluation is required if the separation distance between the user and/or bystander and the device's radiating element is greater than 20 cm, except when the device operates as follows:

- below 20 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 1 W (adjusted for tune-up tolerance);
- at or above 20 MHz and below 48 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than $4.49/f^{0.5}$ W (adjusted for tune-up tolerance), where f is in MHz;
- at or above 48 MHz and below 300 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 0.6 W (adjusted for tune-up tolerance);
- at or above 300 MHz and below 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than $1.31 \times 10^{-2} f^{0.6834}$ W (adjusted for tune-up tolerance), where f is in MHz;
- at or above 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 5 W (adjusted for tune-up tolerance).

In these cases, the information contained in the RF exposure technical brief may be limited to information that demonstrates how the e.i.r.p. was derived.

Table 5: Test Results of RF Exposure Calculations for ISED, Stand-alone mode

Operating Mode	Max. EIRP incl. tune-up (dBm)	Distance (cm)	Maximum EIRP (W)	Threshold power (W)	Verdict
Bluetooth	6.98	20	0.005	2.68	Pass
2.4G Wi-Fi	18.44	20	0.070	2.70	Pass
2.4GHz SDR	25.15	20	0.327	2.71	Pass
5.8G Wi-Fi	19.45	20	0.088	4.90	Pass
5.8GHz SDR	27.51	20	0.564	4.85	Pass

Note: The maximum EIRP lower than the threshold power in section 2.5.2, thus compliant. Simultaneous mode not supported.

4. List of Tables

Table 1: List of Test and Measurement Equipment	4
Table 2: Rating of EUT	5
Table 3: Technical Specification of EUT	5
Table 4: Test Results of RF Exposure Calculations for FCC, stand-alone mode.....	9
Table 5: Test Results of RF Exposure Calculations for ISED, Stand-alone mode	10