

Prüfbericht-Nr.: <i>Test report no.:</i>	CN23WKV3 005	Auftrags-Nr.: <i>Order no.:</i>	168427672	Seite 1 von 12 Page 1 of 12
Kunden-Referenz-Nr.: <i>Client reference no.:</i>	N/A	Auftragsdatum: <i>Order date:</i>	2023-05-22	
Auftraggeber: <i>Client:</i>	SZ DJI TECHNOLOGY CO., LTD Lobby of T2, DJI Sky City, No. 53 Xianyuan Road, Xili Community, Xili Street, Nanshan District, Shenzhen, China.			
Prüfgegenstand: <i>Test item:</i>	DJI Mini 4 Pro			
Bezeichnung / Typ-Nr.: <i>Identification / Type no.:</i>	MT4MFVD, MT4MFVDB (Trademark: DJI)			
Auftrags-Inhalt: <i>Order content:</i>	Test Report			
Prüfgrundlage: <i>Test specification:</i>	FCC Part 2: Section 2.1091			
Wareneingangsdatum: <i>Date of sample receipt:</i>	2023-05-25	Please refer to Photo Document		
Prüfmuster-Nr.: <i>Test sample no.:</i>	A003481038-013~014			
Prüfzeitraum: <i>Testing period:</i>	2023-05-31 - 2023-08-22			
Ort der Prüfung: <i>Place of testing:</i>	TÜV Rheinland (Shenzhen) Co., Ltd.			
Prüflaboratorium: <i>Testing laboratory:</i>	TÜV Rheinland (Shenzhen) Co., Ltd.			
Prüfergebnis*: <i>Test result*:</i>	Pass			
geprüft von: <i>tested by:</i>	<u>x Bell Hu</u>	genehmigt von: <i>authorized by:</i>	<u>X Lin Lin</u>	
Datum: <i>Date:</i>	2023-08-23 <small>Signed by: Bell Hu</small>	Ausstellungsdatum: <i>Issue date:</i>	2023-08-23 <small>Signed by: Lin Lin</small>	
Stellung / Position:	Sachverständige(r)/Expert	Stellung / Position:	Sachverständige(r)/Expert	
Sonstiges / <i>Other:</i>	FCC ID: SS3-MT4MFVD23			
Zustand des Prüfgegenstandes bei Anlieferung: <i>Condition of the test item at delivery:</i>	Prüfmuster vollständig und unbeschädigt <i>Test item complete and undamaged</i>			
<small>* Legende:</small>	<small>P(ass) = entspricht o.g. Prüfgrundlage(n)</small>	<small>F(ail) = entspricht nicht o.g. Prüfgrundlage(n)</small>	<small>N/A = nicht anwendbar</small>	<small>N/T = nicht getestet</small>
<small>* Legend:</small>	<small>P(ass) = passed a.m. test specification(s)</small>	<small>F(ail) = failed a.m. test specification(s)</small>	<small>N/A = not applicable</small>	<small>N/T = not tested</small>
Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens. <i>This test report only relates to the above mentioned test sample. Without permission of the test center this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any test mark.</i>				

v05

Prüfbericht-Nr.: CN23WKV3 005
Test report no.:

Seite 2 von 12
Page 2 of 12

Anmerkungen
Remarks

1	<p>Alle eingesetzten Prüfmittel waren zum angegebenen Prüfzeitraum gemäß eines festgelegten Kalibrierungsprogramms unseres Prüfhauses kalibriert. Sie entsprechen den in den Prüfprogrammen hinterlegten Anforderungen. Die Rückverfolgbarkeit der eingesetzten Prüfmittel ist durch die Einhaltung der Regelungen unseres Managementsystems gegeben. Detaillierte Informationen bezüglich Prüfkonditionen, Prüfequipment und Messunsicherheiten sind im Prüflabor vorhanden und können auf Wunsch bereitgestellt werden.</p> <p><i>The equipment used during the specified testing period was calibrated according to our test laboratory calibration program. The equipment fulfils the requirements included in the relevant standards. The traceability of the test equipment used is ensured by compliance with the regulations of our management system. Detailed information regarding test conditions, equipment and measurement uncertainty is available in the test laboratory and could be provided on request.</i></p>
2	<p>Wie vertraglich vereinbart, wurde dieses Dokument nur digital unterzeichnet. Der TÜV Rheinland hat nicht überprüft, welche rechtlichen oder sonstigen diesbezüglichen Anforderungen für dieses Dokument gelten. Diese Überprüfung liegt in der Verantwortung des Benutzers dieses Dokuments. Auf Verlangen des Kunden kann der TÜV Rheinland die Gültigkeit der digitalen Signatur durch ein gesondertes Dokument bestätigen. Diese Anfrage ist an unseren Vertrieb zu richten. Eine Umweltgebühr für einen solchen zusätzlichen Service wird erhoben.</p> <p><i>As contractually agreed, this document has been signed digitally only. TUV Rheinland has not verified and unable to verify which legal or other pertaining requirements are applicable for this document. Such verification is within the responsibility of the user of this document. Upon request by its client, TUV Rheinland can confirm the validity of the digital signature by a separate document. Such request shall be addressed to our Sales department. An environmental fee for such additional service will be charged.</i></p>
3	<p>Prüfklausel mit der Note * wurden an qualifizierte Unterauftragnehmer vergeben und sind unter der jeweiligen Prüfklausel des Berichts beschrieben. Abweichungen von Prüfspezifikation(en) oder Kundenanforderungen sind in der jeweiligen Prüfklausel im Bericht aufgeführt.</p> <p><i>Test clauses with remark of * are subcontracted to qualified subcontractors and described under the respective test clause in the report.</i> <i>Deviations of testing specification(s) or customer requirements are listed in specific test clause in the report.</i></p>
4	<p>Die Entscheidungsregel für Konformitätserklärungen basierend auf numerischen Messergebnissen in diesem Prüfbericht basiert auf der "Null-Grenzwert-Regel" und der "Einfachen Akzeptanz" gemäß ILAC G8:2019 und IEC Guide 115:2021, es sei denn, in der auf Seite 1 dieses Berichts genannten angewandten Norm ist etwas anderes festgelegt oder vom Kunden gewünscht. Dies bedeutet, dass die Messunsicherheit nicht berücksichtigt wird und daher auch nicht im Prüfbericht angegeben wird. Zu weiteren Informationen bezüglich des Risikos durch diese Entscheidungsregel siehe ILAC G8:2019.</p> <p><i>The decision rule for statements of conformity, based on numerical measurement results, in this test report is based on the "Zero Guard Band Rule" and "Simple Acceptance" in accordance with ILAC G8:2019 and IEC Guide 115:2021, unless otherwise specified in the applied standard mentioned on Page 1 of this report or requested by the customer. This means that measurement uncertainty is not taken in account and hence also not declared in the test report. For additional information on the resulting risk based of this decision rule please refer to ILAC G8:2019.</i></p>

TEST SUMMARY

3.1.1 RF EXPOSURE COMPLIANCE

RESULT: Pass

CONTENTS

1.	TEST SITES.....	5
1.1	TEST FACILITIES	5
1.2	TRACEABILITY	5
1.3	CALIBRATION.....	5
1.4	LOCATION OF ORIGINAL DATA	5
1.5	STATUS OF FACILITY USED FOR TESTING	5
2.	GENERAL PRODUCT INFORMATION	6
2.1	GENERAL DESCRIPTION	6
2.2	RATING AND SYSTEM DETAILS	6
3.	TEST RESULTS	10
3.1	TRANSMITTER REQUIREMENTS & TEST SUITES.....	10
3.1.1	<i>RF Exposure Compliance.....</i>	<i>10</i>
3.1.1.1	FCC Part 1.1310, Part 2.1091	10
4.	LIST OF TABLES.....	12

1. TEST SITES

1.1 TEST FACILITIES

TÜV Rheinland (Shenzhen) Co., Ltd.

Address: No. 362 Huanguan Road Middle, Longhua District, Shenzhen 518110, P.R. China

FCC Registration No.: 694916

ISED Wireless Device Testing Laboratory: 25069

1.2 Traceability

All measurement equipment calibrations are traceable to NIST or where calibration is performed outside the United States, to equivalent nationally recognized standards organizations.

1.3 Calibration

Equipment requiring calibration is calibrated periodically by the manufacturer or according to manufacturer's specifications. Additionally all equipment is verified for proper performance on a regular basis using in house standards or comparisons.

1.4 Location of Original Data

The original copies of all test data taken during actual testing were attached at Appendixes of this report and delivered to the applicant. A copy has been retained in the TÜV Rheinland (Shenzhen) file for certification follow-up purposes.

1.5 Status of Facility Used for Testing

The TÜV Rheinland (Shenzhen) Co., Ltd. facility located at No. 362 Huanguan Road Middle, Longhua District, Shenzhen 518110, P.R. China is listed on the US Federal Communications Commission list of facilities approved to perform measurements.

2. GENERAL PRODUCT INFORMATION

2.1 GENERAL DESCRIPTION

The EUT (Equipment Under Test) is a DJI Mini 4 Pro. It supports Bluetooth, 2.4GHz SDR, 2.4GHz Wi-Fi, 5.2GHz SDR, 5.8GHz Wi-Fi, 5.8GHz SDR and GNSS functions.

*remark: SDR means specific defined radio, and cannot changes radio specification via software/firmware by end-users.

According to the declaration of the applicant, the electrical circuit design and PCB layout are identical, only the model no. is different for market strategy.

For details refer to the User Manual, Technical Description and Circuit Diagram.

2.2 RATING AND SYSTEM DETAILS

Table 1: Rating of EUT

General Information of EUT	Value
Kind of Equipment	DJI Mini 4 Pro
Type Designation	MT4MFVD, MT4MFVDB
Trademark	DJI
Operating Voltage	AC 100-240V, 50/60Hz input via AC/DC Adapter or Battery operated (7.38V @3850mAh, 7.32V @2590mAh)
Testing Voltage	Fully charged battery
Operating Temperature Range	-10°C ~ +40 °C
Radiofrequency operating mode	<ol style="list-style-type: none"> 1) Bluetooth: operating within 2400-2483.5MHz, Bluetooth BLE, 1Mbps&2Mbps 2) 2.4GHz SDR: operating within 2400-2483.5MHz, supports 1.4MHz/3MHz/5MHz/10MHz/20MHz/40MHz/60MHz Bandwidth 3) 2.4GHz Wi-Fi: operating within 2400-2483.5MHz, supports 20MHz/40MHz Bandwidth and IEEE 802.11 b/g/n20/n40 4) 5.2GHz SDR: operating within 5170-5250MHz, supports 10MHz/20MHz/40MHz Bandwidth 5) 5.8GHz SDR: operating within 5725-5850MHz, supports 1.4MHz/3MHz/5MHz/10MHz/20MHz/40MHz/60MHz/80MHz Bandwidth 6) 5.8GHz Wi-Fi: operating within 5725-5850MHz, supports 20MHz/40MHz/80MHz Bandwidth and IEEE 802.11 a/n20/n40/ac20/ac40/ac80 7) GPS & BDS & Galileo & GLONASS (receiver): operating within 1559 to 1610 MHz
Adapter	Model: PD-30US Input: 100-240V, 50/60Hz, 0.8A Max Output: DC 3.3-11.0V/2.72A or 5.0V/3A or 9.0V/3A or 12V/2.5A or 15V/2A

Table 2: Technical Specification of EUT

Technical Specification of Bluetooth	
Operating Frequency	2402-2480MHz
Type of Modulation	GFSK
Data Rate	1Mbps, 2Mbps
Channel Number	40 channels
Channel Separation	2MHz
Antenna Type	Integral Antenna
Antenna Type	Integral Antenna (ANT1)
Antenna Gain	1.0 dBi (Provided by the Client)
Technical Specification of 2.4GHz SDR	
Operating Frequency	2403.5-2467.5MHz for 1.4MHz Bandwidth 2405.12-2469.12MHz for 1.4MHz Bandwidth (CA mode) 2405.5-2465.5MHz for 3MHz Bandwidth 2408.2-2468.2MHz for 3MHz Bandwidth (CA mode) 2404.5-2469.5MHz for 5MHz Bandwidth 2407.5-2467.5MHz for 10MHz Bandwidth 2412.5-2462.5MHz for 20MHz Bandwidth 2422.5-2452.5MHz for 40MHz Bandwidth 2432.5-2442.5MHz for 60MHz Bandwidth
Type of Modulation	OFDM (QPSK/16QAM/64QAM/256QAM/1024QAM/4096QAM)
Channel Number	33 channels for 1.4MHz Bandwidth 33 channels for 1.4MHz Bandwidth (CA mode) 21 channels for 3MHz Bandwidth 21 channels for 3MHz Bandwidth (CA mode) 14 channels for 5MHz Bandwidth 61 channels for 10MHz Bandwidth 51 channels for 20MHz Bandwidth 31 channels for 40MHz Bandwidth 11 channels for 60MHz Bandwidth
Channel Separation	2MHz for 1.4MHz Bandwidth 2MHz for 1.4MHz Bandwidth (CA mode) 3MHz for 3MHz Bandwidth 3MHz and 3MHz for 3MHz Bandwidth (CA mode) 5MHz for 5MHz Bandwidth 1MHz for 10MHz/20MHz/40MHz/60MHz Bandwidth
Antenna Type	Integral Antenna
Antenna Number	1Tx4Rx,1Tx2Rx for SISO mode (ANT0 or ANT1 or ANT2 or ANT3) 2Tx2Rx,2Tx4Rx for MIMO mode (ANT0+ANT1, or ANT0+ANT3, or ANT2+ANT1, or ANT2+ANT3)
Antenna Gain	1.0 dBi for ANT0/ANT1/ANT2/ANT3 (Provided by the Client)
Technical Specification of 2.4GHz Wi-Fi	
Operating Frequency	2412 - 2462MHz for 802.11b/g/n(HT20) 2422 - 2452MHz for 802.11n(HT40)
Type of Modulation	DSSS(DBPSK/DQPSK/CCK) OFDM(BPSK/QPSK/16QAM/64QAM) OFDMA(BPSK/QPSK/16QAM/64QAM/256QAM)
Data Rate	1/2/5.5/11 Mbps for 802.11b 6/9/12/18/24/36/48/54 Mbps for 802.11g

	MCS0 ~ MCS7 Mbps for 802.11n(HT20)/(HT40)
Channel Number	11 channels for 802.11b/g/n(HT20) 7 channels for 802.11n(HT40)
Channel Separation	5 MHz
Antenna Type	Integral Antenna (ANT1)
Antenna Gain	1.0 dBi (Provided by the Client)
Technical Specification of 5.2GHz SDR	
Operating Frequency	5157-5245MHz for 10MHz Bandwidth 5161-5240MHz for 20MHz Bandwidth 5170-5230MHz for 40MHz Bandwidth
Type of Modulation	OFDM (QPSK, 16QAM, 64QAM)
Channel Number	89 channels for 10MHz Bandwidth 80 channels for 20MHz Bandwidth 61 channels for 40MHz Bandwidth
Channel Separation	1MHz for 10MHz Bandwidth 1MHz for 20MHz Bandwidth 1MHz for 40MHz Bandwidth
Antenna Type	Integral Antenna
Antenna Number	1Tx4Rx,1Tx2Rx for SISO mode (ANT0 or ANT1 or ANT2 or ANT3) 2Tx2Rx,2Tx4Rx for MIMO mode (ANT0+ANT1, or ANT0+ANT3, or ANT2+ANT1, or ANT2+ANT3)
Antenna Gain	1.0 dBi for ANT0/ANT1/ANT2/ANT3 (Provided by the Client)
Technical Specification of 5.8GHz SDR	
Operating Frequency	5728.5-5844.5MHz for 1.4MHz Bandwidth 5730.12-5846.12MHz for 1.4MHz Bandwidth (CA mode) 5727.5-5844.5MHz for 3MHz Bandwidth 5730.2-5847.2MHz for 3MHz Bandwidth (CA mode) 5732.5-5842.5MHz for 5MHz Bandwidth 5730.5-5844.5MHz for 10MHz Bandwidth 5735.5-5839.5MHz for 20MHz Bandwidth 5745.5-5829.5MHz for 40MHz Bandwidth 5755.5-5819.5MHz for 60MHz Bandwidth 5765.5-5809.5MHz for 80MHz Bandwidth
Type of Modulation	OFDM (QPSK/16QAM/64QAM/256QAM/1024QAM/4096QAM)
Channel Number	59 channels for 1.4MHz Bandwidth 59 channels for 1.4MHz Bandwidth (CA mode) 40 channels for 3MHz Bandwidth 40 channels for 3MHz Bandwidth (CA mode) 23 channels for 5MHz Bandwidth 115 channels for 10MHz Bandwidth 105 channels for 20MHz Bandwidth 85 channels for 40MHz Bandwidth 65 channels for 60MHz Bandwidth 45 channels for 80MHz Bandwidth
Channel Separation	2MHz for 1.4MHz Bandwidth 2MHz for 1.4MHz Bandwidth (CA mode) 3MHz for 3MHz Bandwidth 3MHz for 3MHz Bandwidth (CA mode) 1MHz for 10MHz Bandwidth 1MHz for 20MHz Bandwidth

Prüfbericht - Nr.: CN23WKV3 005
Test Report No.:
Seite 9 von 12
Page 9 of 12

	1MHz for 40MHz Bandwidth
Antenna system	Integral Antenna
Antenna Number	1Tx4Rx,1Tx2Rx for SISO mode (ANT0 or ANT1 or ANT2 or ANT3) 2Tx2Rx,2Tx4Rx for MIMO mode (ANT0+ANT1, or ANT0+ANT3, or ANT2+ANT1, or ANT2+ANT3)
Antenna Gain	1.5 dBi for ANT0/ANT1/ANT2/ANT3 (Provided by the Client)
Technical Specification of 5.8GHz Wi-Fi	
Operating Frequency	5745–5825MHz for 802.11 a/n20/n40/ac20/ac40/ac80
Type of Modulation	OFDM(BPSK/QPSK/16QAM/64QAM/256QAM)
Data Rate	6/9/12/18/24/36/48/54 Mbps for 802.11a MCS 0 ~ MCS 7 for 802.11 n20/n40 VHT-MCS 0 ~ VHT-MCS 8 for 802.11 ac20 VHT-MCS 0 ~ VHT-MCS 9 for 802.11 ac40 VHT-MCS 0 ~ VHT-MCS 9 for 802.11 ac80
Channel Number	5 channels for 802.11a/n20/ac20 2 channels for 802.11n40/ac40 1 channel for 802.11ac80
Channel Separation	20MHz, 40MHz, 80MHz
Antenna Type	Integral Antenna (ANT1)
Antenna Gain	1.5 dBi (Provided by the Client)
Operating Frequency	5745–5825MHz for 802.11 a/n20/n40/ac20/ac40/ac80

3. Test Results

3.1 Transmitter Requirements & Test Suites

3.1.1 RF Exposure Compliance

RESULT: **Pass**

Test standard : FCC Part 1.1091
 Limit : Table 1 of 47 CFR FCC Part 1.1310
 Kind of test site : Shielded room

This device is mobile device, and the applicant declares that the minimum separation distance is greater than 20cm. Therefore MPE measurement or computational modelling should be used to determine compliance.

MPE Calculation is based on the conducted power, and considering maximum power and Antenna gain. The following formula is used to MPE evaluation.

$$Pd = \frac{P_{out} * G}{4R^2\pi}$$

Where

P_d = power density in mW/cm² or W/m²

P_{out} = output power to antenna in mW or W

G_{num} = Antenna gain in numeric

π = 3.14159

R = Distance between observation point and the center of radiator in cm or m

3.1.1.1 FCC Part 1.1310, Part 2.1091

According to ANSI/IEEE C95.1-1992, the criteria listed in Table 1 shall be used to evaluate the environmental impact of human exposure to radio frequency (RF) radiation as specified in §1.1310.

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3-3.0	614	1.63	*(100)	6
3.0-30	1842/f	4.89/f	*(900/f ²)	6
30-300	61.4	0.163	1.0	6
300-1500			f/300	6
1500-100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500			f/1500	30
1500-100,000			1.0	30

Prüfbericht - Nr.: CN23WKV3 005
Test Report No.:
Seite 11 von 12
Page 11 of 12
Table 3: Test Results of RF Exposure Calculations for FCC, Stand-alone mode

Operating Mode	Measured RF Output Power (dBm)	Antenna Gain (dBi)	Distance (cm)	MPE (mW/cm ²)	Limit (mW/cm ²)	Verdict
BLE	6.59	1.0	20	0.0011	1.0	Pass
2.4GHz Wi-Fi	21.05	1.0	20	0.0319	1.0	Pass
2.4GHz SDR	28.52	1.0	20	0.1416	1.0	Pass
5.2GHz SDR	18.09	1.0	20	0.0161	1.0	Pass
5.8GHz Wi-Fi	14.51	1.5	20	0.0079	1.0	Pass
5.8GHz SDR	28.42	1.5	20	0.1954	1.0	Pass

Note: Simultaneous transmissions not supported when in normal use.

Table 4: Test Results of RF Exposure Calculations for FCC, Simultaneous mode

Co-location Mode	Sum of the MPE ratios	Limit	Verdict
2.4GHz Wi-Fi + 5.2GHz SDR	0.0319/1+0.0161/1<1.0	1.0	Pass
2.4GHz Wi-Fi + 5.8GHz SDR	0.0319/1+0.1954/1<1.0	1.0	Pass
5.8GHz Wi-Fi + 2.4GHz SDR	0.0079/1+0.1416/1<1.0	1.0	Pass
Bluetooth + 5.2GHz SDR	0.0011/1+0.0161/1<1.0	1.0	Pass
Bluetooth + 5.8GHz SDR	0.0011/1+0.1954/1<1.0	1.0	Pass

Therefore the maximum calculations result of above are meet the requirement of Radio Frequency Exposure (MPE) limit.

4. List of Tables

Table 1: Rating of EUT.....	6
Table 2: Technical Specification of EUT	7
Table 3: Test Results of RF Exposure Calculations for FCC, Stand-alone mode	11
Table 4: Test Results of RF Exposure Calculations for FCC, Simultaneous mode.....	11