

# FCC PART 15.249

# **TEST REPORT**

For

# SZ DJI TECHNOLOGY CO., LTD

14th floor, West Wing, Skyworth Semiconductor Design Building NO.18 Gaoxin South 4th Ave, Nanshan, Shenzhen, Guangdong, China

FCC ID: SS3-RD2412F1622

Report Type:		Product Name:	
Original Report		High-Precision Mi	crowave Radar
Test Engineer:	Lorin Biar	n	Lorin Dian
Report Number:	RDG1612	218002B	
Report Date:	2017-01-0	05	
Reviewed By:	Henry Dir EMC Lea	ng der	Henry Ding
Test Laboratory:	Bay Area 5040, Hui JinNiu Dis Tel: 028-6 www.bacl	Compliance Laborator iLongWan Plaza, No. 1 strict, ChengDu, China 55523123, Fax: 028-65 lcorp.com	ies Corp. (Chengdu) , ShaWan Road, 525125

**Note**: This test report was prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Chengdu). Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. This report was valid only with a valid digital signature.

# TABLE OF CONTENTS

GENERAL INFORMATION	3
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	3
Objective Related Submittal (s)/Grant(s)	
TEST METHODOLOGY	
TEST FACILITY	4
SYSTEM TEST CONFIGURATION	5
JUSTIFICATION	5
EUT EXERCISE SOFTWARE	5
EQUIPMENT MODIFICATIONS	5
SUPPORT EQUIPMENT LIST AND DETAILS	5
BLOCK DIAGRAM OF TEST SETUP	
SUMMARY OF TEST RESULTS	7
FCC§15.203 - ANTENNA REQUIREMENT	8
APPLICABLE STANDARD	8
ANTENNA CONNECTOR CONSTRUCTION	8
FCC§15.205, §15.209&§15.249- RADIATED EMISSIONS	9
APPLICABLE STANDARD	9
MEASUREMENT UNCERTAINTY	9
CORRECTED AMPLITUDE & MARGIN CALCULATION	11
TEST EQUIPMENT LIST AND DETAILS	
TEST RESULTS SUMMARY	12
Test Data	13
FCC §15.215(C) – 20 DB BANDWIDTH TESTING	14
APPLICABLE STANDARD	14
TEST PROCEDURE	14
TEST EQUIPMENT LIST AND DETAILS	14
IEST DATA	14

## **GENERAL INFORMATION**

#### **Product Description for Equipment under Test (EUT)**

The *SZ DJI TECHNOLOGY CO., LTD*'s product, model number: *RD2412F* (*FCC ID: SS3-RD2412F1622*) (the "EUT") in this report was a *High-Precision Microwave Radar*, which was measured approximately: 7.8 cm (L) x 7.5 cm (W) x1.5 cm (H), rated input voltage: DC12V.

\*All measurement and test data in this report was gathered from final production sample, serial number: 161218002 (assigned by the BACL, Chengdu). It may have deviation from any other sample. The EUT supplied by the applicant was received on 2016-12-26, and EUT conformed to test requirement.

#### Objective

This type approval report is prepared on behalf of *SZ DJI TECHNOLOGY CO., LTD* in accordance with Part 2-Subpart J, and Part 15-Subparts A, B and C of the Federal Communication Commissions rules.

The tests were performed in order to determine compliance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.209 and 15.249 rules.

#### Related Submittal(s)/Grant(s)

No related submittal(s)/grant(s).

#### **Test Methodology**

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

The uncertainty of any RF tests which use conducted method measurement is  $\pm 3.17$  dB, the uncertainty of any radiation on emissions measurement is:

30M~200MHz: ±4.7 dB; 200M~1GHz: ±6.0 dB; 1G~6GHz: ±5.13dB; 6G~25GHz: ±5.47dB;

And the uncertainty will not be taken into consideration for all test data recorded in the report.

## **Test Facility**

The test site used by BACL to collect test data is located in the 5040, HuiLongWan Plaza, No. 1, ShaWan Road, JinNiu District, ChengDu, China.

Test site at BACL has been fully described in reports submitted to the Federal Communication Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on April 24, 2015. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2014.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 560332. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

## SYSTEM TEST CONFIGURATION

## Justification

The system was configured for testing in Engineering Mode, which was provided by the manufacturer.

## **EUT Exercise Software**

No software was used during testing.

## **Equipment Modifications**

No modifications were made to the EUT.

## Support Equipment List and Details

Manufacturer	turer Description Model		Serial Number	
DJI	Battery	N/A	N/A	

## Block Diagram of Test Setup

Below 1G:



## Above 1G:

	Battery	
	EUT Non-Conductive Table 150	1.0 Meter
Non-Conductive Table 80 cm above Ground Plane	cm above Ground Plane	

Page 6 of 15

# SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§15.203	Antenna Requirement	Compliance
§15.207(a)	Conduction Emissions	Not Applicable
15.205, §15.209, §15.249	Radiated Emissions	Compliance
§15.215 (c)	20 dB Bandwidth	Compliance

Note: This device was powered by DC.

## FCC§15.203 - ANTENNA REQUIREMENT

## **Applicable Standard**

For intentional device, according to §15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used.

## Antenna Connector Construction

The EUT has an integrated antenna, the antenna gain is 12.5dBi, fulfill the requirement of this section. Please refer to the EUT photos.

Result: Compliant.

## FCC§15.205, §15.209&§15.249- RADIATED EMISSIONS

## **Applicable Standard**

As per FCC§15.249 (a), except as provided in paragraph (b) of this section, the field strength of emissions from intentional radiators operated within these frequency bands shall comply with the following:

Fundamental frequency	Field strength of fundamental (millivolts/meter)	Field strength of harmonics (microvolts/meter)
902–928 MHz	50	500
2400–2483.5 MHz	50	500
5725–5875 MHz	50	500
24.0–24.25 GHz	250	2500

As per FCC§15.249 (c), Field strength limits are specified at a distance of 3 meters.

(d) Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in §15.209, whichever is the lesser attenuation.

## **Measurement Uncertainty**

Compliance or non- compliance with a disturbance limit shall be determined in the following manner:

If  $U_{\text{lab}}$  is less than or equal to  $U_{\text{cispr}}$  of Table 1, then:

-compliance is deemed to occur if no measured disturbance level exceeds the disturbance limit; -non - compliance is deemed to occur if any measured disturbance level exceeds the disturbance limit.

If  $U_{\text{lab}}$  is greater than  $U_{\text{cispr}}$  of Table 1, then:

-compliance is deemed to occur if no measured disturbance level, increased by  $(U_{lab} - U_{cispr})$ , exceeds the disturbance limit;

-non - compliance is deemed to occur if any measured disturbance level, increased by  $(U_{lab} - U_{cispr})$ , exceeds the disturbance limit.

Based on CISPR 16-4-2-2011, measurement uncertainty of radiated emission at a distance of 3m at Bay Area Compliance Laboratories Corp. (Chengdu) is: 30M~200MHz: ±4.7 dB; 200M~1GHz: ±6.0 dB; 1G~6GHz: ±5.13dB; 6G~25GHz: ±5.47 dB;

Table 1 – Values of  $U_{cispr}$ 

Measurement					
Radiated disturbance (electric field strength at an OATS or in a SAC) (30 MHz to 1000 MHz)	6.3 dB				
Radiated disturbance (electric field strength in a FAR) (1 GHz to 6 GHz)	5.2 dB				
Radiated disturbance (electric field strength in a FAR) (6 GHz to 18 GHz)	5.5 dB				

## **EUT Setup**

Below 1 GHz:



The radiated emission and out of band emission tests were performed in the 3 meters chamber test site, using the setup accordance with the ANSI C63.10-2013 The specification used was the FCC 15.209/15.205 and FCC 15.249 limits.

#### **Test Equipment Setup**

The system was investigated from 30 MHz to 100 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Detector
30 MHz – 1000 MHz	120 kHz	300 kHz	120 kHz	QP
	1MHz	3 MHz	/	PK
ADOVE I GHZ	1MHz	10 Hz	/	AV

#### Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

All data was recorded in the Quasi-peak detection mode from 30 MHz to 1GHz, peak and average detection mode above 1 GHz.

According to C63.10, the above 40GHz test result shall be extrapolated to the specified distance using an extrapolation factor of 20dB/decade from 3m to 0.5m Distance extrapolation factor =20 log (specific distance [3m]/test distance [0.5m]) dB Extrapolation result = Corrected Amplitude (dB $\mu$ V/m) - distance extrapolation factor (15.56dB)

For above 40GHz, external harmonic mixers are utilized. The antenna is scanned around the entire perimeter surface of the EUT, in both horizontal and vertical polarizations, at the distance of 0.5m from the EUT. The Mixers and it's RF cables is compose a system for calibration, the conversion factor was added into the test Spectrum Analyzer in testing.

#### **Corrected Amplitude & Margin Calculation**

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

Corrected Amplitude = Meter Reading + Antenna Factor + Cable Loss - Amplifier Gain

The "**Margin**" column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

Margin = Limit –Corrected Amplitude

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Agilent	Amplifier	8447D	2944A10442	2016-12-02	2017-12-01
Rohde & Schwarz	EMI Test Receiver	ESCI	100028	2016-12-02	2017-12-01
Sunol Sciences	Broadband Antenna	JB3	A101808	2016-04-10	2019-04-09
Rohde & Schwarz	Spectrum Analyzer	FSEM30	100018	2016-12-02	2017-12-01
ETS	Horn Antenna	3115	003-6076	2016-12-02	2017-12-01
Ducommun Technologies	Horn Antenna	ARH-4223-02	1007726- 0113024	2014-06-16	2017-06-15
Mini-circuits	Amplifier	ZVA-183-S+	771001215	2016-05-20	2017-05-19
HP	Amplifier	8449B	3008A00277	2016-12-02	2017-12-01
EMCT	Semi-Anechoic Chamber	966	N/A	2015-04-24	2018-04-23
N/A	RF Cable (below 1GHz)	NO.1	N/A	2016-11-10	2017-11-09
N/A	RF Cable (below 1GHz)	NO.4	N/A	2016-11-10	2017-11-09
N/A	RF Cable (above 1GHz)	NO.2	N/A	2016-11-10	2017-11-09
Agilent	Spectrum Analyzer	8564E	5943A01752	2016-08-18	2017-08-18
Ducommun Technolagies	Horn Antenna	ARH-2823-02	1007726-01 1312	2016-08-18	2017-08-18
Agilent	Harmonic Mixer	11970U	2332A00853	2015-08-16	2017-08-15
Flann Micowave	Horn Antenna	24245-AB	26	N/A	N/A
Agilent	Harmonic Mixer	11970V	2521A01176 7	2015-08-16	2017-08-15
Alpha Industries	Horn Antenna	861V/385	736	N/A	N/A
Agilent	Harmonic Mixer	11970W	2521A00597	2015-08-16	2017-08-15
Alpha Industries	Horn Antenna	861W/387	355	N/A	N/A
Agilent	Coaxial Cable	1m	N/A	2016-05-06	2017-05-06
AgileInt	Coaxial Cable	1m	N/A	2016-05-06	2017-05-06

## **Test Equipment List and Details**

\* **Statement of Traceability:** BACL (Chengdu) attested that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

## **Test Results Summary**

According to the data in the following table, the EUT complied with the FCC Part 15.209 &15.205 & 15.249.

## **Test Data**

#### **Environmental Conditions**

Temperature:	24.8 °C
Relative Humidity:	40 %
ATM Pressure:	101.8 kPa

The testing was performed by Lorin Bian on 2016-12-29.

Test Mode: Transmitting

## 1) 30MHz-40GHz:

Frequency	Rec	eiver	Rx A	Antenna	Cable	Amplifier	Corrected	Linsit	Morain
(MHz)	Reading (dBµV)	Detector	Polar (H/V)	Factor (dB(1/m))	loss (dB)	Gain (dB)	Amplitude (dBµV/m)	(dBµV/m)	(dB)
24191.1	94.2	PK	Н	35.42	13.93	37.12	106.43	127.96	21.53
24191.1	91.92	AV	Н	35.42	13.93	37.12	104.15	107.96	3.81
24191.1	90.26	PK	V	35.42	13.93	37.12	102.49	127.96	25.47
24191.1	88.16	AV	V	35.42	13.93	37.12	100.39	107.96	7.57
3219	30.27	PK	V	25.43	3.76	26.49	32.97	74.00	41.03
3219	16.21	AV	V	25.43	3.76	26.49	18.91	54.00	35.09
24000	43.82	PK	Н	35.37	14.11	37.03	56.27	74.00	17.73
24000	21.12	AV	Н	35.37	14.11	37.03	33.57	54.00	20.43
24250	45.3	PK	Н	35.45	13.86	37.16	57.45	74.00	16.55
24250	22.26	AV	Н	35.45	13.86	37.16	34.41	54.00	19.59
524.7	45.75	QP	H	18.35	1.67	28.82	36.95	46.00	9.05
637.22	42.64	QP	H	20.10	1.92	28.85	35.81	46.00	10.19

## 2) 40-100GHz:

Frequency	Receiver		Rx Antenna		Corrected	Extrapolation	Limit	Morgin
(GHz) Reading (GHz) Pola		Polar (H/V)	Factor (dB(1/m))	Amplitude (dBµV/m)	result (dBμV/m)	(dBµV/m)	(dB)	
48.3	46.95	PK	Н	40.41	87.36	71.8	87.96	16.16
48.3	32.21	AV	Н	40.41	72.62	57.06	67.96	10.90
72.45	49.89	PK	Н	44.92	94.81	79.25	87.96	8.71
72.45	36.23	AV	Н	44.92	81.15	65.59	67.96	2.37
96.48	45.49	PK	Н	49.41	94.90	79.34	87.96	8.62
96.48	31.68	AV	H	49.41	81.09	65.53	67.96	2.43

Note: for the range 40-100GHz, the test performed at the distance 0.5m.

## FCC §15.215(c) – 20 dB BANDWIDTH TESTING

## **Applicable Standard**

Intentional radiators operating under the alternative provisions to the general emission limits, as contained in §§ 15.217 through 15.257 and in Subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated.

#### **Test Procedure**

- 1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- 2. Position the EUT on the test table without connection to measurement instrument. Turn on the EUT. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
- 3. Measure the frequency difference of two frequencies that were attenuated 20 dB from the reference level. Record the frequency difference as the emission bandwidth.
- 4. Repeat above procedures until all frequencies measured were complete.

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	Spectrum Analyzer	FSEM30	100018	2016-12-02	2017-12-01
Ducommun Technologies	Horn Antenna	ARH-4223-02	1007726- 0113024	2014-06-16	2017-06-15
Quinstar	Amplifier	QLW- 18405536-JO	15964001032	2016-08-18	2017-08-18
N/A	RF Cable	N/A	N/A	Each Time	1

## Test Equipment List and Details

\* **Statement of Traceability:** BACL (Chengdu) attested that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

## Test Data

#### **Environmental Conditions**

Temperature:	25.4 °C	
Relative Humidity:	35 %	
ATM Pressure:	101.7 kPa	

The testing was performed by Lorin Bian on 2016-12-27.

Test Result: Compliant.

Please refer to following tables and plots

Test Mode: Transmitting

Frequency	20 dB Bandwidth	
(MHz)	(MHz)	
24000-24250	200.0	



\*\*\*\*\* END OF REPORT \*\*\*\*\*