



FCC RF EXPOSURE REPORT

For

DJI Relay

MODEL NUMBER: RL01-65

REPORT NUMBER: 4790741213-RF-5

ISSUE DATE: May 6, 2023

FCC ID: SS3-RLO16523

Prepared for

SZ DJI TECHNOLOGY CO., LTD Lobby of T2, DJI Sky City, No. 53 Xianyuan Road, Xili Community, Xili Street, Nanshan District, Shenzhen, China

Prepared by

UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch

Building 10, Innovation Technology Park, No. 1, Li Bin Road, Song Shan Lake Hi-Tech Development Zone Dongguan, 523808, People's Republic of China

> Tel: +86 769 22038881 Fax: +86 769 33244054 Website: www.ul.com

The results reported herein have been performed in accordance with the laboratory's terms of accreditation. This report shall not be reproduced except in full without the written approval of the Laboratory. The results in this report apply to the test sample(s) mentioned above at the time of the testing period only and are not to be used to indicate applicability to other similar products.



Revision History

Rev. Issue Date		Revisions	Revised By
V0	May 6, 2023	Initial Issue	



TABLE OF CONTENTS

1.	ATTESTATION OF TEST RESULTS	4
2.	TEST METHODOLOGY	5
3.	FACILITIES AND ACCREDITATION	5
4.	REQUIREMENT	6



1. ATTESTATION OF TEST RESULTS

Applicant Information

Company Name:	SZ DJI TECHNOLOGY CO., LTD
Address:	Lobby of T2, DJI Sky City, No. 53 Xianyuan Road, Xili
	Community, Xili Street, Nanshan District, Shenzhen, China

Manufacturer Information

Company Name:	SZ DJI TECHNOLOGY CO., LTD
Address:	Lobby of T2, DJI Sky City, No. 53 Xianyuan Road, Xili
	Community, Xili Street, Nanshan District, Shenzhen, China

EUT Information

EUT Name:	DJI Relay
Model:	RL01-65
Sample Received Date:	February 24, 2023
Sample ID:	5825096
Date of Tested:	February 28, 2023 to May 6, 2023

APPLICABLE STANDARDS				
STANDARD	TEST RESULTS			
FCC 47CFR§2.1091	PASS			
KDB447498 D01 V06	PASS			

Prepared By:

Bucul Denny

Denny Huang Senior Project Engineer

Approved By:

Stephen Guo Operations Manager

Checked By:

Kebo Zhang Senior Project Engineer



2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 and KDB 447498 D01 General RF Exposure Guidance v06.

3. FACILITIES AND ACCREDITATION

	A2LA (Certificate No.: 4102.01) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been assessed and proved to be in compliance with A2LA. FCC (FCC Designation No.: CN1187) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. Has been recognized to perform compliance testing on equipment subject
Accreditation Certificate	to the Commission's Delcaration of Conformity (DoC) and Certification rules ISED (Company No.: 21320) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been registered and fully described in a report filed with ISED. The Company Number is 21320 and the test lab Conformity Assessment Body Identifier (CABID) is CN0046. VCCI (Registration No.: G-20019, R-20004, C-20012 and T-20011) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been assessed and proved to be in compliance with VCCI, the Membership No. is 3793. Facility Name: Chamber D, the VCCI registration No. is G-20019 and R-20004 Shielding Room B , the VCCI registration No. is C-20012 and T-20011

Note 1: All tests measurement facilities use to collect the measurement data are located at Building 10, Innovation Technology Park, Song Shan Lake Hi tech Development Zone, Dongguan, 523808, China

Note 2: The test anechoic chamber in UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch had been calibrated and compared to the open field sites and the test anechoic chamber is shown to be equivalent to or worst case from the open field site.

Note 3: For below 30MHz, lab had performed measurements at test anechoic chamber and comparing to measurements obtained on an open field site. And these measurements below 30MHz had been correlated to measurements performed on an OFS.



4. REQUIREMENT

LIMIT AND CALCULATION METHOD

Systems operating under the provisions of FCC 47 CFR section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as mobile device whereby a distance of 0.2m normally can be maintained between the user and the device, and below RF Permissible Exposure limit shall comply with. Limits for General Population/Uncontrolled Exposure

RF EXPOSURE LIMIT

Frequency Range (MHz)	E-field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Time E ² , H ² or S (Minutes)
0.3 1.34	614	1.63	(100)*	30
1.34 30	824/f	2.19/f	(180/f ²)*	30
30 300	27.5	0.073	0.2	30
300 1500			f/1500	30
1500 100,000			1.0	30

CALCULATION METHOD

S=PG/4πR² Where: S=power density P=power input to antenna G=power gain of the antenna in the direction of interest relative to an isotropic radiator R=distance to the center of radiation of the antenna



CALCULATED RESULTS

Radio Frequency Radiation Exposure Evaluation

2.4GHz SRD (Worst case)					
Operating Mode	Max. Tune up Power	Max. Directional Antenna Gain	Power density Limit		
WIDGE	(dBm)	(dBi)	(mW/ cm ²)		
2.4GHz SRD	27	3.5	0.223	1	

5.8 GHz SRD (Worst case)					
Operating Mode	Max. Tune up Power	Max. Directional Antenna Gain	Power density	Limit	
wode	(dBm)	(dBi)	(mW/ cm ²)		
5.8 GHz SRD	26	4.5	0.223	1	

Note:

1. The Power comes from operation description.

2. All the modes had been tested, but only the worst data was recorded in the report.

3. The assess distance is 20 cm.

4. 5.8 GHz SRD + 2.4GHz SRD = 0.223 + 0.223 = 0.446 (mW/cm²)

Therefor the maximum calculations of above situations are less than the "1" limit.

END OF REPORT