Bay Area Compliance Laboratories Corp. (Chengdu)

FCC §15.407 (f) & §1.1310 & §2.1091- MAXIMUM PERMISSIBLE **EXPOSURE (MPE)**

Applicable Standard

According to subpart 15.407(f) and subpart §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Limits for Maximum Permissible Exposure (MPE) (§1.1310, §2.1091)

(B) Limits for General Population/Uncontrolled Exposure									
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (minutes)					
0.3–1.34	614	1.63	*(100)	30					
1.34–30	824/f	2.19/f	*(180/f²)	30					
30–300	27.5	0.073	0.2	30					
300–1500	/	/	f/1500	30					
1500–100,000	1	1	1.0	30					

f = frequency in MHz; * = Plane-wave equivalent power density;

According to §1.1310 and §2.1091 RF exposure is calculated.

Calculation Formula:

Prediction of power density at the distance of the applicable MPE limit

S = PG/4 π R² = power density (in appropriate units, e.g. mW/cm²); P = power input to the antenna (in appropriate units, e.g., mW);

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain;

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm);

$$\sum_{i} \frac{S_i}{S_{Limit,i}} \leq 1$$

Bay Area Compliance Laboratories Corp. (Chengdu)

Calculated Data:

Frequency Range (MHz)	Antenna Gain		Maximum Power Including Tolerance		Evaluation Distance	Power Density (mW/cm ²)	MPE Limit (mW/cm ²)
	(dBi)	(numeric)	(dBm)	(mW)	(cm)	(mwv/cm)	
915.938- 927.738	-0.46	0.90	12	15.85	20.00	0.0028	0.6173
2406.5- 2476.5	1.60	1.45	29	794.33	20.00	0.2285	1.0
5730-5845	0.79	1.20	26	398.11	20.00	0.0950	1.0

Note: The Maximum Power Including Tolerance was declared by manufacturer. 2.4GHz and 5.8GHz can't transmission simultaneously.

The maximum simultaneously transmit is Sub 1G+2.4G mode:

$$\sum_{i} \frac{S_i}{S_{Limit,i}}$$

 $=S_{sub}/S_{limit-sub} + S_{2.4G}/S_{limit-2.4G}$

=0.0028/0.6173+0.2285/1

=0.23

< 1.0

Result: The device meet FCC MPE at 20 cm distance