

Prüfbericht-Nr.: Test report no.:	CN24ZS14 006	Auftrags-Nr.: Order no.:	168484696	Seite 1 von 48 Page 1 of 48
Kunden-Referenz-Nr.: Client reference no.:		Auftragsdatum: Order date:	2024-05-20	
Auftraggeber: Client:	SZ DJI TECHNOLOGY CO., LTD Lobby of T2, DJI Sky City, No. 53 Xianyuan Road, Xili Community, Xili Street, Nanshan District, Shenzhen, China.			
Prüfgegenstand: Test item:	Remote control			
Bezeichnung / Typ-Nr.: Identification / Type no.:	RC520 (Trademark: DJI)			
Auftrags-Inhalt: Order content:	FCC approval			
Prüfgrundlage: Test specification:	FCC 47 CFR § 2.1093 IEEE Std 1528-2013 IEC/62209-1528: 2020 Published RF exposure KDB procedures			
Wareneingangsdatum: Date of sample receipt:	2024-06-13	Please refer to Photo Document		
Prüfmuster-Nr.: Test sample no.:	A003743309-004			
Prüfzeitraum: Testing period:	2024-07-17 - 2024-07-19			
Ort der Prüfung: Place of testing:	TÜV Rheinland (Shenzhen) Co., Ltd.			
Prüflaboratorium: Testing laboratory:	TÜV Rheinland (Shenzhen) Co., Ltd.			
Prüfergebnis*: Test result*:	Pass			
geprüft von: tested by:	<u>X Bell Hu</u>	genehmigt von: authorized by:	<u>X Jonathan Li</u>	
Datum: Date:	2024-11-19 <small>Signed by: Bell Hu</small>	Ausstellungsdatum: Issue date:	2024-11-19 <small>Signed by: Jonathan Li</small>	
Stellung / Position:	Sachverständige(r)/Expert	Stellung / Position:	Sachverständige(r)/Expert	
Sonstiges / Other:	FCC ID: SS3-RC5202410			
Zustand des Prüfgegenstandes bei Anlieferung: Condition of the test item at delivery:	Prüfmuster vollständig und unbeschädigt Test item complete and undamaged			
* Legende:	P(ass) = entspricht o.g. Prüfgrundlage(n)	F(ail) = entspricht nicht o.g. Prüfgrundlage(n)	N/A = nicht anwendbar	N/T = nicht getestet
* Legend:	P(ass) = passed a.m. test specification(s)	F(ail) = failed a.m. test specification(s)	N/A = not applicable	N/T = not tested
Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens. This test report only relates to the above mentioned test sample. Without permission of the test center this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any test mark.				

Prüfbericht-Nr.: CN24ZS14 006
Test report no.:

Seite 2 von 48
Page 2 of 48

Anmerkungen
Remarks

- | | |
|---|--|
| 1 | <p>Alle eingesetzten Prüfmittel waren zum angegebenen Prüfzeitraum gemäß eines festgelegten Kalibrierungsprogramms unseres Prüfhauses kalibriert. Sie entsprechen den in den Prüfprogrammen hinterlegten Anforderungen. Die Rückverfolgbarkeit der eingesetzten Prüfmittel ist durch die Einhaltung der Regelungen unseres Managementsystems gegeben.</p> <p>Detaillierte Informationen bezüglich Prüfkonditionen, Prüfequipment und Messunsicherheiten sind im Prüflabor vorhanden und können auf Wunsch bereitgestellt werden.</p> <p><i>The equipment used during the specified testing period was calibrated according to our test laboratory calibration program. The equipment fulfils the requirements included in the relevant standards. The traceability of the test equipment used is ensured by compliance with the regulations of our management system. Detailed information regarding test conditions, equipment and measurement uncertainty is available in the test laboratory and could be provided on request.</i></p> |
| 2 | <p>Wie vertraglich vereinbart, wurde dieses Dokument nur digital unterzeichnet. Der TÜV Rheinland hat nicht überprüft, welche rechtlichen oder sonstigen diesbezüglichen Anforderungen für dieses Dokument gelten. Diese Überprüfung liegt in der Verantwortung des Benutzers dieses Dokuments. Auf Verlangen des Kunden kann der TÜV Rheinland die Gültigkeit der digitalen Signatur durch ein gesondertes Dokument bestätigen. Diese Anfrage ist an unseren Vertrieb zu richten. Eine Umweltgebühr für einen solchen zusätzlichen Service wird erhoben. Informationen zur Verifizierung der Authentizität unserer Dokumente erhalten Sie auf folgender Webseite: go.tuv.com/digital-signature</p> <p><i>As contractually agreed, this document has been signed digitally only. TUV Rheinland has not verified and unable to verify which legal or other pertaining requirements are applicable for this document. Such verification is within the responsibility of the user of this document. Upon request by its client, TUV Rheinland can confirm the validity of the digital signature by a separate document. Such request shall be addressed to our Sales department. An environmental fee for such additional service will be charged. For information on verifying the authenticity of our documents, please visit the following website: go.tuv.com/digital-signature</i></p> |
| 3 | <p>Prüfklausel mit der Note * wurden an qualifizierte Unterauftragnehmer vergeben und sind unter der jeweiligen Prüfklausel des Berichts beschrieben.</p> <p>Abweichungen von Prüfspezifikation(en) oder Kundenanforderungen sind in der jeweiligen Prüfklausel im Bericht aufgeführt.</p> <p><i>Test clauses with remark of * are subcontracted to qualified subcontractors and described under the respective test clause in the report.</i></p> <p><i>Deviations of testing specification(s) or customer requirements are listed in specific test clause in the report.</i></p> |
| 4 | <p>Die Entscheidungsregel für Konformitätserklärungen basierend auf numerischen Messergebnissen in diesem Prüfbericht basiert auf der "Null-Grenzwert-Regel" und der "Einfachen Akzeptanz" gemäß ILAC G8:2019 und IEC Guide 115:2021, es sei denn, in der auf Seite 1 dieses Berichts genannten angewandten Norm ist etwas anderes festgelegt oder vom Kunden gewünscht. Dies bedeutet, dass die Messunsicherheit nicht berücksichtigt wird und daher auch nicht im Prüfbericht angegeben wird. Zu weiteren Informationen bezüglich des Risikos durch diese Entscheidungsregel siehe ILAC G8:2019.</p> <p><i>The decision rule for statements of conformity, based on numerical measurement results, in this test report is based on the "Zero Guard Band Rule" and "Simple Acceptance" in accordance with ILAC G8:2019 and IEC Guide 115:2021, unless otherwise specified in the applied standard mentioned on Page 1 of this report or requested by the customer. This means that measurement uncertainty is not taken in account and hence also not declared in the test report. For additional information to the resulting risk based of this decision rule please refer to ILAC G8:2019.</i></p> |

Table of Contents

1.	GENERAL INFORMATION	5
1.1.	STATEMENT OF COMPLIANCE	5
1.2.	EQUIPMENT UNDER TEST (EUT) INFORMATION	6
1.2.1.	<i>General Information</i>	6
2.	TEST SITES.....	10
2.1.	TEST FACILITIES	10
2.2.	AMBIENT CONDITION	10
2.3.	LIST OF TEST AND MEASUREMENT INSTRUMENTS	11
3.	MEASUREMENT UNCERTAINTY	12
4.	TEST SPECIFICATION, METHODS AND PROCEDURES	14
5.	SAR MEASUREMENT SYSTEM	15
5.1.	DEFINITION OF SPECIFIC ABSORPTION RATE (SAR)	15
5.2.	SPEAG DASY SYSTEM	15
5.2.1.	<i>Robot.....</i>	16
5.2.2.	<i>Probes.....</i>	17
5.2.3.	<i>Data Acquisition Electronics (DAE).....</i>	17
5.2.4.	<i>Phantoms.....</i>	18
5.2.5.	<i>Device Holder.....</i>	19
5.2.6.	<i>System Validation Dipoles</i>	19
5.2.7.	<i>Tissue Simulating Liquids</i>	20
5.2.8.	<i>SAR System Verification</i>	22
6.	SAR MEASUREMENT PROCEDURE.....	23
6.1.	AREA & ZOOM SCAN PROCEDURE.....	23
6.2.	VOLUME SCAN PROCEDURE	23
6.3.	POWER DRIFT MONITORING.....	24
6.4.	SPATIAL PEAK SAR EVALUATION	24
6.5.	SAR AVERAGED METHODS	24
7.	SAR MEASUREMENT EVALUATION	25
7.1.	EUT CONFIGURATION AND SETTING	25
7.2.	EUT TESTING POSITION	27
7.2.1.	<i>Extremity Exposure Conditions</i>	27
7.3.	SAR TEST EXCLUSION EVALUATIONS.....	28
7.4.	SIMULTANEOUS TRANSMISSION POSSIBILITIES	30
7.5.	TISSUE VERIFICATION	31
7.6.	SYSTEM VALIDATION.....	31
7.7.	SYSTEM VERIFICATION	31
8.	SAR MEASUREMENT EVALUATION	32

8.1.	MAXIMUM CONDUCTED POWER	32
8.2.	SAR TESTING RESULTS	38
8.2.1.	<i>SAR Test Reduction Considerations.....</i>	38
8.2.3.	<i>SAR Results for Extremity Exposure Condition (Separation Distance is 0 cm Gap)</i>	39
8.2.4.	<i>SAR Results for Body-Worn Exposure Condition (Separation Distance is 0 cm Gap)</i>	41
8.2.5.	<i>SAR Measurement Variability</i>	42
8.2.6.	<i>Simultaneous Multi-band Transmission Evaluation</i>	43
APPENDIXES.....		48

Appendix A: SAR Plots of System Verification

Appendix B: SAR Plots of SAR Measurement

Appendix C: Calibration Certificate for probe and Dipole

Appendix D: Photographs of EUT and setup

1. General Information

1.1. Statement of Compliance

The maximum results of Specific Absorption Rate (SAR) found during testing for the EUT are as follows:

Equipment Class	Mode	Highest Reported Extremity SAR _{10g} (0 cm Gap) (W/kg)	Highest Reported Body SAR _{1g} (0 cm Gap) (W/kg)
DTS	2.4G WLAN	0.08	0.03
NII	5.2G WLAN	1.64	0.48
	5.8G WLAN	2.45	1.17
SDR	SDR-2.4G	0.67	0.44
	SDR-5.1G	0.45	0.53
	SDR-5.8G	0.88	0.39
DSS	Bluetooth	N/A	N/A
Highest Simultaneous Transmission SAR		Extremity (W/kg)	Body (W/kg)
SDR-2.4G+NII+DSS		3.55	1.42
SDR-5.1G+DTS+DSS		0.62	0.53
SDR-5.1G+WLAN 5.8G+DSS		2.63	1.43
SDR-5.8G+DTS+DSS		1.14	0.41
SDR-5.8G+WLAN 5.2G+DSS		3.15	0.86

Note:

This device is in compliance with Specific Absorption Rate (SAR) for general population/uncontrolled exposure limits (1.6W/kg as averaged over any 1 gram of tissue; 10-gram SAR for Product Specific 10g SAR, limit: 4.0W/kg) specified in FCC 47 CFR part 2 (2.1093) and ANSI/IEEE C95.1-1992/ IC RSS-102 Issue 6:2023, and had been tested in accordance with the measurement methods and procedures specified in IEEE 1528-2013 and FCC KDB publications.

All sides considered for limb-worn mode with 0mm distance.

Only the bottom and rear sides may have probability to keep towards with body/lap, thus 1-g body-SAR considered for bottom and rear sides as well, detailed description listed on Appendix D.

1.2. Equipment Under Test (EUT) Information

1.2.1. General Information

Note

General Information of EUT	Value
Kind of Equipment:	Remote control
Type Designation:	RC520
Trademark:	DJI
FCC ID:	SS3-RC5202410
Operating Voltage:	7.6V DC by built-in battery or AC 100-240V via AC/DC adapter
Testing Voltage:	Fully charged battery
Extreme Temperature Range:	-10°C to +40°C
Radiofrequency operating mode:	1) Bluetooth: operating within 2400-2483.5MHz, Classic Bluetooth (BR&EDR), Bluetooth BLE (1Mbps&2Mbps) 2) 2.4GHz SDR: operating within 2400-2483.5MHz, supports 1.4MHz/3MHz/5MHz/10MHz/20MHz/40MHz/60MHz Bandwidth 3) 2.4GHz Wi-Fi: operating within 2400-2483.5MHz, supports 20MHz/40MHz Bandwidth and IEEE 802.11 b/g/n20/n40/ax20/ax40 4) 5.2GHz SDR: operating within 5150-5250MHz, supports 10MHz/20MHz/40MHz/60MHz/80MHz Bandwidth 5) 5.2GHz Wi-Fi: operating with 5150-5250MHz, supports 20MHz/40MHz/80MHz Bandwidth and IEEE 802.11 a/n20/n40/ac20/ac40/ac80/ax20/ax40/ax80 6) 5.8GHz SDR: operating within 5725-5850MHz, supports 1.4MHz/3MHz/5MHz/10MHz/20MHz/40MHz/60MHz/80MHz Bandwidth 7) 5.8GHz Wi-Fi: operating within 5725-5850MHz, supports 20MHz/40MHz/80MHz Bandwidth and IEEE 802.11 a/n20/n40/ac20/ac40/ac80/ax20/ax40/ax80
Technical Specification of 2.4GHz SDR	
Operating Frequency:	2403.5-2469.12MHz for 1.4MHz Bandwidth 2405.5-2468.2MHz for 3MHz Bandwidth 2404.5-2469.5MHz for 5MHz Bandwidth 2407.5-2467.5MHz for 10MHz Bandwidth 2412.5-2462.5MHz for 20MHz Bandwidth 2422.5-2452.5MHz for 40MHz Bandwidth 2432.5-2442.5MHz for 60MHz Bandwidth
Type of Modulation:	OFDM (QPSK, 16QAM, 64QAM, 256QAM, 1024QAM, 4096QAM)
Channel Number:	108 channels for 1.4MHz Bandwidth 64 channels for 3MHz Bandwidth 130 channels for 5MHz Bandwidth 155 channels for 10MHz Bandwidth 51 channels for 20MHz Bandwidth 31 channels for 40MHz Bandwidth 11 channels for 60MHz Bandwidth
Antenna Type:	Integral Antennas
Antenna Number:	1Tx for SISO mode 2Tx for MIMO mode
Antenna Gain:	1.5 dBi (Provided by the Client)
The type of wideband data transmission equipment:	DTS

Technical Specification of 2.4GHz Wi-Fi	
Operating Frequency:	2412 - 2462 MHz for 802.11b/g/n(HT20)/ax(HE20) 2422 - 2452 MHz for 802.11n(HT40)/ax(HE40)
Type of Modulation:	DSSS(DBPSK/DQPSK/CCK) OFDM(BPSK/QPSK/16QAM/64QAM/256QAM/1024QAM)
Data Rate:	1/2/5.5/11 Mbps for 802.11b 6/9/12/18/24/36/48/54 Mbps for 802.11g MCS0 ~ MCS7 for 802.11n MCS0 ~ MCS11 for 802.11ax* *Only Full RU mode supported for 802.11ax.
Channel Number:	11 channels for 802.11b/g/n(HT20)/ax(HE20) 7 channels for 802.11n(HT40)/ax(HE40)
Channel Separation:	5 MHz
Antenna Type:	Integral Antenna
Antenna Number:	1Tx1Rx for SISO mode (ANT0 or ANT1) 2Tx2Rx for MIMO mode (ANT0+ANT1)
Antenna Gain:	1.5 dBi Max (Provided by the Client)
The type of wideband data transmission equipment:	DTS
Technical Specification of Bluetooth (dual mode)	
Operating Frequency:	2402 MHz to 2480 MHz
Type of Modulation:	GFSK, $\pi/4$ -DQPSK, 8DPSK
Channel Number:	BR & EDR mode:79 channels, Low Energy mode:40 channels
Channel Separation:	BR & EDR mode:1MHz, Low Energy mode:2MHz
Data Rate:	BR & EDR mode:(1Mbps, 2Mbps, 3Mbps) Low Energy mode: (1Mbps, 2Mbps)
Antenna Type:	Integral Antenna
Antenna Number:	1
Antenna Gain:	1.5 dBi (Provided by the Client)
Technical Specification of 5.2GHz SDR	
Operating Frequency:	5157-5245MHz for 10MHz Bandwidth 5161-5240MHz for 20MHz Bandwidth 5170-5230MHz for 40MHz Bandwidth 5180-5220MHz for 60MHz Bandwidth 5190-5210MHz for 80MHz Bandwidth
Type of Modulation:	OFDM (QPSK, 16QAM, 64QAM, 256QAM,1024QAM,4096QAM)
Channel Number:	239 channels for 10MHz Bandwidth 80 channels for 20MHz Bandwidth 61 channels for 40MHz Bandwidth 41 channels for 60MHz Bandwidth 21 channels for 80MHz Bandwidth
Antenna Type:	Integral Antennas
Antenna Number:	1Tx for SISO mode 2Tx for MIMO mode
Antenna Gain:	0 dBi (Provided by the Client)
The type of wideband data transmission equipment:	DTS
Technical Specification of 5.2GHz Wi-Fi	
Operating Frequency:	5180–5240MHz for 802.11 a/n20/n40/ac20/ac40/ac80/ax20/ax40/ax80

Type of Modulation:	OFDM(BPSK/QPSK/16QAM/64QAM) OFDMA(BPSK/QPSK/16QAM/64QAM/256QAM/1024QAM)
Data Rate:	6/9/12/18/24/36/48/54 Mbps for 802.11a MCS0 ~ MCS7 for 802.11n MCS0 ~ MCS9 for 802.11ac MCS0 - MCS11 for 802.11ax
Channel Number:	4 channels for 802.11a/n20/ac20/ax20 2 channels for 802.11n40/ac40/ax40 1 channels for 802.11ac80/ax80
Channel Separation:	20MHz, 40MHz, 80MHz
Antenna Type:	Integral Antenna
Antenna Number:	1Tx1Rx for SISO mode (ANT0 or ANT1) 2Tx2Rx for MIMO mode (ANT0+ANT1)
Antenna Gain:	-0.5 dBi Max (Provided by the Client)
Technical Specification of 5.8GHz SDR	
Operating Frequency:	5728.5-5846.12MHz for 1.4MHz Bandwidth 5727.5-5847.2MHz for 3MHz Bandwidth 5732.5-5842.5MHz for 5MHz Bandwidth 5730.5-5844.5MHz for 10MHz Bandwidth 5735.5-5839.5MHz for 20MHz Bandwidth 5745.5-5829.5MHz for 40MHz Bandwidth 5755.5-5819.5MHz for 60MHz Bandwidth 5765.5-5809.5MHz for 80MHz Bandwidth
Type of Modulation:	OFDM (QPSK, 16QAM, 64QAM, 256QAM, 1024QAM, 4096QAM)
Channel Number:	194 channels for 1.4MHz Bandwidth 126 channels for 3MHz Bandwidth 229 channels for 5MHz Bandwidth 317 channels for 10MHz Bandwidth 105 channels for 20MHz Bandwidth 85 channels for 40MHz Bandwidth 65 channels for 60MHz Bandwidth 45 channels for 80MHz Bandwidth
Antenna Type:	Integral Antennas
Antenna Number:	1Tx for SISO mode 2Tx for MIMO mode
Antenna Gain:	1.5 dBi (Provided by the Client)
The type of wideband data transmission equipment:	DTS
Technical Specification of 5.8GHz Wi-Fi	
Operating Frequency:	5745–5825MHz for 802.11 a/n20/n40/ac20/ac40/ac80/ax20/ax40/ax80
Type of Modulation:	OFDM(BPSK/QPSK/16QAM/64QAM) OFDMA(BPSK/QPSK/16QAM/64QAM/256QAM/1024QAM)
Data Rate:	6/9/12/18/24/36/48/54 Mbps for 802.11a MCS0 ~ MCS7 for 802.11n MCS0 ~ MCS9 for 802.11ac MCS0 ~ MCS11 for 802.11ax
Channel Number:	5 channels for 802.11a/n20/ac20/ax20 2 channels for 802.11n40/ac40/ax40 1 channel for 802.11ac80/ax80
Channel Separation:	20MHz, 40MHz, 80MHz

Antenna Type:	Integral Antenna
Antenna Number:	1Tx1Rx for SISO mode (ANT0 or ANT1) 2Tx2Rx for MIMO mode (ANT0+ANT1)
Antenna Gain:	2.0 dBi (Provided by the Client)

1. The above EUT information is declared by manufacturer and for more detailed features description please refers to the manufacturer's specifications or User's Manual.

2. Test Sites

2.1. Test Facilities

TÜV Rheinland (Shenzhen) Co., Ltd.

No. 362 Huanguan Road Middle Longhua District, Shenzhen 518110 People's Republic of China

A2LA Cert. No.: 5162.01

FCC Registration No.: 694916

IC Registration No.: 25069

2.2. Ambient Condition

Ambient Temperature	21.6°C – 22.5°C
Relative Humidity	52% - 62%

2.3. List of Test and Measurement Instruments

Equipment	Manufacturer	Model	SN	Cal. Date	Cal. Interval
System Validation Dipole	SPEAG	D2450V2	1014	Jun. 06, 2024	3 years
System Validation Dipole	SPEAG	D5GHzV2	1280	Jun. 06, 2024	3 years
Dosimetric E-Field Probe	SPEAG	EX3DV4	7738	Dec. 13, 2023	1 year
Data Acquisition Electronics	SPEAG	DAE4	1725	Oct. 26, 2023	1 year
Signal Analyzer	R&S	FSV 7	103665	Jun. 29, 2023	1 year
Vector Network Analyzer	R&S	ZNB 8	107040	Jul. 25, 2023	1 year
Signal Generator	R&S	SMB 100A	180840	Jul. 25, 2023	1 year
EPM Series Power Meter	Keysight	N1914A	MY58240005	Nov. 14, 2023	2 years
Power Sensor	Keysight	N8481H	MY58250002	Nov. 14, 2023	1 year
Power Sensor	Keysight	N8481H	MY58250006	Nov. 14, 2023	1 year
DC Power Supply	Topward	3303D	809332	Nov. 14, 2023	1 year
Coaxial Directional Coupler	Keysight	773D	MY52180552	Nov. 14, 2023	1 year
Coaxial Directional Coupler	shhuaxiang	DTO-0.4/3.9-10	18052101	Nov. 14, 2023	1 year
Coaxial attenuator	Keysight	8491A	MY52463219	Nov. 14, 2023	1 year
Coaxial attenuator	Keysight	8491A	MY52463210	Nov. 14, 2023	1 year
Coaxial attenuator	Keysight	8491A	MY52463222	Nov. 14, 2023	1 year
Digital Thermometer	LKM	DTM3000	3116	Nov. 14, 2023	1 year
Power Amplifier Mini circuit	mini-circuits	ZHL-42W	SN002101809	N/A	N/A
Power Amplifier Mini circuit	mini-circuits	ZVE-8G	SN070501814	N/A	N/A
PHANTOM	SPEAG	ELI V8.0	2094	N/A	N/A
PHANTOM	SPEAG	SAM-Twin V8.0	1961	N/A	N/A

3. Measurement Uncertainty

Source of Uncertainty	Tolerance (± %)	Probability Distribution	Divisor	Ci (1g)	Ci (10g)	Standard Uncertainty (1g)	Standard Uncertainty (10g)	Vi Veff
Measurement System Errors								
Probe Calibration	±12.7%	Normal (k=2)	2	1	1	± 6.35 %	± 6.35 %	∞
Probe Calibration Drift	±1.7%	Rectangular	√3	1	1	±1.0%	±1.0%	∞
Probe Linearity	±4.7%	Rectangular	√3	1	1	±2.7%	±2.7%	∞
Broadband Signal	±3.0%	Rectangular	√3	1	1	±1.7%	±1.7%	∞
Probe Isotropy	±7.6%	Rectangular	√3	1	1	±4.4%	±4.4%	∞
Other Probe + Electronic	±0.7%	Normal	1	1	1	±0.7%	±0.7%	∞
RF Ambient	±1.8%	Normal	1	1	1	±1.8%	±1.8%	∞
Probe Positioning	±0.006mm	Normal	1	0.14	0.14	±0.10%	±0.10%	∞
Data Processing	±1.2%	Normal	1	1	1	±1.2%	±1.2%	∞
Phantom and Device Errors								
Conductivity (meas. DAK)	±2.5%	Normal	1	0.78	0.71	±2.0%	±1.8%	100
Conductivity (temp.) ^{BB}	±3.3%	Rectangular	√3	0.78	0.71	±1.5%	±1.4%	∞
Phantom Permittivity	±14.0%	Rectangular	√3	0	0	±0%	±0%	∞
Distance DUT – TSL	±2.0%	Normal	1	2	2	±4.0%	±4.0%	∞
Device Positioning	±2.4%/±2.8%	Normal	1	1	1	±2.8%	±2.8%	30
Device Holder	±3.4%/±3.5%	Normal	1	1	1	±3.5%	±3.5%	30
DUT Modulation ^m	±2.4%	Rectangular	√3	1	1	±1.4%	±1.4%	∞
Time-average SAR	±1.7%	Rectangular	√3	1	1	±1.0%	±1.0%	∞
DUT drift	±2.5%	Normal	1	1	1	±2.5%	±2.5%	30
Val Antenna Unc. ^{val}	±0.0%	Normal	1	1	1	±0%	±0%	
Unc. Input Power ^{val}	±0.0%	Normal	1	1	1	±0%	±0%	
Correction to the SAR results								
C(ε,σ)	±1.9%	Normal	1	1	0.84	±1.9%	±1.6%	
SAR scaling ^p	±0.0%	Rectangular	√3	1	1	±0%	±0%	
Combined Standard Uncertainty (K = 1)						±12.54%	±12.44%	
Expanded Uncertainty (K = 2)						±25.1%	±24.9%	

Uncertainty budget for frequency range 300 MHz to 3 GHz

Source of Uncertainty	Tolerance (± %)	Probability Distribution	Divisor	Ci (1g)	Ci (10g)	Standard Uncertainty (1g)	Standard Uncertainty (10g)	Vi Veff
Measurement System Errors								
Probe Calibration	±13.9%	Normal (k=2)	2	1	1	± 6.95 %	± 6.95 %	∞
Probe Calibration Drift	±1.7%	Rectangular	√3	1	1	±1.0%	±1.0%	∞
Probe Linearity	±4.7%	Rectangular	√3	1	1	±2.7%	±2.7%	∞
Broadband Signal	±2.6%	Rectangular	√3	1	1	±1.5%	±1.5%	∞
Probe Isotropy	±7.6%	Rectangular	√3	1	1	±4.4%	±4.4%	∞
Other Probe + Electronic	±1.2%	Normal	1	1	1	±1.2%	±1.2%	∞
RF Ambient	±1.8%	Normal	1	1	1	±1.8%	±1.8%	∞
Probe Positioning	±0.005mm	Normal	1	0.29	0.29	±0.15%	±0.15%	∞
Data Processing	±2.3%	Normal	1	1	1	±2.3%	±2.3%	∞
Phantom and Device Errors								
Conductivity (meas.) ^{DAK}	±2.5%	Normal	1	0.78	0.71	±2.0%	±1.8%	60
Conductivity (temp.) ^{BB}	±3.3%	Rectangular	√3	0.78	0.71	±1.5%	±1.4%	∞
Phantom Permittivity	±14.0%	Rectangular	√3	0.25	0.25	±2%	±2%	∞
Distance DUT – TSL	±2.0%	Normal	1	2	2	±4.0%	±4.0%	∞
Device Positioning	±2.4%/±2.8%	Normal	1	1	1	±2.8%	±2.8%	30
Device Holder	±3.4%/±3.5%	Normal	1	1	1	±3.5%	±3.5%	30
DUT Modulation ^m	±2.4%	Rectangular	√3	1	1	±1.4%	±1.4%	∞
Time-average SAR	±1.7%	Rectangular	√3	1	1	±1.0%	±1.0%	∞
DUT drift	±2.5%	Normal	1	1	1	±2.5%	±2.5%	30
Val Antenna Unc. ^{val}	±0.0%	Normal	1	1	1	±0%	±0%	
Unc. Input Power ^{val}	±0.0%	Normal	1	1	1	±0%	±0%	
Correction to the SAR results								
Deviation to Target	±1.9%	Normal	1	1	0.84	±1.9%	±1.6%	
SAR scaling ^p	±0.0%	Rectangular	√3	1	1	±0%	±0%	
Combined Standard Uncertainty (K = 1)						±12.8%	±12.7%	
Expanded Uncertainty (K = 2)						±25.6%	±25.4%	

Uncertainty budget for frequency range 3 GHz to 6 GHz

4. Test Specification, Methods and Procedures

The tests documented in this report were performed in accordance with FCC 47 CFR § 2.1093, IEEE STD 1528- 2013, the following FCC Published RF exposure KDB procedures & manufacturer KDB inquiries:

- KDB 865664 D01 SAR Measurement 100 MHz to 6 GHz v01r04
- KDB 865664 D02 RF Exposure Reporting v01r02
- KDB 248227 D01 802 11 Wi-Fi SAR v02r02
- KDB 447498 D01 General RF Exposure Guidance v06
- KDB 447498 D04 Interim General RF Exposure Guidance v01
- IC RSS-102 Issue 6: December 2023 Radio Frequency (RF) Exposure Compliance of Radiocommunication Apparatus (All Frequency Bands)
- IEC/IEEE 62209-1528:2020 Measurement procedure for the assessment of specific absorption rate of human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices - Part 1528: Human models, instrumentation, and procedures (Frequency range of 4 MHz to 10 GHz)

In addition to the above, the following information was used:

- [TCB workshop](#) April, 2019; Page 19, Tissue Simulating Liquids(TSL)

5. SAR Measurement System

5.1. Definition of Specific Absorption Rate (SAR)

SAR is related to the rate at which energy is absorbed per unit mass in an object exposed to a radio field. The SAR distribution in a biological body is complicated and is usually carried out by experimental techniques or numerical modeling. The standard recommends limits for two tiers of groups, occupational/controlled and general population/uncontrolled, based on a person's awareness and ability to exercise control over his or her exposure. In general, occupational/controlled exposure limits are higher than the limits for general population/uncontrolled.

The SAR definition is the time derivative (rate) of the incremental energy (dW) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dv) of a given density (ρ). The equation description is as below:

$$\text{SAR} = \frac{d}{dt} \left(\frac{dW}{dm} \right) = \frac{d}{dt} \left(\frac{dW}{\rho dv} \right)$$

SAR is expressed in units of Watts per kilogram (W/kg)


SAR measurement can be related to the electrical field in the tissue by

$$\text{SAR} = \frac{\sigma |E|^2}{\rho}$$

Where: σ is the conductivity of the tissue, ρ is the mass density of the tissue and E is the RMS electrical field strength.

5.2. SPEAG DASY System

DASY system consists of high precision robot, probe alignment sensor, phantom, robot controller, controlled measurement server and near-field probe. The robot includes six axes that can move to the precision position of the DASY5 software defined. The DASY software can define the area that is detected by the probe. The robot is connected to controlled box. Controlled measurement server is connected to the controlled robot box. The DAE includes amplifier, signal multiplexing, AD converter, offset measurement and surface detection. It is connected to the Electro-optical coupler (ECO). The ECO performs the conversion from the optical into digital electric signal of the DAE and transfers data to the PC.




DASY System Setup

5.2.1. Robot

The DASY system uses the high precision robots from Stäubli SA (France). For the 6-axis controller system, the robot controller version (DASY5: CS8c) from Stäubli is used. The Stäubli robot series have many features that are important for our application:

- High precision (repeatability ± 0.035 mm)
- High reliability (industrial design)
- Jerk-free straight movements
- Low ELF interference (the closed metallic construction shields against motor control fields)



DASY6

5.2.2. Probes

The SAR measurement is conducted with the dosimetric probe. The probe is specially designed and calibrated for use in liquid with high permittivity. The dosimetric probe has special calibration in liquid at different frequency.

Model	EX3DV4	
Construction	Symmetrical design with triangular core. Built-in shielding against static charges. PEEK enclosure material (resistant to organic solvents, e.g., DGBE).	
Frequency	4 MHz – 10 GHz Linearity: ± 0.2 dB (30 MHz – 10 GHz)	
Directivity	± 0.1 dB in TSL (rotation around probe axis) ± 0.3 dB in TSL (rotation normal to probe axis)	
Dynamic Range	10 μ W/g – >100 mW/g Linearity: ± 0.2 dB (noise: typically <1 μ W/g)	
Dimensions	Overall length: 337 mm (tip: 20 mm) Tip diameter: 2.5 mm (body: 12 mm) Typical distance from probe tip to dipole centers: 1 mm	

5.2.3. Data Acquisition Electronics (DAE)

Model	DAE4	
Construction	Signal amplifier, multiplexer, A/D converter and control logic. Serial optical link for communication with DASY embedded system (fully remote controlled). Two step probe touch detector for mechanical surface detection and emergency robot stop.	
Measurement Range	-100 to +300 mV (16 bit resolution and two range settings: 4mV, 400mV)	
Input Offset Voltage	$< 5\mu$ V (with auto zero)	
Input Bias Current	< 50 fA	
Dimensions	60 x 60 x 68 mm	


5.2.4. Phantoms

Model	Twin SAM	
Construction	The shell corresponds to the specifications of the Specific Anthropomorphic Mannequin (SAM) phantom defined in IEC/IEEE 62209-1528. It enables the dosimetric evaluation of left and right hand phone usage as well as body-mounted usage at the flat phantom region. A cover prevents evaporation of the liquid. Reference markings on the phantom allow the complete setup of all predefined phantom positions and measurement grids by teaching three points with the robot.	
Material	Vinylester, glass fiber reinforced (VE-GF)	
Shell Thickness	2 ± 0.2 mm (6 ± 0.2 mm at ear point)	
Dimensions	Length: 1000 mm Width: 500 mm Height: adjustable feet	
Filling Volume	approx. 25 liters	

Model	ELI	
Construction	The ELI phantom is used for compliance testing of handheld and body-mounted wireless devices in the frequency range of 4 MHz to 10 GHz. ELI is fully compatible with the IEC/IEEE 62209-1528 standard and all known tissue simulating liquids. ELI has been optimized regarding its performance and can be integrated into our standard phantom tables. A cover prevents evaporation of the liquid. Reference markings on the phantom allow installation of the complete setup, including all predefined phantom positions and measurement grids, by teaching three points. The phantom is compatible with all of SPEAG's dosimetric probes and dipoles.	
Material	Vinylester, glass fiber reinforced (VE-GF)	
Shell Thickness	2.0 ± 0.2 mm (bottom plate)	
Dimensions	Major axis: 600 mm Minor axis: 400 mm	
Filling Volume	approx. 30 liters	

5.2.5. Device Holder

Model	Mounting Device	
Construction	In combination with the Twin SAM Phantom or ELI4, the Mounting Device enables the rotation of the mounted transmitter device in spherical coordinates. Rotation point is the ear opening point. Transmitter devices can be easily and accurately positioned according to IEC, IEEE, FCC or other specifications. The device holder can be locked for positioning at different phantom sections (left head, right head, flat).	
Material	POM	


Model	Laptop Extensions Kit	
Construction	Simple but effective and easy-to-use extension for Mounting Device that facilitates the testing of larger devices according to IEC 62209-1528 (e.g., laptops, cameras, etc.). It is lightweight and fits easily on the upper part of the Mounting Device in place of the phone positioner.	
Material	POM, Acrylic glass, Foam	

5.2.6. System Validation Dipoles

Model	D-Serial	
Construction	Symmetrical dipole with 1/4 balun. Enables measurement of feed point impedance with NWA. Matched for use near flat phantoms filled with tissue simulating solutions.	
Frequency	750 MHz to 5800 MHz	
Return Loss	> 20 dB	
Power Capability	> 100 W (f < 1GHz), > 40 W (f > 1GHz)	

5.2.7. Tissue Simulating Liquids

For SAR measurement of the field distribution inside the phantom, the phantom must be filled with homogeneous tissue simulating liquid to a depth of at least 15 cm. For head SAR testing, the liquid height from the ear reference point (ERP) of the phantom to the liquid top surface is larger than 15 cm. For body SAR testing, the liquid height from the center of the flat phantom to the liquid top surface is larger than 15 cm. The nominal dielectric values of the tissue simulating liquids in the phantom and the tolerance of 5% are listed.



The dielectric properties of the head tissue simulating liquids are defined in IEEE 1528, and KDB 865664 D01 Appendix A. For the body tissue simulating liquids, the dielectric properties are defined in KDB 865664 D01 Appendix A. The dielectric properties of the tissue simulating liquids were verified prior to the SAR evaluation using a dielectric assessment kit and a network analyzer.

Targets of Tissue Simulating Liquid

Frequency (MHz)	Target Permittivity	Range of $\pm 5\%$	Target Conductivity	Range of $\pm 5\%$
For Head				
750	41.9	39.8 ~ 44.0	0.89	0.85 ~ 0.93
835	41.5	39.4 ~ 43.6	0.90	0.86 ~ 0.95
900	41.5	39.4 ~ 43.6	0.97	0.92 ~ 1.02
1450	40.5	38.5 ~ 42.5	1.20	1.14 ~ 1.26
1640	40.3	38.3 ~ 42.3	1.29	1.23 ~ 1.35
1750	40.1	38.1 ~ 42.1	1.37	1.30 ~ 1.44
1800	40.0	38.0 ~ 42.0	1.40	1.33 ~ 1.47
1900	40.0	38.0 ~ 42.0	1.40	1.33 ~ 1.47
2000	40.0	38.0 ~ 42.0	1.40	1.33 ~ 1.47
2300	39.5	37.5 ~ 41.5	1.67	1.59 ~ 1.75
2450	39.2	37.2 ~ 41.2	1.80	1.71 ~ 1.89
2600	39.0	37.1 ~ 41.0	1.96	1.86 ~ 2.06
3500	37.9	36.0 ~ 39.8	2.91	2.76 ~ 3.06
5200	36.0	34.2 ~ 37.8	4.66	4.43 ~ 4.89
5300	35.9	34.1 ~ 37.7	4.76	4.52 ~ 5.00
5500	35.6	33.8 ~ 37.4	4.96	4.71 ~ 5.21
5600	35.5	33.7 ~ 37.3	5.07	4.82 ~ 5.32
5800	35.3	33.5 ~ 37.1	5.27	5.01 ~ 5.53

The following table gives the recipes for tissue simulating liquids.

Recipes of Tissue Simulating Liquid


Tissue Type	Bactericide	DGBE	HEC	NaCl	Sucrose	Triton X-100	Water	Diethylene Glycol Mono-hexylether
H750	0.2	-	0.2	1.5	56.0	-	42.1	-
H835	0.2	-	0.2	1.5	57.0	-	41.1	-
H900	0.2	-	0.2	1.4	58.0	-	40.2	-
H1450	-	43.3	-	0.6	-	-	56.1	-
H1640	-	45.8	-	0.5	-	-	53.7	-
H1750	-	47.0	-	0.4	-	-	52.6	-
H1800	-	44.5	-	0.3	-	-	55.2	-
H1900	-	44.5	-	0.2	-	-	55.3	-
H2000	-	44.5	-	0.1	-	-	55.4	-
H2300	-	44.9	-	0.1	-	-	55.0	-
H2450	-	45.0	-	0.1	-	-	54.9	-
H2600	-	45.1	-	0.1	-	-	54.8	-
H3500	-	8.0	-	0.2	-	20.0	71.8	-
H5G	-	-	-	-	-	17.2	65.5	17.3

Simulating Head Liquid (HBBL600-6000MHz), Manufactured by SPEAG:

Water (% by weight)	Esters, Emulsifiers, Inhibitors (% by weight)	Sodium salt (% by weight)
50 - 65%	10 - 30%	8 - 25%

5.2.8.SAR System Verification

The system check verifies that the system operates within its specifications. It is performed daily or before every SAR measurement. The system check uses normal SAR measurements in the flat section of the phantom with a matched dipole at a specified distance. The system verification setup is shown as below.



System Verification Setup

The validation dipole is placed beneath the flat phantom with the specific spacer in place. The distance spacer is touch the phantom surface with a light pressure at the reference marking and be oriented parallel to the long side of the phantom. The spectrum analyzer measures the forward power at the location of the system check dipole connector. The signal generator is adjusted for the desired forward power (250 mW is used for 700 MHz to 3 GHz, 100 mW is used for 3.5 GHz to 6 GHz) at the dipole connector and the power meter is read at that level. After connecting the cable to the dipole, the signal generator is readjusted for the same reading at power meter.

After system check testing, the SAR result will be normalized to 1W forward input power and compared with the reference SAR value derived from validation dipole certificate report. The deviation of system check should be within 10 %.

6. SAR Measurement Procedure

According to the SAR test standard, the recommended procedure for assessing the peak spatial-average SAR value consists of the following steps:

- (a) Power reference measurement
- (b) Area scan
- (c) Zoom scan
- (d) Power drift measurement

The SAR measurement procedures for each of test conditions are as follows:

- (a) Make EUT to transmit maximum output power
- (b) Measure conducted output power through RF cable
- (c) Place the EUT in the specific position of phantom
- (d) Perform SAR testing steps on the DASY system
- (e) Record the SAR value

6.1. Area & Zoom Scan Procedure

First Area Scan is used to locate the approximate location(s) of the local peak SAR value(s). The measurement grid within an Area Scan is defined by the grid extent, grid step size and grid offset. Next, in order to determine the EM field distribution in a three-dimensional spatial extension, Zoom Scan is required. The Zoom Scan is performed around the highest E-field value to determine the averaged SAR-distribution over 10 g. According to KDB 865664 D01, the resolution for Area and Zoom scan is specified in the table below.

Items	<= 2 GHz	2-3 GHz	3-4 GHz	4-5 GHz	5-6 GHz
Area Scan ($\Delta x, \Delta y$)	<= 15 mm	<= 12 mm	<= 12 mm	<= 10 mm	<= 10 mm
Zoom Scan ($\Delta x, \Delta y$)	<= 8 mm	<= 5 mm	<= 5 mm	<= 4 mm	<= 4 mm
Zoom Scan (Δz)	<= 5 mm	<= 5 mm	<= 4 mm	<= 3 mm	<= 2 mm
Zoom Scan Volume	>= 30 mm	>= 30 mm	>= 28 mm	>= 25 mm	>= 22 mm

Note:

When zoom scan is required and report SAR is <= 1.4 W/kg, the zoom scan resolution of $\Delta x / \Delta y$ (2-3GHz: <= 8 mm, 3-4GHz: <= 7 mm, 4-6GHz: <= 5 mm) may be applied.

6.2. Volume Scan Procedure

The volume scan is used for assess overlapping SAR distributions for antennas transmitting in different frequency bands. It is equivalent to an oversized zoom scan used in standalone measurements. The measurement volume will be used to enclose all the simultaneous transmitting antennas. For antennas transmitting simultaneously in different frequency bands, the volume scan is measured separately in each frequency band. In order to sum correctly to compute the 1g aggregate SAR, the EUT remain in the same test position for all measurements and all volume scan use the same spatial resolution and grid spacing. When all volume scan were completed, the software, SEMCAD postprocessor can combine and subsequently superpose these measurement data to calculating the multiband SAR.

6.3. Power Drift Monitoring

All SAR testing is under the EUT install full charged battery and transmit maximum output power. In DASY measurement software, the power reference measurement and power drift measurement procedures are used for monitoring the power drift of EUT during SAR test. Both these procedures measure the field at a specified reference position before and after the SAR testing. The software will calculate the field difference in dB. If the power drift more than 5%, the SAR will be retested.

6.4. Spatial Peak SAR Evaluation

The procedure for spatial peak SAR evaluation has been implemented according to the test standard. It can be conducted for 1g and 10g, as well as for user-specific masses. The DASY software includes all numerical procedures necessary to evaluate the spatial peak SAR value.

The base for the evaluation is a "cube" measurement. The measured volume must include the 1g and 10g cubes with the highest averaged SAR values. For that purpose, the center of the measured volume is aligned to the interpolated peak SAR value of a previously performed area scan.

The entire evaluation of the spatial peak values is performed within the post-processing engine (SEMCAD). The system always gives the maximum values for the 1g and 10g cubes. The algorithm to find the cube with highest averaged SAR is divided into the following stages:

- (a) Extraction of the measured data (grid and values) from the Zoom Scan
- (b) Calculation of the SAR value at every measurement point based on all stored data (A/D values and measurement parameters)
- (c) Generation of a high-resolution mesh within the measured volume
- (d) Interpolation of all measured values from the measurement grid to the high-resolution grid
- (e) Extrapolation of the entire 3-D field distribution to the phantom surface over the distance from sensor to surface
- (f) Calculation of the averaged SAR within masses of 1g and 10g

6.5. SAR Averaged Methods

In DASY, the interpolation and extrapolation are both based on the modified Quadratic Shepard's method. The interpolation scheme combines a least-square fitted function method and a weighted average method which are the two basic types of computational interpolation and approximation.

Extrapolation routines are used to obtain SAR values between the lowest measurement points and the inner phantom surface. The extrapolation distance is determined by the surface detection distance and the probe sensor offset. The uncertainty increases with the extrapolation distance. To keep the uncertainty within 1% for the 1 g and 10 g cubes, the extrapolation distance should not be larger than 5 mm.

7. SAR Measurement Evaluation

7.1. EUT Configuration and Setting

<Considerations Related to WLAN for Setup and Testing>

In general, various vendor specific external test software and chipset based internal test modes are typically used for SAR measurement. These chipset based test mode utilities are generally hardware and manufacturer dependent, and often include substantial flexibility to reconfigure or reprogram a device. A Wi-Fi device must be configured to transmit continuously at the required data rate, channel bandwidth and signal modulation, using the highest transmission duty factor supported by the test mode tools for SAR measurement. The test frequencies established using test mode must correspond to the actual channel frequencies. When 802.11 frame gaps are accounted for in the transmission, a maximum transmission duty factor of 92 - 96% is typically achievable in most test mode configurations. A minimum transmission duty factor of 85% is required to avoid certain hardware and device implementation issues related to wide range SAR scaling. In addition, a periodic transmission duty factor is required for current generation SAR systems to measure SAR correctly. The reported SAR must be scaled to 100% transmission duty factor to determine compliance at the maximum tune-up tolerance limit.

According to KDB 248227 D01, this device has installed WLAN engineering testing software which can provide continuous transmitting RF signal. During WLAN SAR testing, this device was operated to transmit continuously at the maximum transmission duty with specified transmission mode, operating frequency, lowest data rate, and maximum output power.

Initial Test Configuration

An initial test configuration is determined for OFDM transmission modes in 2.4 GHz and 5 GHz bands according to the channel bandwidth, modulation and data rate combination(s) with the highest maximum output power specified for production units in each standalone and aggregated frequency band. When the same maximum power is specified for multiple transmission modes in a frequency band, the largest channel bandwidth, lowest order modulation, lowest data rate and lowest order 802.11a/g/n/ac mode is used for SAR measurement, on the highest measured output power channel in the initial test configuration, for each frequency band.

Subsequent Test Configuration

SAR measurement requirements for the remaining 802.11 transmission mode configurations that have not been tested in the initial test configuration are determined separately for each standalone and aggregated frequency band, in each exposure condition, according to the maximum output power specified for production units. Additional power measurements may be required to determine if SAR measurements are required for subsequent highest output power channels in a subsequent test configuration. When the highest reported SAR for the initial test configuration according to the initial test position or fixed exposure position requirements, is adjusted by the ratio of the subsequent test configuration to initial test configuration specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg, SAR is not required for that subsequent test configuration.

SAR Test Configuration and Channel Selection

When multiple channel bandwidth configurations in a frequency band have the same specified maximum output power, the initial test configuration is using largest channel bandwidth, lowest order modulation, lowest data rate, and lowest order 802.11 mode (i.e., 802.11a is chosen over 802.11n then 802.11ac or 802.11g is

chosen over 802.11n). After an initial test configuration is determined, if multiple test channels have the same measured maximum output power, the channel chosen for SAR measurement is determined according to the following.

- 1) The channel closest to mid-band frequency is selected for SAR measurement.
- 2) For channels with equal separation from mid-band frequency; for example, high and low channels or two mid-band channels, the higher frequency (number) channel is selected for SAR measurement.

<Considerations Related to Bluetooth for Setup and Testing>

This device has installed Bluetooth engineering testing software which can provide continuous transmitting RF signal. During Bluetooth SAR testing, this device was operated to transmit continuously at the maximum transmission duty with specified transmission mode, operating frequency, lowest data rate, and maximum output power.

<Considerations Related to SDR for Setup and Testing>


This equipment SDR technology SAR test reference 248227 D01 802 11 Wi-Fi SAR

This device has installed SDR engineering testing software which can provide continuous transmitting RF signal. During SDR SAR testing, this device was operated to transmit continuously at the maximum transmission duty with specified transmission mode, operating frequency, lowest data rate, and maximum output power.

7.2. EUT Testing Position

7.2.1. Extremity Exposure Conditions

For this remote control device, SAR evaluation is required on all sides and edges at 0 mm separation from a flat phantom. The 10-g extremity SAR test exclusions may be applied.



<External, Swivel or Rotating Antennas>

For external antennas or antennas that may swivel or rotate, a KDB inquiry should be submitted to the FCC Laboratory to determine the applicable test configurations. The inquiry should identify if the antenna may transmit in its stowed position, and if a swivel or rotating connector is also used. Depending on the antenna configurations used in the individual dongle design and its operating configurations, different test separation distances may apply and must be determined on a case-by-case basis.

7.3. SAR Test Exclusion Evaluations

According to KDB 447498 D01, the SAR test exclusion condition is based on source-based time-averaged maximum conducted output power, adjusted for tune-up tolerance, and the minimum test separation distance required for the exposure conditions. The SAR exclusion threshold is determined by the following formula.

1. For the test separation distance ≤ 50 mm

$$\frac{\text{Max. Tune up Power}_{(mW)}}{\text{Min. Test Separation Distance}_{(mm)}} \times \sqrt{f_{(GHz)}} \leq 3.0 \text{ for SAR-1g, } \leq 7.5 \text{ for SAR-10g}$$

When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

2. For the test separation distance > 50 mm, and the frequency at 100 MHz to 1500 MHz

$$\left[(\text{Threshold at 50 mm in Step 1}) + (\text{Test Separation Distance} - 50 \text{ mm}) \times \left(\frac{f_{(MHz)}}{150} \right) \right]_{(mW)}$$

3. For the test separation distance > 50 mm, and the frequency at > 1500 MHz to 6 GHz

$$[(\text{Threshold at 50 mm in Step 1}) + (\text{Test Separation Distance} - 50 \text{ mm}) \times 10]_{(mW)}$$

<For WLAN Ant-0/BT>

Mode	Max. Tune-up Power (dBm)	Max. Tune-up Power (mW)	Front Face			Rear Face			Left Side			Right Side			Top Side			Bottom Side		
			Ant. to Surface (mm)	Calculated Result	Require SAR Testing?	Ant. to Surface (mm)	Calculated Result	Require SAR Testing?	Ant. to Surface (mm)	Calculated Result	Require SAR Testing?	Ant. to Surface (mm)	Calculated Result							
WLAN 2.4G	17.5	56.23	3.78	17.6	YES	33.38	2.6	No	22.6	3.9	No	139.18	987 mW	No	51.23	108 mW	No	63.5	231 mW	No
WLAN 5.2G	21.5	141.25	3.78	64.7	YES	33.38	9.7	YES	22.6	14.3	YES	139.18	957 mW	No	51.23	78 mW	YES	63.5	201 mW	No
WLAN 5.8G	21.5	141.25	3.78	68.2	YES	33.38	10.2	YES	22.6	15.1	YES	139.18	954 mW	No	51.23	74 mW	YES	63.5	197 mW	No
BT	2.5	1.78	3.78	0.6	No	33.38	0.1	No	22.6	0.1	No	139.18	987 mW	No	51.23	108 mW	No	63.5	230 mW	No

<For WLAN Ant-1>

Mode	Max. Tune-up Power (dBm)	Max. Tune-up Power (mW)	Front Face			Rear Face			Left Side			Right Side			Top Side			Bottom Side		
			Ant. to Surface (mm)	Calculated Result	Require SAR Testing?	Ant. to Surface (mm)	Calculated Result	Require SAR Testing?	Ant. to Surface (mm)	Calculated Result	Require SAR Testing?	Ant. to Surface (mm)	Calculated Result							
WLAN 2.4G	17.5	56.23	3.78	17.6	YES	33.38	2.6	No	139.18	987 mW	No	22.6	3.9	No	51.23	108 mW	No	63.5	231 mW	No
WLAN 5.2G	21.5	141.25	3.78	64.7	YES	33.38	9.7	YES	139.18	957 mW	No	22.6	14.3	YES	51.23	78 mW	YES	63.5	201 mW	No
WLAN 5.8G	21.5	141.25	3.78	68.2	YES	33.38	10.2	YES	139.18	954 mW	No	22.6	15.1	YES	51.23	74 mW	YES	63.5	197 mW	No

<For SDR Ant-0>

Mode	Max. Tune-up Power (dBm)	Max. Tune-up Power (mW)	Front Face			Rear Face			Left Side			Right Side			Top Side			Bottom Side		
			Ant. to Surface (mm)	Calculated Result	Require SAR Testing?	Ant. to Surface (mm)	Calculated Result	Require SAR Testing?	Ant. to Surface (mm)	Calculated Result	Require SAR Testing?	Ant. to Surface (mm)	Calculated Result							
SDR 2.4G	27.5	562.34	23.06	38.3	YES	42.46	20.8	YES	44.28	19.9	YES	125.15	847 mW	No	0	176.5	YES	130	896 mW	No
SDR 5.1G	20.0	100	23.06	9.9	YES	42.46	5.4	No	44.28	5.2	No	125.15	817 mW	No	0	45.8	YES	130	866 mW	No
SDR 5.8G	29.0	794.33	23.06	83.1	YES	42.46	45.2	YES	44.28	43.3	YES	125.15	814 mW	No	0	383.4	YES	130	862 mW	No

<For SDR Ant-1>

Mode	Max. Tune-up Power (dBm)	Max. Tune-up Power (mW)	Front Face			Rear Face			Left Side			Right Side			Top Side			Bottom Side		
			Ant. to Surface (mm)	Calculated Result	Require SAR Testing?	Ant. to Surface (mm)	Calculated Result	Require SAR Testing?	Ant. to Surface (mm)	Calculated Result	Require SAR Testing?	Ant. to Surface (mm)	Calculated Result							
SDR 2.4G	27.5	562.34	23.06	38.3	YES	42.46	20.8	YES	125.1	847	No	44.26	19.9	YES	0	176.5	YES	130	896	No
SDR 5.1G	20.0	100	23.06	9.9	YES	42.46	5.4	No	125.1	817	No	44.26	5.2	No	0	45.8	YES	130	866	No
SDR 5.8G	29.0	794.33	23.06	83.1	YES	42.46	45.2	YES	125.1	814	No	44.26	43.3	YES	0	383.4	YES	130	862	No

<For SDR Ant-4>

Mode	Max. Tune-up Power (dBm)	Max. Tune-up Power (mW)	Front Face			Rear Face			Left Side			Right Side			Top Side			Bottom Side		
			Ant. to Surface (mm)	Calculated Result	Require SAR Testing?	Ant. to Surface (mm)	Calculated Result	Require SAR Testing?	Ant. to Surface (mm)	Calculated Result	Require SAR Testing?	Ant. to Surface (mm)	Calculated Result							
SDR 2.4G	27.5	562.34	10	88.2	YES	10	88.2	YES	30.29	29.1	YES	30.72	28.7	YES	3.12	176.5	YES	103.3	629	No
SDR 5.1G	20.0	100	10	22.9	YES	10	22.9	YES	30.29	7.6	YES	30.72	7.5	No	3.12	45.8	YES	103.3	599	No
SDR 5.8G	29.0	794.33	10	191.7	YES	10	191.7	YES	30.29	63.3	YES	30.72	62.4	YES	3.12	383.4	YES	103.3	595	YES

<For SDR Ant-5>

Mode	Max. Tune-up Power (dBm)	Max. Tune-up Power (mW)	Front Face			Rear Face			Left Side			Right Side			Top Side			Bottom Side		
			Ant. to Surface (mm)	Calculated Result	Require SAR Testing?	Ant. to Surface (mm)	Calculated Result	Require SAR Testing?	Ant. to Surface (mm)	Calculated Result	Require SAR Testing?	Ant. to Surface (mm)	Calculated Result							
SDR 2.4G	27.5	562.34	10	88.2	YES	10	88.2	YES	30.29	29.1	YES	30.72	28.7	YES	3.12	176.5	YES	103.3	629	No
SDR 5.1G	20.0	100	10	22.9	YES	10	22.9	YES	30.29	7.6	YES	30.72	7.5	No	3.12	45.8	YES	103.3	599	No
SDR 5.8G	29.0	794.33	10	191.7	YES	10	191.7	YES	30.29	63.3	YES	30.72	62.4	YES	3.12	383.4	YES	103.3	595	YES

<For SDR Ant-6>

Mode	Max. Tune-up Power (dBm)	Max. Tune-up Power (mW)	Front Face			Rear Face			Left Side			Right Side			Top Side			Bottom Side		
			Ant. to Surface (mm)	Calculated Result	Require SAR Testing?	Ant. to Surface (mm)	Calculated Result	Require SAR Testing?	Ant. to Surface (mm)	Calculated Result	Require SAR Testing?	Ant. to Surface (mm)	Calculated Result							
SDR 2.4G	27.5	562.34	2.87	176.5	YES	39.46	22.4	YES	27.34	32.3	YES	136.2	958	No	89.7	493	YES	10.49	84.1	YES
SDR 5.1G	20.0	100	2.87	45.8	YES	39.46	5.8	No	27.34	8.4	YES	136.2	928	No	89.7	463	No	10.49	21.8	YES
SDR 5.8G	29.0	794.33	2.87	383.4	YES	39.46	48.6	YES	27.34	70.1	YES	136.2	925	No	89.7	459	YES	10.49	182.8	YES

7.4. Simultaneous Transmission Possibilities

The simultaneous transmission possibilities for this device are listed as below.

Simultaneous TX Combination	Capable Transmit Configurations	Extremity
1	SDR-2.4G+NII+DSS	Yes
2	SDR-5.1G+DTS+DSS	Yes
3	SDR-5.1G+WLAN 5.8G+DSS	Yes
4	SDR-5.8G+DTS+DSS	Yes
5	SDR-5.8G+WLAN 5.2G+DSS	Yes

Note :

1. The 2.4G WLAN and 5G WLAN cannot transmit simultaneously.
2. The SDR has five antennas, Only two antennas can work at the same time. The combination is as follows **【ANT0, ANT1】** , **【ANT0, ANT5】** , **【ANT4, ANT1】** , **【ANT4, ANT5】** , **【ANT6, ANT1】** , **【ANT6, ANT5】**
3. The WLAN and Bluetooth cannot transmit simultaneously, so there is no co-location test requirement for WLAN and Bluetooth.

7.5. Tissue Verification

The measuring results for tissue simulating liquid are shown as below.

Test Date	Tissue Type	Frequency (MHz)	Measured Conductivity (σ)	Measured Permittivity (ϵ_r)	Target Conductivity (σ)	Target Permittivity (ϵ_r)	Conductivity Deviation (%)	Permittivity Deviation (%)
Jul. 17, 2024	H2450	2450	1.844	39.408	1.80	39.20	2.44	0.53
		2437	1.829	39.466	1.79	39.22	2.29	0.63
		2437.5	1.830	39.463	1.79	39.22	2.29	0.62
Jul. 18, 2024	H5G	5250	4.561	37.438	4.71	35.90	-3.16	4.28
		5210	4.523	37.557	4.67	35.99	-3.15	4.35
		5220	4.538	37.520	4.68	35.98	-3.03	4.28
Jul. 19, 2024	H5G	5800	5.145	36.469	5.27	35.30	-2.37	3.31
		5735.5	5.093	36.605	5.21	35.36	-2.15	3.52
		5755	5.109	36.551	5.23	35.34	-2.22	3.43
		5795	5.143	36.459	5.27	35.30	-2.32	3.28

Note:

The dielectric properties of the tissue simulating liquid must be measured within 24 hours before the SAR testing and within $\pm 5\%$ of the target values. Liquid temperature during the SAR testing must be within $\pm 2^\circ\text{C}$.

7.6. System Validation

The SAR measurement system was validated according to procedures in KDB 865664 D01. The validation status in tabulated summary is as below.

Test Date	Probe S/N	Calibration Point	Measured Conductivity (σ)	Measured Permittivity (ϵ_r)	Validation for CW			Validation for Modulation		
					Sensitivity Range	Probe Linearity	Probe Isotropy	Modulation Type	Duty Factor	PAR
Jul. 17, 2024	7738	Head 2450	1.844	39.408	Pass	Pass	Pass	OFDM	N/A	Pass
Jul. 18, 2024	7738	Head 5250	4.561	37.438	Pass	Pass	Pass	OFDM	N/A	Pass
Jul. 19, 2024	7738	Head 5800	5.145	36.469	Pass	Pass	Pass	OFDM	N/A	Pass

7.7. System Verification

The measuring result for system verification is tabulated as below.

Test Date	Frequency (MHz)	1W Target SAR-1g (W/kg)	Measured SAR-1g (W/kg)	Normalized to 1W SAR-1g (W/kg)	Deviation (%)	Dipole S/N	Probe S/N	DAE S/N
Jul. 17, 2024	2450	53.40	12.50	50.00	-6.37	1014	7738	1725
Jul. 18, 2024	5250	79.30	7.62	76.20	-3.91	1280	7738	1725
Jul. 19, 2024	5800	80.70	7.96	79.60	-1.36	1280	7738	1725

Note:

Comparing to the reference SAR value provided by SPEAG, the validation data should be within its specification of 10 %. The result indicates the system check can meet the variation criterion and the plots can be referred to Appendix A of this report.

8. SAR Measurement Evaluation

8.1. Maximum Conducted Power

All Rate have been tested, the Worst average power (Unit: dBm) is shown as below.

<WLAN 2.4G SISO>

Mode	Frequency (MHz)	Average power (ANT0&ANT1)	Tune-up
11B	2412	16.64	17.0
	2437	17.13	
	2462	16.79	
11G	2412	16.52	17.0
	2437	16.68	
	2462	16.55	
11N20	2412	16.70	17.0
	2437	16.80	
	2462	16.58	
11N40	2422	17.09	17.0
	2437	17.04	
	2452	16.56	
11AX20	2412	16.98	17.0
	2437	16.76	
	2462	16.65	
11AX40	2422	16.97	17.0
	2437	16.96	
	2452	16.62	

<WLAN 2.4G MIMO>

Mode	Frequency (MHz)	Average power (MIMO)	Tune-up
11G	2412	16.82	17.0
	2437	16.73	
	2462	16.85	
11N20	2412	16.86	17.0
	2437	16.52	
	2462	16.72	
11N40	2422	16.54	17.0
	2437	16.57	
	2452	16.65	
11AX20	2412	16.53	17.0
	2437	16.77	
	2462	16.51	
11AX40	2422	16.82	17.0
	2437	16.73	

	2452	16.85	
--	------	-------	--

<WLAN 5.2G_SISO>

Mode	Channal	Frequency (MHz)	Average power (ANT0&ANT1)	Tune-up
11a	36	5180	19.52	20.0
	40	5200	19.49	
	48	5240	19.53	
11n20	36	5180	19.46	20.0
	40	5200	19.64	
	48	5240	19.78	
11ac20	36	5180	20.31	20.5
	40	5200	20.15	
	48	5240	19.71	
11ax20	36	5180	20.44	20.5
	40	5200	20.05	
	48	5240	19.60	
11n40	38	5190	20.78	21.0
	46	5230	20.68	
11ac40	38	5190	20.74	21.0
	46	5230	20.66	
11ax40	38	5190	20.50	21.0
	46	5230	20.82	
11ac80	42	5210	20.93	21.5
11ax80	42	5210	21.01	21.5

<WLAN 5.2G_MIMO>

Mode	Channal	Frequency (MHz)	Average power (MIMO)	Tune-up
11n20	36	5180	19.62	20.0
	40	5200	19.47	
	48	5240	19.45	
11ac20	36	5180	19.49	20.0
	40	5200	19.49	
	48	5240	19.44	
11ax20	36	5180	19.86	20.0
	40	5200	19.76	
	48	5240	19.67	
11n40	38	5190	20.63	21.0

	46	5230	20.64	
11ac40	38	5190	20.72	21.0
	46	5230	20.50	
11ax40	38	5190	20.95	21.0
	46	5230	20.75	
11ac80	42	5210	20.65	21.0
11ax80	42	5210	20.53	21.0

<WLAN 5.8G_SISO>

Mode	Channal	Frequency (MHz)	Average power (ANT0&ANT1)	Tune-up
11a	149	5745	21.00	21.5
	157	5785	20.56	
	165	5825	20.55	
11n20	149	5745	20.95	21.5
	157	5785	20.69	
	165	5825	20.98	
11ac20	149	5745	20.80	21.0
	157	5785	20.69	
	165	5825	20.58	
11ax20	149	5745	20.96	21.5
	157	5785	20.77	
	165	5825	20.83	
11n40	151	5755	20.71	21.0
	159	5795	20.67	
11ac40	151	5755	20.60	21.5
	159	5795	21.01	
11ax40	151	5755	20.93	21.5
	159	5795	21.03	
11ac80	155	5775	20.58	21.0
11ax80	155	5775	20.52	21.0

<WLAN 5.8G_MIMO>

Mode	Channal	Frequency (MHz)	Average power (MIMO)	Tune-up
11n20	149	5745	20.82	21.0
	157	5785	20.55	
	165	5825	20.79	
11ac20	149	5745	20.58	21.0
	157	5785	20.58	
	165	5825	20.69	
11ax20	149	5745	20.98	21.5
	157	5785	20.75	
	165	5825	21.06	
11n40	151	5755	20.82	21.5
	159	5795	20.96	
11ac40	151	5755	20.86	21.5
	159	5795	21.03	
11ax40	151	5755	20.67	21.0
	159	5795	20.67	
11ac80	155	5775	20.64	21.0
11ax80	155	5775	20.52	21.0

<Bluetooth>

Mode	Frequency (MHz)	Average power	Tune-up
BT_DH5	2402	0.37	1.0
	2441	2.35	2.5
	2480	0.93	1.5
BT_3DH5	2402	-3.18	-3.0
	2441	-1.04	-0.5
	2480	-2.56	-2.0
BLE_1M	2402	0.23	0.5
	2440	2.24	2.5
	2480	0.81	1.0
BLE_2M	2402	0.19	0.5
	2440	2.26	2.5
	2480	0.82	1.0

<SDR 2.4G>

Test case	Channel	Average power (MIMO)	Tune-up
SDR 1.4M	2403.5	24.58	25.0
	2435.5	24.69	
	2469.12	24.75	
SDR 3M	2405.5	27.19	28.0
	2435.5	27.46	
	2468.2	27.49	
SDR 5M	2404.5	27.22	27.5
	2434.5	27.14	
	2469.5	27.20	
SDR 10MHz	2407.5	26.42	27.0
	2437.5	27.12	27.5
	2467.5	25.03	25.5
SDR 20MHz	2412.5	26.42	27.5
	2437.5	27.29	
	2462.5	26.77	
SDR 40MHz	2422.5	23.88	24.0
	2437.5	27.37	27.5
	2452.5	24.95	25.5
SDR 60MHz	2432.5	22.85	23.5
	2437.5	25.22	26.0
	2442.5	25.40	

<SDR 5.1G>

Testcase	Channel	Average power (MIMO)	Tune-up
SDR 10MHz	5157	7.71	8.0
	5169	17.42	17.5
	5200	19.23	19.5
	5245	19.09	
SDR 20MHz	5161	8.14	8.5
	5169	17.30	17.5
	5200	19.36	19.5
	5240	19.17	
SDR 40MHz	5170	11.43	12.0
	5186	16.70	17.0
	5200	19.37	20.0
	5230	19.50	

SDR 60MHz	5180	13.69	14.0
	5185	16.66	17.0
	5200	19.22	20.0
	5220	19.58	
SDR 80MHz	5190	13.83	14.5
	5192	15.00	15.5
	5200	17.39	17.5
	5210	19.38	19.5

<SDR 5.8G>

Testcase	Channel	Average power (MIMO)	Tune-up
SDR 1.4M	5728.5	27.89	28.5
	5784.5	27.92	
	5846.12	27.73	
SDR 3M	5727.5	27.82	28.5
	5784.5	27.78	
	5847.2	27.96	
SDR 5M	5732.5	27.98	28.5
	5787.5	27.99	
	5842.5	27.73	
SDR 10MHz	5730.5	28.49	29.0
	5787.5	28.37	
	5844.5	28.38	
SDR 20MHz	5735.5	28.36	29.0
	5787.5	28.33	
	5839.5	27.50	
SDR 40MHz	5745.5	23.15	23.5
	5787.5	25.46	26.0
	5829.5	22.37	22.5
SDR 60MHz	5755.5	23.57	24.5
	5787.5	23.98	
	5819.5	23.82	
SDR 80MHz	5765.5	23.59	24.5
	5787.5	23.86	
	5809.5	23.80	

8.2. SAR Testing Results

8.2.1. SAR Test Reduction Considerations

<KDB 447498 D01, General RF Exposure Guidance>

Testing of other required channels within the operating mode of a frequency band is not required when the reported SAR for the mid-band or highest output power channel is:

- (1) ≤ 0.8 W/kg or 2.0 W/kg, for 1-g or 10-g respectively, when the transmission band is ≤ 100 MHz
- (2) ≤ 0.6 W/kg or 1.5 W/kg, for 1-g or 10-g respectively, when the transmission band is between 100 MHz and 200 MHz
- (3) ≤ 0.4 W/kg or 1.0 W/kg, for 1-g or 10-g respectively, when the transmission band is ≥ 200 MHz

<KDB 248227 D01, SAR Guidance for Wi-Fi Transmitters>

- (1) For handsets operating next to ear, hotspot mode or mini-tablet configurations, the initial test position procedures were applied. The test position with the highest extrapolated peak SAR will be used as the initial test position. When the reported SAR of initial test position is ≤ 0.4 W/kg, SAR testing for remaining test positions is not required. Otherwise, SAR is evaluated at the subsequent highest peak SAR positions until the reported SAR result is ≤ 0.8 W/kg or all test positions are measured.
- (2) For WLAN 2.4 GHz, the highest measured maximum output power channel for DSSS was selected for SAR measurement. When the reported SAR is ≤ 0.8 W/kg, no further SAR testing is required. Otherwise, SAR is evaluated at the next highest measured output power channel. When any reported SAR is > 1.2 W/kg, SAR is required for the third channel. For OFDM modes (802.11g/n), SAR is not required when the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and it is ≤ 1.2 W/kg.
- (3) For WLAN 5 GHz, the initial test configuration was selected according to the transmission mode with the highest maximum output power. When the reported SAR of initial test configuration is > 0.8 W/kg, SAR is required for the subsequent highest measured output power channel until the reported SAR result is ≤ 1.2 W/kg or all required channels are measured. For other transmission modes, SAR is not required when the highest reported SAR for initial test configuration is adjusted by the ratio of subsequent test configuration to initial test configuration specified maximum output power and it is ≤ 1.2 W/kg.
- (4) For WLAN MIMO mode, the power-based standalone SAR test exclusion or the sum of SAR provision in KDB 447498 to determine simultaneous transmission SAR test exclusion should be applied. Otherwise, SAR for MIMO mode will be measured with all applicable antennas transmitting simultaneously at the specified maximum output power of MIMO operation.

8.2.3.SAR Results for Extremity Exposure Condition (Separation Distance is 0 cm Gap)

Plot No.	Band	Mode	Test Position	Ch.	Fre.	Antenna	Normal Duty Cycle	Max. Tune-up Power (dBm)	Measured Conducted Power (dBm)	Scaling Factor	Power Drift (dB)	Measured SAR-10g (W/kg)	Scaled SAR-10g (W/kg)
<input type="checkbox"/>	SDR2.4G	40M	Front Face	Mid	2437.5	0 H	10.0%	27.5	27.37	1.03	0.07	0.303	0.03
<input type="checkbox"/>	SDR2.4G	40M	Front Face	Mid	2437.5	0 V	10.0%	27.5	27.37	1.03	-0.06	0.072	0.01
<input type="checkbox"/>	SDR2.4G	40M	Rear Face	Mid	2437.5	0 H	10.0%	27.5	27.37	1.03	-0.09	0.111	0.01
<input type="checkbox"/>	SDR2.4G	40M	Rear Face	Mid	2437.5	0 V	10.0%	27.5	27.37	1.03	-0.14	0.144	0.01
<input type="checkbox"/>	SDR2.4G	40M	Left Side	Mid	2437.5	0 H	10.0%	27.5	27.37	1.03	0.00	<0.01	<0.01
<input type="checkbox"/>	SDR2.4G	40M	Left Side	Mid	2437.5	0 V	10.0%	27.5	27.37	1.03	0.00	<0.01	<0.01
<input type="checkbox"/>	SDR2.4G	40M	Top Side	Mid	2437.5	0 H	10.0%	27.5	27.37	1.03	0.02	2.68	0.28
<input type="checkbox"/>	SDR2.4G	40M	Top Side	Mid	2437.5	0 V	10.0%	27.5	27.37	1.03	0.06	1.08	0.11
<input type="checkbox"/>	SDR2.4G	40M	Front Face	Mid	2437.5	1 H	10.0%	27.5	27.37	1.03	-0.08	0.471	0.05
<input type="checkbox"/>	SDR2.4G	40M	Front Face	Mid	2437.5	1 V	10.0%	27.5	27.37	1.03	0.04	0.14	0.01
<input type="checkbox"/>	SDR2.4G	40M	Rear Face	Mid	2437.5	1 H	10.0%	27.5	27.37	1.03	0.13	0.151	0.02
<input type="checkbox"/>	SDR2.4G	40M	Rear Face	Mid	2437.5	1 V	10.0%	27.5	27.37	1.03	0.05	0.312	0.03
<input type="checkbox"/>	SDR2.4G	40M	Right Side	Mid	2437.5	1_H	10.0%	27.5	27.37	1.03	0.00	<0.01	<0.01
<input type="checkbox"/>	SDR2.4G	40M	Right Side	Mid	2437.5	1_V	10.0%	27.5	27.37	1.03	0.00	<0.01	<0.01
<input type="checkbox"/>	SDR2.4G	40M	Top Side	Mid	2437.5	1 H	10.0%	27.5	27.37	1.03	-0.03	3.97	0.41
<input type="checkbox"/>	SDR2.4G	40M	Top Side	Mid	2437.5	1 V	10.0%	27.5	27.37	1.03	-0.06	3.95	0.41
<input type="checkbox"/>	SDR2.4G	40M	Front Face	Mid	2437.5	4	10.0%	27.5	27.37	1.03	-0.09	0.027	0.00
<input type="checkbox"/>	SDR2.4G	40M	Rear Face	Mid	2437.5	4	10.0%	27.5	27.37	1.03	-0.01	0.173	0.02
<input type="checkbox"/>	SDR2.4G	40M	Left Side	Mid	2437.5	4	10.0%	27.5	27.37	1.03	-0.01	0.013	0.00
<input type="checkbox"/>	SDR2.4G	40M	Right Side	Mid	2437.5	4	10.0%	27.5	27.37	1.03	0.00	<0.01	<0.01
<input type="checkbox"/>	SDR2.4G	40M	Top Side	Mid	2437.5	4	10.0%	27.5	27.37	1.03	-0.08	0.098	0.01
<input type="checkbox"/>	SDR2.4G	40M	Front Face	Mid	2437.5	5	10.0%	27.5	27.37	1.03	-0.07	0.1	0.01
<input type="checkbox"/>	SDR2.4G	40M	Rear Face	Mid	2437.5	5	10.0%	27.5	27.37	1.03	-0.03	0.729	0.08
<input type="checkbox"/>	SDR2.4G	40M	Left Side	Mid	2437.5	5	10.0%	27.5	27.37	1.03	0.00	<0.01	<0.01
<input type="checkbox"/>	SDR2.4G	40M	Right Side	Mid	2437.5	5	10.0%	27.5	27.37	1.03	0.00	<0.01	<0.01
<input type="checkbox"/>	SDR2.4G	40M	Top Side	Mid	2437.5	5	10.0%	27.5	27.37	1.03	-0.09	0.019	0.00
1	SDR2.4G	40M	Front Face	Mid	2437.5	6	10.0%	27.5	27.37	1.03	-0.05	6.55	0.67
<input type="checkbox"/>	SDR2.4G	40M	Rear Face	Mid	2437.5	6	10.0%	27.5	27.37	1.03	-0.09	0.049	0.01
<input type="checkbox"/>	SDR2.4G	40M	Left Side	Mid	2437.5	6	10.0%	27.5	27.37	1.03	0.10	0.236	0.02
<input type="checkbox"/>	SDR2.4G	40M	Top Side	Mid	2437.5	6	10.0%	27.5	27.37	1.03	0.00	<0.01	<0.01
<input type="checkbox"/>	SDR2.4G	40M	Bottom Side	Mid	2437.5	6	10.0%	27.5	27.37	1.03	-0.15	1.9	0.20
<input type="checkbox"/>	SDR2.4G	40M	Front Face	Mid	2437.5	6	10.0%	27.5	27.37	1.03	0.02	6.34	0.65
<input type="checkbox"/>	SDR-5.1G	60M	Front Face	High	5220	0 H	10.0%	20.0	19.58	1.10	-0.09	0.152	0.02
<input type="checkbox"/>	SDR-5.1G	60M	Front Face	High	5220	0 V	10.0%	20.0	19.58	1.10	0.02	0.057	0.01
<input type="checkbox"/>	SDR-5.1G	60M	Rear Face	High	5220	0 H	10.0%	20.0	19.58	1.10	-0.02	0.265	0.03
<input type="checkbox"/>	SDR-5.1G	60M	Rear Face	High	5220	0 V	10.0%	20.0	19.58	1.10	-0.02	0.086	0.01
<input type="checkbox"/>	SDR-5.1G	60M	Top Side	High	5220	0 H	10.0%	20.0	19.58	1.10	0.08	0.495	0.05
<input type="checkbox"/>	SDR-5.1G	60M	Top Side	High	5220	0 V	10.0%	20.0	19.58	1.10	-0.08	0.899	0.10
<input type="checkbox"/>	SDR-5.1G	60M	Front Face	High	5220	1 H	10.0%	20.0	19.58	1.10	-0.05	0.251	0.03
<input type="checkbox"/>	SDR-5.1G	60M	Front Face	High	5220	1 V	10.0%	20.0	19.58	1.10	0.02	0.204	0.02
<input type="checkbox"/>	SDR-5.1G	60M	Rear Face	High	5220	1 H	10.0%	20.0	19.58	1.10	-0.08	0.067	0.01
<input type="checkbox"/>	SDR-5.1G	60M	Rear Face	High	5220	1 V	10.0%	20.0	19.58	1.10	0.02	0.065	0.01
2	SDR-5.1G	60M	Top Side	High	5220	1 H	10.0%	20.0	19.58	1.10	-0.03	4.07	0.45
<input type="checkbox"/>	SDR-5.1G	60M	Top Side	High	5220	1 V	10.0%	20.0	19.58	1.10	-0.01	4.02	0.44
<input type="checkbox"/>	SDR-5.1G	60M	Front Face	High	5220	4	10.0%	20.0	19.58	1.10	-0.03	0.057	0.01
<input type="checkbox"/>	SDR-5.1G	60M	Rear Face	High	5220	4	10.0%	20.0	19.58	1.10	-0.09	0.075	0.01
<input type="checkbox"/>	SDR-5.1G	60M	Left Side	High	5220	4	10.0%	20.0	19.58	1.10	0.00	<0.01	<0.01
<input type="checkbox"/>	SDR-5.1G	60M	Top Side	High	5220	4	10.0%	20.0	19.58	1.10	0.07	0.153	0.02
<input type="checkbox"/>	SDR-5.1G	60M	Front Face	High	5220	5	10.0%	20.0	19.58	1.10	0.00	0.262	0.03
<input type="checkbox"/>	SDR-5.1G	60M	Rear Face	High	5220	5	10.0%	20.0	19.58	1.10	0.00	0.188	0.02
<input type="checkbox"/>	SDR-5.1G	60M	Left Side	High	5220	5	10.0%	20.0	19.58	1.10	0.00	<0.01	<0.01
<input type="checkbox"/>	SDR-5.1G	60M	Top Side	High	5220	5	10.0%	20.0	19.58	1.10	-0.02	0.965	0.11
<input type="checkbox"/>	SDR-5.1G	60M	Front Face	High	5220	6	10.0%	20.0	19.58	1.10	-0.03	0.834	0.09
<input type="checkbox"/>	SDR-5.1G	60M	Left Side	High	5220	6	10.0%	20.0	19.58	1.10	0.15	0.036	0.00

<input type="checkbox"/>	SDR-5.1G	60M	Bottom Side	High	5220	6	10.0%	20.0	19.58	1.10	-0.17	1.29	0.14
<input type="checkbox"/>	SDR-5.1G	60M	Top Side	High	5220	1_H	10.0%	20.0	19.58	1.10	-0.03	3.95	0.44
<input type="checkbox"/>	SDR-5.8G	20M	Front Face	Low	5735.5	0_H	10.0%	29.0	28.36	1.16	-0.07	0.699	0.08
<input type="checkbox"/>	SDR-5.8G	20M	Front Face	Low	5735.5	0_V	10.0%	29.0	28.36	1.16	-0.08	0.125	0.01
<input type="checkbox"/>	SDR-5.8G	20M	Rear Face	Low	5735.5	0_H	10.0%	29.0	28.36	1.16	0.06	0.042	0.00
<input type="checkbox"/>	SDR-5.8G	20M	Rear Face	Low	5735.5	0_V	10.0%	29.0	28.36	1.16	0.05	0.323	0.04
<input type="checkbox"/>	SDR-5.8G	20M	Left Side	Low	5735.5	0_H	10.0%	29.0	28.36	1.16	0.00	<0.01	<0.01
<input type="checkbox"/>	SDR-5.8G	20M	Left Side	Low	5735.5	0_V	10.0%	29.0	28.36	1.16	0.00	<0.01	<0.01
<input type="checkbox"/>	SDR-5.8G	20M	Top Side	Low	5735.5	0_H	10.0%	29.0	28.36	1.16	-0.02	1.6	0.19
<input type="checkbox"/>	SDR-5.8G	20M	Top Side	Low	5735.5	0_V	10.0%	29.0	28.36	1.16	-0.02	1.52	0.18
<input type="checkbox"/>	SDR-5.8G	20M	Front Face	Low	5735.5	1_H	10.0%	29.0	28.36	1.16	-0.09	0.808	0.09
<input type="checkbox"/>	SDR-5.8G	20M	Front Face	Low	5735.5	1_V	10.0%	29.0	28.36	1.16	0.01	0.149	0.02
<input type="checkbox"/>	SDR-5.8G	20M	Rear Face	Low	5735.5	1_H	10.0%	29.0	28.36	1.16	0.02	0.64	0.07
<input type="checkbox"/>	SDR-5.8G	20M	Rear Face	Low	5735.5	1_V	10.0%	29.0	28.36	1.16	-0.01	0.276	0.03
<input type="checkbox"/>	SDR-5.8G	20M	Right Side	Low	5735.5	1_H	10.0%	29.0	28.36	1.16	0.00	<0.01	<0.01
<input type="checkbox"/>	SDR-5.8G	20M	Right Side	Low	5735.5	1_V	10.0%	29.0	28.36	1.16	0.00	<0.01	<0.01
<input type="checkbox"/>	SDR-5.8G	20M	Top Side	Low	5735.5	1_H	10.0%	29.0	28.36	1.16	-0.03	7.59	0.88
3	SDR-5.8G	20M	Top Side	Low	5735.5	1_V	10.0%	29.0	28.36	1.16	0.06	7.63	0.88
<input type="checkbox"/>	SDR-5.8G	20M	Front Face	Low	5735.5	4	10.0%	29.0	28.36	1.16	-0.03	0.065	0.01
<input type="checkbox"/>	SDR-5.8G	20M	Rear Face	Low	5735.5	4	10.0%	29.0	28.36	1.16	0.01	0.167	0.02
<input type="checkbox"/>	SDR-5.8G	20M	Left Side	Low	5735.5	4	10.0%	29.0	28.36	1.16	0.00	<0.01	<0.01
<input type="checkbox"/>	SDR-5.8G	20M	Right Side	Low	5735.5	4	10.0%	29.0	28.36	1.16	0.00	<0.01	<0.01
<input type="checkbox"/>	SDR-5.8G	20M	Top Side	Low	5735.5	4	10.0%	29.0	28.36	1.16	-0.09	0.339	0.04
<input type="checkbox"/>	SDR-5.8G	20M	Front Face	Low	5735.5	5	10.0%	29.0	28.36	1.16	0.06	0.685	0.08
<input type="checkbox"/>	SDR-5.8G	20M	Rear Face	Low	5735.5	5	10.0%	29.0	28.36	1.16	-0.05	0.359	0.04
<input type="checkbox"/>	SDR-5.8G	20M	Left Side	Low	5735.5	5	10.0%	29.0	28.36	1.16	0.00	<0.01	<0.01
<input type="checkbox"/>	SDR-5.8G	20M	Right Side	Low	5735.5	5	10.0%	29.0	28.36	1.16	0.00	<0.01	<0.01
<input type="checkbox"/>	SDR-5.8G	20M	Top Side	Low	5735.5	5	10.0%	29.0	28.36	1.16	-0.08	1.54	0.18
<input type="checkbox"/>	SDR-5.8G	20M	Front Face	Low	5735.5	6	10.0%	29.0	28.36	1.16	0.04	2.01	0.23
<input type="checkbox"/>	SDR-5.8G	20M	Rear Face	Low	5735.5	6	10.0%	29.0	28.36	1.16	0.09	0.133	0.02
<input type="checkbox"/>	SDR-5.8G	20M	Left Side	Low	5735.5	6	10.0%	29.0	28.36	1.16	-0.05	0.05	0.01
<input type="checkbox"/>	SDR-5.8G	20M	Top Side	Low	5735.5	6	10.0%	29.0	28.36	1.16	0.00	<0.01	<0.01
<input type="checkbox"/>	SDR-5.8G	20M	Bottom Side	Low	5735.5	6	10.0%	29.0	28.36	1.16	0.11	0.998	0.12
3	SDR-5.8G	20M	Top Side	Low	5735.5	1_V	10.0%	29.0	28.36	1.16	0.06	7.48	0.87
4	802.11b	-	Front Face	6	2437	0	-	17.5	17.13	1.09	-0.05	0.069	0.08
<input type="checkbox"/>	802.11b	-	Front Face	6	2437	1	-	17.5	17.13	1.09	-0.06	0.018	0.02
5	802.11ac	VHT80	Front Face	42	5210	0	-	21.5	20.93	1.14	-0.05	1.44	1.64
<input type="checkbox"/>	802.11ac	VHT80	Rear Face	42	5210	0	-	21.5	20.93	1.14	-0.06	0.116	0.13
<input type="checkbox"/>	802.11ac	VHT80	Left Side	42	5210	0	-	21.5	20.93	1.14	0.16	0.392	0.45
<input type="checkbox"/>	802.11ac	VHT80	Top Side	42	5210	0	-	21.5	20.93	1.14	0.00	<0.01	<0.01
<input type="checkbox"/>	802.11ac	VHT80	Front Face	42	5210	1	-	21.5	20.93	1.14	0.05	0.984	1.12
<input type="checkbox"/>	802.11ac	VHT80	Rear Face	42	5210	1	-	21.5	20.93	1.14	0.13	0.167	0.19
<input type="checkbox"/>	802.11ac	VHT80	Right Side	42	5210	1	-	21.5	20.93	1.14	-0.08	0.156	0.18
<input type="checkbox"/>	802.11ac	VHT80	Top Side	42	5210	1	-	21.5	20.93	1.14	0.00	<0.01	<0.01
6	802.11ac	VHT40	Front Face	159	5795	0	-	21.5	21.03	1.11	-0.06	2.2	2.45
<input type="checkbox"/>	802.11ac	VHT40	Rear Face	159	5795	0	-	21.5	21.03	1.11	-0.16	0.154	0.17
<input type="checkbox"/>	802.11ac	VHT40	Left Side	159	5795	0	-	21.5	21.03	1.11	0.06	0.174	0.19
<input type="checkbox"/>	802.11ac	VHT40	Top Side	159	5795	0	-	21.5	21.03	1.11	0.00	<0.01	<0.01
<input type="checkbox"/>	802.11ac	VHT40	Front Face	159	5795	1	-	21.5	21.03	1.11	-0.01	1.55	1.73
<input type="checkbox"/>	802.11ac	VHT40	Rear Face	159	5795	1	-	21.5	21.03	1.11	0.09	0.495	0.55
<input type="checkbox"/>	802.11ac	VHT40	Right Side	159	5795	1	-	21.5	21.03	1.11	-0.06	0.478	0.53
<input type="checkbox"/>	802.11ac	VHT40	Top Side	159	5795	1	-	21.5	21.03	1.11	0.00	<0.01	<0.01
<input type="checkbox"/>	802.11ac	VHT40	Front Face	159	5795	0+1	-	21.5	21.03	1.11	-0.06	1.12	1.25
<input type="checkbox"/>	802.11ac	VHT40	Rear Face	159	5795	0+1	-	21.5	21.03	1.11	0.04	0.077	0.09
<input type="checkbox"/>	802.11ac	VHT40	Left Side	159	5795	0+1	-	21.5	21.03	1.11	0.02	0.087	0.10
<input type="checkbox"/>	802.11ac	VHT40	Right Side	159	5795	0+1	-	21.5	21.03	1.11	-0.05	0.238	0.27
<input type="checkbox"/>	802.11ac	VHT40	Top Side	159	5795	0+1	-	21.5	21.03	1.11	0.00	<0.01	<0.01
<input type="checkbox"/>	802.11ac	VHT40	Front Face	151	5755	0	-	21.5	20.60	1.23	0.09	1.96	2.41

<input type="checkbox"/>	802.11ac	VHT40	Front Face	159	5795	0	-	21.5	21.03	1.11	0.06	2.16	2.41
--------------------------	----------	-------	------------	-----	------	---	---	------	-------	------	------	------	------

Note: This device is for properly worn on the limbs when in normal use, and the SAR limit of 4 W/kg averaged over ten gram of tissue applied.

8.2.4.SAR Results for Body-Worn Exposure Condition (Separation Distance is 0 cm Gap)

Note: Considering that the bottom and rear sides may keep towards or touch the lap, thus 1-g Body SAR were evaluated as well. For other sides, no scenes on body-worn which clearly indicated in appendix D.

Plot No.	Band	Mode	Test Position	Ch.	Fre.	Antenna	Normal Duty Cycle	Max. Tune-up Power (dBm)	Measured Conducted Power (dBm)	Scaling Factor	Power Drift (dB)	Measured SAR-1g (W/kg)	Scaled SAR-1g (W/kg)
<input type="checkbox"/>	SDR2.4G	40M	Rear Face	Mid	2437.5	0 V	10.0%	27.5	27.37	1.03	-0.14	0.193	0.02
<input type="checkbox"/>	SDR2.4G	40M	Rear Face	Mid	2437.5	1 H	10.0%	27.5	27.37	1.03	0.13	0.267	0.03
<input type="checkbox"/>	SDR2.4G	40M	Rear Face	Mid	2437.5	1 V	10.0%	27.5	27.37	1.03	0.05	0.269	0.03
<input type="checkbox"/>	SDR2.4G	40M	Rear Face	Mid	2437.5	4	10.0%	27.5	27.37	1.03	-0.01	0.623	0.06
<input type="checkbox"/>	SDR2.4G	40M	Rear Face	Mid	2437.5	5	10.0%	27.5	27.37	1.03	-0.03	0.358	0.04
<input type="checkbox"/>	SDR2.4G	40M	Rear Face	Mid	2437.5	6	10.0%	27.5	27.37	1.03	-0.09	0.088	0.01
7 <input type="checkbox"/>	SDR2.4G	40M	Bottom Side	Mid	2437.5	6	10.0%	27.5	27.37	1.03	-0.15	4.3	0.44
<input type="checkbox"/>	SDR-5.1G	60M	Rear Face	High	5220	0 H	10.0%	20.0	19.58	1.10	-0.02	0.663	0.07
<input type="checkbox"/>	SDR-5.1G	60M	Rear Face	High	5220	0 V	10.0%	20.0	19.58	1.10	-0.02	0.218	0.02
<input type="checkbox"/>	SDR-5.1G	60M	Rear Face	High	5220	1 H	10.0%	20.0	19.58	1.10	-0.08	0.16	0.02
<input type="checkbox"/>	SDR-5.1G	60M	Rear Face	High	5220	1 V	10.0%	20.0	19.58	1.10	0.02	0.152	0.02
<input type="checkbox"/>	SDR-5.1G	60M	Rear Face	High	5220	4	10.0%	20.0	19.58	1.10	-0.09	0.205	0.02
<input type="checkbox"/>	SDR-5.1G	60M	Rear Face	High	5220	5	10.0%	20.0	19.58	1.10	0.00	0.512	0.06
8 <input type="checkbox"/>	SDR-5.1G	60M	Bottom Side	High	5220	6	10.0%	20.0	19.58	1.10	-0.17	4.77	0.53
<input type="checkbox"/>	SDR-5.8G	20M	Rear Face	Low	5735.5	0 H	10.0%	29.0	28.36	1.16	0.06	0.109	0.01
<input type="checkbox"/>	SDR-5.8G	20M	Rear Face	Low	5735.5	0 V	10.0%	29.0	28.36	1.16	0.05	0.754	0.09
<input type="checkbox"/>	SDR-5.8G	20M	Rear Face	Low	5735.5	1 H	10.0%	29.0	28.36	1.16	0.02	1.62	0.19
<input type="checkbox"/>	SDR-5.8G	20M	Rear Face	Low	5735.5	1 V	10.0%	29.0	28.36	1.16	-0.01	0.613	0.07
<input type="checkbox"/>	SDR-5.8G	20M	Rear Face	Low	5735.5	4	10.0%	29.0	28.36	1.16	0.01	0.421	0.05
<input type="checkbox"/>	SDR-5.8G	20M	Rear Face	Low	5735.5	5	10.0%	29.0	28.36	1.16	-0.05	0.891	0.10
<input type="checkbox"/>	SDR-5.8G	20M	Rear Face	Low	5735.5	6	10.0%	29.0	28.36	1.16	0.09	0.335	0.04
9 <input type="checkbox"/>	SDR-5.8G	20M	Bottom Side	Low	5735.5	6	10.0%	29.0	28.36	1.16	0.11	3.38	0.39
<input type="checkbox"/>	802.11b	20M	Rear Face	6	2437	0	-	17.5	17.13	1.09	-0.01	0.08	0.09
10 <input type="checkbox"/>	802.11ac	VHT80	Rear Face	42	5210	0	-	21.5	20.93	1.14	-0.06	0.418	0.48
<input type="checkbox"/>	802.11ac	VHT80	Rear Face	42	5210	1	-	21.5	20.93	1.14	0.13	0.385	0.44
<input type="checkbox"/>	802.11ac	VHT40	Rear Face	159	5795	0	-	21.5	21.03	1.11	-0.16	0.36	0.40
11 <input type="checkbox"/>	802.11ac	VHT40	Rear Face	159	5795	1	-	21.5	21.03	1.11	0.09	1.05	1.17
<input type="checkbox"/>	802.11ac	VHT40	Rear Face	151	5755	1	-	21.5	20.86	1.16	0.02	0.91	1.05
<input type="checkbox"/>	802.11ac	VHT40	Rear Face	159	5795	0+1	-	21.5	21.03	1.11	0.04	0.18	0.20

Max normal duty cycle is 10% for 2.4GHz, 5.2GHz and 5.8GHz SDR bands.

1) 2.4GHz SDR

Ton (ms)	T(Total) ms	Duty cycle (%)
0.5021*2	10.13	10%

2) 5.2GHz SDR

Ton (ms)	T(Total) ms	Duty cycle (%)
0.5021*2	10.13	10%

2) 5.8GHz SDR

Ton (ms)	T(Total) ms	Duty cycle (%)
0.5021*2	10.13	10%

8.2.5.SAR Measurement Variability

According to KDB 865664 D01, SAR measurement variability was assessed for each frequency band, which is determined by the SAR probe calibration point and tissue-equivalent medium used for the device measurements. When both head and body tissue-equivalent media are required for SAR measurements in a frequency band, the variability measurement procedures should be applied to the tissue medium with the highest measured SAR, using the highest measured SAR configuration for that tissue-equivalent medium. Alternatively, if the highest measured SAR for both head and body tissue-equivalent media are ≤ 1.45 W/kg and the ratio of these highest SAR values, i.e., largest divided by smallest value, is ≤ 1.10 , the highest SAR configuration for either head or body tissue-equivalent medium may be used to perform the repeated measurement. These additional measurements are repeated after the completion of all measurements requiring the same head or body tissue-equivalent medium in a frequency band. The test device should be returned to ambient conditions (normal room temperature) with the battery fully charged before it is re-mounted on the device holder for the repeated measurement(s) to minimize any unexpected variations in the repeated results.

SAR repeated measurement procedure:

1. When the highest measured SAR is < 0.80 W/kg, repeated measurement is not required.
2. When the highest measured SAR is ≥ 0.80 W/kg, repeat that measurement once.
3. If the ratio of largest to smallest SAR for the original and first repeated measurements is > 1.20 , or when the original or repeated measurement is ≥ 1.45 W/kg, perform a second repeated measurement.
4. If the ratio of largest to smallest SAR for the original, first and second repeated measurements is > 1.20 , and the original, first or second repeated measurement is ≥ 1.5 W/kg, perform a third repeated measurement.

Band	Mode	Test Position	Fre.	Original Measured SAR-10g (W/kg)	1st Repeated SAR-10g (W/kg)	L/S Ratio	2nd Repeated SAR-1g (W/kg)	L/S Ratio	3rd Repeated SAR-1g (W/kg)	L/S Ratio
SDR2.4G	40M	Front Face	2437.5	6.55	6.34	1.03	N/A	N/A	N/A	N/A
SDR-5.1G	60M	Top Side	5220	4.07	3.95	1.03	N/A	N/A	N/A	N/A
SDR-5.8G	20M	Top Side	5735.5	7.63	7.48	1.02	N/A	N/A	N/A	N/A
802.11ac	VHT40	Front Face	5795	2.2	2.16	1.02	N/A	N/A	N/A	N/A

8.2.6. Simultaneous Multi-band Transmission Evaluation
<Estimated SAR Calculation>

According to KDB 447498 D01, when standalone SAR test exclusion applies to an antenna that transmits simultaneously with other antennas, the standalone SAR was estimated according to following formula to result in substantially conservative SAR values of ≤ 0.4 W/kg to determine simultaneous transmission SAR test exclusion.

$$\text{Estimated SAR} = \frac{\text{Max. Tune up Power}_{(\text{mW})}}{\text{Min. Test Separation Distance}_{(\text{mm})}} \times \frac{\sqrt{f_{(\text{GHz})}}}{7.5}$$

If the minimum test separation distance is < 5 mm, a distance of 5 mm is used for estimated SAR calculation. When the test separation distance is > 50 mm, the 0.4 W/kg is used for SAR-1g.

Mode / Band	Frequency (GHz)	Max. Tune-up Power (dBm)	Test Position	Separation Distance (mm)	Estimated SAR (W/kg)
BT (DSS)	2.48	2.5	Extremity	0	0.07
BT (DSS)	2.48	2.5	Body	0	0.19

Note:

1. The separation distance is determined from the outer housing of the EUT to the user.
2. When standalone SAR testing is not required, an estimated SAR can be applied to determine simultaneous transmission SAR test exclusion.

<SAR Summation Analysis>

Simultaneous transmission SAR test exclusion is determined for each operating configuration and exposure condition according to the reported standalone SAR of each applicable simultaneous transmitting antenna. When the sum of SAR_{1g} of all simultaneously transmitting antennas in an operating mode and exposure condition combination is within the SAR limit (SAR_{1g} 1.6 W/kg), the simultaneous transmission SAR is not required. When the sum of SAR_{1g} is greater than the SAR limit (SAR_{1g} 1.6 W/kg), SAR test exclusion is determined by the SPLSR.

<MIMO_WLAN 2.4G>
Extremity 10-g SAR

Test Position	Max. SAR_Ant.0	Max. SAR_Ant.1	SAR MIMO
Front Face	0.08	0.02	0.10
Rear Face			
Left Side			
Right Side			
Top Side			
Bottom Side			

Body 1-g SAR

Test Position	Max. SAR_Ant.0	Max. SAR_Ant.1	SAR MIMO
Front Face			
Rear Face	0.03	<0.01	0.03
Left Side			
Right Side			
Top Side			
Bottom Side			

<MIMO_WLAN 5.2G>
Extremity 10-g SAR

Test Position	Max. SAR_Ant.0	Max. SAR_Ant.1	SAR MIMO
Front Face	1.64	1.12	2.76
Rear Face	0.13	0.19	0.32
Left Side	0.45		0.45
Right Side	□	0.18	0.18
Top Side	<0.01	<0.01	<0.01
Bottom Side	□	□	□

Body 1-g SAR

Test Position	Max. SAR_Ant.0	Max. SAR_Ant.1	SAR MIMO
Front Face			
Rear Face	0.48	0.44	0.92
Left Side			
Right Side			
Top Side			
Bottom Side			

No.	Conditions (SAR1 + SAR2 +SAR3)	Exposure Condition	Test Position	Max. SAR1	Max. SAR2	Max. SAR3	SAR Summation	SPLSR Analysis
1	SDR 2.4G + NII + BT	Extremity SAR	Front Face	0.72	2.76	0.07	3.55	Σ SAR < 4.0, Not required
			Rear Face	0.10	0.55	0.07	0.72	Σ SAR < 4.0, Not required
			Left Side	0.02	0.45	0.07	0.54	Σ SAR < 4.0, Not required
			Right Side	<0.01	0.53	0.07	0.6	Σ SAR < 4.0, Not required
			Top Side	0.69	<0.01	0.07	0.76	Σ SAR < 4.0, Not required
			Bottom Side	0.20		0.07	0.27	Σ SAR < 4.0, Not required
2	SDR 5.1G + DTS + BT	Extremity SAR	Front Face	0.11	0.10	0.07	0.28	Σ SAR < 4.0, Not required
			Rear Face	0.05		0.07	0.12	Σ SAR < 4.0, Not required
			Left Side	0.00		0.07	0.07	Σ SAR < 4.0, Not required
			Right Side			0.07	0.07	Σ SAR < 4.0, Not required
			Top Side	0.55		0.07	0.62	Σ SAR < 4.0, Not required
			Bottom Side	0.14		0.07	0.21	Σ SAR < 4.0, Not required
3	SDR 5.1G + WLAN 5.8G + BT	Extremity SAR	Front Face	0.11	2.45	0.07	2.63	Σ SAR < 4.0, Not required
			Rear Face	0.05	0.55	0.07	0.67	Σ SAR < 4.0, Not required
			Left Side	0.00	0.19	0.07	0.26	Σ SAR < 4.0, Not required
			Right Side		0.53	0.07	0.60	Σ SAR < 4.0, Not required
			Top Side	0.55	<0.01	0.07	0.62	Σ SAR < 4.0, Not required
			Bottom Side	0.14		0.07	0.21	Σ SAR < 4.0, Not required
4	SDR 5.8G + DTS + DSS	Extremity SAR	Front Face	0.32	0.10	0.07	0.49	Σ SAR < 4.0, Not required
			Rear Face	0.11		0.07	0.18	Σ SAR < 4.0, Not required
			Left Side	0.01		0.07	0.08	Σ SAR < 4.0, Not required
			Right Side	<0.01		0.07	0.07	Σ SAR < 4.0, Not required
			Top Side	1.07		0.07	1.14	Σ SAR < 4.0, Not required
			Bottom Side	0.12		0.07	0.19	Σ SAR < 4.0, Not required
5	SDR 5.8G + WLAN 5.2G + BT	Extremity SAR	Front Face	0.32	2.76	0.07	3.15	Σ SAR < 4.0, Not required
			Rear Face	0.11	0.32	0.07	0.50	Σ SAR < 4.0, Not required
			Left Side	0.01	0.45	0.07	0.53	Σ SAR < 4.0, Not required
			Right Side	<0.01	0.18	0.07	0.25	Σ SAR < 4.0, Not required
			Top Side	1.07	<0.01	0.07	1.14	Σ SAR < 4.0, Not required
			Bottom Side	0.12		0.07	0.19	Σ SAR < 4.0, Not required

No.	Conditions (SAR1 + SAR2 +SAR3)	Exposure Condition	Test Position	Max. SAR1	Max. SAR2	Max. SAR3	SAR Summation	SPLSR Analysis
1	SDR 2.4G +NII + BT	Body SAR	Rear Face	0.06	1.17	0.19	1.42	Σ SAR < 1.6, Not required
			Bottom Side	0.44	/	/	0.44	Σ SAR < 1.6, Not required
2	SDR 5.1G + DTS + BT	Body SAR	Rear Face	0.07	0.03	0.19	0.29	Σ SAR < 1.6, Not required
			Bottom Side	0.53	/	/	0.53	Σ SAR < 1.6, Not required
3	SDR 5.1G + WLAN 5.8G + BT	Body SAR	Rear Face	0.07	1.17	0.19	1.43	Σ SAR < 1.6, Not required
			Bottom Side	0.53	/	/	0.53	Σ SAR < 1.6, Not required
4	SDR 5.8G + DTS + BT	Body SAR	Rear Face	0.19	0.03	0.19	0.41	Σ SAR < 1.6, Not required
			Bottom Side	0.39	/	/	0.39	Σ SAR < 1.6, Not required
5	SDR 5.8G + WLAN 5.2G + BT	Body SAR	Rear Face	0.19	0.48	0.19	0.86	Σ SAR < 1.6, Not required
			Bottom Side	0.39	/	/	0.39	Σ SAR < 1.6, Not required

Test Engineer: Warren Xiong,

Appendixes

All attachments are integral parts of this test report. This applies especially to the following appendix:

Appendix A: SAR Plots of System Verification

The plots for system verification with largest deviation for each SAR system combination are shown as follows.

Appendix B: SAR Plots of SAR Measurement

The SAR plots for highest measured SAR in each exposure configuration, wireless mode and frequency band combination, and measured SAR > 1.5 W/kg are shown as follows.

Appendix C: Calibration Certificate for probe and Dipole

Appendix D: Photographs of EUT, Antenna location Diagram and setup

Test Laboratory: TÜV Rheinland (Shenzhen) Co., Ltd.

Date: 2024/7/17

System Check-D2450V2_H2450

DUT: Dipole 2450 MHz D2450V2 SN:1014

Communication System: UID 0, CW; Frequency: 2450 MHz; Duty Cycle: 1:1


Medium: H2450 Medium parameters used: $f = 2450$ MHz; $\sigma = 1.844$ S/m; $\epsilon_r = 39.408$; $\rho = 1000$ kg/m³

DASY5 Configuration:

- Probe: EX3DV4 - SN7738; ConvF(7.6, 7.6, 7.6) @ 2450 MHz; Calibrated: 2023/12/13
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1725; Calibrated: 20232/10/26
- Phantom: ELI V8.0; Type: QD OVA 004 Ax; Serial: 2094
- Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7483)

Pin=250 mW/Area Scan (71x71x1): Interpolated grid: dx=1.200 mm, dy=1.200 mm
Maximum value of SAR (interpolated) = 20.9 W/kg

Pin=250 mW/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 110.3 V/m; Power Drift = -0.02 dB
Peak SAR (extrapolated) = 25.8 W/kg
SAR(1 g) = 12.5 W/kg; SAR(10 g) = 5.89 W/kg
Smallest distance from peaks to all points 3 dB below = 9 mm
Ratio of SAR at M2 to SAR at M1 = 48.7%
Maximum value of SAR (measured) = 20.9 W/kg



Test Laboratory: TÜV Rheinland (Shenzhen) Co., Ltd.

Date: 2024/7/18

System Check-D5GHz_H5250

DUT: Dipole D5GHzV2 SN:1280

Communication System: UID 0, CW; Frequency: 5250 MHz; Duty Cycle: 1:1


Medium: H5G Medium parameters used: $f = 5250$ MHz; $\sigma = 4.561$ S/m; $\epsilon_r = 37.438$; $\rho = 1000$ kg/m³

DASY5 Configuration:

- Probe: EX3DV4 - SN7738; ConvF(5.38, 5.38, 5.38) @ 5250 MHz; Calibrated: 2023/12/13
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1725; Calibrated: 2023/10/26
- Phantom: ELI V8.0; Type: QD OVA 004 Ax; Serial: 2094
- Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7483)

Pin=100mW/Area Scan (91x91x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm
Maximum value of SAR (interpolated) = 18.1 W/kg

Pin=100mW/Zoom Scan (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm
Reference Value = 62.31 V/m; Power Drift = -0.03 dB
Peak SAR (extrapolated) = 30.9 W/kg
SAR(1 g) = 7.62 W/kg; SAR(10 g) = 2.2 W/kg
Smallest distance from peaks to all points 3 dB below = 7.2 mm
Ratio of SAR at M2 to SAR at M1 = 64.4%
Maximum value of SAR (measured) = 18.2 W/kg



Test Laboratory: TÜV Rheinland (Shenzhen) Co., Ltd.

Date: 2024/7/19

System Check-D5GHz_H5800

DUT: Dipole D5GHzV2 SN:1280

Communication System: UID 0, CW; Frequency: 5800 MHz; Duty Cycle: 1:1

Medium: H5G Medium parameters used: $f = 5800$ MHz; $\sigma = 5.145$ S/m; $\epsilon_r = 36.469$; $\rho = 1000$ kg/m³

DASY5 Configuration:

- Probe: EX3DV4 - SN7738; ConvF(4.74, 4.74, 4.74) @ 5800 MHz; Calibrated: 2023/12/13
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1725; Calibrated: 2023/10/26
- Phantom: ELI V8.0; Type: QD OVA 004 Ax; Serial: 2094
- Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7483)

Pin=100mW/Area Scan (91x91x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 20.3 W/kg

Pin=100mW/Zoom Scan (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 62.09 V/m; Power Drift = -0.02 dB


Peak SAR (extrapolated) = 37.0 W/kg

SAR(1 g) = 7.96 W/kg; SAR(10 g) = 2.27 W/kg

Smallest distance from peaks to all points 3 dB below = 7.4 mm

Ratio of SAR at M2 to SAR at M1 = 60%

Maximum value of SAR (measured) = 20.0 W/kg



Test Laboratory: TÜV Rheinland (Shenzhen) Co., Ltd.

Date: 2024/7/17

P01 SDR-2.4G_40M_Front Face_0cm_Ch Mid_Ant 6

DUT: EUT

Communication System: UID 0, SDR; Frequency: 2437.5 MHz; Duty Cycle: 1:1


Medium: H2450 Medium parameters used: $f = 2437.5$ MHz; $\sigma = 1.83$ S/m; $\epsilon_r = 39.463$; $\rho = 1000$ kg/m³

DASY5 Configuration:

- Probe: EX3DV4 - SN7738; ConvF(7.6, 7.6, 7.6) @ 2437.5 MHz; Calibrated: 2023/12/13
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1725; Calibrated: 2023/10/26
- Phantom: ELI V8.0; Type: QD OVA 004 Ax; Serial: 2094
- Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7483)

- **Area Scan (151x161x1):** Interpolated grid: dx=1.200 mm, dy=1.200 mm
Maximum value of SAR (interpolated) = 38.2 W/kg

- **Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 2.740 V/m; Power Drift = -0.05 dB
Peak SAR (extrapolated) = 49.8 W/kg
SAR(1 g) = 17.7 W/kg; SAR(10 g) = 6.55 W/kg
Smallest distance from peaks to all points 3 dB below = 5.8 mm
Ratio of SAR at M2 to SAR at M1 = 38.7%
Maximum value of SAR (measured) = 35.6 W/kg



Test Laboratory: TÜV Rheinland (Shenzhen) Co., Ltd.

Date: 2024/7/18

P02 SDR-5.1G_60M_Top Side_0cm_Ch High_Ant 1-H

DUT: EUT

Communication System: UID 0, SDR; Frequency: 5220 MHz; Duty Cycle: 1:1

Medium: H5G Medium parameters used: $f = 5220$ MHz; $\sigma = 4.538$ S/m; $\epsilon_r = 37.52$; $\rho = 1000$ kg/m³

DASY5 Configuration:

- Probe: EX3DV4 - SN7738; ConvF(5.38, 5.38, 5.38) @ 5220 MHz; Calibrated: 2023/12/13
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1725; Calibrated: 2023/10/26
- Phantom: ELI V8.0; Type: QD OVA 004 Ax; Serial: 2094
- Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7483)

- **Area Scan (91x101x1)**: Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 57.2 W/kg

- **Zoom Scan (8x8x7)/Cube 0**: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 81.94 V/m; Power Drift = -0.03 dB


Peak SAR (extrapolated) = 91.7 W/kg

SAR(1 g) = 13.7 W/kg; SAR(10 g) = 4.07 W/kg

Smallest distance from peaks to all points 3 dB below = 4.8 mm

Ratio of SAR at M2 to SAR at M1 = 54.9%

Maximum value of SAR (measured) = 44.8 W/kg



Test Laboratory: TÜV Rheinland (Shenzhen) Co., Ltd.

Date: 2024/7/19

P03 SDR-5.8G_20M_Top Side_0cm_Ch Low_Ant 1-V

DUT: EUT

Communication System: UID 0, SDR; Frequency: 5735.5 MHz; Duty Cycle: 1:1


Medium: H5G Medium parameters used: $f = 5735.5$ MHz; $\sigma = 5.093$ S/m; $\epsilon_r = 36.605$; $\rho = 1000$ kg/m³

DASY5 Configuration:

- Probe: EX3DV4 - SN7738; ConvF(4.74, 4.74, 4.74) @ 5735.5 MHz; Calibrated: 2023/12/13
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1725; Calibrated: 2023/10/26
- Phantom: ELI V8.0; Type: QD OVA 004 Ax; Serial: 2094
- Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7483)

- **Area Scan (91x101x1):** Interpolated grid: dx=1.000 mm, dy=1.000 mm
Maximum value of SAR (interpolated) = 129 W/kg

- **Zoom Scan (8x8x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm
Reference Value = 4.030 V/m; Power Drift = 0.06 dB
Peak SAR (extrapolated) = 159 W/kg
SAR(1 g) = 30.1 W/kg; SAR(10 g) = 7.63 W/kg
Smallest distance from peaks to all points 3 dB below = 4.3 mm
Ratio of SAR at M2 to SAR at M1 = 63.1%
Maximum value of SAR (measured) = 80.5 W/kg



Test Laboratory: TÜV Rheinland (Shenzhen) Co., Ltd.

Date: 2024/7/17

P04 802.11b_Front Face_0cm_Ch6_Ant 0

DUT: EUT

Communication System: UID 0, 802.11b; Frequency: 2437 MHz; Duty Cycle: 1:1


Medium: H2450 Medium parameters used: $f = 2437$ MHz; $\sigma = 1.829$ S/m; $\epsilon_r = 39.466$; $\rho = 1000$ kg/m³

DASY5 Configuration:

- Probe: EX3DV4 - SN7738; ConvF(7.6, 7.6, 7.6) @ 2437 MHz; Calibrated: 2023/12/13
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1725; Calibrated: 2023/10/26
- Phantom: ELI V8.0; Type: QD OVA 004 Ax; Serial: 2094
- Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7483)

- Area Scan (81x151x1): Interpolated grid: dx=1.200 mm, dy=1.200 mm
Maximum value of SAR (interpolated) = 0.217 W/kg

- Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 5.164 V/m; Power Drift = -0.05 dB
Peak SAR (extrapolated) = 0.338 W/kg
SAR(1 g) = 0.147 W/kg; SAR(10 g) = 0.069 W/kg
Smallest distance from peaks to all points 3 dB below = 9.8 mm
Ratio of SAR at M2 to SAR at M1 = 42.1%
Maximum value of SAR (measured) = 0.255 W/kg



Test Laboratory: TÜV Rheinland (Shenzhen) Co., Ltd.

Date: 2024/7/18

P05 802.11ac_VHT80_Front Face_0cm_Ch42_Ant 0

DUT: EUT

Communication System: UID 0, 802.11ac; Frequency: 5210 MHz; Duty Cycle: 1:1

Medium: H5G Medium parameters used: $f = 5210$ MHz; $\sigma = 4.523$ S/m; $\epsilon_r = 37.557$; $\rho = 1000$ kg/m³

DASY5 Configuration:

- Probe: EX3DV4 - SN7738; ConvF(5.38, 5.38, 5.38) @ 5210 MHz; Calibrated: 2023/12/13
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1725; Calibrated: 2023/10/26
- Phantom: ELI V8.0; Type: QD OVA 004 Ax; Serial: 2094
- Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7483)

- **Area Scan (81x181x1)**: Interpolated grid: $dx=1.000$ mm, $dy=1.000$ mm

Maximum value of SAR (interpolated) = 11.3 W/kg

- **Zoom Scan (8x8x7)/Cube 0**: Measurement grid: $dx=4$ mm, $dy=4$ mm, $dz=1.4$ mm

Reference Value = 6.074 V/m; Power Drift = -0.05 dB


Peak SAR (extrapolated) = 18.5 W/kg

SAR(1 g) = 4.68 W/kg; SAR(10 g) = 1.44 W/kg

Smallest distance from peaks to all points 3 dB below = 7.2 mm

Ratio of SAR at M2 to SAR at M1 = 64.4%

Maximum value of SAR (measured) = 11.0 W/kg



Test Laboratory: TÜV Rheinland (Shenzhen) Co., Ltd.

Date: 2024/7/19

P06 802.11ac_VHT40_Front Face_0cm_Ch159_Ant 0

DUT: EUT

Communication System: UID 0, 802.11ac; Frequency: 5795 MHz; Duty Cycle: 1:1

Medium: H5G Medium parameters used: $f = 5795$ MHz; $\sigma = 5.143$ S/m; $\epsilon_r = 36.459$; $\rho = 1000$ kg/m³

DASY5 Configuration:

- Probe: EX3DV4 - SN7738; ConvF(4.74, 4.74, 4.74) @ 5795 MHz; Calibrated: 2023/12/13
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1725; Calibrated: 2023/10/26
- Phantom: ELI V8.0; Type: QD OVA 004 Ax; Serial: 2094
- Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7483)

- **Area Scan (81x181x1)**: Interpolated grid: $dx=1.000$ mm, $dy=1.000$ mm
Maximum value of SAR (interpolated) = 23.4 W/kg

- **Zoom Scan (8x8x7)/Cube 0**: Measurement grid: $dx=4$ mm, $dy=4$ mm, $dz=1.4$ mm
Reference Value = 8.537 V/m; Power Drift = -0.06 dB


Peak SAR (extrapolated) = 30.5 W/kg

SAR(1 g) = 7.35 W/kg; SAR(10 g) = 2.2 W/kg

Smallest distance from peaks to all points 3 dB below = 7.2 mm

Ratio of SAR at M2 to SAR at M1 = 62.1%

Maximum value of SAR (measured) = 17.6 W/kg



Test Laboratory: TÜV Rheinland (Shenzhen) Co., Ltd.

Date: 2024/7/17

P01 SDR-2.4G_40M_Bottom Side_0cm_Ch Mid_Ant 6

DUT: EUT

Communication System: UID 0, SDR; Frequency: 2437.5 MHz; Duty Cycle: 1:1

Medium: H2450 Medium parameters used: $f = 2437.5$ MHz; $\sigma = 1.83$ S/m; $\epsilon_r = 39.463$; $\rho = 1000$ kg/m³

DASY5 Configuration:

- Probe: EX3DV4 - SN7738; ConvF(7.6, 7.6, 7.6) @ 2437.5 MHz; Calibrated: 2023/12/13
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1725; Calibrated: 2023/10/26
- Phantom: ELI V8.0; Type: QD OVA 004 Ax; Serial: 2094
- Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7483)

- Area Scan (81x161x1): Interpolated grid: dx=1.200 mm, dy=1.200 mm
Maximum value of SAR (interpolated) = 6.42 W/kg

- Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 20.43 V/m; Power Drift = -0.15 dB



Peak SAR (extrapolated) = 9.54 W/kg

SAR(1 g) = 4.3 W/kg; SAR(10 g) = 1.9 W/kg

Smallest distance from peaks to all points 3 dB below = 8 mm

Ratio of SAR at M2 to SAR at M1 = 51.1%

Maximum value of SAR (measured) = 6.90 W/kg



Test Laboratory: TÜV Rheinland (Shenzhen) Co., Ltd.

Date: 2024/7/18

P02 SDR-5.1G_60M_Bottom Side_0cm_Ch High_Ant 6

DUT: EUT

Communication System: UID 0, SDR; Frequency: 5220 MHz; Duty Cycle: 1:1

Medium: H5G Medium parameters used: $f = 5220$ MHz; $\sigma = 4.538$ S/m; $\epsilon_r = 37.52$; $\rho = 1000$ kg/m³

DASY5 Configuration:

- Probe: EX3DV4 - SN7738; ConvF(5.38, 5.38, 5.38) @ 5220 MHz; Calibrated: 2023/12/13
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1725; Calibrated: 2023/10/26
- Phantom: ELI V8.0; Type: QD OVA 004 Ax; Serial: 2094
- Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7483)

- Area Scan (91x91x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm
Maximum value of SAR (interpolated) = 12.5 W/kg

- Zoom Scan (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm
Reference Value = 10.35 V/m; Power Drift = -0.17 dB


Peak SAR (extrapolated) = 21.5 W/kg

SAR(1 g) = 4.77 W/kg; SAR(10 g) = 1.29 W/kg

Smallest distance from peaks to all points 3 dB below = 5.7 mm

Ratio of SAR at M2 to SAR at M1 = 63%

Maximum value of SAR (measured) = 11.6 W/kg



Test Laboratory: TÜV Rheinland (Shenzhen) Co., Ltd.

Date: 2024/7/19

P03 SDR-5.8G_20M_Bottom Side_0cm_Ch Low_Ant 6 DUT:

EUT

Communication System: UID 0, SDR; Frequency: 5735.5 MHz; Duty Cycle: 1:1

Medium: H5G Medium parameters used: $f = 5735.5$ MHz; $\sigma = 5.093$ S/m; $\epsilon_r = 36.605$; $\rho = 1000$ kg/m³

DASY5 Configuration:

- Probe: EX3DV4 - SN7738; ConvF(4.74, 4.74, 4.74) @ 5735.5 MHz; Calibrated: 2023/12/13
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1725; Calibrated: 2023/10/26
- Phantom: ELI V8.0; Type: QD OVA 004 Ax; Serial: 2094
- Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7483)

- Area Scan (91x91x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm
Maximum value of SAR (interpolated) = 8.78 W/kg

- Zoom Scan (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm
Reference Value = 9.62 V/m; Power Drift = -0.11 dB



Peak SAR (extrapolated) = 18.5 W/kg

SAR(1 g) = 3.38 W/kg; SAR(10 g) = 0.998 W/kg

Smallest distance from peaks to all points 3 dB below = 5.8

mm Ratio of SAR at M2 to SAR at M1 = 63%

Maximum value of SAR (measured) = 10.4 W/kg



Test Laboratory: TÜV Rheinland (Shenzhen) Co., Ltd.

Date: 2024/7/18

P05 802.11ac_VHT80_Rear Face_0cm_Ch42_Ant0

DUT: EUT

Communication System: UID 0, 802.11ac; Frequency: 5210 MHz; Duty Cycle: 1:1

Medium: H5G Medium parameters used: $f = 5210$ MHz; $\sigma = 4.523$ S/m; $\epsilon_r = 37.557$; $\rho = 1000$ kg/m³

DASY5 Configuration:

- Probe: EX3DV4 - SN7738; ConvF(5.38, 5.38, 5.38) @ 5210 MHz; Calibrated: 2023/12/13
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1725; Calibrated: 2023/10/26
- Phantom: ELI V8.0; Type: QD OVA 004 Ax; Serial: 2094
- Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7483)

- Area Scan (81x181x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm
Maximum value of SAR (interpolated) = 1.04 W/kg

- Zoom Scan (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm
Reference Value = 1.341 V/m; Power Drift = -0.06 dB



Peak SAR (extrapolated) = 1.70 W/kg

SAR(1 g) = 0.418 W/kg; SAR(10 g) = 0.116 W/kg

Smallest distance from peaks to all points 3 dB below = 6.8 mm

Ratio of SAR at M2 to SAR at M1 = 65%

Maximum value of SAR (measured) = 0.994 W/kg



Test Laboratory: TÜV Rheinland (Shenzhen) Co., Ltd.

Date: 2024/7/19

P06 802.11ac_VHT40_Rear Face_0cm_Ch159_Ant1

DUT: EUT

Communication System: UID 0, 802.11ac; Frequency: 5795 MHz; Duty Cycle: 1:1

Medium: H5G Medium parameters used: $f = 5795$ MHz; $\sigma = 5.143$ S/m; $\epsilon_r = 36.459$; $\rho = 1000$ kg/m³

DASY5 Configuration:

- Probe: EX3DV4 - SN7738; ConvF(4.74, 4.74, 4.74) @ 5795 MHz; Calibrated: 2023/12/13
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1725; Calibrated: 2023/10/26
- Phantom: ELI V8.0; Type: QD OVA 004 Ax; Serial: 2094
- Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7483)

- Area Scan (81x181x1): Interpolated grid: $dx=1.000$ mm, $dy=1.000$ mm
Maximum value of SAR (interpolated) = 2.99 W/kg

- Zoom Scan (8x8x7)/Cube 0: Measurement grid: $dx=4$ mm, $dy=4$ mm, $dz=1.4$ mm
Reference Value = 6.674 V/m; Power Drift = 0.09 dB

Peak SAR (extrapolated) = 3.36 W/kg

SAR(1 g) = 1.05 W/kg; SAR(10 g) = 0.495 W/kg

Smallest distance from peaks to all points 3 dB below = 7.6 mm

Ratio of SAR at M2 to SAR at M1 = 59.9%

Maximum value of SAR (measured) = 2.37 W/kg

