



BLUEBIRD INC.
 (Dogok-dong, SEI Tower 13~14), ., 39, Eonju-ro30-gil,
 Gangnam-gu, Seoul, Korea
 Tel. +82-70-7730-8210
 Fax +82-2-548-0870

RF EXPOSURE

(KDB 447498 D01 General RF Exposure Guidance v05r01, Section 4.3.1, 1)

1. LIMIT

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$$\frac{[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR,}^{24} \text{ where}$$

- f(GHz) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds in the step 2 below

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm according to 5) in section 4.1 is applied to determine SAR test exclusion.

Appendix A

SAR Test Exclusion Thresholds for 100 MHz – 6 GHz and ≤ 50 mm

Approximate SAR Test Exclusion Power Thresholds at Selected Frequencies and Test Separation Distances are illustrated in the following Table. The equation and threshold in section 4.3.1 must be applied to determine SAR test exclusion.

MHz	5	10	15	20	25	mm
150	39	77	116	155	194	SAR Test Exclusion Threshold (mW)
300	27	55	82	110	137	
450	22	45	67	89	112	
835	16	33	49	66	82	
900	16	32	47	63	79	
1500	12	24	37	49	61	
1900	11	22	33	44	54	
2450	10	19	29	38	48	
3600	8	16	24	32	40	
5200	7	13	20	26	33	
5400	6	13	19	26	32	
5800	6	12	19	25	31	

2. Evaluation of RF Exposure Compliance Requirements

Because the distance against the head is 0mm, a distance of 5mm is applied. At 5mm and a frequency range of 5745-5825 MHz, the maximum power allowed for SAR exclusion is 6mW (7.78dBm).

This device, in the 5745-5825 MHz range, has Average Output Power levels of 5.02 – 7.22 dBm (3.18 – 5.27 mW).

$$\therefore 3.18 < 6 \text{ mW.}$$

$$5.27 < 6 \text{ mW.}$$

Therefore, **SAR Test is not required.**