

# Korenix Technology Co., Ltd

Model Name: JetPort 5804

WLAN: 802.11 b/g

Default IP: 192.168.10.2


MAC Address:   
001277800A9C

S/N:   
JP2013020001

HW Version: V1.0

FCC ID: SSA-JP5804

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions:  
(1) this device may not cause harmful interference, and  
(2) this device must accept any interference received, including interference that may cause undesired operation.



Pin #	RS232	RS422	RS485 (4 wire)	RS485(2 wire)
1	DCD	RXD-	RXD-	
2	RXD	RXD+	RXD+	
3	TXD	TXD+	TXD+	DATA+
4	DTR	TXD-	TXD-	DATA-
5	GND	GND	GND	GND
6	DSR			
7	RTS			
8	CTS			
9	RI			

DIP 1	DIP 2	120ohm Termination Configuration
ON	ON	Long Distance 4-wire RS485 / RS422
ON	OFF	This setting will cause ERRORS !
OFF	ON	Long Distance 2-wire RS485
OFF	OFF	No Termination for RS232/422/485

Input: 12-48 VDC



# Korenix Technology Co., Ltd

Model Name: JetPort 5804i

WLAN: 802.11 b/g

Default IP: 192.168.10.2


MAC Address:   
001277800A9C

S/N:   
JP2013020001

HW Version: V1.0

FCC ID: SSA-JP5804

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions:  
(1) this device may not cause harmful interference, and  
(2) this device must accept any interference received, including interference that may cause undesired operation.



Pin #	RS232	RS422	RS485 (4 wire)	RS485(2 wire)
1	DCD	RXD-	RXD-	
2	RXD	RXD+	RXD+	
3	TXD	TXD+	TXD+	DATA+
4	DTR	TXD-	TXD-	DATA-
5	GND	GND	GND	GND
6	DSR			
7	RTS			
8	CTS			
9	RI			

DIP 1	DIP 2	120ohm Termination Configuration
ON	ON	Long Distance 4-wire RS485 / RS422
ON	OFF	This setting will cause ERRORS !
OFF	ON	Long Distance 2-wire RS485
OFF	OFF	No Termination for RS232/422/485

Input: 12-48 VDC



80 mm

60 mm

60 mm