

# STRYKER ENDOSCOPY


## SYNK RECEIVER

Model: P23366

Oct 2nd, 2013



Report No.: RF\_SL12011902-STR-001\_SYNK\_Receiver (FCC\_15.407) Rev1.2

(This report supersedes: RF\_SL12011902-STR-001\_SYNK\_Receiver (FCC\_15.407) Rev1.1)



Modifications made to the product : None

This Test Report is Issued Under the Authority of:

	
<b>David Zhang</b> Compliance Engineer	<b>Choon Sian Ooi</b> Engineering Reviewer

This test report may be reproduced in full only.  
Test result presented in this test report is applicable to the representative sample only.

# RF Test Report

To: FCC 15.407: 2012; RSS 210 Issue 8

SIEMIC, INC.  
Accessing global markets



## Laboratory Introduction

SIEMIC, headquartered in the heart of Silicon Valley, with superior facilities in US and Asia, is one of the leading independent testing and certification facilities providing customers with one-stop shop services for Compliance Testing and Global Certifications.



In addition to [testing](#) and [certification](#), SIEMIC provides initial design reviews and [compliance management](#) through out a project. Our extensive experience with [China](#), [Asia Pacific](#), [North America](#), [European](#), and [international](#) compliance requirements, assures the fastest, most cost effective way to attain regulatory compliance for the [global markets](#).

### Accreditations for Conformity Assessment

Country/Region	Accreditation Body	Scope
USA	FCC, A2LA	EMC , RF/Wireless , Telecom
Canada	IC, A2LA, NIST	EMC, RF/Wireless , Telecom
Taiwan	BSMI , NCC , NIST	EMC, RF, Telecom , Safety
Hong Kong	OFTA , NIST	RF/Wireless ,Telecom
Australia	NATA, NIST	EMC, RF, Telecom , Safety
Korea	KCC/RRA, NIST	EMI, EMS, RF , Telecom, Safety
Japan	VCCI, JATE, TELEC, RFT	EMI, RF/Wireless, Telecom
Mexico	NOM, COFETEL, Caniety	Safety, EMC , RF/Wireless, Telecom
Europe	A2LA, NIST	EMC, RF, Telecom , Safety

### Accreditations for Product Certifications

Country	Accreditation Body	Scope
USA	FCC TCB, NIST	EMC , RF , Telecom
Canada	IC FCB , NIST	EMC , RF , Telecom
Singapore	iDA, NIST	EMC , RF , Telecom
EU	NB	EMC & R&TTE Directive
Japan	MIC (RCB 208)	RF , Telecom
HongKong	OFTA (US002)	RF , Telecom



**SIEMIC, INC.**  
Accessing global markets

Title: RF Test Report of Stryker Endoscopy,  
Model : P23366  
To : FCC 15.407:2012, RSS-210 Issue 8 : 2010

Serial# RF\_SL12011902-STR-001\_SYNK\_Receiver (FCC\_15.407) Rev1.2  
Issue Date Oct 2nd, 2013  
Page 3 of 93  
[www.siemic.com](http://www.siemic.com)

---

This page has been left blank intentionally.

# CONTENTS

<b>1</b>	<b>EXECUTIVE SUMMARY &amp; EUT INFORMATION .....</b>	<b>6</b>
<b>2</b>	<b>TECHNICAL DETAILS .....</b>	<b>7</b>
<b>3</b>	<b>REPORT REVISION HISTORY.....</b>	<b>9</b>
<b>4</b>	<b>TEST SUMMARY.....</b>	<b>10</b>
<b>5</b>	<b>MEASUREMENTS, EXAMINATION AND DERIVED RESULTS .....</b>	<b>11</b>
	<b>ANNEX A. TEST INSTRUMENT &amp; METHOD.....</b>	<b>56</b>
	<b>ANNEX B EUT AND TEST SETUP PHOTOGRAPHS .....</b>	<b>60</b>
	<b>ANNEX C. TEST SETUP AND SUPPORTING EQUIPMENT .....</b>	<b>61</b>
	<b>ANNEX D USER MANUAL, BLOCK &amp; CIRCUIT DIAGRAM .....</b>	<b>65</b>
	<b>ANNEX F SIEMIC ACCREDITATION.....</b>	<b>66</b>

---

This page has been left blank intentionally.



# 1 Executive Summary & EUT information

The purpose of this test programme was to demonstrate compliance of the Stryker Endoscopy, SYNK Receiver, and Model: P23366 against the current Stipulated Standards. The SYNK Receiver has demonstrated compliance with the FCC 15.407:2012 and RSS 210 Issue 8:2010.

## Applicant & EUT Information

### Applicant Information

Applicant / Client	Stryker Endoscopy 5900 Optical Court, San Jose, California 95138 U.S.A
Manufacturer <sup>1</sup>	Stryker Endoscopy 5900 Optical Court, San Jose, California 95138 U.S.A

### EUT Information

<b>EUT Description</b>	:	SYNK Receiver
<b>Model Name</b>	:	P23366
<b>Serial No</b>	:	RX015
<b>Input Power</b>	:	100-240VAC, 50-60Hz (External Power Adapter Input) 12VDC, 1.5A (External Power Adapter Output)
<b>Frequency</b>	:	5180~5320MHz, 5500~5700MHz, 5745-5825MHz
<b>Radiated power</b>	:	<b>7.26 dBm</b>
<b>Modulation</b>	:	OFDM
<b>Classification Per Stipulated Test Standard</b>	:	UNII Device

## 2 TECHNICAL DETAILS

<b>Laboratory performing the tests</b>	<b>SIEMIC Laboratories</b> 775 Montague Expressway, Milpitas, CA 95035
<b>Date of EUT received</b>	Sep 10th, 2012
<b>Dates of test (from – to)</b>	Oct 18 <sup>th</sup> , 2012 – Jan 7 <sup>th</sup> , 2013
<b>Equipment Category</b>	UNII
<b>Standard applied</b>	See page 2
<b>FCC ID:</b>	SSH-SYNKRX
<b>IC ID:</b>	4919C-SYNKRX

### EUT Test Mode Evaluation

**EUT Major Function List**

Functions	Description
Fn#1	Wireless communication

**EUT Test Mode List**

RF Test Modes	Description	Test Configuration
RF_Test Mode	TTE test software	Continues Tx

5150~5350MHz		5470~5725MHz	
Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	5180	9	5500
2	5200	10	5520
3	5220	11	5540
4	5240	12	5560
5	5260	13	5580
6	5280	14	5660
7	5300	15	5680
8	5320	16	5700

5725~5825MHz	
Channel	Frequency (MHz)
17	5745
18	5765
19	5785
20	5805
21	5825

**Supporting Equipment & Cabling**

**Supporting equipment used with the EUT**

Equipment Description	Model	Serial No.	Manufacturer

**Details of cables between EUT and Supporting Equipment**

Connection Start		Connection Stop		Length / shielding Info	
From	I/O Port	To	I/O Port	Length(m)	Shielding

**Test Software Information**

Test Item	Software	Description
Radiated & conducted Testing	TTE test software	Set the EUT to different modulation and channel



### 3 REPORT REVISION HISTORY

Report No.	Report Version	Description	Issue Date
RF_SL12011902-STR-001_SYNK_Receiver (FCC_15.407)	Original	None	01/07/2013
RF_SL12011902-STR-001_SYNK_Receiver (FCC_15.407) Rev1.1	Rev1.1	Correct typo and test table	02/20/2013
RF_SL12011902-STR-001_SYNK_Receiver (FCC_15.407) Rev1.2	Rev1.2	Correct PSD result table	10/02/2013

## 4 TEST SUMMARY

The product was tested in accordance with the following specifications.  
All Testing has been performed according to below product classification:

UNII Device

### Test Results Summary

Test Standard		Description	Pass / Fail
47 CFR Part 15 Subpart E	RSS 210 Issue 8		
15.205	RSS 210(2.2)	Restricted Band of Operation	Pass
15.207	RSS Gen(7.2.2)	Conducted Emissions Voltage	Pass
15.209	RSS 210(2.6)	Radiated Emissions Limits; General Requirements	Pass
15.407(a)(2)	RSS210(A9.2)(2)	Occupied Bandwidth	Pass
15.407(a)(2)	RSS210(A9.2)(1)	Peak Output Power	Pass
15.407(a)(2)	RSS210(A9.2)(1)	Peak Power Spectral Density	Pass
15.407(a)(2)		Power Reduction (antenna gain > 6dBi)	Pass
15.407(a)(6)		Peak Excursion Ratio	Pass
15.407(b)(6)	RSS Gen(7.2.2)	AC Conducted Emissions	Pass
15.407(b)(2)	RSS210(A9.3)(1)	Radiated Spurious Emissions > 1GHz	Pass
15.407(b)(6)	RSS210(A9.3)(1)	Radiated Spurious Emissions < 1GHz	Pass
15.407(f)	RSS Gen (5.5)	RF Exposure	Pass
15.407(g)	RSS210(A9.5)(e)	Frequency Stability	Pass*
	RSS210(A9.5)(g)	User Manual	Pass
ANSI C63.4: 2009/ RSS-Gen Issue 3: 2010			
PS: All measurement uncertainties are not taken into consideration for all presented test result.			

\*The applicant shall ensure frequency stability by showing that an emission is maintained within the band of operation under all normal operating conditions as specified in the user's manual.

## **5 MEASUREMENTS, EXAMINATION AND DERIVED RESULTS**

### **5.1 Antenna Requirement**

**Requirement(s):** RSS Gen

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

Antenna requirement must meet at least one of the following:

- a) Antenna must be permanently attached to the device.
- b) Antenna must use a unique type of connector to attach to the device.
- c) Device must be professionally installed. Installer shall be responsible for ensuring that the correct antenna is employed with the device.

EUT antenna attach to the PCB.

The peak antenna gain of antenna is: 1.9dBi .

**Results:** PASS


## 5.2 Conducted Emissions Voltage

Frequency of emission (MHz)	Conducted limit (dB $\mu$ V)	
	Quasi-peak	Average
0.15–0.5	66 to 56*	56 to 46*
0.5–5	56	46
5–30	60	50

\*Decreases with the logarithm of the frequency.

1. All possible modes of operation were investigated. Only the 6 worst case emissions measured, using the correct CISPR and Average detectors, are reported. All other emissions were relatively insignificant.
  2. A "-ve" margin indicates a PASS as it refers to the margin present below the limit line at the particular frequency.
  3. Conducted Emissions Measurement Uncertainty  
All test measurements carried out are traceable to national standards. The uncertainty of the measurement at a confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2, in the range 9kHz – 30MHz (Average & Quasi-peak) is  $\pm 3.5$ dB.
  4. Environmental Conditions

Temperature	23°C
Relative Humidity	50%
Atmospheric Pressure	1019mbar
- Test Date : Oct 18th, 2012 - Jan 7th, 2013  
Tested By : David Zhang




Quasi-Peak Limit

Average Limit

**Phase Line Plot at 120Vac, 60Hz**

Frequency (MHz)	QP Value (dB $\mu$ V)	Class B Limit (dB)	Margin (dB)	Avg Value (dB $\mu$ V)	Class B Limit (dB)	Margin (dB)	Line
0.15	55.75	66.19	-10.44	41.59	56.19	-14.60	Phase
0.41	36.26	57.59	-21.34	28.51	47.59	-19.09	Phase
0.25	40.35	61.86	-21.52	25.30	51.86	-26.57	Phase
0.52	31.45	56.00	-24.55	28.58	46.00	-17.42	Phase
0.90	30.97	56.00	-25.03	24.39	46.00	-21.61	Phase
0.92	30.33	56.00	-25.67	21.80	46.00	-24.20	Phase

**Final plot**



Quasi-Peak Limit

Average Limit

**Neutral Line Plot at 120Vac, 60Hz**

Frequency (MHz)	QP Value (dBµV)	Class B Limit (dB)	Margin (dB)	Avg Value (dBµV)	Class B Limit (dB)	Margin (dB)	Line
0.15	55.26	66.19	-10.93	41.37	56.19	-14.82	Neutral
0.25	39.95	62.00	-22.05	26.46	52.00	-25.54	Neutral
0.41	34.09	57.59	-23.51	26.26	47.59	-21.34	Neutral
0.52	31.14	56.00	-24.86	27.74	46.00	-18.26	Neutral
0.81	29.88	56.00	-26.12	24.06	46.00	-21.94	Neutral
0.68	28.45	56.00	-27.55	21.93	46.00	-24.07	Neutral

## 5.3 26dB & 99% Occupied Bandwidth

1. Conducted Measurement  
EUT was set for low , mid, high channel with modulated mode and highest RF output power.  
The spectrum analyzer was connected to the antenna terminal.
2. Conducted Emissions Measurement Uncertainty  
All test measurements carried out are traceable to national standards. The uncertainty of the measurement at a confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2, in the range 30MHz – 40GHz is  $\pm 1.5\text{dB}$ .
3. Environmental Conditions

Temperature	23°C
Relative Humidity	50%
Atmospheric Pressure	1019mbar
4. Test Date : Oct 18th, 2012 - Jan 7th, 2013  
Tested By : David Zhang

**Requirement(s):** The 26dB or 99% bandwidths were measured at the antenna terminal using a spectrum analyzer. 26 dB BW spectrum analyzer setting: RBW = approximately 1% of the emission BW and VBW = approximately 3 times RBW.

Test Result :

### 26dB Bandwidth


Index	Mode	CH No.	Frequency (MHz)	26dB OBW (MHz)	Limit (MHz)	Results
1	5.15–5.25 GHz-TX	Low	5180	19.38	N/A	Pass
2	5.15–5.25 GHz-TX	Mid	5200	19.45	N/A	Pass
3	5.15–5.25 GHz-TX	High	5240	19.60	N/A	Pass
4	5.25–5.35 GHz-TX	Low	5260	19.38	N/A	Pass
5	5.25–5.35 GHz-TX	Mid	5300	19.45	N/A	Pass
6	5.25–5.35 GHz-TX	High	5320	19.68	N/A	Pass
7	5.47–5.725 GHz-TX	Low	5500	19.38	N/A	Pass
8	5.47–5.725 GHz-TX	Mid	5560	19.23	N/A	Pass
9	5.47–5.725 GHz-TX	High	5700	19.30	N/A	Pass

### 99% Occupied Bandwidth


Index	Mode	CH No.	Frequency (MHz)	99% OBW (MHz)	Limit (MHz)	Results
1	5.15–5.25 GHz-TX	Low	5180	15.772	N/A	Pass
2	5.15–5.25 GHz-TX	Mid	5200	15.777	N/A	Pass
3	5.15–5.25 GHz-TX	High	5240	15.790	N/A	Pass
4	5.25–5.35 GHz-TX	Low	5260	15.756	N/A	Pass
5	5.25–5.35 GHz-TX	Mid	5300	15.794	N/A	Pass
6	5.25–5.35 GHz-TX	High	5320	15.771	N/A	Pass
7	5.47–5.725 GHz-TX	Low	5500	15.789	N/A	Pass
8	5.47–5.725 GHz-TX	Mid	5560	15.784	N/A	Pass
9	5.47–5.725 GHz-TX	High	5700	15.620	N/A	Pass

**26dB Bandwidth Test Plots**

26dB BW-TX-Low-5180




26dB BW-TX-Mid-5200







26dB BW-TX -High-5240




26dB BW-TX -Low-5260




26dB BW-TX -Mid-5300




26dB BW-TX -High-5320




26dB BW-TX -Low-5500



26dB BW-TX -Mid-5560




26dB BW-TX -High-5700




**99% bandwidth Test Plots**


99% BW-TX -Low-5180




99% BW-TX -Mid-5200




99% BW-TX -High-5240




99% BW-TX -Low-5260




99% BW-TX -Mid-5300




99% BW-TX -High-5320



99% BW-TX -Low-5500




99% BW-TX -Mid-5560





99% BW-TX -High-5700



## **5.4 Peak Power Spectral Density and Peak Excursion Ratio**

1. **Conducted Measurement**  
 EUT was set for low , mid, high channel with modulated mode and highest RF output power.  
 The spectrum analyzer was connected to the antenna terminal.
2. **Conducted Emissions Measurement Uncertainty**  
 All test measurements carried out are traceable to national standards. The uncertainty of the measurement at a confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2, in the range 30MHz – 40GHz is  $\pm 1.5\text{dB}$ .
3. **Environmental Conditions**

Temperature	23°C
Relative Humidity	50%
Atmospheric Pressure	1019mbar
4. Test Date : Oct 18th, 2012 - Jan 7th, 2013  
 Tested By : David Zhang

**Requirement(s):** FCC 15.407 (a); RSS 210 A9.2 (1)

**PPSD Procedures:** The peak power spectral density (EIRP) measured at the antenna terminal using a spectrum analyzer. RBW=1MHz, VBW=3MHz, Detector = RMS. Use the peak search function on the spectrum analyzer to find the peak of the spectrum.

**Peak Excursion Ratio Procedures:**

The peak excursion ratio was measured at the antenna terminal using a spectrum analyzer. The RBW = 1MHz VBW = 3 MHz (peak detector). Compute the ratio of the maximum of the peak-max-hold spectrum to the PPSD.

**Test Result : Pass**

**FCC Part 15.407 (a): Power Spectral Density and Peak Excursion Ratio Test Result:**

Peak Power Spectral Density

Antenna Gain = 1.9 dBi


Index	Mode	CH No.	Frequency (MHz)	PSD (dBm/MHz)	Combined PSD (dBm/MHz)	Limit (dBm/MHz)	PSD EIRP (dBm/MHz)	PSD EIRP Limit (dBm/MHz)
1	5.15-5.25 GHz-Port1	Low	5180	-6.157	N/A	4	-4.26	10
2	5.15-5.25 GHz-Port1	Mid	5200	-6.247	N/A	4	-4.35	10
3	5.15-5.25 GHz-Port1	High	5240	-6.730	N/A	4	-4.83	10
4	5.25-5.35 GHz-Port1	Low	5260	-6.767	N/A	11	-4.87	N/A
5	5.25-5.35 GHz-Port1	Mid	5300	-7.171	N/A	11	-5.27	N/A
6	5.25-5.35 GHz-Port1	High	5320	-6.775	N/A	11	-4.88	N/A
7	5.47-5.725 GHz-Port1	Low	5500	-4.626	N/A	11	-2.73	N/A
8	5.47-5.725 GHz-Port1	Mid	5560	-3.636	N/A	11	-1.74	N/A
9	5.47-5.725 GHz-Port1	High	5700	-3.220	N/A	11	-1.32	N/A

Index	Mode	CH No.	Frequency (MHz)	Measured Peak Excursion ratio (dB)	Combined Peak Excursion ratio (dB)	Limit (dB)
1	5.15-5.25 GHz-Port1	Low	5180	10.41	N/A	13
2	5.15-5.25 GHz-Port1	Mid	5200	10.07	N/A	13
3	5.15-5.25 GHz-Port1	High	5240	11.05	N/A	13
4	5.25-5.35 GHz-Port1	Low	5260	9.925	N/A	13
5	5.25-5.35 GHz-Port1	Mid	5300	9.924	N/A	13
6	5.25-5.35 GHz-Port1	High	5320	10.24	N/A	13
7	5.47-5.725 GHz-Port1	Low	5500	10.08	N/A	13
8	5.47-5.725 GHz-Port1	Mid	5560	9.828	N/A	13
9	5.47-5.725 GHz-Port1	High	5700	11.54	N/A	13




### PSD Test Plots


PSD- TX-Low-Port1-5180




PSD- TX-Mid-Port1-5200




PSD- TX-High-Port1-5240




PSD- TX-Low-Port1-5260




PSD- TX-Mid-Port1-5300




PSD- TX-High-Port1-5320



PSD- TX-Low-Port1-5500



PSD- TX-Mid-Port1-5560









**Peak Excursion Ratio Test Plots**


Peak Excursion Ratio TX-Low-Port1-5180




Peak Excursion Ratio TX-Mid-Port1-5200




Peak Excursion Ratio TX-High-Port1-5240




Peak Excursion Ratio TX-Low-Port1-5260




Peak Excursion Ratio TX-Mid-Port1-5300




Peak Excursion Ratio TX-High-Port1-5320




Peak Excursion Ratio TX-Low-Port1-5500



Peak Excursion Ratio TX-Mid-Port1-5560



Peak Excursion Ratio TX-High-Port1-5700



## 5.5 Peak Output Power

1. Conducted Measurement  
EUT was set for low , mid, high channel with modulated mode and highest RF output power.  
The spectrum analyzer was connected to the antenna terminal.
2. Conducted Emissions Measurement Uncertainty  
All test measurements carried out are traceable to national standards. The uncertainty of the measurement at a confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2, in the range 30MHz – 40GHz is  $\pm 1.5$ dB.
3. Environmental Conditions  

Temperature	23°C
Relative Humidity	50%
Atmospheric Pressure	1019mbar
4. Test Date : Oct 18th, 2012 - Jan 7th, 2013  
Tested By : David Zhang

**Requirement(s):** 15.407(a); RSS 210 A9.2(1)

**Procedures:** The peak output power was measured at the antenna terminal using Acceptable Procedures: Peak conducted transmit output power outlined in FCC DA 02-2138 Appendix A.

For the band 5.15–5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed the lesser of 50 mW or  $4 \text{ dBm} + 10 \log B$ , where B is the 26–dB emission bandwidth in MHz.

For the 5.25–5.35 GHz and 5.47–5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or  $11 \text{ dBm} + 10 \log B$ , where B is the 26 dB emission bandwidth in megahertz.

For the band 5.725–5.825 GHz, the maximum conducted output power over the frequency band of operation shall not exceed the lesser of 1 W or  $17 \text{ dBm} + 10 \log B$ , where B is the 26-dB emission bandwidth in MHz.

FCC Part 15.407(a) Calculated Power Limit

Band 5.15–5.25 GHz / 20MHz BW:	EBW = 19.60MHz	Peak Power Limit = 16.92 dBm
Band 5.25–5.35 GHz / 20MHz BW:	EBW = 19.68MHz	Peak Power Limit = 23.94 dBm
Band 5.470–5.725 GHz / 20MHz BW:	EBW = 19.38MHz	Peak Power Limit = 23.87 dBm

RSS 210 A9.2 (1) Calculated Power Limit

Band 5.15–5.25 GHz / 20MHz BW:	99%BW = 15.79MHz	Conducted Power Limit= 20.08 dBm
		E.I.R.P Power Limit = 21.98 dBm
Band 5.25–5.35 GHz / 20MHz BW:	99%BW = 15.79MHz	Conducted Power Limit= 21.08 dBm
		E.I.R.P Power Limit = 22.98 dBm
Band 5.470–5.725 GHz / 20MHz BW:	99%BW = 15.79MHz	Conducted Power Limit= 21.08 dBm
		E.I.R.P Power Limit = 22.98 dBm

**FCC Part 15.407 (a): Peak Output Power Test Result:**

Conducted Power Test Result for FCC

Index	Mode	CH No.	Frequency (MHz)	Output Power (dBm)	Combined Power (dBm)	Limit (dBm)
1	5.15-5.25 GHz-Port1	Low	5180	5.23	5.23	16.92
2	5.15-5.25 GHz-Port1	Mid	5200	4.72	4.72	16.92
3	5.15-5.25 GHz-Port1	High	5240	3.78	3.78	16.92
4	5.25-5.35 GHz-Port1	Low	5260	3.53	3.53	23.94
5	5.25-5.35 GHz-Port1	Mid	5300	3.56	3.56	23.94
6	5.25-5.35 GHz-Port1	High	5320	3.80	3.80	23.94
7	5.47-5.725 GHz-Port1	Low	5500	5.74	5.74	23.87
8	5.47-5.725 GHz-Port1	Mid	5560	6.62	6.62	23.87
9	5.47-5.725 GHz-Port1	High	5700	7.15	7.15	23.87

Conducted Power Test Result for RSS210

Index	Mode	CH No.	Frequency (MHz)	Output Power (dBm)	Combined Power (dBm)	Limit (dBm)
1	5.15-5.25 GHz-Port1	Low	5180	5.23	5.23	20.08
2	5.15-5.25 GHz-Port1	Mid	5200	4.72	4.72	20.08
3	5.15-5.25 GHz-Port1	High	5240	3.78	3.78	20.08
4	5.25-5.35 GHz-Port1	Low	5260	3.53	3.53	21.08
5	5.25-5.35 GHz-Port1	Mid	5300	3.56	3.56	21.08
6	5.25-5.35 GHz-Port1	High	5320	3.80	3.80	21.08
7	5.47-5.725 GHz-Port1	Low	5500	5.74	5.74	21.08
8	5.47-5.725 GHz-Port1	Mid	5560	6.62	6.62	21.08
9	5.47-5.725 GHz-Port1	High	5700	7.15	7.15	21.08


EIRP Test Result for RSS 210 – Antenna Gain: 1.9dBi

Index	Mode	CH No.	Frequency (MHz)	Combined Power (dBm)	EIRP (dBm)	Limit (dBm)
1	5.15-5.25 GHz-Port1	Low	5180	5.23	7.13	21.98
2	5.15-5.25 GHz-Port1	Mid	5200	4.72	6.62	21.98
3	5.15-5.25 GHz-Port1	High	5240	3.78	5.68	21.98
4	5.25-5.35 GHz-Port1	Low	5260	3.53	5.43	22.98
5	5.25-5.35 GHz-Port1	Mid	5300	3.56	5.46	22.98
6	5.25-5.35 GHz-Port1	High	5320	3.80	5.70	22.98
7	5.47-5.725 GHz-Port1	Low	5500	5.74	7.64	22.98
8	5.47-5.725 GHz-Port1	Mid	5560	6.62	8.52	22.98
9	5.47-5.725 GHz-Port1	High	5700	7.15	9.05	22.98




**Peak Output Power Test Plots**


Output Power -TX-Low-Port1-5180




Output Power -TX-Mid-Port1-5200




Output Power -TX-High-Port1-5240




Output Power -TX-Low-Port1-5260




Output Power -TX-Mid-Port1-5300




Output Power -TX-High-Port1-5320




Output Power -TX-Low-Port1-5500



Output Power -TX-Mid-Port1-5560



Output Power -TX-High-Port1-5700



## 5.6 Radiated Spurious Emission < 1GHz

1. All possible modes of operation were investigated. Only the 6 worst case emissions measured, using the correct CISPR detectors, are reported. All other emissions were relatively insignificant.
2. A "-ve" margin indicates a PASS as it refers to the margin present below the limit line at the particular frequency.
3. Radiated Emissions Measurement Uncertainty  
All test measurements carried out are traceable to national standards. The uncertainty of the measurement at a confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2, in the range 30MHz – 1GHz (QP only @ 3m & 10m) is +5.6dB/-4.5dB (for EUTs < 0.5m X 0.5m X 0.5m).
4. Environmental Conditions
 

Temperature	23°C
Relative Humidity	50%
Atmospheric Pressure	1019mbar

Test Date : Oct 18th, 2012 - Jan 7th, 2013  
 Tested By : David Zhang

**Requirement(s):** 15.205; RSS 210 (2.6)

**Procedures:** Radiated emissions were measured according to ANSI C63.4. Equipment was tested at low, mid and hi channel with different channel bandwidth and reported the worst case.


Sample Calculation: Corrected Amplitude = Raw Amplitude + Antenna Factor + Cable Loss

**Test Result: Pass**



### Radiated Emission Plot

#### Radiated Emissions for SYNK Receiver with host : SYNK Wireless Receiver (Model number: 0240031030)




Limit

30MHz ~1000MHz Result @ 3m

Frequency (MHz)	Corrected Quasi-Peak (dBμV/m) @ 3m	Turntable position (deg)	Polarity	Antenna height (cm)	Limit (dBμV/m)	Margin (dB)
297.03	39.99	148.00	H	124.00	46.00	-6.01
594.01	40.49	208.00	H	103.00	46.00	-5.51
77.89	27.69	154.00	V	193.00	40.00	-12.31
84.64	27.62	280.00	V	112.00	40.00	-12.38
445.47	36.22	144.00	V	107.00	46.00	-9.78
921.50	29.96	260.00	H	347.00	46.00	-16.04

### Radiated Emission Plot

Radiated Emissions for SYNK Receiver with host : SYNK VisionPro 26" Wireless LED Display (Model number: 0240031000)



Limit

30MHz ~1000MHz Result @ 3m

Frequency (MHz)	Corrected Quasi-Peak (dBμV/m) @ 3m	Turntable position (deg)	Polarity	Antenna height (cm)	Limit (dBμV/m)	Margin (dB)
33.33	39.58	0.00	V	106.00	40.00	-0.42
742.54	43.93	229.00	H	123.00	46.00	-2.07
816.86	44.75	222.00	H	113.00	46.00	-1.25
519.87	38.15	335.00	V	124.00	46.00	-7.85
98.44	38.61	148.00	H	223.00	43.52	-4.91
37.275	38.17	177.00	V	108.00	40.00	-1.83



## 5.7 Radiated Spurious Emissions > 1GHz

1. All possible modes of operation were investigated. Only the 6 worst case emissions measured, using the correct CISPR detectors, are reported. All other emissions were relatively insignificant.
2. A "-ve" margin indicates a PASS as it refers to the margin present below the limit line at the particular frequency.
3. Radiated Emissions Measurement Uncertainty  
All test measurements carried out are traceable to national standards. The uncertainty of the measurement at a confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2, in the range 1GHz – 40GH is +5.6dB/-4.5dB (for EUTs < 0.5m X 0.5m X 0.5m).
4. Environmental Conditions
 

Temperature	23°C
Relative Humidity	50%
Atmospheric Pressure	1019mbar

Test Date : Oct 18th, 2012 - Jan 7th, 2013  
Tested By : David Zhang

**Requirement(s):** FCC 15.407; RSS 210 A9.3(1)

**Procedures:** Equipment was setup in a semi-anechoic chamber. For measurements above 1 GHz an average measurement was taken with a 1MHz resolution bandwidth and a 10Hz video bandwidth was used. The EUT was tested at low and high with the highest output power. Emissions were investigated up to 40 GHz.

- 27 dBm = 68.2 dBμV/m at 3 meter distance.

Sample Calculation: EUT Field Strength = Raw Amplitude – Amplifier Gain + Antenna Factor + Cable Loss + Filter Attenuation (if used)

**Test Result: Pass**

**Test Result for SYNK Receiver with host : SYNK Wireless Receiver (Model number: 0240031030)**

**5180MHz @ 3 Meters**

Frequency	Reading	Direction	Height	Polar	Antenna Loss	Cable loss	Amplifier	Corrected Reading	15.407/15.209 Limit	15.407/15.209 Margin	Detector
GHz	(dBuV/m)	Degree	Meter	H / V	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/m)		
10.36	30.54	245	1.65	v	39.40	6.64	32.77	43.81	68.3	-24.49	Peak
10.36	32.22	286	1.00	h	39.40	6.64	32.77	45.49	68.3	-22.81	Peak
5.15	36.20	221	1.83	v	32.90	4.32	32.55	40.87	68.3	-27.43	Peak
5.15	38.54	170	2.19	h	32.90	4.32	32.55	43.21	68.3	-25.09	Peak

**Note:** Emission was scanned up to 40GHz; no emissions were detected above the noise floor which was at least 20dB below the specification limit

**5220MHz @ 3 Meters**

Frequency	Reading	Direction	Height	Polar	Antenna Loss	Cable loss	Amplifier	Corrected Reading	15.407/15.209 Limit	15.407/15.209 Margin	Detector
GHz	(dBuV/m)	Degree	Meter	H / V	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/m)		
10.882	31.84	11	2.85	v	40.30	6.905	32.83	46.22	74	-27.79	Peak
10.882	31.13	175	1.00	h	40.30	6.905	32.83	45.50	74	-28.50	Peak

**Note:** Emission was scanned up to 40GHz; no emissions were detected above the noise floor which was at least 20dB below the specification limit

**5240MHz @ 3 Meters**

Frequency	Reading	Direction	Height	Polar	Antenna Loss	Cable loss	Amplifier	Corrected Reading	15.407/15.209 Limit	15.407/15.209 Margin	Detector
GHz	(dBuV/m)	Degree	Meter	H / V	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/m)		
10.48	29.74	234	1.56	v	39.40	6.64	32.77	43.01	68.3	-25.29	Peak
10.48	32.06	198	1.00	h	39.40	6.64	32.77	45.33	68.3	-22.97	Peak

**Note:** Emission was scanned up to 40GHz; no emissions were detected above the noise floor which was at least 20dB below the specification limit

### 5260MHz @ 3 Meters

Frequency	Reading	Direction	Height	Polar	Antenna Loss	Cable loss	Amplifier	Corrected Reading	15.407/15.209 Limit	15.407/15.209 Margin	Detector
GHz	(dBuV/m)	Degree	Meter	H / V	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/m)		
10.52	35.08	117	1.56	v	40.30	6.91	32.83	49.46	68.3	-18.84	Peak
10.52	36.90	251	1.00	h	40.30	6.91	32.83	51.28	68.3	-17.02	Peak

**Note:** Emission was scanned up to 40GHz; no emissions were detected above the noise floor which was at least 20dB below the specification limit

### 5300MHz @ 3 Meters

Frequency	Reading	Direction	Height	Polar	Antenna Loss	Cable loss	Amplifier	Corrected Reading	15.407/15.209 Limit	15.407/15.209 Margin	Detector
GHz	(dBuV/m)	Degree	Meter	H / V	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/m)		
10.6	34.95	117	1.65	v	40.30	6.91	32.83	49.33	74	-24.67	Peak
10.6	36.76	285	1.00	h	40.30	6.91	32.83	51.14	74	-22.86	Peak
10.6	28.81	117	1.65	v	40.30	6.91	32.83	43.19	54	-10.81	Ave
10.6	30.00	285	1.56	h	40.30	6.91	32.83	44.38	54	-9.62	Ave

**Note:** Emission was scanned up to 40GHz; no emissions were detected above the noise floor which was at least 20dB below the specification limit

### 5320MHz @ 3 Meters

Frequency	Reading	Direction	Height	Polar	Antenna Loss	Cable loss	Amplifier	Corrected Reading	15.407/15.209 Limit	15.407/15.209 Margin	Detector
GHz	(dBuV/m)	Degree	Meter	H / V	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/m)		
10.64	36.01	232	1.65	v	40.30	6.91	32.83	50.39	74	-23.61	Peak
10.64	38.48	145	1.00	h	40.30	6.91	32.83	52.86	74	-21.14	Peak
10.64	30.99	232	1.65	v	40.30	6.91	32.83	45.37	54	-8.63	Ave
10.64	32.71	145	1.56	h	40.30	6.91	32.83	47.09	54	-6.91	Ave
5.35	45.24	125	1.00	v	32.90	4.32	32.55	49.91	68.3	-18.39	Peak
5.35	47.98	232	1.00	h	32.90	4.32	32.55	52.65	68.3	-15.65	Peak

**Note:** Emission was scanned up to 40GHz; no emissions were detected above the noise floor which was at least 20dB below the specification limit

### 5500MHz @ 3 Meters

Frequency	Reading	Direction	Height	Polar	Antenna Loss	Cable loss	Amplifier	Corrected Reading	15.407/15.209 Limit	15.407/15.209 Margin	Detector
GHz	(dBuV/m)	Degree	Meter	H / V	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/m)		
11	38.89	289	1.92	v	40.40	7.17	32.7	53.76	74	-20.24	Peak
11	39.80	251	1.00	h	40.40	7.17	32.7	54.67	74	-19.33	Peak
11	33.15	289	1.92	v	40.40	7.17	32.7	48.02	54	-5.98	Ave
11	34.21	251	1.83	h	40.40	7.17	32.7	49.08	54	-4.92	Ave
5.47	25.50	232	1.00	v	32.90	4.32	0	62.72	68.3	-5.58	Peak
5.47	24.20	154	1.00	h	32.90	4.32	0	61.42	68.3	-6.88	Peak

**Note:** Emission was scanned up to 40GHz; no emissions were detected above the noise floor which was at least 20dB below the specification limit

### 5560MHz @ 3 Meters

Frequency	Reading	Direction	Height	Polar	Antenna Loss	Cable loss	Amplifier	Corrected Reading	15.407/15.209 Limit	15.407/15.209 Margin	Detector
GHz	(dBuV/m)	Degree	Meter	H / V	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/m)		
11.12	36.04	261	1.83	v	40.40	7.17	32.7	50.91	74	-23.09	Peak
11.12	37.75	170	1.00	h	40.40	7.17	32.7	52.62	74	-21.38	Peak
11.12	30.19	261	1.83	v	40.40	7.17	32.7	45.06	54	-8.94	Ave
11.12	31.21	170	1.74	h	40.40	7.17	32.7	46.08	54	-7.92	Ave

**Note:** Emission was scanned up to 40GHz; no emissions were detected above the noise floor which was at least 20dB below the specification limit

### 5700MHz @ 3 Meters

Frequency	Reading	Direction	Height	Polar	Antenna Loss	Cable loss	Amplifier	Corrected Reading	15.407/15.209 Limit	15.407/15.209 Margin	Detector
GHz	(dBuV/m)	Degree	Meter	H / V	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/m)		
11.40	35.84	279	1.70	v	40.40	7.17	32.7	50.71	74	-23.29	Peak
11.40	37.12	230	1.00	h	40.40	7.17	32.7	51.99	74	-22.01	Peak
11.40	30.10	279	1.70	v	40.40	7.17	32.7	44.97	54	-9.03	Ave
11.40	30.96	230	1.87	h	40.40	7.17	32.7	45.83	54	-8.18	Ave
5.725	23.29	117	1.00	v	33.40	4.56	0	61.25	68.3	-7.05	Peak
5.725	25.00	229	1.00	h	33.40	4.56	0	62.96	68.3	-5.34	Peak

**Note:** Emission was scanned up to 40GHz; no emissions were detected above the noise floor which was at least 20dB below the specification limit

**Test Result for SYNK Receiver with host : SYNK VisionPro 26" Wireless LED Display (Model number: 0240031000)**

**5180MHz @ 3 Meters**

Frequency	Reading	Direction	Height	Polar	Antenna Loss	Cable loss	Amplifier	Corrected Reading	15.407/15.209 Limit	15.407/15.209 Margin	Detector
GHz	(dBuV/m)	Degree	Meter	H / V	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/m)		
10.36	31.93	242	1.82	v	39.40	6.64	32.77	45.20	68.3	-23.10	Peak
10.36	33.47	278	1.22	h	39.40	6.64	32.77	46.74	68.3	-21.56	Peak
5.15	37.13	220	1.98	v	32.90	4.32	32.55	41.80	68.3	-26.50	Peak
5.15	39.29	174	2.31	h	32.90	4.32	32.55	43.96	68.3	-24.34	Peak

**Note:** Emission was scanned up to 40GHz; no emissions were detected above the noise floor which was at least 20dB below the specification limit

**5220MHz @ 3 Meters**

Frequency	Reading	Direction	Height	Polar	Antenna Loss	Cable loss	Amplifier	Corrected Reading	15.407/15.209 Limit	15.407/15.209 Margin	Detector
GHz	(dBuV/m)	Degree	Meter	H / V	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/m)		
10.882	33.12	31	2.92	v	40.30	6.905	32.83	47.50	74	-26.50	Peak
10.882	32.47	179	1.22	h	40.30	6.905	32.83	46.84	74	-27.16	Peak

**Note:** Emission was scanned up to 40GHz; no emissions were detected above the noise floor which was at least 20dB below the specification limit

**5240MHz @ 3 Meters**

Frequency	Reading	Direction	Height	Polar	Antenna Loss	Cable loss	Amplifier	Corrected Reading	15.407/15.209 Limit	15.407/15.209 Margin	Detector
GHz	(dBuV/m)	Degree	Meter	H / V	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/m)		
10.48	31.19	232	1.74	v	39.40	6.64	32.77	44.46	68.3	-23.84	Peak
10.48	33.33	199	1.22	h	39.40	6.64	32.77	46.60	68.3	-21.70	Peak

**Note:** Emission was scanned up to 40GHz; no emissions were detected above the noise floor which was at least 20dB below the specification limit

### 5260MHz @ 3 Meters

Frequency	Reading	Direction	Height	Polar	Antenna Loss	Cable loss	Amplifier	Corrected Reading	15.407/15.209 Limit (dBuV/m)	15.407/15.209 Margin	Detector
GHz	(dBuV/m)	Degree	Meter	H / V	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	Margin	
10.52	36.10	126	1.74	v	40.30	6.91	32.83	50.48	68.3	-17.82	Peak
10.52	37.78	247	1.22	h	40.30	6.91	32.83	52.16	68.3	-16.14	Peak

**Note:** Emission was scanned up to 40GHz; no emissions were detected above the noise floor which was at least 20dB below the specification limit

### 5300MHz @ 3 Meters

Frequency	Reading	Direction	Height	Polar	Antenna Loss	Cable loss	Amplifier	Corrected Reading	15.407/15.209 Limit (dBuV/m)	15.407/15.209 Margin	Detector
GHz	(dBuV/m)	Degree	Meter	H / V	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	Margin	
10.60	35.98	126	1.82	v	40.30	6.91	32.83	50.36	74	-23.64	Peak
10.60	37.65	278	1.22	h	40.30	6.91	32.83	52.03	74	-21.97	Peak
10.60	30.34	126	1.82	v	40.30	6.91	32.83	44.72	54	-9.28	Ave
10.60	31.43	278	1.74	h	40.30	6.91	32.83	45.81	54	-8.19	Ave

**Note:** Emission was scanned up to 40GHz; no emissions were detected above the noise floor which was at least 20dB below the specification limit

### 5320MHz @ 3 Meters

Frequency	Reading	Direction	Height	Polar	Antenna Loss	Cable loss	Amplifier	Corrected Reading	15.407/15.209 Limit (dBuV/m)	15.407/15.209 Margin	Detector
GHz	(dBuV/m)	Degree	Meter	H / V	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	Margin	
10.64	36.96	230	1.82	v	40.30	6.91	32.83	51.34	74	-22.66	Peak
10.64	39.23	152	1.22	h	40.30	6.91	32.83	53.61	74	-20.39	Peak
10.64	32.34	230	1.82	v	40.30	6.91	32.83	46.72	54	-7.28	Ave
10.64	33.92	152	1.74	h	40.30	6.91	32.83	48.30	54	-5.70	Ave
5.35	45.45	134	1.22	v	32.90	4.32	32.55	50.12	68.3	-18.18	Peak
5.35	47.97	230	1.22	h	32.90	4.32	32.55	52.64	68.3	-15.66	Peak

**Note:** Emission was scanned up to 40GHz; no emissions were detected above the noise floor which was at least 20dB below the specification limit

### 5500MHz @ 3 Meters

Frequency	Reading	Direction	Height	Polar	Antenna Loss	Cable loss	Amplifier	Corrected Reading	15.407/15.209 Limit	15.407/15.209 Margin	Detector
GHz	(dBuV/m)	Degree	Meter	H / V	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/m)		
11.00	39.61	281	2.07	v	40.40	7.17	32.7	54.48	74	-19.52	Peak
11.00	40.45	247	1.22	h	40.40	7.17	32.7	55.32	74	-18.68	Peak
11.00	34.33	281	2.07	v	40.40	7.17	32.7	49.20	54	-4.80	Ave
11.00	35.30	247	1.98	h	40.40	7.17	32.7	50.17	54	-3.83	Ave
5.47	27.29	230	1.22	v	32.90	4.32	0	64.51	68.3	-3.79	Peak
5.47	26.09	160	1.22	h	32.90	4.32	0	63.31	68.3	-4.99	Peak

**Note:** Emission was scanned up to 40GHz; no emissions were detected above the noise floor which was at least 20dB below the specification limit

### 5560MHz @ 3 Meters

Frequency	Reading	Direction	Height	Polar	Antenna Loss	Cable loss	Amplifier	Corrected Reading	15.407/15.209 Limit	15.407/15.209 Margin	Detector
GHz	(dBuV/m)	Degree	Meter	H / V	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/m)		
11.12	36.99	256	1.98	v	40.40	7.17	32.7	51.86	74	-22.14	Peak
11.12	38.56	174	1.22	h	40.40	7.17	32.7	53.43	74	-20.57	Peak
11.12	31.60	256	1.98	v	40.40	7.17	32.7	46.47	54	-7.53	Ave
11.12	32.54	174	1.90	h	40.40	7.17	32.7	47.41	54	-6.59	Ave

**Note:** Emission was scanned up to 40GHz; no emissions were detected above the noise floor which was at least 20dB below the specification limit

### 5700MHz @ 3 Meters

Frequency	Reading	Direction	Height	Polar	Antenna Loss	Cable loss	Amplifier	Corrected Reading	15.407/15.209 Limit	15.407/15.209 Margin	Detector
GHz	(dBuV/m)	Degree	Meter	H / V	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/m)		
11.40	36.80	272	1.86	v	40.40	7.17	32.7	51.67	74	-22.33	Peak
11.40	37.98	228	1.22	h	40.40	7.17	32.7	52.85	74	-21.15	Peak
11.40	31.52	272	1.86	v	40.40	7.17	32.7	46.39	54	-7.61	Ave
11.40	32.31	228	2.02	h	40.40	7.17	32.7	47.18	54	-6.82	Ave
5.725	25.26	126	1.22	v	33.40	4.56	0	63.22	68.3	-5.08	Peak
5.725	26.83	227	1.22	h	33.40	4.56	0	64.79	68.3	-3.51	Peak

**Note:** Emission was scanned up to 40GHz; no emissions were detected above the noise floor which was at least 20dB below the specification limit

**Annex A. TEST INSTRUMENT & METHOD**

**Annex A.i. TEST INSTRUMENTATION & GENERAL PROCEDURES**

Instrument	Model	Serial #	Calibration Date	Calibration Due	Calibrate Cycle
<b>CONDUCTED EMISSIONS</b>					
R & S Receiver	ESIB 40	100179	4/20/2012	4/20/2013	1year
R&S LISN	ESH2-Z5	861741/013	05/18/2012	05/18/2013	1year
CHASE LISN	MN2050B	1018	05/18/2012	05/18/2013	1year
Sekonic Hygro Hermograph	ST-50	HE01-000092	05/25/2012	05/25/2013	1year
<b>Radiated Emissions</b>					
R & S Receiver	ESIB 40	100179	4/20/2012	4/20/2013	1year
Sunol Sciences, Inc. antenna (30MHz~2GHz)	JB1	A030702	2/9/2012	2/9/2013	1year
3 Meters SAC	3M	N/A	10/13/2012	10/13/2013	1year
10 Meters SAC	10M	N/A	06/05/2012	06/05/2013	1year
Sekonic Hygro Hermograph	ST-50	HE01-000092	05/25/2012	05/25/2013	1year
Spectrum Analyzer	8564E	3738A00962	05/19/2012	05/19/2013	1year
Antenna(1 ~18GHz)	3115	10SL0059	4/26/2012	4/26/2013	1year
Pre-Amplifier(1 ~ 26GHz)	8449	3008A00715	5/17/2012	5/17/2013	1year
Horn Antenna (18~40GHz)	AH-840	101013	4/23/2012	4/23/2013	1year
Microwave Preamplifier; 18-40 GHz	PA-840	181251	N/A	N/A	Every 2000hours
Signal Analyzer	FSIQ7	825555/013	5/10/2012	5/10/2013	1year
Spectrum Analyzer	E4407B	US88441016	5/31/2012	5/31/2013	1year

Note: Functional Verification



**Annex A.ii. CONDUCTED EMISSIONS TEST DESCRIPTION**

**Test Set-up**

1. The EUT and supporting equipment were set up in accordance with the requirements of the standard on top of a 1.5m x 1m x 0.8m high, non-metallic table, as shown in Annex B.
2. The power supply for the EUT was fed through a 50Ω/50μH EUT LISN, connected to filtered mains.
3. The RF OUT of the EUT LISN was connected to the EMI test receiver via a low-loss coaxial cable.
4. All other supporting equipments were powered separately from another main supply.

**Test Method**

1. The EUT was switched on and allowed to warm up to its normal operating condition.
2. A scan was made on the NEUTRAL line (for AC mains) or Earth line (for DC power) over the required frequency range using an EMI test receiver.
3. High peaks, relative to the limit line, were then selected.
4. The EMI test receiver was then tuned to the selected frequencies and the necessary measurements made with a receiver bandwidth setting of 10 KHz. For FCC tests, only Quasi-peak measurements were made; while for CISPR/EN tests, both Quasi-peak and Average measurements were made.
5. Steps 2 to 4 were then repeated for the LIVE line (for AC mains) or DC line (for DC power).

**Sample Calculation Example**

At 20 MHz	limit = 250 μV = 47.96 dBμV
Transducer factor of LISN, pulse limiter & cable loss at 20 MHz = 11.20 dB	
Q-P reading obtained directly from EMI Receiver = 40.00 dBμV (Calibrated for system losses)	
Therefore, Q-P margin = 47.96 – 40.00 = 7.96	i.e. <b>7.96 dB below limit</b>

**Annex A. iii RADIATED EMISSIONS TEST DESCRIPTION**


**EUT Characterisation**

EUT characterisation, over the frequency range from 30MHz to 10<sup>th</sup> Harmonic , was done in order to minimise radiated emissions testing time while still maintaining high confidence in the test results.

The EUT was placed in the chamber, at a height of about 0.8m on a turntable. Its radiated emissions frequency profile was observed, using a spectrum analyzer /receiver with the appropriate broadband antenna placed 3m away from the EUT. Radiated emissions from the EUT were maximised by rotating the turntable manually, changing the antenna polarisation and manipulating the EUT cables while observing the frequency profile on the spectrum analyzer / receiver. Frequency points at which maximum emissions occurred, clock frequencies and operating frequencies were then noted for the formal radiated emissions test at the Open Area Test Site (OATS).

**Test Set-up**

1. The EUT and supporting equipment were set up in accordance with the requirements of the standard on top of a 1.5m X 1.0m X 0.8m high, non-metallic table.
2. The filtered power supply for the EUT and supporting equipment were tapped from the appropriate power sockets located on the turntable.
3. The relevant broadband antenna was set at the required test distance away from the EUT and supporting equipment boundary.



**Test Method**

The following procedure was performed to determine the maximum emission axis of EUT:

1. With the receiving antenna is H polarization, rotate the EUT in turns with three orthogonal axes to determine the axis of maximum emission.
2. With the receiving antenna is V polarization, rotate the EUT in turns with three orthogonal axes to determine the axis of maximum emission.
3. Compare the results derived from above two steps. So, the axis of maximum emission from EUT was determined and the configuration was used to perform the final measurement.

**Final Radiated Emission Measurement**

1. Setup the configuration according to figure 1. Turn on EUT and make sure that it is in normal function.
2. For emission frequencies measured below 1 GHz, a pre-scan is performed in a shielded chamber to determine the accurate frequencies of higher emissions will be checked on a open test site. As the same purpose, for emission frequencies measured above 1 GHz, a pre-scan also be performed with a 1 meter measuring distance before final test.
3. For emission frequencies measured below and above 1 GHz, set the spectrum analyzer on a 100 kHz and 1 MHz resolution bandwidth respectively for each frequency measured in step 2.
4. The search antenna is to be raised and lowered over a range from 1 to 4 meters in horizontally polarized orientation. Position the highness when the highest value is indicated on spectrum analyzer, then change the orientation of EUT on test table over a range from 0 ° to 360 ° with a speed as slow as possible, and keep the azimuth that highest emission is indicated on the spectrum analyzer. Vary the antenna position again and record the highest value as a final reading.
5. Repeat step 4 until all frequencies need to be measured were complete.
6. Repeat step 5 with search antenna in vertical polarized orientations.

During the radiated emission test, the Spectrum Analyzer was set with the following configurations:

Frequency Band (MHz)	Function	Resolution bandwidth	Video Bandwidth
30 to 1000	Peak	100 kHz	100 kHz
Above 1000	Peak	1 MHz	1 MHz
	Average	1 MHz	10 Hz

**Sample Calculation Example**

The field strength is calculated by adding the Antenna Factor and Cable Factor, and subtracting the Amplifier Gain (if any) from the measured reading. For the limit is employed average value, therefore the peak value can be transferred to average value by subtracting the duty factor. The basic equation with a sample calculation is as follows:

$$\text{Peak} = \text{Reading} + \text{Corrected Factor}$$

where

$$\text{Corr. Factor} = \text{Antenna Factor} + \text{Cable Factor} - \text{Amplifier Gain (if any)}$$

And the average value is

$$\text{Average} = \text{Peak Value} + \text{Duty Factor or}$$

$$\text{Set RBW} = 1\text{MHz, VBW} = 10\text{Hz.}$$

Note :

If the measured frequencies are fall in the restricted frequency band, the limit employed must be quasi peak value when frequencies are below or equal to 1 GHz. And the measuring instrument is set to quasi peak detector function.



**SIEMIC, INC.**

Accessing global markets

Title: RF Test Report of Stryker Endoscopy,  
Model : P23366  
To : FCC 15.407:2012, RSS-210 Issue 8 : 2010

Serial# RF\_SL12011902-STR-001\_SYNK\_Receiver (FCC\_15.407) Rev1.2  
Issue Date Oct 2nd, 2013  
Page 60 of 93  
www.siemic.com

## **Annex B EUT AND TEST SETUP PHOTOGRAPHS**

**Please see the attachment.**

**Annex C. TEST SETUP AND SUPPORTING EQUIPMENT**


**EUT TEST CONDITIONS**

**Annex C. i. SUPPORTING EQUIPMENT DESCRIPTION**


The following is a description of supporting equipment and details of cables used with the EUT.

Equipment Description (Including Brand Name)	Model & Serial Number	Cable Description (List Length, Type & Purpose)
-	-	-

### Block Configuration Diagram for Radiated Emission



### Block Configuration Diagram for Conducted Emission



**Annex C.ii. EUT OPERATING CONDITIONS**

The following is the description of how the EUT is exercised during testing.

Test	Description Of Operation
<b>Emissions Testing</b>	The EUT was controlled via PC Using manufacturer's program.
<b>Others Testing</b>	TX mode is Special mode and full power.





**SIEMIC, INC.**  
Accessing global markets

Title: RF Test Report of Stryker Endoscopy,  
Model : P23366  
To : FCC 15.407:2012, RSS-210 Issue 8 : 2010

Serial# RF\_SL12011902-STR-001\_SYNK\_Receiver (FCC\_15.407) Rev1.2  
Issue Date Oct 2nd, 2013  
Page 65 of 93  
www.siemac.com

## **Annex D USER MANUAL, BLOCK & CIRCUIT DIAGRAM**

**Please see attachment**

**Annex F SIEMIC ACCREDITATION**

**SIEMIC ACCREDITATION DETAILS: A2LA 17025 & ISO Guide 65 : 2742.01 , 2742.2**

		<b>American Association for Laboratory Accreditation</b>
--	--	--

*Accredited Laboratory*

A2LA has accredited

**SIEMIC, INC.**

*Milpitas, CA*

for technical competence in the field of

**Electrical Testing**

This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2005 *General Requirements for the Competence of Testing and Calibration Laboratories*. This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (refer to joint ISO-ILAC-IAF Communiqué dated 8 January 2009).

Presented this 19<sup>th</sup> day of September 2012.

President & CEO  
For the Accreditation Council  
Certificate Number 2742.01  
Valid to September 30, 2014

*For the tests or types of tests to which this accreditation applies, please refer to the laboratory's Electrical Scope of Accreditation.*



American Association for Laboratory Accreditation

SCOPE OF ACCREDITATION TO ISO/IEC 17025:2005

SIEMIC, INC.  
dba SIEMIC LABORATORIES  
775 Montague Expressway  
Milpitas, CA 95035  
Mr. Leslie Bai Phone: 408 526 1188 Email: leslie.bai@siemic.com  
Mr. Snell Leong Phone: 408 526 1188 Email: snell.leong@siemic.com  
[www.siemic.com](http://www.siemic.com)

ELECTRICAL

Valid to: September 30, 2014

Certificate Number: 2742.01

In recognition of the successful completion of the A2LA evaluation process, accreditation is granted to this laboratory to perform the following EMC, Product Safety, Radio and Telecommunication tests:

<u>Test Technology:</u>	<u>Test Method(s):</u>
EN & IEC – Emissions & Immunity	IEC/CISPR 11; EN 55011; IEC/CISPR 12; IEC/CISPR 20; EN 55020; IEC/CISPR 22; EN 55022; IEC/CISPR 24; EN 55024; EN 61000-6-1; EN 61000-6-2; EN 61000-6-3; EN 61000-6-4; EN 61204-3; EN 61326-1; EN 61326-2-1; EN 61326-2-2; EN 61326-2-3; EN 61326-2-4; EN 61326-2-5; EN 61000-3-2; EN 61000-3-3; EN 50081-1, EN 50081-2; EN 50082-1; IEC 61000-4-2; EN 61000-4-2; IEC 61000-4-3 (limited up to 2.7 GHz and 3V/m); EN 61000-4-3 (limited up to 2.7 GHz and 3V/m); IEC 61000-4-4; EN 61000-4-4; IEC 61000-4-5; EN 61000-4-5; IEC 61000-4-6; EN 61000-4-6; IEC 61000-4-8; EN 61000-4-8; IEC 61000-4-11; EN 61000-4-11; EN 50412-2-1; EN 50083-2; EN 50090-2-2; EN 50091-2; EN 50491-5-1; EN 50491-5-2; EN 50491-5-3; EN 50130-4; EN 50130-4 + A12; EN 12184; EN 55015; EN 61547; IEC 60601-1-2; CISPR 16-2-3



<u>Test Technology:</u>	<u>Test Method(s):</u>
Korea – Emissions & Immunity	RRA Public Notification 2011-24; RRA Announce 2011-30; Annex 2 (KN 11); Annex 3 (KN 13); Annex 4 (KN 14-1); Annex 5 (KN 22); Annex 6 (KN 41); Annex 7 (KN 50); Annex 9 (KN 15); Annex 10 (KN 19); Annex 11 (KN 60); Annex 1-1 (KN 16-1-1); Annex 1-2 (KN 16-1-2); Annex 1-3 (KN 16-1-3); Annex 1-4 (KN 16-1-4); Annex 1-5 (KN 16-1-5); Annex 1-6 (KN 16-2-1); Annex 1-7 (KN 16-2-2); Annex 1-8 (KN 16-2-3); Annex 1-9 (KN 16-2-4); Annex 8-5 (KN 301-489-06); Annex 8-6 (KN 301-489-13); Annex 8-7 (KN 301-489-05); Annex 8-8 (KN 301-489-03); Annex 8-9 (KN 301-489-09); Annex 8-10 (KN 301-489-26); Annex 8-11 (KN 301-489-18); Annex 8-12 (KN 301-489-15); Annex 8-13 (KN 301-489-02); Annex 8-14 (KN 301-489-27); Annex 8-15 (KN 301-489-32); Annex 8-16 (KN 301-489-20); Annex 8-17 (KN 60945) RRA Public Notification 2011-25; RRA Announce 2011-31; Annex 1-1 (KN 61000-4-2); Annex 1-2 (KN 61000-4-3); Annex 1-3 (KN 61000-4-4); Annex 1-4 (KN 61000-4-5); Annex 1-5 (KN 61000-4-6); Annex 1-6 (KN 61000-4-8); Annex 1-7 (KN 61000-4-11); Annex 2 (KN 60601-1-2); Annex 3 (KN 20); Annex 4 (KN 14-2); Annex 5 (KN 24); Annex 6 (KN 41); Annex 7 (KN 51); Annex 8-1 (KN 301-489-01); Annex 8-2(KN 301-489-07); Annex 8-3 (KN 301-489-17); Annex 8-4(KN 301-489-24);
US / FCC - Emissions	FCC Method 47 CFR Part 18, FCC Report and Order ET Docket 98-153 (FCC 02-48); FCC Method 47 CFR Parts15, including Subpart G, using FCC Order 04-425; ANSI C63.4 (2003); ANSI C63.4 (2009); ANSI C63.10 (2009); ANSI C63.4 (2003) with FCC Method 47 CFR Part 11; ANSI C63.4 (2003) with FCC Method 47 CFR Part 15, Subpart E; ANSI C63.4 (2003) with FCC Method 47 CFR Part 15, Subpart C; ANSI C63.4 (2003) and DA 02-2138; ANSI C63.4 (2003) with FCC Method 47 CFR Part 15, Subpart B
Canada – Emissions	ICES-001; ICES-002; ICES-003; ICES-005; ICES-006
Vietnam – Emission & Immunity	TCN 68-193:2003; TCN 68-196:2001; TCVN 7189:2002; TCVN 7189:2009 (CISPR 22:2006)
Australia / New Zealand – Emissions and Immunity	AS/NZS 1044; AS/NZS 2279.3; AS/NZS 3548; AS/NZS 4251.1; AS/NZS 4251.2; AS/NZS CISPR 11; AS/NZS CISPR 14.1; AS/NZS CISPR 22; AS/NZS CISPR 24; AS/NZS 61000.3.2; AS/NZS 61000.3.3; AS/NZS 61000.6.3; AS/NZS 61000.6.4
Japan – Emissions	JEITA IT-3001; VCCI-V-3 (up to 6 GHz)
China – Emissions	GB9254; GB17625.1





<b><u>Test Technology:</u></b>	<b><u>Test Method(s):</u></b>
Taiwan – Emissions	CNS 13438 (up to 6 GHz); CNS 13783-1; CNS 13803; CNS 13439
Singapore – Emissions & Immunity	IDA TS EMC; CISPR 22; IEC 61000-4-2; IEC 61000-4-3; IEC 61000-4-4; IEC 61000-4-5; IEC 61000-4-6
FCC – Unlicensed Radio A1 to A4	<p>A1: 47 CFR Parts 11 (Emergency Alert System (EAS)), 15 (Radio Frequency Devices) and 18 (Industrial, Scientific, and Medical Equipment); FCC OST/MP-5(1986); ANSI C63.4(2003); ANSI C63.4(2009); ANSI C63.10(2009)</p> <p>A2: 47 CFR Part 15 (Radio Frequency Devices); ANSI C63.4(2003); ANSI C63.4(2009); ANSI C63.10(2009)</p> <p>A3: 47 CFR Part 15 (Radio Frequency Devices); ANSI C63.17:2006; ANSI C63.10(2009); IEEE Std 1528:2003 + A1; Std IEEE 528A:2005</p> <p>A4: 47 CFR Part 15 (Radio Frequency Devices); ANSI C63.10(2009); IEEE Std 1528:2003 + A1; Std IEEE 1528A:2005</p>
FCC – Licensed Radio B1 to B4	<p>B1: 47 CFR Parts 2 (Frequency Allocations and Radio Treaty Matters; General Rules and Regulations), 22 (Public Mobile Services), 24 (Personal Communications Services), 25 (Satellite Communications), and 27 (Miscellaneous Wireless Communications Services); ANSI/TIA-603-C (2004), ANSI/TIA-603-D(2010), Land Mobile FM or PM Communications Equipment Measurement and Performance Standard; IEEE Std 1528:2003 + Ad1; Std IEEE 1528A:2005</p> <p>B2: 47 CFR Parts 2 (Frequency Allocations and Radio Treaty Matters; General Rules and Regulations), 22 (Public Mobile Services), 74 (Experimental Radio Auxiliary, Special Broadcast and Other Program Distributional Services), 90 (Private Land Mobile Radio Services), 95 (Personal Radio Services), and 97 (Amateur Radio Services); ANSI/TIA-603-C (2004), ANSI/TIA-603-D(2010), Land Mobile FM or PM Communications Equipment Measurement and Performance Standard</p> <p>B3: 47 CFR Parts 2 (Frequency Allocations and Radio Treaty Matters; General Rules and Regulations); 80 (Stations in the Maritime Services), 87 (Aviation Services); ANSI/TIA-603-C (2004), ANSI/TIA-603-D(2010), Land Mobile FM or PM Communications Equipment Measurement and Performance Standard</p> <p>B4: 47 CFR Parts 2 (Frequency Allocations and Radio Treaty Matters; General Rules and Regulations); 27 (Broadband Radio Services (BRS) and Educational Broadband Services (EBS)), 74 (Experimental Radio Auxiliary, Special Broadcast and Other Program Distributional Services), and 101 (Fixed Microwave Services); ANSI/TIA-603-C (2004), ANSI/TIA-603-D(2010), Land Mobile FM or PM Communications Equipment Measurement and Performance Standard</p>



<u>Test Technology:</u>	<u>Test Method(s):</u>
Canada – Radio	RSS 102; RSS 111; RSS 112; RSS 117; RSS 118; RSS 119; RSS 123; RSS 125; RSS 127; RSS 129; RSS 131; RSS 132; RSS 133; RSS 134; RSS 135; RSS 136; RSS 137; RSS 138; RSS 139; RSS 141; RSS 142; RSS 170; RSS 181; RSS 182; RSS 191; RSS 192; RSS 194; RSS 195; RSS 196; RSS 197; RSS 199; RSS 210; RSS 220; RSS 213; RSS 215; RSS 243; RSS 287; RSS 288; RSS 310; RSS Gen
CE – Radio	EN 301 502; EN 301 511; EN 301 526; EN 301 681; EN 301 721; EN 301 751; EN 301 753; EN 301 783-2; EN 301 796; EN 301 797; EN 301 840-2; EN 301 843-1; EN 301 843-4; EN 301 843-5; EN 301 893; EN 301 908-01; EN 301 908-02; EN 301 908-03; EN 301 908-04; EN 301 908-05; EN 301 908-06; EN 301 908-07; EN 301 908-08; EN 301 908-09; EN 301 908-10; EN 301 908-11; EN 301 929-2; EN 301 997-2; EN 302 018-2; EN 302 054-2; EN 302 064-2; EN 302 066-2; EN 302 077-2; EN 302 186; EN 302 195-2; EN 302 217-3; EN 302 245-2; EN 302 288-2; EN 302 291-2; EN 302 296; EN 302 297; EN 302 326-2; EN 302 326-3; EN 302 340; EN 302 372-2; EN 302 426; EN 302 454-2; EN 302 480; EN 302 502; EN 302 510-2; EN 302 217-4-2; EN 300 224-1; EN 300 279; EN 300 339; EN 300 385; EN 301 839-2; EN 301 843-6; EN 302 017-2; EN 302 208-2; EN 302 217-2-2; ETS 300 329; ETS 300 445; ETS 300 446; ETS 300 683; ETS 300 826; ETS EN 300 328; ETSI EN 300 086-2; EN 302 217-1; EN 302 217-2-1; EN 302 217-4-1; EN 302 288-1; EN 302 908-12; EN 302 326-1; EN 301 929-1; EN 301 997-1; EN 300 224-2; EN 301 839-1; EN 301 843-1; EN 301 843-2; EN 301 843-3; EN 301 843-4; EN 301 843-5; EN 302 017-1; EN 302 208-1; EN 300 086-1; EN 300 113-1; EN 300 224-1; EN 300 341-1; EN 302 291-1; EN 302 500-1; EN 302 500-2; ETSI EN 300 113-2; ETSI EN 300 197; ETSI EN 300 198; ETSI EN 300 219-1; ETSI EN 300 219-2; ETSI EN 300 220-1; ETSI EN 300 220-2; ETSI EN 300 220-3; ETSI EN 300 224-2; ETSI EN 300 296-1; ETSI EN 300 296-2; ETSI EN 300 328-1; ETSI EN 300 328-2; ETSI EN 300 330; ETSI EN 300 330-1; ETSI EN 300 330-2; ETSI EN 300 341-2; ETSI EN 300 373-1; ETSI EN 300 373-2; ETSI EN 300 373-3; ETSI EN 300 390-1; ETSI EN 300 390-2; ETSI EN 300 422-1; ETSI EN 300 422-2; ETSI EN 300 431; ETSI EN 300 440-1; ETSI EN 300 440-2; ETSI EN 300 454-1; ETSI EN 300 454-2; ETSI EN 300 718-2; ETSI EN 301 021; ETSI EN 301 166-1; ETSI EN 301 166-2; ETSI EN 301 178-2; ETSI EN 301 213-1; ETSI EN 301 213-2; ETSI EN 301 213-3; ETSI EN 301 213-4; ETSI EN 301 213-5; ETSI EN 301 357-1; ETSI EN 301 357-2; ETSI EN 301 390; ETSI EN 301 459; ETSI EN 301 489-01 (excluding section 9.6); ETSI EN 301 489-02; ETSI EN 301 489-03; ETSI EN 301 489-04; ETSI EN 301 489-05; ETSI EN 301 489-06; ETSI EN 301 489-07; ETSI EN 301 489-08; ETSI EN 301 489-09; ETSI EN 301 489-10; ETSI EN 301 489-11; ETSI EN 301 489-12; ETSI EN 301 489-13; ETSI EN 301 489-14; ETSI EN 301 489-15; ETSI EN 301 489-16; ETSI EN 301 489-17; ETSI EN 301 489-18; ETSI EN 301 489-19; ETSI EN 301 489-20; ETSI EN 301 489-22; ETSI EN 301 489-23; ETSI EN 301 489-24; ETSI EN 301 489-25; ETSI EN 301 489-26;



<b><u>Test Technology:</u></b>	<b><u>Test Method(s):</u></b>
CE – Radio (continued)	ETSI EN 301 489-27; ETSI EN 301 489-28; ETSI EN 301 489-31; ETSI EN 301 489-32; IEC 60945; EN 302 480
IDA – Radio	IDA TS AR; IDA TS CT-CTS; IDA TS GMPCS; IDA TS LMR; IDA TS RPG; IDA TS SRD; IDA TS UWB; IDA TS WBA; IDA TS CMT; IDA TS CBS
Vietnam – Radio	QCVN 54:2011/BTTTT; TCN 68-242:2006; QCVN 11:2010/BTTTT; QCVN 17:2010/BTTTT
Korea – Radio	KCC Public Notification 2012-12; RRA Announce 2011-32; RRA Public Notification 2010-46
Taiwan – Radio	LP0002; PLMN07; PLMN01; PLMN08
Australia - New Zealand – Radio	AS 2772.2; AS/NZS 4281; AS/NZS 4268; AS/NZS 4280.1; AS/NZS 4583; AS/NZS 4280.2; AS/NZS 4281; AS/NZS 4295; AS/NZS 4582; AS/NZS 4769.1; AS/NZS 4769.2; AS/NZS 4770; AS/NZS 4771
Hong Kong – Radio	HKCA 1002; HKCA 1007; HKCA 1008; HKCA 1010; HKCA 1015; HKCA 1016; HKCA 1020; HKCA 1022; HKCA 1026; HKCA 1027; HKCA 1029; HKCA 1030; HKCA 1031; HKCA 1032; HKCA 1033; HKCA 1034; HKCA 1035; HKCA 1036; HKCA 1037; HKCA 1039; HKCA 1041; HKCA 1042; HKCA 1043; HKCA 1044; HKCA 1046; HKCA 1047; HKCA 1048; HKCA 1049; HKCA 1051; HKCA1052; HKCA1053; HKCA 1054; HKCA 1055; HKCA 1056; HKCA 1057; HKCA 1061
FCC Telephone Terminal Equipment Scope C1	TIA-968-B; FCC Rule Part 68; 47 CFR Part 68.316; 47 CFR Part 68.317; ANSI/TIA/EIA-464-C; TIA-810-B; T1.TRQ6 (2002); TCB-31-B (1998); TIA-470.110-C; TIA-920
Canada – Telecom	CS-03 Part I Issue 9:2010, Amendment 4; CS-03 Part II Issue 9:2004; CS-03 Part V Issue 9:2009 Amendment 1; CS-03 Part VI Issue 9:2004; CS-03 Part VII Issue 9:2006 Amendment 3; CS-03 Part VIII Issue 9:2009 Amendment 4
Europe – Telecom	TBR 2: 01-1997; TBR 004 Ed.1.95 + A1 (97); TBR 1; TBR 3; TBR 12:A1 01-1996; TBR 013 ed.1; TBR 024 ed.1; TBR 25; TBR 38 ed.1; TBR 021; ETSI ES 203 021-05 ; ETSI ES 203 021-2 ; ETSI ES 021-3; ETSI EG 201 121; ETSI EN 301 437; ETSI TS 101 270-1; ITU-T Recommendation Q.920; ITU-T Recommendation Q.920 – Amendment 1; ITU-T Recommendation Q.921; ITU-T Recommendation Q.921 – Amendment 1; ITU-T Recommendation Q.931; ITU-T Recommendation Q.931 – Amendment 1; Erratum 1 (02/2003) ITU-T Recommendation Q.931 (05/1998);





<b><u>Test Technology:</u></b>	<b><u>Test Method(s):</u></b>
Europe – Telecom <i>(cont'd)</i>	ISDN User Network Interface Layer 3 Specification for Basic Call Control; ITU-T Recommendation P.300
Australia – Telecom  Australia – Telecom	AS/CA S003.1:2010; AS/CA S002:2011; AS/ACIF S004:2008; AS/CA S042.1:2011; AS/CA S003.2:2010; AS/CA S003.3:2010; AS/CA S004:2010; AS/ACIF S006:2008; AS/ACIF S041.1:2009 AS/ACIF S041.2:2009; AS/ACIF S041.3:2009; AS/ACIF S042.1:2008; AS/ACIF S043.2:2008; AS/ACIF S043.3:2008; AS/ACIF S002:05; AS/ACIF S003:06; AS/ACIF S004:08; AS/ACIF S006:01; AS/ACIF S016:01; AS/ACIF S031:01; AS/ACIF S038:01; AS/ACIF S040:01; AS/ACIF S041:05; AS/ACIF S043.2:06
New Zealand – Telecom	PTC200:2006; PTC200 Issue No.2:97 + A1(980); PTC220; PTC273:2007; TNA 115; TNA 117
Singapore – Telecom	IDA TS ADSL; IDA TS DLCN; IDA TS ISDN BA; IDA TS ISDN PRA; IDA TS BISDN; IDA TS-PSTN; IDA TS ACLIP; IDA TS CM
Hong Kong – Telecom	HKCA 2011; HKCA 2012; HKCA 2013; HKCA 2014; HKCA 2015; HKCA 2017; HKCA 2018; HKCA 2019; HKCA 2022; HKCA 2023; HKCA 2024; HKCA 2026; HKCA 2027; HKCA 2028; HKCA 2029; HKCA 2030; HKCA 2031; HKCA 2032; HKCA 2033
Vietnam – Telecom	QCVN 10:2010/BTTTT; QCVN 19:2010/BTTTT; TCN 68-189:2000; QCVN 18:2010/BTTTT; TCVN 7317:2003 (CISPR 24:1997); QCVN 12:2010/BTTTT; QCVN 13:2010/BTTTT; QCVN 55:2011/BTTTT; QCVN 15:2010/BTTTT
Korea – Telecom	Presidential Decree 21098; RRA Public Notification 2010-36; RRA Public Notification 2009-38; RRA Announce 2011-2; Annex 1 (RRA Announce 2011-2); Annex 3 (RRA Announce 2011-2); Annex 5 (RRA Announce 2011-2); Annex 6 (RRA Announce 2011-2)





<b><u>Test Technology:</u></b>	<b><u>Test Method(s):</u></b>
China – Telecom	YD/T 514-1:98; YD/T 1277.1-2003; GB/T 17904.1-1999; GB/T 17904.2-1999; GB/T 17154.1-1997; GB/T 17154.2-1997; YD/T1091-2000; YD/T1006-1999; GB/T 17789-1999
Taiwan – Telecom	PSTN01:2007; ADSL01:08; ID0002:2007; IS6100: 93
Japan – Telecom	JATE Blue Book, Green Book; Ministerial Ordinance of the Ministry of Posts and Telecommunications No. 31 of April 1, 1985 (last amended on March 22 2004); Ordinance Concerning Technical Conditions Compliance Approval etc. of Terminal Equipment (amended by the Ministerial Ordinance of the MIC No.92 of October 25, 2010) and Ordinance Concerning Terminal Facilities etc. (amended by the Ministerial Ordinance of the MIC No. 91 of October 25, 2010)
South Africa – Telecom	DPT-TE-001; TE-002; TE-003; TE-004; TE-005; TE-006; TE-007; TE-008; TE-009; TE-010; TE-012 (telephone interface); TE-013 (telephone interface); TE-014; TE-015; TE-018; SWS-001; SWS-002; SWS-003; SWS-004; SWS-005; SWS-006; SWS-007; SWS-008; SWS-009; SWS-010
Israel – Telecom	Israel MoC Spe. 23/96
Mexico – Telecom	NOM-151-SCT1-1999; NOM-152-SCT1-1999
Argentina – Telecom	CNC-ST2-44-01
Brazil – Telecom	Resolution 392-2005
International Telecom Union	ITU-T-G.703:01; ITU-T-G.823:93; ITU-T G.824; ITU-T G.825; ITU-T-G.991.2; ITU-T-G.992.1; ITU-T-G.992.3; ITU-T-G.992.5; ITU-T-G.993.1
Product Safety	IEC 60950-1; EN 60950-1; UL 60950-1; IEC 60601-1-1; CAN/CSA 22.2 NO. 60950-1-03; SS-EN 60950-1; AS/NZ 60950-1, (voltage surge testing up to 6kV, excluding Annex A, H, and Y); CNS 14336, CNS 14408; GB4943; President Notice 20664; RRA Public Notification 2011-14; RRA Announce 2011-3; Annex 1(RRA Announce 2011-3); QCVN 22:2010/BTTTT; SABS IEC 60950; IEC/EN 61558; IEC/EN 61558-2-7; EN 62115; IEC 60215; EN 60958; EN 60598; IEC 215 (1987) + A1 (1992) + A2 (1994)
Japan - Radio	ARIB STD-T81; ARIB STD-T66; RCR STD-1; RCR STD-29; ARIB STD-T94 Fascicle 1; ARIB STD-T90; ARIB STD-T89; RCR STD-33
SAR & HAC	IEEE P1528:2003 + Ad1; IEEE 1528A:2005; FCC OET Bulletin 65 Supplement C; FCC OET Bulletin 65; ANSI C95; ANSI C63.19; FCC 47 CFR 20.19; H46-2/99-273E; EN 50360; EN 50361; IEC62209-1; IEC 62209-2; EN 50371; EN 50383; EN 50357; EN 50364;



<b><u>Test Technology:</u></b>	<b><u>Test Method(s):</u></b>
SAR & HAC ( <i>cont'd</i> )	KCC Public Notification 2009-27; RRA Public Notification 2010-45; KCC Public Notification 2012-2; CNS 14958-1; CNS 14959; NZS 2772.1; Resolution N 533; AS/NZS 2772.2:2011
Japan – Notification No. 88 of MIC 2004	
Table No 13	CB Radio
Table No 21	Cordless Telephone
Table Nos 22-1 thru 22-17	Low Power Radio Equipment
Table No 36	Low Power Security System
Table No 43	Low Power Data Communication in the 2.4 GHz Band
Table No 44	Low Power Data Communication in the 2.4 GHz Band
Table No 45	Low Power Data Communication in the 5.2, 5.3, 5.6 GHz Bands
Table No 46	Low Power Data Communication in the 25 and 27 GHz Bands
Table No 47	Base Station for 5 GHz Band Wireless Access System
Table No 47	Base Station for 5 GHz Band Wireless Access System (low spurious type)
Table No 47	Land Mobile Relay for 5 GHz Band Wireless Access System (limited for use in special zones)
Table No 47	Land Mobile Relay for 5 GHz Band Wireless Access System (limited for use in special zones, low spurious type)
Table No 47	Land Mobile Relay for 5 GHz Band Wireless Access System
Table No 47	Land Mobile Relay for 5 GHz Band Wireless Access System (low spurious type)
Table No 47	Land Mobile Relay for 5 GHz Band Wireless Access System (low power type)
Table No 50	Digital Cordless Telephone
Table No 50	PHS Base Station
Table No 50	PHS Land Mobile Station
Table No 50	PHS Relay Station
Table No 50	PHS Test Station
Table No 64	Mobile Station for Dedicated Short Range Communication Systems
Table No 64	Base Station for Dedicated Short Range Communication Systems
Table No 64	Test Station for Dedicated Short Range Communication Systems
Table No 70	UWB (Ultra Wide Band) Radio System

\*Limitations for listed standards are indicated by italics and Scope excludes protocol sections of applicable standards.



**SIEMIC, INC.**

Accessing global markets

Title: RF Test Report of Stryker Endoscopy,  
Model : P23366  
To : FCC 15.407:2012, RSS-210 Issue 8 : 2010

Serial# RF\_SL12011902-STR-001\_SYNK\_Receiver (FCC\_15.407) Rev1.2  
Issue Date Oct 2nd, 2013  
Page 75 of 93  
www.siemic.com



**American Association for Laboratory Accreditation**

## *Accredited Product Certification Body*

A2LA has accredited

**SIEMIC, INC.**

*Milpitas, CA*

for technical competence as a

**Product Certification Body**

This product certification body is accredited in accordance with the recognized International Standard ISO/IEC Guide 65:1996 *General requirements for bodies operating product certification systems*. This accreditation demonstrates technical competence for a defined scope and the operation of a quality management system.

Presented this 19<sup>th</sup> day of September 2012.

President & CEO  
For the Accreditation Council  
Certificate Number 2742.02  
Valid to September 30, 2014



*For the product certification schemes to which this accreditation applies, please refer to the organization's Product Certification Scope of Accreditation*



SCOPE OF ACCREDITATION TO ISO/IEC GUIDE 65:1996

SIEMIC, INC.  
775 Montague Expressway  
Milpitas, CA 95035  
Mr. Snell Leong (Authorized Representative) Phone: 408 526 1188  
[www.siemic.com](http://www.siemic.com)

PRODUCT CERTIFICATION CONFORMITY ASSESSMENT BODY (CAB)

Valid to: September 30, 2014

Certificate Number: 2742.02

In recognition of the successful completion of the A2LA Certification Body Accreditation Program evaluation, including the US Federal Communications Commission (FCC), Industry Canada (IC), Singapore (IDA), Hong Kong (OFCA) and Japan (MIC) requirements for the indicated types of product certifications, accreditation is granted to this organization to certify products in accordance with the following product certification schemes:

Economy:

Scope:

**Federal Communication Commission - (FCC)**

Unlicensed Radio Frequency Devices	A1, A2, A3, A4
Licensed Radio Frequency Devices	B1, B2, B3, B4
Telephone Terminal Equipment	C

*\*Please refer to FCC TCB Program Roles and Responsibilities, released January 6, 2011, detailing scopes, roles and responsibilities. [TCB Program Roles and Responsibilities](#)*

**Industry Canada - (IC)**

Radio	Scope 1-Licence-Exempt Radio Frequency Devices; Scope 2-Licensed Personal Mobile Radio Services; Scope 3-Licensed General Mobile & Fixed Radio Services; Scope 4-Licensed Maritime & Aviation Radio Services; Scope 5-Licensed Fixed Microwave Radio Services;
-------	--

*\*Please refer to Industry Canada (IC) website at: <http://www.ic.gc.ca/eic/site/smt-gst.nsf/eng/sf09888.html>*





**IDA – Singapore**

Line Terminal Equipment All Technical Specifications for Line Terminal Equipment – Table 1 of IDA MRA Recognition Scheme: 2011, Annex 2

Radio-Communication Equipment All Technical Specifications for Radio-Communication Equipment – Table 2 of IDA MRA Recognition Scheme: 2011, Annex 2

*\*Please refer to Info-Communication Development Authority (IDA) Singapore website at:  
[http://www.ida.gov.sg/doc/Policies%20and%20Regulation/Policies\\_and\\_Regulation\\_Level2\\_20060609145118/MRARecScheme.pdf](http://www.ida.gov.sg/doc/Policies%20and%20Regulation/Policies_and_Regulation_Level2_20060609145118/MRARecScheme.pdf)*

**OFCA – Hong Kong**

Radio Equipment HKCA 1001, 1002, 1003, 1004, 1005, 1006, 1007, 1008, 1010, 1015, 1016, 1019, 1020, 1022, 1026, 1027, 1033, 1034, 1035, 1036, 1037, 1038, 1039, 1041, 1042, 1043, 1044, 1045, 1046, 1047, 1048, 1049, 1050, 1052, 1053, 1054, 1056, 1057, 1061

*\*Please refer to the Office of the Communications Authority's website at:  
[Radio Equipment Specifications \(HKCA 10XX\)](#)*

Fixed Network Equipment HKCA 2001, 2005, 2011, 2012, 2013, 2014, 2015, 2016, 2017, 2018, 2019, 2020, 2021, 2022, 2023, 2024, 2026, 2027, 2028, 2029, 2030, 2031, 2032, 2033, 2034, 2035, 2036, 2037, 2040, 2041, 2102, 2103, 2104, 2108, 2201, 2202, 2203, 2204

*\*Please refer to the Office of the Communications Authority's website at:  
[Fixed Network Equipment Specifications \(HKCA 2XXX\)](#)*

**MIC – Japan**

Telecommunications Business Law (Terminal Equipment) Scope A1 - Terminal Equipment for the Purpose of Calls

Radio Law (Radio Equipment) Scope B1 - Specified Radio Equipment specified in, Article 38-2-2, paragraph 1, item 1 of the Radio Law

**SIEMIC ACCREDITATION DETAILS: FCC Test Site Registration No. 881796**

**FEDERAL COMMUNICATIONS COMMISSION**

**Laboratory Division  
7435 Oakland Mills Road  
Columbia, MD 21046**

August 03, 2012

Registration Number: 881796

SIEMIC Labs  
775 Montague Expressway,  
Milpitas, CA 95035

Attention: Leslie BAI

Re: Measurement facility located at 775 Montague Expressway, Milpitas, CA 95035  
Anechoic chamber (10 meters)  
Date of Listing: August 03, 2012

Dear Sir or Madam:

Your request for registration of the subject measurement facility has been reviewed and found to be in compliance with the requirements of Section 2.948 of the FCC rules. The information has, therefore, been placed on file and the name of your organization added to the list of facilities whose measurement data will be accepted in conjunction with applications for Certification under Parts 15 or 18 of the Commission's Rules. Please note that the file must be updated for any changes made to the facility and the registration must be renewed at least every three years.

Measurement facilities that have indicated that they are available to the public to perform measurement services on a fee basis may be found on the FCC website [www.fcc.gov](http://www.fcc.gov) under E-Filing, OET Equipment Authorization Electronic Filing, Test Firms.

Sincerely,

Katie Hawkins  
Electronics Engineer

**SIEMIC ACCREDITATION DETAILS: Industry of Canada CAB ID : US0160**



**UNITED STATES DEPARTMENT OF COMMERCE**  
**National Institute of Standards and Technology**  
Gaithersburg, Maryland 20899

March 4, 2009

Mr. Leslie Bai  
SIEMIC, Inc.  
2206 Ringwood Avenue  
San Jose, CA 95131

Dear Mr. Bai:

NIST is pleased to inform you that your laboratory has been recognized by Industry Canada (IC), under the Asia Pacific Economic Cooperation for Telecommunications Equipment Mutual Recognition Arrangement (APEC Tel MRA). Your laboratory is now designated to act as a Conformity Assessment Body (CAB) under Appendix B, **Phase I** Procedures, of the APEC Tel MRA. The pertinent information about your laboratory's designation is as follows:

CAB Name: SIEMIC, Inc.  
Physical Location: 2206 Ringwood Avenue, San Jose, CA 95131 USA  
Identification No.: US0160  
Recognized Scope: CS-03 Part I, II, V, VI, VII and VIII

You may submit test data to IC to verify that the equipment to be imported into Canada satisfies the applicable requirements. The designation of your organization will remain in force as long as its accreditation for the designated scope remains valid and comply with the designation requirements.

Recognized CABs are listed on the NIST website at <http://ts.nist.gov/mra>. Please contact Ms. Ramona Saar at (301) 975-5521 or [ramona.saar@nist.gov](mailto:ramona.saar@nist.gov) if you have any questions.


Sincerely,

David F. Alderman  
Group Leader, Standards Coordination and Conformity Group  
Standards Services Division

Enclosure

cc: CAB Program Manager

**SIEMIC ACCREDITATION DETAILS: Industry of Canada Test Site Registration No. 4842-1**



July 03, 2012

OUR FILE: 46405-4842  
Submission No: 157820

Siemic Inc.  
775 Montague Expressway  
Milpitas, CA, 95035  
United States

**Attention:**

Dear Sir/Madame: Snell Leong

The Bureau has received your application for the renewal of 3/10m alternative test site. Be advised that the information received was satisfactory to Industry Canada. The following number(s) is now associated to the site(s) for which registration / renewal was sought (**Site# 4842D-2**). Please reference the appropriate site number in the body of test reports containing measurements performed on the site. In addition, please keep for your records the following information;


- The company address code associated to the site(s) located at the above address is: **4842D**

Furthermore, to obtain or renew a unique site number, the applicant shall demonstrate that the site has been accredited to ANSI C63.4-2003 or later. A scope of accreditation indicating the accreditation by a recognized accreditation body to ANSI C63.4-2003 or later shall be accepted. Please indicate in a letter the previous assigned site number if applicable and the type of site (example: 3 metre OATS or 3 metre chamber). If the test facility is not accredited to ANSI C63.4-2003 or later, the test facility shall submit test data demonstrating full compliance with the ANSI standard. The Bureau will evaluate the filing to determine if recognition shall be granted.

The frequency for re-validation of the test site and the information that is required to be filed or retained by the testing party shall comply with the requirements established by the accrediting organization. However, in all cases, test site re-validation shall occur on an interval not to **exceed three years**. There is no fee or form associated with an OATS filing. OATS submissions are encouraged to be submitted electronically to the Bureau using the following URL;  
[http://strategis.ic.gc.ca/epic/internet/inceb-bhst.nsf/en/h\\_tt00052e.html](http://strategis.ic.gc.ca/epic/internet/inceb-bhst.nsf/en/h_tt00052e.html).

If you have any questions, you may contact the Bureau by e-mail at [certification.bureau@ic.gc.ca](mailto:certification.bureau@ic.gc.ca) Please reference our file and submission number above for all correspondence.

Yours sincerely,



Dalwinder Gill  
For: Wireless Laboratory Manager  
**Certification and Engineering Bureau**  
3701 Carling Ave., Building 94  
P.O. Box 11490, Station "H"  
Ottawa, Ontario K2H 8S2  
Email: [dalwinder.gill@ic.gc.ca](mailto:dalwinder.gill@ic.gc.ca)  
Tel. No. (613) 998-8363  
Fax. No. (613) 990-4752





**SIEMIC ACCREDITATION DETAILS: FCC DOC CAB Recognition : US1109**

**FEDERAL COMMUNICATIONS COMMISSION**

**Laboratory Division  
7435 Oakland Mills Road  
Columbia, MD 21046**

August 28, 2008

Siemic Laboratories  
2206 Ringwood Ave.,  
San Jose, CA 95131

Attention: Leslie Bai

Re: Accreditation of Siemic Laboratories  
Designation Number: US1109  
Test Firm Registration #: 540430

Dear Sir or Madam:

We have been notified by American Association for Laboratory Accreditation that Siemic Laboratories has been accredited as a Conformity Assessment Body (CAB).

At this time Siemic Laboratories is hereby designated to perform compliance testing on equipment subject to Declaration Of Conformity (DOC) and Certification under Parts 15 and 18 of the Commission's Rules.

This designation will expire upon expiration of the accreditation or notification of withdrawal of designation.

Sincerely,

George Tannahill  
Electronics Engineer

**SIEMIC ACCREDITATION DETAILS: Australia CAB ID : US0160**



**UNITED STATES DEPARTMENT OF COMMERCE**  
**National Institute of Standards and Technology**  
Gaithersburg, Maryland 20899

November 20, 2008

Mr. Leslie Bai  
SIEMIC, Inc.  
2206 Ringwood Avenue  
San Jose, CA 95131

Dear Mr. Bai:

NIST is pleased to inform you that your laboratory has been recognized by the Australian Communications and Media Authority (ACMA) under the Asia Pacific Economic Cooperation for Telecommunications Equipment Mutual Recognition Arrangement (APEC Tel MRA). Your laboratory is now designated to act as a Conformity Assessment Body (CAB) under Appendix B, **Phase I** Procedures, of the APEC Tel MRA. The pertinent information about your laboratory's designation is as follows:

CAB Name: Siemic, Inc.  
Physical Location: 2206 Ringwood Avenue, San Jose, CA 95131  
Identification No.: US0160  
Recognized Scope: EMC: AS/NZS 4251.1 (until 5/31/2009), AS/NZS 4251.2 (until 5/31/2009), AS/NZS CISPR 11, AS/NZS CISPR 14.1, AS/NZS CISPR 22, AS/NZS 61000.6.3, AS/NZS 61000.6.4  
Radiocommunications: AS/NZS 4281, AS/NZS 4268, AS/NZS 4280.1, AS/NZS 4280.2, AS/NZS 4295, AS/NZS 4582, AS/NZS 4583, AS/NZS 4769.1, AS/NZS 4769.2, AS/NZS 4770, AS/NZS 4771  
Telecommunications: AS/ACIF S002:05, AS/ACIF S003:06, AS/ACIF S004:06, AS/ACIF S006:01, AS/ACIF S016:01, AS/ACIF S031:01, AS/ACIF S038:01, AS/ACIF S040:01, AS/ACIF S041:05, AS/ACIF S043.2:06, AS/NZS 60950.1

You may submit test data to ACMA to verify that the equipment to be imported into Australia satisfies the applicable requirements. The designation of your organization will remain in force as long as its accreditation for the designated scope remains valid and comply with the designation requirements. Recognized CABs are listed on the NIST website at <http://ts.nist.gov/mra>. Please contact Ms. Ramona Saar, at (301) 975-5521 or [ramona.saar@nist.gov](mailto:ramona.saar@nist.gov) if you have questions.

Sincerely,

David F. Alderman  
Group Leader, Standards Coordination and Conformity Group  
Standards Services Division

Enclosure

cc: Snell Leong, Siemic, Inc.; Ramona Saar, NIST

**NIST**

**SIEMIC ACCREDITATION DETAILS: Korea CAB ID: US0160**



**UNITED STATES DEPARTMENT OF COMMERCE**  
**National Institute of Standards and Technology**  
Gaithersburg, Maryland 20899

December 3, 2012

Mr. Leslie Bai  
SIEMIC, Inc.  
775 Montague Expressway  
Milpitas, CA 95035

Dear Mr. Bai:

NIST is pleased to inform you that your laboratory continues to be recognized by the National Radio Research Agency (RRA) Korea Communications Commission (KCC) under Phase I of the APEC Tel MRA. The scope of recognition has been updated. The information regarding your recognition is as follows:

**CAB Name:** SIEMIC, Inc.  
**Physical Location:** 775 Montague Expressway, Milpitas, CA 95035  
**Identification No.:** US0160  
**Updated Scope:** **EMI:** RRA Public Notification 2011-24, RRA Announce 2011-30, KN11, KN13, KN14-1, KN 22, KN 41, KN 50, KN 15, KN 19, KN 60, KN 16-1-1, KN 16-1-2, KN 16-1-3, KN 16-1-4, KN 16-1-5, KN 16-2-1, KN 16-2-2, KN 16-2-3, KN 16-2-4, KN 301-489-01, KN 301-489-07, KN 301-489-17, KN 301-489-24, KN 301-489-06, KN 301-489-13, KN 301-489-05, KN 301-489-03, KN 301-489-09, KN 301-489-26, KN 301-489-18, KN 301-489-15, KN 301-489-02, KN 301-489-27, KN 301-489-32, KN 301-489-20, KN 60945;  
**EMS:** RRA Public Notification 2011-25, RRA Announce 2011-31, KN 61000-4-2, KN 61000-4-3, KN 61000-4-4, KN 61000-4-5, KN 61000-4-6, KN 61000-4-8, KN 61000-4-11, KN 60601-1-2, KN 20, KN 14-2, KN 24, KN 41, KN 51, KN 301-489-01, KN 301-489-07, KN 301-489-17, KN 301-489-24, KN 301-489-06, KN 301-489-13, KN 301-489-05, KN 301-489-03, KN 301-489-09, KN 301-489-26, KN 301-489-18, KN 301-489-15, KN 301-489-02, KN 301-489-27, KN 301-489-32, KN 301-489-20, KN 60945;  
**RF:** KCC Public Notification 2012-12, RRA Announce 2011-32, RRA Public Notification 2010-46;  
**SAR:** KCC Public Notification 2009-27, RRA Public Notification 2010-45, KCC Public Notification 2012-2;  
**TELECOM:** RRA Public Notification 2010-36; RRA Public Notification 2009-38, RRA Announce 2011-2 (Annexes 1, 3, 5, 6)

**NIST**



You may submit test data to RRA/KCC to verify that the equipment to be imported into Korea satisfies the applicable requirements. The recognition of your organization will remain in force as long as the accreditation for the designated scope remains valid and your organization complies with the designation requirements.

Recognized CABs are listed on the NIST website at <http://gsi.nist.gov/global/index.cfm/L1-4/L2-16/L3-90>. If you have any questions please contact Ramona Saar via email at [ramona.saar@nist.gov](mailto:ramona.saar@nist.gov) or phone at (301) 975-5521.

Sincerely,

David F. Alderman  
Standards Services Group

Enclosure

cc: Ramona Saar



**National Radio Research Agency**

29, Wonhyoro 41Gil, Yongsan-gu, Seoul, 140-848, Korea  
Tel: +82 2 710 6600, Fax: +82 2 710 6629  
Homepage : www.rra.go.kr

November 27, 2012

Mr. David F. Alderman  
Group Leader, Standards Coordination and Conformity Group  
National Institute of Standards and Technology  
100 Bureau Drive, Stop 2100  
Gaithersburg, Maryland 20899-2100, USA

Dear Mr. David F. Alderman:

This is to confirm the recognition by National Radio Research Agency of

**SIEMIC, Inc. (US0160)**

as an accredited Conformity Assessment Body (CAB) under the terms of Phase I of the APEC TEL MRA.  
The scope for which this laboratory has been recognized is given below.


Coverage	Standards	Date of Recognition
Current Scope	EMI : RRA Public Notification 2011-18, RRA Announce 2010-5, KN 11, KN 13, KN 14-1, KN 22, KN 41, KN 50, KN 15, KN 19, KN 60, KN 16-1-1, -1-2, -1-3, -1-4, -1-5, -2-1, -2-2, -2-3, -2-4 EMS : RRA Public Notification 2011-17, RRA Announce 2010-6, KN 61000-4-2, -4-3, -4-4, -4-5, -4-6, -4-8, -4-11, KN 60101-1-2, KN 20, KN 24, KN 41, KN 51 RF : KCC Public Notification 2011-31, KCC Public Notification 2011-10, RRA Public Notification 2010-46, KN 301-489-01, -489-07, -489-17, -489-24 SAR : KCC Public Notification 2009-27, RRA Public Notification 2010-45, KCC Public Notification 2011-10 TELECOM : RRA Public Notification 2010-36, RRA Public Notification 2009-38	November 27, 2012
Updated Scope	EMI : RRA Public Notification 2011-24, RRA Announce 2011-30, KN 11, KN 13, KN 14-1, KN 22, KN 41, KN 50, KN 15, KN 19, KN 60, KN 16-1-1, -1-2, -1-3, -1-4, -1-5, -2-1, -2-2, -2-3, -2-4, KN 301-489-01, -489-07, -489-17, -489-24, -489-06, -489-13, -489-05, -489-03, -489-09, -489-26, -489-18, -489-15, -489-02, -489-27, -489-32, -489-20, KN 60945 EMS : RRA Public Notification 2011-25, RRA Announce 2011-31, KN 61000-4-2, -4-3, -4-4, -4-5, -4-6, -4-8, -4-11, KN 60601-1-2, KN 20, KN 14-2, KN 24, KN 41, KN 51, KN 301-489-01, -489-07, -489-17, -489-24, -489-06, -489-13, -489-05, -489-03, -489-09, -489-26, -489-18, -489-15, -489-02, -489-27, -489-32, -489-20, KN 60945 RF : KCC Public Notification 2012-12, RRA Announce 2011-32, RRA Public Notification 2010-46 SAR : KCC Public Notification 2009-27, RRA Public Notification 2010-45, KCC Public Notification 2012-2 TELECOM : RRA Public Notification 2010-36, RRA Public Notification 2009-38, RRA Announce 2011-2(Annexes 1, 3, 5, 6)	

This recognition is contingent upon the maintenance of this CAB's accreditation status and is limited to the standards listed above.

If you have any inquiries about this recognition, please contact to Conformity Policy Division of National Radio Research Agency with above address and telephone numbers.

Best Regards,

Yoon, Hye-Joo  
Director



Conformity Policy Division

cc: Ramona Saar – NIST  
Gerry Funk – NIST





**SIEMIC ACCREDITATION DETAILS: Taiwan BSMI Accreditation No. SL2-IN-E-1130R**



**UNITED STATES DEPARTMENT OF COMMERCE**  
**National Institute of Standards and Technology**  
Gaithersburg, Maryland 20899

May 3, 2006

Mr. Leslie Bai  
SIEMIC Laboratories  
2206 Ringwood Avenue  
San Jose, CA 95131

Dear Mr. Bai:

I am pleased to inform you that your laboratory has been recognized by the Chinese Taipei's Bureau of Standards, Metrology, and Inspection (BSMI) under the Asia Pacific Economic Cooperation (APEC) Mutual Recognition Arrangement (MRA). Your laboratory is now designated to act as a Conformity Assessment Body (CAB) under Appendix B, **Phase I** Procedures, of the APEC Tel MRA. You may submit test data to BSMI to verify that the equipment to be imported into Chinese Taipei satisfies the applicable requirements. The designation of your organization will remain in force as long as its accreditation for the designated scope remains valid and comply with the designation requirements. The pertinent designation information is as follows:

- BSMI number: **SL2-IN-E-1130R** (Must be applied to the test reports)
- U.S Identification No: **US0160**
- Scope of Designation: **CNS 13438**
- Authorized signatory: **Mr. Leslie Bai**

The names of all recognized CABs will be posted on the NIST website at <http://ts.nist.gov/mra>. If you have any questions, please contact Mr. Dhillon at 301-975-5521. We appreciate your continued interest in our international conformity assessment activities.

Sincerely,

David F. Alderman  
Group Leader, Standards Coordination and Conformity Group

cc: Jogindar Dhillon

**NIST**



**SIEMIC, Inc.**  
Accessing global markets

Title: RF Test Report of Stryker Endoscopy,  
Model: P23366  
To: FCC 15.407:2012, RSS-210 Issue 8 : 2010

Serial# RF\_SL12011902-STR-001\_SYNK\_Receiver (FCC\_15.407) Rev1.2  
Issue Date Oct 2nd, 2013  
Page 87 of 93  
www.siemic.com

**SIEMIC ACCREDITATION DETAILS: Taiwan NCC CAB ID: US0160**



**UNITED STATES DEPARTMENT OF COMMERCE**  
**National Institute of Standards and Technology**  
Gaithersburg, Maryland 20899

April 25, 2011

Mr. Leslie Bai  
SIEMIC, Inc.  
2206 Ringwood Avenue  
San Jose, CA 95131

Dear Mr. Bai:

NIST is pleased to inform you that your laboratory has been recognized by the National Communications Commission (NCC) under the Asia Pacific Economic Cooperation for Telecommunications Equipment Mutual Recognition Arrangement (APEC Tel MRA). Your laboratory is now designated to act as a Conformity Assessment Body (CAB) under Appendix B, **Phase I** Procedures, of the APEC Tel MRA. The pertinent information about the laboratory's designation is as follows:

CAB Name:	SIEMIC, Inc.
Physical Location:	2206 Ringwood Avenue, San Jose, CA 95131
Identification No.:	US0160
Previous Scope:	LP0002, PSTN01, ADSL01, ID0002, IS6100, CNS 14336, PLMN07
Current Scope:	LP0002, PSTN01, ADSL01, ID0002, IS6100, CNS 14336, PLMN07, PLMN01 and PLMN08

You may submit test data to NCC to verify that the equipment to be imported into Chinese Taipei satisfies the applicable requirements. The designation of your organization will remain in force as long as its accreditation for the designated scope remains valid and comply with the designation requirements.

Recognized CABs are listed on the NIST website at <http://ts.nist.gov/mra>. If you have any questions please contact Ramona Saar at (301) 975-5521 or [ramona.saar@nist.gov](mailto:ramona.saar@nist.gov).

Sincerely,

David F. Alderman  
Standards Services Group

Enclosure

cc: Ramona Saar

**NIST**

**SIEMIC ACCREDITATION DETAILS: Vietnam CAB ID: US0160**



**UNITED STATES DEPARTMENT OF COMMERCE**  
**National Institute of Standards and Technology**  
Gaithersburg, Maryland 20899-

July 11, 2012

Mr. Leslie Bai  
SIEMIC, Inc.  
2206 Ringwood Avenue  
San Jose, CA 95131

Dear Mr. Bai:

NIST is pleased to inform you that your laboratory continues to be recognized by Vietnam's Ministry of Information and Communication (MIC) under the Asia Pacific Economic Cooperation for Telecommunications Equipment Mutual Recognition Arrangement (APEC Tel MRA). MIC has updated your scope of recognition. The pertinent information about the continued recognition is as follows:

**CAB Name:** SIEMIC, Inc.  
**Physical Location:** 2206 Ringwood Avenue, San Jose, CA 95131  
**Identification No.:** US0160  
**Current Scope:** TCN68-188, TCN68-190, TCN68-193, TCN68-196, TCN68-143, TCN68-192, TCN68-189, TCN68-221, TCN68-222, TCN68-223, TCN68-245, TCN68-242, TCN68-243, TCN68-246, TCVN 7189  
**Updated Scope:** QCVN 19:2010/BTTTT, QCVN 22:2010/BTTTT, TCVN 7189:2009, TCVN 7317:2003, QCVN 10:2010/BTTTT, QCVN 12:2010/BTTTT, QCVN 3:2010/BTTTT, QCVN 15:2010/BTTTT, QCVN 11:2010/BTTTT, QCVN 54:2011/BTTTT, QCVN 55:2011/BTTTT, QCVN 18:2010/BTTTT, QCVN 17:2010/BTTTT

You may submit test data to MIC to verify that the equipment to be imported into Vietnam satisfies the applicable requirements. *Please note that your recognition from Vietnam will expire on **September 30, 2012**. To continue the recognition beyond this date, it will be necessary to submit to NIST the updated ISO/IEC 17025 Scope and Certification of Accreditation as soon as it is reissued during your next accreditation renewal period. NIST will then submit the updated information to MIC so that the recognition can be extended.*

Recognized CABs are listed on the NIST website at <http://gsi.nist.gov/global/index.cfm/L1-4/L2-16/L3-90/A-380>. If you have any questions please contact Ramona Saar via email at [ramona.saar@nist.gov](mailto:ramona.saar@nist.gov) or phone at (301) 975-5521.

Sincerely,

David F. Alderman  
Standards Services Group

Enclosure

cc: Ramona Saar

**NIST**





**SIEMIC ACCREDITATION DETAILS: Mexico NOM Recognition**



CAMERA NACIONAL  
DE LA INDUSTRIA  
ELECTRONICA, DE  
TELECOMUNICACIONES  
E INFORMATICA

**Laboratorio Valentín V. Rivero**

México D.F. a 16 de octubre de 2005.


**LESLIE BAI  
DIRECTOR OF CERTIFICATION  
SIEMIC LABORATORIES, INC.  
ACCESSING GLOBAL MARKETS  
P R E S E N T E**

En contestación a su escrito de fecha 5 de septiembre del año en curso, le comento que estamos muy interesados en su intención de firmar un Acuerdo de Reconocimiento Mutuo, para lo cual adjunto a este escrito encontrara el Acuerdo en idioma inglés y español prellenado de los cuales le pido sea revisado y en su caso corregido, para que si esta de acuerdo poder firmarlo para mandarlo con las autoridades Mexicanas para su visto bueno y así poder ejercer dicho acuerdo.

Aprovecho este escrito para mencionarle que nuestro intermediano gestor será la empresa Isabel de México, S. A. de C. V., empresa que ha colaborado durante mucho tiempo con nosotros en lo relacionado a la evaluación de la conformidad y que cuenta con amplia experiencia en la gestión de la certificación de cumplimiento con Normas Oficiales Mexicanas de producto en México.

Me despido de usted enviándole un cordial saludo y esperando sus comentarios al Acuerdo que nos ocupa

Atentamente:

  
**Ing. Faustino Gomez Gonzalez  
Gerente Técnico del Laboratorio de  
CANIETI.**

**SIEMIC ACCREDITATION DETAILS: Hong Kong OFTA CAB ID : US0160**



**UNITED STATES DEPARTMENT OF COMMERCE**  
**National Institute of Standards and Technology**  
Gaithersburg, Maryland 20899-

December 8, 2008

Mr. Leslie Bai  
SIEMIC, Inc.  
2206 Ringwood Avenue  
San Jose, CA 95131

Dear Mr. Bai:

NIST is pleased to inform you that your laboratory has been recognized by the Office of the Telecommunications Authority (OFTA) under the Asia Pacific Economic Cooperation for Telecommunications Equipment Mutual Recognition Arrangement (APEC Tel MRA). Your laboratory is now designated to act as a Conformity Assessment Body (CAB) under Appendix B, **Phase I** Procedures, of the APEC Tel MRA. The pertinent information about your laboratory's designation is as follows:

CAB Name: SIEMIC, Inc.  
Physical Location: 2206 Ringwood Avenue, San Jose, California 95131 USA  
Identification No.: US0160  
Recognized Scope: **Radio:** HKTA 1002, 1007, 1008, 1010, 1015, 1016, 1020, 1022, 1026, 1027, 1029, 1030, 1031, 1032, 1033, 1034, 1035, 1036, 1037, 1039, 1041, 1042, 1043, 1044, 1046, 1047, 1048, 1049, 1051  
**Telecom:** HKTA 2011, 2012, 2013, 2014, 2017, 2018, 2022, 2024, 2026, 2027, 2028, 2029, 2030, 2031, 2032, 2033

You may submit test data to OFTA to verify that the equipment to be imported into Hong Kong satisfies the applicable requirements. The designation of your organization will remain in force as long as its accreditation for the designated scope remains valid and comply with the designation requirements.

Recognized CABs are listed on the NIST website at <http://ts.nist.gov/mra>. If you have any questions please contact Ramona Saar at (301) 975-5521 or [ramona.saar@nist.gov](mailto:ramona.saar@nist.gov).

Sincerely,

David F. Alderman  
Group Leader, Standards Coordination and Conformity Group  
Standards Services Division

Enclosure

cc: Ramona Saar





**SIEMIC, Inc.**  
Accessing global markets

Title: RF Test Report of Stryker Endoscopy,  
Model: P23366  
To: FCC 15.407:2012, RSS-210 Issue 8 : 2010

Serial# RF\_SL12011902-STR-001\_SYNK\_Receiver (FCC\_15.407) Rev1.2  
Issue Date Oct 2nd, 2013  
Page 91 of 93  
www.sieminc.com

**SIEMIC ACCREDITATION DETAILS: Australia ACMA CAB ID: US0160**



**UNITED STATES DEPARTMENT OF COMMERCE**  
**National Institute of Standards and Technology**  
Gaithersburg, Maryland 20899

November 20, 2008

Mr. Leslie Bai  
SIEMIC, Inc.  
2206 Ringwood Avenue  
San Jose, CA 95131

Dear Mr. Bai:

NIST is pleased to inform you that your laboratory has been recognized by the Australian Communications and Media Authority (ACMA) under the Asia Pacific Economic Cooperation for Telecommunications Equipment Mutual Recognition Arrangement (APEC Tel MRA). Your laboratory is now designated to act as a Conformity Assessment Body (CAB) under Appendix B, **Phase I** Procedures, of the APEC Tel MRA. The pertinent information about your laboratory's designation is as follows:

CAB Name: Siemic, Inc.  
Physical Location: 2206 Ringwood Avenue, San Jose, CA 95131  
Identification No.: US0160  
Recognized Scope: EMC: AS/NZS 4251.1 (until 5/31/2009), AS/NZS 4251.2 (until 5/31/2009), AS/NZS CISPR 11, AS/NZS CISPR 14.1, AS/NZS CISPR 22, AS/NZS 61000.6.3, AS/NZS 61000.6.4  
Radiocommunications: AS/NZS 4281, AS/NZS 4268, AS/NZS 4280.1, AS/NZS 4280.2, AS/NZS 4295, AS/NZS 4582, AS/NZS 4583, AS/NZS 4769.1, AS/NZS 4769.2, AS/NZS 4770, AS/NZS 4771  
Telecommunications: AS/ACIF S002:05, AS/ACIF S003:06, AS/ACIF S004:06, AS/ACIF S006:01, AS/ACIF S016:01, AS/ACIF S031:01, AS/ACIF S038:01, AS/ACIF S040:01, AS/ACIF S041:05, AS/ACIF S043.2:06, AS/NZS 60950.1

You may submit test data to ACMA to verify that the equipment to be imported into Australia satisfies the applicable requirements. The designation of your organization will remain in force as long as its accreditation for the designated scope remains valid and comply with the designation requirements. Recognized CABs are listed on the NIST website at <http://ts.nist.gov/mra>. Please contact Ms. Ramona Saar, at (301) 975-5521 or [ramona.saar@nist.gov](mailto:ramona.saar@nist.gov) if you have questions.

Sincerely,

David F. Alderman  
Group Leader, Standards Coordination and Conformity Group  
Standards Services Division

Enclosure

cc: Snell Leong, Siemic, Inc.; Ramona Saar, NIST

**NIST**

## SIEMIC ACCREDITATION DETAILS: Australia NATA Recognition



Leslie Bai  
SIEMIC, Inc.  
2206 Ringwood Avenue  
San Jose, CA 95131

November 4, 2008

Under Australian government legislation, the Australian Communications and Media Authority (ACMA) has determined the National Association of Testing Authorities, Australia (NATA) as an accreditation body as per Section 409(1) of the Telecommunications Act 1997 (Cth). Pursuant to Section 409(2) of the Telecommunications Act 1997 (Cth), I am pleased to advise that your laboratory has been determined as a Recognised Testing Authority (RTA).

This determination has been made on the basis of your accreditation by A2LA accreditation no. 2742.01 and the Mutual Recognition Agreement between NATA and A2LA. It is effective from 11 July 2008. RTA status applies only to the following standards and is contingent upon their continued inclusion in your laboratory's scope of accreditation.

**AS/ACIF S002, AS/ACIF S003, AS/ACIF S004,  
AS/ACIF S006, AS/ACIF S016, AS/ACIF S031,  
AS/ACIF S038, AS/ACIF S041 and  
AS/ACIF S043.2**

As an RTA, your laboratory has the following obligations:

1. the laboratory shall continue to meet all of the accreditation criteria of A2LA;
2. the authorised representative of the laboratory shall notify NATA of changes to the staff or operations of the laboratory which would affect the performance of the tests for which the laboratory has been determined;
3. compliance of equipment shall be reported on test reports bearing the A2LA logo/endorsement.

Current information on the Australian Communications and Media Authority and regulatory requirements for telecommunications products within Australia can be obtained from the ACMA's web-site at "<http://www.acma.gov.au>". Further information about NATA may be gained by visiting "<http://www.nata.asn.au>".

Please note that AS/ACIF S040 and New Zealand standards do not form part of the RTA scheme.

Your RTA listing will appear on the NATA website shortly.

Kind Regards

Chris Norton,  
Senior Scientific Officer  
Measurement Science and Technology  
National Association of Testing Authorities (NATA)  
71-73 Flemington Road  
North Melbourne Vic 3051  
Australia  
Ph: +61 3 9329 1633 Fx: +61 3 9326 5148  
E-Mail: [Christopher.Norton@nata.asn.au](mailto:Christopher.Norton@nata.asn.au)  
Internet: [www.nata.asn.au](http://www.nata.asn.au)



**SIEMIC ACCREDITATION DETAILS: VCCI Radiated Test Site Registration No. A-0133**

## Certificate of VCCI Laboratory registration

1. Registration Information		
<b>1.1 Laboratory Info.</b>	<b>Company name (VCCI Membership No.)</b>	SIEMIC Laboratories (3081)
	<b>Laboratory Name</b>	SIEMIC Labs (Milpitas location)
	<b>VCCI Laboratory registration No.</b>	A-0133
	<b>VCCI Laboratory registration date</b>	09/21/2012 (mm/dd/yyyy)
	<b>Registration expiration date</b>	09/30/2014 (mm/dd/yyyy)
	<b>Country of Laboratory</b>	USA
	<b>ISO 17025 Accreditation body name</b>	A2LA
	<b>Accreditation No.</b>	2742.01
	<b>Accreditation valid to mm/dd/yyyy</b>	09/30/2014 (mm/dd/yyyy)
	<b>Edition (year) of the VCCI rule indicated in the scope of accreditation (example: V-3 20xx.04)</b>	Not described in Scope
	<b>Zip code</b>	95035
<b>Address</b>	775 Montague Expressway, Milpitas , CA 95035 USA	



VCCI Council