FCC ID: SSM393036E

Portable device

According to §15.247(e)(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to KDB447498 D01 General RF Exposure Guidance V05

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances \leq 50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)] * $[\sqrt{f(GHz)}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

f(GHz) is the RF channel transmit frequency in GHz;

Power and distance are rounded to the nearest mW and mm before calculation;

The result is rounded to one decimal place for comparison;

The test exclusions are applicable only when the minimum test separation distance is \leq 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion. We use 5mm as separation distance to calculated.

Transmit Frequency (GHz)	Mode	Measured Power (dBm)	Tune-up power (dBm)	Max tune-up power(dBm)	Result calculation	1-g SAR
2.402	GFSK	0.244	-1.5±1.5	0	0.3100	3.00
2.441	GFSK	-0.586	-1.5±1.5	0	0.3125	3.00
2.480	GFSK	-2.913	-1.5±1.5	0	0.3150	3.00
2.402	π /4-DQPSK	-1.225	-2.5 ± 1.5	-1	0.2462	3.00
2.441	π /4-DQPSK	-2.622	-2.5±1.5	-1	0.2482	3.00
2.480	π /4-DQPSK	-3.904	-2.5±1.5	-1	0.2502	3.00
2.402	8DPSK	-0.728	-2.3±1.6	-0.7	0.2638	3.00
2.441	8DPSK	-2.850	-2.3±1.6	-0.7	0.2660	3.00
2.480	8DPSK	-3.833	-2.3±1.6	-0.7	0.2681	3.00

Maximum measured transmitter power:

Conclusion:

For the max result $0.3150 \le 3.0$ for 1-g SAR extremity SAR, No SAR is required.

Sincerely,

Signature Company Name: SHENZHEN EMTEK CO., LTD. Address: Bldg 69, Majialong Industry Zone, NanshanDistrict, Shenzhen, China. David Lee/ Manager