

# FCC ID: SSMMEF1225

## Portable device

According to §15.247(e)(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to KDB447498 D01 General RF Exposure Guidance V05

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})]^*$

$[\sqrt{f(\text{GHz})}] \leq 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR, where

$f(\text{GHz})$  is the RF channel transmit frequency in GHz;

Power and distance are rounded to the nearest mW and mm before calculation;

The result is rounded to one decimal place for comparison;

The test exclusions are applicable only when the minimum test separation distance is  $\leq 50$  mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is  $< 5$  mm, a distance of 5 mm is applied to determine SAR test exclusion.

We use 5mm as separation distance to calculate.

Maximum measured transmitter power:

BT DSS:

Transmit Frequency (GHz)	Mode	Max Conducted Power (dBm)	Max Conducted Power (mW)	Result calculation	1-g SAR
2.402	GFSK	-3.553	0.44	0.14	3.0
2.441	GFSK	-2.876	0.52	0.16	3.0
2.480	GFSK	-3.018	0.50	0.16	3.0
2.402	$\pi/4$ -DQPSK	-5.891	0.26	0.08	3.0
2.441	$\pi/4$ -DQPSK	-4.601	0.35	0.11	3.0
2.480	$\pi/4$ -DQPSK	-4.834	0.33	0.10	3.0
2.402	8DPSK	-5.338	0.29	0.09	3.0
2.441	8DPSK	-4.134	0.39	0.12	3.0
2.480	8DPSK	-4.025	0.40	0.12	3.0

**Conclusion:**

For the max result :  $0.16 \leq 3.0$  for 1-g SAR extremity SAR, No SAR is required.

Signature: 

Date: 2015-03-17

NAME AND TITLE (Please print or type): David Lee/Manager

COMPANY (Please print or type): Shenzhen EMTEK Co.,Ltd./Building 69, Majialong Industry Zone, Nanshan District, Shenzhen,Guangdong,China