

No. 1 Workshop, M-10, Middle section, Science & Technology Park,

Shenzhen, Guangdong, China 518057 Telephone: +86 (0) 755 2601 2053 Fax: +86 (0) 755 2671 0594

Email: ee.shenzhen@sgs.com

Report No.: SZEM161201139502

Page: 1 of 8

RF Exposure Evaluation Report

Application No.: SZEM1612011395CR

Applicant: MODERN ELECTRONICS FACTORY LTD.

Manufacturer: MODERN ELECTRONICS FACTORY LTD.

Factory Keng Fu Jia Electronics (Shenzhen) Co., Ltd.

Product Name: Classic Wooden Turntable with Dust Cover

Model No.(EUT): MD-909

Trade Mark:

by one

FCC ID: SSMMEF909

Standards: 47 CFR Part 1.1307 (2016)

47 CFR Part 1.1310 (2016)

Date of Receipt: 2017-01-22

Date of Test: 2017-02-08 to 2017-03-02

Date of Issue: 2017-03-06

Test Result : PASS*

* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:



Jack Zhang EMC Laboratory Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sqs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sqs.com/en/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.



Report No.: SZEM161201139502

Page: 2 of 8

2 Version

Revision Record					
Version	Chapter	Date	Modifier	Remark	
01		2017-03-06		Original	

Authorized for issue by:			
Tested By	Peter Gene	2017-03-02	
	Peter Geng /Project Engineer	Date	
Checked By	Eric Fu	2017-03-06	
	Eric Fu /Reviewer	Date	



Report No.: SZEM161201139502

Page: 3 of 8

3 Contents

		Pa	ge
1	С	COVER PAGE	1
2	٧	/ERSION	2
3	С	CONTENTS	3
4	G	GENERAL INFORMATION	4
	4.1	CLIENT INFORMATION	4
	4.2		4
	4.3	TEST LOCATION	5
	4.4	TEST FACILITY	5
	4.5		6
	4.6	ABNORMALITIES FROM STANDARD CONDITIONS	
	4.7	OTHER INFORMATION REQUESTED BY THE CUSTOMER	6
5	R	RF EXPOSURE EVALUATION	7
	5.1	RF Exposure Compliance Requirement	7
		5.1.1 Limits	
	5	5.1.2 Test Procedure	7
	4.1.3	3 EUT RF Exposure Evaluation	8



Report No.: SZEM161201139502

Page: 4 of 8

4 General Information

4.1 Client Information

Applicant:	MODERN ELECTRONICS FACTORY LTD.
Address of Applicant:	FLAT C, 10/F, PHASE 4, KWUN TONG INDUSTRIAL CENTRE, 472-478 KWUN TONG ROAD, HONG KONG
Manufacturer:	MODERN ELECTRONICS FACTORY LTD.
Address of Manufacturer:	FLAT C, 10/F, PHASE 4, KWUN TONG INDUSTRIAL CENTRE, 472-478 KWUN TONG ROAD, HONG KONG
Factory:	Keng Fu Jia Electronics (Shenzhen) Co., Ltd.
Address of Factory:	Sui Wai Sun Chuen, Tai Long, Lung Wah, Shenzhen, GDGZ

4.2 General Description of EUT

Product Name:	Classic Wooden Turntable with Dust Cover	
Model No.:	MD-909	
Trade Mark:	The by one	
Operation Frequency:	2402MHz~2480MHz	
Bluetooth Version:	2.1+EDR	
Modulation Type:	GFSK, π/4DQPSK	
Number of Channel:	79	
Antenna Type:	Integral Antenna	
Antenna Gain:	2dBi	
Power Supply	adapter model: HK15-HASF0902000	
	INPUT: AC 100-240V, 50/60Hz	
	OUTPUT: DC 9.0V, 2000mA	



Report No.: SZEM161201139502

Page: 5 of 8

4.3 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

No. 1 Workshop, M-10, Middle section, Science & Technology Park, Shenzhen, Guangdong, China 518057

Telephone: +86 (0) 755 2601 2053 Fax: +86 (0) 755 2671 0594

No tests were sub-contracted.

4.4 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

• CNAS (No. CNAS L2929)

CNAS has accredited SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC

Lab to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

• A2LA (Certificate No. 3816.01)

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 3816.01.

VCCI

The 10m Semi-anechoic chamber and Shielded Room of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-823, R-4188, T-1153 and C-2383 respectively.

FCC – Registration No.: 556682

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No.: 556682.

Industry Canada (IC)

Two 3m Semi-anechoic chambers and the 10m Semi-anechoic chamber of SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab have been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 4620C-1, 4620C-2, 4620C-3.



Report No.: SZEM161201139502

Page: 6 of 8

4.5 Deviation from Standards

None.

4.6 Abnormalities from Standard Conditions

None

4.7 Other Information Requested by the Customer

None.



Report No.: SZEM161201139502

Page: 7 of 8

5 RF Exposure Evaluation

5.1 RF Exposure Compliance Requirement

5.1.1 Limits

According to FCC Part1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in part1.1307(b)

Table 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm²)	Averaging time (minutes)		
(A) Limits for Occupational/Controlled Exposures						
0.3–3.0 3.0–30 30–300 300–1500 1500–100,000	614 1842/f 61.4	1.63 4.89/f 0.163	*(100) *(900/f²) 1.0 f/300 5	6 6 6 6		
(B) Limits for General Population/Uncontrolled Exposure						
0.3–1.34 1.34–30 30–300 300–1500 1500–100,000	614 824/f 27.5	1.63 2.19/f 0.073	*(100) *(180/f²) 0.2 f/1500 1.0	30 30 30 30 30		

F= Frequency in MHz

Friis Formula

Friis transmission formula: Pd = (Pout*G)/(4*Pi*R2)

Where

Pd = power density in mW/cm2

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

Pd id the limit of MPE, 1 mW/cm2. If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

5.1.2 Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.



Report No.: SZEM161201139502

Page: 8 of 8

4.1.3 EUT RF Exposure Evaluation

Antenna Gain: 2dBi

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 1.58 in linear scale.

Output Power Into Antenna & RF Exposure Evaluation Distance:

Channel	Frequency	Max Conducted	Output Power	Power Density	Limit	Result
	(MHz)	Peak Output	to Antenna	at R = 20 cm		
		Power (dBm)	(mW)	(mW/cm²)		
highest	2480	-3.95	0.40	0.000126	1.0	PASS

Note: Refer to report No. SZEM161201139501 for EUT test Max Conducted Peak Output Power value. The distance r (4th column) calculated from the Fries transmission formula is far greater than 20 cm separation requirement.