

Advanced
Compliance Laboratory

6 Randolph Way
Hillsborough, NJ 08844
Tel: (908) 927 9288
Fax: (908) 927 0728

ELECTROMAGNETIC EMISSION COMPLIANCE REPORT

of

ASSET/PATIENT/TEMPERATURE TAG

MODEL: IT-711, IT-713, IT-714, IT-715, IT-721, IT-723, IT-724, IT-325
FCC ID: ST2-2X71Y

November 03, 2010

This report concerns (check one): Original grant <input checked="" type="checkbox"/> Class II change <input type="checkbox"/>	
Equipment type: <u>Low Power Intentional Radiator</u>	
Deferred grant requested per 47 CF 0.457(d)(1)(ii)?	yes <input type="checkbox"/> no <input checked="" type="checkbox"/>
If yes, defer until: _____ (date)	
Company agrees to notify the Commission by	_____ (date)
of the intended date of announcement of the product so that the grant can be issued on that date.	
Transition Rules Request per 15.37?	yes <input type="checkbox"/> no <input checked="" type="checkbox"/>
If no, assumed Part 15, Subpart B for unintentional radiators - the new 47 CFR [10-1-90 Edition] provision.	
Report prepared for:	REMOTE PLAY, INC.
Report prepared by:	Advanced Compliance Lab
Report number:	0048-101019-01-FCC



Lab Code: 200101

The test result in this report IS supported and covered by the NVLAP accreditation

Table of Contents

Report Cover Page 1

Table of Contents 2

Figures 3

1. GENERAL INFORMATION 4

1.1 Verification of Compliance 4

1.2 Equipment Modifications 5

1.3 Product Information 6

1.4 Test Methodology..... 6

1.5 Test Facility 6

1.6 Test Equipment..... 6

1.7 Statement of the Document Use..... 7

2. PRODUCT LABELING..... 8

3. SYSTEM TEST CONFIGURATION..... 9

3.1 Justification 9

3.2 Special Accessories 9

3.3 Configuration of Tested System 9

4. SYSTEM SCHEMATICS 12

5. RADIATED EMISSION DATA 13

5.1 Field Strength Calculation..... 13

5.2 Test Methods and Conditions..... 13

5.3 Test Data 13

6. EUT RECEIVING MODE VERIFICATION 18

7. PHOTOS OF TESTED EUT..... 19

Figures

Figure 2.1 FCC ID Label..... 8

Figure 2.2 Location of Label on Back of the EUT..... 8

Figure 3.1 Radiated Test Setup, Position 1 10

Figure 3.2 Radiated Test Setup, Position 2 10

Figure 3.3 Radiated Test Setup, Position 3 11

Figure 4.1 EUT Schematics..... 12

Figure 7.1 Front View 20

Figure 7.2 Back View 21

Figure 7.3 Inside View..... 22

Figure 7.4 PCB Component View..... 23

Figure 7.5 PCB Foil View..... 24

1. GENERAL INFORMATION

1.1 Verification of Compliance

EUT: ASSET/PATIENT/TEMPERATURE TAG

Model: IT-711, IT-713, IT-714, IT-715, IT-721, IT-723, IT-724, IT-325

Applicant: REMOTE PLAY, INC.

Test Type: FCC Part 15C CERTIFICATION

Result: PASS

Tested by: ADVANCED COMPLIANCE LABORATORY


Test Date: October 19 - November 03, 2010

Report Number: 0048-101019-01-FCC

The above equipment was tested by Compliance Laboratory, Advanced Technologies, Inc. for compliance with the requirement set forth in the FCC rules and regulations Part 15 subpart C. This said equipment in the configuration described in the report, shows the maximum emission levels emanating from equipment are within the compliance requirements.

The estimated uncertainty of the test result is given as following. The method of uncertainty calculation is provided in Advanced Compliance Lab. Doc. No. 0048-01-01.

	Prob. Dist.	Uncertainty(dB)	Uncertainty(dB)	Uncertainty(dB)
		30-1000MHz	1-6.5GHz	Conducted
Combined Std. Uncertainty u_c	norm.	± 2.36	± 2.99	± 1.83



Wei Li
Lab Manager
Advanced Compliance Lab

Date November 03, 2010

1.2 Equipment Modifications

N/A

1.3 Product Information

System Configuration

ITEM	DESCRIPTION	FCC ID	CABLE
Product	ASSET/PATIENT/TEMPERATURE TAG 2X74Y ⁽¹⁾	ST2-2X71Y	
Housing	PLASTICS		
Power Supply	3V DC Battery		
Operation Freq.	904MHz ~ 926MHz		
Receiver	2X71Y(RX)	Verification	

(1) EUT submitted for grant.

1.4 Test Methodology

Radiated tests were performed according to the procedures in ANSI C63.4-2003 at an antenna to EUT distance of 3 meters.

1.5 Test Facility

The open area test site and conducted measurement facility used to collect the radiated and conducted data are located at Hillsborough, New Jersey. This site has been accepted by FCC to perform measurements under Part 15 or 18 in a letter dated May 19, 1997 (Refer to: 31040/PRV 1300F2). The NVLAP Lab code for accreditation of FCC EMC Test Method is: 200101-0.

1.6 Test Equipment


Manufacture	Model	Serial No.	Description	Cal Due dd/mm/yy
Hewlett-Packard	HP8546A	3448A0029 0	EMI Receiver	25/09/11
EMCO	3104C	9307-4396	20-300MHz Biconical Antenna	19/10/11
EMCO	3146	9008-2860	200-1000MHz Log-Periodic Antenna	19/10/11
Fischer Custom	LISN-2	900-4-0008	Line Impedance Stabilization Networks	05/10/11
Fischer Custom	LISN-2	900-4-0009	Line Impedance Stabilization Networks	18/10/11
EMCO	3115	4945	Double Ridge Guide Horn Antenna	17/10/11

All Test Equipment Used are Calibrated Traceable to NIST Standards.

1.7 Statement for the Document Use

This report shall not be reproduced except in full, without the written approval of the laboratory. And this report must not be used by the client to claim product endorsement by NVLAP or any agency of the U.S. Government.

2. PRODUCT LABELING



**Figure 2.1 FCC ID Label
(Only FCC ID shown on EUT)**



Figure 2.2 FCC Label Location

3. SYSTEM TEST CONFIGURATION

3.1 Justification

The system was configured for testing in a typical fashion (as a customer would normally use it). And its antenna was permanently attached to the EUT with max length, 3”.

Testing was performed as EUT was continuously operated at the following frequency channels:

Low=904MHz, Middle= 914MHz, High=926MHz.

Fresh external battery was used for extended operating time.

3.2 Special Accessories

N/A

3.3 Configuration of Tested System

Figure 3.1 to Figure 3.3 illustrate this system, which is tested standing along.




Figure 3.1 Radiated Test Setup, position 1



Figure 3.2 Radiated Test Setup, position 2



Figure 3.3 Radiated Test Setup, position 3

4. SYSTEM SCHEMATICS

See Attachment.

Figure 4.1 System Schematics

5. RADIATED EMISSION DATA

5.1 Field Strength Calculation

The corrected field strength is automatically calculated by EMI Receiver using following:

$$FS = RA + AF + CF + AG$$

where FS: Corrected Field Strength in dB μ V/m

RA: Amplitude of EMI Receiver before correction in dB μ V

AF: Antenna Factor in dB/m

CF: Cable Attenuation Factor in dB

AG: Built-in Preamplifier Gain in dB (Stored in receiver as part of the calibration data)

THE "DUTY CYCLE CORRECTION FACTOR" FOR SPURIOUS RADIATED EMISSIONS IS;
 $20 \log * (4 \text{ ms} / 100 \text{ ms}) = -28 \text{ dB}$, WHICH WAS USED TO CORRECT THE AVERAGE RADIATED EMISSION READINGS.

5.2 Test Methods and Conditions

The initial step in collecting radiated data is a EMI Receiver scan of the measurement range below 30MHz using peak detector and 9KHz IF bandwidth / 30KHz video bandwidth. For the range 30MHz - 1GHz, 100KHz IF bandwidth / 100KHz video bandwidth are used. Both bandwidths are 1MHz for above 1GHz measurement. Up to 10th harmonics were investigated.

5.3 Test Data

The following data lists the significant emission frequencies, polarity and position, peak reading of the EMI Receiver, the FCC limit, and the difference between the peak reading and the limit. Explanation of the correction and calculation are given in section 5.1.

Test Personnel: _____



Typed/Printed Name: Edward Lee

Date: November 03, 2010

Radiated Test Data (CH-904MHz/914MHz/926MHz & Harmonics)

Frequency (MHz)	Polarity (V,H) Position (X,Y,Z)	Antenna Height (m)	Azimuth (Degree)	Peak Reading at 3m (2) (dBuV/m)	Peak Reading After Correction (dBuV/m)	FCC 3m Limit (1) (dBuV/m)	Difference (dBuV/m)
904	V/X	1.2	180	84.3	56.3	94	-37.7
1808	V/X	1.1	180	48.4	20.4	54	-33.6
2712	V/X	1.1	180	58.9	30.9	54	-23.1
904	H/X	1.2	225	88.5	60.5	94	-33.5
1808	H/X	1.1	180	47.4	19.4	54	-34.6
2712	H/X	1.1	180	66.1	38.1	54	-15.9
914	V/X	1.2	270	88.5	60.5	94	-33.5
1828	V/X	1.1	180	49.2	21.2	54	-32.8
2712	V/X	1.0	180	56	28	54	-26
914	H/X	1.2	135	93.2	65.2	94	-28.8
1828	H/X	1.1	180	45.7	17.7	54	-36.3
2742	H/X	1.1	180	60.4	32.4	54	-21.6
926	V/X	1.2	180	89.9	61.9	94	-32.1
1852	V/X	1.0	180	38.9	10.9	54	-43.1
2778	V/X	1.0	135	51.1	23.1	54	-30.9
926	H/X	12.0	135	96.1	68.1	94	-25.9
1852	H/X	1.0	180	44.6	16.6	54	-37.4
2778	H/X	1.0	180	62.3	34.3	54	-19.7
904	V/Y	1.2	270	86.5	58.5	94	-35.5
1808	V/Y	1.1	180	49.9	21.9	54	-32.1
2712	V/Y	1.0	180	60.2	32.2	54	-21.8
904	H/Y	1.1	135	89.7	61.7	94	-32.3
1808	H/Y	1.1	135	46.6	18.6	54	-35.4
2712	H/Y	1.0	135	57.9	29.9	54	-24.1
914	V/Y	1.2	180	91.5	63.5	94	-30.5
1828	V/Y	1.1	180	46.9	18.9	54	-35.1
2712	V/Y	1.0	180	56.6	28.6	54	-25.4
914	H/Y	1.2	135	95.3	67.3	94	-26.7
1828	H/Y	1.0	135	37.3	9.3	54	-44.7
2742	H/Y	1.0	135	60.3	32.3	54	-21.7
926	V/Y	1.2	135	88.7	60.7	94	-33.3

1852	V/Y	1.0	180	46.2	18.2	54	-35.8
2778	V/Y	1.0	180	57.6	29.6	54	-24.4
926	H/Y	1.2	180	96.1	68.1	94	-25.9
1852	H/Y	1.0	180	46.2	18.2	54	-35.8
2778	H/Y	1.0	180	61.7	33.7	54	-20.3
904	V/Z	1.2	225	83.1	55.1	94	-38.9
1808	V/Z	1.1	180	47.5	19.5	54	-34.5
2712	V/Z	1.1	180	59.3	31.3	54	-22.7
904	H/Z	1.2	180	88.0	60	94	-34
1808	H/Z	1.0	180	38.2	10.2	54	-43.8
2712	H/Z	1.0	180	58.3	30.3	54	-23.7
914	V/Z	1.2	135	92.2	64.2	94	-29.8
1828	V/Z	1.1	180	50.8	22.8	54	-31.2
2712	V/Z	1.1	180	60.3	32.3	54	-21.7
914	H/Z	1.2	180	93.7	65.7	94	-28.3
1828	H/Z	1.1	225	43.6	15.6	54	-38.4
2742	H/Z	1.0	170	54.7	26.7	54	-27.3
926	V/Z	1.2	135	93.5	65.5	94	-28.5
1852	V/Z	1.0	180	43.4	15.4	54	-38.6
2778	V/Z	1.0	180	55.3	27.3	54	-26.7
926	H/Z	1.2	180	96.9	68.9	94	-25.1
1852	H/Z	1.0	180	42.8	14.8	54	-39.2
2778	H/Z	1.0	180	56.5	28.5	54	-25.5



(1) The limit for emissions within the 902-928MHz band is 50mV(94dB) per Sec. 15.249. The limit for its harmonics is 500uV (54dB). Other spurious emissions shall be lower than either its fundamental by 50dB or the limit defined in Sec. 15.209, whichever is higher.

(2) If each peak reading is less than the FCC average limit, it'll be not necessary to show the measured/ calculated average reading.

Other Spurious outside of the band 902-928MHz

Frequency (MHz)	Polarity (V,H) Position (X,Y,Z)	Antenna Height (m)	Azimuth (Degree)	Peak Reading at 3m (2) (dBuV/m)	Peak Reading After Correction (dBuV/m)	FCC 3m Limit (1) (dBuV/m)	Difference (dBuV/m)
368	V/Y	1.1	090	26.8		46.5	-19.7
394	V/Y	1.1	090	26.6		46.5	-19.9
420	V/Y	1.1	090	27.8		46.5	-18.7
316	H/Z	1.0	045	29.5		46.5	-17.0
368	H/Z	1.0	045	37.3		46.5	-9.2
394	H/Z	1.0	045	31.4		46.5	-15.1
420	H/X	1.0	180	32.0		46.5	-14.5

Comparing to the limit defined in Sec. 15.209, emissions below the limit by 20dB were not recorded.



6. EUT RECEIVING MODE VERIFICATION

Radiated Test Data for Receiving Mode (worst case: X-position)

Frequency (MHz)	Polarity (H or V)	Antenna Height (m)	Azimuth (Degree)	Peak Reading at 3m(2) (dBuV/m)	FCC 3m Limit(1) (dBuV/m)	Difference (dBuV/m)
157.5	H	1.3	090	34.4	43.5	-9.1
316	H	1.0	000	31.5	46.5	-15.0
342	H	1.0	000	27.8	46.5	-18.7
368	H	1.0	000	34.3	46.5	-12.2
161.0	V	1.3	270	35.8	43.5	-7.7
316	V	1.1	045	24.4	46.5	-22.1
338	V	1.0	045	24.2	46.5	-22.3
368	V	1.0	270	25.4	46.5	-21.1

(1) Receiving mode spurious emissions shall be lower than the limit defined in Sec. 15.209.

(2) If each peak reading is less than the FCC average limit, it'll be not necessary to show the measured/ calculated average reading.

7. PHOTOS OF TESTED EUT

The following photos show the inside details of the EUT.