

**Advanced
Compliance Laboratory**

6 Randolph Way
Hillsborough, NJ 08844
Tel: (908) 927 9288
Fax: (908) 927 0728

ELECTROMAGNETIC EMISSION COMPLIANCE REPORT
of

HYGIENE TAG
MODEL: IT-753/IT-754
FCC ID: ST2-2X75Y

August 31, 2011

This report concerns (check one): Original grant <input checked="" type="checkbox"/> Class II change <input type="checkbox"/>	
Equipment type: <u>Low Power Intentional Radiator</u>	
Deferred grant requested per 47 CF 0.457(d)(1)(ii)?	yes <input type="checkbox"/> no <input checked="" type="checkbox"/>
If yes, defer until: _____ (date)	
Company agrees to notify the Commission by	_____ (date)
of the intended date of announcement of the product so that the grant can be issued on that date.	
Transition Rules Request per 15.37?	yes <input type="checkbox"/> no <input checked="" type="checkbox"/>
If no, assumed Part 15, Subpart B for unintentional radiators - the new 47 CFR [10-1-90 Edition] provision.	
Report prepared for:	REMOTE PLAY, INC.
Report prepared by:	Advanced Compliance Lab
Report number:	0048-110816-01-FCC



Lab Code: 200101

The test result in this report IS supported and covered by the NVLAP accreditation

Table of Contents

Report Cover Page 1

Table of Contents 2

Figures 3

1. GENERAL INFORMATION 4

1.1 Verification of Compliance 4

1.2 Equipment Modifications 5

1.3 Product Information 6

1.4 Test Methodology..... 6

1.5 Test Facility 6

1.6 Test Equipment..... 6

1.7 Statement of the Document Use..... 7

2. PRODUCT LABELING..... 8

3. SYSTEM TEST CONFIGURATION..... 9

3.1 Justification 9

3.2 Special Accessories 9

3.3 Configuration of Tested System 9

4. SYSTEM SCHEMATICS 13

5. RADIATED EMISSION DATA 14

5.1 Field Strength Calculation..... 14

5.2 Test Methods and Conditions..... 14

5.3 Test Data 14

6. EUT RECEIVING MODE VERIFICATION 19

7. PHOTOS OF TESTED EUT..... 20

Figures

Figure 2.1 FCC ID Label..... 8

Figure 2.2 Location of Label on Back of the EUT..... 8

Figure 3.1 Radiated Test Setup, Position 1 10

Figure 3.2 Radiated Test Setup, Position 2 11

Figure 3.3 Radiated Test Setup, Position 3 12

Figure 4.1 EUT Schematics..... 13

Figure 7.1 Front View 21

Figure 7.2 Back View 22

Figure 7.3 Inside View..... 23

Figure 7.4 PCB Component View..... 24

Figure 7.5 PCB Foil View..... 25

1. GENERAL INFORMATION

1.1 Verification of Compliance

EUT: HYGIENE TAG

Model: IT-753/IT-754

Applicant: REMOTE PLAY, INC.

Test Type: FCC Part 15C Sec. 15.249 CERTIFICATION

Result: PASS

Tested by: ADVANCED COMPLIANCE LABORATORY


Test Date: August 16 - August 31, 2011

Report Number: 0048-110816-01-FCC

The above equipment was tested by Compliance Laboratory, Advanced Technologies, Inc. for compliance with the requirement set forth in the FCC rules and regulations Part 15 subpart C. This said equipment in the configuration described in the report, shows the maximum emission levels emanating from equipment are within the compliance requirements.

The estimated uncertainty of the test result is given as following. The method of uncertainty calculation is provided in Advanced Compliance Lab. Doc. No. 0048-01-01.

	Prob. Dist.	Uncertainty(dB)	Uncertainty(dB)	Uncertainty(dB)
		30-1000MHz	1-6.5GHz	Conducted
Combined Std. Uncertainty u_c	norm.	± 2.36	± 2.99	± 1.83



Wei Li
Lab Manager
Advanced Compliance Lab

Date August 31, 2011

1.2 Equipment Modifications

N/A

1.3 Product Information

System Configuration

ITEM	DESCRIPTION	FCC ID	CABLE
Product	HYGIENE TAG ⁽¹⁾	ST2-2X75Y	
Housing	PLASTICS		
Power Supply	3V DC Battery		
Operation Freq.	904MHz ~ 926MHz		
Receiver	2X75Y(RX)	Verification	

(1) EUT submitted for grant.

1.4 Test Methodology

Radiated tests were performed according to the procedures in ANSI C63.4-2003 at an antenna to EUT distance of 3 meters.

1.5 Test Facility

The open area test site and conducted measurement facility used to collect the radiated and conducted data are located at Hillsborough, New Jersey. This site has been accepted by FCC to perform measurements under Part 15 or 18 in a letter dated May 19, 1997 (Refer to: 31040/PRV 1300F2). The NVLAP Lab code for accreditation of FCC EMC Test Method is: 200101-0.

1.6 Test Equipment

Manufacture	Model	Serial No.	Description	Cal Due dd/mm/yy
Hewlett-Packard	HP8546A	3448A0029 0	EMI Receiver	25/09/11
R&S	ESPI	100018	EMI Test Receiver	25/08/12
EMCO	3104C	9307-4396	20-300MHz Biconical Antenna	19/10/11
EMCO	3146	9008-2860	200-1000MHz Log-Periodic Antenna	19/10/11
Fischer Custom	LISN-2	900-4-0008	Line Impedance Stabilization Networks	05/10/11
Fischer Custom	LISN-2	900-4-0009	Line Impedance Stabilization Networks	18/10/11
EMCO	3115	4945	Double Ridge Guide Horn Antenna	17/10/11

All Test Equipment Used are Calibrated Traceable to NIST Standards.

1.7 Statement for the Document Use

This report shall not be reproduced except in full, without the written approval of the laboratory. And this report must not be used by the client to claim product endorsement by NVLAP or any agency of the U.S. Government.

2. PRODUCT LABELING

FCC ID: ST2-2X75Y

This device complies with part 15 of the FCC Rules. Operating is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

**Figure 2.1 FCC ID Label
(Only FCC ID shown on EUT)**



Figure 2.2 FCC Label Location (back of EUT)

3. SYSTEM TEST CONFIGURATION

3.1 Justification

The system was configured for testing in a typical fashion (as a customer would normally use it). And its antenna was permanently attached to the EUT with max length, 3”.

Testing was performed as EUT was continuously operated at the following frequency channels:

Low=904MHz, Middle= 914MHz, High=926MHz.

Fresh external battery was used for extended operating time.

3.2 Special Accessories

N/A

3.3 Configuration of Tested System

Figure 3.1 to Figure 3.3 illustrate this system, which is tested standing along.



Figure 3.1 Radiated Test Setup, position 1



Figure 3.2 Radiated Test Setup, position 2



Figure 3.3 Radiated Test Setup, position 3

4. SYSTEM SCHEMATICS

See Attachment.

Figure 4.1 System Schematics

5. RADIATED EMISSION DATA

5.1 Field Strength Calculation

The corrected field strength is automatically calculated by EMI Receiver using following:

$$FS = RA + AF + CF + AG$$

where FS: Corrected Field Strength in dB μ V/m

RA: Amplitude of EMI Receiver before correction in dB μ V

AF: Antenna Factor in dB/m

CF: Cable Attenuation Factor in dB

AG: Built-in Preamplifier Gain in dB (Stored in receiver as part of the calibration data)

*THE "DUTY CYCLE CORRECTION FACTOR" FOR SPURIOUS RADIATED EMISSIONS IS;
20 log * (4 ms / 100 ms) = -28 dB, WHICH WAS USED TO CORRECT THE AVERAGE RADIATED
EMISSION READINGS.*

5.2 Test Methods and Conditions

The initial step in collecting radiated data is a EMI Receiver scan of the measurement range below 30MHz using peak detector and 9KHz IF bandwidth / 30KHz video bandwidth. For the range 30MHz - 1GHz, 100KHz IF bandwidth / 100KHz video bandwidth are used. Both bandwidths are 1MHz for above 1GHz measurement. Up to 10th harmonics were investigated.

5.3 Test Data

The following data lists the significant emission frequencies, polarity and position, peak reading of the EMI Receiver, the FCC limit, and the difference between the peak reading and the limit. Explanation of the correction and calculation are given in section 5.1.

Test Personnel: _____



Typed/Printed Name: Edward Lee

Date: August 31, 2011



Radiated Test Data (CH-904MHz/914MHz/926MHz)


Frequency (MHz)	Polarity (V,H) Position (X,Y,Z)	Antenna Height (m)	Azimuth (Degree)	Reading at 3m (2) (dBuV/m)	Calculated Avg. Reading After Correction (dBuV/m)	FCC 3m Limit (1) (dBuV/m)	Difference (dBuV/m)
904	V/X	1.0	090	88.9	60.9	94	-33.1
1808	V/X	1.5	180	54.7	26.7	54	-27.3
2712	V/X	1.5	090	45.1	17.1	54	-36.9
904	H/X	1.0	135	90.7	62.7	94	-31.3
1808	H/X	1.0	135	58.2	30.2	54	-23.8
2712	H/X	1.0	135	56.3	28.3	54	-25.7
914	V/X	1.0	045	84.8	56.8	94	-37.2
1828	V/X	1.2	090	58.9	30.9	54	-23.1
2742	V/X	1.2	090	44.0	16	54	-38
914	H/X	1.0	330	92.5	64.5	94	-29.5
1828	H/X	1.0	000	58.2	30.2	54	-23.8
2742	H/X	1.0	180	52.0	24	54	-30
926	V/X	1.0	270	79.9	51.9	94	-42.1
1852	V/X	1.0	330	54.1	26.1	54	-27.9
2778	V/X	1.0	090	42.5	14.5	54	-39.5
926	H/X	1.0	045	86.9	58.9	94	-35.1
1852	H/X	1.5	235	56.1	28.1	54	-25.9
2778	H/X	1.5	235	43.4	15.4	54	-38.6
904	V/Y	1.0	480	87.2	59.2	94	-34.8
1808	V/Y	1.5	090	55.7	27.7	54	-26.3
2712	V/Y	1.5	090	49.8	21.8	54	-32.2
904	H/Y	1.0	135	91.0	63	94	-31
1808	H/Y	1.0	330	56.8	28.8	54	-25.2
2712	H/Y	1.0	330	56.3	28.3	54	-25.7
914	V/Y	1.0	330	89.4	61.4	94	-32.6
1828	V/Y	1.2	090	60.1	32.1	54	-21.9
2742	V/Y	1.0	090	48.6	20.6	54	-33.4
914	H/Y	1.0	000	91.9	63.9	94	-30.1
1828	H/Y	1.0	180	56.7	28.7	54	-25.3
2742	H/Y	1.0	180	55.6	27.6	54	-26.4

926	V/Y	1.1	045	81.1	53.1	94	-40.9
1852	V/Y	1.0	090	59.6	31.6	54	-22.4
2778	V/Y	1.0	090	44.7	16.7	54	-37.3
926	H/Y	1.0	245	86.5	58.5	94	-35.5
1852	H/Y	1.5	135	53.5	25.5	54	-28.5
2778	H/Y	1.5	180	42.2	14.2	54	-39.8
904	V/Z	1.0	325	92.5	64.5	94	-29.5
1808	V/Z	1.2	090	58.2	30.2	54	-23.8
2712	V/Z	1.2	210	53.0	25	54	-29
904	H/Z	1.0	090	87.9	59.9	94	-34.1
1808	H/Z	1.5	000	54.2	26.2	54	-27.8
2712	H/Z	1.5	000	48.5	20.5	54	-33.5
914	V/Z	1.0	330	92.5	64.5	94	-29.5
1828	V/Z	1.0	180	57.1	29.1	54	-24.9
2742	V/Z	1.0	090	46.4	18.4	54	-35.6
914	H/Z	1.0	045	87.1	59.1	94	-34.9
1828	H/Z	1.0	090	55.8	27.8	54	-26.2
2742	H/Z	1.0	180	47.6	19.6	54	-34.4
926	V/Z	1.1	270	89.4	61.4	94	-32.6
1852	V/Z	1.0	090	57.4	29.4	54	-24.6
2778	V/Z	1.0	135	41.9	13.9	54	-40.1
926	H/Z	1.0	090	82.9	54.9	94	-39.1
1852	H/Z	1.5	090	54.0	26	54	-28
2778	H/Z	1.5	330	42.6	14.6	54	-39.4


(1) The limit for emissions within the 902-928MHz band is 50mV(94dB) per Sec. 15.249. The limit for its harmonics is 500uV (54dB). Other spurious emissions shall be lower than either its fundamental by 50dB or the limit defined in Sec. 15.209, whichever is higher.

(2) If each peak reading is less than the FCC average limit, it'll be not necessary to show the measured/ calculated average reading.





20dB Bandwidth Plot



Duty Cycle Plot

6. EUT RECEIVING MODE VERIFICATION

Radiated Test Data for Receiving Mode (worst case: Y-position)

Frequency (MHz)	Polarity (H or V)	Antenna Height (m)	Azimuth (Degree)	Peak Reading at 3m(2) (dBuV/m)	FCC 3m Limit(1) (dBuV/m)	Difference (dBuV/m)
38.9	H	1.4	090	30.6	40.0	-9.4
53.0	H	1.4	090	28.1	40.0	-11.9
159.2	H	1.4	235	33.8	43.5	-9.7
312	H	1.0	180	36.1	46.5	-10.4
334	H	1.0	180	33.2	46.5	-13.3
366	H	1.0	235	36.4	46.5	-10.1
37.2	V	1.1	045	31.3	40.0	-8.7
49.6	V	1.1	090	29.2	40.0	-10.8
95.5	V	1.1	045	30.0	43.5	-13.5
153.7	V	1.1	090	34.5	43.5	-9.0
334	V	1.0	180	34.0	46.5	-12.5
416	V	1.0	180	34.5	46.5	-12
632	V	1.0	235	36.7	46.5	-9.8

(1) Receiving mode spurious emissions shall be lower than the limit defined in Sec. 15.209.

(2) If each peak reading is less than the FCC QP or average limit, it'll be not necessary to show the measured/ calculated QP or average reading.

7. PHOTOS OF TESTED EUT

The following photos show the inside details of the EUT.