

Table of Contents

- Report Cover Page 1**
- Table of Contents 2**
- Figures 3**

- 1. GENERAL INFORMATION 4
 - 1.1 Verification of Compliance 4
 - 1.2 Equipment Modifications..... 5
 - 1.3 Product Information 6
 - 1.4 Test Methodology 6
 - 1.5 Test Facility 6
 - 1.6 Test Equipment 6
 - 1.7 Statement for the Document Use 7
- 2. PRODUCT LABELING 8
- 3. SYSTEM TEST CONFIGURATION 9
 - 3.1 Justification 9
 - 3.2 Special Accessories 9
 - 3.3 Configuration of Tested System..... 9
- 4. SYSTEM SCHEMATICS 15
- 5. RADIATED EMISSION DATA 16
 - 5.1 Field Strength Calculation 16
 - 5.2 Test Methods and Conditions 16
 - 5.3 Test Data 16
- 6. EUT RECEIVING MODE VERIFICATION 22
- 7. PHOTOS OF TESTED EUT 22

Figures

Figure 2.1 FCC/IC ID Label 8

Figure 2.2 Location of Label 8

Figure 3.1 Radiated Test Setup..... 10

Figure 4.1 EUT Schematics..... 12

Figure 7.1 Front View 21

Figure 7.2 Back View 22

Figure 7.3 Inside View..... 23

Figure 7.4 PCB Component Side View..... 24

Figure 7.5 PCB Foil Side View..... 25

1. GENERAL INFORMATION


1.1 Verification of Compliance

EUT: PATIENT TAG
Model: IT-723E
Applicant: CENTRAK, INC.
Test Type: FCC Part 15.249 &
IC RSS-210 (Issue 8) A2.9 & RSS-Gen (Issue 3)
Result: PASS
Tested by: ADVANCED COMPLIANCE LABORATORY
Test Date: August 06, 2013
Report Number: 0048-130729-01

The above equipment was tested by Compliance Laboratory, Advanced Technologies, Inc. for compliance with the requirement set forth in the FCC rules and regulations Part 15 subpart C. This said equipment in the configuration described in the report, shows the maximum emission levels emanating from equipment are within the compliance requirements.

The estimated uncertainty of the test result is given as following. The method of uncertainty calculation is provided in Advanced Compliance Lab. Doc. No. 0048-01-01.

	Prob. Dist.	Uncertainty(dB)	Uncertainty(dB)	Uncertainty(dB)
		30-1000MHz	1-6.5GHz	Conducted
Combined Std. Uncertainty u_c	norm.	± 2.36	± 2.99	± 1.83



Wei Li
Lab Manager
Advanced Compliance Lab

Date August 06, 2013

1.2 Equipment Modifications

N/A

1.3 Product Information

System Configuration

ITEM	DESCRIPTION	FCC/IC ID	CABLE
Product	PATIENT TAG IT-723E ⁽¹⁾	ST2-IT723E 6012A-IT723E	
Housing	PLASTICS		
Power Supply	3V DC Battery		
Operation Freq.	904MHz ~ 926MHz		
Receiver	IT-723E(RX)	Verification	

(1) EUT submitted for grant.

1.4 Test Methodology

Radiated tests were performed according to the procedures in ANSI C63.4-2003 at an antenna to EUT distance of 3 meters.

1.5 Test Facility

The open area test site and conducted measurement facility used to collect the radiated and conducted data are located at Hillsborough, New Jersey, USA. This site is accepted by FCC to perform measurements under Part 15 or 18 (Registration # 90601) and also designated by IC as “site IC 3130”. This site The NVLAP Lab code for accreditation of FCC EMC Test Method is: 200101-0.

1.6 Test Equipment

Manufacture	Model	Serial No.	Description	Cal Due dd/mm/yy
Hewlett-Packard	HP8546A	3448A00290	EMI Receiver	15/10/13
EMCO	3104C	9307-4396	20-300MHz Biconical Antenna	15/01/14
EMCO	3146	9008-2860	200-1000MHz Log-Periodic Antenna	15/01/14
Electro-Meterics	ALR-25M/30	289	10KHz-30MHz Active Loop Antenna	28/05/14
Fischer Custom	LISN-2	900-4-0008	Line Impedance Stabilization Networks	18/03/14
Fischer Custom	LISN-2	900-4-0009	Line Impedance Stabilization Networks	24/03/14
EMCO	3115	4945	Double Ridge Guide Horn Antenna	22/01/14

All Test Equipment Used are Calibrated Traceable to NIST Standards.

1.7 Statement for the Document Use

This report shall not be reproduced except in full, without the written approval of the laboratory. And this report must not be used by the client to claim product endorsement by NVLAP or any agency of the U.S. & Canada Government.

3. SYSTEM TEST CONFIGURATION

3.1 Justification

The system was configured for testing in a typical fashion (as a customer would normally use it). And its antenna was permanently attached to the EUT with max length, 3”.

Testing was performed as EUT was continuously operated at the following frequency channels: Low=904MHz, Middle= 915MHz, High=926MHz.

Fresh external battery was used for extended operating time.

3.2 Special Accessories

N/A

3.3 Configuration of Tested System

Figure 3.1 to Figure 3.3 illustrate this system, which is tested standing along.









Figure 3.1 Radiated Test Setup

4. SYSTEM SCHEMATICS

See Attachment.

Figure 4.1 System Schematics

5. RADIATED EMISSION DATA

5.1 Field Strength Calculation

The corrected field strength is automatically calculated by EMI Receiver using following:

$$FS = RA + AF + CF + AG$$

where FS: Corrected Field Strength in dB μ V/m

RA: Amplitude of EMI Receiver before correction in dB μ V

AF: Antenna Factor in dB/m

CF: Cable Attenuation Factor in dB

AG: Built-in Preamplifier Gain in dB (Stored in receiver as part of the calibration data)

THE "DUTY CYCLE CORRECTION FACTOR" FOR SPURIOUS RADIATED EMISSIONS IS;
 $20 \log * (4 \text{ ms} / 100 \text{ ms}) = -28 \text{ dB}$, WHICH WAS USED TO CORRECT THE AVERAGE RADIATED EMISSION READINGS.

5.2 Test Methods and Conditions

The initial step in collecting radiated data is a EMI Receiver scan of the measurement range below 30MHz using peak detector and 9KHz IF bandwidth / 30KHz video bandwidth. For the range 30MHz - 1GHz, 100KHz IF bandwidth / 100KHz video bandwidth are used. Both bandwidths are 1MHz for above 1GHz measurement. Up to 10th harmonics were investigated.

5.3 Test Data

The following data lists the significant emission frequencies, polarity and position, peak reading of the EMI Receiver, the FCC limit, and the difference between the peak reading and the limit. Explanation of the correction and calculation are given in section 5.1.

Test Personnel: _____



Typed/Printed Name: Edward Lee

Date: August 06, 2013

Radiated Test Data (CH-904MHz/915MHz/926MHz)

Frequency (MHz)	Polarity (V,H) Position (X,Y,Z)	Antenna Height (m)	Azimuth (Degree)	Peak Reading at 3m (2) (dBuV/m)	Peak Reading After Correction (dBuV/m)	FCC/IC 3m Limit (1) (dBuV/m)	Difference (dBuV/m)
904	V/X	1.1	045	81.1	81.1	94	-12.9
1808	V/X	1.1	330	62.5	34.5	54	-19.5
2712	V/X	1.1	000	61.0	33.0	54	-21.0
904	H/X	1.0	315	92.0	92.0	94	-2.0
1808	H/X	1.0	090	61.5	33.5	54	-20.5
2712	H/X	1.0	150	56.3	28.3	54	-25.7
915	V/X	1.1	000	79.2	79.2	94	-14.8
1830	V/X	1.1	330	59.7	31.7	54	-22.3
2745	V/X	1.1	000	59.6	31.6	54	-22.4
915	H/X	1.0	270	92.2	92.2	94	-1.8
1828	H/X	1.0	090	64.1	36.1	54	-17.9
2745	H/X	1.0	135	55.7	27.7	54	-26.3
926	V/X	1.1	000	79.0	79.0	94	-15
1852	V/X	1.1	330	61.1	33.1	54	-20.9
2778	V/X	1.1	045	59.7	31.7	54	-22.3
926	H/X	1.0	235	83.0	83.0	94	-11
1852	H/X	1.0	090	63.0	35.0	54	-19
2778	H/X	1.0	180	55.5	27.5	54	-26.5
904	V/Y	1.1	135	80.7	80.7	94	-13.3
1808	V/Y	1.1	180	59.1	31.1	54	-22.9
2712	V/Y	1.1	180	57.5	29.5	54	-24.5
904	H/Y	1.0	090	90.3	90.3	94	-3.7
1808	H/Y	1.0	270	58.8	30.8	54	-23.2
2712	H/Y	1.0	135	57.9	29.9	54	-24.1
915	V/Y	1.1	135	82.9	82.9	94	-11.1
1830	V/Y	1.1	045	60.8	32.8	54	-21.2
2745	V/Y	1.1	180	56.9	28.9	54	-25.1
915	H/Y	1.0	045	89.6	89.6	94	-4.4
1828	H/Y	1.0	270	57.0	29.0	54	-25.0
2745	H/Y	1.0	090	58.2	30.2	54	-23.8
926	V/Y	1.1	135	83.1	83.1	94	-10.9

1852	V/Y	1.1	180	59.5	31.5	54	-22.5
2778	V/Y	1.1	235	58.9	30.9	54	-23.1
926	H/Y	1.0	045	89.0	89.0	94	-5.0
1852	H/Y	1.0	330	58.0	30.0	54	-24
2778	H/Y	1.0	135	57.5	29.5	54	-24.5
904	V/Z	1.1	180	84.9	84.9	94	-9.1
1808	V/Z	1.1	235	68.3	40.3	54	-13.7
2712	V/Z	1.1	270	62.5	34.5	54	-19.5
904	H/Z	1.0	135	87.8	87.8	94	-6.2
1808	H/Z	1.0	170	56.0	28.0	54	-26.0
2712	H/Z	1.0	180	52.1	24.1	54	-29.9
915	V/Z	1.1	180	84.0	84.0	94	-10.0
1830	V/Z	1.1	270	69.2	41.2	54	-12.8
2745	V/Z	1.1	250	61.3	33.3	54	-20.7
915	H/Z	1.0	135	87.1	87.1	94	-6.9
1830	H/Z	1.0	135	56.7	28.7	54	-25.3
2745	H/Z	1.0	235	54.7	26.7	54	-27.3
926	V/Z	1.1	270	83.3	83.3	94	-10.7
1852	V/Z	1.1	090	70.1	42.1	54	-11.9
2778	V/Z	1.1	135	61.8	33.8	54	-20.2
926	H/Z	1.0	090	86.5	86.5	94	-7.5
1852	H/Z	1.0	180	57.7	29.7	54	-24.3
2778	H/Z	1.0	235	54.0	26.0	54	-28.0

(1) The limit for emissions within the 902-928MHz band is 50mV(94dB) per FCC Sec. 15.249 & IC RSS-210 Annex 2.9. The limit for its harmonics is 500uV (54dB). Other spurious emissions shall be lower than either its fundamental by 50dB or the limit defined in Sec. 15.209, whichever is higher.

(2) If the peak reading is less than the FCC/IC quasi-peak or average limit, it'll be not necessary to show the measured/ calculated quasi-peak or average reading.

Other Spurious outside of the band 902-928MHz

Frequency (MHz)	Polarity (V,H) Position (X,Y,Z)	Antenna Height (m)	Azimuth (Degree)	Peak Reading at 3m (2) (dBuV/m)	Peak Reading After Correction (dBuV/m)	FCC/IC 3m Limit (1) (dBuV/m)	Difference (dBuV/m)
52.0	H/X	1.4	045	30.0		40.0	-10
78.0	H/X	1.3	090	32.2		40.0	-7.8
130.0	H/X	1.2	180	29.7		43.5	-13.8
182.0	H/X	1.0	135	28.5		43.5	-15
52.0	V/Z	1.1	200	31.3		40.0	-8.7
78.0	V/Z	1.1	000	32.0		40.0	-8
130.0	V/Z	1.1	235	29.7		43.5	-13.8
182.0	V/Z	1.1	190	28.2		43.5	-15.3
312.0	V/Z	1.2	200	30.4		46.5	-16.1
416.0	V/Z	1.0	240	31.2		46.5	-15.3

Comparing to the limit defined in FCC Sec. 15.209/IC RSS-Gen, emissions below the limit by 20dB were not recorded.

