

Report Number: F690501/RF-RTL004066-1 Page: 37 of 38

# 8. RF Exposure Evaluation

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in § 1.1307(b)

### LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (MHz)	Electric Field Strength(V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm²)	Average Time		
(A) Limits for Occupational /Control Exposures						
300 – 1 500			F/300	6		
1 500 – 100 000			5	6		
(B) Limits for General Population/Uncontrol Exposures						
300 – 1500			F/1500	6		
<u>1 500 – 100 000</u>	=	<u></u>	<u>1</u>	<u>30</u>		

## 8.1 Friis transmission formula : Pd = (Pout\*G)/(4\*pi\*R²)

Where

Pd = power density in mW/cm<sup>2</sup>
Pout = output power to antenna in mW
G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

Pd the limit of MPE, 1 mW/cm<sup>2</sup>. If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.



Report Number: F690501/RF-RTL004066-1 Page: 38 of 38

### 8.2 Test Result of RF Exposure Evaluation

Test Item : RF Exposure Evaluation Data

Test Mode : Normal Operation

## 8.2.1 Output Power into Antenna & RF Exposure Evaluation Distance

### **PCS** band

### **Uplink mode**

Channel	Frequency (쌘)	Output Power to Antenna (dB m)	Antenna Gain (dB i)	R (cm)
Low	1 851.25	29.29	9	23.174
Mid	1 880.00	30.29	9	26.002
High	1 908.75	29.87	9	24.775

#### **Downlink mode**

Channel	Frequency (쌘)	Output Power to Antenna (dB m)	Antenna Gain (dB i)	R (cm)
Low	1 931.25	30.00	4.5	14.980
Mid	1 960.00	30.56	4.5	15.977
High	1 988.75	30.47	4.5	15.813