

Report Number: F690501/RF-RTL003363 Page: 40 of 41

8. RF Exposure Evaluation

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in § 1.1307(b)

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (MHz)	Electric Field Strength(V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time			
(A) Limits for Occupational /Control Exposures							
300 – 1500			F/300	6			
1500 - 100000			5	6			
(B) Limits for General Population/Uncontrol Exposures							
300 – 1500			F/1500	6			
<u>1500 - 100000</u>			<u>1</u>	<u>30</u>			

8.1 Friis transmission formula : $Pd = (Pout*G)/(4*pi*R^2)$

Where

 $Pd = power density in mW/cm^2$

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

Pd the limit of MPE, 1 mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.



Report Number: F690501/RF-RTL003363 Page: 41 of 41

8.2 Test Result of RF Exposure Evaluation

Test Item : RF Exposure Evaluation Data

Test Mode : Normal Operation

8.2.1 Output Power into Antenna & RF Exposure Evaluation Distance

Antenna: 8 dBi(Patch Antenna)

Test Mode: Down link_64QAM 3/4

Channel	Frequency (MHz)	Peak output power (dBm)	Antenna gain (dBi)	Power density at 20cm (mW/cm²)	Limit (mW/cm ²)
Low	2508.5	23.78	8	0.29988	
Middle	2630.5	24.64	8	0.36555	1
High	2683.5	23.39	8	0.27413	

Test Mode Mode: Up link_16QAM 3/4

Channel	Frequency (MHz)	Peak output power (dBm)	Antenna gain (dBi)	Power density at 20cm (mW/cm²)	Limit (mW/cm ²)
Low	2508.5	23.78	8	0.29988	
Middle	2630.5	24.40	8	0.34590	1
High	2683.5	23.45	8	0.27794	