

FCC 47 CFR MPE REPORT

Klipsch L.L.C.

Klipsch Heritage Wireless TableTop Bluetooth Small

Model Number: the One II Phono

FCC ID: STI-THEONEIIP

| | |
|---------------|---|
| Prepared for: | Klipsch L.L.C. |
| | 3502 Woodview Trace, Suite 200, Indianapolis, IN 46268, USA |
| | |
| Prepared By: | EST Technology Co., Ltd. |
| | Chilingxiang, Qishantou, Santun, Houjie, Dongguan, Guangdong, China |
| | Tel: 86-769-83081888-808 |

| | |
|-----------------|-----------------------|
| Report Number: | ESTE-R2006093 |
| Date of Test: | Jun. 04~Jun. 13, 2020 |
| Date of Report: | Jun. 17, 2020 |

Maximum Permissible Exposure

1. Applicable Standards

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 0.2m normally can be maintained between the user and the device.

1.1. Limits for Maximum Permissible Exposure (MPE)

(a) Limits for Occupational/Controlled Exposure

| Frequency Range (MHz) | Electric Field Strength (E) (V/m) | Magnetic Field Strength (H) (A/m) | Power Density (S) (mW/cm ²) | Averaging Times E ² , H ² or S (minutes) |
|-----------------------|-----------------------------------|-----------------------------------|---|--|
| 0.3-3.0 | 614 | 1.63 | (100)* | 6 |
| 3.0-30 | 1842/f | 4.89/f | (900/f)* | 6 |
| 30-300 | 61.4 | 0.163 | 1.0 | 6 |
| 300-1500 | | | F/300 | 6 |
| 1500-10000 | | | 5 | 6 |

(b) Limits for General Population / Uncontrolled Exposure

| Frequency Range (MHz) | Electric Field Strength (E) (V/m) | Magnetic Field Strength (H) (A/m) | Power Density (S) (mW/cm ²) | Averaging Times E ² , H ² or S (minutes) |
|-----------------------|-----------------------------------|-----------------------------------|---|--|
| 0.3-1.34 | 614 | 1.63 | (100)* | 30 |
| 1.34-30 | 824/f | 2.19/f | (180/f)* | 30 |
| 30-300 | 27.5 | 0.073 | 0.2 | 30 |
| 300-1500 | | | F/1500 | 30 |
| 1500-10000 | | | 1.0 | 30 |

Note: f=frequency in MHz; *Plane-wave equivalent power density

1.2. MPE Calculation Method

$$E \text{ (V/m)} = \frac{\sqrt{30 \times P \times G}}{d} \quad \text{Power Density: Pd (W/m}^2\text{)} = \frac{E^2}{377}$$

E = Electric Field (V/m)

P = Peak RF output Power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 \times P \times G}{377 \times d^2}$$

From the peak EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the gain of the used antenna, the RF power density can be obtained

2. Conducted Power Result

| Mode | Frequency (MHz) | Peak output power (dBm) | Peak output power (mW) | Target power (dBm) | Antenna gain | |
|--------|-----------------|-------------------------|------------------------|--------------------|--------------|----------|
| | | | | | (dBi) | (Linear) |
| GFSK | 2402 | 2.72 | 1.871 | 2±1 | 0.5 | 1.122 |
| | 2441 | 2.86 | 1.932 | 2±1 | 0.5 | 1.122 |
| | 2480 | 1.66 | 1.466 | 1±1 | 0.5 | 1.122 |
| 8-DPSK | 2402 | 0.78 | 1.197 | 0±1 | 0.5 | 1.122 |
| | 2441 | 0.89 | 1.227 | 0±1 | 0.5 | 1.122 |
| | 2480 | -0.35 | 0.923 | -1±1 | 0.5 | 1.122 |
| BLE | 2402 | 0.92 | 1.236 | 0±1 | 0.5 | 1.122 |
| | 2440 | 1.09 | 1.285 | 1±1 | 0.5 | 1.122 |
| | 2480 | 0.07 | 1.016 | 0±1 | 0.5 | 1.122 |

3. Calculated Result and Limit

| Mode | Target power (dBm) | Antenna gain | | Power Density (S) (mW/cm ²) | Limited of Power Density (S) (mW/cm ²) | Test Result |
|--------|--------------------|--------------|----------|---|--|-------------|
| | | (dBi) | (Linear) | | | |
| GFSK | 3 | 0.5 | 1.122 | 0.00045 | 1 | Compiles |
| 8-DPSK | 1 | 0.5 | 1.122 | 0.00028 | 1 | Compiles |
| BLE | 2 | 0.5 | 1.122 | 0.00035 | 1 | Compiles |

End of Test Report