

FCC PART 15C TEST REPORT FOR CERTIFICATION
On Behalf of

Klipsch L.L.C.

Klipsch Heritage Wireless TableTop Bluetooth Small

Model Number: the One II Phono

FCC ID: STI-THEONEIIP

Prepared for:	Klipsch L.L.C.
	3502 Woodview Trace, Suite 200, Indianapolis, IN 46268, USA
Prepared By:	EST Technology Co., Ltd.
	Chilingxiang, Qishantou, Santun, Houjie, Dongguan, Guangdong, China
	Tel: 86-769-83081888-808




Report Number:	ESTE-R2006092
Date of Test:	Jun. 04~Jun. 13, 2020
Date of Report:	Jun. 17, 2020

TABLE OF CONTENTS

Description	Page
TEST REPORT VERIFICATION	3
1. GENERAL INFORMATION.....	5
1.1. Description of Device (EUT)	5
1.2. Antenna Information	5
2. SUMMARY OF TEST	6
2.1. Summary of test result.....	6
2.2. Test Facilities.....	7
2.3. Measurement uncertainty	8
2.4. Assistant equipment used for test.....	8
2.5. Block Diagram.....	8
2.6. Test Mode.....	9
2.7. Power Setting of Test Software	9
2.8. Duty Cycle.....	10
2.9. Channel List.....	11
2.10. Test Equipment List	12
3. 6DB BANDWIDTH	13
3.1. Limit	13
3.2. Test Setup	13
3.3. Spectrum Analyzer Setting.....	13
3.4. Test Procedure	13
3.5. Test Result	14
4. MAXIMUM PEAK OUTPUT POWER	16
4.1. Limit	16
4.2. Test Setup	16
4.3. Spectrum Analyzer Setting.....	16
4.4. Test Procedure	16
4.5. Test Result	17
5. POWER SPECTRAL DENSITY.....	19
5.1. Limit	19
5.2. Test Setup	19
5.3. Spectrum Analyzer Setting.....	19
5.4. Test Procedure	19
5.5. Test Result	20
6. CONDUCTED BAND EDGE	22
6.1. Limit	22
6.2. Test Setup	22
6.3. Spectrum Analyzer Setting.....	22
6.4. Test Procedure	22
6.5. Test Result	23
7. CONDUCTED SPURIOUS EMISSIONS	24
7.1. Limit	24
7.2. Test Setup	24
7.3. Spectrum Analyzer Setting.....	24
7.4. Test Procedure	24

- 7.5. Test Result 25
- 8. RADIATED SPURIOUS EMISSIONS AND BAND EDGE 27
 - 8.1. Limit 27
 - 8.2. Test Setup 28
 - 8.3. Spectrum Analyzer Setting 29
 - 8.4. Test Procedure 30
 - 8.5. Test Result 31
- 9. AC POWER LINE CONDUCTED EMISSIONS 43
 - 9.1. Limit 43
 - 9.2. Test Setup 43
 - 9.3. Spectrum Analyzer Setting 43
 - 9.4. Test Procedure 43
 - 9.5. Test Result 44
- 10. ANTENNA REQUIREMENTS 48
 - 10.1. Limit 48
 - 10.2. Test Result 48
- 11. TEST SETUP PHOTO 49
- 12. EUT PHOTO 51

EST Technology Co., Ltd.

Applicant:	Klipsch L.L.C.		
Address:	3502 Woodview Trace, Suite 200, Indianapolis, IN 46268, USA		
Manufacturer:	Klipsch L.L.C.		
Address:	3502 Woodview Trace, Suite 200, Indianapolis, IN 46268, USA		
E.U.T:	Klipsch Heritage Wireless TableTop Bluetooth Small		
Model Number:	the One II Phono		
Power Supply:	AC 100-240V, 50/60Hz		
Trade Name:	Klipsch	Serial No.:	-----
Date of Receipt:	Jun. 04, 2020	Date of Test:	Jun. 04~Jun. 13, 2020
Test Specification:	FCC Part 15 Subpart C (15.247) ANSI C63.10:2013 FCC KDB 558074 D01 15.247 Meas Guidance v05r02		
Test Result:	<p>The device described above is tested by EST Technology Co., Ltd. The measurement results were contained in this test report and EST Technology Co., Ltd. was assumed full responsibility for the accuracy and completeness of these measurements. Also, this report shows that the EUT to be technically compliance with the FCC Rules and Regulations Part 15 Subpart C requirements.</p> <p style="text-align: center;">This report applies to above tested sample only and shall not be reproduced in part without written approval of EST Technology Co., Ltd.</p>		
Prepared by:	Reviewed by:	Date: Jun. 03, 2020 Approved by:	
 Ring Wang / Assistant	 Seven Wang / Engineer	 Iceman Hu / Manager	
Other Aspects:	None.		
Abbreviations: OK/P=passed fail/F=failed n.a/N=not applicable E.U.T=equipment under tested			
This test report is based on a single evaluation of one sample of above mentioned products ,It is not permitted to be duplicated in extracts without written approval of EST Technology Co., Ltd.			

1. GENERAL INFORMATION

1.1. Description of Device (EUT)

Product Name	:	Klipsch Heritage Wireless TableTop Bluetooth Small
Model Number	:	the One II Phono
Software Version	:	N/A
Hardware Version	:	N/A
Operation frequency	:	2402MHz~2480MHz
Number of channel	:	40
Max Output Power (PEAK)	:	1.09dBm
Modulation Type	:	GFSK
Sample Type	:	Prototype production

Note:

For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.

1.2. Antenna Information

Ant No.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)
1	N/A	N/A	PCB	N/A	0.5

2. SUMMARY OF TEST

2.1. Summary of test result

Report Section	Description of Test Item	FCC Standard Section	Results
3	6dB Bandwidth	15.247(a)(2)	PASS
4	Maximum Peak Output Power	15.247(b)(3)	PASS
5	Power Spectral Density	15.247(e)	PASS
6	Conducted Band Edge	15.247(d)	PASS
7	Conducted Spurious Emissions	15.247(d)	PASS
8	Radiated Spurious Emissions and Band Edge	15.205 15.209 15.247(d)	PASS
9	AC Power Line Conducted Emissions	15.207	PASS
10	Antenna Requirement	15.203	PASS

Note:

(1) "N/A" denotes test is not applicable in this test report

2.2. Test Facilities

EMC Lab : Certificated by CNAS, CHINA
Registration No.: L5288
Date of registration: November 13, 2017

Certificated by FCC, USA
Designation Number: CN1215
Test Firm Registration Number: 722932
Date of registration: November 21, 2017

Certificated by A2LA, USA
Registration No.: 4366.01
Date of registration: November 07, 2017

Certificated by Industry Canada
CAB identifier No.: CN0035
Date of registration: January 04, 2019

Certificated by VCCI, Japan
Registration No.: R-13663; C-14103
Date of registration: July 25, 2017
This Certificate is valid until: July 24, 2020

Certificated by TUV Rheinland, Germany
Registration No.: UA 50413872 0001
Date of registration: July 31, 2018

Certificated by TUV/PS, Shenzhen
Registration No.: SCN1017
Date of registration: January 27, 2011

Certificated by Intertek ETL SEMKO
Registration No.: 2011-RTL-L2-64
Date of registration: April 28, 2011

Certificated by Nemko, Hong Kong
Registration No.: 175193
Date of registration: May 4, 2011

Name of Firm : EST Technology Co., Ltd.

Site Location : Chilingxiang, Qishantou, Santun, Houjie, Dongguan, Guangdong, China

2.3. Measurement uncertainty

Test Item	Uncertainty
Uncertainty for Conduction emission test	±3.48dB
Uncertainty for spurious emissions test (30MHz-1GHz)	±4.60 dB(Polarize: H)
	±4.68 dB(Polarize: V)
Uncertainty for spurious emissions test (1GHz to 25GHz)	±4.96dB
Uncertainty for radio frequency	7×10^{-8}
Uncertainty for conducted RF Power	0.20dB
Uncertainty for Power density test	0.26dB

Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.


2.4. Assistant equipment used for test

Item	Equipment	Brand	Model Name/Type No.	FCC ID	Series No.
A	Adapter	DYS	DYS850-200250W-K	-	-

Item	Shielded Type	Ferrite Core	Length	Note
1	NO	NO	1.5m	DC Cable

2.5. Block Diagram

For radiated emissions test: EUT was placed on a turn table, which is 0.8 (or 1.5) meter high above ground. EUT was beset into BLE test mode by software before test.



(EUT: Klipsch Heritage Wireless TableTop Bluetooth Small)

2.6. Test Mode

The test mode was selected for the final test as listed below.

Test Item	Modulation Type	Test Channel
6dB Bandwidth	GFSK	Low/Middle/High
Maximum Peak Output Power	GFSK	Low/Middle/High
Power Spectral Density	GFSK	Low/Middle/High
Conducted Band Edge	GFSK	Low/ High
Conducted Spurious Emissions	GFSK	Low/Middle/High
Radiated Spurious Emissions(Below 1GHz)	GFSK	Low/Middle/High
Radiated Spurious Emissions(Above 1GHz)	GFSK	Low/Middle/High
Radiated Band Edge	GFSK	Low/High
AC Power Line Conducted Emissions	GFSK	Low/Middle/High

Note:

1. In radiated measurement,the EUT had been pre-scan on the positioned of each 3 axis(X,Y,Z), the worst case was found when positioned on **X-plane**.

2.7. Power Setting of Test Software


Software Name	BlueTest 3		
Frequency(MHz)	2402	2440	2480
Setting	Default	Default	Default

2.8. Duty Cycle

Temperature	23.5°C	Relative Humidity	50%	Test Voltage	120V/60Hz
Mode	Fre(MHz)	On time(ms)	Total Time(ms)	Duty Cycle	Duty Factor
GFSK	2440	0.44348	0.64638	68.61	1.64

Note:

1. If duty cycle <98 %, the conducted average output power and average power spectral density should be add duty factor.
2. If duty cycle ≥ 98 %,the EUT is consider to be transmitting continuously,the conducted average output power and average power spectral density no need to add duty factor(consider to be zero).
3. The conducted peak output power and peak power spectral density no need to consider duty factor.
4. The on-time time is transmission duration(T).



2.9. Channel List

Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)
0	2402	1	2404
2	2406	3	2408
4	2410	5	2412
6	2414	7	2416
8	2418	9	2420
10	2422	11	2424
12	2426	13	2428
14	2430	15	2432
16	2434	17	2436
18	2438	19	2440
20	2442	21	2444
22	2446	23	2448
24	2450	25	2452
26	2454	27	2456
28	2458	29	2460
30	2462	31	2464
32	2466	33	2468
34	2470	35	2472
36	2474	37	2476
38	2478	39	2480

2.10. Test Equipment List

For conducted emission test						
Equipment	Manufacturer	Model No.	Serial No.	Calibration Body	Last Cal.	Next Cal.
EMI Test Receiver	Rohde & Schwarz	ESHS30	EST-E001	LISAI	June 14,19	1 Year
Artificial Mains Network	Rohde & Schwarz	ENV216	EST-E002	LISAI	June 14,19	1 Year
Pulse Limiter	Rohde & Schwarz	ESH3-Z2	EST-E078	LISAI	June 14,19	1 Year
Test Software	Audix	e3-6.111221a	N/A	N/A	N/A	N/A

For radiated emission test(9kHz-30MHz)						
Equipment	Manufacturer	Model No.	Serial No.	Calibration Body	Last Cal.	Next Cal.
EMI Test Receiver	Rohde & Schwarz	ESR7	EST-E047	LISAI	June 14,19	1 Year
Active Loop Antenna	SCHWARZB ECK	FMZB 1519B	EST-E054	LISAI	June 14,19	1 Year
Test Software	Audix	e3-6.111221a	N/A	N/A	N/A	N/A
9kHz-30MHz Cable	N/A	EST-001	N/A	N/A	N/A	N/A

For radiated emissions test (30MHz-1000MHz)						
Equipment	Manufacturer	Model No.	Serial No.	Calibration Body	Last Cal.	Next Cal.
EMI Test Receiver	Rohde & Schwarz	ESR7	EST-E047	LISAI	June 14,19	1 Year
Bilog Antenna	Teseq	CBL 6111D	EST-E034	LISAI	June 14,19	1 Year
Test Software	Audix	e3-6.111221a	N/A	N/A	N/A	N/A
30-1000MHz Cable	N/A	EST-002	N/A	N/A	N/A	N/A

For radiated emission test(Above 1000MHz)						
Equipment	Manufacturer	Model No.	Serial No.	Calibration Body	Last Cal.	Next Cal.
Horn Antenna	SCHWARZB ECK	BBHA9120D	EST-E031	LISAI	June 14,19	1 Year
Signal Amplifier	SCHWARZB ECK	BBV9718	EST-E032	LISAI	June 14,19	1 Year
Spectrum Analyzer	Rohde & Schwarz	FSV40	EST-E069	LISAI	June 14,19	1 Year
Test Software	Audix	e3-6.111221a	N/A	N/A	N/A	N/A
Above 1GHz Cable	N/A	EST-003	N/A	N/A	N/A	N/A

For connect EUT antenna terminal test						
Equipment	Manufacturer	Model No.	Serial No.	Calibration Body	Last Cal.	Next Cal.
Spectrum Analyzer	Rohde&Schwarz	FSV40	EST-E069	LISAI	June 14,19	1 Year

3. 6DB BANDWIDTH

3.1. Limit

Systems using digital modulation techniques operate in the 2400-2483.5 MHz, the minimum 6 dB bandwidth shall be at least 500 kHz.

3.2. Test Setup



3.3. Spectrum Analyzer Setting


Spectrum Parameters	Setting
RBW	100KHz
VBW	300KHz
Span	3MHz
Sweep Time	Auto
Detector	Peak
Trace Mode	Max Hold

3.4. Test Procedure


- a. Connect EUT antenna terminal to the spectrum analyzer with RF cable.
- b. Spectrum analyzer setting parameters in accordance with section 3.3.
- c. Set the EUT transmit continuously with maximum output power.
- d. Allow trace to stabilize, use the ndB down function to measure 6dB Bandwidth.
- e. Repeat above procedures until all channels were measured.
- f. Record the results in the test report.

3.5. Test Result


Temperature	23.5 °C	Relative Humidity	50%	
Test Voltage	120V/60Hz			
Mode	Freq (MHz)	6dB Bandwidth (MHz)	6dB BW Limit (MHz)	Result
GFSK	2402	0.7033	≥0.5	PASS
	2440	0.6990	≥0.5	PASS
	2480	0.6946	≥0.5	PASS



GFSK 2440 MHz



GFSK 2480 MHz




4. MAXIMUM PEAK OUTPUT POWER

4.1. Limit

For systems using digital modulation in 2400-2483.5 MHz, the maximum peak output power is 1 Watt(30dBm).

4.2. Test Setup



4.3. Spectrum Analyzer Setting


Spectrum Parameters	Setting
RBW	1MHz
VBW	3MHz
Span	3MHz
Sweep Time	Auto
Detector	Peak
Trace Mode	Max Hold

4.4. Test Procedure


- a. Connect EUT antenna terminal to the spectrum analyzer with RF cable.
- b. Spectrum analyzer setting parameters in accordance with section 4.3.
- c. Set the EUT transmit continuously with maximum output power.
- d. Allow trace to stabilize, use the marker-to-peak function to set the marker to the peak of the emission.
- e. Repeat above procedures until all channels were measured.
- f. Record the results in the test report.

4.5. Test Result


Temperature	23.5 °C	Relative Humidity	50%	Test Voltage		120V/60Hz
Mode	Freq (MHz)	Peak Output Power		Limit		Result
		dBm	W	dBm	W	
GFSK	2402	0.92	0.0012	30.00	1.0000	PASS
	2440	1.09	0.0013	30.00	1.0000	PASS
	2480	0.07	0.0010	30.00	1.0000	PASS



GFSK 2440MHz



GFSK 2480MHz




5. POWER SPECTRAL DENSITY

5.1. Limit

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

5.2. Test Setup



5.3. Spectrum Analyzer Setting


Spectrum Parameters	Setting
RBW	3KHz
VBW	10KHz
Span	2MHz
Sweep Time	Auto
Detector	Peak
Trace Mode	Max Hold

5.4. Test Procedure


- a. Connect EUT antenna terminal to the spectrum analyzer with RF cable.
- b. Spectrum analyzer setting parameters in accordance with section 5.3.
- c. Set the EUT transmit continuously with maximum output power.
- d. Allow trace to stabilize, use the marker-to-peak function to set the marker to the peak of the emission.
- e. Repeat above procedures until all channels were measured.
- f. Record the results in the test report.

5.5. Test Result


Temperature	23.5°C	Relative Humidity	50%	Test Voltage	120V/60Hz
Mode	Freq (MHz)	Power Density (dBm/3kHz)	Limit (dBm/3kHz)	Result	
GFSK	2402	-15.15	8.00	PASS	
	2440	-14.79	8.00	PASS	
	2480	-15.81	8.00	PASS	



GFSK 2440MHz



GFSK 2480MHz



6. CONDUCTED BAND EDGE

6.1. Limit

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

6.2. Test Setup



6.3. Spectrum Analyzer Setting

Spectrum Parameters	Setting
RBW	100KHz
VBW	300KHz
Span	100MHz
Sweep Time	Auto
Detector	Peak
Trace Mode	Max Hold


6.4. Test Procedure

- a. Connect EUT antenna terminal to the spectrum analyzer with RF cable.
- b. Spectrum analyzer setting parameters in accordance with section 6.3.
- c. Set the EUT transmit continuously with maximum output power.
- d. Allow trace to stabilize, use the marker function to mark the highest emission level outside the authorized band.
- e. Repeat above procedures until all channels were measured.
- f. Record the results in the test report.


6.5. Test Result

Temperature	23.5°C	Relative Humidity	50%	Test Voltage	120V/60Hz
Result	PASS				

GFSK Low Channel



GFSK High Channel




7. CONDUCTED SPURIOUS EMISSIONS

7.1. Limit

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

7.2. Test Setup



7.3. Spectrum Analyzer Setting


Spectrum Parameters	Setting
RBW	100KHz
VBW	300KHz
Start frequency	30MHz
Stop frequency	25GHz
Sweep Time	Auto
Detector	Peak
Trace Mode	Max Hold

7.4. Test Procedure


- a. Connect EUT antenna terminal to the spectrum analyzer with RF cable.
- b. Spectrum analyzer setting parameters in accordance with section 7.3.
- c. Set the EUT transmit continuously with maximum output power.
- d. Allow trace to stabilize, use the marker function to mark the highest emission level outside the authorized band.
- e. Repeat above procedures until all channels were measured.
- f. Record the results in the test report.

7.5. Test Result


Temperature	23.5°C	Relative Humidity	50%	Test Voltage	120V/60Hz
Result	PASS				



GFSK 2440MHz



GFSK 2480MHz



8. RADIATED SPURIOUS EMISSIONS AND BAND EDGE

8.1. Limit

All the emissions appearing within 15.205 restricted frequency bands shall not exceed the limits shown in 15.209, all the other emissions shall be at least 20dB below the fundamental emissions, or comply with 15.209 limits.

15.205 Restricted frequency band

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
¹ 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2690 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	(²)

15.209 Limit


Frequency (MHz)	Field Strength(μ V/m)	Distance(m)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Note:


- (1) Emission level $\text{dB}\mu\text{V} = 20 \log \text{Emission level } \mu\text{V/m}$.
- (2) The smaller limit shall apply at the cross point between two frequency bands.
- (3) Distance is the distance in meters between the measuring instrument, antenna and the closest point of any part of the device or system.

8.2. Test Setup


9kHz~30MHz



30~1000MHz



Above 1GHz



8.3. Spectrum Analyzer Setting

For 9KHz-150KHz

Spectrum Parameters	Setting
RBW	300Hz(for Peak&AVG)/CISPR 200Hz(for QP)
VBW	300Hz(for Peak&AVG)/CISPR 200Hz(for QP)
Start frequency	9KHz
Stop frequency	150KHz
Sweep Time	Auto
Detector	PEAK/QP/AVG
Trace Mode	Max Hold

For 150KHz-30MHz

Spectrum Parameters	Setting
RBW	9KHz
VBW	9KHz
Start frequency	150KHz
Stop frequency	30MHz
Sweep Time	Auto
Detector	QP
Trace Mode	Max Hold

For 30MHz-1GHz

Spectrum Parameters	Setting
RBW	120KHz
VBW	300KHz
Start frequency	30MHz
Stop frequency	1GHz
Sweep Time	Auto
Detector	QP
Trace Mode	Max Hold

For Above 1GHz

Spectrum Parameters	Setting	
RBW	1MHz	
VBW	PEAK Measurement	
	3MHz	Duty cycle $\geq 98\%$, VBW=10Hz
		Duty cycle $< 98\%$, VBW $\geq 1/T$
Start frequency	1GHz	
Stop frequency	25GHz	
Sweep Time	Auto	
Detector	PEAK	
Trace Mode	Max Hold	

Note :

1. T is the on-time time of the duty cycle,when EUT transmit continuously with maximum output power,unit is seconds. reference section 2.8 for the on-time time.

8.4. Test Procedure

- a. EUT was placed on a turn table, which is 0.8 meter high above ground for below 1GHz test, and which is 1.5 meter high above ground for above 1GHz test.
- b. EUT is set 3 meters away from the receiving antenna, which is mounted on a antenna tower.
- c. Set the EUT transmit continuously with maximum output power.
- d. The turn table can rotate 360 degrees to determine the position of the maximum emission level.
- e. The antenna can be moved up and down between 1 meter and 4 meters to find out the maximum emission level. Both horizontal and vertical polarization of the antenna are set on test.
- f. Spectrum analyzer setting parameters in accordance with section 8.3.
- g. Repeat above procedures until all channels were measured.
- h. Record the results in the test report.

Note:


1. For emissions above 1GHz, if peak level comply with average limit, then the average level is deemed to comply with average limit.
2. The frequency 2402MHz ,2440MHz and 2480MHz is fundamental frequency which no limit, the limit on plots is automatically generated by the software, it's not fundamental limit, we can't remove it.

8.5. Test Result

Radiated Emissions Below 1GHz

EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878



Site no. : 1# 966 Chamber Data no. : 23
 Dis. / Ant. : 3m 37062 Ant. pol. : VERTICAL
 Limit : FCC PART 15 B(3M)
 Env. / Ins. : Temp:26.3Humi:49%;Press:101.52KPa
 Engineer : Carlos
 EUT : Klipsch Heritage Wireless TableTop
 Bluetooth Small
 Power : DC 20V From Adapter Input AC 120V/60Hz
 M/N : the One II Phono
 Test Mode : TX Mode


	Freq. (MHz)	ANT Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	33.88	15.60	0.18	11.30	27.08	40.00	12.92	QP
2	44.55	10.15	0.25	15.85	26.25	40.00	13.75	QP
3	129.91	11.70	0.98	18.36	31.04	43.50	12.46	QP
4	141.55	12.23	1.05	17.89	31.17	43.50	12.33	QP
5	171.62	9.74	1.19	20.27	31.20	43.50	12.30	QP
6	903.00	23.93	3.88	5.81	33.62	46.00	12.38	QP

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading.
 2. Margin= Limit - Emission Level.
 3. The emission levels that are 20dB below the official limit are not reported.

EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 24 File: \\Emc-966-1\test data\2020\RF\Mei Long\Mei Long.EM6 (24) Date: 2020-06-12



Site no. : 1# 966 Chamber Data no. : 24
 Dis. / Ant. : 3m 37062 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15 B(3M)
 Env. / Ins. : Temp:26.3Humi:49%;Press:101.52KPa
 Engineer : Carlos
 EUT : Klipsch Heritage Wireless TableTop
 Bluetooth Small
 Power : DC 20V From Adapter Input AC 120V/60Hz
 M/N : the One II Phono
 Test Mode : TX Mode

	Freq. (MHz)	ANT Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	171.62	9.74	1.19	22.93	33.86	43.50	9.64	QP
2	184.23	9.26	1.22	24.83	35.31	43.50	8.19	QP
3	211.39	8.84	1.37	25.41	35.62	43.50	7.88	QP
4	225.94	10.30	1.47	24.87	36.64	46.00	9.36	QP
5	285.11	13.20	1.80	21.30	36.30	46.00	9.70	QP
6	320.03	14.00	1.92	20.54	36.46	46.00	9.54	QP

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading.
 2. Margin= Limit - Emission Level.
 3. The emission levels that are 20dB below the official limit are not reported.

Note:

1. The amplitude of 9KHz to 30MHz spurious emission that is attenuated by more than 20dB below the permissible limit has no need to be reported.
2. All channels had been pre-test, only the worst case was reported.




Radiated Emissions Above 1G

EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 11 File: \\Emc-966-1\test data\2020\RF\MM\Mei Long\Mei Long.EM6 (24) Date: 2020-06-12



Site no. : 1# 966 Chamber Data no. : 11
 Dis. / Ant. : 3m ANI9120D 1-18G Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:26.3Humi:49%;Press:101.52KPa
 Engineer : Carlos
 EUT : Klipsch Heritage Wireless TableTop
 Bluetooth Small
 Power : DC 20V From Adapter Input AC 120V/60Hz
 M/N : the One II Phono
 Test Mode : GFSK TX 2402MHz


	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2402.00	27.26	1.45	34.64	96.28	90.35	74.00	-16.35	Peak
2	4804.00	31.12	3.25	34.66	44.09	43.80	74.00	30.20	Peak
3	7206.00	36.21	5.19	34.82	37.18	43.76	74.00	30.24	Peak
4	9959.00	38.83	5.86	34.21	39.75	50.23	74.00	23.77	Peak
5	15076.00	40.82	6.76	34.57	39.50	52.51	74.00	21.49	Peak
6	17983.00	48.76	8.23	34.30	30.41	53.10	74.00	20.90	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. Margin= Limit - Emission Level.
 3. The emission levels that are 20dB below the official limit are not reported.

EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 12 File: \\Emc-966-1\test data\2020\RF\Mei Long\Mei Long.EM6 (24) Date: 2020-06-12



Site no. : 1# 966 Chamber Data no. : 12
 Dis. / Ant. : 3m ANT9120D 1-18G Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:26.3Humi:49%;Press:101.52KPa
 Engineer : Carlos
 EUT : Klipsch Heritage Wireless TableTop
 Bluetooth Small
 Power : DC 20V From Adapter Input AC 120V/60Hz
 M/N : the One II Phono
 Test Mode : GFSK TX 2402MHz


	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2402.00	27.26	1.45	34.64	90.95	85.02	74.00	-11.02	Peak
2	4804.00	31.12	3.25	34.66	42.38	42.09	74.00	31.91	Peak
3	7206.00	36.21	5.19	34.82	38.00	44.58	74.00	29.42	Peak
4	9976.00	38.87	5.88	34.20	40.93	51.48	74.00	22.52	Peak
5	15025.00	40.88	6.80	34.59	39.30	52.39	74.00	21.61	Peak
6	17779.00	47.14	8.10	34.32	31.87	52.79	74.00	21.21	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. Margin= Limit - Emission Level.
 3. The emission levels that are 20dB below the official limit are not reported.

EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 13 File: \\Emc-966-1\test data\2020\RF\Mei Long\Mei Long.EM6 (24) Date: 2020-06-12



Site no. : 1# 966 Chamber Data no. : 13
 Dis. / Ant. : 3m ANT9120D 1-18G Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:26.3Humi:49%;Press:101.52KPa
 Engineer : Carlos
 EUT : Klipsch Heritage Wireless TableTop
 Bluetooth Small
 Power : DC 20V From Adapter Input AC 120V/60Hz
 M/N : the One II Phono
 Test Mode : GFSK TX 2440MHz


	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBUV)	Emission Level (dBUV/m)	Limits (dBUV/m)	Margin (dB)	Remark
1	2440.00	27.33	1.47	34.62	90.91	85.09	74.00	-11.09	Peak
2	4880.00	31.37	3.31	34.68	42.82	42.82	74.00	31.18	Peak
3	7320.00	36.46	5.22	34.83	38.12	44.97	74.00	29.03	Peak
4	10180.00	39.09	5.94	34.26	39.54	50.31	74.00	23.69	Peak
5	14549.00	40.99	6.89	34.46	39.07	52.49	74.00	21.51	Peak
6	17643.00	46.05	8.01	34.34	32.90	52.62	74.00	21.38	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. Margin= Limit - Emission Level.
 3. The emission levels that are 20dB below the official limit are not reported.

EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 14 File: \\Emc-966-1\test data\2020\RF\MM\Mei Long\Mei Long.EM6 (24) Date: 2020-06-12



Site no. : 1# 966 Chamber Data no. : 14
 Dis. / Ant. : 3m ANT9120D 1-18G Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:26.3Humi:49%;Press:101.52KPa
 Engineer : Carlos
 EUT : Klipsch Heritage Wireless TableTop
 Bluetooth Small
 Power : DC 20V From Adapter Input AC 120V/60Hz
 M/N : the One II Phono
 Test Mode : GFSK TX 2440MHz


	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2440.00	27.33	1.47	34.62	96.01	90.19	74.00	-16.19	Peak
2	4880.00	31.37	3.31	34.68	46.24	46.24	74.00	27.76	Peak
3	7320.00	36.46	5.22	34.83	37.83	44.68	74.00	29.32	Peak
4	10673.00	39.58	6.05	34.40	39.13	50.36	74.00	23.64	Peak
5	14073.00	41.09	6.58	34.32	37.78	51.13	74.00	22.87	Peak
6	17915.00	48.22	8.18	34.31	30.40	52.49	74.00	21.51	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. Margin= Limit - Emission Level.
 3. The emission levels that are 20dB below the official limit are not reported.

EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 15 File: \\Emc-966-1\test data\2020\RF\Mei Long\Mei Long.EM6 (24) Date: 2020-06-12




Site no. : 1# 966 Chamber Data no. : 15
 Dis. / Ant. : 3m ANT9120D 1-18G Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:26.3Humi:49%;Press:101.52KPa
 Engineer : Carlos
 EUT : Klipsch Heritage Wireless TableTop
 Bluetooth Small
 Power : DC 20V From Adapter Input AC 120V/60Hz
 M/N : the One II Phono
 Test Mode : GFSK TX 2480MHz

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBUV)	Emission Level (dBUV/m)	Limits (dBUV/m)	Margin (dB)	Remark
1	2480.00	27.38	1.48	34.61	97.33	91.58	74.00	-17.58	Peak
2	4960.00	31.68	3.38	34.69	44.36	44.73	74.00	29.27	Peak
3	7440.00	36.70	5.26	34.84	37.46	44.58	74.00	29.42	Peak
4	9993.00	38.90	5.89	34.20	39.37	49.96	74.00	24.04	Peak
5	14549.00	40.99	6.89	34.46	38.50	51.92	74.00	22.08	Peak
6	17745.00	46.87	8.07	34.33	32.38	52.99	74.00	21.01	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. Margin= Limit - Emission Level.
 3. The emission levels that are 20dB below the official limit are not reported.

Data: 16 File: \\Emc-966-1\test data\2020\RF\MM\Mei Long\Mei Long.EM6 (24) Date: 2020-06-12



Site no. : 1# 966 Chamber Data no. : 16
 Dis. / Ant. : 3m ANT9120D 1-18G Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:26.3Humi:49%;Press:101.52KPa
 Engineer : Carlos
 EUT : Klipsch Heritage Wireless TableTop
 Bluetooth Small
 Power : DC 20V From Adapter Input AC 120V/60Hz
 M/N : the One II Phono
 Test Mode : GFSK TX 2480MHz

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2480.00	27.38	1.48	34.61	87.97	82.22	74.00	-8.22	Peak
2	4960.00	31.68	3.38	34.69	40.86	41.23	74.00	32.77	Peak
3	7440.00	36.70	5.26	34.84	37.33	44.45	74.00	29.55	Peak
4	9993.00	38.90	5.89	34.20	39.34	49.93	74.00	24.07	Peak
5	14600.00	40.98	6.88	34.48	38.64	52.02	74.00	21.98	Peak
6	16351.00	40.19	7.06	34.27	39.62	52.60	74.00	21.40	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. Margin= Limit - Emission Level.
 3. The emission levels that are 20dB below the official limit are not reported.

Note:


1. The amplitude of 18GHz to 25GHz spurious emission that is attenuated by more than 20dB below the permissible limit has no need to be reported.

Radiated Band Edge

EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 17 File: \\Emc-966-1\test data\2020\RFMM\Mei Long\Mei Long.EM6 (24) Date: 2020-06-12



Site no. : 1# 966 Chamber Data no. : 17
 Dis. / Ant. : 3m ANT9120D 1-18G Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:26.3Humi:49%;Press:101.52KPa
 Engineer : Carlos
 EUT : Klipsch Heritage Wireless TableTop
 Bluetooth Small
 Power : DC 20V From Adapter Input AC 120V/60Hz
 M/N : the One II Phono
 Test Mode : GFSK TX 2402MHz


	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2390.00	27.26	1.45	34.64	43.12	37.19	74.00	36.81	Peak
2	2402.41	27.26	1.45	34.64	96.33	90.40	74.00	-16.40	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. Margin= Limit - Emission Level.
 3. The emission levels that are 20dB below the official limit are not reported.

EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 18 File: \\Emc-966-1\test data\2020\RF\Mei Long\Mei Long.EM6 (24) Date: 2020-06-12



Site no. : 1# 966 Chamber Data no. : 18
 Dis. / Ant. : 3m ANT9120D 1-18G Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:26.3Humi:49%;Press:101.52KPa
 Engineer : Carlos
 EUT : Klipsch Heritage Wireless TableTop
 Bluetooth Small
 Power : DC 20V From Adapter Input AC 120V/60Hz
 M/N : the One II Phono
 Test Mode : GFSK TX 2402MHz


	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBUV)	Emission Level (dBUV/m)	Limits (dBUV/m)	Margin (dB)	Remark
1	2390.00	27.26	1.45	34.64	42.24	36.31	74.00	37.69	Peak
2	2402.41	27.26	1.45	34.64	91.35	85.42	74.00	-11.42	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. Margin= Limit - Emission Level.
 3. The emission levels that are 20dB below the official limit are not reported.

EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 19 File: \\Emc-966-1\test data\2020\RF\MM\Mei Long\Mei Long.EM6 (24) Date: 2020-06-12




Site no. : 1# 966 Chamber Data no. : 19
 Dis. / Ant. : 3m ANT9120D 1-18G Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:26.3Humi:49%;Press:101.52KPa
 Engineer : Carlos
 EUT : Klipsch Heritage Wireless TableTop
 Bluetooth Small
 Power : DC 20V From Adapter Input AC 120V/60Hz
 M/N : the One II Phono
 Test Mode : GFSK TX 2480MHz

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2479.76	27.38	1.48	34.61	88.52	82.77	74.00	-8.77	Peak
2	2483.50	27.38	1.48	34.61	43.55	37.80	74.00	36.20	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. Margin= Limit - Emission Level.
 3. The emission levels that are 20dB below the official limit are not reported.

EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878



Site no. : 1# 966 Chamber Data no. : 20
 Dis. / Ant. : 3m ANI9120D 1-18G Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:26.3Humi:49%;Press:101.52KPa
 Engineer : Carlos
 EUT : Klipsch Heritage Wireless TableTop
 Bluetooth Small
 Power : DC 20V From Adapter Input AC 120V/60Hz
 M/N : the One II Phono
 Test Mode : GFSK TX 2480MHz

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2479.76	27.38	1.48	34.61	96.75	91.00	74.00	-17.00	Peak
2	2483.50	27.38	1.48	34.61	44.49	38.74	74.00	35.26	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. Margin= Limit - Emission Level.
 3. The emission levels that are 20dB below the official limit are not reported.

Note:

1. All channels had been pre-test, only of the worst case channels were reported.



9. AC POWER LINE CONDUCTED EMISSIONS


9.1. Limit

Frequency		Maximum RF Line Voltage	
		Quasi-Peak Level dB(μV)	Average Level dB(μV)
150kHz	~ 500kHz	66 ~ 56*	56 ~ 46*
500kHz	~ 5MHz	56	46
5MHz	~ 30MHz	60	50

Note:

- * Decreasing linearly with logarithm of frequency.
- The lower limit shall apply at the transition frequencies.

9.2. Test Setup



9.3. Spectrum Analyzer Setting

Spectrum Parameters	Setting
RBW	9KHz
VBW	9KHz
Start frequency	150KHz
Stop frequency	30MHz
Sweep Time	Auto
Detector	QP/AVG
Trace Mode	Max Hold


9.4. Test Procedure

- The EUT was placed on a non-metallic table, 80cm above the ground plane.
- The EUT Power connected to the power mains through a line impedance stabilization network.
- Provides a 50 ohm coupling impedance for the EUT (Please refer the block diagram of the test setup and photographs).
- Set the EUT transmit continuously with maximum output power.
- Spectrum analyzer setting parameters in accordance with section 9.3.
- The AC line are checked to find out the maximum conducted emission. In order to find the maximum emission levels, the relative positions of equipment and all of the interface cables shall be changed according to ANSI C63.10: 2013 on Conducted Emission Test.
- Record the results in the test report.

9.5. Test Result

EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel:+86-769-83081888
Fax:+86-769-83081878




Trace: 289
 Site no : 2# Conduction Shield Room Data no. : 290
 Env. / Ins. : Temp:24.9°C Humi:52% Press:101.50kPa LINE Phase : NEUTRAL
 Limit : FCC PART 15B QP
 Engineer : YYB
 EUT : Klipsch Heritage Wireless TableTop
 Bluetooth Small
 Power : DC 20V From Adapter Input AC 120V/60Hz
 M/N : the One II Phono
 Test Mode : TX Mode

	Freq. (MHz)	LISN Factor (dB)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV)	Limits (dBuV)	Margin (dB)	Remark
1	0.17	9.64	0.04	16.67	26.35	55.21	28.86	Average
2	0.17	9.64	0.04	33.99	43.67	65.21	21.54	QP
3	0.19	9.65	0.04	16.92	26.61	54.24	27.63	Average
4	0.19	9.65	0.04	31.81	41.50	64.24	22.74	QP
5	0.34	9.67	0.05	31.20	40.92	49.22	8.30	Average
6	0.34	9.67	0.05	35.91	45.63	59.22	13.59	QP
7	0.38	9.67	0.05	22.12	31.84	48.30	16.46	Average
8	0.38	9.67	0.05	28.22	37.94	58.30	20.36	QP
9	0.64	9.71	0.05	17.11	26.87	46.00	19.13	Average
10	0.64	9.71	0.05	22.96	32.72	56.00	23.28	QP
11	1.40	9.77	0.06	16.31	26.14	46.00	19.86	Average
12	1.40	9.77	0.06	22.85	32.68	56.00	23.32	QP

Remarks: 1. Emission Level= LISN Factor + Cable Loss + Reading.
 2. Margin= Limit - Emission Level.
 3. If the average limit is met when using a quasi-peak detector, the EUT shall be deemed to meet both limits and measurement with average detector is unnecessary.

Data: 292 File: \\Emc-ce-2\Test Data\2020\MM\Mei long.EM6 (312)

Date: 2020-06-09



Trace: 291


Site no : 2# Conduction Shield Room Data no. : 292
 Env. / Ins. : Temp:24.9°C Humi:52% Press:101.50kPa LINE Phase : LINE
 Limit : FCC PART 15B QP
 Engineer : YYB
 EUT : Klipsch Heritage Wireless TableTop
 Bluetooth Small
 Power : DC 20V From Adapter Input AC 120V/60Hz
 M/N : the One II Phono
 Test Mode : TX Mode

	Freq. (MHz)	LISN Factor (dB)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV)	Limits (dBuV)	Margin (dB)	Remark
1	0.17	9.68	0.04	20.98	30.70	55.21	24.51	Average
2	0.17	9.68	0.04	34.82	44.54	65.21	20.67	QP
3	0.30	9.73	0.04	22.30	32.07	50.24	18.17	Average
4	0.30	9.73	0.04	27.81	37.58	60.24	22.66	QP
5	0.34	9.74	0.05	32.95	42.74	49.22	6.48	Average
6	0.34	9.74	0.05	38.50	48.29	59.22	10.93	QP
7	0.39	9.76	0.05	22.67	32.48	48.17	15.69	Average
8	0.39	9.76	0.05	29.13	38.94	58.17	19.23	QP
9	0.66	9.83	0.05	14.30	24.18	46.00	21.82	Average
10	0.66	9.83	0.05	21.55	31.43	56.00	24.57	QP
11	1.93	9.84	0.06	15.31	25.21	46.00	20.79	Average
12	1.93	9.84	0.06	22.22	32.12	56.00	23.88	QP

Remarks: 1. Emission Level= LISN Factor + Cable Loss + Reading.
 2. Margin= Limit - Emission Level.
 3. If the average limit is met when using a quasi-peak detector,
 the EUT shall be deemed to meet both limits and measurement
 with average detector is unnecessary.

Data: 294 File: \\Emc-ce-2\Test Data\2020\MMei long.EM6 (312)

Date: 2020-06-09



Trace: 293


Site no : 2# Conduction Shield Room Data no. : 294
 Env. / Ins. : Temp:24.9°C Humi:52% Press:101.50kPa LINE Phase : LINE
 Limit : FCC PART 15B QP
 Engineer : YYB
 EUT : Klipsch Heritage Wireless TableTop
 Bluetooth Small
 Power : DC 20V From Adapter Input AC 240V/60Hz
 M/N : the One II Phono
 Test Mode : TX Mode

	Freq. (MHz)	LISN Factor (dB)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV)	Limits (dBuV)	Margin (dB)	Remark
1	0.27	9.72	0.04	24.44	34.20	51.12	16.92	Average
2	0.27	9.72	0.04	31.10	40.86	61.12	20.26	QP
3	0.36	9.75	0.05	32.81	42.61	48.74	6.13	Average
4	0.36	9.75	0.05	39.70	49.50	58.74	9.24	QP
5	0.75	9.85	0.05	19.30	29.20	46.00	16.80	Average
6	0.75	9.85	0.05	26.60	36.50	56.00	19.50	QP
7	1.18	9.88	0.06	19.40	29.34	46.00	16.66	Average
8	1.18	9.88	0.06	25.10	35.04	56.00	20.96	QP
9	1.71	9.85	0.06	18.93	28.84	46.00	17.16	Average
10	1.71	9.85	0.06	24.71	34.62	56.00	21.38	QP
11	2.22	9.85	0.06	17.80	27.71	46.00	18.29	Average
12	2.22	9.85	0.06	23.50	33.41	56.00	22.59	QP

Remarks: 1. Emission Level= LISN Factor + Cable Loss + Reading.
 2. Margin= Limit - Emission Level.
 3. If the average limit is met when using a quasi-peak detector,
 the EUT shall be deemed to meet both limits and measurement
 with average detector is unnecessary.

Data: 296 File: \\Emc-ce-2\Test Data\2020\MMei long.EM6 (312)

Date: 2020-06-09



Trace: 295

Site no : 2# Conduction Shield Room Data no. : 296
 Env. / Ins. : Temp:24.9°C Humi:52% Press:101.50kPa LINE Phase : NEUTRAL
 Limit : FCC PART 15B QP
 Engineer : YYB
 EUT : Klipsch Heritage Wireless TableTop
 Bluetooth Small
 Power : DC 20V From Adapter Input AC 240V/60Hz
 M/N : the One II Phono
 Test Mode : TX Mode

	Freq. (MHz)	LISN Factor (dB)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV)	Limits (dBuV)	Margin (dB)	Remark
1	0.27	9.66	0.04	22.51	32.21	50.98	18.77	Average
2	0.27	9.66	0.04	28.40	38.10	60.98	22.88	QP
3	0.36	9.67	0.05	30.68	40.40	48.74	8.34	Average
4	0.36	9.67	0.05	37.50	47.22	58.74	11.52	QP
5	0.70	9.71	0.05	21.60	31.36	46.00	14.64	Average
6	0.70	9.71	0.05	27.40	37.16	56.00	18.84	QP
7	1.18	9.77	0.06	21.01	30.84	46.00	15.16	Average
8	1.18	9.77	0.06	26.19	36.02	56.00	19.98	QP
9	1.63	9.78	0.06	19.59	29.43	46.00	16.57	Average
10	1.63	9.78	0.06	26.40	36.24	56.00	19.76	QP
11	2.13	9.81	0.06	18.71	28.58	46.00	17.42	Average
12	2.13	9.81	0.06	24.50	34.37	56.00	21.63	QP

Remarks: 1. Emission Level= LISN Factor + Cable Loss + Reading.
 2. Margin= Limit - Emission Level.
 3. If the average limit is met when using a quasi-peak detector,
 the EUT shall be deemed to meet both limits and measurement
 with average detector is unnecessary.

10. ANTENNA REQUIREMENTS

10.1. Limit


An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §§15.211, 15.213, 15.217, 15.219, 15.221, or §15.236. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with §15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

10.2. Test Result


The antennas used for this product is internal antenna ,so compliance with antenna requirements.
(Please refer to the EUT photo for details)

11. TEST SETUP PHOTO

Conducted Test



Radiated Test (Below 1GHz)



Radiated Test (Above 1GHz)



12. EUT PHOTO

External Photos
M/N: the One II Phono



External Photos
M/N: the One II Phono





External Photos
M/N: the One II Phono




External Photos
M/N: the One II Phono




External Photos
M/N: the One II Phono





Internal Photos
M/N: the One II Phono



Internal Photos
M/N: the One II Phono





Internal Photos
M/N: the One II Phono





Bluetooth
Antenna

Internal Photos
M/N: the One II Phono



Internal Photos
M/N: the One II Phono



End of Test Report