



# SAR Evaluation Report

IN ACCORDANCE WITH THE REQUIREMENTS OF  
FCC OET BULLETIN 65 SUPPLEMENT C  
IC RSS 102 ISSUE 1 : 1999

FOR

WIRELESS USB ADAPTER

MODEL: DWL-AG132

FCC ID: STJ80411396001  
IC: 5627A-80411396

REPORT NUMBER: 07U11148-1

ISSUE DATE: JUNE 1, 2007

*Prepared for*

HOSPIRA, INC.  
755 JARVIS DRIVE  
MORGAN HILL, CA 95037

*Prepared by*

COMPLIANCE CERTIFICATION SERVICES  
47173 BENICIA STREET,  
FREMONT, CA 94538 USA



NVLAP LAB CODE 200065-0

**Revision History**

Rev.	Issued date	Revisions	Revised By
--	7/1/07	Initial issue	M. Heckrotte

**CERTIFICATE OF COMPLIANCE (SAR EVALUATION)****DATES OF TEST:** June 22 and 25, 2007

APPLICANT: ADDRESS:	HOSPIRA, INC. 755 JARVIS DRIVE, MORGAN HILL, CA 95037
FCC ID: MODEL:	STJ80411396001 DWL-AG132
DEVICE CATEGORY: EXPOSURE CATEGORY:	Portable Device General Population/Uncontrolled Exposure

Wireless USB Adaptor is installed in Symbiq medical pump.		
Test Sample is a:	Production unit	
Modulation type:	Direct Sequence Spread Spectrum (DSSS) for 802.11b Orthogonal Frequency Division Multiplexing (OFDM) for 802.11ag	
Rule Parts	Frequency Range [MHz]	The Highest SAR Values [1g_mW/g]
FCC 15.247	2412 - 2462	0.095
	5745 - 5825	0.581
FCC 15.401	5180 - 5320	0.441
	5500 - 5700	0.278

This wireless portable device has been shown to be capable of compliance for localized specific absorption rate (SAR) for General Population/Uncontrolled Exposure limits specified in ANSI/IEEE Std. C95.1-1992 and had been tested in accordance with the measurement procedures specified in FCC OET 65 Supplement C (Edition 01-01) and RSS 102.

This wireless device has been shown to be capable of compliance for localized specific absorption rate (SAR) for General Population/Uncontrolled Exposure limits specified and tested in accordance with procedures referenced below in Section 2.

Note: The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. This document may not be altered or revised in any way unless done so by Compliance Certification Services and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by Compliance Certification Services will constitute fraud and shall nullify the document. No part of this report may be used to claim product certification, approval, or endorsement by NVLAP, NIST, or any government agency.

Approved &amp; Released For CCS By:

Tested By:



Michael Heckrotte  
Engineering Manager  
Compliance Certification Services

Ninous Davoudi  
EMC Engineer  
Compliance Certification Services

Table Of Contents

1	DEVICE UNDER TEST (DUT) DESCRIPTION .....	5
2	FACILITIES AND ACCREDITATION .....	6
3	SYSTEM DESCRIPTION .....	7
3.1	COMPOSITION OF INGREDIENTS FOR TISSUE SIMULATING LIQUIDS .....	8
4	SIMULATING LIQUID PARAMETERS CHECK.....	9
4.1	SIMULATING LIQUID PARAMETER CHECK RESULT.....	11
5	SYSTEM PERFORMANCE CHECK .....	15
5.1	SYSTEM PERFORMANCE CHECK RESULTS.....	17
6	SAR MEASUREMENT PROCEDURE .....	18
6.1	DASY4 SAR MEASUREMENT PROCEDURE .....	19
7	PROCEDURE USED TO ESTABLISH TEST SIGNAL .....	20
8	SAR MEASUREMENT RESULTS.....	21
8.1	2.4GHZ.....	21
8.1.1	TOP POSITION.....	21
8.1.2	FACE UP POSITION .....	22
8.2	5GHZ.....	23
8.2.1	TOP POSITION.....	23
8.2.2	FACE UP POSITION .....	24
9	MEASUREMENT UNCERTAINTY .....	25
9.1	MEASUREMENT UNCERTAINTY FOR 300 MHZ – 3000 MHZ .....	25
9.2	MEASUREMENT UNCERTAINTY 3 GHZ – 6 GHZ .....	26
10	EQUIPMENT LIST AND CALIBRATION.....	27
11	PHOTOS .....	28
12	ATTACHMENTS.....	30

**1 DEVICE UNDER TEST (DUT) DESCRIPTION**

Wireless USB Adaptor is installed in Symbiq medical pump.	
Duty cycle:	100% abg modes
Host Device(s):	Symbiq Medical Pump
Antenna(s)	Tyco, PN: 1513164-1
Power supply:	Power supplied through the host device.

## 2 FACILITIES AND ACCREDITATION

The test sites and measurement facilities used to collect data are located at 47173 Benicia Street, Fremont, CA 94538 USA. The sites are constructed in conformance with the requirements of ANSI C63.4, ANSI C63.7 and CISPR Publication 22. All receiving equipment conforms to CISPR Publication 16-1, "Radio Interference Measuring Apparatus and Measurement Methods."




NVLAP LAB CODE 200065-0

CCS is accredited by NVLAP, Laboratory Code 200065-0. The full scope of accreditation can be viewed at <http://www.ccsemc.com>.

No part of this report may be used to claim product certification, approval, or endorsement by NVLAP, NIST, or any government agency.

### 3 SYSTEM DESCRIPTION



#### The DASY4 system for performing compliance tests consists of the following items:

- A standard high precision 6-axis robot (Stäubli RX family) with controller, teach pendant and software. An arm extension for accommodating the data acquisition electronics (DAE).
- A dosimetric probe, i.e., an isotropic E-field probe optimized and calibrated for usage in tissue simulating liquid. The probe is equipped with an optical surface detector system.
- A data acquisition electronics (DAE) which performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.
- The function of the measurement server is to perform the time critical tasks such as signal filtering, control of the robot operation and fast movement interrupts.
- A probe alignment unit which improves the (absolute) accuracy of the probe positioning.
- A computer operating Windows 2000 or Windows XP.
- DASY4 software.
- Remote controls with teach pendant and additional circuitry for robot safety such as warning lamps, etc.
- The SAM twin phantom enabling testing left-hand and right-hand usage.
- The device holder for handheld mobile phones.
- Tissue simulating liquid mixed according to the given recipes.
- Validation dipole kits allowing to validate the proper functioning of the system.

### 3.1 COMPOSITION OF INGREDIENTS FOR TISSUE SIMULATING LIQUIDS

The following tissue formulations are provided for reference only as some of the parameters have not been thoroughly verified. The composition of ingredients may be modified accordingly to achieve the desired target tissue parameters required for routine SAR evaluation.

Ingredients (% by weight)	Frequency (MHz)									
	450		835		915		1900		2450	
Tissue Type	Head	Body	Head	Body	Head	Body	Head	Body	Head	Body
Water	38.56	51.16	41.45	52.4	41.05	56.0	54.9	40.4	62.7	73.2
Salt (NaCl)	3.95	1.49	1.45	1.4	1.35	0.76	0.18	0.5	0.5	0.04
Sugar	56.32	46.78	56.0	45.0	56.5	41.76	0.0	58.0	0.0	0.0
HEC	0.98	0.52	1.0	1.0	1.0	1.21	0.0	1.0	0.0	0.0
Bactericide	0.19	0.05	0.1	0.1	0.1	0.27	0.0	0.1	0.0	0.0
Triton X-100	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	36.8	0.0
DGBE	0.0	0.0	0.0	0.0	0.0	0.0	44.92	0.0	0.0	26.7
Dielectric Constant	43.42	58.0	42.54	56.1	42.0	56.8	39.9	54.0	39.8	52.5
Conductivity (S/m)	0.85	0.83	0.91	0.95	1.0	1.07	1.42	1.45	1.88	1.78

Salt: 99+% Pure Sodium Chloride

Sugar: 98+% Pure Sucrose

Water: De-ionized, 16 MΩ+ resistivity

HEC: Hydroxyethyl Cellulose


DGBE: 99+% Di(ethylene glycol) butyl ether, [2-(2-butoxyethoxy)ethanol]

Triton X-100 (ultra pure): Polyethylene glycol mono [4-(1,1, 3, 3-tetramethylbutyl)phenyl]ether



**4 SIMULATING LIQUID PARAMETERS CHECK**

The simulating liquids should be checked at the beginning of a series of SAR measurements to determine if the dielectric parameters are within the tolerances of the specified target values. The relative permittivity and conductivity of the tissue material should be within  $\pm 5\%$  of the values given in the table below.



Set-up for liquid parameters check

**Reference Values of Tissue Dielectric Parameters for Head and Body Phantom (for 150 – 3000 MHz and 5800 MHz)**

The head tissue dielectric parameters recommended by the IEEE SCC-34/SC-2 in IEEE Standard 1528 have been incorporated in the following table. These head parameters are derived from planar layer models simulating the highest expected SAR for the dielectric properties and tissue thickness variations in a human head. Other head and body tissue parameters that have not been specified in P1528 are derived from the tissue dielectric parameters computed from the 4-Cole-Cole equations and extrapolated according to the head parameters specified in IEEE Standard 1528.

Target Frequency (MHz)	Head		Body	
	$\epsilon_r$	$\sigma$ (S/m)	$\epsilon_r$	$\sigma$ (S/m)
150	52.3	0.76	61.9	0.80
300	45.3	0.87	58.2	0.92
450	43.5	0.87	56.7	0.94
835	41.5	0.90	55.2	0.97
900	41.5	0.97	55.0	1.05
915	41.5	0.98	55.0	1.06
1450	40.5	1.20	54.0	1.30
1610	40.3	1.29	53.8	1.40
1800 – 2000	40.0	1.40	53.3	1.52
2450	39.2	1.80	<b>52.7</b>	<b>1.95</b>
3000	38.5	2.40	52.0	2.73
5800	35.3	5.27	48.2	6.00

( $\epsilon_r$  = relative permittivity,  $\sigma$  = conductivity and  $\rho = 1000 \text{ kg/m}^3$ )

### Reference Values of Tissue Dielectric Parameters for Head and Body Phantom (for 3000 MHz – 5800 MHz)

In the current guidelines and draft standards for compliance testing of mobile phones (i.e., IEEE P1528, OET 65 Supplement C), the dielectric parameters suggested for head and body tissue simulating liquid are given only at 3.0 GHz and 5.8 GHz. As an intermediate solution, dielectric parameters for the frequencies between 5 to 5.8 GHz were obtained using linear interpolation (see table below).

SPEAG has developed suitable head and body tissue simulating liquids consisting of the following ingredients: de-ionized water, salt and a special composition including mineral oil and an emulgators. Dielectric parameters of these liquids were measured using a HP 8570C Dielectric Probe Kit in conjunction with HP 8753ES Network Analyzer (30 kHz – 6G Hz). The differences with respect to the interpolated values were well within the desired  $\pm 5\%$  for the whole 5 to 5.8 GHz range.

f (MHz)	Head Tissue		Body Tissue		Reference
	rel. permittivity	conductivity	rel. permittivity	conductivity	
3000	38.5	2.40	52.0	2.73	Standard
5800	35.3	5.27	<b>48.2</b>	<b>6.00</b>	Standard
5000	36.2	1.45	49.3	5.07	Interpolated
5100	36.1	4.55	49.1	5.18	Interpolated
5200	36.0	4.66	<b>49.0</b>	<b>5.30</b>	Interpolated
5300	35.9	4.76	48.9	5.42	Interpolated
5400	35.8	4.86	48.7	5.53	Interpolated
5500	35.6	4.96	<b>48.6</b>	<b>5.65</b>	Interpolated
5600	35.5	5.07	48.5	5.77	Interpolated
5700	35.4	5.17	48.3	5.88	Interpolated

( $\epsilon_r$  = relative permittivity,  $\sigma$  = conductivity and  $\rho = 1000 \text{ kg/m}^3$ )

**4.1 SIMULATING LIQUID PARAMETER CHECK RESULT**

Simulating Liquid Dielectric Parameter Check Result @ Muscle 2450 MHz

Room Ambient Temperature = 23°C; Relative humidity = 40%

Measured by: Ninous Davoudi

Simulating Liquid			Parameters		Measured	Target	Deviation (%)	Limit (%)	
f (MHz)	Temp. (°C)	Depth (cm)							
2450	21	15	e'	54.3001	Relative Permittivity (e <sub>r</sub> ):	54.3001	52.7	3.04	± 5
			e"	14.8217	Conductivity (σ):	2.02015	1.95	3.60	± 5

Liquid Check

Ambient temperature: 22.0 deg. C; Liquid temperature: 21.0 deg C

June 22, 2007 09:48 PM

Frequency	e'	e"
2400000000.	53.8230	14.2832
2405000000.	53.7643	14.4099
2410000000.	53.7398	14.5114
2415000000.	53.7424	14.6092
2420000000.	53.7664	14.6869
2425000000.	53.8319	14.7416
2430000000.	53.9293	14.7898
2435000000.	54.0527	14.8269
2440000000.	54.1572	14.8372
2445000000.	54.2349	14.8151
<b>2450000000.</b>	<b>54.3001</b>	<b>14.8217</b>
2455000000.	54.3500	14.7844
2460000000.	54.3736	14.7101
2465000000.	54.3893	14.6301
2470000000.	54.3246	14.5566
2475000000.	54.2903	14.4816
2480000000.	54.2355	14.4356
2485000000.	54.1650	14.4159
2490000000.	54.0672	14.4227
2495000000.	53.9662	14.4587
2500000000.	53.8236	14.5250

The conductivity (σ) can be given as:

$$\sigma = \omega \epsilon_0 e'' = 2 \pi f \epsilon_0 e''$$

where  $f = \text{target } f * 10^6$

$\epsilon_0 = 8.854 * 10^{-12}$

Simulating Liquid Parameter Check Result @ Muscle 5GHz

Room Ambient Temperature = 25°C; Relative humidity = 40%

Measured by: Jonathan King

Simulating Liquid			Parameters		Measured	Target	Deviation (%)	Limit (%)	
f (MHz)	Temp. (°C)	Depth (cm)							
5200	24	15	e'	46.2875	Relative Permittivity (ε <sub>r</sub> ):	46.2875	49.0	-5.54	± 10
			e"	18.5796	Conductivity (σ):	5.37476	5.30	1.41	± 5

Liquid Check

Ambient temperature: 25 deg. C; Liquid temperature: 24 deg C

June 25, 2007 09:56 AM

Frequency	e'	e"
4600000000.	47.4964	17.8000
4650000000.	47.3810	17.8543
4700000000.	47.3162	17.9617
4750000000.	47.2138	17.9977
4800000000.	47.0988	18.0830
4850000000.	47.0158	18.1324
4900000000.	46.8866	18.2107
4950000000.	46.7482	18.2799
5000000000.	46.6891	18.3284
5050000000.	46.6018	18.4218
5100000000.	46.4898	18.4471
5150000000.	46.3820	18.5484
<b>5200000000.</b>	<b>46.2875</b>	<b>18.5796</b>
5250000000.	46.1680	18.6534
5300000000.	46.0747	18.7068
5350000000.	45.9574	18.7648
5400000000.	45.8656	18.8153
5450000000.	45.7619	18.8622
5500000000.	45.6638	18.9388
5550000000.	45.5444	18.9651
5600000000.	45.4684	19.0281
5650000000.	45.3598	19.0649
5700000000.	45.2626	19.1242
5750000000.	45.1413	19.1549
5800000000.	45.0628	19.2284
5850000000.	44.9550	19.2619
5900000000.	44.8791	19.3407
5950000000.	44.7710	19.3511
6000000000.	44.6542	19.4185

The conductivity (σ) can be given as:

$$\sigma = \omega \epsilon_0 e'' = 2 \pi f \epsilon_0 e''$$

where  $f = \text{target } f * 10^6$   
 $\epsilon_0 = 8.854 * 10^{-12}$

Simulating Liquid Parameter Check Result @ Muscle 5GHz

Room Ambient Temperature = 25°C; Relative humidity = 40%

Measured by: Jonathan King

Simulating Liquid			Parameters		Measured	Target	Deviation (%)	Limit (%)	
f (MHz)	Temp. (°C)	Depth (cm)							
5500	24	15	e'	45.6638	Relative Permittivity (ε <sub>r</sub> ):	45.6638	48.6	-6.04	± 10
			e"	18.9388	Conductivity (σ):	5.79474	5.65	2.56	± 5

Liquid Check

Ambient temperature: 25 deg. C; Liquid temperature: 24 deg C

June 25, 2007 09:56 AM

Frequency	e'	e"
4600000000.	47.4964	17.8000
4650000000.	47.3810	17.8543
4700000000.	47.3162	17.9617
4750000000.	47.2138	17.9977
4800000000.	47.0988	18.0830
4850000000.	47.0158	18.1324
4900000000.	46.8866	18.2107
4950000000.	46.7482	18.2799
5000000000.	46.6891	18.3284
5050000000.	46.6018	18.4218
5100000000.	46.4898	18.4471
5150000000.	46.3820	18.5484
5200000000.	46.2875	18.5796
5250000000.	46.1680	18.6534
5300000000.	46.0747	18.7068
5350000000.	45.9574	18.7648
5400000000.	45.8656	18.8153
5450000000.	45.7619	18.8622
<b>5500000000.</b>	<b>45.6638</b>	<b>18.9388</b>
5550000000.	45.5444	18.9651
5600000000.	45.4684	19.0281
5650000000.	45.3598	19.0649
5700000000.	45.2626	19.1242
5750000000.	45.1413	19.1549
5800000000.	45.0628	19.2284
5850000000.	44.9550	19.2619
5900000000.	44.8791	19.3407
5950000000.	44.7710	19.3511
6000000000.	44.6542	19.4185

The conductivity (σ) can be given as:

$$\sigma = \omega \epsilon_0 e'' = 2 \pi f \epsilon_0 e''$$

where  $f = \text{target } f * 10^6$   
 $\epsilon_0 = 8.854 * 10^{-12}$

Simulating Liquid Parameter Check Result @ Muscle 5GHz

Room Ambient Temperature = 25°C; Relative humidity = 40%

Measured by: Jonathan King

Simulating Liquid			Parameters		Measured	Target	Deviation (%)	Limit (%)	
f (MHz)	Temp. (°C)	Depth (cm)							
5800	24	15	e'	45.0628	Relative Permittivity (ε <sub>r</sub> ):	45.0628	48.2	-6.51	± 10
			e"	19.2284	Conductivity (σ):	6.20426	6.00	3.40	± 5

Liquid Check

Ambient temperature: 25 deg. C; Liquid temperature: 24 deg C

June 25, 2007 09:56 AM

Frequency	e'	e"
4600000000.	47.4964	17.8000
4650000000.	47.3810	17.8543
4700000000.	47.3162	17.9617
4750000000.	47.2138	17.9977
4800000000.	47.0988	18.0830
4850000000.	47.0158	18.1324
4900000000.	46.8866	18.2107
4950000000.	46.7482	18.2799
5000000000.	46.6891	18.3284
5050000000.	46.6018	18.4218
5100000000.	46.4898	18.4471
5150000000.	46.3820	18.5484
5200000000.	46.2875	18.5796
5250000000.	46.1680	18.6534
5300000000.	46.0747	18.7068
5350000000.	45.9574	18.7648
5400000000.	45.8656	18.8153
5450000000.	45.7619	18.8622
5500000000.	45.6638	18.9388
5550000000.	45.5444	18.9651
5600000000.	45.4684	19.0281
5650000000.	45.3598	19.0649
5700000000.	45.2626	19.1242
5750000000.	45.1413	19.1549
<b>5800000000.</b>	<b>45.0628</b>	<b>19.2284</b>
5850000000.	44.9550	19.2619
5900000000.	44.8791	19.3407
5950000000.	44.7710	19.3511
6000000000.	44.6542	19.4185

The conductivity (σ) can be given as:

$$\sigma = \omega \epsilon_0 e'' = 2 \pi f \epsilon_0 e''$$

where  $f = \text{target } f * 10^6$   
 $\epsilon_0 = 8.854 * 10^{-12}$

## 5 SYSTEM PERFORMANCE CHECK

The system performance check is performed prior to any usage of the system in order to guarantee reproducible results. The system performance check verifies that the system operates within its specifications of  $\pm 10\%$ .

### System Performance Check Measurement Conditions

- The measurements were performed in the flat section of the SAM twin phantom filled with Body simulating liquid of the following parameters.
- The DASY4 system with an Isotropic E-Field Probe EX3DV3-SN: 3531 was used for the measurements.
- The dipole was mounted on the small tripod so that the dipole feed point was positioned below the center marking of the flat phantom section and the dipole was oriented parallel to the body axis (the long side of the phantom). The standard measuring distance was 10 mm (above 1 GHz) and 15 mm (below 1 GHz) from dipole center to the simulating liquid surface.
- The coarse grid with a grid spacing of 15 mm was aligned with the dipole.  
For 5 GHz band - The coarse grid with a grid spacing of 10 mm was aligned with the dipole.
- Special 5 x 5 x 7 fine cube was chosen for cube integration(dx=dy=7.5mm; dz=5mm).  
For 5 GHz band - Special 8x8x8 fine cube was chosen for cube integration(dx=dy=4.3mm; dz=3mm)
- Distance between probe sensors and phantom surface was set to 4 mm.  
For 5 GHz band - Distance between probe sensors and phantom surface was set to 2.0mm
- The dipole input power (forward power) was 250 mW $\pm 3\%$ .
- The results are normalized to 1 W input power.

### Reference SAR Values for body-tissue

In the table below, the numerical reference SAR values of a SPEAG validation dipoles placed below the flat phantom filled with body-tissue simulating liquid are given. The reference SAR values were calculated using the finite-difference time-domain method and the geometry parameters.

Dipole Type	Distance (mm)	Frequency (MHz)	SAR (1g) [W/kg]	SAR (10g) [W/kg]	SAR (peak) [W/kg]
D450V2	15	450	5.01	3.36	7.22
D835V2	15	835	9.71	6.38	14.1
D900V2	15	900	11.1	7.17	16.3
D1450V2	10	1450	29.6	16.6	49.8
D1800V2	10	1800	38.5	20.3	67.5
D1900V2	10	1900	39.8	20.8	69.6
D2000V2	10	2000	40.9	21.2	71.5
D2450V2	10	2450	<b>51.2</b>	<b>23.7</b>	97.6

Note: All SAR values normalized to 1 W forward power.

**Reference SAR Values for body-tissue**

In the table below, the numerical reference SAR values of a SPEAG validation dipoles placed below the flat phantom filled with body-tissue simulating liquid are given. The reference SAR values were calculated using finite-difference time-domain FDTD method (feed point-impedance set to 50 ohms) and the mechanical dimensions of the D5GHzV2 dipole (manufactured by SPEAG).

f (MHz)	Head Tissue		Body Tissue		
	SAR <sub>1g</sub>	SAR <sub>10g</sub>	SAR <sub>1g</sub>	SAR <sub>10g</sub>	SAR <sub>Peak</sub>
5000	72.9	20.7	68.1	19.2	260.3
5100	74.6	21.1	78.8	19.6	272.3
5200	76.5	21.6	<b>71.8</b>	<b>20.1</b>	284.7
5500	83.3	23.4	<b>79.1</b>	<b>22.0</b>	326.3
5800	78.0	21.9	<b>74.1</b>	<b>20.5</b>	324.7

Note: All SAR values normalized to 1 W forward power.



**5.1 SYSTEM PERFORMANCE CHECK RESULTS**

**System Validation Dipole: D2450V2 SN: 706**

Date: June 22, 2007

Room Ambient Temperature = 23°C; Relative humidity = 40%

Measured by: Ninous Davoudi:

Body Simulating Liquid			SAR (mW/g)		Normalized to 1 W	Target	Deviation (%)	Limit (%)
f (MHz)	Temp. (°C)	Depth (cm)						
2450	21	15	1g	13.00	52	51.2	1.56	± 10
			10g	6.04				

**System Validation Dipole: D5GHzV2 SN 1003**

Date: June 25, 2007

Ambient Temperature = 25°C; Relative humidity = 40%

Measured by: Jonathan King

Body Simulating Liquid			SAR (mW/g)		Normalized to 1 W	Target	Deviation (%)	Limit (%)
f (MHz)	Temp. (°C)	Depth (cm)						
5200	24	15	1g	18.80	75.2	71.8	4.74	± 10
			10g	5.35				

**System Validation Dipole: D5GHzV2 SN 1003**

Date: June 25, 2007

Ambient Temperature = 25°C; Relative humidity = 40%

Measured by: Jonathan King

Body Simulating Liquid			SAR (mW/g)		Normalized to 1 W	Target	Deviation (%)	Limit (%)
f (MHz)	Temp. (°C)	Depth (cm)						
5500	24	15	1g	18.80	75.2	79.1	-4.93	± 10
			10g	5.4				

**System Validation Dipole: D5GHzV2 SN 1003**

Date: June 25, 2007

Ambient Temperature = 25°C; Relative humidity = 40%

Measured by: Jonathan King

Body Simulating Liquid			SAR (mW/g)		Normalized to 1 W	Target	Deviation (%)	Limit (%)
f (MHz)	Temp. (°C)	Depth (cm)						
5800	24	15	1g	17.90	71.6	74.1	-3.37	± 10
			10g	5.03				

## 6 SAR MEASUREMENT PROCEDURE

A summary of the procedure follows:

- a) A measurement of the SAR value at a fixed location is used as a reference value for assessing the power drop of the DUT. The SAR at this point is measured at the start of the test, and then again at the end of the test.
- b) The SAR distribution at the exposed flat section of the flat phantom is measured at a distance of 4 mm from the inner surface of the shell. The area covers the entire dimension of the DUT and the horizontal grid spacing is 15 mm x 15 mm. Based on this data, the area of the maximum absorption is determined by Spline interpolation. The first Area Scan covers the entire dimension of the DUT to ensure that the hotspot was correctly identified.

For 5 GHz band - The SAR distribution at the exposed flat section of the flat phantom is measured at a distance of 2.0 mm from the inner surface of the shell. The area covers the entire dimension of the DUT and the horizontal grid spacing is 10 mm x 10 mm. Based on this data, the area of the maximum absorption is determined by Spline interpolation. The first Area Scan covers the entire dimension of the DUT to ensure that the hotspot was correctly identified.

- c) Around this point, a volume of X=Y= 30 and Z=21 mm is assessed by measuring 5 x 5 x 7 mm points. On the basis of this data set, the spatial peak SAR value is evaluated with the following procedure:

For 5 GHz band - Around this point, a volume of X=Y=24 and Z=20 mm is assessed by measuring 7 x 7 x 9 mm points. On the basis of this data set, the spatial peak SAR value is evaluated with the following procedure:

- (i) The data at the surface are extrapolated, since the centre of the dipoles is 1.2 mm away from the tip of the probe and the distance between the surface and the lowest measuring point is 1.3 mm. The extrapolation is based on a least square algorithm. A polynomial of the fourth order is calculated through the points in z-axes. This polynomial is then used to evaluate the points between the surface and the probe tip.
- (ii) The maximum interpolated value is searched with a straightforward algorithm. Around this maximum the SAR values averaged over the spatial volumes (1 g and 10 g) are computed using the 3D-Spline interpolation algorithm. The 3D-Spline is composed of three one-dimensional splines with the "Not a knot"- condition (in x, y and z-direction). The volume is integrated with the trapezoidal – algorithm. One thousand points (10 x 10 x 10) are interpolated to calculate the averages.
- (iii) All neighbouring volumes are evaluated until no neighbouring volume with a higher average value is found.
- (iv) The SAR value at the same location as in Step (a) is again measured to evaluate the actual power drift.

## 6.1 DASY4 SAR MEASUREMENT PROCEDURE

### Step 1: Power Reference Measurement

The Power Reference Measurement and Power Drift Measurements are for monitoring the power drift of the device under test in the batch process. The Minimum distance of probe sensors to surface determines the closest measurement point to phantom surface. The minimum distance of probe sensors to surface is 2.1 mm. This distance cannot be smaller than the Distance of sensor calibration points to probe tip as defined in the probe properties (for example, 1.2 mm for an EX3DV3 probe type).

### Step 2: Area Scan

The Area Scan is used as a fast scan in two dimensions to find the area of high field values, before doing a fine measurement around the hot spot. The sophisticated interpolation routines implemented in DASY4 software can find the maximum locations even in relatively coarse grids. When an Area Scan has measured all reachable points, it computes the field maximal found in the scanned area, within a range of the global maximum. The range (in dB) is specified in the standards for compliance testing. For example, a 2 dB range is required in IEEE Standard 1528, EN 50361 and IEC 62209 standards, whereby 3 dB is a requirement when compliance is assessed in accordance with the ARIB standard (Japan). If only one Zoom Scan follows the Area Scan, then only the absolute maximum will be taken as reference. For cases where multiple maximums are detected, the number of Zoom Scans has to be increased accordingly.

### Step 3: Zoom Scan

Zoom Scans are used to assess the peak spatial SAR values within a cubic averaging volume containing 1 g and 10 g of simulated tissue. The Zoom Scan measures 5 x 5 x 7 points within a cube whose base faces are centered on the maxima found in a preceding area scan job within the same procedure. When the measurement is done, the Zoom Scan evaluates the averaged SAR for 1 g and 10 g and displays these values next to the job's label.

For 5 GHz band – Same as above except the Zoom Scan measures 7 x 7 x 9 points.

### Step 4: Power drift measurement

The Power Drift Measurement measures the field at the same location as the most recent power reference measurement within the same procedure, and with the same settings. The Power Drift Measurement gives the field difference in dB from the reading conducted within the last Power Reference Measurement. This allows a user to monitor the power drift of the device under test within a batch process. The measurement procedure is the same as Step 1.

### Step 5: Z-Scan

The Z Scan measures points along a vertical straight line. The line runs along the Z-axis of a one-dimensional grid. In order to get a reasonable extrapolation, the extrapolated distance should not be larger than the step size in Z-direction.

## 7 PROCEDURE USED TO ESTABLISH TEST SIGNAL

The following procedures had been used to prepare the EUT for the SAR test.

The client provided a special driver and program, ART version 5.3 build 22, which enable a user to control the frequency and output power of the module.

### *b mode*

Channel	Frequency (MHz)	Power (dBm)
Low	2412	17.3
Middle	2437	17.5
High	2462	17.6

### *g mode*

Channel	Frequency (MHz)	Power (dBm)
Low	2412	17.4
Middle	2437	17.3
High	2462	17.5

### *a mode*

Channel	Frequency (MHz)	Power (dBm)
Low	5180	16.2
Middle	5280	16.1
High	5320	16.0


Channel	Frequency (MHz)	Power (dBm)
Low	5500	16.5
Middle	5600	16.6
High	5700	16.1

Channel	Frequency (MHz)	Power (dBm)
Low	5745	19.2
Middle	5785	18.5
High	5825	18.4

**8 SAR MEASUREMENT RESULTS**

**8.1 2.4GHZ**

**8.1.1 TOP POSITION**



**802.11b**

Channel	f (MHz)	Measured SAR 1g (mW/g)	Power Drift (dB)	Extrapolated <sup>1)</sup> SAR 1g (mW/g)
1	2412	<b>0.095</b>	<b>0.000</b>	<b>0.095</b>
<b>6</b>	<b>2437</b>			
11	2462			


**802.11g**

Channel	f (MHz)	Measured SAR 1g (mW/g)	Power Drift (dB)	Extrapolated <sup>1)</sup> SAR 1g (mW/g)
1	2412	0.080	-0.107	0.082
6	2437			
11	2462			

Notes:

- 1) The exact method of extrapolation is  $\text{Measured SAR} \times 10^{(-\text{drift}/10)}$ . The SAR reported at the end of the measurement process by the DASY4 system can be scaled up by the Power drift to determine the SAR at the beginning of the measurement process.
- 2) The SAR measured at the middle channel for this configuration is at least 3 dB lower (0.8 mW/g) than SAR limit (1.6 mW/g), thus testing at low & high channel is optional.
- 3) Please see attachments for the detailed measurement data and plots showing the maximum SAR location of the EUT.

**8.1.2 FACE UP POSITION**



**802.11b**

Channel	f (MHz)	Measured SAR 1g (mW/g)	Power Drift (dB)	Extrapolated <sup>1)</sup> SAR 1g (mW/g)
1	2412			
6	2437	0.040	-0.135	0.041
11	2462			

**802.11g**


Channel	f (MHz)	Measured SAR 1g (mW/g)	Power Drift (dB)	Extrapolated <sup>1)</sup> SAR 1g (mW/g)
1	2412			
6	2437	0.032	-0.191	0.034
11	2462			

Notes:

- 1) The exact method of extrapolation is  $\text{Measured SAR} \times 10^{(-\text{drift}/10)}$ . The SAR reported at the end of the measurement process by the DASY4 system can be scaled up by the Power drift to determine the SAR at the beginning of the measurement process.
- 2) The SAR measured at the middle channel for this configuration is at least 3 dB lower (0.8 mW/g) than SAR limit (1.6 mW/g), thus testing at low & high channel is optional.
- 3) Please see attachments for the detailed measurement data and plots showing the maximum SAR location of the EUT.

8.2 5GHZ

8.2.1 TOP POSITION




<b>802.11a 5.2 GHz</b>				
Channel	f (MHz)	Measured SAR 1g (mW/g)	Power Drift (dB)	Extrapolated <sup>1)</sup> SAR 1g (mW/g)
36	5180			
<b>52</b>	<b>5260</b>	<b>0.441</b>	<b>0.000</b>	<b>0.441</b>
64	5320			
<b>802.11a 5.5 GHz</b>				
Channel	f (MHz)	Measured SAR 1g (mW/g)	Power Drift (dB)	Extrapolated <sup>1)</sup> SAR 1g (mW/g)
100	5500			
<b>120</b>	<b>5600</b>	<b>0.278</b>	<b>0.000</b>	<b>0.278</b>
140	5700			
<b>802.11a 5.8 GHz</b>				
Channel	f (MHz)	Measured SAR 1g (mW/g)	Power Drift (dB)	Extrapolated <sup>1)</sup> SAR 1g (mW/g)
149	5745			
<b>157</b>	<b>5785</b>	<b>0.581</b>	<b>0.000</b>	<b>0.581</b>
165	5825			

Notes:

- 1) The exact method of extrapolation is Measured SAR x 10<sup>^(-drift/10)</sup>. The SAR reported at the end of the measurement process by the DASY4 system can be scaled up by the Power drift to determine the SAR at the beginning of the measurement process.
- 2) The SAR measured at the middle channel for this configuration is at least 3 dB lower (0.8 mW/g) than SAR limit (1.6 mW/g), thus testing at low & high channel is optional.
- 3) Please see attachments for the detailed measurement data and plots showing the maximum SAR location of the EUT.

**8.2.2 FACE UP POSITION**



**802.11a 5.2 GHz**

Channel	f (MHz)	Measured SAR 1g (mW/g)	Power Drift (dB)	Extrapolated <sup>1)</sup> SAR 1g (mW/g)
36	5180			
52	5260	0.039	0.000	0.039
64	5320			

**802.11a 5.5 GHz**

Channel	f (MHz)	Measured SAR 1g (mW/g)	Power Drift (dB)	Extrapolated <sup>1)</sup> SAR 1g (mW/g)
100	5500			
120	5600	0.035	0.000	0.035
140	5700			

**802.11a 5.8 GHz**

Channel	f (MHz)	Measured SAR 1g (mW/g)	Power Drift (dB)	Extrapolated <sup>1)</sup> SAR 1g (mW/g)
149	5745			
157	5785	0.104	0.000	0.104
165	5825			

Notes:

- 1) The exact method of extrapolation is Measured SAR x 10<sup>^(-drift/10)</sup>. The SAR reported at the end of the measurement process by the DASY4 system can be scaled up by the Power drift to determine the SAR at the beginning of the measurement process.
- 2) The SAR measured at the middle channel for this configuration is at least 3 dB lower (0.8 mW/g) than SAR limit (1.6 mW/g), thus testing at low & high channel is optional.
- 3) Please see attachments for the detailed measurement data and plots showing the maximum SAR location of the EUT.



**9 MEASUREMENT UNCERTAINTY**

**9.1 MEASUREMENT UNCERTAINTY FOR 300 MHz – 3000 MHz**

Uncertainty component	Tol. (±%)	Probe Dist.	Div.	Ci (1g)	Ci (10g)	Std. Unc.(±%)	
						Ui (1g)	Ui(10g)
<b>Measurement System</b>							
Probe Calibration	4.80	N	1	1	1	4.80	4.80
Axial Isotropy	4.70	R	1.732	0.707	0.707	1.92	1.92
Hemispherical Isotropy	9.60	R	1.732	0.707	0.707	3.92	3.92
Boundary Effects	1.00	R	1.732	1	1	0.58	0.58
Linearity	4.70	R	1.732	1	1	2.71	2.71
System Detection Limits	1.00	R	1.732	1	1	0.58	0.58
Readout Electronics	1.00	N	1	1	1	1.00	1.00
Response Time	0.80	R	1.732	1	1	0.46	0.46
Integration Time	2.60	R	1.732	1	1	1.50	1.50
RF Ambient Conditions - Noise	1.59	R	1.732	1	1	0.92	0.92
RF Ambient Conditions - Reflections	0.00	R	1.732	1	1	0.00	0.00
Probe Positioner Mechanical Tolerance	0.40	R	1.732	1	1	0.23	0.23
Probe Positioning With Respect to Phantom Shell	2.90	R	1.732	1	1	1.67	1.67
Extrapolation, interpolation, and integration algorithms for max. SAR evaluation	3.90	R	1.732	1	1	2.25	2.25
<b>Test sample Related</b>							
Test Sample Positioning	1.10	N	1	1	1	1.10	1.10
Device Holder Uncertainty	3.60	N	1	1	1	3.60	3.60
Power and SAR Drift Measurement	5.00	R	1.732	1	1	2.89	2.89
<b>Phantom and Tissue Parameters</b>							
Phantom Uncertainty	4.00	R	1.732	1	1	2.31	2.31
Liquid Conductivity - Target	5.00	R	1.732	0.64	0.43	1.85	1.24
Liquid Conductivity - Meas.	8.60	N	1	0.64	0.43	5.50	3.70
Liquid Permittivity - Target	5.00	R	1.732	0.6	0.49	1.73	1.41
Liquid Permittivity - Meas.	3.30	N	1	0.6	0.49	1.98	1.62
<b>Combined Standard Uncertainty</b>			RSS			11.44	10.49
<b>Expanded Uncertainty (95% Confidence Interval)</b>			K=2			22.87	20.98
Notes for table							
1. Tol. - tolerance in influence quantity							
2. N - Nomal							
3. R - Rectangular							
4. Div. - Divisor used to obtain standard uncertainty							
5. Ci - is te sensitivity coefficient							

**9.2 MEASUREMENT UNCERTAINTY 3 GHz – 6 GHz**

Uncertainty component	Tol. (±%)	Probe Dist.	Div.	Ci (1g)	Ci (10g)	Std. Unc.(±%)	
						Ui (1g)	Ui(10g)
<b>Measurement System</b>							
Probe Calibration	4.80	N	1	1	1	4.80	4.80
Axial Isotropy	4.70	R	1.732	0.707	0.707	1.92	1.92
Hemispherical Isotropy	9.60	R	1.732	0.707	0.707	3.92	3.92
Boundary Effects	1.00	R	1.732	1	1	0.58	0.58
Linearity	4.70	R	1.732	1	1	2.71	2.71
System Detection Limits	1.00	R	1.732	1	1	0.58	0.58
Readout Electronics	1.00	N	1	1	1	1.00	1.00
Response Time	0.80	R	1.732	1	1	0.46	0.46
Integration Time	2.60	R	1.732	1	1	1.50	1.50
RF Ambient Conditions - Noise	3.00	R	1.732	1	1	1.73	1.73
RF Ambient Conditions - Reflections	3.00	R	1.732	1	1	1.73	1.73
Probe Positioner Mechanical Tolerance	0.40	R	1.732	1	1	0.23	0.23
Probe Positioning With Respect to Phantom Shell	2.90	R	1.732	1	1	1.67	1.67
Extrapolation, interpolation, and integration algorithms for max. SAR evaluation	3.90	R	1.732	1	1	2.25	2.25
<b>Test sample Related</b>							
Test Sample Positioning	1.10	N	1	1	1	1.10	1.10
Device Holder Uncertainty	3.60	N	1	1	1	3.60	3.60
Power and SAR Drift Measurement	5.00	R	1.732	1	1	2.89	2.89
<b>Phantom and Tissue Parameters</b>							
Phantom Uncertainty	4.00	R	1.732	1	1	2.31	2.31
Liquid Conductivity - Target	5.00	R	1.732	0.64	0.43	1.85	1.24
Liquid Conductivity - Meas.	8.60	N	1	0.64	0.43	5.50	3.70
Liquid Permittivity - Target	5.00	R	1.732	0.6	0.49	1.73	1.41
Liquid Permittivity - Meas.	3.30	N	1	0.6	0.49	1.98	1.62
<b>Combined Standard Uncertainty</b>	RSS					11.66	10.73
<b>Expanded Uncertainty (95% Confidence Interval)</b>	K=2					23.32	21.46
Notes for table							
1. Tol. - tolerance in influence quantity							
2. N - Nomal							
3. R - Rectangular							
4. Div. - Divisor used to obtain standard uncertainty							
5. Ci - is te sensitivity coefficient							

**10 EQUIPMENT LIST AND CALIBRATION**


Name of Equipment	Manufacturer	Type/Model	Serial Number	Cal. Due date		
				MM	DD	Year
Robot - Six Axes	Stäubli	RX90BL	N/A			N/A
Robot Remote Control	Stäubli	CS7MB	3403-91535			N/A
DASY4 Measurement Server	SPEAG	SEUMS001BA	1041			N/A
Probe Alignment Unit	SPEAG	LB (V2)	261			N/A
SAM Phantom (SAM1)	SPEAG	QD000P40CA	1185			N/A
SAM Phantom (SAM2)	SPEAG	QD000P40CA	1050			N/A
Oval Flat Phantom (ELI 4.0)	SPEAG	QD OVA001 B	1003			N/A
Electronic Probe kit	HP	85070C	N/A			N/A
S-Parameter Network Analyzer	Agilent	8753ES-6	US39173569	2	14	2008
E-Field Probe	SPEAG	EX3DV4	3554	4	24	2008
Thermometer	ERTCO	639-1S	1718	11	7	2007
Data Acquisition Electronics	SPEAG	DAE3 V1	427	11	16	2007
System Validation Dipole	SPEAG	D2450V2	706	4	27	2008
System Validation Dipole	SPEAG	D5GHzV2	1003	11	22	2007
Signal Generator	R&S	SMP 04	DE34210	10	9	2007
Power Meter	Giga-tronics	8651A	8651404	4	3	2008
Power Sensor	Giga-tronics	80701A	1834588	4	17	2008
Amplifier	Mini-Circuits	ZVE-8G	360			N/A
Amplifier	Mini-Circuits	ZHL-42W	D072701-5			N/A
Simulating Liquid	CCS	H450	N/A	Within 24 hrs of first test		
Simulating Liquid	CCS	M2450	N/A	Within 24 hrs of first test		
Simulating Liquid	SPEAG	M5200-5800	N/A	Within 24 hrs of first test		

11 PHOTOS

Symbiq Medical Pump



Symbiq Medical Pump



**12 ATTACHMENTS**

<b>No.</b>	<b>Contents</b>	<b>No. Of Pages</b>
1	System Performance Check Plots	8
2	SAR Test Plots	12
3	Certificate of E-Field Probe - EX3DV4SN3554	10
4	Certificate of System Validation Dipole - D2450 SN:706	9
5	Certificate of System Validation Dipole - D5GHzV2 SN:1003	10

**END OF REPORT**