# **EMC Technologies (NZ) Ltd**

Test Report No **70101.1** Report date: 8 February 2007

## **Radio Frequency Hazard Information**

As per Section 1.1310 and Section 2.1091 certification of this transmitter is sought using the Controlled / Occupational exposure limits as detailed in OST/OET Bulletin Number 65 as a power of 25 watts is to be used in a mobile environment where the use of the transmitter will be employment related.

Calculations have been made using the General Public/Uncontrolled Exposure limits.

Minimum safe distances have been calculated below.

Power density,  $W/m^2 = E^2/3770$ 

- Occupational / Controlled Exposure limit will be 1.46 mW/cm<sup>2</sup> (f/300 = 440 MHz/300)
- General Population / Uncontrolled exposure limit will be  $0.29~\text{mW/cm}^2$  (f/1500 = 440 MHz/1500)

The minimum distance from the antenna at which the MPE is met is calculated from the equation relating field strength in V/m, transmit power in watts, transmit antenna gain, transmitter duty cycle and separation distance in metres:

E, 
$$V/m = (\sqrt{(30 * P * G)}) / d$$

#### Controlled

E = 1.46 mW/cm<sup>2</sup> = E<sup>2</sup>/3770 E= $\sqrt{1.46*3770}$ E = 74.2 V/m

#### Uncontrolled

E = 0.29 mW/cm<sup>2</sup> = E<sup>2</sup>/3770 E=  $\sqrt{0.29*3770}$ E = 33.1 V/m

The rated maximum transmitter power = 25 watts.

Transmitter operated using a quarter wave whip antenna with a gain of 2.15 dBi (1.64).

The transmitter is a push to talk device that would typically be used with a duty cycle of 50% in a 6 minute period or a 30 minute period.

## **Controlled**

 $d = \sqrt{(30 * P * G*DC) / E}$  $d = \sqrt{(30 * 25.0 * 1.64 * 0.5) / 74.2}$ 

d = 0.3342 metres or 34 cm

## Uncontrolled

 $d = \sqrt{(30 * 25.0 * 1.64 * 0.5) / 33.1}$ 

d = 0.7492 metres or 75 cm

## **Result:** Complies

Phone: +64 9 360 0862 Fax: +64 9 360 0861