

RAE Systems Inc

SAR COMPLIANCE REPORT

Report Type:
FCC SAR assessment report

Model:
BWS1

REPORT NUMBER:
180601421SHA-002

ISSUE DATE:
August 24, 2018

DOCUMENT CONTROL NUMBER:
TTRFFCCSAR-01_V1 © 2018 Intertek



Applicant: RAE Systems Inc
1349 Moffett Park Drive Sunnyvale, CA 94089, USA

Manufacturer: RAE Systems Inc
1349 Moffett Park Drive Sunnyvale, CA 94089, USA

Manufacturing site: RAE Systems (Shanghai) Inc
990 East Huiwang Road, Jiading District, Shanghai, China

FCC ID: SU3BWS1

IC: 20969-BWS1

SUMMARY:

The equipment complies with the requirements according to the following standard(s) or Specification:

KDB447498 D01 General RF Exposure Guidance v06

FCC Part2.1091, FCC Part2.1093 FCC Part1.1307(b)

PREPARED BY:

REVIEWED BY:



Project Engineer
Erick Liu

Reviewer
Daniel Zhao

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

Revision History

| Report No. | Version | Description | Issued Date |
|------------------|---------|-------------------------|--------------|
| 180601421SHA-002 | Rev. 01 | Initial issue of report | Aug 24, 2018 |
| | | | |
| | | | |

1 GENERAL INFORMATION

1.1 Description of Equipment Under Test (EUT)

| | |
|-----------------------|---|
| Product name: | Honeywell BW Solo |
| Type/Model: | BWS1 |
| Description of EUT: | The EUT is a single gas monitor with a BLE module, which is divided into 20 configurations according to the type of gas measurement sensor, each configuration has two colors: black and yellow. We tested all the configurations, and the BWS1-ML-Y, which uses the CO gas measurement sensor with yellow shell is the worst case configuration. |
| Rating: | Built-in battery DC 3.6V |
| Category of EUT: | Class B |
| EUT type: | <input checked="" type="checkbox"/> Table top <input type="checkbox"/> Floor standing |
| Software Version: | 1.0 |
| Hardware Version: | Rev. A |
| Sample received date: | July 11, 2018 |
| Date of test: | July 25, 2018-August 08, 2018 |

1.2 Technical Specification

| | |
|----------------------|---------------|
| Frequency Range: | 2402-2480MHz |
| Support Standards: | IEEE 802.15.1 |
| Type of Modulation: | GFSK |
| Channel Number: | 40 |
| Channel Separation: | 2MHz |
| Antenna Information: | 2.1dBi, SMD |

1.3 Description of Test Facility

| | |
|------------|--|
| Name: | Intertek Testing Services Shanghai |
| Address: | Building 86, No. 1198 Qinzhou Road(North), Shanghai 200233, P.R. China |
| Telephone: | 86 21 61278200 |
| Telefax: | 86 21 54262353 |

| | |
|---|--|
| The test facility is recognized, certified, or accredited by these organizations: | CNAS Accreditation Lab Registration No. CNAS L0139 |
| | FCC Accredited Lab Designation Number: CN1175 |
| | IC Registration Lab Registration code No.: 2042B-1 |
| | VCCI Registration Lab Registration No.: R-4243, G-845, C-4723, T-2252 |
| | NVLAP Accreditation Lab NVLAP LAB CODE: 200849-0 |
| | A2LA Accreditation Lab Certificate Number: 3309.02 |

TEST REPORT

2 SAR Assessment

Test result: Pass

2.1 SAR Test Exclusion Limit

100 MHz – 6 GHz and ≤ 50 mm

| MHz | 5 | 10 | 15 | 20 | 25 | mm |
|------|-----|-----|-----|-----|-----|--|
| 150 | 39 | 77 | 116 | 155 | 194 | <i>SAR Test Exclusion Threshold (mW)</i> |
| 300 | 27 | 55 | 82 | 110 | 137 | |
| 450 | 22 | 45 | 67 | 89 | 112 | |
| 835 | 16 | 33 | 49 | 66 | 82 | |
| 900 | 16 | 32 | 47 | 63 | 79 | |
| 1500 | 12 | 24 | 37 | 49 | 61 | |
| 1900 | 11 | 22 | 33 | 44 | 54 | |
| 2450 | 10 | 19 | 29 | 38 | 48 | |
| 3600 | 8 | 16 | 24 | 32 | 40 | |
| 5200 | 7 | 13 | 20 | 26 | 33 | |
| 5400 | 6 | 13 | 19 | 26 | 32 | |
| 5800 | 6 | 12 | 19 | 25 | 31 | |
| MHz | 30 | 35 | 40 | 45 | 50 | |
| 150 | 232 | 271 | 310 | 349 | 387 | <i>SAR Test Exclusion Threshold (mW)</i> |
| 300 | 164 | 192 | 219 | 246 | 274 | |
| 450 | 134 | 157 | 179 | 201 | 224 | |
| 835 | 98 | 115 | 131 | 148 | 164 | |
| 900 | 95 | 111 | 126 | 142 | 158 | |
| 1500 | 73 | 86 | 98 | 110 | 122 | |
| 1900 | 65 | 76 | 87 | 98 | 109 | |
| 2450 | 57 | 67 | 77 | 86 | 96 | |
| 3600 | 47 | 55 | 63 | 71 | 79 | |
| 5200 | 39 | 46 | 53 | 59 | 66 | |
| 5400 | 39 | 45 | 52 | 58 | 65 | |
| 5800 | 37 | 44 | 50 | 56 | 62 | |

TEST REPORT
100 MHz – 6 GHz and > 50 mm

| MHz | 50 | 60 | 70 | 80 | 90 | 100 | 110 | 120 | 130 | 140 | 150 | 160 | 170 | 180 | 190 | mm |
|------|-----|-----|-----|-----|-----|-----|-----|-----|-----|------|------|------|------|------|------|----|
| 100 | 474 | 481 | 487 | 494 | 501 | 507 | 514 | 521 | 527 | 534 | 541 | 547 | 554 | 561 | 567 | mW |
| 150 | 387 | 397 | 407 | 417 | 427 | 437 | 447 | 457 | 467 | 477 | 487 | 497 | 507 | 517 | 527 | |
| 300 | 274 | 294 | 314 | 334 | 354 | 374 | 394 | 414 | 434 | 454 | 474 | 494 | 514 | 534 | 554 | |
| 450 | 224 | 254 | 284 | 314 | 344 | 374 | 404 | 434 | 464 | 494 | 524 | 554 | 584 | 614 | 644 | |
| 835 | 164 | 220 | 275 | 331 | 387 | 442 | 498 | 554 | 609 | 665 | 721 | 776 | 832 | 888 | 943 | |
| 900 | 158 | 218 | 278 | 338 | 398 | 458 | 518 | 578 | 638 | 698 | 758 | 818 | 878 | 938 | 998 | |
| 1500 | 122 | 222 | 322 | 422 | 522 | 622 | 722 | 822 | 922 | 1022 | 1122 | 1222 | 1322 | 1422 | 1522 | |
| 1900 | 109 | 209 | 309 | 409 | 509 | 609 | 709 | 809 | 909 | 1009 | 1109 | 1209 | 1309 | 1409 | 1509 | |
| 2450 | 96 | 196 | 296 | 396 | 496 | 596 | 696 | 796 | 896 | 996 | 1096 | 1196 | 1296 | 1396 | 1496 | |
| 3600 | 79 | 179 | 279 | 379 | 479 | 579 | 679 | 779 | 879 | 979 | 1079 | 1179 | 1279 | 1379 | 1479 | |
| 5200 | 66 | 166 | 266 | 366 | 466 | 566 | 666 | 766 | 866 | 966 | 1066 | 1166 | 1266 | 1366 | 1466 | |
| 5400 | 65 | 165 | 265 | 365 | 465 | 565 | 665 | 765 | 865 | 965 | 1065 | 1165 | 1265 | 1365 | 1465 | |
| 5800 | 62 | 162 | 262 | 362 | 462 | 562 | 662 | 762 | 862 | 962 | 1062 | 1162 | 1262 | 1362 | 1462 | |

< 100 MHz and < 200 mm

| MHz | < 50 | 50 | 60 | 70 | 80 | 90 | 100 | 110 | 120 | 130 | 140 | 150 | 160 | 170 | 180 | 190 | mm |
|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|----|
| 100 | 237 | 474 | 481 | 487 | 494 | 501 | 507 | 514 | 521 | 527 | 534 | 541 | 547 | 554 | 561 | 567 | mW |
| 50 | 308 | 617 | 625 | 634 | 643 | 651 | 660 | 669 | 677 | 686 | 695 | 703 | 712 | 721 | 729 | 738 | |
| 10 | 474 | 948 | 961 | 975 | 988 | 1001 | 1015 | 1028 | 1041 | 1055 | 1068 | 1081 | 1095 | 1108 | 1121 | 1135 | |
| 1 | 711 | 1422 | 1442 | 1462 | 1482 | 1502 | 1522 | 1542 | 1562 | 1582 | 1602 | 1622 | 1642 | 1662 | 1682 | 1702 | |
| 0.1 | 948 | 1896 | 1923 | 1949 | 1976 | 2003 | 2029 | 2056 | 2083 | 2109 | 2136 | 2163 | 2189 | 2216 | 2243 | 2269 | |
| 0.05 | 1019 | 2039 | 2067 | 2096 | 2125 | 2153 | 2182 | 2211 | 2239 | 2268 | 2297 | 2325 | 2354 | 2383 | 2411 | 2440 | |
| 0.01 | 1185 | 2370 | 2403 | 2437 | 2470 | 2503 | 2537 | 2570 | 2603 | 2637 | 2670 | 2703 | 2737 | 2770 | 2803 | 2837 | |

TEST REPORT

2.2 Assessment Results

The highest EIRP adjusted with tune-up tolerance is 4.26dBm = 2.67mW < 10mW (Test Exclusion Thresholds of 2450MHz at 5mm). Therefore, the SAR requirement is deemed to be satisfied without test.

***** END *****