

EMC TEST REPORT for Intentional Radiator

No. 140401054SHA-001

Applicant : RAE Systems Inc.
3775 N. 1st St., San Jose, California USA 95134

Manufacturer : RAE Systems Inc.
3775 N. 1st St., San Jose, California USA 95134

Product Name : RAEMesh Radio

Type/Model : RM900

SUMMARY

The equipment complies with the requirements according to the following standard(s):

47CFR Part 15 (2013): Radio Frequency Devices


ANSI C63.4 (2003): American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz

RSS-210 Issue 8 (December 2010): Low-power Licence-exempt Radiocommunication Devices (All Frequency Bands): Category I Equipment

RSS-Gen Issue 3 (December 2010): General Requirements and Information for the Certification of Radiocommunication Equipment


Date of issue: May 23, 2014

Prepared by:



Wakeyou Wang (*Project Engineer*)

Reviewed by:



Daniel Zhao (*Reviewer*)



Description of Test Facility

Name: Intertek Testing Services Limited Shanghai
Address: Building 86, No. 1198 Qinzhou Rd., North, Shanghai 200233, P.R. China

FCC Registration Number: 236597
IC Assigned Code: 2042B-1

Name of contact: Jonny Jing
Tel: +86 21 61278271
Fax: +86 21 54262353

Content

SUMMARY	1
DESCRIPTION OF TEST FACILITY	2
1. GENERAL INFORMATION	4
1.1 Applicant Information.....	4
1.2 Identification of the EUT	4
1.3 Technical specification	4
1.4 Mode of operation during the test / Test peripherals used.....	5
2. TEST SPECIFICATION	6
2.1 Instrument list	6
2.2 Test Standard	6
3. RADIATED EMISSION	8
3.1 Test limit	8
3.2 Test Configuration	8
3.3 Test procedure and test setup.....	9
3.4 Test protocol	10
4. ASSIGNED BANDWIDTH (20DB BANDWIDTH)	11
4.1 Limit.....	13
4.2 Test Configuration	13
4.3 Test procedure and test setup.....	13
4.4 Test protocol	14
5. POWER LINE CONDUCTED EMISSION	15
5.1 Limit.....	15
5.2 Test configuration	15
5.3 Test procedure and test set up.....	16
5.4 Test protocol	17
6. OCCUPIED BANDWIDTH	18
6.1 Test limit	18
6.2 Test Configuration	18
6.3 Test procedure and test setup.....	18
6.4 Test protocol	18
7. SPURIOUS EMISSION FOR RECEIVER	21
7.1 Test limit	21
7.2 Test Configuration	21
7.3 Test procedure and test setup.....	21
7.4 Test protocol	22



1. General Information

1.1 Applicant Information

Applicant: RAE Systems Inc.
3775 N. 1st St., San Jose, California USA 95134

Name of contact: James Liu

Tel: 408-9528200
Fax: 408-9528480
Email: jliu@raesystems.com

Manufacturer: RAE Systems Inc.
3775 N. 1st St., San Jose, California USA 95134

Sample received date : April 17, 2014
Date of test : April 17, 2014 ~ April 23, 2014

1.2 Identification of the EUT

Equipment: RAEMesh Radio
Type/model: RM900
FCC ID: SU3RM900
IC: Not applied

1.3 Technical specification

Operation Frequency Band: 906 - 924 MHz
Modulation: O-QPSK
Antenna Designation: Omnidirectional antenna, PCB antenna
Gain of Antenna: 0.7dBd (2.0dBi) for Omnidirectional antenna;
-0.8dBd (0.5dBi) for PCB antenna

Rating: DC 3.3V powered by the debug board

Description of EUT: Here is one model only.
The EUT is a wireless RF module for data transmission
(IEEE 802.15.4 compliant Zigbee-ready transceiver).



Channel Description:

Channel Identifier	Frequency (MHz)	Channel Identifier	Frequency (MHz)
1	906	6	916
2	908	7	918
3	910	8	920
4	912	9	922
5	914	10	924

Software applied: SSCOM3.2

1.4 Mode of operation during the test / Test peripherals used

While testing transmitter mode of the EUT, the internal modulation was applied.

While testing receiver mode of EUT, the signal generator with a transmitting antenna generating 916MHz sine wave is put in close proximity to the EUT.

For the EUT can be used in any axes as the user wants, it was set up in three axis (X, Y, Z) while the antenna always was kept vertically and performed test. The three axes were tested one by one while the test receiver worked as “max hold” continuously and the highest reading among the whole test procedure was recorded.

Maximum allowable power level setting in the controlling software is **-9dBm**.

The lowest, middle and highest channel were tested as representatives (906MHz,916MHz and 924MHz).

Test Peripherals:

PC: HP ProBook 6450b

2. Test Specification

2.1 Instrument list

Equipment	Type	Manu.	Internal no.	Cal. Date	Due date
Test Receiver	ESCS 30	R&S	EC 2107	2013-10-21	2014-10-20
Test Receiver	ESIB 26	R&S	EC 3045	2013-10-20	2014-10-19
A.M.N.	ESH2-Z5	R&S	EC 3119	2014-1-9	2015-1-8
A.M.N.	ENV 216	R&S	EC 3393	2013-8-9	2014-8-8
A.M.N.	ENV 216	R&S	EC 3394	2013-8-9	2014-8-8
A.M.N.	ENV4200	R&S	EC3558	2013-8-9	2014-8-8
Ultra-broadband antenna	HL 562	R&S	EC 3046-1	2013-5-16	2014-5-14
Bilog Antenna	CBL 6112D	TESEQ	EC 4206	2013-4-28	2015-4-27
Horn antenna	HF 906	R&S	EC 3049	2013-4-28	2015-4-27
Pre-amplifier	Pre-amp 18	R&S	EC 3222	2014-4-12	2015-4-11
Semi-anechoic chamber	-	Albatross project	EC 3048	2013-5-12	2014-5-11
High Pass Filter	WHKX 1.0/15G-10SS	Wainwright	EC4297-1	2014-1-8	2015-1-7
Power sensor / Power meter	N1911A/N1921A	Agilent	EC4318	2014-04-12	2015-04-11

2.2 Test Standard

47CFR Part 15 (2013)
 ANSIC63.4 (2003)
 RSS-210 Issue 8 (December 2010)
 RSS-Gen Issue 3 (December 2010)

2.3 Test Summary

This report applies to tested sample only. This report shall not be reproduced in part without written approval of Intertek Testing Service Shanghai Limited.

TEST ITEM	FCC REFERANCE	IC REFERANCE	RESULT
Radiated emission	15.249 & 15.205	RSS-210 Issue 8 Annex A2.9 & Clause 2.2	Pass
Assigned bandwidth (20dB bandwidth)	15.215(c)	-	Pass
Occupied bandwidth	-	RSS-Gen Issue 3 Clause 4.6.1	Pass
Power line conducted emission	15.207	RSS-Gen Issue 3 Clause 7.2.4	Pass
Spurious emission for receiver	15B	RSS-Gen	Pass

2.4 Data rate VS power

The data rate of EUT is fixed and cannot be adjusted.

3. Radiated emission

Test result: **PASS**


3.1 Test limit

Fundamental Frequency (MHz)	Fundamental limit (dBuV/m)	Harmonic limit (dBuV/m)
<input checked="" type="checkbox"/> 902 - 928	94	54
<input type="checkbox"/> 2400 - 2483.5	94	54
<input type="checkbox"/> 5725 - 5875	94	54
<input type="checkbox"/> 24000 - 24250	108	68

The radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) showed as below:

Frequency (MHz)	Field Strength (dBuV/m)	Measurement Distance (m)
30 - 88	40.0	3
88 - 216	43.5	3
216 - 960	46.0	3
Above 960	54.0	3

3.2 Test Configuration



3.3 Test procedure and test setup

The measurement was applied in a semi-anechoic chamber. While testing for spurious emission higher than 1GHz, if applied, the pre-amplifier would be equipped just at the output terminal of the antenna.

The EUT and simulators were placed on a 0.8m high wooden turntable above the horizontal metal ground plane. The turn table rotated 360 degrees to determine the position of the maximum emission level. The EUT was set 3 meters away from the receiving antenna which was mounted on an antenna mast. The antenna moved up and down between from 1meter to 4 meters to find out the maximum emission level.

The radiated emission was measured using the Spectrum Analyzer with the resolutions bandwidth set as:

RBW = 100kHz, VBW = 300kHz (30MHz~1GHz for PK)

RBW = 1MHz, VBW = 3MHz (>1GHz for PK);

RBW = 1MHz, VBW = 10Hz (>1GHz for AV);

3.4 Test protocol

Omnidirectional Antenna Applied

CH	Antenna	Frequency (MHz)	Correct Factor (dB/m)	Corrected Reading (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
L	V	906.69	25.10	94.40	/	/	PK
	V	906.69	25.10	93.10	94.00	0.90	QP
	H	1112.35	-18.90	43.20	54.00	10.80	PK
	V	1814.63	-14.30	40.40	54.00	13.60	PK
	V	2603.21	-10.80	42.20	54.00	11.80	PK
	V	3054.11	-8.70	50.90	54.00	3.10	PK
	V	3625.25	-6.50	43.60	54.00	10.40	PK
	V	5719.43	-1.60	44.80	54.00	9.20	PK
M	V	916.47	25.10	94.70	/	/	PK
	V	916.47	25.10	93.40	94.00	0.60	QP
	H	1060.12	-19.10	42.90	54.00	11.10	PK
	H	1561.12	-16.70	43.50	54.00	10.50	PK
	H	1821.64	-14.60	43.70	54.00	10.30	PK
	V	2132.26	-12.70	43.50	54.00	10.50	PK
	V	3655.31	-6.40	43.50	54.00	10.50	PK
	V	4787.58	-3.60	41.90	54.00	12.10	PK
H	V	924.19	25.20	94.50	/	/	PK
	V	924.19	25.20	93.30	94.00	0.70	QP
	H	1120.24	-18.80	46.50	54.00	7.50	PK
	H	1781.56	-14.90	45.80	54.00	8.20	PK
	H	4106.21	-5.10	46.10	54.00	7.90	PK
	V	1060.12	-19.10	47.30	54.00	6.70	PK
	V	2122.24	-12.70	44.50	54.00	9.50	PK
	V	2772.39	-9.20	38.90	54.00	15.10	PK

PCB Antenna Applied

CH	Antenna	Frequency (MHz)	Correct Factor (dB/m)	Corrected Reading (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
L	V	906.69	25.10	90.50	94.00	3.50	PK
	H	1112.35	-18.90	43.50	54.00	10.50	PK
	H	1320.64	-18.00	41.90	54.00	12.10	PK
	V	2012.02	-13.20	44.70	54.00	9.30	PK
	V	3054.11	-8.70	43.60	54.00	10.40	PK
	V	4777.55	-3.60	41.50	54.00	12.50	PK
	V	5719.43	-1.60	43.10	54.00	10.90	PK
M	V	916.47	25.10	91.30	94.00	2.70	PK
	H	1060.12	-19.10	41.60	54.00	12.40	PK
	H	1240.48	-18.30	40.90	54.00	13.10	PK
	V	1561.12	-16.70	43.50	54.00	10.50	PK
	V	1821.64	-14.60	43.70	54.00	10.30	PK
	V	4787.57	-3.60	41.30	54.00	12.70	PK
	V	5889.78	-1.30	40.40	54.00	13.60	PK
H	V	924.19	25.20	90.70	94.00	3.30	PK
	H	1420.84	-17.50	40.20	54.00	13.80	PK
	H	1501.00	-17.20	40.60	54.00	13.40	PK
	H	4246.49	-4.80	38.30	54.00	15.70	PK
	V	1060.12	-19.10	46.80	54.00	7.20	PK
	V	1771.54	-15.00	42.10	54.00	11.90	PK
	V	3414.83	-7.20	37.90	54.00	16.10	PK

- Remark: 1. For fundamental emission test, no pre-amplifier is employed.
 2. The Pulse-repetition frequency for fundamental emission is higher than 20Hz. Therefore, the QP detector can be applied for fundamental emission test.
 3. Correct Factor = Antenna Factor + Cable Loss (-Amplifier, is employed)
 4. Corrected Reading = Original Receiver Reading + Correct Factor
 5. Margin = limit – Corrected Reading
 6. If the PK reading is lower than AV limit, the AV test can be elided.
 7. The shaded data is the fundamental emission.

Example: Assuming Antenna Factor = 30.20dB/m, Cable Loss = 2.00dB,
Gain of Preamplifier = 32.00dB, Original Receiver Reading = 10dBuV.
Then Correct Factor = $30.20 + 2.00 - 32.00 = 0.20\text{dB/m}$; Corrected Reading =
 $10\text{dBuV} + 0.20\text{dB/m} = 10.20\text{dBuV/m}$
Assuming limit = 54dBuV/m, Corrected Reading = 10.20dBuV/m, then Margin =
 $54 - 10.20 = 43.80\text{dBuV/m}$

4. Assigned bandwidth (20dB bandwidth)

Test result: PASS

4.1 Limit

Intentional radiators must be designed to ensure that the 20 dB bandwidth of the emission is contained within the allocated frequency band as clause 3.1 shows.

If frequency stability is not specified in the regulations, it is recommended that the fundamental emission be kept within at least the central 80% of the permitted band in order to minimize the possibility of out-of-band operation.

4.2 Test Configuration



See clause 3.2.

4.3 Test procedure and test setup

The 20dB Bandwidth per FCC §15.215(c) is measured using the Spectrum Analyzer.

4.4 Test protocol

20dB bandwidth (MHz)	80% of permitted band (MHz)	Result
905.63 ~ 924.46	904.60 ~ 925.40	Pass



5. Power line conducted emission


Test result: Pass

5.1 Limit

Frequency of Emission (MHz)	Conducted Limit (dBuV)	
	QP	AV
0.15-0.5	66 to 56*	56 to 46 *
0.5-5	56	46
5-30	60	50

* Decreases with the logarithm of the frequency.

5.2 Test configuration



For table top equipment, wooden support is 0.8m height table


For floor standing equipment, wooden support is 0.1m height rack.

5.3 Test procedure and test set up

The EUT are connected to the main power through a line impedance stabilization network (LISN). This provides a $50\Omega/50\mu\text{H}$ coupling impedance for the measuring equipment. The peripheral devices are also connected to the main power through a LISN that provides a $50\Omega/50\mu\text{H}$ coupling impedance with 50Ω termination.

Both sides (Line and Neutral) of AC line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.4 on conducted measurement. The bandwidth of the test receiver is set at 9 kHz.

5.4 Test protocol



Frequency (MHz)	LISN Factor (dB)	Cable Loss (dB)	Corrected Reading (dBµV)		Limit (dBµV)		Margin (dB)	
			QP	AV	QP	AV	QP	AV
0.20 (N)	2.70	0.30	54.81	45.91	63.82	53.82	9.01	7.91
0.26 (N)	2.70	0.30	54.01	46.00	61.35	51.35	7.34	5.35
0.73 (L)	2.70	0.30	53.39	41.13	56.00	46.00	2.61	4.87
1.41 (L)	2.70	0.30	50.26	44.68	56.00	46.00	5.74	1.32
2.81 (N)	2.70	0.30	48.05	39.16	56.00	46.00	7.95	6.84
4.22 (L)	2.70	0.30	47.71	39.79	56.00	46.00	8.29	6.21

Remark: 1. Corrected Reading = LISN Factor (dB) + Cable Loss (dB) + receiver reading.
 2. Margin (dB) = Limit - Corrected Reading.

6. Occupied Bandwidth

Test Status: Tested

6.1 Test limit

None

6.2 Test Configuration

See clause 3.2.

6.3 Test procedure and test setup


The occupied bandwidth per RSS-Gen Issue 3 Clause 4.6.1 was measured using the Spectrum Analyzer.

6.4 Test protocol


Temperature : 22 °C
Relative Humidity : 43 %

Channel	Occupied Bandwidth (kHz)	Max. reading (kHz)
L	750	750
M	750	
H	750	


Chanel L



Chanel M



Chanel H



7. Spurious emission for receiver

Test result: Pass

7.1 Test limit

The spurious emission shall test through 3 times tuneable or local oscillator frequency whichever is the higher, without exceeding 40 GHz.

1) If a conducted measurement is made, no spurious output signals appearing at the antenna terminals shall exceed 2nW per any 4 kHz spurious frequency in the band 30-1000 MHz, or 5nW above 1 GHz.

2) If a radiated measurement is made, all spurious emissions shall comply with the limits of Table below:

Frequency (MHz)	Field Strength (dBuV/m)	Measurement Distance (m)
30 - 88	40.0	3
88 - 216	43.5	3
216 - 960	46.0	3
Above 960	54.0	3

7.2 Test Configuration

Please refer to clause 3.2

7.3 Test procedure and test setup

Please refer to clause 3.2

7.4 Test protocol

Polarization	Frequency (MHz)	Correct Factor (dB/m)	Corrected Reading (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
H	154.41	14.20	33.80	43.50	9.70	PK
H	191.34	12.00	40.00	43.50	3.50	PK
H	274.93	14.40	43.30	46.00	2.70	PK
H	381.84	18.20	36.60	46.00	9.40	PK
H	653.99	22.70	40.40	46.00	5.60	PK
H	4080.16	-5.20	41.20	54.00	12.80	PK
V	30.00	22.00	37.00	40.00	3.00	PK
V	191.34	12.00	35.50	43.50	8.00	PK
V	344.91	16.60	41.70	46.00	4.30	PK
V	414.89	19.30	38.10	46.00	7.90	PK
V	685.209	22.50	40.80	46.00	5.20	PK
V	4763.53	-3.70	42.10	54.00	11.90	PK

- Remark: 1. Correct Factor = Antenna Factor + Cable Loss (-Amplifier, is employed)
 2. Corrected Reading = Original Receiver Reading + Correct Factor
 3. Margin = limit – Corrected Reading

Example: Assuming Antenna Factor = 30.20dB/m, Cable Loss = 2.00dB,
 Original Receiver Reading = 10dBuV.

Then Correct Factor = 30.20 + 2.00 = 32.20dB/m; Corrected Reading = 10dBuV + 32.20dB/m = 42.20dBuV/m

Assuming limit = 54dBuV/m, Corrected Reading = 42.20dBuV/m, then Margin = 54 - 42.20 = 11.80dBuV/m