

FCC TEST REPORT

for

SOUNDCAST LLC

Bluetooth and NFC Speaker

Model Number: VG7

FCC ID: SUD-VGBT07A

Prepared for : SOUNDCAST LLC
Address : 9771-E Clairemont Mesa Blvd.San Diego,CA92124

Prepared by : Keyway Testing Technology Co., Ltd.
Address : Building 1, Baishun Industrial Zone, Zhangmutou Town,
Dongguan, Guangdong, China

Tel: 86-769-8718 2258
Fax: 86-769-8718 1058

Report No. : 17KWE025060F
Date of Test : Jan. 20~ Feb.10, 2017
Date of Report : Feb. 14, 2017

TABLE OF CONTENTS

	Page
Test Report Declaration	4
1. TEST SUMMARY	4
2. GENERAL PRODUCT INFORMATION	5
2.1. Product Function.....	5
2.2. Description of Device (EUT)	5
2.3. Independent Operation Modes.....	6
2.4. Product Version	6
2.5. TEST SITES.....	6
2.6. List of Test and Measurement Instruments	7
3. TEST SET-UP AND OPERATION MODES.....	8
3.1. Principle of Configuration Selection.....	8
3.2. Block Diagram of Test Set-up.....	8
3.3. Test Operation Mode and Test Software.....	8
3.4. Special Accessories and Auxiliary Equipment.....	8
3.5. Countermeasures to Achieve EMC Compliance	8
4. EMISSION TEST RESULTS	9
4.1. Conducted Emission at the Mains Terminals Test.....	9
4.2. Radiated Emission Test.....	14
5. BAND EDGE COMPLIANCE TEST	21
5.1. Limits	21
5.2. Test setup	21
5.3. TEST Procedure	22
6. 6DB OCCUPY BANDWIDTH	28
6.1. Limits	28
6.2. TEST PROCEDURE.....	28
7. OUTPUT POWER TEST	31
7.1. Limits	31
7.2. Test Procedure.....	31
7.3. Test setup	31
7.4. Test result.....	31
8. DUTY CYCLE.....	34
8.1. Test Procedure.....	34
8.2. Test Setup.....	34
9. POWER SPECTRAL DENSITY TEST.....	36
9.1. Limits	36
9.2. Test setup	36
9.3. Test result.....	36
10. ANTENNA REQUIREMENTS	39
10.1. Limits	39
10.2. Result	39

Keyway Testing Technology Co., Ltd.

Applicant:	SOUNDCAST LLC		
Address:	9771-E Clairemont Mesa Blvd.San Diego,CA92124		
Manufacturer:	Gigatek Electronics(DongGuan) Co.; LTD.		
Address:	No.132,DongXing E.Rd., DongXing Industrial VG7, KengMei Village, DongKeng Town, DongGuan City, GuangDong, China		
E.U.T:	Bluetooth and NFC Speaker		
Model Number:	VG7		
Serial Model:	N/A		
Trade Name:	Soundcast	Serial No.:	-----
Date of Receipt:	Jan. 09, 2017	Date of Test:	Jan. 20~ Feb.10, 2017
Test Specification:	FCC Part 15, Subpart C Section 15.247: 2015 ANSI C63.10:2013 KDB558074 D01 DTS Meas Guidance v03r05		
Test Result:	The equipment under test was found to be compliance with the requirements of the standards applied.		
		Issue Date: Feb. 14, 2017	
Tested by:	Reviewed by:	Approved by:	
			
_____ Keven Wu / Engineer	_____ Mark Li / Supervisor	 _____ Andy Gao / Supervisor	
Other Aspects:	None.		
<i>Abbreviations: OK/P=passed fail/F=failed n.a/N=not applicable E.U.T=equipment under tested</i>			
<i>This test report is based on a single evaluation of one sample of above mentioned products. It is not permitted to be duplicated in extracts without written approval of Keyway Testing Technology Co., Ltd.</i>			

1.TEST SUMMARY

Test Items	Test Requirement	Result
Conducted Emissions	15.207	PASS
Radiated Emissions	15.205(a) /15.209/ 15.247(d)	PASS
6dB&99% Bandwidth	15.247(a)(2)	PASS
Power density	15.247(e)	PASS
Maximum Peak Output Power	15.247(b)(3)	PASS
Emissions from out of band	15.247(d)	PASS
Antenna Requirement	15.203	PASS

2. GENERAL PRODUCT INFORMATION

2.1. Product Function

Refer to Technical Construction Form and User Manual.

2.2. Description of Device (EUT)

Product Name:	Bluetooth and NFC Speaker
Model No.:	VG7
Frequency Rang	2402~2480 MHz
Modulation type:	GFSK
Channel numbers:	40 channels for BT4.0, 79 channels for BT3.0
Channel separation:	2MHz for BT4.0, 1MHz for BT3.0
Antenna Type:	PCB Antenna
Antenna gain:	4.01dBi
Power Supply:	battery 7.4V
Adapter:	GOLDEN PROFIT ELECTRONICS LTD. MODEL: GPE060D-120500D INPUT: AC100-240V 50/60Hz 1.5A OUTPUT: DC 12V/5000mA 60W

2.3. Independent Operation Modes

The basic operation modes are:

2.3.1. EUT work BT mode, and Test Mode as below:

Final Test Mode	Description
Mode 1	CH00
Mode 2	CH19
Mode 3	CH39
Mode 4	Link Mode

2.4. Product Version

Product SW version	V0.8.6
Product HW version	X1R2
Radio SW version	V001B002
Radio HW version	JS-BTM8670-V0.01D
Test SW Version	Blue Test3
RF power setting in TEST SW	3dBm

2.5. TEST SITES

2.5.1. Test Facilities

Lab Qualifications : Certificated by Industry Canada
Registration No.: 9868A
Date of registration: December 8, 2011

Certificated by FCC, USA
Registration No.: 370994
Date of registration: February 21, 2012

Certificated by CNAS China
Registration No.: CNAS L5783
Date of registration: August 8, 2012

2.6. List of Test and Measurement Instruments

2.6.1. For conducted emission at the mains terminals test

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
EMI Test Receiver	Rohde&Schwarz	ESCI	101156	Apr. 09,16	Apr. 08,17
Artificial Mains Network	Rohde&Schwarz	ENV216	101315	Apr. 09,16	Apr. 08,17
Artificial Mains Network (AUX)	Rohde&Schwarz	ENV216	101314	Apr. 09,16	Apr. 08,17
RF Cable	FUJIKURA	3D-2W	944 Cable	Apr. 09,16	Apr. 08,17

2.6.2. For radiated emission test

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
EMI Test Receiver	Rohde&Schwarz	ESCI	101156	Apr. 09,16	Apr. 08,17
System Simulator	Agilent	E5515C	GB43130245	Apr. 09,16	Apr. 08,17
Power Splitter	Weinschel	1506A	NW425	Apr. 09,16	Apr. 08,17
Bilog Antenna	ETS-LINDGREEN	3142D	135452	Apr. 09,16	Apr. 08,17
Spectrum Analyzer	Agilent	E4411B	MY4511304	Apr. 09,16	Apr. 08,17
Spectrum Analyzer	R&S	FSV40	132.1.3008K39-100967	Apr. 09,16	Apr. 08,17
3m Semi-anechoic Chamber	ETS-LINDGREEN	966	KW01	Apr. 09,16	Apr. 08,17
Signal Amplifier	SONOMA	310	187016	Apr. 09,16	Apr. 08,17
Signal Amplifier	Agilent	8449B	3008A00251	Apr. 09,16	Apr. 08,17
RF Cable	IMRO	IMRO-400	966 Cable 1#	Apr. 09,16	Apr. 08,17
MULTI-DEVICE Controller	ETS-LINDGREEN	2090	126913	Apr. 09,16	Apr. 08,17
Horn Antenna	DAZE	ZN30701	11003	Apr. 09,16	Apr. 08,17
Horn Antenna	SCHWARZBECK	BBHA9170	9170-068	Apr. 09,16	Apr. 08,17
Spectrum Analyzer	Agilent	8593E	3911A04271	Apr. 09,16	Apr. 08,17
Spectrum Analyzer	Agilent	E4408B	MY44211125	Apr. 09,16	Apr. 08,17
Signal Amplifier	DAZE	ZN3380C	11001	Apr. 09,16	Apr. 08,17
High Pass filter	Micro	HPM50111	324216	Apr. 09,16	Apr. 08,17
Filter	COM-MW	ZBSF-C836.5-25-X	KW032	Apr. 09,16	Apr. 08,17
Filter	COM-MW	ZBSF-C1747.5-75-X2	KW035	Apr. 09,16	Apr. 08,17
Filter	COM-MW	ZBSF-C1880-60-X2	KW037	Apr. 09,16	Apr. 08,17
DC Power Supply	LongWei	PS-305D	010964729	Apr. 09,16	Apr. 08,17
Constant temperature and humidity box	GF	GTH-800-40-1P	MAA9906-005	Apr. 09,16	Apr. 08,17
Universal radio communication tester	Rohde&Schwarz	CMU200	3215420	Apr. 09,16	Apr. 08,17
Splitter	Agilent	11636B	0025164	Apr. 09,16	Apr. 08,17
Loop Antenna	ARA	PLA-1030/B	1029	Apr. 09,16	Apr. 08,17
Power Meter	Anritsu	ML2495A	1204003	Apr. 09,16	Apr. 08,17
Power Sensor	Anritsu	MA2411B	1126150	Apr. 09,16	Apr. 08,17

3. TEST SET-UP AND OPERATION MODES

3.1. Principle of Configuration Selection

Emission: The equipment under test (EUT) was configured to measure its highest possible radiation level. The test modes were adapted accordingly in reference to the Operating Instructions.

3.2. Block Diagram of Test Set-up

System Diagram of Connections between EUT and Simulators

Conducted Emission



Radiated Emission



(EUT: Bluetooth and NFC Speaker)

3.3. Test Operation Mode and Test Software

Final Test Mode	Description
Mode 1	CH00
Mode 2	CH19
Mode 3	CH39
Mode 4	Link Mode

Test Software: e3 and bluetest3

3.4. Special Accessories and Auxiliary Equipment

None.

3.5. Countermeasures to Achieve EMC Compliance

None.

4. EMISSION TEST RESULTS

4.1. Conducted Emission at the Mains Terminals Test

4.1.1. Limit 15.207

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dBµV)	
	Quasi-peak	Average
0.15-0.5	66 to 56	56 to 46
0.5-5	56	46
5-30	60	50

4.1.2. Test Setup


The EUT was put on a wooden table which was 0.8 m high above the ground and connected to the AC mains through the Artificial Mains Network (AMN). Where the mains cable supplied by the manufacture was longer than 0.8 m, the excess was folded back and forth parallel to the cable at the centre so as to form a bundle no longer than 0.4 m.

The EUT was kept 0.4 m from any other earthed conducting surface. Both sides of AC line were checked to find out the maximum conducted emission levels according to the test procedure during the conducted emission test.

The frequency range from 150 kHz to 30 MHz was investigated.

The bandwidth of the test receiver was set at 9 kHz.

Pretest for all mode, The test data of the worst case condition(s) was reported on the following page.




Remark:
 E.U.T: Equipment Under Test
 LISN: Line Impedance Stabilization Network
 Test table height=0.8m

Block diagram of Test Setup




EUT :	Bluetooth and NFC Speaker	Model Name :	VG7
Temperature :	26 °C	Relative Humidity :	54%
Pressure :	1010hPa	Phase :	L
Test Voltage :	DC 12V from adapter AC 120V/60Hz	Test Mode :	Mode 4



Trace: 45

	Freq	Level	Limit	Over	Remark
	MHz	dBuV	Line	Limit	
			dBuV	dB	
1	0.194	43.82	53.84	-10.02	Average
2	0.194	57.30	63.84	-6.54	QP
3	0.244	38.86	51.95	-13.09	Average
4	0.244	51.80	61.95	-10.15	QP
5	0.308	33.56	50.02	-16.46	Average
6	0.308	47.80	60.02	-12.22	QP
7	0.614	30.14	46.00	-15.86	Average
8	0.614	39.20	56.00	-16.80	QP
9	5.535	25.49	50.00	-24.51	Average
10	5.535	38.40	60.00	-21.60	QP
11	10.620	33.48	50.00	-16.52	Average
12	10.620	45.70	60.00	-14.30	QP


EUT :	Bluetooth and NFC Speaker	Model Name :	VG7
Temperature :	26 °C	Relative Humidity :	54%
Pressure :	1010hPa	Phase :	N
Test Voltage :	DC 12V from adapter AC 120V/60Hz	Test Mode :	Mode 4



ace: 47


	Freq	Level	Limit	Over	Remark
	MHz	dBuV	dBuV	dB	
1	0.194	44.06	53.84	-9.78	Average
2	0.194	57.80	63.84	-6.04	QP
3	0.256	38.51	51.56	-13.05	Average
4	0.256	51.60	61.56	-9.96	QP
5	0.775	29.33	46.00	-16.67	Average
6	0.775	38.80	56.00	-17.20	QP
7	1.744	27.63	46.00	-18.37	Average
8	1.744	36.10	56.00	-19.90	QP
9	4.952	24.19	46.00	-21.81	Average
10	4.952	36.60	56.00	-19.40	QP
11	10.564	32.16	50.00	-17.84	Average
12	10.564	44.40	60.00	-15.60	QP

EUT :	Bluetooth and NFC Speaker	Model Name :	VG7
Temperature :	26 °C	Relative Humidity :	54%
Pressure :	1010hPa	Phase :	L
Test Voltage :	DC 12V from adapter AC 240V/60Hz	Test Mode :	Mode 4



	Freq	Level	Limit	Over	Remark
	MHz	dBuV	dBuV	dB	
1	0.185	43.01	54.24	-11.23	Average
2	0.185	60.20	64.24	-4.04	QP
3	0.247	37.43	51.86	-14.43	Average
4	0.247	53.40	61.86	-8.46	QP
5	0.518	34.49	46.00	-11.51	Average
6	0.518	43.10	56.00	-12.90	QP
7	0.788	33.11	46.00	-12.89	Average
8	0.788	41.20	56.00	-14.80	QP
9	10.847	31.69	50.00	-18.31	Average
10	10.847	42.80	60.00	-17.20	QP
11	13.841	28.64	50.00	-21.36	Average
12	13.841	37.60	60.00	-22.40	QP

EUT :	Bluetooth and NFC Speaker	Model Name :	VG7
Temperature :	26 °C	Relative Humidity :	54%
Pressure :	1010hPa	Phase :	N
Test Voltage :	DC 12V from adapter AC 240V/60Hz	Test Mode :	Mode 4



Trace: 19

	Freq	Level	Limit	Over	Remark
	MHz	dBuV	Line	Limit	
			dBuV	dB	
1	0.181	43.48	54.46	-10.98	Average
2	0.181	60.40	64.46	-4.06	QP
3	0.249	37.43	51.78	-14.35	Average
4	0.249	52.80	61.78	-8.98	QP
5	0.527	34.27	46.00	-11.73	Average
6	0.527	41.90	56.00	-14.10	QP
7	0.775	32.33	46.00	-13.67	Average
8	0.775	40.50	56.00	-15.50	QP
9	10.564	32.08	50.00	-17.92	Average
10	10.564	40.60	60.00	-19.40	QP
11	13.841	28.32	50.00	-21.68	Average
12	13.841	38.20	60.00	-21.80	QP

4.2. Radiated Emission Test

4.2.1. Limit

15.205(a) /15.209/ 15.247(d)

FREQUENCY MHz	DISTANCE Meters	FIELD STRENGTHS LIMIT	
		$\mu\text{V}/\text{m}$	$\text{dB}(\mu\text{V})/\text{m}$
30 ~ 88	3	100	40.0
88 ~ 216	3	150	43.5
216 ~ 960	3	200	46.0
960 ~ 1000	3	500	54.0
Above 1000	3	74.0 $\text{dB}(\mu\text{V})/\text{m}$ (Peak) 54.0 $\text{dB}(\mu\text{V})/\text{m}$ (Average)	

4.2.2. Restricted bands of operation

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
¹ 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2690 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	(²)

All the emissions appearing within 15.205 restricted frequency bands shall not exceed the limits shown in 15.209, all the other emissions shall be at least 20dB below the fundamental emissions, or comply with 15.209 limits.

4.2.3. Test setup

The EUT was placed on a turn table which was 0.8 m (above 1GHz, the table was 1.5m) above the ground. The turn table can rotate 360 degrees to determine the position of the maximum emission level. The EUT was set 3 m away from the receiving antenna which was mounted on an antenna tower. The measuring antenna moved up and down to find out the maximum emission level. It moved from 1 m to 4 m for both horizontal and vertical polarizations.

The EUT was tested in the Chamber Site. It was pre-scanned with a Peak detector from the spectrum, and all the final readings from the test receiver were measured with the Quasi-Peak detector.

The bandwidth of the EMI test receiver is set at 120kHz for frequency range from 30MHz to 1000 MHz.

The bandwidth of the Spectrum's VBW is set at 3MHz and RBW is set at 1MHz for peak emissions measurement above 1GHz and 1MHz RBW, 10Hz VBW for average emissions measure above 1GHz, Both PK and AV measure, PK detector is used.

The frequency range from 30MHz to 10th harmonic (25GHz) are checked. and no any emissions were found from 18GHz to 25 GHz, So the radiated emissions from 18GHz to 25GHz were not record.

Notes: 1. Emission Level = Antenna Factor + Cable Loss + Meter Reading-Preamp Factor.

2. Measurement Uncertainty: ± 3.2 dB at a level of confidence of 95%.


3. For emissions above 1GHz, if peak level comply with average limit, then the average level is deemed to comply with average limit.

4. For emissions below 1GHz, pretest for all mode, The test data of the worst case condition(s) was reported on the following pages.


5. For Both PK and AV value above 1GHz, PK detector is used.

6. EUT Pre-scan X/Y/Z orientation, only worst case is presented in the report (Z orientation).


Block diagram of Test Setup




Radiated Emission Test-Up Frequency Below 30MHz



30MHz- 1GHz



Above 1GHz



Below 30MHz

Freq.	Reading	Limit	Margin	State
(MHz)	(dBuV/m)	(dBuV/m)	(dB)	P/F
--	--	--	--	P
--	--	--	--	P

Note:

The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.


Distance extrapolation factor = $40 \log (\text{specific distance}/\text{test distance})$ (dB);

Limit line = specific limits(dBuv) + distance extrapolation factor.

EUT :	Bluetooth and NFC Speaker	Model Name :	VG7
Temperature :	24 °C	Relative Humidity :	48%
Pressure :	1010hPa	Test Mode :	TX
Test Voltage :	DC 7.4V		


30- 1GHz

Vertical



	Read Freq	Preamp Level	Antenna Factor	Cable Factor	Cable Loss	Limit Level	Over Line	Limit	Over Limit	Remark
	MHz	dBuV	dB	dB/m	dB	dBuV/m	dBuV/m	dB	dB	
1	57.16	31.18	31.36	7.73	0.75	8.30	40.00	-31.70	QP	
2	88.20	29.83	31.35	8.90	0.94	8.32	43.50	-35.18	QP	
3	151.25	36.62	31.25	9.02	1.22	15.61	43.50	-27.89	QP	
4	235.64	38.12	30.94	12.50	1.61	21.29	46.00	-24.71	QP	
5	419.94	38.79	30.63	16.94	2.48	27.58	46.00	-18.42	QP	
6	519.85	38.19	30.67	19.10	2.94	29.56	46.00	-16.44	QP	

Horizontal



	Read Freq	Preamp Level	Antenna Factor	Cable Loss	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dB	dBuV/m	dB	
1	30.00	17.76	31.41	0.56	40.00	-34.29	QP
2	165.80	36.36	31.21	1.30	43.50	-27.33	QP
3	231.76	40.75	30.93	1.61	46.00	-22.18	QP
4	371.44	39.94	30.62	2.27	46.00	-18.24	QP
5	419.94	37.86	30.63	2.48	46.00	-19.35	QP
6	471.35	39.83	30.60	2.69	46.00	-15.88	QP

NOTE:

Absolute Level= ReadingLevel+antenna Factor+cable loss-preamp factor,
 Over Limit= Absolute Level – Limit

EUT :	Bluetooth and NFC Speaker	Model Name :	VG7
Temperature :	24 °C	Relative Humidity :	48%
Pressure :	1010hPa	Test Mode :	GFSK
Test Voltage :	DC 7.4V		

Frequency	Meter Reading	Antenna Factor	Cable loss	Preamp factor	Emission Level	Limits	Margin	Detector Type	Comment
(MHz)	(dBµV)	(dB)	(dB)	(dB)	(dBµV/m)	(dBµV/m)	(dB)		
TX-2402									
4804	29.03	32.94	11.96	27.49	46.44	54	-7.56	Average	Vertical
4804	36.15	32.94	11.96	27.49	53.56	74	-20.44	peak	Vertical
7206	28.70	25.28	16.61	27.94	42.65	54	-11.35	Average	Vertical
7206	37.70	25.28	16.61	27.94	51.65	74	-22.35	peak	Vertical
17100	29.66	24.76	21.42	30.14	45.70	54	-8.30	Average	Vertical
17100	40.12	24.76	21.42	30.14	56.16	74	-17.84	peak	Vertical
4804	28.04	32.94	11.96	27.49	45.45	54	-8.55	Average	Horizontal
4804	38.93	32.94	11.96	27.49	56.34	74	-17.66	peak	Horizontal
7206	28.03	25.28	16.61	27.94	41.98	54	-12.02	Average	Horizontal
7206	38.91	25.28	16.61	27.94	52.86	74	-21.14	peak	Horizontal
17100	28.47	24.76	21.42	30.14	44.51	54	-9.49	Average	Horizontal
17100	39.86	24.76	21.42	30.14	55.90	74	-18.10	peak	Horizontal
TX-2440									
4880	30.68	32.11	12.14	27.53	47.40	54	-6.60	Average	Vertical
4880	39.88	32.11	12.14	27.53	56.60	74	-17.40	peak	Vertical
7320	32.74	24.33	16.62	27.96	45.73	54	-8.27	Average	Vertical
7320	40.97	24.33	16.62	27.96	53.96	74	-20.04	peak	Vertical
17245	30.80	23.92	23.76	29.64	48.84	54	-5.16	Average	Vertical
17245	40.57	23.92	23.76	29.64	58.61	74	-15.39	peak	Vertical
4880	28.91	32.11	12.14	27.53	45.63	54	-8.37	Average	Horizontal
4880	38.73	32.11	12.14	27.53	55.45	74	-18.55	peak	Horizontal
7320	29.45	24.33	16.62	27.96	42.44	54	-11.56	Average	Horizontal
7320	41.87	24.33	16.62	27.96	54.86	74	-19.14	peak	Horizontal
17500	29.39	23.92	23.76	29.64	47.43	54	-6.57	Average	Horizontal
17500	39.54	23.92	23.76	29.64	57.58	74	-16.42	peak	Horizontal
TX-2480									
4960	30.13	31.32	12.36	27.58	46.23	54	-7.77	Average	Vertical
4960	40.33	31.32	12.36	27.58	56.43	74	-17.57	peak	Vertical
7440	28.86	24.38	16.62	27.99	41.87	54	-12.13	Average	Vertical
7440	39.96	24.38	16.62	27.99	52.97	74	-21.03	peak	Vertical
17384	29.27	23.61	22.67	29.85	45.70	54	-8.30	Average	Vertical
17384	41.18	23.61	22.67	29.85	57.61	74	-16.39	peak	Vertical
4960	29.77	31.32	12.36	27.58	45.87	54	-8.13	Average	Horizontal
4960	37.87	31.32	12.36	27.58	53.97	74	-20.03	peak	Horizontal
7440	28.86	24.38	16.62	27.99	41.87	54	-12.13	Average	Horizontal
7440	37.86	24.38	16.62	27.99	50.87	74	-23.13	peak	Horizontal
17384	28.35	23.61	22.67	29.85	44.78	54	-9.22	Average	Horizontal
17384	39.75	23.61	22.67	29.85	56.18	74	-17.82	peak	Horizontal
NOTE: 1. Absolute Level= ReadingLevel+antenna Factor+cable loss-preamp factor. 2. Over Limit= Absolute Level – Limit. 3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has not to be reported. 4. EUT Pre-scan X/Y/Z orientation, only worst case is presented in the report (Z orientation)									

5. BAND EDGE COMPLIANCE TEST

5.1. Limits

According to 15.247(d)


All the lower and upper band-edges emissions appearing within 2310MHz to 2390MHz and 2483.5MHz to 2500MHz restricted frequency bands shall not exceed the limits shown in 15.209, all the other emissions outside operation frequency band 2400MHz to 2483.5MHz shall be at least 20dB below the fundamental emissions, or comply with 15.209 limits.

5.2. Test setup

For Conducted Test



For Radiated emission Test



5.3. TEST Procedure

For Conducted Test

1. The transmitter output is connected to a spectrum analyzer. The resolution bandwidth is set to 100KHz. The video bandwidth is set to 300KHz.
2. The spectrum from 30MHz to 26 GHz is investigated with the transmitter set to the lowest, middle, and highest channels.

EMI Test Receiver	Setting
Attenuation	Auto
RBW	100KHz
VBW	300KHz
Detector	Peak
Trace	Max hold

For Radiated emission Test

The EUT was placed on a styrofoam table which is 1.5m above ground plane.

The measurement procedure at the band edges was simplified by performing the measurement in just one plot. Both, the in-band-emission and the unwanted emission were encompassed by the span. After trace stabilization, the maximum peak was determined by a peak detector and the value was marked by an appropriate limit line. The second limit line, which is 20dB below the first, marks the limit for the emissions in the unrestricted band. A maximum-peak-detector marks the highest emission in the unrestricted band next to the band edge.

The measurements were performed at the lower end of the 2.4GHz band.

Use the following spectrum analyzer settings:

For Restricted Band, When spectrum scanned above 1GHz setting resolution bandwidth 1MHz, video bandwidth 3MHz:

EMI Test Receiver	Setting
Attenuation	Auto
RBW	1MHz
VBW	3MHz
Detector	Peak
Trace	Max hold


For Non-Restricted Band, When spectrum scanned above 1GHz setting resolution bandwidth 100KHz, video bandwidth 300KHz:

EMI Test Receiver	Setting
Attenuation	Auto
RBW	100KHz
VBW	300KHz
Detector	Peak
Trace	Max hold

For radiated test as follows:


CH00

Vertical



	Read Freq	Preamp Level	Antenna Factor	Cable Loss	Limit Line	Over Limit	Remark		
	MHz	dBuV	dB	dB/m	dB	dBuV/m	dB		
1	2390.00	25.85	26.32	28.72	7.34	35.59	74.00	-38.41	Peak


Horizontal



	Read Freq	Preamp Level	Antenna Factor	Cable Loss	Limit Line	Over Limit	Remark	
	MHz	dBuV	dB	dB/m	dB	dBuV/m	dB	
1	2390.00	31.92	26.32	28.72	7.34	41.66	74.00	-32.34 Peak


CH39

Vertical



	Read Freq	Preamp Level	Antenna Factor	Cable Factor	Cable Loss	Limit Level	Over Line	Limit	Remark
	MHz	dBuV	dB	dB/m	dB	dBuV/m	dBuV/m	dB	
1	2483.50	33.20	26.34	28.79	7.57	43.22	74.00	-30.78	Peak

Horizontal




	Read Freq	Preamp Level	Antenna Factor	Cable Loss	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dB/m	dB	dBuV/m	dBuV/m	dB
1	2483.50	34.73	26.34	28.79	7.57	44.75	74.00	-29.25 Peak

If the PK measured levels comply with average limit, then the average level were deemed to comply with average limit.

conduction band-edge

Frequency Band	Delta Peak to band emission (dBc)	>Limit (dBc)	Result
Left-band	42.414	20	Pass
Right-band	54.239	20	Pass

Left Side



Right Side



6. 6DB OCCUPY BANDWIDTH


6.1. Limits

According to 15.247(a)(2)

For direct sequence systems, the minimum 6dB bandwidth shall be at least 500kHz

6.2. TEST PROCEDURE



1. Set RBW = 100 kHz.
2. Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.




Test data:

Channel Frequency (MHz)	6dB Bandwidth (MHz)	99% Bandwidth (MHz)	Result
2402	0.696	1.049	Pass
2440	0.697	1.045	Pass
2480	0.693	1.046	Pass

Test plot as follows:



2480 MHz



7. OUTPUT POWER TEST

7.1. Limits

According to 15.247(b)(3)

For systems using digital modulation in the 2400~2483.5MHz, The maximum peak conducted output Power shall not exceed 1W (30dBm) , The e.i.r.p. shall not exceed 4 W


7.2. Test Procedure

For Peak power

- a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- b. Spectrum Setting : RBW > the 20 dB bandwidth of the emission being measured
 VBW ≥ RBW
 Sweep = auto
 Detector function = peak
 Trace = max hold

7.3. Test setup


Peak power





7.4. Test result

Frequency (MHz)	Maximum Peak Conducted Output Power (dBm)	Limit (dBm)
2402	2.363	30
2440	2.723	30
2480	2.888	30

Test plot as follows:





8. DUTY CYCLE

8.1. Test Procedure

The zero-span mode on a spectrum analyzer or EMI receiver if the response time and spacing between bins on the sweep are sufficient to permit accurate measurements of the on and off times of the transmitted signal. Set the center frequency of the instrument to the center frequency of the transmission. Set $RBW \geq OBW$ if possible; otherwise, set RBW to the largest available value. Set $VBW \geq RBW$. Set detector = peak or average. The zero-span measurement method shall not be used unless both RBW and VBW are $> 50/T$ and the number of sweep points across duration T exceeds 100. (For example,

if VBW and/or RBW are limited to

3 MHz, then the zero-span method of measuring duty cycle shall not be used if $T \leq 16.7$ microseconds.)

The transmitter output is connected to the Spectrum Analyzer. We tested according to the zero-span measurement method, 6.0)b) in KDB 558074(issued 06/09/2015)

The largest available value of RBW is 8 MHz and VBW is 50 MHz. The zero-span method of measuring duty cycle shall not be used if $T \leq 6.25$ microseconds. ($50/6.25 = 8$)

The zero-span method was used because all measured T data are > 6.25 microseconds and both RBW and VBW are $> 50/T$.

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.

The path loss was compensated to the results for each measurement.

Set to the maximum power setting and enable the EUT transmit continuously.

The EUT was operating in controlled its channel.

Use the following spectrum analyzer settings:

Span = Zero Span

RBW = 1MHz

VBW = 1MHz

Number of points in Sweep > 100


Detector function = peak

Trace = Clear write

Measure T_{total} and T_{on}


Calculate Duty Cycle = T_{on} / T_{total} and Duty Cycle Factor = $10 \cdot \log(1/\text{Duty Cycle})$

8.2. Test Setup



EUT :	Bluetooth and NFC Speaker	Model Name :	VG7
Temperature :	24 °C	Relative Humidity :	48%
Pressure :	1010hPa	Test Mode :	TX-2440
Test Voltage :	DC 7.4V		

Modulation Mode	Data rate	Ton	Ttotal	Duty Cycle	Duty Cycle Factor(db)
GFSK	1Mbps	448	646	0.69	1.59



9. POWER SPECTRAL DENSITY TEST


9.1. Limits

According to 15.247(e)

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3kHz band during any time interval of continuous transmission.

9.2. Test setup


1. Set analyzer center frequency to DTS channel center frequency.
2. Set the span to 1.5 times the DTS bandwidth.
3. Set the RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
4. Set the VBW $\geq 3 \text{ RBW}$
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level within the RBW.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.




9.3. Test result

Channel Frequency (MHz)	Power density (dBm/3kHz)	Limit (dBm/3kHz)	Result
2402	-16.509	8	Pass
2440	-14.795	8	Pass
2480	-14.075	8	Pass


TX CH00



TX CH 19



TX CH39



10. ANTENNA REQUIREMENTS

10.1. Limits

According to 15.203

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

10.2. Result

The antennas used for this product is PCB antenna and that no antenna other than that furnished by the responsible party shall be used with the device, the maximum peak gain of the transmit antenna is only 4.01dBi.

---END---