




RF TEST REPORT



Report No.: 18070144-FCC-R2

Supersede Report No.: N/A

Applicant	Soundcast LLC	
Product Name	Bluetooth and NFC Speaker	
Model No.	VG7SE	
Serial No.	N/A	
Test Standard	FCC Part 15.247: 2017, ANSI C63.10: 2013	
Test Date	February 01 to April 03, 2018	
Issue Date	April 04, 2018	
Test Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail	
Equipment complied with the specification	<input checked="" type="checkbox"/>	
Equipment did not comply with the specification	<input type="checkbox"/>	
		
Aarron Liang Test Engineer	David Huang Checked By	
<p>This test report may be reproduced in full only Test result presented in this test report is applicable to the tested sample only</p>		

Issued by:

SIEMIC (SHENZHEN-CHINA) LABORATORIES

Zone A, Floor 1, Building 2 Wan Ye Long Technology Park

South Side of Zhoushi Road, Bao' an District, Shenzhen, Guangdong China 518108

Phone: +86 0755 2601 4629801 Email: China@siemic.com.cn

Laboratories Introduction

SIEMIC, headquartered in the heart of Silicon Valley, with superior facilities in US and Asia, is one of the leading independent testing and certification facilities providing customers with one-stop shop services for Compliance Testing and Global Certifications.



In addition to testing and certification, SIEMIC provides initial design reviews and compliance management throughout a project. Our extensive experience with China, Asia Pacific, North America, European, and International compliance requirements, assures the fastest, most cost effective way to attain regulatory compliance for the global markets.

Accreditations for Conformity Assessment

Country/Region	Scope
USA	EMC, RF/Wireless, SAR, Telecom
Canada	EMC, RF/Wireless, SAR, Telecom
Taiwan	EMC, RF, Telecom, SAR, Safety
Hong Kong	RF/Wireless, SAR, Telecom
Australia	EMC, RF, Telecom, SAR, Safety
Korea	EMI, EMS, RF, SAR, Telecom, Safety
Japan	EMI, RF/Wireless, SAR, Telecom
Singapore	EMC, RF, SAR, Telecom
Europe	EMC, RF, SAR, Telecom, Safety

Test Report No.	18070144-FCC-R2
Page	3 of 46

This page has been left blank intentionally.

CONTENTS

1. REPORT REVISION HISTORY	5
2. CUSTOMER INFORMATION.....	5
3. TEST SITE INFORMATION	6
4. EQUIPMENT UNDER TEST (EUT) INFORMATION	7
5. TEST SUMMARY	8
6. MEASUREMENTS, EXAMINATION AND DERIVED RESULTS.....	9
6.1 ANTENNA REQUIREMENT	9
6.2 DTS (6 DB) CHANNEL BANDWIDTH	10
6.3 MAXIMUM OUTPUT POWER.....	12
6.4 POWER SPECTRAL DENSITY	14
6.5 BAND-EDGE & UNWANTED EMISSIONS INTO RESTRICTED FREQUENCY BANDS	16
6.6 AC POWER LINE CONDUCTED EMISSIONS.....	19
6.7 RADIATED EMISSIONS & RESTRICTED BAND.....	25
ANNEX A. TEST INSTRUMENT	31
ANNEX B. EUT AND TEST SETUP PHOTOGRAPHS.....	32
ANNEX C. TEST SETUP AND SUPPORTING EQUIPMENT.....	41
ANNEX D. USER MANUAL / BLOCK DIAGRAM / SCHEMATICS / PARTLIST	45
ANNEX E. DECLARATION OF SIMILARITY	46

1. Report Revision History

Report No.	Report Version	Description	Issue Date
18070144-FCC-R2	NONE	Original	April 04, 2018

2. Customer information

Applicant Name	Soundcast LLC
Applicant Add	9771-E Clairemont Mesa Blvd. San Diego, CA92124
Manufacturer	Gigatek Electronics(DongGuan) Co., LTD.
Manufacturer Add	No.132, DongXing E.Rd, DongXing Industrial Zone, KengMei Village, DongKeng Town, DongGuan City, GuangDong, China.

3. Test site information

Test Lab A:

Lab performing tests	SIEMIC (Shenzhen-China) LABORATORIES
Lab Address	Zone A, Floor 1, Building 2 Wan Ye Long Technology Park South Side of Zhoushi Road, Bao' an District, Shenzhen, Guangdong China 518108
FCC Test Site No.	535293
IC Test Site No.	4842E-1
Test Software	Radiated Emission Program-To Shenzhen v2.0

Test Lab B:

Lab performing tests	SIEMIC (Nanjing-China) Laboratories
Lab Address	2-1 Longcang Avenue Yuhua Economic and Technology Development Park, Nanjing, China
FCC Test Site No.	694825
IC Test Site No.	4842B-1
Test Software	EZ_EMG(ver.lcp-03A1)

Note: We just perform Radiated Spurious Emission above 18GHz in the test Lab. B.

4. Equipment under Test (EUT) Information

Description of EUT:	Bluetooth and NFC Speaker
Main Model:	VG7SE
Serial Model:	N/A
Date EUT received:	January 31, 2018
Test Date(s):	February 01 to April 03, 2018
Equipment Category :	DTS
Antenna Gain:	Bluetooth/BLE: 0dBi
Antenna Type:	PCB Antenna
Type of Modulation:	Bluetooth: GFSK, π /4DQPSK, 8DPSK BLE: GFSK
RF Operating Frequency (ies):	Bluetooth&BLE: 2402-2480 MHz
Max. Output Power:	0.591 dBm
Number of Channels:	Bluetooth: 79CH BLE: 40CH
Port:	Please refer to user manual
Trade Name :	SOUNDCAST
Type of Modulation:	Bluetooth: GFSK, π /4DQPSK, 8DPSK BLE: GFSK
FCC ID:	SUD-VGBT7SE

5. Test Summary

The product was tested in accordance with the following specifications.

All testing has been performed according to below product classification:

FCC Rules	Description of Test	Result
§15.203	Antenna Requirement	Compliance
§15.247 (a)(2)	DTS (6 dB) CHANNEL BANDWIDTH	Compliance
§15.247(b)(3)	Conducted Maximum Output Power	Compliance
§15.247(e)	Power Spectral Density	Compliance
§15.247(d)	Band-Edge & Unwanted Emissions into Restricted Frequency Bands	Compliance
§15.207 (a),	AC Power Line Conducted Emissions	Compliance
§15.205, §15.209, §15.247(d)	Radiated Emissions & Unwanted Emissions into Restricted Frequency Bands	Compliance

Measurement Uncertainty

Emissions		
Test Item	Description	Uncertainty
Band-Edge & Unwanted Emissions into Restricted Frequency Bands and Radiated Emissions & Unwanted Emissions into Restricted Frequency Bands	Confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2 (for EUTs < 0.5m X 0.5m X 0.5m)	+5.6dB/-4.5dB
-	-	-

6. Measurements, Examination And Derived Results

6.1 Antenna Requirement

Applicable Standard

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
- b. Antenna must use a unique type of connector to attach to the EUT.

Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

And according to FCC 47 CFR section 15.247 (b), if the transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Antenna Connector Construction

The EUT has 1 antenna:


A permanently attached PCB Antenna for Bluetooth, the gain is 0dBi for Bluetooth/BLE.

The antenna meets up with the ANTENNA REQUIREMENT.

Result: Compliance.

6.2 DTS (6 dB) Channel Bandwidth

Temperature	24 °C
Relative Humidity	54%
Atmospheric Pressure	1020mbar
Test date :	March 29, 2018
Tested By :	Aarron Liang

Spec	Item	Requirement	Applicable
§ 15.247(a)(2)	a)	6dB BW ≥ 500kHz;	<input checked="" type="checkbox"/>
RSS Gen(4.6.1)	b)	99% BW: For FCC reference only; required by IC.	<input checked="" type="checkbox"/>
Test Setup	 <p style="text-align: center;">Spectrum Analyzer EUT</p>		
Test Procedure	<p>558074 D01 DTS MEAS Guidance v03r03, 8.1 DTS bandwidth <u>6dB Emission bandwidth measurement procedure</u></p> <ul style="list-style-type: none"> - Set RBW = 100 kHz. - Set the video bandwidth (VBW) ≥ 3 RBW. - Detector = Peak. - Trace mode = max hold. - Sweep = auto couple. - Allow the trace to stabilize. <p>Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.</p>		
Remark			
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail		

Test Data Yes N/A


Test Plot Yes (See below) N/A

6dB Bandwidth measurement result


Test Data

CH	Frequency (MHz)	6dB Bandwidth (kHz)	99% Occupied Bandwidth (MHz)
Low	2402	698.60	1.0473
Mid	2440	692.00	1.0469
High	2480	697.60	1.0483


Test Plots



6dB Bandwidth - Low CH 2402



6dB Bandwidth - Mid CH 2440




6dB Bandwidth - High CH 2480

6.3 Maximum Output Power

Temperature	24 °C
Relative Humidity	54%
Atmospheric Pressure	1020mbar
Test date :	March 29, 2018
Tested By :	Aarron Liang

Requirement(s):

Spec	Item	Requirement	Applicable
§15.247(b) (3),RSS210 (A8.4)	a)	FHSS in 2400-2483.5MHz with ≥ 75 channels: ≤ 1 Watt	<input type="checkbox"/>
	b)	FHSS in 5725-5850MHz: ≤ 1 Watt	<input type="checkbox"/>
	c)	For all other FHSS in the 2400-2483.5MHz band: ≤ 0.125 Watt.	<input type="checkbox"/>
	d)	FHSS in 902-928MHz with ≥ 50 channels: ≤ 1 Watt	<input type="checkbox"/>
	e)	FHSS in 902-928MHz with ≥ 25 & <50 channels: ≤ 0.25 Watt	<input type="checkbox"/>
	f)	DTS in 902-928MHz, 2400-2483.5MHz: ≤ 1 Watt	<input checked="" type="checkbox"/>

Test Setup	 <p style="text-align: center;">Spectrum Analyzer EUT</p>
------------	--

Test Procedure	<p>558074 D01 DTS MEAS Guidance v03r03, 9.1.2 Integrated band power method Maximum output power measurement procedure</p> <p>a) Set the RBW \geq DTS bandwidth. b) Set VBW $\geq 3 \times$ RBW. c) Set span $\geq 3 \times$ RBW d) Sweep time = auto couple. e) Detector = peak. f) Trace mode = max hold. g) Allow trace to fully stabilize. h) Use peak marker function to determine the peak amplitude level.</p>
----------------	---

Remark	
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail


Test Data Yes N/A
 Test Plot Yes (See below) N/A

Output Power measurement result


Test Data

Type	CH	Frequency (MHz)	Conducted Power (dBm)	Limit (dBm)	Result
Output power	Low	2402	0.456	30	Pass
	Mid	2440	0.591	30	Pass
	High	2480	0.396	30	Pass


Test Plots



AV Output power - Low CH 2402




AV Output power - Mid CH 2440



AV Output power - High CH 2480

6.4 Power Spectral Density

Temperature	24 °C
Relative Humidity	54%
Atmospheric Pressure	1020mbar
Test date :	March 29, 2018
Tested By :	Aarron Liang

Spec	Item	Requirement	Applicable
§15.247(e)	a)	The power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.	<input checked="" type="checkbox"/>
Test Setup	 <p style="text-align: center;">Spectrum Analyzer EUT</p>		
Test Procedure	<p>558074 D01 DTS MEAS Guidance v03r03, 10.2 power spectral density method power spectral density measurement procedure</p> <ul style="list-style-type: none"> - a) Set analyzer center frequency to DTS channel center frequency. - b) Set the span to 1.5 times the DTS bandwidth. - c) Set the RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$. - d) Set the VBW $\geq 3 \times \text{RBW}$. - e) Detector = peak. - f) Sweep time = auto couple. - g) Trace mode = max hold. - h) Allow trace to fully stabilize. - i) Use the peak marker function to determine the maximum amplitude level within the RBW. - j) If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat. 		
Remark			
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail		

Test Data Yes N/A
 Test Plot Yes (See below) N/A


Power Spectral Density measurement result

Test Data


Type	CH	Freq (MHz)	Reading (dBm)	Factor (dB)	Result (dBm)	Limit (dBm)	Result
PSD	Low	2402	-14.011	-5.23	-19.241	8	Pass
	Mid	2440	-12.467	-5.23	-17.697	8	Pass
	High	2480	-11.731	-5.23	-16.961	8	Pass

Note: factor= $10\log(3/10)=-5.23$


Test Plots



PSD - Low CH 2402



PSD - Mid CH 2440




PSD - High CH 2480

6.5 Band-Edge & Unwanted Emissions into Restricted Frequency Bands

Temperature	24 °C
Relative Humidity	54%
Atmospheric Pressure	1020mbar
Test date :	March 29, 2018
Tested By :	Aarron Liang

Requirement(s):

Spec	Item	Requirement	Applicable
§15.247(d)	a)	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits.	<input checked="" type="checkbox"/>

Test Setup	
------------	--

Test Procedure	<p>Radiated Method Only</p> <ul style="list-style-type: none"> - 1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator. - 2. Position the EUT without connection to measurement instrument. Put it on the Rotated table and turn on the EUT and make it operate in transmitting mode. Then set it to Low Channel and High Channel within its operating range, and make sure the instrument is operated in its linear range.
----------------	---


Test Report No.	18070144-FCC-R2
Page	17 of 46

	<ul style="list-style-type: none"> - 3. First, set both RBW and VBW of spectrum analyzer to 100 kHz with a convenient frequency span including 100kHz bandwidth from band edge, check the emission of EUT, if pass then set Spectrum Analyzer as below: <ul style="list-style-type: none"> a. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Quasiy Peak detection at frequency below 1GHz. b. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz with Peak detection for Peak measurement at frequency above 1GHz. c. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 10Hz with Peak detection for Average Measurement as below at frequency above 1GHz. - 4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency. - 5. Repeat above procedures until all measured frequencies were complete.
Remark	
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail

Test Data Yes N/A
 Test Plot Yes (See below) N/A

Test Plots

Band Edge measurement result




6.6 AC Power Line Conducted Emissions

Temperature	27 °C
Relative Humidity	55%
Atmospheric Pressure	1023mbar
Test date :	March 22, 2018
Tested By :	Aarron Liang

Requirement(s):

Spec	Item	Requirement	Applicable														
47CFR§15.207, RSS210 (A8.1)	a)	For Low-power radio-frequency devices that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 [mu] H/50 ohms line impedance stabilization network (LISN). The lower limit applies at the boundary between the frequencies ranges.	<input checked="" type="checkbox"/>														
		<table border="1"> <thead> <tr> <th rowspan="2">Frequency ranges (MHz)</th> <th colspan="2">Limit (dBµV)</th> </tr> <tr> <th>QP</th> <th>Average</th> </tr> </thead> <tbody> <tr> <td>0.15 ~ 0.5</td> <td>66 – 56</td> <td>56 – 46</td> </tr> <tr> <td>0.5 ~ 5</td> <td>56</td> <td>46</td> </tr> <tr> <td>5 ~ 30</td> <td>60</td> <td>50</td> </tr> </tbody> </table>		Frequency ranges (MHz)	Limit (dBµV)		QP	Average	0.15 ~ 0.5	66 – 56	56 – 46	0.5 ~ 5	56	46	5 ~ 30	60	50
		Frequency ranges (MHz)			Limit (dBµV)												
				QP	Average												
0.15 ~ 0.5	66 – 56	56 – 46															
0.5 ~ 5	56	46															
5 ~ 30	60	50															



Procedure	<ol style="list-style-type: none"> The EUT and supporting equipment were set up in accordance with the requirements of the standard on top of a 1.5m x 1m x 0.8m high, non-metallic table. The power supply for the EUT was fed through a 50W/50mH EUT LISN, connected to filtered mains. The RF OUT of the EUT LISN was connected to the EMI test receiver via a low-loss
-----------	---


Test Report No.	18070144-FCC-R2
Page	20 of 46

	<p>coaxial cable.</p> <ol style="list-style-type: none"> 4. All other supporting equipment were powered separately from another main supply. 5. The EUT was switched on and allowed to warm up to its normal operating condition. 6. A scan was made on the NEUTRAL line (for AC mains) or Earth line (for DC power) over the required frequency range using an EMI test receiver. 7. High peaks, relative to the limit line, The EMI test receiver was then tuned to the selected frequencies and the necessary measurements made with a receiver bandwidth setting of 10 kHz. 8. Step 7 was then repeated for the LIVE line (for AC mains) or DC line (for DC power).
Remark	
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail

Test Data Yes N/A

Test Plot Yes (See below) N/A

Test Mode:	Transmitting Mode
-------------------	--------------------------




Test Data

Phase Line Plot at 120Vac, 60Hz

No.	P/L	Frequency (MHz)	Reading (dBµV)	Detector	Corrected (dB)	Result (dBµV)	Limit (dBµV)	Margin (dB)
1	L1	0.1685	35.37	QP	10.03	45.40	64.98	-19.58
2	L1	0.1685	21.25	AVG	10.03	31.28	54.98	-23.70
3	L1	0.3091	28.43	QP	10.03	38.46	60.18	-21.72
4	L1	0.3091	9.34	AVG	10.03	19.37	50.18	-30.81
5	L1	0.6131	22.12	QP	10.03	32.15	56.00	-23.85
6	L1	0.6131	2.98	AVG	10.03	13.01	46.00	-32.99
7	L1	1.3844	22.16	QP	10.03	32.19	56.00	-23.81
8	L1	1.3844	6.98	AVG	10.03	17.01	46.00	-28.99
9	L1	2.3310	19.82	QP	10.05	29.87	56.00	-26.13
10	L1	2.3310	7.11	AVG	10.05	17.16	46.00	-28.84
11	L1	4.6935	19.74	QP	10.08	29.82	56.00	-26.18
12	L1	4.6935	7.68	AVG	10.08	17.76	46.00	-28.24

Test Mode:	Transmitting Mode
-------------------	--------------------------




Test Data

Phase Neutral Plot at 120Vac, 60Hz

No.	P/L	Frequency (MHz)	Reading (dBµV)	Detector	Corrected (dB)	Result (dBµV)	Limit (dBµV)	Margin (dB)
1	N	0.1695	30.00	QP	10.02	40.02	64.98	-24.96
2	N	0.1695	16.41	AVG	10.02	26.43	54.98	-28.55
3	N	0.3138	29.17	QP	10.02	39.19	59.87	-20.68
4	N	0.3138	14.38	AVG	10.02	24.40	49.87	-25.47
5	N	0.6024	23.88	QP	10.02	33.90	56.00	-22.10
6	N	0.6024	8.16	AVG	10.02	18.18	46.00	-27.82
7	N	1.3083	23.00	QP	10.03	33.03	56.00	-22.97
8	N	1.3083	7.18	AVG	10.03	17.21	46.00	-28.79
9	N	3.0585	21.06	QP	10.05	31.11	56.00	-24.89
10	N	3.0585	3.11	AVG	10.05	13.16	46.00	-32.84
11	N	8.6004	18.28	QP	10.12	28.40	60.00	-31.60
12	N	8.6004	-1.38	AVG	10.12	8.74	50.00	-41.26

Test Mode:	Transmitting Mode
-------------------	--------------------------




Test Data

Phase Line Plot at 240Vac, 60Hz

No.	P/L	Frequency (MHz)	Reading (dBµV)	Detector	Corrected (dB)	Result (dBµV)	Limit (dBµV)	Margin (dB)
1	L1	0.2864	38.47	QP	10.03	48.50	60.63	-12.13
2	L1	0.2864	32.10	AVG	10.03	42.13	50.63	-8.50
3	L1	0.6121	32.73	QP	10.03	42.76	56.00	-13.24
4	L1	0.6121	20.10	AVG	10.03	30.13	46.00	-15.87
5	L1	1.0733	28.80	QP	10.03	38.83	56.00	-17.17
6	L1	1.0733	19.30	AVG	10.03	29.33	46.00	-16.67
7	L1	2.1351	27.71	QP	10.04	37.75	56.00	-18.25
8	L1	2.1351	10.46	AVG	10.04	20.50	46.00	-25.50
9	L1	3.4841	28.07	QP	10.06	38.13	56.00	-17.87
10	L1	3.4841	10.36	AVG	10.06	20.42	46.00	-25.58
11	L1	6.1100	20.01	QP	10.10	30.11	60.00	-29.89
12	L1	6.1100	7.42	AVG	10.10	17.52	50.00	-32.48

Test Mode:	Transmitting Mode
-------------------	--------------------------



Test Data

Phase Neutral Plot at 240Vac, 60Hz


No.	P/L	Frequency (MHz)	Reading (dBµV)	Detector	Corrected (dB)	Result (dBµV)	Limit (dBµV)	Margin (dB)
1	N	0.3238	31.49	QP	10.02	41.51	59.87	-18.36
2	N	0.3238	22.48	AVG	10.02	32.50	49.87	-17.37
3	N	0.6257	23.88	QP	10.02	33.90	56.00	-22.10
4	N	0.6257	6.43	AVG	10.02	16.45	46.00	-29.55
5	N	1.2878	23.16	QP	10.03	33.19	56.00	-22.81
6	N	1.2878	5.97	AVG	10.03	16.00	46.00	-30.00
7	N	2.7445	20.85	QP	10.05	30.90	56.00	-25.10
8	N	2.7445	5.90	AVG	10.05	15.95	46.00	-30.05
9	N	5.1597	20.17	QP	10.07	30.24	60.00	-29.76
10	N	5.1597	4.37	AVG	10.07	14.44	50.00	-35.56
11	N	9.0275	16.10	QP	10.13	26.23	60.00	-33.77
12	N	9.0275	0.07	AVG	10.13	10.20	50.00	-39.80

6.7 Radiated Emissions & Restricted Band

Temperature	27 °C
Relative Humidity	55%
Atmospheric Pressure	1023mbar
Test date :	March 22, 2018
Tested By :	Aarron Liang

Requirement(s):

Spec	Item	Requirement	Applicable																
47CFR§15.247(d), RSS210 (A8.5)	a)	<p>Except higher limit as specified elsewhere in other section, the emissions from the low-power radio-frequency devices shall not exceed the field strength levels specified in the following table and the level of any unwanted emissions shall not exceed the level of the fundamental emission. The tighter limit applies at the band edges</p> <table border="1"> <thead> <tr> <th>Frequency range (MHz)</th> <th>Field Strength (µV/m)</th> </tr> </thead> <tbody> <tr> <td>0.009~0.490</td> <td>2400/F(KHz)</td> </tr> <tr> <td>0.490~1.705</td> <td>24000/F(KHz)</td> </tr> <tr> <td>1.705~30.0</td> <td>30</td> </tr> <tr> <td>30 – 88</td> <td>100</td> </tr> <tr> <td>88 – 216</td> <td>150</td> </tr> <tr> <td>216 960</td> <td>200</td> </tr> <tr> <td>Above 960</td> <td>500</td> </tr> </tbody> </table>	Frequency range (MHz)	Field Strength (µV/m)	0.009~0.490	2400/F(KHz)	0.490~1.705	24000/F(KHz)	1.705~30.0	30	30 – 88	100	88 – 216	150	216 960	200	Above 960	500	<input checked="" type="checkbox"/>
	Frequency range (MHz)	Field Strength (µV/m)																	
	0.009~0.490	2400/F(KHz)																	
0.490~1.705	24000/F(KHz)																		
1.705~30.0	30																		
30 – 88	100																		
88 – 216	150																		
216 960	200																		
Above 960	500																		
b)	<p>For non-restricted band, In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB or 30dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, determined by the measurement method on output power to be used. Attenuation below the general limits specified in § 15.209(a) is not required</p> <p><input checked="" type="checkbox"/> 20 dB down <input type="checkbox"/> 30 dB down</p>	<input checked="" type="checkbox"/>																	
c)	<p>or restricted band, emission must also comply with the radiated emission limits specified in 15.209</p>	<input checked="" type="checkbox"/>																	

<p>Test Setup</p>	
<p>Procedure</p>	<ol style="list-style-type: none"> 1. The EUT was switched on and allowed to warm up to its normal operating condition. 2. The test was carried out at the selected frequency points obtained from the EUT characterization. Maximization of the emissions, was carried out by rotating the EUT, changing the antenna polarization, and adjusting the antenna height in the following manner: <ol style="list-style-type: none"> a. Vertical or horizontal polarization (whichever gave the higher emission level over a full rotation of the EUT) was chosen. b. The EUT was then rotated to the direction that gave the maximum emission. c. Finally, the antenna height was adjusted to the height that gave the maximum emission. 3. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Quasi Peak detection at frequency below 1GHz. 4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz with Peak detection for Peak measurement at frequency above 1GHz.

	<p>The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 10Hz with Peak detection for Average Measurement as below at frequency above 1GHz.</p> <p>5. Steps 2 and 3 were repeated for the next frequency point, until all selected frequency points were measured.</p>
Remark	
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail

Test Data Yes N/A

Test Plot Yes (See below) N/A

Test Result:

Test Mode:	Transmitting Mode
-------------------	-------------------

Frequency range: 9KHz - 30MHz

Freq. (MHz)	Detection value	Factor (dB/m)	Reading (dBuV/m)	Result (dBuV/m)	Limit@3m (dBuV/m)	Margin (dB)
--	--	--	--	--	--	>20
--	--	--	--	--	--	>20

Note:


The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Distance extrapolation factor = 40 log (specific distance/test distance)(dB);

Limit line = specific limits(dBuV) + distance extrapolation factor.

Test Mode:	Transmitting Mode
-------------------	--------------------------

30MHz -1GHz




Test Data

Vertical Polarity Plot @3m

No.	P/L	Frequency (MHz)	Reading (dBuV/m)	Detect or	Ant_F (dB/m)	PA_G (dB)	Cab_L (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Degr ee ()
1	H	614.2142	37.71	peak	19.26	21.55	2.53	37.95	46.00	-8.05	100	154
2	H	517.2480	41.89	QP	17.94	21.77	2.44	40.50	46.00	-5.50	100	143
3	H	319.9370	44.67	peak	14.02	22.23	1.89	38.35	46.00	-7.65	100	353
4	H	221.3921	43.26	peak	11.80	22.34	1.61	34.33	46.00	-11.67	100	127
5	H	151.0666	34.44	peak	12.60	22.33	1.35	26.06	43.50	-17.44	100	167
6	H	85.8984	37.48	peak	7.84	22.36	1.05	24.01	40.00	-15.99	100	147

30MHz -1GHz



Test Data

Horizontal Polarity Plot @3m

N o.	P/ L	Frequency (MHz)	Reading (dBuV/m)	Detect or	Ant_F (dB/m)	PA_G (dB)	Cab_L (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Degr ee ()
1	V	85.2981	34.28	peak	7.81	22.37	1.06	20.78	40.00	-19.22	100	284
2	V	171.9946	38.30	peak	11.64	22.26	1.36	29.04	43.50	-14.46	100	284
3	V	221.3921	50.73	QP	11.80	22.34	1.61	41.80	46.00	-4.20	100	49
4	V	319.9370	42.48	peak	14.02	22.23	1.89	36.16	46.00	-9.84	100	292
5	V	369.4047	48.47	QP	15.06	22.10	2.03	43.46	46.00	-2.54	100	181
6	V	614.2142	42.56	QP	19.26	21.55	2.53	42.80	46.00	-3.20	200	305

Above 1GHz

Test Mode:	Transmitting Mode
-------------------	--------------------------

Frequency (MHz)	Meter Reading (dBµV)	Antenna Factor (dB)	Cable loss (dB)	Preamp factor (dB)	Emission Level (dBµV/m)	Limits (dBµV/m)	Margin (dB)	Detector (PK/AV)	Polarity (H/V)
Low Channel:GFSK Mode-2402MHz									
2390	36.35	28.72	3.36	26.32	42.11	74	-31.89	peak	Vertical
4804	27.14	32.94	3.98	27.49	36.57	54	-17.43	Average	Vertical
4804	36.32	32.94	3.98	27.49	45.75	74	-28.25	peak	Vertical
7206	31.18	25.28	5.51	27.94	34.03	54	-19.97	Average	Vertical
7206	39.64	25.28	5.51	27.94	42.49	74	-31.51	peak	Vertical
2390	37.62	28.72	3.36	26.32	43.38	74	-30.62	peak	Horizontal
4804	29.89	32.94	3.98	27.49	39.32	54	-14.68	Average	Horizontal
4804	40.28	32.94	3.98	27.49	49.71	74	-24.29	peak	Horizontal
7206	30.69	25.28	5.51	27.94	33.54	54	-20.46	Average	Horizontal
7206	41.17	25.28	5.51	27.94	44.02	74	-29.98	peak	Horizontal
Middle Channel:GFSK Mode-2441MHz									
4882	29.76	32.11	4.04	27.53	38.38	54	-15.62	Average	Vertical
4882	38.59	32.11	4.04	27.53	47.21	74	-26.79	peak	Vertical
7323	29.75	24.33	5.58	27.96	31.70	54	-22.30	Average	Vertical
7323	40.87	24.33	5.58	27.96	42.82	74	-31.18	peak	Vertical
4882	30.28	32.11	4.04	27.53	38.90	54	-15.10	Average	Horizontal
4882	40.48	32.11	4.04	27.53	49.10	74	-24.90	peak	Horizontal
7323	34.75	24.33	5.58	27.96	36.70	54	-17.30	Average	Horizontal
7323	40.65	24.33	5.58	27.96	42.60	74	-31.40	peak	Horizontal
High Channel:GFSK Mode-2480MHz									
2483.5	38.29	28.79	3.48	26.34	44.22	74	-29.78	peak	Vertical
4960	30.09	31.32	4.12	27.58	37.95	54	-16.05	Average	Vertical
4960	38.89	31.32	4.12	27.58	46.75	74	-27.25	peak	Vertical
7440	30.08	24.38	5.68	27.99	32.15	54	-21.85	Average	Vertical
7440	40.44	24.38	5.68	27.99	42.51	74	-31.49	peak	Vertical
2483.5	39.78	28.79	3.48	26.34	45.71	74	-28.29	peak	Horizontal
4960	29.53	31.32	4.12	27.58	37.39	54	-16.61	Average	Horizontal
4960	40.59	31.32	4.12	27.58	48.45	74	-25.55	peak	Horizontal
7440	33.64	24.38	5.68	27.99	35.71	54	-18.29	Average	Horizontal

Annex A. TEST INSTRUMENT

Instrument	Model	Serial #	Cal Date	Cal Due	In use
AC Line Conducted					
EMI test receiver	ESCS30	8471241027	09/15/2017	09/14/2018	<input checked="" type="checkbox"/>
Line Impedance	LI-125A	191106	09/23/2017	09/22/2018	<input checked="" type="checkbox"/>
Line Impedance	LI-125A	191107	09/23/2017	09/22/2018	<input checked="" type="checkbox"/>
ISN	ISN T800	34373	09/23/2017	09/22/2018	<input type="checkbox"/>
Transient Limiter	LIT-153	531118	08/30/2017	08/29/2018	<input type="checkbox"/>
RF conducted test					
Agilent ESA-E SERIES	E4407B	MY45108319	09/15/2017	09/14/2018	<input checked="" type="checkbox"/>
Power Splitter	1#	1#	08/30/2017	08/29/2018	<input checked="" type="checkbox"/>
DC Power Supply	E3640A	MY40004013	09/15/2017	09/14/2018	<input checked="" type="checkbox"/>
Radiated Emissions					
EMI test receiver	ESL6	100262	09/15/2017	09/14/2018	<input checked="" type="checkbox"/>
Positioning Controller	UC3000	MF780208282	11/17/2017	11/16/2018	<input checked="" type="checkbox"/>
OPT 010 AMPLIFIER (0.1-1300MHz)	8447E	2727A02430	08/30/2017	08/29/2018	<input checked="" type="checkbox"/>
Microwave Preamplifier (1 ~ 26.5GHz)	8449B	3008A02402	03/22/2018	03/21/2019	<input checked="" type="checkbox"/>
Horn Antenna	BBHA9170	3145226D1	09/27/2017	09/26/2018	<input checked="" type="checkbox"/>
Active Antenna (9kHz-30MHz)	AL-130	121031	10/12/2017	10/11/2018	<input checked="" type="checkbox"/>
Bilog Antenna (30MHz~6GHz)	JB6	A110712	09/19/2017	09/18/2018	<input checked="" type="checkbox"/>
Double Ridge Horn Antenna (1 ~18GHz)	AH-118	71283	09/22/2017	09/21/2018	<input checked="" type="checkbox"/>
Universal Radio Communication Tester	CMU200	121393	09/23/2017	09/22/2018	<input checked="" type="checkbox"/>

Annex B. EUT And Test Setup Photographs

Annex B.i. Photograph: EUT External Photo

Whole Package View



EUT - Front View



EUT - Top View



EUT - Bottom View



EUT - Left View



EUT - Right View



Adapter - Front View




Adapter - Front View




Annex B.ii. Photograph: EUT Internal Photo


Mainboard - Front View




Mainboard - Rear View



Small board - Front View




Small board - Rear View




Battery - Front View



Battery - Rear View



BT/BLE - Antenna View




Annex B.iii. Photograph: Test Setup Photo



Conducted Emissions Test Setup Front View



Conducted Emissions Test Setup Side View



Radiated Spurious Emissions Test Setup Below 1GHz




Radiated Spurious Emissions Test Setup Above
1GHz


Annex C. TEST SETUP AND SUPPORTING EQUIPMENT

Annex C.ii. TEST SET UP BLOCK


Block Configuration Diagram for AC Line Conducted Emissions



Block Configuration Diagram for Radiated Emissions (Below 1GHz) .



Block Configuration Diagram for Radiated Emissions (Above 1GHz) .



Annex C. ii. SUPPORTING EQUIPMENT DESCRIPTION

The following is a description of supporting equipment and details of cables used with the EUT.

Supporting Equipment:

Manufacturer	Equipment Description	Model	Serial No
Soundcast LLC	Adapter	ATS160T-P120	N/A
MEIZU	Phone	Y685Q	Y15QFBP922VGM
acer	Laptop	ZQE	N/A

Supporting Cable:

Cable type	Shield Type	Ferrite Core	Length	Serial No
Power Cable	Un-shielding	No	0.8m	N/A

Test Report No.	18070144-FCC-R2
Page	45 of 46

Annex D. User Manual / Block Diagram / Schematics / Partlist

Please see the attachment

Test Report No.	18070144-FCC-R2
Page	46 of 46

Annex E. DECLARATION OF SIMILARITY

N/A