

## RF MEASUREMENT REPORT

---

**FCC ID:** SVC-BLSP43A  
**Applicant:** Lenbrook Industries Limited  
**Product:** Wireless Streaming Sound System  
**Model No.:** PULSE SOUNDBAR+  
**Brand Name:** BLUESOUND  
**FCC Classification:** Digital Transmission System (DTS)  
**FCC Rule Part(s):** Part 15 Subpart C (Section 15.247)  
**Result:** Complies  
**Test Date:** 2021-08-27 ~ 2022-03-16 (Original Date)  
2021-08-15 ~ 2022-03-16 (Retest Date)

**Reviewed By:**

\_\_\_\_\_  
Kevin Guo

**Approved By:**

\_\_\_\_\_  
Robin Wu



The test results relate only to the samples tested.

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C63.10-2013. Test results reported herein relate only to the item(s) tested.

The test report shall not be reproduced except in full without the written approval of MRT Technology (Suzhou) Co., Ltd.

### Revision History

Report No.	Version	Description	Issue Date	Note
2105RSU032-U7	Rev. 01	Initial Report	2022-08-16	Valid

Note: This report reused the test data from other authorized device (FCC ID: SVC-BLSP43B, Original Grant Date: 08/04/2022). Since radio 2 changes from 19SoM with FC20 to 19SoM with 8223A and it is a plug-in module, the change has no effect on the radio 1 & 3 results.

---

## CONTENTS

Description	Page
<b>1. General Information .....</b>	<b>5</b>
1.1. Applicant .....	5
1.2. Manufacturer .....	5
1.3. Testing Facility .....	5
1.4. Product Information .....	6
1.5. Radio Specification .....	6
1.6. Working Frequencies .....	7
1.7. Antennas Information .....	7
1.8. Description of Operating Paths .....	8
<b>2. Test Configuration .....</b>	<b>9</b>
2.1. Test Mode .....	9
2.2. Test System Connection Diagram .....	9
2.3. Test Software .....	10
2.4. Applied Standards .....	10
2.5. Test Environment Condition .....	10
<b>3. Antenna Requirements .....</b>	<b>11</b>
<b>4. Measuring Instrument .....</b>	<b>12</b>
<b>5. Decision Rules and Measurement Uncertainty .....</b>	<b>14</b>
5.1. Decision Rules .....	14
5.2. Measurement Uncertainty .....	14
<b>6. Test Result .....</b>	<b>15</b>
6.1. Summary .....	15
6.2. 6dB Bandwidth .....	16
6.2.1. Test Limit .....	16
6.2.2. Test Procedure .....	16
6.2.3. Test Setting .....	16
6.2.4. Test Setup .....	16
6.2.5. Test Result .....	16
6.3. Output Power .....	17
6.3.1. Test Limit .....	17
6.3.2. Test Procedure .....	17
6.3.3. Test Setting .....	17
6.3.4. Test Setup .....	17
6.3.5. Test Result .....	17
6.4. Power Spectral Density .....	18
6.4.1. Test Limit .....	18

6.4.2.	Test Procedure .....	18
6.4.3.	Test Setting .....	18
6.4.4.	Test Setup .....	19
6.4.5.	Test Result .....	19
6.5.	Conducted Band Edge and Out-of-Band Emissions .....	20
6.5.1.	Test Limit .....	20
6.5.2.	Test Procedure .....	20
6.5.3.	Test Setting .....	20
6.5.4.	Test Setup .....	21
6.5.5.	Test Result .....	21
6.6.	Radiated Spurious Emission .....	22
6.6.1.	Test Limit .....	22
6.6.2.	Test Procedure .....	22
6.6.3.	Test Setting .....	22
6.6.4.	Test Setup .....	24
6.6.5.	Test Result .....	24
6.7.	Radiated Restricted Band Edge .....	25
6.7.1.	Test Limit .....	25
6.7.2.	Test Procedure .....	26
6.7.3.	Test Setting .....	26
6.7.4.	Test Setup .....	27
6.7.5.	Test Result .....	27
6.8.	AC Conducted Emissions .....	28
6.8.1.	Test Limit .....	28
6.8.2.	Test Setup .....	28
6.8.3.	Test Result .....	28
<b>Appendix A – Test Result .....</b>		<b>29</b>
A.1	Duty Cycle Test Result .....	29
A.2	6dB Bandwidth Test Result .....	31
A.3	Output Power Test Result .....	37
A.4	Power Spectral Density Test Result .....	41
A.5	Conducted Band Edge and Out-of-Band Emissions Test Result .....	47
A.6	Radiated Spurious Emission Test Result .....	65
A.7	Radiated Restricted Band Edge Test Result .....	77
A.8	AC Conducted Emissions Test Result .....	141
<b>Appendix B – Test Setup Photograph .....</b>		<b>145</b>
<b>Appendix C – EUT Photograph .....</b>		<b>146</b>



#### 1.4. Product Information

Product Name	Wireless Streaming Sound System
Model No.	PULSE SOUNDBAR+
Serial No.	H211P430BP01023, H215P430B04504, H211P430BP01011
Wi-Fi Specification	802.11a/b/g/n/ac
Bluetooth Specification	V4.2 single mode for BR/EDR
Antenna Information	Refer to section 1.7
Working Voltage	100-240V ~ 50/60Hz, 80W
Remark: <ol style="list-style-type: none"> <li>The information of EUT was provided by the manufacturer, and the accuracy of the information shall be the responsibility of the manufacturer.</li> <li>The device (FCC ID: SVC-BLSP43A) is based on the authorized device (FCC ID: SVC-BLSP43B, Original Grant Date: 08/04/2022) to change the Radio 2 from 19SoM with FC20 to 19SoM with 8223A. Others are the same with the authorized device. Details are shown in section 1.8 of this report.</li> <li>According to the description as above, this device reuses the test data of Radio 1 &amp; 3 of authorized device according to KDB 484596 D01v01.</li> </ol>	

#### 1.5. Radio Specification

Frequency Range	802.11b/g/n-HT20: 2412 ~ 2462MHz 802.11n-HT40: 2412 ~ 2452MHz
Channel Number	802.11b/g/n-HT20: 11 802.11n-HT40: 7
Type of Modulation	802.11b: DSSS 802.11g/n: OFDM
Data Rate	802.11b: 1/2/5.5/11Mbps 802.11g: 6/9/12/18/24/36/48/54Mbps 802.11n: up to 150Mbps

Note 1: For other features of this EUT, test report will be issued separately.

Note 2: Radio 2 and Radio 3 have the same Wi-Fi 2.4G radio specification.

### 1.6. Working Frequencies

802.11b/g/n-HT20

Channel	Frequency	Channel	Frequency	Channel	Frequency
01	2412 MHz	02	2417 MHz	03	2422 MHz
04	2427 MHz	05	2432 MHz	06	2437 MHz
07	2442 MHz	08	2447 MHz	09	2452 MHz
10	2457 MHz	11	2462 MHz	--	--

802.11n-HT40


Channel	Frequency	Channel	Frequency	Channel	Frequency
03	2422 MHz	04	2427 MHz	05	2432 MHz
06	2437 MHz	07	2442 MHz	08	2447 MHz
09	2452 MHz	--	--	--	--

### 1.7. Antennas Information

Antenna Type	Frequency Band (MHz)	T <sub>x</sub> Paths	Antenna Gain (dBi)
<b>Bluetooth</b>			
PIFA Antenna	2402 ~ 2480	1	0
<b>Radio 2 Wi-Fi Antenna</b>			
PIFA Antenna	2400 ~ 5850	1	0
<b>Radio 3 Wi-Fi Antenna</b>			
PIFA Antenna	2400 ~ 5850	1	0

### 1.8. Description of Operating Paths

Operating Mode	Radio 1 (CSR8675)	Radio 2 (19SoM with 8223A)	Radio 3 (FC20)
DSS (2402 ~ 2480MHz)	√	×	×
DTS (2412 ~ 2462MHz)	×	√	√
NII (5180 ~ 5240MHz)	×	√	√
NII (5260 ~ 5320MHz)	×	√	×
NII ( 5500 ~ 5720MHz)	×	√	×
NII (5745 ~ 5825MHz)	×	√	√



**Remark:**

1. “√” means “Support”, “X” means “Not support”.
2. Radio 1, Radio 2 and Radio 3 can transmit simultaneously, but Radio 2 and Radio 3 will not work at the same frequency, such as Radio 2 works at Wi-Fi 2.4G, Radio 3 will work at Wi-Fi 5G automatically at this time.
3. Wi-Fi 2.4G and 5G of Radio 2 or Radio 3 cannot transmit simultaneously.




## 2. Test Configuration

### 2.1. Test Mode

Radio 2
Mode 1: Transmit by 802.11b (1Mbps)
Mode 2: Transmit by 802.11g (54Mbps)
Mode 3: Transmit by 802.11n-HT20 (MCS7)
Mode 4: Transmit by 802.11n-HT40 (MCS7)
Radio 3
Mode 5: Transmit by 802.11b (1Mbps)
Mode 6: Transmit by 802.11g (6Mbps)
Mode 7: Transmit by 802.11n-HT20 (MCS0)
Mode 8: Transmit by 802.11n-HT40 (MCS0)

### 2.2. Test System Connection Diagram

The device was tested per the guidance ANSI C63.10-2013 was used to reference the appropriate EUT setup for radiated emissions testing and AC line conducted testing.

Connection Diagram			
			
No.	Cable Type	Cable Spec.	Length
A	LAN Cable	Non-Shielded	> 10.0m
B	Power Cable	Non-Shielded	< 3.0m
C	LAN Cable	Non-Shielded	< 2.0m

No.	Product	Manufacturer	Model No.
1	Router	NETGEAR	R6220
2	Notebook	Lenovo	E431

### 2.3. Test Software

The test utility software used during testing was “SecureCRT”, and the version was 6.2.3 (build 313).

### 2.4. Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- FCC Part 15.247
- KDB 558074 D01v05r02
- ANSI C63.10-2013

### 2.5. Test Environment Condition

Ambient Temperature	15 ~ 35°C
Relative Humidity	20 ~ 75%RH

### 3. Antenna Requirements

#### **Excerpt from §15.203 of the FCC Rules/Regulations:**

“An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.”

- The antenna of the device is **permanently attached**.
- There are no provisions for connection to an external antenna.

#### **Conclusion:**

The unit complies with the requirement of §15.203.

#### 4. Measuring Instrument

Instrument	Manufacturer	Model No.	Asset No.	Cali. Interval	Cali. Due Date	Test Site
EMI Test Receiver	R&S	ESR7	MRTSUE06001	1 year	2022-12-29	WZ-AC1
				1 year	2021-12-31	WZ-AC1
TRILOG Antenna	Schwarzbeck	VULB 9168	MRTSUE06172	1 year	2022-06-21	WZ-AC1
Anechoic Chamber	TDK	WZ-AC1	MRTSUE06212	1 year	2022-04-21	WZ-AC1
Thermohygrometer	testo	608-H1	MRTSUE06403	1 year	2022-06-06	WZ-AC1
Signal Analyzer	Keysight	N9010B	MRTSUE06607	1 year	2022-12-29	WZ-AC1
				1 year	2021-12-31	WZ-AC1
Thermohygrometer	testo	Testo 608-H1	MRTSUE11039	1 year	2022-11-11	WZ-AC1
				1 year	2021-11-15	WZ-AC1
Loop Antenna	Schwarzbeck	FMZB 1519	MRTSUE06025	1 year	2022-10-28	WZ-AC1
				1 year	2021-10-30	WZ-AC1
Horn Antenna	ETS	3117	MRTSUE06257	1 year	2022-09-25	WZ-AC2
				1 year	2022-09-28	WZ-AC2
Horn Antenna	Schwarzbeck	BBHA 9170	MRTSUE06597	1 year	2022-12-01	WZ-AC2
				1 year	2021-12-05	WZ-AC2
Preamplifier	EMCI	EMC184045SE	MRTSUE06640	1 year	2023-01-13	WZ-AC2
				1 year	2022-01-16	WZ-AC2
Preamplifier	EMCI	EMC051845SE	MRTSUE06987	1 year	2022-09-09	WZ-AC2
				1 year	2021-09-11	WZ-AC2
Thermohygrometer	Mingle	ETH529	MRTSUE06170	1 year	2022-12-01	WZ-AC2
				1 year	2021-12-04	WZ-AC2
Horn Antenna	Schwarzbeck	BBHA 9120D	MRTSUE06171	1 year	2022-10-21	WZ-AC2
				1 year	2021-10-24	WZ-AC2
Preamplifier	Schwarzbeck	BBV 9718	MRTSUE06176	1 year	2022-11-12	WZ-AC2
Anechoic Chamber	RIKEN	WZ-AC2	MRTSUE06213	1 year	2022-04-21	WZ-AC2
Thermohygrometer	testo	Testo 608-H1	MRTSUE11038	1 year	2022-11-11	WZ-AC2
				1 year	2021-11-15	WZ-AC2
Two-Line V-Network	R&S	ENV216	MRTSUE06002	1 year	2022-06-04	WZ-SR2
CDN	Teseq	ISN PLT-A	MRTSUE06007	1 year	2022-03-28	WZ-SR2
Shielding Room	MIX-BEP	WZ-SR2	MRTSUE06215	5 years	2026-12-20	WZ-SR2
Thermohygrometer	testo	608-H1	MRTSUE06404	1 year	2022-06-06	WZ-SR2
EMI Test Receiver	R&S	ESR3	MRTSUE06909	1 year	2022-11-01	WZ-SR2
				1 year	2021-11-09	WZ-SR2
USB Power Sensor	Agilent	U2021XA	MRTSUE06030	1 year	2022-10-10	WZ-SR5
				1 year	2021-10-18	WZ-SR5

Instrument	Manufacturer	Model No.	Asset No.	Cali. Interval	Cali. Due Date	Test Site
USB Power Sensor	Boonton	55006	MRTSUE06109	1 year	2022-04-06	WZ-SR5
USB Power Sensor	Keysight	U2021XA	MRTSUE06446	1 year	2022-06-04	WZ-SR5
USB Power Sensor	Keysight	U2021XA	MRTSUE06447	1 year	2022-06-04	WZ-SR5
USB Power Sensor	Keysight	U2021XA	MRTSUE06582	1 year	2022-08-08	WZ-SR5
				1 year	2021-08-10	WZ-SR5
Signal Analyzer	Agilent	N9020A	MRTSUE06106	1 year	2022-04-06	WZ-SR5
Thermohygrometer	testo	608-H1	MRTSUE06402	1 year	2022-06-06	WZ-SR5
Shielding Room	HUAMING	WZ-SR5	MRTSUE06442	N/A	N/A	WZ-SR5
Signal Analyzer	Keysight	N9010B	MRTSUE06457	1 year	2022-06-04	WZ-SR5
Attenuator	MVE	MVE2213	MRTSUE11071	1 year	2022-06-09	WZ-SR5
Attenuator	MVE	MVE2213	MRTSUE11072	1 year	2022-06-09	WZ-SR5
Attenuator	MVE	MVE2213	MRTSUE11073	1 year	2022-06-09	WZ-SR5

Software	Version	Function
EMI Software	V3	EMI Test Software
Controller_MF 7802	2.03C	RE Antenna & Turntable
Controller_MF 7802	1.02	RE Antenna & Turntable
Agilent Power Panel	V 3.9	Power

## 5. Decision Rules and Measurement Uncertainty

### 5.1. Decision Rules

The Decision Rule is based on Simple Acceptance in accordance with ISO Guide 98-4: 2012 Clause 8.2. (Measurement uncertainty is not taken into account when stating conformity with a specified requirement.)

### 5.2. Measurement Uncertainty

Where relevant, the following test uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of  $k = 2$ .

<b>AC Conducted Emission Measurement</b>
Measurement Uncertainty for a Level of Confidence of 95% ( $U=2Uc(y)$ ): 9kHz~150kHz: 3.74dB 150kHz~30MHz: 3.44dB
<b>Radiated Disturbance</b>
Measurement Uncertainty for a Level of Confidence of 95% ( $U=2Uc(y)$ ): Horizontal: 30MHz~300MHz: 5.04dB 300MHz~1GHz: 4.95dB 1GHz~40GHz: 6.40dB Vertical: 30MHz~300MHz: 5.24dB 300MHz~1GHz: 6.03dB 1GHz~40GHz: 6.40dB
<b>Spurious Emissions, Conducted</b>
Measuring Uncertainty for a Level of Confidence of 95% ( $U=2Uc(y)$ ): 0.78dB
<b>Output Power</b>
Measuring Uncertainty for a Level of Confidence of 95% ( $U=2Uc(y)$ ): 1.13dB
<b>Power Spectrum Density</b>
Measuring Uncertainty for a Level of Confidence of 95% ( $U=2Uc(y)$ ): 1.15dB
<b>Occupied Bandwidth</b>
Measuring Uncertainty for a Level of Confidence of 95% ( $U=2Uc(y)$ ): 0.28%

## 6. Test Result

### 6.1. Summary

FCC Section(s)	Test Description	Test Condition	Verdict
15.247(a)(2)	6dB Bandwidth	Conducted	Pass
15.247(b)(3)	Output Power		Pass
15.247(e)	Power Spectral Density		Pass
15.247(d)	Band Edge / Out-of-Band Emissions		Pass
15.205 15.209	General Field Strength (Restricted Bands and Radiated Emission)	Radiated	Pass
15.207	AC Conducted Emissions 150kHz - 30MHz	Line Conducted	Pass

**Remark:**

The analyzer plots shown in this section were all taken with a correction table loaded into the analyzer. The correction table was used to account for the losses of the cables and attenuators used as part of the system to connect the EUT to the analyzer at all frequencies of interest.

## 6.2. 6dB Bandwidth

### 6.2.1. Test Limit

The minimum 6dB bandwidth shall be at least 500 kHz.


### 6.2.2. Test Procedure

ANSI C63.10-2013 - Section 11.8

### 6.2.3. Test Setting

1. The Spectrum's automatic bandwidth measurement capability was used to perform the 6dB bandwidth measurement. The "X" dB bandwidth parameter was set to  $X = 6$ . The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
2. Set RBW = 100 kHz
3.  $VBW \geq 3 \times RBW$
4. Detector = Peak
5. Trace mode = Max hold
6. Sweep = Auto couple
7. Allow the trace to stabilize

### 6.2.4. Test Setup



### 6.2.5. Test Result

Refer to Appendix A.2.



### 6.3. Output Power

#### 6.3.1. Test Limit

The maximum output power shall be less 1 Watt (30dBm).

The conducted output power limit specified in paragraph FCC Part 15.247(b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. If transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs FCC Part 15.247(b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

#### 6.3.2. Test Procedure

ANSI C63.10-2013 - Section 11.9.2.3.2

#### 6.3.3. Test Setting

##### Average Power Measurement

Average power measurements were performed only when the EUT was transmitting at its maximum power control level using a broadband power meter with a pulse sensor. The power meter implemented triggering and gating capabilities which were set up such that power measurements were recorded only during the ON time of the transmitter.

#### 6.3.4. Test Setup



#### 6.3.5. Test Result

Refer to Appendix A.3.

## **6.4. Power Spectral Density**

### **6.4.1. Test Limit**

The maximum permissible power spectral density is 8dBm in any 3 kHz band.

The same method of determining the conducted output power shall be used to determine the power spectral density.

### **6.4.2. Test Procedure**


ANSI C63.10-2013 - Section 11.10.5

### **6.4.3. Test Setting**

1. Measure the duty cycle (x) of the transmitter output signal.
2. Set instrument center frequency to DTS channel center frequency.
3. Set span to at least 1.5 times the OBW.
4. RBW = 10 kHz.
5. VBW = 30 kHz.
6. Detector = RMS.
7. Ensure that the number of measurement points in the sweep  $\geq 2 \times \text{span}/\text{RBW}$ .
8. Sweep time = auto couple.
9. Don't use sweep triggering. Allow sweep to "free run".
10. Employ trace averaging (RMS) mode over a minimum of 100 traces.
11. Use the peak marker function to determine the maximum amplitude level.
12. Add  $10 \log (1/x)$ , where x is the duty cycle measured in step (a), to the measured PSD to compute the average PSD during the actual transmission time. If measured value exceeds requirement specified by regulatory agency, then reduce RBW (but no less than 3 kHz) and repeat (note that this may require zooming in on the emission of interest and reducing the span to meet the minimum measurement point requirement as the RBW is reduced).

#### 6.4.4. Test Setup

Spectrum Analyzer



DC Block  
&  
Attenuator



#### 6.4.5. Test Result

Refer to Appendix A.4.

## **6.5. Conducted Band Edge and Out-of-Band Emissions**

### **6.5.1. Test Limit**

The limit for out-of-band spurious emissions at the band edge is 30dB below the fundamental emission level, as determined from the in-band power measurement of the DTS channel performed in a 100 kHz bandwidth per the PSD procedure.

### **6.5.2. Test Procedure**

ANSI C63.10-2013 - Section 11.11

### **6.5.3. Test Setting**

#### **Reference level measurement**


1. Set instrument center frequency to DTS channel center frequency
2. Set the span to  $\geq 1.5$  times the DTS bandwidth
3. Set the RBW = 100 kHz
4. Set the VBW  $\geq 3 \times$  RBW
5. Detector = peak
6. Sweep time = auto couple
7. Trace mode = max hold
8. Allow trace to fully stabilize

#### **Emission level measurement**

1. Set the center frequency and span to encompass frequency range to be measured
2. RBW = 100kHz
3. VBW = 300kHz
4. Detector = Peak
5. Trace mode = max hold
6. Sweep time = auto couple
7. The trace was allowed to stabilize

#### 6.5.4. Test Setup

Spectrum Analyzer



DC Block  
&  
Attenuator



#### 6.5.5. Test Result

Refer to Appendix A.5.

## 6.6. Radiated Spurious Emission

### 6.6.1. Test Limit

All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47 CFR must not exceed the limits shown in Table per Section 15.209.

FCC Part 15 Subpart C Paragraph 15.209		
Frequency [MHz]	Field Strength [uV/m]	Measured Distance [Meters]
0.009 - 0.490	2400/F (kHz)	300
0.490 - 1.705	24000/F (kHz)	30
1.705 - 30	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

### 6.6.2. Test Procedure

ANSI C63.10-2013 - Section 11.11 & 11.12

ANSI C63.10-2013 - Section 6.3 (General Requirements)

ANSI C63.10-2013 - Section 6.4 (Standard test method below 30MHz)

ANSI C63.10-2013 - Section 6.5 (Standard test method above 30MHz to 1GHz)

ANSI C63.10-2013 - Section 6.6 (Standard test method above 1GHz)

### 6.6.3. Test Setting

**Table 1 - RBW as a function of frequency**

Frequency	RBW
9 ~ 150 kHz	200 ~ 300 Hz
0.15 ~ 30 MHz	9 ~ 10 kHz
30 ~ 1000 MHz	100 ~ 120 kHz
> 1000MHz	1MHz

**Quasi-Peak Measurements below 1GHz**

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. Span was set greater than 1MHz
3. RBW = as specified in Table 1
4. Detector = CISPR quasi-peak
5. Sweep time = auto couple
6. Trace was allowed to stabilize

**Peak Measurements above 1GHz**


1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1MHz
3. VBW = 3MHz
4. Detector = peak
5. Sweep time = auto couple
6. Trace mode = max hold
7. Trace was allowed to stabilize

**Average Measurements above 1GHz (Method VB)**


1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1MHz
3. VBW; If the EUT is configured to transmit with duty cycle  $\geq 98\%$ , set VBW = 10 Hz.  
If the EUT duty cycle is  $< 98\%$ , set VBW  $\geq 1/T$ . T is the minimum transmission duration.
4. Detector = Peak
5. Sweep time = auto
6. Trace mode = max hold
7. Trace was allowed to stabilize

### 6.6.4. Test Setup

Below 1GHz Test Setup:



Above 1GHz Test Setup:



### 6.6.5. Test Result

Refer to Appendix A.6.



## 6.7. Radiated Restricted Band Edge

### 6.7.1. Test Limit

#### For 15.205 requirement:

Radiated emissions which fall in the restricted bands, as defined in Section 15.205(a) of FCC part 15, must also comply with the radiated emission limits specified in Section 15.209(a).

Frequency (MHz)	Frequency (MHz)	Frequency (MHz)	Frequency (GHz)
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
<sup>1</sup> 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2690 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	( <sup>2</sup> )
13.36 - 13.41	--	--	--

All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47CFR must not exceed the limits shown in Table per Section 15.209.

FCC Part 15 Subpart C Paragraph 15.209		
Frequency [MHz]	Field Strength [uV/m]	Measured Distance [Meters]
0.009 - 0.490	2400/F (kHz)	300
0.490 - 1.705	24000/F (kHz)	30
1.705 - 30	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

### 6.7.2. Test Procedure

ANSI C63.10-2013 Section 6.3

ANSI C63.10-2013 Section 6.6

ANSI C63.10-2013 Section 11.13

### 6.7.3. Test Setting


#### Peak Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1MHz
3. VBW = 3MHz
4. Detector = peak
5. Sweep time = auto couple
6. Trace mode = max hold
7. Trace was allowed to stabilize

### Average Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1MHz
3. VBW  $\geq 1/T$
4. As an alternative, the instrument may be set to linear detector mode. Ensure that video filtering is applied in linear voltage domain (rather than in a log or dB domain). Some instruments require linear display mode in order to accomplish this. Others have a setting for Average-VBW Type, which can be set to "Voltage" regardless of the display mode
5. Detector = Peak
6. Sweep time = auto
7. Trace mode = max hold
8. Allow max hold to run for at least 50 times (1/duty cycle) traces

#### 6.7.4. Test Setup



#### 6.7.5. Test Result

Refer to Appendix A.7.

## 6.8. AC Conducted Emissions


### 6.8.1. Test Limit

FCC Part 15 Subpart C Paragraph 15.207 Limits		
Frequency (MHz)	QP (dBuV)	AV (dBuV)
0.15 - 0.50	66 - 56	56 - 46
0.50 - 5.0	56	46
5.0 - 30	60	50

Note 1: The lower limit shall apply at the transition frequencies.

Note 2: The limit decreases linearly with the logarithm of the frequency in the range 0.15MHz to 0.5MHz.

### 6.8.2. Test Setup



### 6.8.3. Test Result

Refer to Appendix A.8.


## Appendix A – Test Result

### A.1 Duty Cycle Test Result

Radio 2 Test Data – Retest Data			
Test Site	WZ-SR5	Test Engineer	Liz Yuan
Test Date	2021/08/15		

Test Mode	Duty Cycle
802.11b	99.04%
802.11g	93.64%
802.11n-HT20	93.03%
802.11n-HT40	89.30%


#### Duty Cycle (T = Transmission Duration)



Radio 3 Test Data – Original Data			
Test Site	WZ-SR5	Test Engineer	Liz Yuan
Test Date	2021/12/17		

Test Mode	Duty Cycle
802.11b	98.81%
802.11g	90.77%
802.11n-HT20	93.87%
802.11n-HT40	87.57%

Duty Cycle (T = Transmission Duration)




**A.2 6dB Bandwidth Test Result**

Radio 2 Test Data – Retest Data			
Test Site	WZ-SR5	Test Engineer	Liz Yuan
Test Date	2021/08/15 ~ 2022/03/16		


Test Mode	Data Rate / MCS	Channel No.	Frequency (MHz)	6dB Bandwidth (MHz)	Limit (MHz)
11b	1Mbps	01	2412	8.084	≥ 0.5
11b	1Mbps	06	2437	8.078	≥ 0.5
11b	1Mbps	11	2462	7.242	≥ 0.5
11g	54Mbps	01	2412	15.35	≥ 0.5
11g	54Mbps	06	2437	15.15	≥ 0.5
11g	54Mbps	11	2462	15.13	≥ 0.5
11n-HT20	MCS7	01	2412	15.12	≥ 0.5
11n-HT20	MCS7	06	2437	15.15	≥ 0.5
11n-HT20	MCS7	11	2462	14.98	≥ 0.5
11n-HT40	MCS7	03	2422	35.14	≥ 0.5
11n-HT40	MCS7	06	2437	35.09	≥ 0.5
11n-HT40	MCS7	09	2452	35.10	≥ 0.5

### 802.11b 6dB Bandwidth


#### Channel 01 (2412MHz)



#### Channel 06 (2437MHz)




#### Channel 11 (2462MHz)




### 802.11g 6dB Bandwidth


#### Channel 01 (2412MHz)



#### Channel 06 (2437MHz)




#### Channel 11 (2462MHz)






802.11n-HT20 6dB Bandwidth


Channel 01 (2412MHz)



Channel 06 (2437MHz)




Channel 11 (2462MHz)




802.11n-HT40 6dB Bandwidth


Channel 03 (2422MHz)



Channel 06 (2437MHz)



Channel 09 (2452MHz)




Radio 3 Test Data – Original Data			
Test Site	WZ-SR5	Test Engineer	Liz Yuan
Test Date	2021/12/16 ~ 2022/03/16		


Test Mode	Data Rate / MCS	Channel No.	Frequency (MHz)	6dB Bandwidth (MHz)	Limit (MHz)
11b	1Mbps	01	2412	8.090	≥ 0.5
11b	1Mbps	06	2437	9.050	≥ 0.5
11b	1Mbps	11	2462	7.104	≥ 0.5
11g	6Mbps	01	2412	15.08	≥ 0.5
11g	6Mbps	06	2437	15.72	≥ 0.5
11g	6Mbps	11	2462	13.78	≥ 0.5
11n-HT20	MCS0	01	2412	15.97	≥ 0.5
11n-HT20	MCS0	06	2437	15.97	≥ 0.5
11n-HT20	MCS0	11	2462	14.98	≥ 0.5
11n-HT40	MCS0	03	2422	35.09	≥ 0.5
11n-HT40	MCS0	06	2437	35.06	≥ 0.5
11n-HT40	MCS0	09	2452	35.05	≥ 0.5

### 802.11b 6dB Bandwidth


#### Channel 01 (2412MHz)



#### Channel 06 (2437MHz)




#### Channel 11 (2462MHz)




### 802.11g 6dB Bandwidth


#### Channel 01 (2412MHz)



#### Channel 06 (2437MHz)




#### Channel 11 (2462MHz)




## 802.11n-HT20 6dB Bandwidth


## Channel 01 (2412MHz)



## Channel 06 (2437MHz)




## Channel 11 (2462MHz)




## 802.11n-HT40 6dB Bandwidth

## Channel 03 (2422MHz)



## Channel 06 (2437MHz)



## Channel 09 (2452MHz)



### A.3 Output Power Test Result

#### Radio 2 Test Data – Retest Data

Power output test was verified over all data rates of each mode shown as below, and then choose the maximum power output (gray marker) for final test of each channel.

Test Mode	Bandwidth (MHz)	Channel No.	Frequency (MHz)	Data Rate / MCS	Average Power (dBm)
802.11b	20	6	2437	1Mbps	20.90
				5.5Mbps	20.77
				11Mbps	20.59
802.11g	20	6	2437	6Mbps	20.66
				24Mbps	20.83
				54Mbps	20.95
802.11n	20	6	2437	MCS0	20.18
				MCS3	20.26
				MCS7	20.41
802.11n	40	6	2437	MCS0	20.03
				MCS3	20.12
				MCS7	20.25

Test Site	WZ-SR5	Test Engineer	Liz Yuan
Test Date	2021/12/06 ~ 2022/03/16		

Test Mode	Data Rate/ MCS	Channel No.	Freq. (MHz)	Average Power (dBm)	Limit (dBm)
11b	1Mbps	01	2412	20.55	≤ 30.00
11b	1Mbps	06	2437	20.90	≤ 30.00
11b	1Mbps	11	2462	20.61	≤ 30.00
11g	54Mbps	01	2412	18.16	≤ 30.00
11g	54Mbps	06	2437	20.95	≤ 30.00
11g	54Mbps	11	2462	21.02	≤ 30.00
11n-HT20	MCS7	01	2412	16.93	≤ 30.00
11n-HT20	MCS7	06	2437	20.41	≤ 30.00
11n-HT20	MCS7	11	2462	17.35	≤ 30.00
11n-HT40	MCS7	03	2422	12.65	≤ 30.00
11n-HT40	MCS7	06	2437	20.25	≤ 30.00
11n-HT40	MCS7	09	2452	14.42	≤ 30.00

**Radio 3 Test Data – Original Data**

Power output test was verified over all data rates of each mode shown as below, and then choose the maximum power output (gray marker) for final test of each channel.

Test Mode	Bandwidth (MHz)	Channel No.	Frequency (MHz)	Data Rate / MCS	Average Power (dBm)
802.11b	20	6	2437	1Mbps	20.36
				5.5Mbps	20.22
				11Mbps	20.10
802.11g	20	6	2437	6Mbps	19.55
				24Mbps	19.43
				54Mbps	19.27
802.11n	20	6	2437	MCS0	19.42
				MCS3	19.28
				MCS7	19.14
802.11n	40	6	2437	MCS0	19.37
				MCS3	19.22
				MCS7	19.04

Test Site	WZ-SR5	Test Engineer	Liz Yuan
Test Date	2022/01/22 ~ 2022/03/16		

Test Mode	Data Rate/ MCS	Channel No.	Freq. (MHz)	Average Power (dBm)	Limit (dBm)
11b	1Mbps	01	2412	19.27	≤ 30.00
11b	1Mbps	06	2437	20.36	≤ 30.00
11b	1Mbps	11	2462	19.25	≤ 30.00
11g	6Mbps	01	2412	17.45	≤ 30.00
11g	6Mbps	06	2437	19.55	≤ 30.00
11g	6Mbps	11	2462	18.70	≤ 30.00
11n-HT20	MCS0	01	2412	17.86	≤ 30.00
11n-HT20	MCS0	06	2437	19.42	≤ 30.00
11n-HT20	MCS0	11	2462	18.35	≤ 30.00
11n-HT40	MCS0	03	2422	16.78	≤ 30.00
11n-HT40	MCS0	06	2437	19.37	≤ 30.00
11n-HT40	MCS0	09	2452	12.78	≤ 30.00



**A.4 Power Spectral Density Test Result**

Radio 2 Test Data - Retest Data			
Test Site	WZ-SR5	Test Engineer	Liz Yuan
Test Date	2022/01/15 ~ 2022/03/16		

Test Mode	Data Rate/MCS	Channel No.	Freq. (MHz)	AV PSD (dBm/10kHz)	Duty Cycle (%)	10*log (1/x)	Total PSD (dBm/10kHz)	Limit (dBm/3kHz)	Result
11b	1Mbps	01	2412	-5.50	99.04	0.04	-5.50	≤ 8.00	Pass
11b	1Mbps	06	2437	-5.65	99.04	0.04	-5.65	≤ 8.00	Pass
11b	1Mbps	11	2462	-5.75	99.04	0.04	-5.75	≤ 8.00	Pass
11g	54Mbps	01	2412	-10.10	93.64	0.29	-9.81	≤ 8.00	Pass
11g	54Mbps	06	2437	-8.75	93.64	0.29	-8.46	≤ 8.00	Pass
11g	54Mbps	11	2462	-9.65	93.64	0.29	-9.36	≤ 8.00	Pass
11n-HT20	MCS7	01	2412	-11.30	93.03	0.31	-10.99	≤ 8.00	Pass
11n-HT20	MCS7	06	2437	-8.75	93.03	0.31	-8.44	≤ 8.00	Pass
11n-HT20	MCS7	11	2462	-11.22	93.03	0.31	-10.91	≤ 8.00	Pass
11n-HT40	MCS7	03	2422	-18.93	89.30	0.49	-18.44	≤ 8.00	Pass
11n-HT40	MCS7	06	2437	-11.72	89.30	0.49	-11.23	≤ 8.00	Pass
11n-HT40	MCS7	09	2452	-17.02	89.30	0.49	-16.53	≤ 8.00	Pass

Note:

When EUT duty cycle > 98%, Total PSD (dBm/10kHz) = AV PSD (dBm/10kHz)

When EUT duty cycle ≤ 98%, Total PSD (dBm/10kHz) = AV PSD (dBm/10kHz) + 10\*log (1/Duty Cycle).

802.11b – AV PSD

Channel 01 (2412MHz)



Channel 06 (2437MHz)




Channel 11 (2462MHz)




802.11g – AV PSD


Channel 01 (2412MHz)



Channel 06 (2437MHz)




Channel 11 (2462MHz)




802.11n-HT20 – AV PSD


Channel 01 (2412MHz)



Channel 06 (2437MHz)




Channel 11 (2462MHz)




802.11n-HT40 – AV PSD


Channel 03 (2422MHz)



Channel 06 (2437MHz)



Channel 09 (2452MHz)



Radio 3 Test Data - Original Data			
Test Site	WZ-SR5	Test Engineer	Liz Yuan
Test Date	2021/12/17 ~ 2022/03/16		

Test Mode	Data Rate/MCS	Channel No.	Freq. (MHz)	AV PSD (dBm/10kHz)	Duty Cycle (%)	10*log (1/x)	Total PSD (dBm/10kHz)	Limit (dBm/3kHz)	Result
11b	1Mbps	01	2412	-5.90	98.81	0.05	-5.90	≤ 8.00	Pass
11b	1Mbps	06	2437	-5.22	98.81	0.05	-5.22	≤ 8.00	Pass
11b	1Mbps	11	2462	-4.64	98.81	0.05	-4.64	≤ 8.00	Pass
11g	6Mbps	01	2412	-10.73	90.77	0.42	-10.31	≤ 8.00	Pass
11g	6Mbps	06	2437	-9.27	90.77	0.42	-8.85	≤ 8.00	Pass
11g	6Mbps	11	2462	-9.69	90.77	0.42	-9.27	≤ 8.00	Pass
11n-HT20	MCS0	01	2412	-9.80	93.87	0.27	-9.53	≤ 8.00	Pass
11n-HT20	MCS0	06	2437	-9.01	93.87	0.27	-8.73	≤ 8.00	Pass
11n-HT20	MCS0	11	2462	-9.50	93.87	0.27	-9.23	≤ 8.00	Pass
11n-HT40	MCS0	03	2422	-15.80	87.57	0.58	-15.22	≤ 8.00	Pass
11n-HT40	MCS0	06	2437	-11.47	87.57	0.58	-10.89	≤ 8.00	Pass
11n-HT40	MCS0	09	2452	-18.62	87.57	0.58	-18.04	≤ 8.00	Pass

Note:

When EUT duty cycle > 98%, Total PSD (dBm/10kHz) = AV PSD (dBm/10kHz)

When EUT duty cycle ≤ 98%, Total PSD (dBm/10kHz) = AV PSD (dBm/10kHz) + 10\*log (1/Duty Cycle).

802.11b – AV PSD

Channel 01 (2412MHz)



Channel 06 (2437MHz)




Channel 11 (2462MHz)




802.11g – AV PSD


Channel 01 (2412MHz)



Channel 06 (2437MHz)




Channel 11 (2462MHz)




## 802.11n-HT20 – AV PSD


## Channel 01 (2412MHz)



## Channel 06 (2437MHz)




## Channel 11 (2462MHz)




## 802.11n-HT40 – AV PSD

## Channel 03 (2422MHz)



## Channel 06 (2437MHz)



## Channel 09 (2452MHz)

