Safety Human Exposure

1.1 Radio Frequency Exposure Compliance

1.1.1 Electromagnetic Fields

RESULT:

Pass

Test Specification		
Test item	:	Smart interactive whiteboard
Identification / Type No.	:	DHI-LCH65-MC410-B
FCC ID	:	SVN-LCH65
Test standard	:	CFR47 FCC Part 2: Section 2.1091
		CFR47 FCC Part 1: Section 1.1310
		FCC KDB Publication 447498 v06
		FCC KDB Publication 865664 D01 v01r04
		FCC KDB Publication 865664 D02 v01r02

Product Classification

This device defined as a transmitting device designed to be used in other than fixed locations and to generally be used in such a way that a separation distance of at 20 cm is normally maintained between the transmitter's radiating structure(s) and the body of the user or nearby persons.

Max 5.14 dBi for 2.4GHz Wi-Fi, Max 4.69 dBi for 5GHz Wi-Fi

> Radio Frequency Exposure Limit

For FCC:	For	FC	C:
----------	-----	----	----

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm²)
300-1,500			f/1500
1,500-100,000			1.0

For IC:

Frequency Range	Electric Field	Magnetic Field	Power Density	Reference Period
(MHz)	(V/m rms)	(A/m rms)	(W/m ²)	(minutes)
0.003-10 ²¹	83	90	-	Instantaneous*
0.1-10	-	0.73/ f	-	6**
1.1-10	87/ f ^{0.5}	-	-	6**
10-20	27.46	0.0728	2	6
20-48	58.07/ f ^{0.25}	0.1540/ f ^{0.25}	8.944/ f ^{0.5}	6
48-300	22.06	0.05852	1.291	6
300-6000	$3.142 f^{0.3417}$	$0.008335 f^{0.3417}$	$0.02619 f^{0.6834}$	6
6000-15000	61.4	0.163	10	6
15000-150000	61.4	0.163	10	$616000/f^{1.2}$
150000-300000	$0.158 f^{0.5}$	$4.21 \ge 10^{-4} f^{0.5}$	6.67 x 10 ⁻⁵ f	616000/ f ^{1.2}
Note: <i>f</i> is frequency in MHz.				
*Based on nerve stimulation (NS).				
** Based on specific absorption rate (SAR).				

> Radio Frequency Exposure Calculation Formula

$$S = \frac{PG}{4\pi R^2}$$

where: S = power density (in appropriate units, e.g. mW/cm²)

P = power input to the antenna (in appropriate units, e.g., mW)

- G = power gain of the antenna in the direction of interest relative to an isotropic radiator
- R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

or:

$$S = \frac{EIRP}{4\pi R^2}$$

where: EIRP = equivalent (or effective) isotropically radiated power

a) EUT RF Exposure Evaluation standalone operations

Mode	*Measured RF Output Power (dBm)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm²)	FCC Limit (mW/cm²)
2.4G Wi-Fi	24.06	5.14	20	0.166	1.0
5G Wi-Fi	20.94	4.69	20	0.073	1.0

Note:

- *2.4GHz Band RF Output Power: Refer CN22GK21 001 Appendix B
 *5GHz Bands RF Output Power: Refer CN22GK21 002 Appendix B

b) Simultaneous transmission MPE:

Per KDB 447498 D01 v06, simultaneous transmission MPE test exclusion applies when the sum of the MPE ratios for all simultaneous transmitting antennas incorporated in a host device, based on calculated or measured field strengths or power density, is \leq 1.0.

Simultaneous transmission Scenarios

No.	Simultaneous transmission Scenarios
1	2.4GHz Wi-Fi
2	5GHz Wi-Fi

1) For 2.4GHz Wi-Fi:

The MPE ratio for 2.4GHz WiFi can be calculated as follow: =The power density at 20cm distance/MPE limit =0.166 mW/cm²/1 mW/cm² =0.166

2) For 5GHz Wi-Fi:

The MPE ratio for 5GHz WiFi can be calculated as follow: =The power density at 20cm distance/MPE limit =0.073 mW/cm²/1 mW/cm² =0.073

The sum of the MPE ratios for all simultaneous transmitting antennas: =0.166+0.073 = 0.239<1.0

As the sum of MPE ratios for all simultaneous transmitting antennas is \leq 1.0, simultaneous transmission MPE test exclusion will be applied.

> Conclusion

Therefore the maximum calculations result of above are meet the requirement of Radio Frequency Exposure (MPE) limit.