

Report No.: SHEM190201084302

Page: 1 of 7

1 Cover Page

RF Exposure Evaluation Report

Application No.: SHEM1902010843CR **FCC ID:** SVNDH-IPC-B1BX0-B

Applicant: Zhejiang Dahua Vision Technology Co., Ltd.

Address of Applicant: No.1199, Bin'an Road, Binjiang District, Hangzhou, P.R. China

Manufacturer: Zhejiang Dahua Vision Technology Co., Ltd.

Address of Manufacturer: No.1199, Bin'an Road, Binjiang District, Hangzhou, P.R. China

Equipment Under Test (EUT):

EUT Name: CONSUMER CAMERA

Model No.: IPC-G42P

 $IPC\text{-}G42,\ IPC\text{-}G42N,\ IPC\text{-}G42N\text{-}imou,\ IPC\text{-}G42P\text{-}imou,\ IPC\text{-}B1B40N\text{-}W,$

Add Model No.: IPC-B1B40P-W, IPC-B1B40-W, DH-IPC-HFW1430T0N-W, DH-IPC-

HFW1430T0P-W, DH-IPC-HFW1430T0-W, DH-IPC-HFW1430AN-W, DH-

IPC-HFW1430AP-W, DH-IPC-HFW1430A-W, TF1T-4M ¤

FCC Rules 47 CFR §2.1091

Standard(s): KDB447498 D01 General RF Exposure Guidance v06

Date of Receipt: 2019-02-02

Date of Test: 2019-02-15 to 2019-02-22

Date of Issue: 2019-02-26

Test Result: Pass*

arlan 2han

Parlam Zhan E&E Section Manager

检验检测专用章 nspection & Testing Services

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-en-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443,

or email: CN.Doccheck@sgs.com NO.588 West Jindu Road,Songjiang District,Shanghai,China 201612 ((86-21)61915666 f(86-21)61915678 www.sgsgroup.com.cn 中国・上海・松江区金都西路588号 邮编: 201612 ((86-21)61915666 f(86-21)61915678 e sgs.china@sgs.com

^{*} In the configuration tested, the EUT complied with the standards specified above.



Report No.: SHEM190201084302 Page: 2 of 7

Revision Record				
Version	Description	Date	Remark	
00	Original	2019-02-26	/	

Authorized for issue by:		
	Vincent Zhu	
	Vincent Zhu /Project Engineer	
	Parlam Zhan	
	Parlam Zhan /Reviewer	



Report No.: SHEM190201084302

Page: 3 of 7

2 Contents

		P	age
1	C	COVER PAGE	1
2	C	CONTENTS	3
3	G	GENERAL INFORMATION	4
	3.1	GENERAL DESCRIPTION OF E.U.T.	4
	3.2	TEST LOCATION	5
	3.3	TEST FACILITY	5
4	T	TEST STANDARDS AND LIMITS	6
	4.1	FCC RADIOFREQUENCY RADIATION EXPOSURE LIMITS:	6
5	M	MEASUREMENT AND CALCULATION	6
	5.1	MAXIMUM TRANSMIT POWER	6
	5.2	MPE CALCULATION	7



Report No.: SHEM190201084302

Page: 4 of 7

3 General Information

3.1 General Description of E.U.T.

	DC 12V by adapter		
	Adapter:		
Power supply:	Model:ADS-12AM-12 12012EPCU		
	Input:100-240V~50/60Hz Max 0.3A		
	Output:12V 1A		
Test voltage:	AC 120V 60Hz		
Cable:	DC Cable 3m for adapter		
Antenna Gain	2 dBi		
Antenna Type	Whip Antenna		
Channel Spacing	5MHz		
Mad Jaffaa Tara	802.11b: DSSS (CCK, DQPSK, DBPSK)		
Modulation Type	802.11g/n: OFDM (64QAM, 16QAM, QPSK, BPSK)		
	802.11b/g/n(HT20):11		
Number of Channels	802.11n(HT40):7		
0 5	802.11b/g/n(HT20): 2412MHz to 2462MHz		
Operation Frequency	802.11n(HT40): 2422MHz to 2452MHz		



Report No.: SHEM190201084302

Page: 5 of 7

3.2 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd. Shanghai Branch

588 West Jindu Road, Xinqiao, Songjiang, 201612 Shanghai, China.

Tel: +86 21 6191 5666 Fax: +86 21 6191 5678

3.3 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

CNAS (No. CNAS L0599)

CNAS has accredited SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

• NVLAP (Certificate No. 201034-0)

SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. is accredited by the National Voluntary Laboratory Accreditation Program(NVLAP). Certificate No. 201034-0.

FCC –Designation Number: CN5033

SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. has been recognized as an accredited testing laboratory.

Designation Number: CN5033. Test Firm Registration Number: 479755.

Industry Canada (IC) – IC Assigned Code: 8617A

The 3m Semi-anechoic chamber of SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 8617A-1.

• VCCI (Member No.: 3061)

The 3m Semi-anechoic chamber and Shielded Room of SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. has been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: R-13868, C-14336, T-12221, G-10830 respectively.



Report No.: SHEM190201084302

Page: 6 of 7

4 Test Standards and Limits

4.1 FCC Radiofrequency radiation exposure limits:

According to §1.1310, the limit for general population/uncontrolled exposures

Frequency	Power density(mW/cm²)	Averaging time(minutes)
300MHz~1.5GHz	f/1500	30
1.5GHz~100GHz	1.0	30

5 Measurement and Calculation

5.1 Maximum transmit power

The Power Data is based on the RF Test Report SHEM190201084301

Test Mode	Test Channel	Ant	Level [dBm]	Power [dBm]	Power [mW]
11B	2412	Ant1	15.53	15.53	35.73
11B	2437	Ant1	15.22	15.22	33.27
11B	2462	Ant1	13.78	13.78	23.88
11G	2412	Ant1	15	15.00	31.62
11G	2437	Ant1	14.47	14.47	27.99
11G	2462	Ant1	13.49	13.49	22.34
11N20SISO	2412	Ant1	14.45	14.45	27.86
11N20SISO	2437	Ant1	14.18	14.18	26.18
11N20SISO	2462	Ant1	13.16	13.16	20.70
11N40SISO	2422	Ant1	13.41	13.41	21.93
11N40SISO	2437	Ant1	13.09	13.09	20.37
11N40SISO	2452	Ant1	12.66	12.66	18.45



Report No.: SHEM190201084302

Page: 7 of 7

5.2 MPE Calculation

The Max Conducted Peak Output Power is 35.73mW;

The best case gain of the antenna is 2dBi. 2dB logarithmic terms convert to numeric result is nearly 1.58

For FCC:

According to the formula $S = \frac{PG}{4R^2\pi}$, we can calculate S which is MPE.

Note:

- 1) P (Watts)
- 2) G (Antenna gain in numeric)
- 3) R = distance to the center of radiation of antenna (in meter) = 20cm
- 4) MPE limit = 1mW/cm²

$$S = \frac{PG}{4R^2\pi} = \frac{35.73 \times 1.58}{4 \times 400 \times 3.14} = 0.01 \text{mW/cm}^2 < 1 \text{mW/cm}^2$$

So the device is exclusion from SAR test.

-- End of the Report--