

SGS-CSTC Standards Technical Services Co., Ltd. Shanghai Branch

> Report No.: SHEM190901736202 Page: 1 of 7

1 Cover Page

RF Exposure Evaluation Report

Application No.: FCC ID: Applicant: Address of Applicant: Manufacturer: Address of Manufacturer:	SHEM1909017362CR SVNDH-IPC-C22E-S2 ZHEJIANG DAHUA VISION TECHNOLOGY CO., LTD. No.1199, Bin'an Road, Binjiang District, Hangzhou, P.R. China ZHEJIANG DAHUA VISION TECHNOLOGY CO., LTD.			
Factory:	No.1199, Bin'an Road, Binjiang District, Hangzhou, P.R. China 1, ZHEJIANG DAHUA VISION TECHNOLOGY CO., LTD.			
Address of Factory:	2, ZHEJIANG DAHUA ZHILIAN CO.,LTD. 1, No.1199, Bin'an Road, Binjiang District, Hangzhou, P.R. China 2, No.28, Dongqiao Road, Dongzhou Street, Fuyang District, Hangzhou, P.R. China.			
Equipment Under Test (EU	T):			
EUT Name:	CONSUMER CAMERA			
Model No.:	IPC-C22EP-S2			
Add Model No.:	IPC-C22EN-S2,C22E			
Standard(s) :	FCC Rules 47 CFR §2.1091			
	KDB447498 D01 General RF Exposure Guidance v06			
Date of Receipt:	2019-09-23			
Date of Test:	2019-09-24 to 2019-09-30			
Date of Issue:	2019-11-29			
Test Result:	Pass*			

* In the configuration tested, the EUT complied with the standards specified above.

parlan shar

Parlam Zhan E&E Section Manager cturer should ensure that a

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.



Member of the SGS Group (SGS SA)



Report No.: SHEM190901736202 Page: 2 of 7

Revision Record					
Version	Description	Date	Remark		
00 Original		2019-11-29	/		

Authorized for issue by:		
	Vincent Zhu	
	Vincent Zhu /Project Engineer	
	Parlam zhan	
	Parlam Zhan /Reviewer	



Report No.: SHEM190901736202 Page: 3 of 7

2 Contents

1	COV	ER PAGE	1
2	CON	TENTS	3
3	GEN	ERAL INFORMATION	4
	3.1	GENERAL DESCRIPTION OF E.U.T.	4
	3.2	TEST LOCATION	5
	3.3	TEST FACILITY	5
4	TES	T STANDARDS AND LIMITS	6
	4.1	FCC RADIOFREQUENCY RADIATION EXPOSURE LIMITS:	6
5	MEA	SUREMENT AND CALCULATION	6
	5.1	MAXIMUM TRANSMIT POWER	6
	5.2	MPE CALCULATION	7



Report No.: SHEM190901736202 Page: 4 of 7

3 General Information

3.1 General Description of E.U.T.

Power supply:	DC 5V by adapter
	Adapter:
	Model:NBS05B050100VUU
	Input:100-240V~50/60Hz 0.2A
	Output:5V 1A
Test voltage:	AC 120V 60Hz
Cable:	DC Cable 2m with USB port
Antenna Gain	2.84dBi
Antenna Type	Integral Antenna
Channel Spacing	5MHz
Modulation Type	802.11b: DSSS (CCK, DQPSK, DBPSK)
	802.11g/n: OFDM (64QAM, 16QAM, QPSK, BPSK)
Number of Channels	802.11b/g/n(HT20):11
	802.11n(HT40):7
Operation Frequency	802.11b/g/n(HT20): 2412MHz to 2462MHz
	802.11n(HT40): 2422MHz to 2452MHz

NO.588 West Jindu Road,Songjiang District,Shanghai,China 201612 中国・上海・松江区金都西路588号 邮编: 201612



Report No.: SHEM190901736202 Page: 5 of 7

3.2 Test Location

All tests were performed at: SGS-CSTC Standards Technical Services Co., Ltd. Shanghai Branch 588 West Jindu Road, Xinqiao, Songjiang, 201612 Shanghai, China. Tel: +86 21 6191 5666 Fax: +86 21 6191 5678

3.3 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

CNAS (No. CNAS L0599)

CNAS has accredited SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

• NVLAP (Certificate No. 201034-0)

SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. is accredited by the National Voluntary Laboratory Accreditation Program(NVLAP). Certificate No. 201034-0.

• FCC – Designation Number: CN5033

SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. has been recognized as an accredited testing laboratory.

Designation Number: CN5033. Test Firm Registration Number: 479755.

• Innovation, Science and Economic Development Canada

SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. EMC Laboratory has been recognized by ISED as an accredited testing laboratory.

IC Registration No.: 8617A-1. CAB Identifier: CN0020.

• VCCI (Member No.: 3061)

The 3m Semi-anechoic chamber and Shielded Room of SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. has been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: R-13868, C-14336, T-12221, G-10830 respectively.



Report No.: SHEM190901736202 Page: 6 of 7

4 Test Standards and Limits

4.1 FCC Radiofrequency radiation exposure limits:

According to§1.1310, the limit for general population/uncontrolled exposures

Frequency	Power density(mW/cm ²)	Averaging time(minutes)	
300MHz~1.5GHz	f/1500	30	
1.5GHz~100GHz	1.0	30	

5 Measurement and Calculation

5.1 Maximum transmit power

The Power Data is based on the RF Test Report SHEM190901736201

Test Mode	Test Channel	Ant	Power [dBm]	Power [mW]
11B	2412	Ant1	14.22	26.42
11B	2442	Ant1	14.69	29.44
11B	2472	Ant1	14.29	26.85
11G	2412	Ant1	13.27	21.23
11G	2442	Ant1	13.96	24.89
11G	2472	Ant1	13.64	23.12
11N20SISO	2412	Ant1	13.31	21.43
11N20SISO	2442	Ant1	14.22	26.42
11N20SISO	2472	Ant1	13.77	23.82
11N40SISO	2422	Ant1	12.88	19.41
11N40SISO	2437	Ant1	13.13	20.56
11N40SISO	2452	Ant1	13.09	20.37



Report No.: SHEM190901736202 Page: 7 of 7

5.2 MPE Calculation

For FCC:

According to the formula S=P/4 π R², we can calculate S which is MPE.

Note:

- 1) P (mW)
- 2) R = distance to the center of radiation of antenna (in meter) = 20cm
- 3) MPE limit = 1mW/cm²

The max. antenna gain is 2.84

Max. Conducted Power P(mW)	Gain in Linear Scale G	Operation Distance R(cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)	Result
29.44	1.923	20	0.01126	1	Pass

So the device is exclusion from SAR test.

--End of the Report--

dBi