



**FCC RF EXPOSURE REPORT**

*For*

**CONSUMER CAMERA**

**MODEL NUMBER:**

**DH-IPC-G26P, IPC-G26P, DH-IPC-G26N, IPC-G26N, TF2, DH-IPC-G26, IPC-G26**

**PROJECT NUMBER: 4788109955**

**REPORT NUMBER: 4788109955-6**

**FCC ID: SVNDH-IPC-GX6**

**ISSUE DATE: Dec. 10, 2017**

*Prepared for*

**Zhejiang Dahua Vision Technology Co., Ltd.**

*Prepared by*

*Prepared by*

**UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch  
Room 101, Building 10, Innovation Technology Park,  
Song Shan Lake Hi tech Development Zone, Dongguan, 523808, China**

**Tel: +86 769 33817100**

**Fax: +86 769 33244054**

**Website: [www.ul.com](http://www.ul.com)**

Revision History

<u>Rev.</u>	<u>Issue Date</u>	<u>Revisions</u>	<u>Revised By</u>
--	12/10/2017	Initial Issue	

## TABLE OF CONTENTS

1. ATTESTATION OF TEST RESULTS .....	4
2. TEST METHODOLOGY .....	6
3. FACILITIES AND ACCREDITATION .....	6
4. REQUIREMENT .....	7

# 1. ATTESTATION OF TEST RESULTS


<b>Applicant Information</b>	
Company Name:	Zhejiang Dahua Vision Technology Co., Ltd.
Address:	No.1199, Bin'an road, Binjiang District, Hangzhou, P.R.China.
<b>Manufacturer Information</b>	
Company Name:	Zhejiang Dahua Vision Technology Co., Ltd.
Address:	No.1199, Bin'an road, Binjiang District, Hangzhou, P.R.China.
<b>Factory Information</b>	
Company Name:	ZHEJIANG DAHUA VISION TECHNOLOGY CO.,LTD
Address:	No.1199, Bin'an road, Binjiang District, Hangzhou, P.R.China.
Company Name:	ZHEJIANG DAHUA ZHILIAN CO.,LTD.
Address:	No.28, Dongqiao Road, Dongzhou Street, Fuyang District, Hangzhou,P.R.China.
<b>EUT Description</b>	
Product Name	CONSUMER CAMERA
Model Name	DH-IPC-G26P
Additional No.	IPC-G26P, DH-IPC-G26N, IPC-G26N, TF2, DH-IPC-G26, IPC-G26
Sample Number	1155429-001
Data of Receipt Sample	Aug 11, 2017
Date Tested	Aug 15, 2017 ~ Dec. 8, 2017

<b>APPLICABLE STANDARDS</b>	
<b>STANDARD</b>	<b>TEST RESULTS</b>
FCC Guidelines for Human Exposure IEEE C95.1	Complies

Test By : 

---

Denny Huang  
Engineer Project Associate

Check By: 

---

Shawn Wen  
Laboratory Leader

Approved By: 

---

Stephen Guo  
Laboratory Manager

## 2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with KDB 447498 D01 General RF Exposure Guidance v05.

## 3. FACILITIES AND ACCREDITATION

Test Location	UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch.
Address	Building 10, Innovation Technology Park, Song Shan Lake Hi tech Development Zone, Dongguan, 523808, China
Accreditation Certificate	UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. EMC Laboratory has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025: 2005 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing. The Certificate Registration Number is 4102.01. UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The Designation Number is CN1187. UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. EMC Laboratory has been registered and fully described in a report filed with Industry Canada. The Company Number is 21320.

Note: The test anechoic chamber in UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch had been calibrated and compared to the open field sites.

**4. REQUIREMENT****LIMIT**

Limits for General Population/Uncontrolled Exposure

Limits for General Population/Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm <sup>2</sup> )	Averaging Time  E  <sup>2</sup> ,  H  <sup>2</sup> or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f <sup>2</sup> )*	30
30-300	27.5	0.073	0.2	30
300-1500	--	--	f/150	30
1500-100,000	--	--	1.0	30

Note 1: f = frequency in MHz, \* means Plane-wave equivalent power density

Note 2: General population/uncontrolled exposures apply in situations in which the general public may be exposed, or in which persons that are exposed as a consequence of their employment may not be fully aware of the potential for exposure or cannot exercise control over their exposure.

Note 3: The limit value 1.0mW/cm<sup>2</sup> is available for this EUT.

**MPE CALCULATION METHOD**

$$S = PG / (4\pi R^2)$$

where: S = power density (in appropriate units, e.g. mW/ cm<sup>2</sup>)

P = power input to the antenna (in appropriate units, e.g., mW) (the measured power value see Report: F12124 Section 6.6)

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

**CALCULATED RESULTS**

## Radio Frequency Radiation Exposure Evaluation

## 1) For SISO

WIFI (Worst case)-Antenna 1							
Frequency	Output Power to Antenna		Antenna Gain		Power Density	Limit	Test Result
	(MHz)	(dBm)	(mW)	(dBi)			
2412	16.5	44.67	1	1.26	0.01	1	Complies

WIFI (Worst case)- Antenna 2							
Frequency	Output Power to Antenna		Antenna Gain		Power Density	Limit	Test Result
	(MHz)	(dBm)	(mW)	(dBi)			
2412	12.5	17.78	1	1.26	0.004	1	Complies

## 2) For MIMO

WIFI (Worst case)- 802.11n20 MIMO							
Frequency	Output Power to Antenna		Antenna Gain		Power Density	Limit	Test Result
	(MHz)	(dBm)	(mW)	(dBi)			
2412	17.5	56.23	1	1.26	0.014	1	Complies

Note: the calculated distance is 20cm.

**END OF REPORT**