

588 West Jindu Road, Xinqiao, Songjiang, 201612 Shanghai, China

Telephone: +86 (0) 21 6191 5666 Fax: +86 (0) 21 6191 5678

ee.shanghai@sgs.com

Report No.: SHEM170400188602

1 Cover Page

RF MPE REPORT

Application No.: SHEM1704001886CR					
Applicant:	Zhejiang Dahua Vision Technology Co., Ltd.				
FCC ID:	SVNDH-IPC-KX6				
Equipment Under Test	t (EUT):				
NOTE: The following sa	imple(s) was/were submitted and identified by the client as				
Product Name:	CONSUMER CAMERA				
Model No.(EUT):	DH-IPC-K26P				
Add Model No.:	DH-IPC-K26N, DH-IPC-K46P, DH-IPC-K46N, DH-IPC-K86P, DH-IPC-K86N,				
	IPC-K26P, IPC-K26N, IPC-K46P, IPC-K46N, IPC-K86P, IPC-K86N, TC4S				
Standards:	FCC Rules 47 CFR §2.1091				
	KDB447498 D01 General RF Exposure Guidance v06				
Date of Receipt:	2017-04-18				
Date of Test:	2017-04-18 to 2017-04-22				
Date of Issue:	2017-05-23				
Test Result: Pass*					

* In the configuration tested, the EUT detailed in this report complied with the standards specified above.



The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_edocument.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's spot responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction. documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to thesample(s) tested and such sample(s) are retained for 90 days only



Report No.: SHEM170400188602

Page: 2 of 8

2 Version

Revision Record							
Version Chapter		Date	Modifier	Remark			
00	/	2017-05-23	1	Original			

Authorized for issue by:		
Engineer	Eddy Zong	Eddy Zong
	Print Name	
Clerk	Susie Liu	Suire Lin
	Print Name	
Reviewer	Parlam Zhan	Darlam Zhan
	Print Name	



Report No.: SHEM170400188602

Page: 3 of 8

3 Contents

		Pa	age
1	C	OVER PAGE	1
2	V	ERSION	2
3	C	CONTENTS	3
4	G	ENERAL INFORMATION	4
	4.1	CLIENT INFORMATION	4
	4.1	GENERAL DESCRIPTION OF E.U.T.	4
	4.2	TECHNICAL SPECIFICATIONS	4
	4.3	TEST LOCATION	5
	4.4	TEST FACILITY	5
5	T	EST STANDARDS AND LIMITS	6
	5.1	FCC RADIOFREQUENCY RADIATION EXPOSURE LIMITS:	6
6	M	IEASUREMENT AND CALCULATION	7
	6.1	MAXIMUM TRANSMIT POWER	7
	6.2	MPE CALCULATION	8
7	E	UT CONSTRUCTIONAL DETAILS	8



Report No.: SHEM170400188602

Page: 4 of 8

4 General Information

4.1 Client Information

Applicant:	Zhejiang Dahua Vision Technology Co., Ltd.	
Address of Applicant:	No.1199, Bin'an Road, Binjiang District, Hangzhou, P.R. China	
Manufacturer:	Zhejiang Dahua Vision Technology Co., Ltd.	
Address of Manufacturer:	No.1199, Bin'an Road, Binjiang District, Hangzhou, P.R. China	
Factory:	Zhejiang Dahua Vision Technology Co., Ltd.	
Address of Factory:	No.1199, Bin'an Road, Binjiang District, Hangzhou, P.R. China	

4.1 General Description of E.U.T.

•					
Product Des	Product Description:		Fixed product with 2.4G WiFi function		
Rated Input:	Rated Input:		DC 12V 1A		
Test Voltage	Test Voltage:		AC 120V 60Hz for Adapter		
	Manufacturer:	SHENZHEN HONOR ELECTRONIC CO.,LTD.			
	Model No.:	ADS-12AM-12 12012EPCU			
Adaptor	Rated Input:	AC 100~240V, 50/60Hz 0.3A			
Adapter:	Rated Output:	DC 12V 1.0A			
	Cable length:	AC port:	2 wires		
		DC port:	300 cm		

4.2 Technical Specifications

Operation Frequency:	802.11 b/g/n(HT20): 2412MHz-2462MHz
o processors to question.	802.11 n(HT40): 2422MHz-2452MHz
Modulation Technique:	02.11 b DSSS(CCK, DQPSK, DBPSK)
Modulation rechilique.	802.11 g/n(HT20)/n(HT40) OFDM(64QAM, 16QAM, QPSK, BPSK)
Data Rate:	802.11 b/g/n(HT20): 11
Data Nate.	802.11 n(HT40) 7
	802.11b: 1/2/5.5/11Mbps,
Number of Channel:	802.11g: 6/9/12/18/24/36/48/54Mbps
	802.11n: MCS0-7
Antenna Type:	Chip Antenna
Antenna Gain:	2 dBi



Report No.: SHEM170400188602

Page: 5 of 8

4.3 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd.

588 West Jindu Road, Xinqiao, Songjiang, 201612 Shanghai, China

Tel: +86 21 6191 5666 Fax: +86 21 6191 5678

4.4 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

CNAS (No. CNAS L0599)

CNAS has accredited SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

FCC – Registration No.: 402683

SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. has been registered and fully described in a report filed with the Federal Communications Commission (FCC). The acceptance letter from the FCC is maintained in our files. Registration No.: 402683.

Industry Canada (IC) – IC Assigned Code: 8617A

The 3m Semi-anechoic chamber of SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 8617A-1.

• VCCI (Member No.: 3061)

The 3m Semi-anechoic chamber and Shielded Room of SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. has been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: R-3868, C-4336, T-2221, G-830 respectively.



Report No.: SHEM170400188602

Page: 6 of 8

5 Test Standards and Limits

5.1 FCC Radiofrequency radiation exposure limits:

According to §1.1310, the limit for general population/uncontrolled exposures

Frequency	Power density(mW/cm ²)	Averaging time(minutes)	
300MHz~1.5GHz	f/1500	30	
1.5GHz~100GHz	1.0	30	



Report No.: SHEM170400188602

Page: 7 of 8

6 Measurement and Calculation

6.1 Maximum transmit power

The Power Data is based on the RF Test Report SHEM170400188602.

Test Mode	Test Channel	Power[dBm]	Power[mW]	Limit[dBm]	Verdict
11B	2412	19.04	80.17	30	PASS
11B	2437	20.28	106.66	30	PASS
11B	2462	19.8	95.50	30	PASS
11G	2412	19.51	89.33	30	PASS
11G	2437	20.88	122.46	30	PASS
11G	2462	21.52	141.91	30	PASS
11N20SISO	2412	21.06	127.64	30	PASS
11N20SISO	2437	22.52	178.65	30	PASS
11N20SISO	2462	22.27	168.66	30	PASS
11N40SISO	2422	22.52	178.65	30	PASS
11N40SISO	2437	22.99	199.07	30	PASS
11N40SISO	2452	23	199.53	30	PASS



Report No.: SHEM170400188602

Page: 8 of 8

6.2 MPE Calculation

The Max Conducted Peak Output Power is 23dBm (199.53 mW);

The best case gain of the antenna is 2dBi. 2dB logarithmic terms convert to numeric result is nearly 1.58.

For FCC:

According to the formula S= $\frac{PG}{4R^2\pi}$, we can calculate S which is MPE.

Note

dBm

- 1) P (Watts) = Power Input to antenna = 10^{10} / 1000
- 2) G (Antenna gain in numeric) = 10[^] (Antenna gain in dBi /10)
- 3) R = distance to the center of radiation of antenna (in meter) = 20cm
- 4) MPE limit = 1mW/cm²

$$S = \frac{PG}{4R^2\pi} = \frac{199.53 \times 1.58}{4 \times 400 \times 3.14} = 0.063 \text{ mW/cm}^2$$

So the device is exclusion from SAR test.

7 EUT Constructional Details

Refer to the < DH-IPC-K26P _External Photos > & < DH-IPC-K26P _Internal Photos >.

-- End of the Report--