

588 West Jindu Road, Xinqiao, Songjiang, 201612 Shanghai, China

+86 (0) 21 6191 5666 Telephone: +86 (0) 21 6191 5678 Fax:

ee.shanghai@sgs.com

Report No.: SHEM160300099103

1 **Cover Page**

FCC MPE REPORT

Application No.:	SHEM1603000991CR				
Applicant:	plicant: Zhejiang Dahua Vision Technology Co., Ltd.				
FCC ID:	SVNDH-PFM880				
Equipment Under Tes	t (EUT):				
NOTE: The following sa	ample(s) submitted was/were identified on behalf of the client as				
Product Name:	5G Wireless Video Transmission Device AP				
Model No.(EUT):	Model No.(EUT): DH-PFM880				
Add Model No.: PFM880, DHI-PFM880					
Standards: FCC Rules 47 CFR §2.1091					
KDB447498 D01 General RF Exposure Guidance v06					
Date of Receipt: 2016-03-16					
Date of Test: 2016-04-12 to 2016-04-18					
Date of Issue:	2016-05-03				
Test Result: Pass*					

In the configuration tested, the EUT detailed in this report complied with the standards specified above.



SGS-CSTC (Shanghai) Co., Ltd.

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government. All test results in this report can be traceable to National or International Standards.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms and conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this www.sgs.com/terms e-ocument.ntm. Attention is drawn to the limitation or liability, indemnification and jurisdiction issues defined therein. Any noiser of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only



Report No.: SHEM160300099103

Page: 2 of 8

2 Version

Revision Record							
Version	Chapter	Date	Modifier	Remark			
00	/	2016-05-03	/	Original			

Authorized for issue by:		
Engineer	Eddy Zong	Eddy Zong
	Print Name	
Clerk	Susie Liu	Sustre Lin
	Print Name	
Reviewer	Parlam Zhan	Darlam Zhan
	Print Name	



Report No.: SHEM160300099103

Page: 3 of 8

3 Contents

		F	age
1	\mathbf{C}	COVER PAGE	1
2	V	/ERSION	2
3	C	CONTENTS	3
4	G	GENERAL INFORMATION	4
	4.1	CLIENT INFORMATION	4
	4.2	GENERAL DESCRIPTION OF E.U.T.	4
	4.3	TECHNICAL SPECIFICATIONS	4
	4.4	TEST LOCATION	5
	4.5	TEST FACILITY	5
5	T	EST STANDARDS AND LIMITS	6
6	M	IEASUREMENT AND CALCULATION	7
	6.1	MAXIMUM TRANSMIT POWER	7
	6.2	MPE CALCULATION	8
7	E	CUT CONSTRUCTIONAL DETAILS	8

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms and conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms-e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction

documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to thesample(s) tested and such sample(s) are retained for 90 days only



Report No.: SHEM160300099103

Page: 4 of 8

4 General Information

4.1 Client Information

Applicant:	Zhejiang Dahua Vision Technology Co., Ltd.		
Address of Applicant:	The 1st Floor, Building F, No.1199 Binan Road, Changhe Stree Binjiang District, Hangzhou, Zhejiang, P.R.China		
Manufacturer:	Zhejiang Dahua Vision Technology Co., Ltd.		
Address of Manufacturer:	The 1st Floor, Building F, No.1199 Binan Road, Changhe Street Binjiang District, Hangzhou, Zhejiang, P.R.China		
Factory:	Zhejiang Dahua Vision Technology Co., Ltd.		
Address of Factory:	No.1199 Binan Road, Changhe Street, Binjiang District, Hangzhou, Zhejiang, P.R.China		

4.2 General Description of E.U.T.

Product Description:		Portable p	Portable product with WiFi function			
Rated Input:		DC 48V 0	DC 48V 0.5A PoE			
Model No.:		GRT-4800	GRT-480050A-FW			
	Rated Input:	AC 100V-	AC 100V-240V 50/60Hz			
Adapter:	Rated Output:	DC 48V 500mA				
	Cable length:	AC port:	2 wires			
	Cable leffgtif.	DC port:	90 cm			

4.3 Technical Specifications

Operation Frequency:	5745-5825MHz		
Modulation Technique:	OFDM(64QAM, 16QAM, QPSK, BPSK)		
Data Rate:	802.11a: 6/9/12/18/24/36/48/54Mbps 802.11n: MCS0-15 up to 300Mbps		
Antenna Type	Integral antenna (2Tx2R MIMO)		
Antenna Gain	16dBi		
Number of Channel:	802.11 a/n(HT20): 5 Channel 149, 153, 157, 161, 165 802.11 n(HT40): 2 Channel 151, 159		

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms and conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction

documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to thesample(s) tested and such sample(s) are retained for 90 days only



Report No.: SHEM160300099103

Page: 5 of 8

4.4 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd.

588 West Jindu Road, Xinqiao, Songjiang, 201612 Shanghai, China

Tel: +86 21 6191 5666 Fax: +86 21 6191 5678

4.5 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

CNAS (No. CNAS L0599)

CNAS has accredited SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

FCC – Registration No.: 402683

SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. has been registered and fully described in a report filed with the Federal Communications Commission (FCC). The acceptance letter from the FCC is maintained in our files. Registration No.: 402683.

Industry Canada (IC) – IC Assigned Code: 8617A

The 3m Semi-anechoic chamber of SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 8617A-1.

VCCI (Member No.: 3061)

The 3m Semi-anechoic chamber and Shielded Room of SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. has been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: R-3868, C-4336, T-2221, G-830 respectively.



Report No.: SHEM160300099103

Page: 6 of 8

5 Test Standards and Limits

According to §1.1310 Radiofrequency radiation exposure limits:

The limit for general population/uncontrolled exposures

Frequency	Power density(mW/cm²)	Averaging time(minutes)		
300MHz~1.5GHz	f/1500	30		
1.5GHz~100GHz	1.0	30		



Report No.: SHEM160300099103

Page: 7 of 8

6 Measurement and Calculation

6.1 Maximum transmit power

The Powe Data is based on the RF Test Report SHEM160300099102.

Test Mode	CH No.	Freq (MHz)	Reading (dBm)		Conducted Power (dBm)		
1 est iviode			Ant A	Ant B	Ant A	Ant B	MIMO
	149	5745	8.20	8.30	8.70	8.80	/
802.11a	157	5785	8.44	7.40	8.94	7.90	/
	165	5825	9.95	7.64	10.45	8.14	/
000.11	149	5745	8.10	8.23	8.60	8.73	11.68
802.11n	157	5785	8.38	7.46	8.88	7.96	11.45
(HT20)	165	5825	9.76	7.49	10.26	7.99	12.28
802.11n	151	5755	8.08	7.91	8.58	8.41	11.51
(HT40)	159	5795	9.15	7.36	9.65	7.86	11.86



Report No.: SHEM160300099103

Page: 8 of 8

6.2 MPE Calculation

According to the formula S= $\frac{PG}{4R^2\pi}$, we can calculate S which is MPE.

Note:

dBm

- 1) P (Watts) =Power Input to antenna = 10 10 / 1000
- 2) G (Antenna gain in numeric) = 10[^] (Antenna gain in dBi /10)
- 3) R = distance to the center of radiation of antenna (in meter) = 20cm
- 4) MPE limit = 1mW/cm²

The Max Conducted Peak Output Power is 12.28(16.90)mW in highest channel;

The best case gain of the antenna is 16dBi. 16dB logarithmic terms convert to numeric result is nearly 39.81

$$S = \frac{PG}{4R^2\pi} = \frac{16.90 \times 39.81}{4 \times 400 \times 3.14} = 0.133 \text{ mW/cm}^2$$

So the device is exclusion from SAR test.

7 EUT Constructional Details

Refer to the < DH-PFM880_External Photos > & < DH-PFM880_Internal Photos>.

-- End of the Report--