



MPE Report

Applicant : Zhejiang Dahua Vision Technology Co., Ltd.

Address : The 1st floor, building F, No.1199 Bin'an road, Changhe Street, Binjiang District, Hangzhou, P.R. China.

Manufacturer : Zhejiang Dahua Vision Technology Co., Ltd.

Address : The 1st floor, building F, No.1199 Bin'an road, Changhe Street, Binjiang District, Hangzhou, P.R. China.

Equipment : Network Video Recorder

Model No. : NVR4104HS-W-SX, NVR4108HS-W-SX, DHI-NVR4104HS-W-SX, DHI-NVR4108HS-W-SX, DHI-NVR41A04HS-W-SX,
DHI-NVR41A08HS-W-SX
(X can be 2/3/4/5)

FCC ID : SVNDHNVR41WSX

- The test result refers exclusively to the test presented test model / sample.,
- Without written approval of **Cerpass Technology (Suzhou) Co., Ltd.** the test report shall not be reproduced except in full.
- The EUT is also considered as a kind of computer peripheral, because the connection to computer is necessary for typical use. It has been verified to comply with the requirements of FCC Rules and Regulations Part 15. The test report has been issued separately.
- The test report must not be used by the clients to claim product certification approval by **NVLAP** or any agency of the Government.

Approved by:

Miro Chueh
EMC/RF Manager

Laboratory Accreditation:

Cerpass Technology Corporation Test Laboratory

<input type="checkbox"/>	NVLAP LAB Code:	200954-0
	TAF LAB Code:	1439

Cerpass Technology (SuZhou) Co., Ltd.

<input checked="" type="checkbox"/>	NVLAP LAB Code:	200814-0
	CNAS LAB Code:	L5515



Radio Frequency Exposure

LIMIT

For 2.4G Band: According to §15.247(i), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines. See § 1.1307(b)(1) of this chapter.

**EUT Specification**

EUT	Network Video Recorder
Frequency band (Operating)	<input checked="" type="checkbox"/> WLAN: 2.412GHz ~ 2.462GHz
Device category	<input type="checkbox"/> Portable (<20cm separation) <input checked="" type="checkbox"/> Mobile (>20cm separation)
Exposure classification	<input type="checkbox"/> Occupational/Controlled exposure (S = 5mW/cm ²) <input checked="" type="checkbox"/> General Population/Uncontrolled exposure (S=1mW/cm ²)
Antenna diversity	<input type="checkbox"/> Single antenna <input checked="" type="checkbox"/> Multiple antennas <input type="checkbox"/> Tx diversity <input type="checkbox"/> Rx diversity <input checked="" type="checkbox"/> Tx/Rx diversity
Max. output power for 2.4G Band	IEEE802.11b: 28.77 dBm (0.7534W) IEEE802.11g: 29.41 dBm (0.8730W) IEEE802.11n HT20: 29.50 dBm (0.8913W) IEEE802.11n HT40: 29.39 dBm (0.8690W)
Antenna gain (Max)	5 dBi for 2.4G Band
Evaluation applied	<input checked="" type="checkbox"/> MPE Evaluation* <input type="checkbox"/> SAR Evaluation <input type="checkbox"/> N/A

Remark:

1. The maximum output power is 29.50dBm (0.8913W) at 2437MHz (with numeric 5 antenna gain.) for 2.4G band
2. DTS device is not subject to routine RF evaluation; MPE estimate is used to justify the compliance.
3. For mobile or fixed location transmitters, no SAR consideration applied. The maximum power density is 1.0 mW/cm² even if the calculation indicates that the power density would be larger.

*Note: Simultaneous transmission is not applicable for this EUT.

**The test mode of the test software can support.**

Test Mode	Test Channel	Ant 1	Ant 2	Ant 3	MIMO Mode(Ant1+2+3)
802.11b	2412	√	√	√	×
	2437	√	√	√	×
	2462	√	√	√	×
802.11g	2412	√	√	√	×
	2437	√	√	√	×
	2462	√	√	√	×
802.11n(20MHz)	2412	√	√	√	√
	2437	√	√	√	√
	2462	√	√	√	√
802.11n(40MHz)	2422	√	√	√	√
	2437	√	√	√	√
	2452	√	√	√	√

**TEST RESULTS FOR 2.4G BAND**

No non-compliance noted.

Calculation

Given $E = \frac{\sqrt{30 \times P \times G}}{d}$ & $S = \frac{E^2}{3770}$

Where E = Field strength in Volts / meter

P = Power in Watts

G = Numeric antenna gain

d = Distance in meters

S = Power density in milliwatts / square centimeter

Combining equations and re-arranging the terms to express the distance as a function of the remaining variables yields:

$$S = \frac{30 \times P \times G}{3770 d^2}$$

Changing to units of mW and cm, using:

$$P \text{ (mW)} = P \text{ (W)} / 1000 \text{ and}$$

$$d \text{ (cm)} = d \text{ (m)} / 100$$

Yields

$$S = \frac{30 \times (P/1000) \times G}{3770 \times (d/100)^2} = 0.0796 \times \frac{P \times G}{d^2} \quad \text{Equation 1}$$

Where d = Distance in cm

P = Power in mW

G = Numeric antenna gain

S = Power density in mW / cm²

Maximum Permissible Exposure

Modulation Mode	Frequency band (MHz)	Max. Conducted output power(dBm)	Antenna gain (dBi)	Distance (cm)	Power density (mW/cm2)	Limit (mW/cm2)
IEEE802.11b	2412-2462	28.77	5	20	0.47	1
IEEE802.11g	2412-2462	29.41	5	20	0.55	1
IEEE802.11n HT20	2412-2462	29.50	5	20	0.56	1
IEEE802.11n HT40	2422-2452	29.39	5	20	0.55	1