



FCC TEST REPORT

According to

FCC Rules and Regulations Part 15 Subpart C

Applicant : Good Way Technology Co., Ltd.
Address : 3F, No. 135, Lane 235, Pau Chiao Rd.,
Hsin-Tien City, 231 Taipei Hsien, Taiwan
Equipment : 4-Port Wireless Serial Device Server
Model No. : FW2440
FCC ID. : SW8FW2440
Trade Name : GOOD WAY

- The test result refers exclusively to the test presented test model / sample.,
- Without written approval of **CerpPASS Technology Corp.**, the test report shall not be reproduced except in full.
- The EUT is also considered as a kind of computer peripheral, because the connection to computer is necessary for typical use. It has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (DoC). The test report has been issued separately.



Contents

1. Report of Measurements and Examinations	6
1.1 List of Measurements and Examinations	6
2. Test Configuration of Equipment under Test	7
2.1 Feature of Equipment under Test	7
2.2 RF Specifications	7
2.3 Carrier Frequency of Channels	8
2.4 Test Mode and Test Software	8
2.5 Description of Test System	9
2.6 General Information of Test	10
2.7 Measurement Uncertainty	10
3. Antenna Requirements	11
3.1 Standard Applicable	11
3.2 Antenna Construction and Directional Gain	11
4. Test of Conducted Emission	12
4.1 Test Limit	12
4.2 Test Procedures	12
4.3 Typical Test Setup	13
4.4 Measurement Equipment	13
4.5 Test Result and Data	14
4.6 Test Photographs	20
5. Test of Radiated Emission	21
5.1 Test Limit	21
5.2 Test Procedures	21
5.3 Typical Test Setup	22
5.4 Measurement Equipment	22
5.5 Test Result and Data	23
5.6 Test Photographs (30MHz~1GHz)	59
5.7 Test Photographs (1GHz~25GHz)	60
6. 6dB Bandwidth Measurement Data	61
6.1 Test Limit	61
6.2 Test Procedures	61
6.3 Test Setup Layout	61
6.4 Measurement Equipment	61
6.5 Test Result and Data	61
7. Maximum Peak and Average Output Power	68
7.1 Test Limit	68
7.2 Test Procedures	68
7.3 Test Setup Layout	68
7.4 Measurement Equipment	68
7.5 Test Result and Data	69
8. Power Spectral Density	82
8.1 Test Limit	82
8.2 Test Procedures	82



8.3 Test Setup Layout 82

8.4 Measurement Equipment..... 82

8.5 Test Result and Data..... 82

9. Band Edges Measurement 89

9.1 Test Limit 89

9.2 Test Procedure 89

9.3 Test Setup Layout 89

9.4 Measurement Equipment..... 89

9.5 Test Result and Data..... 89

9.6 Restrict Band Emission Measurement Data 98

10. Restricted Bands of Operation 100

10.1 Labeling Requirement..... 100

Appendix A. Photographs of EUT..... A1 ~ A7



CERTIFICATE OF COMPLIANCE

According to

FCC Rules and Regulations Part 15 Subpart C

Applicant : Good Way Technology Co., Ltd.
Address : 3F, No. 135, Lane 235, Pau Chiao Rd.,
Hsin-Tien City, 231 Taipei Hsien, Taiwan
Equipment : 4-Port Wireless Serial Device Server
Model No. : FW2440
FCC ID. : SW8FW2440

I HEREBY CERTIFY THAT :

The measurements shown in this test report were made in accordance with the procedures given in **ANSI C63.4** The equipment was **passed** the test performed according to **FCC Rules and Regulations Part 15 Subpart C (2010)**.

The test was carried out on Mar. 12, 2012 at CerpPASS Technology Corp.

Signature

Hill Chen
EMC/RF B.U. Assistant Manager



1. Report of Measurements and Examinations

1.1 List of Measurements and Examinations

FCC Rule	Description of Test	Result
15.203	. Antenna Requirement	Pass
15.207	. Conducted Emission	Pass
15.209 15.247(d)	. Radiated Emission	Pass
15.247(a)(2)	. 6dB Bandwidth	Pass
15.247(b)	. Maximum Peak Output Power	Pass
15.247(d)	. 100kHz Bandwidth of Frequency Band Edges	Pass
15.247(e)	. Power Spectral Density	Pass
1.1307 1.1310 2.1091 2.1093	. RF Exposure Compliance	Pass



2. Test Configuration of Equipment under Test

2.1 Feature of Equipment under Test

Item	Description
Ports	4xRS-232/422/485
Connector	8-pin RJ-45
FIFO	512 bytes
ESD protect	15 KV ESD, 3KV isolation (RS-485)
Transmission Speed	110bps~921.6kbps
Interface	GigaLAN / Wi-Fi
Interface connector	RJ-45 / Antenna
Power requirements	5V3A DC / 9~36 VDC
Operating temperature	0~55°C
Operating humidity	5~95% RH

2.2 RF Specifications

Spreading	802.11b: DSSS, CCK, QPSK, BPSK 802.11g: OFDM (64QAM, 16QAM, QPSK, BPSK) 802.11n, HT20: OFDM (64QAM, 16QAM, QPSK, BPSK) 802.11n, HT40: OFDM (64QAM, 16QAM, QPSK, BPSK)
Frequency Range	2.4 ~ 2.4835 GHz
Number of Channels	USA, Canada and Taiwan: 1 ~ 11 Most European Countries: 1 ~ 13
Data Rate	802.11b: 11, 5.5, 2, 1 Mbps 802.11g: 54, 48, 36, 24, 18, 12, 9, 6 Mbps 802.11n HT20: 130/15, 117/14, 104/13, 78/12, 52/11, 39/10, 26/9, 13/8, 65/7, 58.5/6, 52/5, 39/4, 26/3, 19.5/2, 13/1, 6.5/0Mbps 802.11 n HT40: 270/15, 243/14, 216/13, 162/12, 108/11, 81/10, 54/9, 27/8, 135/7, 121.5/6, 108/5, 81/4, 54/3, 40.5/2, 27/1, 13.5/0Mbps
Modulation	802.11b: DSSS, CCK, QPSK, BPSK 802.11g: OFDM (64QAM, 16QAM, QPSK, BPSK) 802.11n, HT20: OFDM (64QAM, 16QAM, QPSK, BPSK) 802.11n, HT40: OFDM (64QAM, 16QAM, QPSK, BPSK)
Antenna Type	Dipole Antenna
Antenna Gain	2dBi
Transmit Power	FCC: 802.11b: 17.27 dBm / 802.11g: 15.93 dBm / 802.11n: 15.95 dBm ETSI: (EIRP): 802.11b: 17.44 dBm / 802.11g: 15.34 dBm / 802.11n: 15.58 dBm



2.3 Carrier Frequency of Channels

802.11b, 802.11g, 802.11n HT 20

Channel	Frequency(MHz)	Channel	Frequency(MHz)
01	2412	07	2442
02	2417	08	2447
03	2422	09	2452
04	2427	10	2457
05	2432	11	2462
06	2437	---	---

802.11n HT40

Channel	Frequency(MHz)	Channel	Frequency(MHz)
---	---	07	2442
---	---	08	2447
03	2422	09	2452
04	2427	---	---
05	2432	---	---
06	2437	---	---

2.4 Test Mode and Test Software

- a. During testing, the interface cables and equipment positions were varied according to ANSI C63.4.
- b. The complete test system included the Remote Workstation and EUT for RF test. The Remote workstation includes Notebook.
- c. An executive program, "QA Test" under WIN XP was executed to transmit and receive data to through Wireless.
- d. The following test modes were performed for test:
 - 802.11b/g/n HT20: CH01: 2412MHz, CH06: 2437MHz, CH11: 2462MHz
 - 802.11n HT40: CH03: 2422MHz, CH06: 2437MHz, CH09: 2452MHz
- e. The following data rates were the worst cases of power output and be performed for test:
 - 802.11b: 11Mbps
 - 802.11g: 54Mbps
 - 802.11n HT20: 130Mbps
 - 802.11n HT40: 270Mbps

* Power output of data rate:

802.11b		802.11g	
Data Rate (Mbps)	Power output (dBm)	Data Rate (Mbps)	Power output (dBm)
11	17.14	54	15.65
5.5	17.09	48	15.52
2	17.06	36	15.55
1	17.11	24	15.52
		18	15.56
		12	15.60
		9	15.58
		6	15.55



802.11n HT20		802.11n HT40	
Data Rate (Mbps)	Power output (dBm)	Data Rate (Mbps)	Power output (dBm)
130/15	15.38	270/15	15.29
117/14	15.31	243/14	15.20
104/13	15.28	216/13	15.19
78/12	15.24	162/12	15.15
52/11	15.26	108/11	15.16
39/10	15.25	81/10	15.13
26/9	15.23	54/9	15.18
13/8	15.21	27/8	15.15
65/7	15.25	135/7	15.12
58.5/6	15.20	121.5/6	15.11
52/5	15.29	108/5	15.16
39/4	15.22	81/4	15.11
26/3	15.21	54/3	15.16
19.5/2	15.25	40.5/2	15.12
13/1	15.31	27/1	15.22
6.5/0	15.32	13.5/0	15.22

2.5 Description of Test System

Device	Manufacturer	Model No.	Description
Remote Workstation			
Notebook	SONY	VPCEB25FW	Power Cable, Unshielding 1.8 m

Use Cable:

Cable	Quantity	Description
RJ45	1	Unshielding, 15m
RJ45	4	Unshielding, 0.5m



2.6 General Information of Test

Test Site :	CerpPASS Technology Corp. 2F-11, No. 3, Yuan Qu St., (Nankang Software Park), Taipei, Taiwan 115, R.O.C.
Test Site Location (OATS2-SD) :	No.68-1, Shihbachongsi, Shihding Township, Taipei City 223, Taiwan, R.O.C.
FCC Registration Number :	TW1049, TW1061, 488071, 390316
IC Registration Number :	4934B-1, 4934D-1
VCCI Registration Number :	T-1173 for Telecommunication Test C-4139 for Conducted emission test R-3428 for Radiated emission test G-97 for Radiated emission test above 1GHz
Test in Compliance with:	ANSI C63.4-2009 FCC Part 15 Subpart C
Frequency Range Investigated:	Conducted: from 150kHz to 30MHz Radiation: from 30MHz to 25,000MHz
Test Distance:	The test distance of radiated emission from antenna to EUT is 3 M.



2.7 Measurement Uncertainty

Measurement Item	Uncertainty
Radiated emission	±4.11dB
Peak Output Power(conducted)	±1.38dB
Peak Output Power(Radiated)	±1.70dB
Power Spectral Density	±1.39dB
Radiated emission(3m)	±4.11dB
Radiated emission(10m)	±3.89dB



3. Antenna Requirements

3.1 Standard Applicable

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

3.2 Antenna Construction and Directional Gain

Antenna Type: Dipole antenna

Antenna Gain: 2 dBi

Connector: I-PEX (Reverse Polarity meets FCC part 15. 203 Requirement)



4. Test of Conducted Emission

4.1 Test Limit

Conducted Emissions were measured from 150 kHz to 30 MHz with a bandwidth of 9 KHz on the 120 VAC power and return leads of the EUT according to the methods defined in ANSI C63.4-2009 Section 3.1. The EUT was placed on a nonmetallic stand in a shielded room 0.8 meters above the ground plane as shown in section 2.2. The interface cables and equipment positioning were varied within limits of reasonable applications to determine the position produced maximum conducted emissions.

Frequency (MHz)	Quasi Peak (dB μ V)	Average (dB μ V)
0.15 – 0.5	66-56*	56-46*
0.5 – 5.0	56	46
5.0 – 30.0	60	50


*Decreases with the logarithm of the frequency.

4.2 Test Procedures

- a. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
- b. Connect EUT to the power mains through a line impedance stabilization network (LISN).
- c. All the support units are connecting to the other LISN.
- d. The LISN provides 50 ohm coupling impedance for the measuring instrument.
- e. The FCC states that a 50 ohm, 50 micro-Henry LISN should be used.
- f. Both sides of AC line were checked for maximum conducted interference.
- g. The frequency range from 150 kHz to 30 MHz was searched.
- h. Set the test-receiver system to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.



4.3 Typical Test Setup




4.4 Measurement Equipment

Instrument/Ancillary	Model No.	Manufacturer	Serial No.	Calibration Date	Valid Date
EMI Receiver	R&S	ESCI	100443	2012/01/12	2013/01/11
LISN	Schwarzbeck	NSLK 8127	8127-516	2011/05/05	2012/05/04
LISN	Schwarzbeck	NSLK 8127	8127-568	2011/08/24	2012/08/23



4.5 Test Result and Data


Power	: AC 120V	Pol/Phase	: LINE
Test Mode 1	: 802.11g, CH1	Temperature	: 26 °C
Test Date	: Mar. 05, 2012	Humidity	: 60 %



No.	Frequency (MHz)	Factor (dBuV)	Reading (dBuV)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F
1	0.1620	0.12	46.72	46.84	65.36	-18.52	QP	P
2	0.1620	0.12	36.49	36.61	55.36	-18.75	AVG	P
3	0.1900	0.12	46.29	46.41	64.03	-17.62	QP	P
4	0.1900	0.12	36.86	36.98	54.03	-17.05	AVG	P
5	0.6740	0.15	35.66	35.81	56.00	-20.19	QP	P
6	0.6740	0.15	33.11	33.26	46.00	-12.74	AVG	P
7	7.4820	0.48	30.10	30.58	60.00	-29.42	QP	P
8	7.4820	0.48	16.39	16.87	50.00	-33.13	AVG	P
9	9.9140	0.58	17.86	18.44	60.00	-41.56	QP	P
10	9.9140	0.58	9.71	10.29	50.00	-39.71	AVG	P
11	13.7140	0.74	29.10	29.84	60.00	-30.16	QP	P
12	13.7140	0.74	14.72	15.46	50.00	-34.54	AVG	P




Power	: AC 120V	Pol/Phase	: NEUTRAL
Test Mode 1	: 802.11g, CH1	Temperature	: 26 °C
Test Date	: Mar. 05, 2012	Humidity	: 60 %



No.	Frequency (MHz)	Factor (dBuV)	Reading (dBuV)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F
1	0.4420	0.13	32.53	32.66	57.02	-24.36	QP	P
2	0.4420	0.13	22.03	22.16	47.02	-24.86	AVG	P
3	0.6740	0.15	36.71	36.86	56.00	-19.14	QP	P
4	0.6740	0.15	33.01	33.16	46.00	-12.84	AVG	P
5	5.0020	0.39	28.18	28.57	60.00	-31.43	QP	P
6	5.0020	0.39	23.15	23.54	50.00	-26.46	AVG	P
7	10.0020	0.58	39.67	40.25	60.00	-19.75	QP	P
8	10.0020	0.58	27.43	28.01	50.00	-21.99	AVG	P
9	13.7540	0.74	23.04	23.78	60.00	-36.22	QP	P
10	13.7540	0.74	19.54	20.28	50.00	-29.72	AVG	P
11	27.9580	1.28	9.28	10.56	60.00	-49.44	QP	P
12	27.9580	1.28	4.35	5.63	50.00	-44.37	AVG	P




Power	: AC 120V	Pol/Phase	: LINE
Test Mode 2	: 802.11n HT20, CH1	Temperature	: 26 °C
Test Date	: Mar. 05, 2012	Humidity	: 60 %



No.	Frequency (MHz)	Factor (dBuV)	Reading (dBuV)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F
1	0.1780	0.12	40.00	40.12	64.57	-24.45	QP	P
2	0.1780	0.12	23.53	23.65	54.57	-30.92	AVG	P
3	0.2660	0.12	42.57	42.69	61.24	-18.55	QP	P
4	0.2660	0.12	36.72	36.84	51.24	-14.40	AVG	P
5	0.3020	0.12	28.82	28.94	60.19	-31.25	QP	P
6	0.3020	0.12	15.53	15.65	50.19	-34.54	AVG	P
7	0.6980	0.16	26.20	26.36	56.00	-29.64	QP	P
8	0.6980	0.16	21.25	21.41	46.00	-24.59	AVG	P
9	9.1220	0.55	15.33	15.88	60.00	-44.12	QP	P
10	9.1220	0.55	11.14	11.69	50.00	-38.31	AVG	P
11	16.7860	0.86	21.61	22.47	60.00	-37.53	QP	P
12	16.7860	0.86	15.98	16.84	50.00	-33.16	AVG	P




Power	: AC 120V	Pol/Phase	: NEUTRAL
Test Mode 2	: 802.11n HT20, CH1	Temperature	: 26 °C
Test Date	: Mar. 05, 2012	Humidity	: 60 %



No.	Frequency (MHz)	Factor (dBuV)	Reading (dBuV)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F
1	0.1700	0.12	48.52	48.64	64.96	-16.32	QP	P
2	0.1700	0.12	32.05	32.17	54.96	-22.79	AVG	P
3	0.2140	0.12	40.12	40.24	63.04	-22.80	QP	P
4	0.2140	0.12	28.53	28.65	53.04	-24.39	AVG	P
5	0.2700	0.12	35.52	35.64	61.12	-25.48	QP	P
6	0.2700	0.12	23.11	23.23	51.12	-27.89	AVG	P
7	0.3860	0.13	26.54	26.67	58.15	-31.48	QP	P
8	0.3860	0.13	19.53	19.66	48.15	-28.49	AVG	P
9	12.8940	0.70	19.78	20.48	60.00	-39.52	QP	P
10	12.8940	0.70	14.96	15.66	50.00	-34.34	AVG	P
11	13.9580	0.74	19.76	20.50	60.00	-39.50	QP	P
12	13.9580	0.74	14.73	15.47	50.00	-34.53	AVG	P




Power	: AC 120V	Pol/Phase	: LINE
Test Mode 3	: 802.11n HT40, CH3	Temperature	: 26 °C
Test Date	: Mar. 05, 2012	Humidity	: 60 %



No.	Frequency (MHz)	Factor (dBuV)	Reading (dBuV)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F
1	0.1860	0.12	45.57	45.69	64.21	-18.52	QP	P
2	0.1860	0.12	33.53	33.65	54.21	-20.56	AVG	P
3	0.2420	0.12	36.03	36.15	62.02	-25.87	QP	P
4	0.2420	0.12	22.72	22.84	52.02	-29.18	AVG	P
5	0.3260	0.12	32.24	32.36	59.55	-27.19	QP	P
6	0.3260	0.12	19.44	19.56	49.55	-29.99	AVG	P
7	0.6780	0.15	26.51	26.66	56.00	-29.34	QP	P
8	0.6780	0.15	25.73	25.88	46.00	-20.12	AVG	P
9	16.9740	0.87	22.32	23.19	60.00	-36.81	QP	P
10	16.9740	0.87	17.78	18.65	50.00	-31.35	AVG	P
11	27.9580	1.28	19.08	20.36	60.00	-39.64	QP	P
12	27.9580	1.28	14.14	15.42	50.00	-34.58	AVG	P



Power	: AC 120V	Pol/Phase	: NEUTRAL
Test Mode 3	: 802.11n HT40, CH3	Temperature	: 26 °C
Test Date	: Mar. 05, 2012	Humidity	: 60 %



No.	Frequency (MHz)	Factor (dBuV)	Reading (dBuV)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F
1	0.1620	0.12	48.42	48.54	65.36	-16.82	QP	P
2	0.1620	0.12	35.08	35.20	55.36	-20.16	AVG	P
3	0.2140	0.12	40.45	40.57	63.04	-22.47	QP	P
4	0.2140	0.12	25.53	25.65	53.04	-27.39	AVG	P
5	0.2819	0.12	36.13	36.25	60.76	-24.51	QP	P
6	0.2819	0.12	28.44	28.56	50.76	-22.20	AVG	P
7	0.3300	0.12	29.53	29.65	59.45	-29.80	QP	P
8	0.3300	0.12	18.35	18.47	49.45	-30.98	AVG	P
9	7.2100	0.47	24.10	24.57	60.00	-35.43	QP	P
10	7.2100	0.47	22.21	22.68	50.00	-27.32	AVG	P
11	16.9740	0.87	20.87	21.74	60.00	-38.26	QP	P
12	16.9740	0.87	16.02	16.89	50.00	-33.11	AVG	P

Test engineer: Ben




4.6 Test Photographs

Front View



Rear View





5. Test of Radiated Emission

5.1 Test Limit

Radiated emissions from 30 MHz to 25 GHz were measured according to the methods defines in ANSI C63.4-2009. The EUT was placed, 0.8 meter above the ground plane, as shown in section 5.6.3. The interface cables and equipment positions were varied within limits of reasonable applications to determine the positions producing maximum radiated emissions for unintentional device, according to § 15.109(a), except for Class A digital devices, the field strength of radiated emissions from unintentional radiators at a distance of 3 meters shall not exceed the following values:

Frequency (MHz)	Distance Meters	Radiated (μ V / M)	Radiated (dB μ V / M)
30-88	3	100	40.0
88-216	3	150	43.5
216-960	3	200	46.0
Above 960	3	500	54.0

For unintentional device, according to CISPR PUB.22, for Class B digital devices, the general requirement of field strength of radiated emissions from intentional radiators at a distance of 10 meters shall not exceed the below table.

Frequency (MHz)	Distance Meters	Radiated (dB μ V / M)
30-230	10	30
230-1000	10	37


5.2 Test Procedures

- b. The EUT was placed on a rotatable table top 0.8 meter above ground.
- c. The EUT was set 3 meters from the interference receiving antenna which was mounted on the top of a variable height antenna tower.
- d. The table was rotated 360 degrees to determine the position of the highest radiation.
- e. The antenna is a broadband antenna and its height is varied between one meter and four meters above ground to find the maximum value of the field strength both horizontal polarization and vertical polarization of the antenna are set to make the measurement.
- f. For each suspected emission the EUT was arranged to its worst case and then tune the antenna tower (from 1 M to 4 M) and turn table (from 0 degree to 360 degrees) to find the maximum reading.
- g. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function and specified bandwidth with Maximum Hold Mode.
- h. If the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method and reported.
- i. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than average limit (that means the emission level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
- j. "Cone of radiation" has been considered to be 3dB bandwidth of the measurement antenna.




5.3 Typical Test Setup

Below 1GHz Test Setup



Above 1GHz Test Setup




5.4 Measurement Equipment

Instrument/Ancillary	Manufacturer	Model No.	Serial No.	Calibration Date	Valid Date
Amplifier	Agilent	8447D	2944A10531	2012/01/13	2013/01/12
Bilog Antenna	Schaffner	CBL6112D	22242	2012/01/12	2013/01/11
EMI Receiver	R&S	ESCI	101200	2011/07/26	2012/07/25
Spectrum Analyzer	R&S	FSP40	100047	2011/05/05	2012/05/04
Horn Antenna	EMCO	3115	31589	2011/05/02	2012/05/01
Preamplifier	Agilent	8449B	3008A01954	2012/02/29	2013/02/28



5.5 Test Result and Data

Power	: AC 120V	Pol/Phase	: VERTICAL
Test Mode 1	: 802.11g, CH1	Temperature	: 23 °C
Memo	:	Humidity	: 65 %




Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	Deg
1	44.30	31.04	3.12	34.16	40.00	-5.84	QP	100	360
2	67.13	41.90	-8.16	33.74	40.00	-6.26	Peak	100	360
3	75.38	42.70	-6.00	36.70	40.00	-3.30	QP	100	360
4	120.20	32.56	7.80	40.36	43.50	-3.14	QP	100	360
5	167.50	34.14	-1.24	32.90	43.50	-10.60	Peak	100	360
6	300.05	44.44	-4.15	40.29	46.00	-5.71	QP	100	360

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. All emission below 1GHz at 802.11b/g/n mode are all the same,so the 802.11g/n mode chosen as representative in final test.
5. According to technical experiences,all spurious emission of 802.11g/n mode at channel 1,6,11 or 3,6,9(for HT40) are almost the same below 1GHz,so that the channel 1 or 3(for HT40)was chosen as representative in final test.
6. The data is worse case.



Power	: AC 120V	Pol/Phase	: VERTICAL
Test Mode 1	: 802.11g, CH1	Temperature	: 23 °C
Memo	:	Humidity	: 65 %




Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	Deg
1	321.00	41.39	-4.14	37.25	46.00	-8.75	Peak	100	0
2	480.60	33.81	-0.65	33.16	46.00	-12.84	Peak	100	0
3	590.50	35.88	6.33	42.21	46.00	-3.79	QP	100	0
4	639.50	32.58	3.46	36.04	46.00	-9.96	Peak	100	0
5	749.40	29.38	8.23	37.61	46.00	-8.39	Peak	100	0
6	839.00	24.97	15.21	40.18	46.00	-5.82	QP	100	0

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. All emission below 1GHz at 802.11b/g/n mode are all the same, so the 802.11g/n mode chosen as representative in final test.
5. According to technical experiences, all spurious emission of 802.11g/n mode at channel 1, 6, 11 or 3, 6, 9 (for HT40) are almost the same below 1GHz, so that the channel 1 or 3 (for HT40) was chosen as representative in final test.
6. The data is worse case.



Power	: AC 120V	Pol/Phase	: HORIZONTAL
Test Mode 1	: 802.11g, CH1	Temperature	: 23 °C
Memo	:	Humidity	: 65 %




Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	Deg
1	67.13	46.79	-15.64	31.15	40.00	-8.85	Peak	100	360
2	75.38	50.50	-14.67	35.83	40.00	-4.17	QP	100	360
3	100.13	38.98	-8.02	30.96	43.50	-12.54	Peak	100	360
4	120.20	44.94	-10.27	34.67	43.50	-8.83	Peak	100	360
5	133.95	43.72	-9.64	34.08	43.50	-9.42	Peak	100	360
6	300.05	43.84	-6.07	37.77	46.00	-8.23	Peak	100	360

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. All emission below 1GHz at 802.11b/g/n mode are all the same,so the 802.11g/n mode chosen as representative in final test.
5. According to technical experiences,all spurious emission of 802.11g/n mode at channel 1,6,11 or 3,6,9(for HT40) are almost the same below 1GHz,so that the channel 1 or 3(for HT40)was chosen as representative in final test.
6. The data is worse case.



Power	: AC 120V	Pol/Phase	: HORIZONTAL
Test Mode 1	: 802.11g, CH1	Temperature	: 23 °C
Memo	:	Humidity	: 65 %




Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	Deg
1	501.60	32.46	2.59	35.05	46.00	-10.95	Peak	100	0
2	590.50	32.54	8.31	40.85	46.00	-5.15	QP	100	0
3	676.60	29.77	6.47	36.24	46.00	-9.76	Peak	100	0
4	749.40	32.50	7.75	40.25	46.00	-5.75	Peak	100	0
5	833.40	25.48	13.72	39.20	46.00	-6.80	Peak	100	0
6	912.50	27.28	11.28	38.56	46.00	-7.44	Peak	100	0

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. All emission below 1GHz at 802.11b/g/n mode are all the same,so the 802.11g/n mode chosen as representative in final test.
5. According to technical experiences,all spurious emission of 802.11g/n mode at channel 1,6,11 or 3,6,9(for HT40) are almost the same below 1GHz,so that the channel 1 or 3(for HT40)was chosen as representative in final test.
6. The data is worse case.



Power	: AC 120V	Pol/Phase	: VERTICAL
Test Mode 1	: 802.11b, CH1	Temperature	: 23 °C
Memo	:	Humidity	: 65 %




Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	Deg
1	4924.00	41.78	5.37	47.15	74.00	-26.85	Peak	100	224

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too low to be measured.
7. The data is worse case.



Power	: AC 120V	Pol/Phase	: HORIZONTAL
Test Mode 1	: 802.11b, CH1	Temperature	: 23 °C
Memo	:	Humidity	: 65 %




Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	Deg
1	4824.00	40.44	3.71	44.15	74.00	-29.85	Peak	100	121

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too low to be measured.
7. The data is worse case.



Power	: AC 120V	Pol/Phase	: VERTICAL
Test Mode 1	: 802.11b, CH6	Temperature	: 23 °C
Memo	:	Humidity	: 65 %




Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	Deg
1	4874.00	39.92	6.36	46.28	74.00	-27.72	Peak	100	222

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too low to be measured.
7. The data is worse case.



Power	: AC 120V	Pol/Phase	: HORIZONTAL
Test Mode 1	: 802.11b, CH6	Temperature	: 23 °C
Memo	:	Humidity	: 65 %




Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	Deg
1	4874.00	40.85	4.50	45.35	74.00	-28.65	Peak	100	120

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too low to be measured.
7. The data is worse case.



Power	: AC 120V	Pol/Phase	: VERTICAL
Test Mode 1	: 802.11b, CH11	Temperature	: 23 °C
Memo	:	Humidity	: 65 %




Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	Deg
1	4924.00	40.12	6.94	47.06	74.00	-26.94	Peak	100	222

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too low to be measured.
7. The data is worse case.



Power	: AC 120V	Pol/Phase	: HORIZONTAL
Test Mode 1	: 802.11b, CH11	Temperature	: 23 °C
Memo	:	Humidity	: 65 %




Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	Deg
1	4924.00	40.08	4.93	45.01	74.00	-28.99	Peak	100	117

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too low to be measured.
7. The data is worse case.



Power	: AC 120V	Pol/Phase	: VERTICAL
Test Mode 1	: 802.11g, CH1	Temperature	: 23 °C
Memo	:	Humidity	: 65 %




Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	Deg
1	4824.00	40.20	5.37	45.57	74.00	-28.43	Peak	100	228

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too low to be measured.
7. The data is worse case.



Power	: AC 120V	Pol/Phase	: HORIZONTAL
Test Mode 1	: 802.11g, CH1	Temperature	: 23 °C
Memo	:	Humidity	: 65 %




Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	Deg
1	4824.00	39.70	3.71	43.41	74.00	-30.59	Peak	100	113

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too low to be measured.
7. The data is worse case.



Power	: AC 120V	Pol/Phase	: VERTICAL
Test Mode 1	: 802.11g, CH6	Temperature	: 23 °C
Memo	:	Humidity	: 65 %




Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	Deg
1	4874.00	40.75	6.36	47.11	74.00	-26.89	Peak	100	232

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too low to be measured.
7. The data is worse case.



Power	: AC 120V	Pol/Phase	: HORIZONTAL
Test Mode 1	: 802.11g, CH6	Temperature	: 23 °C
Memo	:	Humidity	: 65 %




Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	Deg
1	4874.00	39.86	4.50	44.36	74.00	-29.64	Peak	100	133

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too low to be measured.
7. The data is worse case.



Power	: AC 120V	Pol/Phase	: VERTICAL
Test Mode 1	: 802.11g, CH11	Temperature	: 23 °C
Memo	:	Humidity	: 65 %




Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	Deg
1	4924.00	39.78	6.94	46.72	74.00	-27.28	Peak	100	225

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too low to be measured.
7. The data is worse case.



Power	: AC 120V	Pol/Phase	: HORIZONTAL
Test Mode 1	: 802.11g, CH11	Temperature	: 23 °C
Memo	:	Humidity	: 65 %




Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	Deg
1	4924.00	39.98	4.93	44.91	74.00	-29.09	Peak	100	121

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too low to be measured.
7. The data is worse case.



Power	: AC 120V	Pol/Phase	: VERTICAL
Test Mode 2	: 802.11n HT20, CH1	Temperatur	: 23 °C
Memo	:	Humidity	: 65 %




Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	Deg
1	67.13	43.44	-8.16	35.28	40.00	-4.72	QP	100	360
2	75.38	42.28	-6.00	36.28	40.00	-3.72	QP	100	360
3	102.05	36.29	0.38	36.67	43.50	-6.83	Peak	100	360
4	120.20	31.83	7.80	39.63	43.50	-3.87	QP	100	360
5	133.95	35.34	0.43	35.77	43.50	-7.73	Peak	100	360
6	300.05	43.51	-4.15	39.36	46.00	-6.64	Peak	100	360

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. All emission below 1GHz at 802.11b/g/n mode are all the same, so the 802.11g/n mode chosen as representative in final test.
5. According to technical experiences, all spurious emission of 802.11g/n mode at channel 1,6,11 or 3,6,9(for HT40) are almost the same below 1GHz, so that the channel 1 or 3(for HT40) was chosen as representative in final test.
6. The data is worse case.



Power	: AC 120V	Pol/Phase	: VERTICAL
Test Mode 2	: 802.11n HT20, CH1	Temperature	: 23 °C
Memo	:	Humidity	: 65 %




Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	Deg
1	321.00	39.91	-4.14	35.77	46.00	-10.23	Peak	100	0
2	480.60	35.49	-0.65	34.84	46.00	-11.16	Peak	100	0
3	567.40	30.66	8.98	39.64	46.00	-6.36	Peak	100	0
4	590.50	35.56	6.33	41.89	46.00	-4.11	QP	100	0
5	639.50	31.89	3.46	35.35	46.00	-10.65	Peak	100	0
6	749.40	30.20	8.23	38.43	46.00	-7.57	Peak	100	0

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. All emission below 1GHz at 802.11b/g/n mode are all the same,so the 802.11g/n mode chosen as representative in final test.
5. According to technical experiences,all spurious emission of 802.11g/n mode at channel 1,6,11 or 3,6,9(for HT40) are almost the same below 1GHz,so that the channel 1 or 3(for HT40)was chosen as representative in final test.
6. The data is worse case.



Power	: AC 120V	Pol/Phase	: HORIZONTAL
Test Mode 2	: 802.11n HT20, CH1	Temperature	: 23 °C
Memo	:	Humidity	: 65 %




Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	Deg
1	67.13	47.77	-15.64	32.13	40.00	-7.87	Peak	100	360
2	75.38	47.88	-14.67	33.21	40.00	-6.79	Peak	100	360
3	100.95	39.87	-8.91	30.96	43.50	-12.54	Peak	100	360
4	120.20	44.87	-10.27	34.60	43.50	-8.90	Peak	100	360
5	133.95	41.05	-9.64	31.41	43.50	-12.09	Peak	100	360
6	300.05	43.78	-6.07	37.71	46.00	-8.29	Peak	100	360

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. All emission below 1GHz at 802.11g/n mode are all the same, so the 802.11g/n mode chosen as representative in final test.
5. According to technical experiences, all spurious emission of 802.11g/n mode at channel 1,6,11 or 3,6,9(for HT40) are almost the same below 1GHz, so that the channel 1 or 3(for HT40) was chosen as representative in final test.
6. The data is worse case.



Power	: AC 120V	Pol/Phase	: HORIZONTAL
Test Mode 2	: 802.11n HT20, CH1	Temperature	: 23 °C
Memo	:	Humidity	: 65 %




Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	Deg
1	401.50	33.12	-0.17	32.95	46.00	-13.05	Peak	100	0
2	480.60	33.28	2.56	35.84	46.00	-10.16	Peak	100	0
3	590.50	32.79	8.31	41.10	46.00	-4.90	QP	100	0
4	720.00	32.77	5.32	38.09	46.00	-7.91	Peak	100	0
5	749.40	31.93	7.75	39.68	46.00	-6.32	Peak	100	0
6	833.40	25.22	13.72	38.94	46.00	-7.06	Peak	100	0

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. All emission below 1GHz at 802.11b/g/n mode are all the same,so the 802.11g/n mode chosen as representative in final test.
5. According to technical experiences,all spurious emission of 802.11g/n mode at channel 1,6,11 or 3,6,9(for HT40) are almost the same below 1GHz,so that the channel 1 or 3(for HT40)was chosen as representative in final test.
6. The data is worse case.



Power	: AC 120V	Pol/Phase	: VERTICAL
Test Mode 2	: 802.11n HT20, CH1	Temperature	: 23 °C
Memo	:	Humidity	: 65 %




Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	Deg
1	4824.00	39.41	5.37	44.78	74.00	-29.22	Peak	100	184

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too low to be measured.
7. The data is worse case.



Power	: AC 120V	Pol/Phase	: HORIZONTAL
Test Mode 2	: 802.11n HT20, CH1	Temperature	: 23 °C
Memo	:	Humidity	: 65 %




Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	Deg
1	4824.00	40.32	3.71	44.03	74.00	-29.97	Peak	100	176

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too low to be measured.
7. The data is worse case.



Power	: AC 120V	Pol/Phase	: VERTICAL
Test Mode 2	: 802.11n HT20, CH6	Temperature	: 23 °C
Memo	:	Humidity	: 65 %




Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	Deg
1	4874.00	39.86	6.36	46.22	74.00	-27.78	Peak	100	176

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too low to be measured.
7. The data is worse case.



Power	: AC 120V	Pol/Phase	: HORIZONTAL
Test Mode 2	: 802.11n HT20, CH6	Temperature	: 23 °C
Memo	:	Humidity	: 65 %




Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	Deg
1	4874.00	41.38	4.50	45.88	74.00	-28.12	Peak	100	161

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too low to be measured.
7. The data is worse case.



Power	: AC 120V	Pol/Phase	: VERTICAL
Test Mode 2	: 802.11n HT20, CH11	Temperature	: 23 °C
Memo	:	Humidity	: 65 %




Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	Deg
1	4924.00	38.84	6.94	45.78	74.00	-28.22	Peak	100	161

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too low to be measured.
7. The data is worse case.



Power	: AC 120V	Pol/Phase	: HORIZONTAL
Test Mode 2	: 802.11n HT20, CH11	Temperature	: 23 °C
Memo	:	Humidity	: 65 %




Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	Deg
1	4924.00	40.39	4.93	45.32	74.00	-28.68	Peak	100	187

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too low to be measured.
7. The data is worse case.



Power	: AC 120V	Pol/Phase	: VERTICAL
Test Mode 3	: 802.11n HT40, CH3	Temperature	: 23 °C
Memo	:	Humidity	: 65 %




Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	Deg
1	35.50	29.81	6.25	36.06	40.00	-3.94	QP	100	360
2	75.38	42.28	-6.00	36.28	40.00	-3.72	QP	100	360
3	100.13	37.40	0.84	38.24	43.50	-5.26	QP	100	360
4	120.20	31.99	7.80	39.79	43.50	-3.71	QP	100	360
5	166.95	32.96	-1.45	31.51	43.50	-11.99	Peak	100	360
6	300.05	43.68	-4.15	39.53	46.00	-6.47	Peak	100	360

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. All emission below 1GHz at 802.11b/g/n mode are all the same, so the 802.11g/n mode chosen as representative in final test.
5. According to technical experiences, all spurious emission of 802.11g/n mode at channel 1, 6, 11 or 3, 6, 9 (for HT40) are almost the same below 1GHz, so that the channel 1 or 3 (for HT40) was chosen as representative in final test.
6. The data is worse case.



Power	: AC 120V	Pol/Phase	: VERTICAL
Test Mode 3	: 802.11n HT40, CH3	Temperature	: 23 °C
Memo	:	Humidity	: 65 %




Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	Deg
1	480.60	34.19	-0.65	33.54	46.00	-12.46	Peak	100	0
2	567.40	29.86	8.98	38.84	46.00	-7.16	Peak	100	0
3	590.50	35.63	6.33	41.96	46.00	-4.04	QP	100	0
4	639.50	31.93	3.46	35.39	46.00	-10.61	Peak	100	0
5	749.40	29.33	8.23	37.56	46.00	-8.44	Peak	100	0
6	840.40	24.23	15.58	39.81	46.00	-6.19	Peak	100	0

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. All emission below 1GHz at 802.11b/g/n mode are all the same,so the 802.11g/n mode chosen as representative in final test.
5. According to technical experiences,all spurious emission of 802.11g/n mode at channel 1,6,11 or 3,6,9(for HT40) are almost the same below 1GHz,so that the channel 1 or 3(for HT40)was chosen as representative in final test.
6. The data is worse case.



Power	: AC 120V	Pol/Phase	: HORIZONTAL
Test Mode 3	: 802.11n HT40, CH3	Temperature	: 23 °C
Memo	:	Humidity	: 65 %




Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	Deg
1	67.13	46.10	-15.64	30.46	40.00	-9.54	Peak	100	360
2	75.38	48.44	-14.67	33.77	40.00	-6.23	Peak	100	360
3	100.13	39.48	-8.02	31.46	43.50	-12.04	Peak	100	360
4	120.20	45.54	-10.27	35.27	43.50	-8.23	Peak	100	360
5	133.95	41.38	-9.64	31.74	43.50	-11.76	Peak	100	360
6	300.05	43.92	-6.07	37.85	46.00	-8.15	Peak	100	360

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. All emission below 1GHz at 802.11b/g/n mode are all the same, so the 802.11g/n mode chosen as representative in final test.
5. According to technical experiences, all spurious emission of 802.11g/n mode at channel 1,6,11 or 3,6,9(for HT40) are almost the same below 1GHz, so that the channel 1 or 3(for HT40) was chosen as representative in final test.
6. The data is worse case.



Power	: AC 120V	Pol/Phase	: HORIZONTAL
Test Mode 3	: 802.11n HT40, CH3	Temperature	: 23 °C
Memo	:	Humidity	: 65 %




Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	Deg
1	401.50	33.11	-0.17	32.94	46.00	-13.06	Peak	100	0
2	459.60	36.44	0.64	37.08	46.00	-8.92	Peak	100	0
3	501.60	32.77	2.59	35.36	46.00	-10.64	Peak	100	0
4	590.50	31.91	8.31	40.22	46.00	-5.78	QP	100	0
5	720.00	32.97	5.32	38.29	46.00	-7.71	Peak	100	0
6	832.00	25.31	13.57	38.88	46.00	-7.12	Peak	100	0

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. All emission below 1GHz at 802.11b/g/n mode are all the same, so the 802.11g/n mode chosen as representative in final test.
5. According to technical experiences, all spurious emission of 802.11g/n mode at channel 1, 6, 11 or 3, 6, 9 (for HT40) are almost the same below 1GHz, so that the channel 1 or 3 (for HT40) was chosen as representative in final test.
6. The data is worse case.



Power	: AC 120V	Pol/Phase	: VERTICAL
Test Mode 3	: 802.11n HT40, CH3	Temperature	: 23 °C
Memo	:	Humidity	: 65 %




Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	Deg
1	4844.00	39.57	5.77	45.34	74.00	-28.66	Peak	100	187

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too low to be measured.
7. The data is worse case.



Power	: AC 120V	Pol/Phase	: HORIZONTAL
Test Mode 3	: 802.11n HT40, CH3	Temperature	: 23 °C
Memo	:	Humidity	: 65 %




Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	Deg
1	4844.00	40.63	4.03	44.66	74.00	-29.34	Peak	100	187

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300KHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too low to be measured.
7. The data is worse case.



Power	: AC 120V	Pol/Phase	: VERTICAL
Test Mode 3	: 802.11n HT40, CH6	Temperature	: 23 °C
Memo	:	Humidity	: 65 %




Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	Deg
1	4874.00	40.47	6.36	46.83	74.00	-27.17	Peak	100	187

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300KHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too low to be measured.
7. The data is worse case.



Power	: AC 120V	Pol/Phase	: HORIZONTAL
Test Mode 3	: 802.11n HT40, CH6	Temperature	: 23 °C
Memo	:	Humidity	: 65 %




Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	Deg
1	4874.00	40.01	4.50	44.51	74.00	-29.49	Peak	100	187

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too low to be measured.
7. The data is worse case.



Power	: AC 120V	Pol/Phase	: VERTICAL
Test Mode 3	: 802.11n HT40, CH9	Temperature	: 23 °C
Memo	:	Humidity	: 65 %




Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	Deg
1	4904.00	39.73	6.89	46.62	74.00	-27.38	Peak	100	187

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too low to be measured.
7. The data is worse case.



Power	: AC 120V	Pol/Phase	: HORIZONTAL
Test Mode 3	: 802.11n HT40, CH9	Temperature	: 23 °C
Memo	:	Humidity	: 65 %



Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	Deg
1	4904.00	39.73	4.92	44.65	74.00	-29.35	Peak	100	187

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too low to be measured.
7. The data is worse case.

Test engineer: Ben



5.6 Test Photographs (30MHz~1GHz)

Front View



Rear View






5.7 Test Photographs (1GHz~25GHz)

Front View



Rear View





6. 6dB Bandwidth Measurement Data


6.1 Test Limit

The minimum of 6dB Bandwidth Measurement is 0.5 MHz.

6.2 Test Procedures

- The transmitter output was connected to the spectrum analyzer.
- Set RBW of spectrum analyzer to 1~5% of the emission bandwidth and VBW \geq 3x RBW.
- The 6 dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 6 dB.
- The 6dB Bandwidth was measured and recorded.

6.3 Test Setup Layout



6.4 Measurement Equipment

Instrument/Ancillary	Manufacturer	Model No.	Serial No.	Calibration Date	Valid Date
Spectrum Analyzer	R&S	FSP40	100219	2011/11/24	2012/11/23

6.5 Test Result and Data

Test Date: Mar. 12, 2012

Temperature: 24°C


Atmospheric pressure: 1020 hPa

Humidity: 65%


Modulation Standard	Channel	Frequency (MHz)	6dB Bandwidth (MHz)
802.11b (11Mbps)	01	2412	11.6
	06	2437	11.7
	11	2462	11.5
802.11g (54Mbps)	01	2412	16.7
	06	2437	16.8
	11	2462	16.7
802.11n HT20 (130Mbps)	01	2412	17.6
	06	2437	17.6
	11	2462	17.7
802.11n HT40 (270Mbps)	03	2422	36.4
	06	2437	36.2
	09	2452	36.0



Modulation Standard: 802.11b (11Mbps)
Channel: 01




Modulation Standard: 802.11b (11Mbps)
Channel: 06






Modulation Standard: 802.11b (11Mbps)
Channel: 11




Modulation Standard: 802.11g (54Mbps)
Channel: 01






Modulation Standard: 802.11g (54Mbps)
Channel: 06




Modulation Standard: 802.11g (54Mbps)
Channel: 11






Modulation Standard: 802.11n HT20 (130Mbps)
Channel: 01




Modulation Standard: 802.11n HT20 (130Mbps)
Channel: 06






Modulation Standard: 802.11n HT20 (130Mbps)
Channel: 11




Modulation Standard: 802.11n HT40 (270Mbps)
Channel: 03






Modulation Standard: 802.11n HT40 (270Mbps)
Channel: 06



Modulation Standard: 802.11n HT40 (270Mbps)
Channel: 09





7. Maximum Peak and Average Output Power


7.1 Test Limit

The Maximum Output Power Measurement is 30dBm.

7.2 Test Procedures

- a. The transmitter output was connected to the spectrum analyzer.
- b. Set RBW of spectrum analyzer to 1MHz and VBW to 3MHz.
- c. Set detector mode to peak (for peak output power) or set detector mode to RMS (for average output power).
- d. Use the spectrum analyzer's integrated band power measurement function with band limits set equal to the EBW band edges.
- e. The maximum peak and average output power was measured and recorded.

7.3 Test Setup Layout



7.4 Measurement Equipment

Instrument/Ancillary	Manufacturer	Model No.	Serial No.	Calibration Date	Valid Date
Spectrum Analyzer	R&S	FSP40	100219	2011/11/24	2012/11/23



7.5 Test Result and Data

Test Date: Mar. 12, 2012

Temperature: 24°C

Atmospheric pressure: 1020 hPa


Humidity: 65%

Modulation Standard	Channel	Frequency (MHz)	Peak Power Output (dBm)		Peak Power Output (mW)	
			Peak	Average	Peak	Average
802.11b (11Mbps)	01	2412	17.14	13.92	51.8	24.7
	06	2437	17.18	13.77	52.2	23.8
	11	2462	17.27	13.73	53.3	23.6
802.11g (54Mbps)	01	2412	15.65	9.88	36.7	9.7
	06	2437	15.48	9.86	35.3	9.7
	11	2462	15.93	10.28	39.2	10.7
802.11n HT20 (130Mbps)	01	2412	15.38	9.72	34.5	9.4
	06	2437	15.79	10.09	37.9	10.2
	11	2462	15.79	10.13	37.9	10.3
802.11n HT40 (270Mbps)	03	2422	15.29	9.62	33.8	9.2
	06	2437	15.85	10.06	38.5	10.1
	09	2452	15.95	10.61	39.4	11.5




Peak:

Modulation Standard: 802.11b (11Mbps)
Channel: 01



Tx Channel			
Bandwidth	22 MHz	Power	17.14 dBm
Adjacent Channel			
Bandwidth	11 MHz	Lower	-48.40 dB
Spacing	16.5 MHz	Upper	-46.54 dB
Alternate Channel			
Bandwidth	11 MHz	Lower	-----
Spacing	27.5 MHz	Upper	-----


Modulation Standard: 802.11b (11Mbps)
Channel: 06




Tx Channel			
Bandwidth	22 MHz	Power	17.18 dBm
Adjacent Channel			
Bandwidth	11 MHz	Lower	-49.28 dB
Spacing	16.5 MHz	Upper	-47.34 dB
Alternate Channel			
Bandwidth	11 MHz	Lower	-----
Spacing	27.5 MHz	Upper	-----



Modulation Standard: 802.11b (11Mbps)
Channel: 11




Modulation Standard: 802.11g (54Mbps)
Channel: 01






Modulation Standard: 802.11g (54Mbps)
Channel: 06




Modulation Standard: 802.11g (54Mbps)
Channel: 11






Modulation Standard: 802.11n HT20 (130Mbps)
Channel: 01




Modulation Standard: 802.11n HT20 (130Mbps)
Channel: 06






Modulation Standard: 802.11n HT20 (130Mbps)
Channel: 11




Modulation Standard: 802.11n HT40 (270Mbps)
Channel: 03






Modulation Standard: 802.11n HT40 (270Mbps)
Channel: 06



Tx Channel			
Bandwidth	44 MHz	Power	15.85 dBm
Adjacent Channel			
Bandwidth	22 MHz	Lower	-4.67 dB
Spacing	16.5 MHz	Upper	-4.71 dB
Alternate Channel			
Bandwidth	22 MHz	Lower	-15.31 dB
Spacing	27.5 MHz	Upper	-15.02 dB

Modulation Standard: 802.11n HT40 (270Mbps)
Channel: 09




Tx Channel			
Bandwidth	44 MHz	Power	15.95 dBm
Adjacent Channel			
Bandwidth	22 MHz	Lower	-4.59 dB
Spacing	16.5 MHz	Upper	-4.80 dB
Alternate Channel			
Bandwidth	22 MHz	Lower	-15.05 dB
Spacing	27.5 MHz	Upper	-15.28 dB




Average:

Modulation Standard: 802.11b (11Mbps)
Channel: 01




Modulation Standard: 802.11b (11Mbps)
Channel: 06






Modulation Standard: 802.11b (11Mbps)
Channel: 11



Tx Channel			
Bandwidth	22 MHz	Power	13.73 dBm
Adjacent Channel			
Bandwidth	11 MHz	Lower	-50.98 dB
Spacing	16.5 MHz	Upper	-49.29 dB
Alternate Channel			
Bandwidth	11 MHz	Lower	-----
Spacing	27.5 MHz	Upper	-----


Modulation Standard: 802.11g (54Mbps)
Channel: 01




Tx Channel			
Bandwidth	22 MHz	Power	9.88 dBm
Adjacent Channel			
Bandwidth	11 MHz	Lower	-43.96 dB
Spacing	16.5 MHz	Upper	-42.17 dB
Alternate Channel			
Bandwidth	11 MHz	Lower	-----
Spacing	27.5 MHz	Upper	-----



Modulation Standard: 802.11g (54Mbps)
Channel: 06




Modulation Standard: 802.11g (54Mbps)
Channel: 11






Modulation Standard: 802.11n HT20 (130Mbps)
Channel: 01




Modulation Standard: 802.11n HT20 (130Mbps)
Channel: 06






Modulation Standard: 802.11n HT20 (130Mbps)
Channel: 11



Tx Channel		Bandwidth	22 MHz	Power	10.13 dBm
Adjacent Channel		Bandwidth	11 MHz	Lower	-43.40 dB
	Spacing	16.5 MHz	Upper	-41.47 dB	
Alternate Channel		Bandwidth	11 MHz	Lower	----
	Spacing	27.5 MHz	Upper	----	


Modulation Standard: 802.11n HT40 (270Mbps)
Channel: 03




Tx Channel		Bandwidth	44 MHz	Power	9.62 dBm
Adjacent Channel		Bandwidth	22 MHz	Lower	-4.79 dB
	Spacing	16.5 MHz	Upper	-4.56 dB	
Alternate Channel		Bandwidth	22 MHz	Lower	-15.26 dB
	Spacing	27.5 MHz	Upper	-13.76 dB	



Modulation Standard: 802.11n HT40 (270Mbps)
Channel: 06



Modulation Standard: 802.11n HT40 (270Mbps)
Channel: 09





8. Power Spectral Density


8.1 Test Limit

The Maximum of Power Spectral Density Measurement is 8dBm.

8.2 Test Procedures

- The transmitter output was connected to spectrum analyzer.
- The spectrum analyzer's resolution bandwidth were set at 100KHz RBW and 300KHz VBW as that of the fundamental frequency. Set the sweep time=auto couple.
- Scale the observed power level to an equivalent value in 3 kHz by adjusting the measured power by a bandwidth correction factor (BWCF) where $BWCF = 10\log(3\text{ kHz}/100) = -15.2\text{ dB}$.
- The Sweep time is allowed to be longer than span/3KHz for a full response of the mixer in the spectrum analyzer.

8.3 Test Setup Layout



8.4 Measurement Equipment

Instrument/Ancillary	Manufacturer	Model No.	Serial No.	Calibration Date	Valid Date
Spectrum Analyzer	R&S	FSP40	100219	2011/11/24	2012/11/23

8.5 Test Result and Data

Test Date: Mar. 12, 2012

Temperature: 24°C


Atmospheric pressure: 1020 hPa

Humidity: 65%


Modulation Standard	Channel	Frequency (MHz)	Maximum Power Density of 3 kHz Bandwidth (dBm)
802.11b (11Mbps)	01	2412	-14.20
	06	2437	-14.52
	11	2462	-14.67
802.11g (54Mbps)	01	2412	-20.52
	06	2437	-20.65
	11	2462	-20.23
802.11n HT20 (130Mbps)	01	2412	-20.97
	06	2437	-20.44
	11	2462	-20.50
802.11n HT40 (270Mbps)	03	2422	-24.47
	06	2437	-24.21
	09	2452	-23.96



Modulation Standard: 802.11b (11Mbps)
Channel: 01




Modulation Standard: 802.11b (11Mbps)
Channel: 06






Modulation Standard: 802.11b (11Mbps)
Channel: 11




Modulation Standard: 802.11g (54Mbps)
Channel: 01






Modulation Standard: 802.11g (54Mbps)
Channel: 06




Modulation Standard: 802.11g (54Mbps)
Channel: 11






Modulation Standard: 802.11n HT20 (130Mbps)
Channel: 01




Modulation Standard: 802.11n HT20 (130Mbps)
Channel: 06






Modulation Standard: 802.11n HT20 (130Mbps)
Channel: 11




Modulation Standard: 802.11n HT40 (270Mbps)
Channel: 03






Modulation Standard: 802.11n HT40 (270Mbps)
Channel: 06



Modulation Standard: 802.11n HT40 (270Mbps)
Channel: 09





9. Band Edges Measurement


9.1 Test Limit

Below -20dB of the highest emission level of operating band (In 100 kHz Resolution Bandwidth)

9.2 Test Procedure

- a. The transmitter output was connected to the spectrum analyzer via a low lose cable.
- b. Set RBW of spectrum analyzer to 100 KHz and VBW of spectrum analyzer to 300 KHz with convenient frequency span including 100 KHz bandwidth from band edge.
- c. The band edges was measured and recorded.

9.3 Test Setup Layout



9.4 Measurement Equipment

Instrument/Ancillary	Manufacturer	Model No.	Serial No.	Calibration Date	Valid Date
Spectrum Analyzer	R&S	FSP40	100219	2011/11/24	2012/11/23

9.5 Test Result and Data

Test Date: Mar. 12, 2012

Temperature: 24°C



Atmospheric pressure: 1020 hPa

Humidity: 65%

Modulation Standard	Channel	Frequency (MHz)	maximum value in frequency (MHz)	maximum value (dBm)
802.11b (11Mbps)	01	2412	2399.60	-44.44
	11	2462	2515.70	-44.94
802.11g (54Mbps)	01	2412	2400.00	-42.88
	11	2462	2510.10	-46.15
802.11n HT20 (130Mbps)	01	2412	2400.00	-42.66
	11	2462	2525.30	-45.29
802.11n HT40 (270Mbps)	03	2422	2400.00	-42.55
	09	2452	2487.50	-45.66





Modulation Standard: 802.11b (11Mbps)
Channel: 01







Modulation Standard: 802.11b (11Mbps)
Channel: 11







Modulation Standard: 802.11g (54Mbps)
Channel: 01







Modulation Standard: 802.11g (54Mbps)
Channel: 11







Modulation Standard: 802.11n HT20 (130Mbps)
Channel: 01







Modulation Standard: 802.11n HT20 (130Mbps)
Channel: 11







Modulation Standard: 802.11n HT40 (270Mbps)
Channel: 03





Modulation Standard: 802.11n HT40 (270Mbps)
Channel: 09





9.6 Restrict Band Emission Measurement Data

Test Date: Mar. 05, 2012

Temperature: 24°C

Atmospheric pressure: 1020 hPa

Humidity: 65%

Modulation Standard: IEEE 802.11b (11Mbps)

Channel 1						Fundamental Frequency: 2412 MHz				
Frequency (MHz)	Ant-Pol H/V	Meter Reading (dBuV)	Corrected Factor (dB)	Result (dBuV/m)	Remark	Limit (dBuV/m)		Margin (dB)	Table Deg.	Ant High (m)
						Peak	Ave			
2331.93	H	49.83	1.69	51.52	Peak	74	54	-22.48	237	100
-----	H	-----	-----	-----	Ave	74	54	-----	-----	-----
2338.05	V	51.97	2.95	54.92	Peak	74	54	-19.08	226	100
2338.05	V	39.06	2.95	42.01	Ave	74	54	-11.99	138	100

Channel 11						Fundamental Frequency: 2462 MHz				
Frequency (MHz)	Ant-Pol H/V	Meter Reading (dBuV)	Corrected Factor (dB)	Result (dBuV/m)	Remark	Limit (dBuV/m)		Margin (dB)	Table Deg.	Ant High (m)
						Peak	Ave			
2496.50	H	49.64	-0.09	49.55	Peak	74	54	-24.45	56	100
-----	H	-----	-----	-----	Ave	74	54	-----	-----	-----
2484.04	V	53.21	-2.57	50.64	Peak	74	54	-23.36	137	100
-----	V	-----	-----	-----	Ave	74	54	-----	-----	-----

Modulation Standard: IEEE 802.11g (54Mbps)

Channel 1						Fundamental Frequency: 2412 MHz				
Frequency (MHz)	Ant-Pol H/V	Meter Reading (dBuV)	Corrected Factor (dB)	Result (dBuV/m)	Remark	Limit (dBuV/m)		Margin (dB)	Table Deg.	Ant High (m)
						Peak	Ave			
2336.52	H	50.25	1.66	51.91	Peak	74	54	-22.09	248	100
-----	H	-----	-----	-----	Ave	74	54	-----	-----	-----
2359.78	V	53.34	2.57	55.91	Peak	74	54	-18.09	249	100
2359.68	V	42.26	2.58	44.84	Ave	74	54	-9.16	114	100

Channel 11						Fundamental Frequency: 2462 MHz				
Frequency (MHz)	Ant-Pol H/V	Meter Reading (dBuV)	Corrected Factor (dB)	Result (dBuV/m)	Remark	Limit (dBuV/m)		Margin (dB)	Table Deg.	Ant High (m)
						Peak	Ave			
2483.74	H	49.17	0.10	49.27	Peak	74	54	-24.73	233	100
-----	H	-----	-----	-----	Ave	74	54	-----	-----	-----
2484.04	V	54.12	-2.57	51.55	Peak	74	54	-22.45	103	100
-----	V	-----	-----	-----	Ave	74	54	-----	-----	-----



Modulation Standard: IEEE 802.11n HT20 (130Mbps)

Channel 1						Fundamental Frequency: 2412 MHz				
Frequency (MHz)	Ant-Pol H/V	Meter Reading (dBuV)	Corrected Factor (dB)	Result (dBuV/m)	Remark	Limit (dBuV/m)		Margin (dB)	Table Deg.	Ant High (m)
						Peak	Ave			
2339.38	H	49.32	1.66	50.98	Peak	74	54	-23.02	71	100
-----	H	-----	-----	-----	Ave	74	54	-----	-----	-----
2359.98	V	53.29	2.57	55.86	Peak	74	54	-18.14	108	100
2360.18	V	42.38	2.57	44.95	Ave	74	54	-9.05	236	100
Channel 11						Fundamental Frequency: 2462 MHz				
Frequency (MHz)	Ant-Pol H/V	Meter Reading (dBuV)	Corrected Factor (dB)	Result (dBuV/m)	Remark	Limit (dBuV/m)		Margin (dB)	Table Deg.	Ant High (m)
						Peak	Ave			
2487.27	H	49.33	0.04	49.37	Peak	74	54	-24.63	257	100
-----	H	-----	-----	-----	Ave	74	54	-----	-----	-----
2484.12	V	57.01	-2.57	54.44	Peak	74	54	-19.56	110	100
2484.12	V	41.00	-2.57	38.43	Ave	74	54	-15.57	268	100

Modulation Standard: IEEE 802.11n HT40 (270Mbps)

Channel 3						Fundamental Frequency: 2422 MHz				
Frequency (MHz)	Ant-Pol H/V	Meter Reading (dBuV)	Corrected Factor (dB)	Result (dBuV/m)	Remark	Limit (dBuV/m)		Margin (dB)	Table Deg.	Ant High (m)
						Peak	Ave			
2337.03	H	49.56	1.66	51.22	Peak	74	54	-22.78	92	100
-----	H	-----	-----	-----	Ave	74	54	-----	-----	-----
2389.36	V	54.07	2.08	56.15	Peak	74	54	-17.85	69	100
2389.36	V	41.70	2.08	43.78	Ave	74	54	-10.22	228	100
Channel 9						Fundamental Frequency: 2452 MHz				
Frequency (MHz)	Ant-Pol H/V	Meter Reading (dBuV)	Corrected Factor (dB)	Result (dBuV/m)	Remark	Limit (dBuV/m)		Margin (dB)	Table Deg.	Ant High (m)
						Peak	Ave			
2486.40	H	49.06	0.05	49.11	Peak	74	54	-24.89	274	100
-----	H	-----	-----	-----	Ave	74	54	-----	-----	-----
2483.74	V	58.65	-2.55	56.10	Peak	74	54	-17.90	251	100
2483.74	V	45.48	-2.55	42.93	Ave	74	54	-11.07	96	100

Notes:

1. Result = Meter Reading + Factor
2. Factor = Antenna Factor + Cable Loss – Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3 MHz (detector peak mode) for Peak detection at frequency above 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3 MHz (detector sample mode) for Average detection at frequency above 1GHz.



10. Restricted Bands of Operation

Only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.09000 – 0.11000	16.42000 – 16.42300	399.9 – 410.0	4.500 – 5.250
0.49500 – 0.505**	16.69475 – 16.69525	608.0 – 614.0	5.350 – 5.460
2.17350 – 2.19050	16.80425 – 16.80475	960.0 – 1240.0	7.250 – 7.750
4.12500 – 4.12800	25.50000 – 25.67000	1300.0 – 1427.0	8.025 – 8.500
4.17725 – 4.17775	37.50000 – 38.25000	1435.0 – 1626.5	9.000 – 9.200
4.20725 – 4.20775	73.00000 – 74.60000	1645.5 – 1646.5	9.300 – 9.500
6.21500 – 6.21800	74.80000 – 75.20000	1660.0 – 1710.0	10.600 – 12.700
6.26775 – 6.26825	108.00000 – 121.94000	1718.8 – 1722.2	13.250 – 13.400
6.31175 – 6.31225	123.00000 – 138.00000	2200.0 – 2300.0	14.470 – 14.500
8.29100 – 8.29400	149.90000 – 150.05000	2310.0 – 2390.0	15.350 – 16.200
8.36200 – 8.36600	156.52475 – 156.52525	2483.5 – 2500.0	17.700 – 21.400
8.37625 – 8.38675	156.70000 – 156.90000	2655.0 – 2900.0	22.010 – 23.120
8.41425 – 8.41475	162.01250 – 167.17000	3260.0 – 3267.0	23.600 – 24.000
12.29000 – 12.29300	167.72000 – 173.20000	3332.0 – 3339.0	31.200 – 31.800
12.51975 – 12.52025	240.00000 – 285.00000	3345.8 – 3358.0	36.430 – 36.500
12.57675 – 12.57725	322.00000 – 335.40000	3600.0 – 4400.0	Above 38.6
13.36000 – 13.41000			

** : Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz

10.1 Labeling Requirement

The device shall bear the following statement in a conspicuous location on the device:

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.