

FCC RF Exposure Report

FCC ID : SWX-AFT

Equipment : AMPLIFI Teleport

Model No. : AFi-T

Brand Name : ULABS

Applicant : Ubiquiti Networks, Inc.

Address : 685 Third Avenue, 27th Floor New York, New

York 10017 USA

Standard : 47 CFR FCC Part 2.1091

Received Date : Jun. 19, 2017

Tested Date : Jul. 11 ~ Aug. 15, 2017

We, International Certification Corp., would like to declare that the tested sample has been evaluated and in compliance with the requirement of the above standards. The test results contained in this report refer exclusively to the product. It may be duplicated completely for legal use with the approval of the applicant. It shall not be reproduced except in full without the written approval of our laboratory.

Reviewed by: Approved by:

Along Chen / Assistant Manager Gary Chang / Manager

Testing Laboratory 2732

Report No.: FA761901 Page: 1 of 5



Table of Contents

1	MPE EVALUATION OF MOBILE DEVICES	4
1.1	LIMITS FOR GENERAL POPULATION/UNCONTROLLED EXPOSURE	4
1.2	MPE EVALUATION FORMULA	4
1.3	MPE EVALUATION RESULTS	4
2	TEST LABORATORY INFORMATION	_ 5

Report No.: FA761901

Page : 2 of 5



Release Record

Report No.	Version	Description	Issued Date	
FA761901	Rev. 01	Initial issue	Oct. 27, 2017	
FA761901	Rev. 02	Adding rated power	Dec 22, 2017	

Report No.: FA761901 Page: 3 of 5



1 MPE EVALUATION OF MOBILE DEVICES

Human exposure to RF emissions from mobile devices (47 CFR §2.1091) may be evaluated based on the MPE limits adopted by the FCC for electric and magnetic field strength and/or power density, as appropriate, since exposures are assumed to occur at distances of 20 cm or more from persons.

1.1 LIMITS FOR GENERAL POPULATION/UNCONTROLLED EXPOSURE

Frequency Range (MHz)	Power Density (mW /cm²)	Averaging Time (minutes)		
300~1500	F/1500	30		
1500~100000	1.0	30		

1.2 MPE EVALUATION FORMULA

$$Pd = \frac{Pt}{4*Pi*R^2}$$

Where

Pd= Power density in mW/cm²

Pt= EIRP in mW

Pi= 3.1416

R= Measurement distance

1.3 MPE EVALUATION RESULTS

Frequency Range (MHz)	Maximum Conducted Power (dBm)	Rated Power (dBm)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm²)	Limit (mW/cm²)
2412~2462	19.93	20	1	20	0.025	1
5180~5240	19.73	20	2	20	0.032	1
5745~5825	19.61	20	2	20	0.032	1

Report No.: FA761901 Page: 4 of 5



2 Test laboratory information

Established in 2012, ICC provides foremost EMC & RF Testing and advisory consultation services by our skilled engineers and technicians. Our services employ a wide variety of advanced edge test equipment and one of the widest certification extents in the business.

International Certification Corp (EMC and Wireless Communication Laboratory), it is our definitive objective is to institute long term, trust-based associations with our clients. The expectation we set up with our clients is based on outstanding service, practical expertise and devotion to a certified value structure. Our passion is to grant our clients with best EMC / RF services by oriented knowledgeable and accommodating staff.

Our Test sites are located at Linkou District and Kwei Shan District. Location map can be found on our website http://www.icertifi.com.tw.

Linkou

Tel: 886-2-2601-1640

No. 30-2, Ding Fwu Tsuen, Lin Kou District, New Taipei City,

Taiwan, R.O.C.

Kwei Shan

No. 3-1, Lane 6, Wen San 3rd St., Kwei Shan District, Tao Yuan City

333, Taiwan, R.O.C.

Tel: 886-3-271-8666

Kwei Shan Site II

Tel: 886-3-271-8640

No. 14-1, Lane 19, Wen San 3rd St., Kwei Shan District, Tao Yuan

City 333, Taiwan, R.O.C.

If you have any suggestion, please feel free to contact us as below information.

Tel: 886-3-271-8666 Fax: 886-3-318-0155

Email: ICC_Service@icertifi.com.tw

__END__

Report No.: FA761901 Page: 5 of 5